



# FCC MPE Exemption Evaluation Report

Report No. : W7L-230830W001SA02  
Applicant : Minda Corporation Ltd.  
Address : D 6-11 Sector 59 Noida Uttar Pradesh India  
Product : Immobilizer  
FCC ID : 2A29L-10237A  
Brand : SPARK  
Model No. : ML-10237A  
Standards : FCC 47 CFR Part 2 (2.1091) / Part 1 (1.1307)  
KDB 447498 D04 v01  
Sample Received Date : Oct. 19 ,2023  
Date of Testing : Aug. 30, 2023 ~ Oct. 19 ,2023

**CERTIFICATION:** The above equipment have been tested by **HUARUI 7LAYERS HIGH TECHNOLOGY (SUZHOU) CO., LTD.**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's SAR characteristics under the conditions specified in this report. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by A2LA or any government agencies.

Prepared By :

*chao wu*

Chao Wu/ Engineer

Approved By :

*Sun Peibo*

Peibo Sun/ Manager

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



## Table of Contents

RELEASE CONTROL RECORD.....	3
1. DESCRIPTION OF EQUIPMENT UNDER TEST .....	4
2. SAR EXEMPTION EVALUATION.....	5
2.1    MAXIMUM TUNE-UP POWER (DECLARED BY MANUFACTURER) .....	错误!未定义书签。
2.2    SAR TEST EXCLUSION THRESHOLDS.....	7
3. INFORMATION ON THE TESTING LABORATORIES.....	8



**BUREAU  
VERITAS** FCC RF Exposure Test Report



Certificate #6613.01

## **Release Control Record**



## 1. Description of Equipment Under Test

EUT Type*	Immobilizer
Brand Name*	SPARK
Model Name*	ML-10237A
Tx Frequency Bands (Unit: MHz)	125kHz
Uplink Modulations	ASK
Maximum measured power (Unit: mW)	125kHz: 0.0000007585mW
Antenna Type*	Loop coil Antenna
EUT Stage*	Production Unit

**NOTE:**

1. \*Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, Test Lab is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.
2. The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.



## 2. SAR Exemption Evaluation

### Following FCC KDB 447498 D04 "Interim General RF Exposure Guidance" v01

#### SAR-based Exemption:

The corresponding SAR Exclusion Threshold condition, listed below:

- 1) SAR-based thresholds are derived based on frequency, power, and separation distance of the RF source. The formula defines the thresholds in general for either available maximum time averaged power or maximum time-averaged ERP, whichever is greater.
- 2) Per § 1.1307(b)(3)(i)(B), for single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2) of this section): A single RF source is exempt if:
- 3) The available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold  $P_{th}$  (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive).  $P_{th}$  is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

$d$  = the separation distance (cm);



### Blanket 1 mW Blanket Exemption:

The 1 mW Blanket Exemption of § 1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

The 1 mW blanket exemption applies at separation distances less than 0.5 cm, including where there is no separation. This exemption shall not be used in conjunction with other exemption criteria other than those for multiple RF sources in paragraph § 1.1307(b)(3)(ii)(A).

The 1 mW exemption is independent of service type and covers the full range of 100 kHz to 100 GHz, but it shall not be used in conjunction with other exemption criteria or in devices with higher-power transmitters operating in the same time-averaging period. Exposure from such higher-power transmitters would invalidate the underlying assumption that exposure from the lower-power transmitter is the only contributor to SAR in the relevant volume of tissue.

For multiple RF sources: Multiple RF sources are exempt if:

In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation:

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

### Smallest distance from the antenna and radiating structures or outer surface of the device

The minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander.



## 2.1 Maximum measured power

Mode	Maximum measured power (mW)
125kHz	0.0000007585

## 2.2 SAR Test Exclusion Thresholds

Mode	Frequency (MHz)	E-field strength (dBuV/m)	E-field strength (V/m)	Maximum measured power (mW)	Minimum separation distance (mm)	Exception Limit (mW)	Verdict
RFID	125kHz	57.55	0.000754	0.0000007585	5	1	Exempt from SAR

## Conclusion

According to the table above, the device can meet the MPE test exclusion thresholds requirement of FCC KDB 447498 D04 v01 and MPE evaluation is not required.

Therefore this device complies with FCC's RF radiation exposure limits for general population without SAR evaluation.



### **3. Information on the Testing Laboratories**

We, Huarui 7layers High Technology (Suzhou) Co., Ltd. ,were founded in 2020 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Suzhou EMC/RF Lab:**

Tel: +86 (0557) 368 1008

---END---