



Test Mode: Traffic mode


PCS1900 (GPRS 1 link)



Lowest channel





Middle channel




Highest channel

Test Mode: Traffic mode


PCS1900 (EGPRS 1 link)



Lowest channel




Middle channel




Highest channel

Test Mode: Traffic mode


WCDMA Band V (RMC 12.2Kbps link)



Lowest channel




Middle channel




Highest channel

Test Mode: Traffic mode


WCDMA Band II (RMC 12.2Kbps link)



Lowest channel




Middle channel




Highest channel

Test Mode: Traffic mode


WCDMA Band IV (RMC 12.2Kbps link)



Lowest channel



Middle channel




Highest channel


Band Edge:

Test Mode: Traffic mode

GSM850 (GPRS 1 link)




Lowest channel




Highest channel

Test Mode: Traffic mode

GSM850 (EGPRS 1 link)




Lowest channel




Highest channel

Test Mode: Traffic mode

PCS1900 (GPRS 1 link)




Lowest channel




Highest channel

Test Mode: Traffic mode

PCS1900 (EGPRS 1 link)




Lowest channel



Highest channel

Test Mode: Traffic mode

WCDMA Band V (RMC 12.2Kbps link)



Lowest channel



Highest channel

Test Mode: Traffic mode

WCDMA Band II (RMC 12.2Kbps link)



Lowest channel



Highest channel

Test Mode: Traffic mode

WCDMA Band IV (RMC 12.2Kbps link)






Lowest channel



Highest channel

4.8 ERP, EIRP Measurement

Test Requirement:	FCC part22.913(a) and FCC part24.232(b) , Part 27.54(h)
Test Method:	FCC part2.1046
Limit:	GSM850, WCDMA Band V: 7W PCS1900, WCDMA Band II: 2W WCDMA Band IV: 1W
Test setup:	Below 1GHz  Above 1GHz  Substituted method: 

Test Procedure:	1. The EUT was placed on an non-conductive turntable using a non-conductive support. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and EMI spectrum analyzer. 2. During the measurement, the EUT was communication with the station. The highest emission was recorded with the rotation of the turntable and the lowering of the test antenna from 4m to 1m. The reading was recorded and the field strength (E in dBuV/m) was calculated. 3. ERP in frequency band 824.2 –848.80.8MHz were measured using a substitution method. The EUT was replaced by dipole antenna connected, the S.G. output was recorded and ERP was calculated asfollows: $\text{ERP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBd)} - \text{Cable Loss (dB)}$ 4. EIRP in frequency band 1850.2 –1909.8MHz were measured using a substitution method. The EUT was replaced by or horn antenna connected, the S.G. output was recorded and EIRP was calculated as follows: $\text{EIRP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBi)} - \text{Cable Loss (dB)}$
Test Instruments:	Refer to section 3 for details
Test mode:	Refer to section 4.1 for details
Test results:	Pass

Measurement Data

EUT mode	Channel	EUT Pol.	Antenna Pol.	ERP(dBm)	Limit (dBm)	Result
GSM850 (GPRS 1 link)	Lowest	H	V	29.48	38.45	Pass
			H	28.93		
		E1	V	29.89		
			H	29.84		
		E2	V	29.67		
			H	30.62		
	Middle	H	V	29.13	38.45	Pass
			H	30.04		
		E1	V	30.84		
			H	29.36		
		E2	V	28.89		
			H	31.01		
	Highest	H	V	31.09	38.45	Pass
			H	29.91		
		E1	V	30.19		
			H	31.51		
		E2	V	30.40		
			H	29.61		

EUT mode	Channel	EUT Pol.	Antenna Pol.	ERP(dBm)	Limit (dBm)	Result
GSM850 (EGPRS 1 link)	Lowest	H	V	27.02	38.45	Pass
			H	27.51		
		E1	V	27.97		
			H	27.88		
		E2	V	27.07		
			H	28.06		
	Middle	H	V	26.65	38.45	Pass
			H	27.42		
		E1	V	28.17		
			H	29.40		
		E2	V	28.04		
			H	27.63		
	Highest	H	V	29.61	38.45	Pass
			H	28.75		
		E1	V	26.91		
			H	27.74		
		E2	V	27.71		
			H	28.79		

EUT mode	Channel	EUT Pol.	Antenna Pol.	EIRP (dBm)	Limit (dBm)	Result
PCS1900 (GPRS 1 link)	Lowest	H	V	30.88	33.01	Pass
			H	30.87		
		E1	V	30.22		
			H	30.33		
		E2	V	31.45		
			H	30.27		
	Middle	H	V	31.28	33.01	Pass
			H	29.03		
		E1	V	28.92		
			H	29.29		
		E2	V	29.32		
			H	30.13		
	Highest	H	V	30.93	33.01	Pass
			H	30.84		
		E1	V	30.67		
			H	29.47		
		E2	V	31.25		
			H	30.13		




EUT mode	Channel	EUT Pol.	Antenna Pol.	EIRP (dBm)	Limit (dBm)	Result
PCS1900 (EGPRS 1 link)	Lowest	H	V	27.94	33.01	Pass
			H	28.28		
		E1	V	27.39		
			H	26.98		
		E2	V	27.73		
			H	27.43		
	Middle	H	V	28.80	33.01	Pass
			H	27.19		
		E1	V	27.72		
			H	27.54		
		E2	V	29.20		
			H	28.27		
	Highest	H	V	27.09	33.01	Pass
			H	29.33		
		E1	V	27.20		
			H	28.93		
		E2	V	29.32		
			H	27.75		

EUT mode	Channel	EUT Pol.	Antenna Pol.	ERP(dBm)	Limit (dBm)	Result
WCDMA Band V	Lowest	H	V	21.62	38.45	Pass
			H	22.69		
		E1	V	22.68		
			H	22.25		
		E2	V	22.72		
			H	23.52		
	Middle	H	V	21.99	38.45	Pass
			H	23.55		
		E1	V	22.12		
			H	21.94		
		E2	V	23.60		
			H	21.32		
	Highest	H	V	21.17	38.45	Pass
			H	21.80		
		E1	V	22.25		
			H	22.71		
		E2	V	23.18		
			H	21.97		

EUT mode	Channel	EUT Pol.	Antenna Pol.	EIRP(dBm)	Limit (dBm)	Result
WCDMA Band II	Lowest	H	V	23.27	33.01	Pass
			H	23.27		
		E1	V	22.67		
			H	22.59		
		E2	V	22.40		
			H	22.94		
	Middle	H	V	22.27	33.01	Pass
			H	22.59		
		E1	V	23.54		
			H	22.72		
		E2	V	21.96		
			H	23.22		
	Highest	H	V	23.70	33.01	Pass
			H	22.59		
		E1	V	23.19		
			H	21.90		
		E2	V	22.85		
			H	23.19		

EUT mode	Channel	EUT Pol.	Antenna Pol.	EIRP(dBm)	Limit (dBm)	Result
WCDMA Band IV	Lowest	H	V	21.53	33.01	Pass
			H	21.84		
		E1	V	23.26		
			H	23.29		
		E2	V	23.38		
			H	23.46		
	Middle	H	V	23.44	33.01	Pass
			H	22.54		
		E1	V	21.86		
			H	23.36		
		E2	V	23.17		
			H	22.01		
	Highest	H	V	22.19	33.01	Pass
			H	22.70		
		E1	V	22.95		
			H	21.72		
		E2	V	22.29		
			H	23.91		

4.9 Field strength of spurious radiation measurement

Test Requirement:	FCC part22.917(a) and FCC part24.238(a), Part 27.54(h)
Test Method:	FCC part2.1053
Limit:	-13dBm
Test setup:	Below 1GHz  Above 1GHz  Substituted method: 

Test Procedure:	1. The EUT was placed on an non-conductive turntable using a non-conductive support. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and EMI spectrum analyzer. 2. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations. 3. The frequency range up to tenth harmonic was investigated for each of three fundamental frequency (low, middle and high channels). Once spurious emission was identified, the power of the emission was determined using the substitution method. 4. The spurious emissions attenuation was calculated as the difference between radiated power at the fundamental frequency and the spurious emissions frequency. $\text{ERP / EIRP} = \text{S.G. output (dBm)} + \text{Antenna Gain(dB/dBi)} - \text{Cable Loss (dB)}$
Test Instruments:	Refer to section 3 for details
Test mode:	Refer to section 4.1 for details
Test results:	Pass

Measurement Data

Test mode:	GPRS850		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1697.82	V	-37.54	-13.00	Pass
2546.75	V	-39.66		
3395.40	V	-36.22		
4242.30	V	-34.95		
5092.26	V	-31.49		
1696.19	H	-41.14	-13.00	Pass
2545.41	H	-35.89		
3393.97	H	-35.83		
4243.34	H	-31.44		
5092.72	H	-30.87		
Test mode:	EGPRS850		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1697.43	V	-39.24	-13.00	Pass
2545.43	V	-37.56		
3394.58	V	-33.50		
4243.72	V	-33.01		
5093.71	V	-31.29		
1697.24	H	-39.18	-13.00	Pass
2545.91	H	-37.48		
3394.80	H	-35.45		
4242.74	H	-32.53		
5093.72	H	-29.94		

Remark :

1. The emission behaviour belongs to narrowband spurious emission.
2. The above table only shows the worst case channel of each mode.
3. The emission levels of below 1 GHz are very lower than the limit and not show in test report.

Test mode:	GPRS1900		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3818.92	V	-38.50	-13.00	Pass
5728.17	V	-38.29		
7639.51	V	-35.79		
9547.69	V	-33.85		
11460.58	V	-28.94		
3818.73	H	-39.34	-13.00	Pass
5729.21	H	-36.43		
7641.57	H	-33.74		
9547.98	H	-33.54		
11458.85	H	-29.37		
Test mode:	EGPRS1900		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3819.66	V	-37.39	-13.00	Pass
5729.90	V	-38.19		
7639.11	V	-35.87		
9548.27	V	-33.82		
11459.05	V	-33.01		
3819.89	H	-38.20	-13.00	Pass
5729.10	H	-37.49		
7638.77	H	-38.07		
9549.04	H	-33.12		
11458.08	H	-27.76		

Remark:

1. The emission behaviour belongs to narrowband spurious emission.
2. The above table only shows the worst case channel of each mode.
3. The emission levels of below 1 GHz are very lower than the limit and not show in test report.

Test mode:	WCDMA Band V		Test channel:	Lowest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1652.70	V	-38.89	-13.00	Pass
2479.54	V	-37.08		
3304.72	V	-33.37		
4132.85	V	-32.70		
4957.86	V	-30.44		
1653.10	H	-38.68	-13.00	Pass
2478.09	H	-39.44		
3305.43	H	-34.80		
4129.84	H	-34.63		
4959.27	H	-29.88		
Test mode:	WCDMA Band V		Test channel:	Middle
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1672.73	V	-37.07	-13.00	Pass
2509.14	V	-36.42		
3345.68	V	-35.86		
4183.04	V	-35.13		
5016.94	V	-31.42		
1672.58	H	-37.82	-13.00	Pass
2508.05	H	-36.52		
3345.88	H	-34.54		
4182.18	H	-33.34		
5018.31	H	-28.69		
Test mode:	WCDMA Band V		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1692.84	V	-39.06	-13.00	Pass
2538.94	V	-37.95		
3385.92	V	-36.06		
4231.56	V	-32.89		
5078.46	V	-31.54		
1695.12	H	-38.36	-13.00	Pass
2539.08	H	-35.83		
3386.41	H	-36.17		
4234.25	H	-33.93		
5079.66	H	-30.03		

Remark :

1. The emission behaviour belongs to narrowband spurious emission.
2. Remark"---" means that the emission level is too low to be measured
3. The emission levels of below 1 GHz are very lower than the limit and not show in test report.

Test mode:	WCDMA Band II		Test channel:	Lowest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3704.92	V	-39.12	-13.00	Pass
5557.30	V	-36.07		
7409.39	V	-35.71		
9260.31	V	-32.93		
11113.65	V	-31.51		
3703.24	H	-37.79	-13.00	Pass
5558.07	H	-37.57		
7410.03	H	-35.15		
9261.80	H	-32.24		
11114.96	H	-30.41		
Test mode:	WCDMA Band II		Test channel:	Middle
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3760.13	V	-40.79	-13.00	Pass
5640.43	V	-36.96		
7519.82	V	-33.96		
9400.19	V	-31.97		
11281.97	V	-29.67		
3760.58	H	-39.06	-13.00	Pass
5640.59	H	-37.44		
7520.93	H	-36.15		
9399.49	H	-31.19		
11277.94	H	-29.94		
Test mode:	WCDMA Band II		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3814.74	V	-39.13	-13.00	Pass
5722.24	V	-36.40		
7629.28	V	-36.63		
9536.57	V	-32.60		
11445.11	V	-31.33		
3813.77	H	-37.69	-13.00	Pass
5723.84	H	-36.92		
7631.52	H	-35.55		
9536.89	H	-34.32		
11446.94	H	-31.55		

Remark:

1. The emission behaviour belongs to narrowband spurious emission.
2. Remark"---" means that the emission level is too low to be measured
3. The emission levels of below 1 GHz are very lower than the limit and not show in test report.

Test mode:	WCDMA Band IV		Test channel:	Lowest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3423.64	V	-39.31	-13.00	Pass
5136.76	V	-37.74		
6847.69	V	-36.78		
8560.94	V	-34.35		
10276.05	V	-32.51		
3424.35	H	-38.90	-13.00	Pass
5137.56	H	-36.11		
6848.89	H	-35.32		
8562.29	H	-34.14		
10273.06	H	-30.58		
Test mode:	WCDMA Band IV		Test channel:	Middle
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3480.07	V	-38.17	-13.00	Pass
5219.78	V	-38.48		
6960.32	V	-34.33		
8700.12	V	-33.84		
10440.96	V	-31.46		
3481.46	H	-39.46	-13.00	Pass
5221.73	H	-38.43		
6961.36	H	-36.10		
8699.70	H	-32.29		
10440.03	H	-30.56		
Test mode:	WCDMA Band IV		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3503.72	V	-39.54	-13.00	Pass
5258.46	V	-38.51		
7009.34	V	-36.14		
8761.80	V	-34.71		
10514.15	V	-29.70		
3505.71	H	-40.33	-13.00	Pass
5258.46	H	-36.70		
7010.06	H	-34.71		
8763.94	H	-32.88		
10515.20	H	-31.02		

Remark:

1. The emission behaviour belongs to narrowband spurious emission.
2. Remark"---" means that the emission level is too low to be measured
3. The emission levels of below 1 GHz are very lower than the limit and not show in test report.

4.10 Frequency stability V.S. Temperature measurement

Test Requirement:	FCC Part2.1055(a)(1)(b)
Test Method:	FCC Part2.1055(a)(1)(b)
Limit:	2.5ppm
Test setup:	Note : Measurement setup for testing on Antenna connector
Test procedure:	1. The equipment under test was connected to an external DC power supply and input rated voltage. 2. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. 3. The EUT was placed inside the temperature chamber. 4. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 25°C operating frequency as reference frequency. 5. Turn EUT off and set the chamber temperature to –20°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. 6. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached.
Test Instruments:	Refer to section 3 for details
Test mode:	Refer to section 4.1 for details
Test results:	Pass

Measurement Data

Reference Frequency: GSM850 (GPRS 1 link) Middle channel=190 channel=836.6MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
12	-20	28	0.0337	2.5	Pass
	-10	-7	-0.0085		
	0	20	0.0242		
	10	-8	-0.0092		
	20	20	0.0241		
	30	17	0.0209		
	40	17	0.0208		
	50	6	0.0070		
	60	19	0.0222		
Reference Frequency: GSM850 (EGPRS 1 link) Middle channel=190 channel=836.6MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
12	-20	19	0.0233	2.5	Pass
	-10	-19	-0.0222		
	0	16	0.0191		
	10	-4	-0.0051		
	20	16	0.0188		
	30	8	0.0098		
	40	8	0.0094		
	50	10	0.0122		
	60	16	0.0188		

Reference Frequency: PCS1900 (GPRS 1 link) Middle channel=661 channel=1880MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error			Result
		Hz	ppm		
12	-20	30	0.0161	2.5	Pass
	-10	-5	-0.0026		
	0	26	0.0140		
	10	-4	-0.0024		
	20	28	0.0149		
	30	9	0.0047		
	40	14	0.0074		
	50	7	0.0037		
	60	18	0.0096		
Reference Frequency: PCS1900 (EGPRS 1 link) Middle channel=661 channel=1880MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error			Result
		Hz	ppm		
12	-20	19	0.0100	2.5	Pass
	-10	-13	-0.0067		
	0	19	0.0099		
	10	-10	-0.0054		
	20	19	0.0099		
	30	19	0.0101		
	40	8	0.0045		
	50	13	0.0072		
	60	12	0.0063		

Reference Frequency: WCDMA Band V Middle channel=4183 channel=836.6MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
12	-20	17	0.0198	2.5	Pass
	-10	-9	-0.0113		
	0	22	0.0269		
	10	-7	-0.0082		
	20	14	0.0169		
	30	18	0.0212		
	40	8	0.0097		
	50	15	0.0176		
	60	20	0.0237		
Reference Frequency: WCDMA Band II Middle channel=9400 channel=1880.0MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
12	-20	18	0.0095	2.5	Pass
	-10	-11	-0.0058		
	0	27	0.0146		
	10	-11	-0.0059		
	20	18	0.0097		
	30	10	0.0052		
	40	10	0.0055		
	50	11	0.0058		
	60	13	0.0071		
Reference Frequency: WCDMA Band IV Middle channel=1450 channel=1732.5MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.8	-20	30	0.0175	2.5	Pass
	-10	-4	-0.0025		
	0	28	0.0160		
	10	-2	-0.0013		
	20	18	0.0102		
	30	17	0.0099		
	40	9	0.0053		
	50	6	0.0034		
	60	12	0.0071		

4.11 Frequency stability V.S. Voltage measurement

Test Requirement:	FCC Part2.1055(d)(1)(2)
Test Method:	FCC Part2.1055(d)(1)(2)
Limit:	2.5ppm
Test setup:	Note : Measurement setup for testing on Antenna connector
Test procedure:	1. Set chamber temperature to 25°C. Use a variable DC power source to power the EUT and set the voltage to rated voltage. 2. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency. 3. Reduce the input voltage to specified extreme voltage variation (+/- 15%) and endpoint, record the maximum frequency change.
Test Instruments:	Refer to section 3 for details
Test mode:	Refer to section 4.1 for details
Test results:	Pass



Measurement Data

Reference Frequency: GSM850 (GPRS 1 link) Middle channel=190 channel=836.6MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	36	24	0.0289	2.5	Pass
	24	-16	-0.0192		
	9	15	0.0182		
Reference Frequency: GSM850 (EGPRS 1 link) Middle channel=190 channel=836.6MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	36	12	0.0146	2.5	Pass
	24	-10	-0.0123		
	9	26	0.0311		
Reference Frequency: PCS1900 (GPRS 1 link) Middle channel=661 channel=1880MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	36	10	0.0052	2.5	Pass
	24	-17	-0.0088		
	9	30	0.0160		
Reference Frequency: PCS1900 (EGPRS 1 link) Middle channel=661 channel=1880MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	36	25	0.0131	2.5	Pass
	24	-19	-0.0101		
	9	26	0.0140		

Reference Frequency: WCDMA Band V Middle channel=4183 channel=836.6MHz					
Temperature (℃)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	36	20	0.0243	2.5	Pass
	24	-3	-0.0030		
	9	28	0.0331		
Reference Frequency: WCDMA Band II Middle channel=940 channel=1880.0MHz					
Temperature (℃)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	36	20	0.0107	2.5	Pass
	24	-15	-0.0080		
	9	27	0.0143		
Reference Frequency: WCDMA Band IV Middle channel=1450 channel=1732.5MHz					
Temperature (℃)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	36	9	0.0054	2.5	Pass
	24	-6	-0.0033		
	9	22	0.0125		

5 Test Setup Photo

Radiated Emission



-----END OF REPORT-----