



RF Exposure Evaluation

For

Shen Zhen Lian Zhong Xin Electronic Co., Ltd.

optical zoom camera

Test Model: DC125

Prepared for : Shen Zhen Lian Zhong Xin Electronic Co., Ltd.
Address : Room 615, Block A, Zhihui Innovation Center, Taoyuanju South, NO.2
Qianjin Road, BaoAn District, Shenzhen, China

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei,
Shajing Street, Baoan District, Shenzhen, 518000, China

Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : February 28, 2025
Number of tested samples : 2
Sample number : A250115065-1, A250115065-2
Serial number : Prototype
Date of Test : February 28, 2025 ~ March 05, 2025
Date of Report : March 06, 2025





RF Exposure Evaluation	
Report Reference No.	LCSA02275001EB
Date of Issue	March 06, 2025
Testing Laboratory Name	Shenzhen LCS Compliance Testing Laboratory Ltd.
Address	101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Testing Location/ Procedure	Full application of Harmonised standards <input checked="" type="checkbox"/> Partial application of Harmonised standards <input type="checkbox"/> Other standard testing method <input type="checkbox"/>
Applicant's Name	Shen Zhen Lian Zhong Xin Electronic Co., Ltd.
Address	Room 615, Block A, Zhihui Innovation Center, Taoyuanju South, NO.2 Qianjin Road, BaoAn District, Shenzhen, China
Test Specification	
Standard	CFR 47 § 1.1310 CFR 47 § 2.1093 KDB447498 D01 General RF Exposure Guidance v06
Test Report Form No.	TRF-4-E-147 A/0
TRF Originator	Shenzhen LCS Compliance Testing Laboratory Ltd.
Master TRF	Dated 2011-03
Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.	
This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.	
EUT Description	optical zoom camera
Trade Mark	N/A
Test Model	DC125
Ratings	Input: DC 5V DC 3.7V by Rechargeable Li-ion Battery, 1200mAh
Result	Positive

Compiled by:

Kevin Huang

Kevin Huang/ Administrator

Supervised by:

Jack Liu

Jack Liu/ Technique principal

Approved by:

Gavin Liang

Gavin Liang/ Manager





TEST REPORT

Test Report No. : LCSA02275001EB	March 06, 2025 Date of issue
---	---------------------------------

Test Model.....	: DC125
EUT.....	: optical zoom camera
Applicant.....	: Shen Zhen Lian Zhong Xin Electronic Co., Ltd.
Address.....	: Room 615, Block A, Zihui Innovation Center, Taoyuanju South, NO.2 Qianjin Road, BaoAn District, Shenzhen, China
Telephone.....	: /
Fax.....	: /
Manufacturer.....	: Shen Zhen Lian Zhong Xin Electronic Co., Ltd.
Address.....	: Room 615, Block A, Zihui Innovation Center, Taoyuanju South, NO.2 Qianjin Road, BaoAn District, Shenzhen, China
Telephone.....	: /
Fax.....	: /
Factory.....	: Shen Zhen Lian Zhong Xin Electronic Co., Ltd.
Address.....	: Room 615, Block A, Zihui Innovation Center, Taoyuanju South, NO.2 Qianjin Road, BaoAn District, Shenzhen, China
Telephone.....	: /
Fax.....	: /

Test Result	Positive
--------------------	-----------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.





Revision History

Report Version	Issue Date	Revision Content	Revised By
000	March 06, 2025	Initial Issue	--





TABLE OF CONTENTS

1. PRODUCT INFORMATION6

2. EVALUATION METHOD AND LIMIT7

3. REFER EVALUATION METHOD8

4. CONDUCTED POWER RESULTS8

5. MANUFACTURING TOLERANCE9

6. EVALUATION RESULTS10

7. CONCLUSION10

8. DESCRIPTION OF TEST FACILITY10

9. MEASUREMENT UNCERTAINTY10





1. Product Information

Applicant's Name	:	Shen Zhen Lian Zhong Xin Electronic Co., Ltd.
Address	:	Room 615, Block A, Zihui Innovation Center, Taoyuanju South, NO.2 Qianjin Road, BaoAn District, Shenzhen, China
Product name	:	optical zoom camera
Test Model	:	DC125
Ratings	:	Input: DC 5V DC 3.7V by Rechargeable Li-ion Battery, 1200mAh
Hardware Version	:	V1.0
Software Version	:	/
WIFI(2.4G Band)		
Frequency Range	:	2412MHz~2462MHz
Channel Spacing	:	5MHz
Channel Number	:	11 Channels for 20MHz bandwidth (2412~2462MHz) 7 Channels for 40MHz bandwidth (2422~2452MHz)
Modulation Type	:	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Description	:	Internal Antenna, 0.47dBi(Max.)
Exposure category	:	General population/uncontrolled environment
EUT Type	:	Production Unit
Device Type	:	Portable Device
Date of Test	:	February 28, 2025 ~ March 05, 2025
Date of Report	:	March 06, 2025





2. Evaluation method and Limit

According to KDB447498 D01 General RF Exposure Guidance v06 Section 4.3.1 Standalone SAR test exclusion considerations: "Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition, listed below, is satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.²² The minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander (see 5) of section 4.1). To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, typically in the SAR measurement or SAR analysis report, according to the required published RF exposure KDB procedures. When no other RF exposure testing or reporting is required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for the SAR test exclusion. When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions; for example, handheld PTT two-way radios, handsets, laptops & tablets etc."

$$\left[\frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \cdot [\sqrt{f \text{ (GHz)}}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$$

- f (GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to f) in section 4.1 is applied to determine SAR test exclusion.

When one of the following test exclusion conditions is satisfied for all combinations of simultaneous transmission configurations, further equipment approval is not required to incorporate transmitter modules in host devices that operate in the mixed mobile and portable host platform exposure conditions. The grantee is responsible for documenting this according to Class I permissive change requirements. Antennas that qualify for standalone SAR test exclusion must apply the estimated standalone SAR to determine simultaneous transmission test exclusion.

- a) The $[\sum \text{ of (the highest measured or estimated SAR for each standalone antenna configuration, adjusted for maximum tune-up tolerance) / 1.6 W/kg}] + [\sum \text{ of MPE ratios}] \leq 1.0$.
- b) The SAR to peak location separation ratios of all simultaneously transmitting antenna pairs operating in portable device exposure conditions are all ≤ 0.04 , and the $[\sum \text{ of MPE ratios}] \leq 1.0$.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



3. Refer Evaluation Method

[ANSI C95.1–1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 447498 D01 General RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1093](#): Radiofrequency radiation exposure evaluation: portable devices

4. Conducted Power Results

[2.4GWIFI]

Mode	Channel	Frequency(MHz)	Max Conducted Power (dBm)
11B	1	2412	8.99
	6	2437	8.88
	11	2462	8.48
11G	1	2412	8.63
	6	2437	8.51
	11	2462	8.22
11N20SISO	1	2412	7.80
	6	2437	8.26
	11	2462	8.66
11N40SISO	3	2422	8.52
	6	2437	7.77
	9	2452	8.38



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



5. Manufacturing Tolerance

[2.4GWIFI]

11B (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	8.0	8.0	8.0
Tolerance ±(dB)	1.0	1.0	1.0
11G (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	8.0	8.0	8.0
Tolerance ±(dB)	1.0	1.0	1.0
11N20SISO (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	7.0	8.0	8.0
Tolerance ±(dB)	1.0	1.0	1.0
11N40SISO (Peak)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	8.0	7.0	8.0
Tolerance ±(dB)	1.0	1.0	1.0



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



6. Evaluation Results

6.1 Standalone Evaluation

[2.4GWIFI]

Band/Mode	Frequency (GHz)	Antenna Distance (mm)	RF output power		SAR Test Exclusion Threshold	SAR Test Exclusion
			dBm	mW		
IEEE 802.11b	2.462	5	9.0	7.9433	2.4927<3.0	Yes
IEEE 802.11g	2.462	5	9.0	7.9433	2.4927<3.0	Yes
IEEE 802.11n HT20	2.462	5	9.0	7.9433	2.4927<3.0	Yes
IEEE 802.11n HT40	2.452	5	9.0	7.9433	2.4877<3.0	Yes

Remark:

1. Output power including tune up tolerance;
2. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to f) in section 4.1 is applied to determine SAR test exclusion.

6.2 Simultaneous Transmission for SAR Exclusion

The sample support one BT modular. No need consider simultaneous transmission.

7. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06.

8. Description of Test Facility

NVLAP Accreditation Code is 600167-0.
 FCC Designation Number is CN5024.
 CAB identifier is CN0071.
 CNAS Registration Number is L4595.
 Test Firm Registration Number: 254912.

9. Measurement Uncertainty

Test Item	Frequency Range	Uncertainty	Note
Output power	1GHz-40GHz	±0.57dB	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

.....THE END OF REPORT.....

