

47 CFR PART 15 SUBPART C TEST REPORT

for

3 OUTLET WALL MNT SMART POWER

Model No.: PR-W3PI

FCC ID: 2A47N-PRW3PI

of

Applicant: Ethereal Home Theater, LLC

Address: 460 Walker St. Holly Hill Florida 32117 United States

Tested and Prepared

by

Worldwide Testing Services (Taiwan) Co., Ltd.

FCC Registration No.: TW1477, TW1072

Industry Canada filed test laboratory Reg. No. 20037, 5107A



Report No.: W6M22201-21487-C-1

6F, NO. 58, LANE 188, RUEY-KUANG RD., NEIHU TAIPEI 114, TAIWAN, R.O.C.
TEL: 886-2-66068877 FAX: 886-2-66068879 E-mail: wts@wts-lab.com





TABLE OF CONTENTS

1	GENERAL INFORMATION	2
1.1	NOTES.....	2
1.2	TESTING LABORATORY	3
1.2.1	Location	3
1.2.2	Details of accreditation status	3
1.3	DETAILS OF APPROVAL HOLDER.....	3
1.4	APPLICATION DETAILS	3
1.5	GENERAL INFORMATION OF TEST ITEM.....	4
1.6	TEST STANDARDS	5
2	TECHNICAL TEST	6
2.1	SUMMARY OF TEST RESULTS	6
2.2	TEST ENVIRONMENT	6
2.3	TEST EQUIPMENT LIST	7
2.4	GENERAL TEST PROCEDURE	10
3	TEST RESULTS (ENCLOSURE)	12
3.1	DUTY CYCLE.....	13
3.2	PEAK OUTPUT POWER (TRANSMITTER).....	16
3.3	EQUIVALENT ISOTROPIC RADIATED POWER (EIRP)	23
3.4	EXEMPTION LIMITS FOR ROUTINE EVALUATION.....	23
3.5	TRANSMITTER EMISSIONS IN NON-RESTRICTED BANDS.....	25
3.6	TRANSMITTER RADIATED EMISSIONS IN RESTRICTED BANDS	30
3.7	BAND EDGE.....	31
3.8	MINIMUM 6 dB BANDWIDTH	47
3.9	PEAK POWER SPECTRAL DENSITY	54
3.10	RADIATED EMISSION FROM RECEIVER PART	61
3.11	POWER LINE CONDUCTED EMISSION	62
	APPENDIX	64



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22201-21487-C-1

FCC ID: 2A47N-PRW3PI

1 General Information

1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems.

The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that its performance generally conforms to representative cases of communications equipment.

The test results of this test report relate exclusively to the item tested as specified in 1.5.

The test report may only be reproduced or published in full.

Reproduction or publication of extracts from the report requires the prior written approval of the Worldwide Testing Services(Taiwan) Co., Ltd.

Specific Conditions:

Usage of the hereunder tested device in combination with other integrated or external antennas requires at least additional output power measurements, spurious emission measurements, conducted emission measurements (AC supply lines) and radio frequency exposure evaluations for each individual configuration performed, for certification by FCC.

The test sample is able to work according to IEEE 802.11 b/g/n.

This report is related to FCC Part 15 C (DSSS and OFDM device).

Tester:

April 11, 2022

Spencer Yang

Spencer

Date

WTS-Lab.

Name

Signature

Technical responsibility for area of testing:

April 11, 2022

Kevin Wang


Kevin Wang

Date

WTS

Name

Signature



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22201-21487-C-1

FCC ID: 2A47N-PRW3PI

1.2 Testing laboratory

1.2.1 Location

OATS

No.5-1, Lishui, Shuang Sing Village,
Wanli Dist., New Taipei City 207,
Taiwan (R.O.C.)

3 meter semi-anechoic chamber

No.35, Aly. 21, Ln. 228, Ankang Rd., Neihu Dist., Taipei City 114, Taiwan (R.O.C.)

TEL:886-2-6613-0228

FAX:886-2-2791-5046

Company

Worldwide Testing Services(Taiwan) Co., Ltd.

6F, NO. 58, LANE 188, RUEY-KUANG RD.

NEIHU, TAIPEI 114, TAIWAN R.O.C.

Tel : 886-2-66068877

Fax : 886-2-66068879

1.2.2 Details of accreditation status

Accredited testing laboratory

A2LA accredited number: 2732.01

FCC filed test laboratory Reg. No. TW1477, TW1072

Industry Canada filed test laboratory Reg. No. 20037, 5107A

Test location, where different from Worldwide Testing Services (Taiwan) Co., Ltd. :

Name: ./.

Accredited number: ./.

Street: ./.

Town: ./.

Country: ./.

Telephone: ./.

Fax: ./.

1.3 Details of approval holder

Name: Ethereal Home Theater, LLC

Street: 460 Walker St. Holly Hill


Town: Florida 32117

Country: United States

1.4 Application details

Date of receipt of test item: January 10, 2022

Date of test: from January 11, 2022 to March 31, 2022



Registration number: W6M22201-21487-C-1

FCC ID: 2A47N-PRW3PI

1.5 General information of Test item

Type of test item: 3 OUTLET WALL MNT SMART POWER
Model Number: PR-W3PI
Brand Name: BIG DOG POWER
Multi-listing model number: ./.
Photos: see Appendix
Sample No: #01

Technical data


Frequency band: 2.4 GHz – 2.4835 GHz
11b, 11g, 11n 20MHz
Frequency (ch 1 or A): 2.412 GHz
Frequency (ch 6 or B): 2.437 GHz
Frequency (ch 11 or C): 2.462 GHz
11n 40MHz
Frequency (ch 1 or A): 2.422 GHz
Frequency (ch 4 or B): 2.437 GHz
Frequency (ch 7 or C): 2.452 GHz

Number of Channels: 11b, 11g, 11n 20MHz: 11
11n 40MHz: 7

Operation modes: Duplex
Modulation Type: DSSS / OFDM
Fixed point-to-point operation: ☐ Yes / ☒ No
Type of Antenna: Dipole Aantenna
Antenna gain: 2 dBi
Power supply: AC 120V, 12A, 1440W, 60Hz
Emission designator: 802.11b: DSSS: 13M5G1D
802.11g: OFDM: 16M7D1D
802.11n 20MHz: 17M4D1D
802.11n 40MHz: OFDM: 34M5D1D

Host device: none
Classification :

Fixed Device	☒
Mobile Device (Human Body distance > 20cm)	☐
Portable Device (Human Body distance < 20cm)	☐
Modular Radio Device	☐



Registration number: W6M22201-21487-C-1

FCC ID: 2A47N-PRW3PI

Transmitter

Unom

Mode A (DSSS)

Power (ch 1):	Conducted: 16.20 dBm
Power (ch 6):	Conducted: 16.46 dBm
Power (ch 11):	Conducted: 16.47 dBm

Mode B (OFDM)

Power (ch 1):	Conducted: 13.70 dBm
Power (ch 6):	Conducted: 13.80 dBm
Power (ch 11):	Conducted: 13.67 dBm

Mode C (OFDM)

Power (ch 1):	Conducted: 13.40 dBm
Power (ch 6):	Conducted: 13.31 dBm
Power (ch 11):	Conducted: 13.09 dBm

Mode D (OFDM)

Power (ch 1):	Conducted: 12.90 dBm
Power (ch 4):	Conducted: 12.90 dBm
Power (ch 7):	Conducted: 12.00 dBm

Manufacturer: (if applicable)


Name:	./.
Street:	./.
Town:	./.
Country:	./.

1.6 Test standards

Technical standard : 47 CFR PART 15 SUBPART C § 15.247 (2020-10)

Setup Configuration

1. EUT connected to jig and computer.
2. Turn on the engineering software "EspRFTestTool_v2.8_Manual.exe" and choose the corresponding com port.
3. Enter the test interface and set up the related parameter.
After setting down, jig would be removed.
4. Adding test configuration for set up and following is the worst case.
Connected to far-end computer by internet cable when testing.
Use the directive of ping to continue the action.
Output port of AC connected to lamp as a load. (Output is 216W (120Va.c., 1.8A))
After estimation, set up is the worst case.



Registration number: W6M22201-21487-C-1

FCC ID: 2A47N-PRW3PI

2 Technical test

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed.



or

The deviations were ascertained in the course of the tests performed.




2.2 Test environment

Temperature: 23 °C
Relative humidity content: 20 ... 75 %
Air pressure: 86 ... 103 kPa
Power supply: AC 120V, 12A, 1440W, 60Hz
Extreme conditions parameters: ./.

Test item Name	Uncertainty
Estimation Result of Uncertainty of Conducted Emission (Power Line Conducted Emission)	Expanded Uncertainty : AMN : 1.03 dB Voltage probe : 1.05 dB
Estimation Result of Uncertainty of Radiated Emission(3M) (Transmitter Radiated Emissions in Restricted Bands, Spurious Emissions (tx), Radiated Emission from Receiver Part)	Expanded Uncertainty : 0.009-30 MHz : 3.48 dB 30-1000 MHz : 4.48 dB 1-18 GHz : 4.15 dB 18-40 GHz : 3.78 dB
Estimation Result of Uncertainty of Bandwidth Measurement (Minimum 6 dB Bandwidth)	Expanded Uncertainty : 0.45 kHz
Estimation Result of Uncertainty of Conducted Output Power Measurement (Peak Output Power (transmitter))	Expanded Uncertainty : 3.07 dB
Estimation Result of Uncertainty of Power Density Measurement (Peak Power Spectral Density)	Expanded Uncertainty : 3.63 dB
Estimation Result of Uncertainty of Band Edge Measurement (Radiated Emission on the band edge)	Expanded Uncertainty : 0.67 dBc

The decision rule is: Measurement uncertainty is not included in the calculation of test results.




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22201-21487-C-1

FCC ID: 2A47N-PRW3PI

2.3 Test Equipment List

No.	Test equipment	Type	Serial No.	Manufacturer	Cal. Date	Next Cal. Date
ETSTW-CE 001	EMI TEST RECEIVER	ESHS10	842121/013	R&S	2021/6/17	2022/6/16
ETSTW-CE 003	AC POWER SOURCE	APS-9102	D161137	GW	Function Test	
ETSTW-CE 004	ZWEILEITER-V- NETZNACHBILDUNG TWO-LINE V-NETWORK	ESH3-Z5	840731/011	R&S	2021/11/9	2022/11/8
ETSTW-CE 006	IMPULSBEGRENZER PULSE LIMITER	ESH3-Z2	100226	R&S	2021/9/22	2022/9/21
ETSTW-CE 008	HF-EICHELLEITUNG RF STEP ATTENUATOR 139dB DPSP	334.6010.02	844581/024	R&S	Function Test	
ETSTW-CE 009	TEMP.&HUMIDITY CHAMBER	GTH-225-40-1P-U	MAA0305-009	GIANT FORCE	2021/7/29	2022/7/28
ETSTW-CE 016	TWO-LINE V-NETWORK	ENV216	100050	R&S	2021/11/8	2022/11/7
ETSTW-CE 028	MXE EMI Receiver	N9038A	MY53220110	Agilent	2021/7/28	2022/7/27
ETSTW-RE 003	EMI TEST RECEIVER	ESI 26	831438/001	R&S	2021/6/17	2022/6/16
ETSTW-RE 004	EMI TEST RECEIVER	ESI 40	832427/004	R&S	2021/9/28	2022/9/27
ETSTW-RE 012	TUNABLE BANDREJECT FILTER	D.C 0309	146	K&L	Function Test	
ETSTW-RE 013	TUNABLE BANDREJECT FILTER	D.C 0336	397	K&L	Function Test	
ETSTW-RE 018	MICROWAVE HORN ANTENNA	AT4560	27212	AR	2021/8/4	2022/8/3
ETSTW-RE 019	MICROWAVE HORN ANTENNA	22240-25	121074	FM	2021/5/31	2022/5/30
ETSTW-RE 027	Passive Loop Antenna	6512	00034563	ETS-Lindgren	2021/6/16	2022/6/15
ETSTW-RE 030	Double-Ridged Guide Horn Antenna	3117	00035224	ETS-Lindgren	2021/5/5	2022/5/4
ETSTW-RE 042	Biconical Antenna	HK116	100172	R&S	2022/2/3	2023/2/2
ETSTW-RE 043	Log-Periodic Dipole Antenna	HL223	100166	R&S	2021/5/21	2022/5/20
ETSTW-RE 044	Log-Periodic Antenna	HL050	100094	R&S	2021/7/14	2022/7/13
ETSTW-RE 045	ESA-E SERIES SPECTRUM ANALYZER	E4404B	MY45111242	Agilent	Pre-test Use	
ETSTW-RE 050	Attenuator 10dB	50HF-010-1	None	JFW	2022/2/18	2023/2/17
ETSTW-RE 051	Attenuator 6dB	50HF-006-1	None	JFW	2022/2/18	2023/2/17
ETSTW-RE 053	Attenuator 3dB	50HF-003-1	None	JFW	2022/2/18	2023/2/17
ETSTW-RE 055	SPECTRUM ANALYZER	FSU 26	200074	R&S	2022/3/4	2023/3/3
ETSTW-RE 060	Attenuator 30dB	5015-30	F651012z-01	ATM	2022/2/18	2023/2/17
ETSTW-RE 062	Amplifier Module	CHC 2	None	KMIC	2021/5/14	2022/5/13
ETSTW-RE 064	Bluetooth Test Set	MT8852B-042	6K00005709	Anritsu	Function Test	
ETSTW-RE 069	Double-Ridged Guide Horn Antenna	3117	00069377	ETS-Lindgren	Function Test	
ETSTW-RE 072	CELL SITE TEST SET	8921A	3339A00375	HP	2021/10/27	2022/10/26
ETSTW-RE 088	SOLID STATE AMPLIFIER	KMA180265A01	99057	KMIC	2021/9/17	2022/9/16
ETSTW-RE 091	Match Pad	MDCS1500	None	WOKEN	2021/5/27	2022/5/26
ETSTW-RE 099	DC Block	50DB-007-1	None	JFW	2022/2/18	2023/2/17
ETSTW-RE 112	AC POWER SOURCE	TFC-1005	T-0A023536	T-Power	Function test	




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22201-21487-C-1

FCC ID: 2A47N-PRW3PI

ETSTW-RE 115	2.4GHz Notch Filter	N0124411	473874	MICROWAVE CIRCUITS	2022/1/5	2023/1/4
ETSTW-RE 120	RF Player	MP9200	MP9210-111022	ADIVIC	2021/10/29	2022/10/28
ETSTW-RE 122	SIGNAL GENERATOR	SMF100A	102149	R&S	2021/6/8	2022/6/7
ETSTW-RE 125	5GHz Notch filter	5NSL11-5200/E221.3-O/O	1	K&L Microwave	2021/8/6	2022/8/5
ETSTW-RE 126	5GHz Notch filter	5NSL12-5800/E221.3-O/O	1	K&L Microwave	2021/8/6	2022/8/5
ETSTW-RE 127	RF Switch Box	RFS-01	None	WTS	2022/2/18	2023/2/17
ETSTW-RE 128	5.3GHz Notch filter	N0153001	SN487233	Microwave Circuits	2021/8/6	2022/8/5
ETSTW-RE 129	5.5GHz Notch filter	N0555984	SN487234	Microwave Circuits	2021/8/6	2022/8/5
ETSTW-RE 130	Handheld RF Spectrum Analyzer	N9340A	CN0147000204	Agilent	Pre-test Use	
ETSTW-RE 142	Amplifier	8447D	2805A03378	Agilent	2021/5/14	2022/5/13
ETSTW-RE 146	Preamplifier	JPA-10M1G	15090004	JPT	2021/6/4	2022/6/3
ETSTW-RE 152	Bi-log Hybrid Antenna	MCTD 2786B	BLB20J04029	ETC	2021/10/5	2022/10/4
ETSTW-RE 153	Signal Analyzer	FSV40	101929	R&S	2021/10/6	2022/10/5
ETSTW-RE 159	Bi-log Hybrid Antenna (30M~1000 MHz)	MCTD 2786B	BLB21N04035	ETC	2021/12/06	2022/12/05
ETSTW-RF 002	Electromagnetic field probe	LF-30	K-0007	STT	2021/7/19	2022/7/18
ETSTW-EMI 011	USB Compact Modulator	SFC-U	101689	R&S	2021/6/2	2022/6/1
ETSTW-GSM 002	Universal Radio Communication Tester	CMU 200	109439	R&S	2022/3/4	2023/3/3
ETSTW-GSM 003	Radio Communication Analyzer	MT8820C	6201342073	Anritsu	2021/4/27	2022/4/26
ETSTW-GSM 004	Wideband Radio Communication Tester	CMW500	128092	R&S	2021/10/29	2022/10/28
ETSTW-GSM 019	Band Reject Filter	WRCTF824/849-822/851-40 /12+9SS	3	WI	2022/1/5	2023/1/4
ETSTW-GSM 020	Band Reject Filter	WRCD1747/1748-1743/1752-32/5SS	1	WI	2022/1/5	2023/1/4
ETSTW-GSM 021	Band Reject Filter	WRCD1879.5/1880.5-1875.5/1884.5-32/5SS	3	WI	2022/1/5	2023/1/4
ETSTW-GSM 022	Band Reject Filter	WRCT901.9/903.1-904.25-50/8SS	1	WI	2022/1/5	2023/1/4
ETSTW-GSM 023	Power Divider	4901.19.A	None	SUHNER	2021/9/7	2022/9/6
ETSTW-GSM 024	Radio Communication Analyzer	MT8821C	None	Anritsu	2021/4/1	2022/3/31
ETSTW-GSM 025	Band Reject Filter	BRM19835	001	Micro-Tronics	2021/8/6	2022/8/5
ETSTW-Cable 011	SMA to N type Cable	RGU-400	None	THERMAX	Pre-test Use NCR	
ETSTW-Cable 016	BNC Cable	Switch Box	B Cable 1	Schwarz beck	2022/2/18	2023/2/17
ETSTW-Cable 017	BNC Cable	X Cable	B Cable 2	Schwarz beck	2022/2/18	2023/2/17
ETSTW-Cable 018	BNC Cable	Y Cable	B Cable 3	Schwarz beck	2022/2/18	2023/2/17
ETSTW-Cable 019	BNC Cable	Z Cable	B Cable 4	Schwarz beck	2022/2/18	2023/2/17
ETSTW-Cable 020	N TYPE Cable	OATS Cable 1	N30N30-L335-15M	JYE BAO CO.,LTD.	2021/7/1	2022/6/30
ETSTW-Cable 027	Microwave Cable	SUCOFLEX 104	279083	HUBER+SUHNER	2021/5/7	2022/5/6
ETSTW-Cable 028	Microwave Cable	FA147A0015M2020	30064-2	UTIFLEX	2021/9/17	2022/9/16
ETSTW-Cable 029	Microwave Cable	FA147A0015M2020	30064-3	UTIFLEX	2021/9/17	2022/9/16
ETSTW-Cable 030	Microwave Cable	SUCOFLEX 104 (S Cable 9)	279067	HUBER+SUHNER	2022/2/18	2023/2/17




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22201-21487-C-1

FCC ID: 2A47N-PRW3PI

ETSTW-Cable 043	Microwave Cable	SUCOFLEX 104	317576	HUBER+SUHNER	2021/5/14	2022/5/13
ETSTW-Cable 047	Microwave Cable	SUCOFLEX 104	325518	HUBER+SUHNER	2021/7/2	2022/7/1
ETSTW-Cable 058	Microwave Cable	SUCOFLEX 104	none	HUBER+SUHNER	2021/6/4	2022/6/3
ETSTW-Cable 064	Microwave Cable	SUCOFLEX 104	MY28891	HUBER+SUHNER	2021/5/14	2022/5/13
ETSTW-Cable 071	N TYPE CABLE	EMCCFD400-NM-NM-25000	170239	EMCI	2021/6/4	2022/6/3
ETSTW-Cable 072	SMA type cable (8m)	SUCOFLEX 104	805800/4	HUBER+SUHNER	2021/5/14	2022/5/13
ETSTW-Cable 074	SMA type cable (2m)	SUCOFLEX 104	802563/4	HUBER+SUHNER	2021/5/14	2022/5/13
WTSTW-SW 002	EMI TEST SOFTWARE	EZ EMC	None	Farad	Version ETS-03A1 Version EMEC-3A1+	
WTSTW-SW 006	EMI TEST SOFTWARE	e3	None	AUDIX	Version 9.161014	
WTSTW-SW 008	Signal studio	Agilent	None	AUDIX	Version 2.0.0.1	
ETSTW-TH 002	Thermohygrometer	608-H1	45204317	Testo	2021/10/18	2022/10/17
ETSTW-TH 003	Wireless weather station	GAIA	N/A	TFA	2021/10/18	2022/10/17



Registration number: W6M22201-21487-C-1

FCC ID: 2A47N-PRW3PI

2.4 General Test Procedure

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI STANDARD C63.10-2013 6.2 using a 50 μ H LISN (if necessary). Both lines were observed. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

RADIATION INTERFERENCE: The test procedure used was according to ANSI STANDARD C63.10-2013 6.3 employing a spectrum analyzer. For investigated frequency is equal to or below 1GHz, the RBW and VBW of the spectrum analyzer was 100 kHz and 100kHz respectively with an appropriate sweep speed. For investigated frequency is above 1GHz, both of RBW and VBW of the spectrum analyzer were 1 MHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dB μ V) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB.

Example:


Freq (MHz)	METER READING + ACF + CABLE LOSS (to the receiver) = FS
33	20 dB μ V + 10.36 dB + 6 dB = 36.36 dB μ V/m @3m

The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m (non metallic table) and arranged according to ANSI C63.10-2013 6.2.2. The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to the frequency specified as follows:

- (1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
- (2) If the intentional radiator operates at or above 10 GHz and below 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.
- (3) If the intentional radiator operates at or above 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 200 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.
- (4) If the intentional radiator contains a digital device, regardless of whether this digital device controls the functions of the intentional radiator or the digital device is used for additional control or function purposes other than to enable the operation of the intentional radiator, the frequency range shall be investigated up to the range specified in paragraphs (a)(1)-(a)(3) of this section or the range applicable to the digital device, as shown in paragraph (b)(1) of this Section, whichever is the higher frequency range of investigation.

For hand-held devices, a exploratory test was performed with three (3) orthogonal planes to determine the highest emissions.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.



Registration number: W6M22201-21487-C-1

FCC ID: 2A47N-PRW3PI

When the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.

The formula is as follows:


Average = Peak + Duty Factor

Duty Factor = $20 \log (\text{dwell time}/T)$

$T = 100\text{ms}$ when the pulse train period is over 100 ms or the period of the pulse train.

Modified Limits for peak according to 15.35 (b) = Max Permitted average Limits + 20dB

ANSI STANDARD C63.10-2013 B.2.7: Any measurements that utilize special test software shall be indicated and referenced in the test report. During testing, test software 'EZ EMC' was used for setting up different operation modes.




Registration number: W6M22201-21487-C-1

FCC ID: 2A47N-PRW3PI

3 Test results (enclosure)

Test case	Para. Number	Required	Test passed	Test failed
Duty Cycle	Subclause 11.6 of ANSI C63.10	☒	☒	☐
Peak Output Power	15.247(b) Subclause 11.9.2.2.2 of ANSI C63.10	☒	☒	☐
Equivalent isotropically radiated Power	15.247(b) Subclause 11.9.2.2 of ANSI C63.10	☒	☒	☐
Transmitter Emissions in Non-Restricted Bands	15.247(c): 15.209 Subclause 11.11 of ANSI C63.10	☒	☒	☐
Spurious Emissions radiated-Transmitter operating	15.247(c): 15.209 Subclause 11.12 of ANSI C63.10	☒	☒	☐
Band Edge Measurement	15.247(d) Subclause 6.10.5 of ANSI C63.10	☒	☒	☐
Minimum 6 dB Bandwidth	15.247(a)(2) Subclause 11.8.1 of ANSI C63.10	☒	☒	☐
Peak Power Spectral Density	15.247(e) Subclause 11.10.2 of ANSI C63.10	☒	☒	☐
Radiated Emission from Receiver Part	15.109	☒	☒	☐
Power Line Conducted Emission	15.207	☒	☒	☐



Registration number: W6M22201-21487-C-1

FCC ID: 2A47N-PRW3PI

3.1 Duty Cycle


Test date: March 07, 2022

Temperature: 20.8 °C

Humidity: 58.0 %


Tester: Spencer

	T(on)	T(on+off)	duty cycle	duty factor(dB)
802.11b	100	100	100%	0
802.11g	100	100	100%	0
802.11n20	100	100	100%	0
802.11n40	100	100	100%	0




DUTY CYCLE 802.11B CH1


Date: 7.MAR.2022 11:31:37




Registration number: W6M22201-21487-C-1
FCC ID: 2A47N-PRW3PI




DUTY CYCLE 802.11G CH1
Date: 7.MAR.2022 11:32:18



DUTY CYCLE 802.11N 20MHZ CH1
Date: 7.MAR.2022 11:35:37




Registration number: W6M22201-21487-C-1
FCC ID: 2A47N-PRW3PI



DUTY CYCLE 802.11N 40MHZ CH1
Date: 7.MAR.2022 11:36:01

Test equipment used: ETSTW-RE 055



Registration number: W6M22201-21487-C-1

FCC ID: 2A47N-PRW3PI

3.2 Peak Output Power (transmitter)

FCC Rule: 15.247(b)(3)

This measurement applies to equipment with an integral antenna and to equipment with an antenna connector and equipped with an antenna as declared by the applicant.

The power was measured with modulation (declared by the applicant).


Test date: January 18, 2022

Temperature: 20.3 °C

Humidity: 54.2 %


Tester: Spencer

Mode A




MAX OUTPUT POWER 802.11B CH01


Date: 18.JAN.2022 08:39:46




Registration number: W6M22201-21487-C-1
FCC ID: 2A47N-PRW3PI



MAX OUTPUT POWER 802.11B CH06
Date: 18.JAN.2022 08:40:32




MAX OUTPUT POWER 802.11B CH11
Date: 18.JAN.2022 08:41:12



Registration number: W6M22201-21487-C-1


FCC ID: 2A47N-PRW3PI

Mode B




MAX OUTPUT POWER 802.11G CH01

Date: 18.JAN.2022 08:43:04




MAX OUTPUT POWER 802.11G CH06

Date: 18.JAN.2022 08:44:21




Registration number: W6M22201-21487-C-1
FCC ID: 2A47N-PRW3PI




MAX OUTPUT POWER 802.11G CH11
Date: 18.JAN.2022 08:45:02

Mode C




MAX OUTPUT POWER 802.11N 20MHz CH1
Date: 18.JAN.2022 09:01:51



Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M22201-21487-C-1

FCC ID: 2A47N-PRW3PI




MAX OUTPUT POWER 802.11N 20MHZ CH6

Date: 18.JAN.2022 09:02:35



MAX OUTPUT POWER 802.11N 20MHZ CH11


Date: 18.JAN.2022 09:05:24



Registration number: W6M22201-21487-C-1


FCC ID: 2A47N-PRW3PI

Mode D




MAX OUTPUT POWER 802.11N 40MHZ CH1

Date: 18.JAN.2022 09:06:31




MAX OUTPUT POWER 802.11N 40MHZ CH4

Date: 18.JAN.2022 09:07:51



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22201-21487-C-1
FCC ID: 2A47N-PRW3PI




MAX OUTPUT POWER 802.11N 40MHZ CH7
Date: 18.JAN.2022 09:10:01

Limits:

Frequency MHz	Power dBm
902 - 928	30
2400 – 2483.5	30
5725 – 5850	30

In case of employing transmitter antennas having antenna gain > 6 dBi and using fixed point-to point operation consider §15.247 (b)(4)

Test equipment used: ETSTW-RE 055, ETSTW-RE 050



Registration number: W6M22201-21487-C-1

FCC ID: 2A47N-PRW3PI

3.3 Equivalent isotropic radiated power (EIRP)

FCC Rule: 15.247(b)(3)

EIRP=max. conducted output power+antenna gain

EIRP=16.47 dBm+2 dBi[antenna gain claimed by manufacturer]=18.47 dBm=70.31 mW

3.4 Exemption Limits for Routine Evaluation

according to 47 CFR FCC Part 2 Subpart J, section 2.1091

FCC OET Bulletin 65 Edition 97.01 determines the equations for predicting RF fields and applicable limits.

The prediction for power density in the far-field but will over-predict power density in the near field, where it could be used for walking a “worst case” or conservative prediction.

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 20 cm normally can be maintained between the user and the device.

MPE Calculation Method

(A) Limits for Occupational/Controlled Exposure


Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6

(B) Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100,000	--	--	1.0	30

f = frequency in MHz

*Plane-wave equivalent power density



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22201-21487-C-1

FCC ID: 2A47N-PRW3PI

E = Electric field (V/m) P = output power (W) G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

mW/cm².

Established separation distance is 20 cm.


Operating frequency band : 2412-2462 MHz

The product meets RF exposure requirement.

Because the power density of 0.014 mW/cm² at 2462 MHz is below the power density limit of 1 mW/cm².

Limits:

Limit for General Population / Uncontrolled Exposure	
Frequency (MHz)	Power Density (mW/cm ²)
1500 – 100.000	1.0



Registration number: W6M22201-21487-C-1

FCC ID: 2A47N-PRW3PI

3.5 Transmitter Emissions in Non-Restricted Bands

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required.


Test date: January 18, 2022

Temperature: 20.3 °C

Humidity: 54.2 %


Tester: Spencer

Mode A




BANDEDGE 802.11B CH01

Date: 18.JAN.2022 08:40:08




Registration number: W6M22201-21487-C-1
FCC ID: 2A47N-PRW3PI




BANDEDGE 802.11B CH11
Date: 18.JAN.2022 08:41:33


Mode B



BANDEDGE 802.11G CH01
Date: 18.JAN.2022 08:43:25




Registration number: W6M22201-21487-C-1
FCC ID: 2A47N-PRW3PI




BANDEDGE 802.11G CH11
Date: 18.JAN.2022 08:45:23


Mode C



BANDEDGE 802.11N 20MHz CH01
Date: 18.JAN.2022 09:02:12




Registration number: W6M22201-21487-C-1
FCC ID: 2A47N-PRW3PI




BANDEDGE 802.11N 20MHZ CH11
Date: 18.JAN.2022 09:05:45


Mode D




BANDEDGE 802.11N 40MHZ CH01
Date: 18.JAN.2022 09:06:59



Registration number: W6M22201-21487-C-1
FCC ID: 2A47N-PRW3PI



BANDEDGE 802.11N 40MHZ CH07
Date: 18.JAN.2022 09:10:29



Registration number: W6M22201-21487-C-1

FCC ID: 2A47N-PRW3PI

3.6 Transmitter Radiated Emissions in Restricted Bands

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

FCC Rules: 15.247 (c), 15.205, 15.209, 15.35

Radiated emission measurements were performed from 30 MHz to 26500 MHz.

For radiated emission tests, the analyzer setting was as followings:

Frequency $\leq$ 1 GHz, RBW:100 kHz, VBW: 100 kHz (Peak measurements)

Frequency $>$ 1 GHz, RBW: 1 MHz, VBW: 1 MHz (Peak measurements)

Frequency $>$ 1 GHz , RBW:1 MHz , VBW: 10 Hz (Average measurements)

Limits.

For frequencies below 1GHz:

Frequency of Emission (MHz)	Field strength (microvolts/meter)	Field Strength (dB microvolts/meter)
30 - 88	100	40.0
88 - 216	150	43.5
216 - 960	200	46.0
Above	500	54.0

For frequencies above 1GHz (Average measurements).

Guidance on Measurement of Digit Transmission Systems:


“If the emission is pulsed, modify the unit for continuous operation, use the setting shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.”

The correction factor, based on the total channel dwell time in a 100 ms period, may be mathematically applied to a measurement made with an average detector, to further reduce the value.

Duty cycle correction = $20 \log (\text{dwell time} / 100\text{ms})$

Note: No duty cycle correction was added to the reading of this EUT.

Explanation: see attached diagrams in Appendix.




Registration number: W6M22201-21487-C-1

FCC ID: 2A47N-PRW3PI


3.7 Band edge

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Mode A




Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2390.000	17.32	peak	38.42	55.74	74.00	150	305	-18.26	
*	2390.000	4.74	AVG	38.42	43.16	54.00	150	305	-10.84	




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22201-21487-C-1
FCC ID: 2A47N-PRW3PI




Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2390.000	20.74	peak	38.42	59.16	74.00	100	210	-14.84	
*	2390.000	9.70	AVG	38.42	48.12	54.00	100	210	-5.88	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22201-21487-C-1
FCC ID: 2A47N-PRW3PI



Site : Chamber

Condition : FCC 15.247 PK (Bandedge)

EUT : W6M22201-21487

M/N:

Test Mode : TX 802.11b CH11


Note :

Polarization: *Horizontal*

Power : 120 Va.c.


Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2483.500	16.83	peak	38.75	55.58	74.00	150	300	-18.42	
*	2483.500	5.18	AVG	38.75	43.93	54.00	150	300	-10.07	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22201-21487-C-1
FCC ID: 2A47N-PRW3PI



Site : Chamber

Condition : FCC 15.247 PK (Bandedge)

EUT : W6M22201-21487

M/N:

Test Mode : TX 802.11b CH11


Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2483.500	20.67	peak	38.75	59.42	74.00	150	215	-14.58	
*	2483.500	9.17	AVG	38.75	47.92	54.00	150	215	-6.08	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22201-21487-C-1

FCC ID: 2A47N-PRW3PI

Mode B

Radiated Emission Measurement

Operator: Allen

File :bandedge

Data :#1


Date: 1/13/2022

Temperature:20.0 °C

132.0 dBuV/m

Time: 5:18:22 AM

Humidity:59.4 %



Site : Chamber

Condition : FCC 15.247 PK (Bandedge)

EUT : W6M22201-21487

M/N:

Test Mode : TX 802.11g CH1


Note :

Polarization: *Horizontal*

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	2390.000	31.47	peak	38.42	69.89	74.00	180	300	-4.11	
	2390.000	3.41	AVG	38.42	41.83	54.00	180	300	-12.17	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22201-21487-C-1
FCC ID: 2A47N-PRW3PI

Radiated Emission Measurement

Operator: Allen

File :bandedge


Data :#2

Date: 1/13/2022

Temperature:20.0 °C

Time: 5:21:24 AM

Humidity:59.4 %



Site : Chamber

Condition : FCC 15.247 PK (Bandedge)

EUT : W6M22201-21487

M/N:

Test Mode : TX 802.11g CH1


Note :

Polarization: *Vertical*

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	2390.000	34.44	peak	38.42	72.86	74.00	150	120	-1.14	
	2390.000	3.62	AVG	38.42	42.04	54.00	150	120	-11.96	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22201-21487-C-1
FCC ID: 2A47N-PRW3PI

Radiated Emission Measurement

Operator: Allen

File :bandedge


Data :#1

Date: 1/13/2022

Temperature:20.0 °C

Time: 6:43:26 AM

Humidity:59.4 %



Site : Chamber

Condition : FCC 15.247 PK (Bandedge)

EUT : W6M22201-21487

M/N:

Test Mode : TX 802.11g CH11


Note :

Polarization: *Horizontal*

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	2483.500	26.34	peak	38.75	65.09	74.00	150	180	-8.91	
	2483.500	3.28	AVG	38.75	42.03	54.00	150	180	-11.97	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22201-21487-C-1
FCC ID: 2A47N-PRW3PI

Radiated Emission Measurement

Operator: Allen

File :bandedge


Data :#2

Date: 1/13/2022

Temperature:20.0 °C

Time: 6:45:08 AM

Humidity:59.4 %



Site : Chamber

Condition : FCC 15.247 PK (Bandedge)

EUT : W6M22201-21487

M/N:

Test Mode : TX 802.11g CH11


Note :

Polarization: *Vertical*

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	2483.500	34.18	peak	38.75	72.93	74.00	150	180	-1.07	
	2483.500	3.62	AVG	38.75	42.37	54.00	150	180	-11.63	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22201-21487-C-1

FCC ID: 2A47N-PRW3PI

Mode C

Radiated Emission Measurement

Operator: Allen

File :bandedge

Data :#1


Date: 1/13/2022

Temperature:20.0 °C

Time: 5:39:34 AM

Humidity:59.4 %

132.0 dBuV/m



Site : Chamber

Condition : FCC 15.247 PK (Bandedge)

EUT : W6M22201-21487

M/N:

Test Mode : TX 802.11n20 CH1


Note :

Polarization: *Horizontal*

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	2390.000	27.50	peak	38.42	65.92	74.00	150	300	-8.08	
	2390.000	3.57	AVG	38.42	41.99	54.00	150	300	-12.01	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22201-21487-C-1
FCC ID: 2A47N-PRW3PI

Radiated Emission Measurement

Operator: Allen

File :bandedge


Data :#2

Date: 1/13/2022

Temperature:20.0 °C

Time: 5:43:37 AM

Humidity:59.4 %



Site : Chamber

Condition : FCC 15.247 PK (Bandedge)

EUT : W6M22201-21487

M/N:

Test Mode : TX 802.11n20 CH1


Note :

Polarization: *Vertical*

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	2390.000	34.82	peak	38.42	73.24	74.00	150	120	-0.76	
	2390.000	3.69	AVG	38.42	42.11	54.00	150	120	-11.89	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22201-21487-C-1
FCC ID: 2A47N-PRW3PI

Radiated Emission Measurement

Operator: Allen

File :bandedge


Data :#1

Date: 1/13/2022

Temperature:20.0 °C

Time: 6:22:16 AM

Humidity:59.4 %



Site : Chamber

Condition : FCC 15.247 PK (Bandedge)

EUT : W6M22201-21487

M/N:

Test Mode : TX 802.11n20 CH11


Note :

Polarization: *Horizontal*

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	2483.500	24.31	peak	38.75	63.06	74.00	150	180	-10.94	
	2483.500	3.14	AVG	38.75	41.89	54.00	150	180	-12.11	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22201-21487-C-1
FCC ID: 2A47N-PRW3PI

Radiated Emission Measurement

Operator: Allen

File :bandedge

Data :#2


Date: 1/13/2022

Temperature:20.0 °C

132.0 dBuV/m

Time: 6:25:56 AM

Humidity:59.4 %



Site : Chamber

Condition : FCC 15.247 PK (Bandedge)

EUT : W6M22201-21487

M/N:

Test Mode : TX 802.11n20 CH11


Note :

Polarization: *Vertical*

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	2483.500	34.11	peak	38.75	72.86	74.00	150	50	-1.14	
	2483.500	3.86	AVG	38.75	42.61	54.00	150	50	-11.39	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22201-21487-C-1

FCC ID: 2A47N-PRW3PI

Mode D

Radiated Emission Measurement

Operator: Allen

File :bandedge

Data :#1


Date: 1/13/2022

Temperature:20.0 °C

132.0 dBuV/m

Time: 5:52:45 AM

Humidity:59.4 %



Site : Chamber

Condition : FCC 15.247 PK (Bandedge)

EUT : W6M22201-21487

M/N:

Test Mode : TX 802.11n40 CH1


Note :

Polarization: *Horizontal*

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	2390.000	27.39	peak	38.42	65.81	74.00	150	300	-8.19	
	2390.000	3.17	AVG	38.42	41.59	54.00	150	300	-12.41	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22201-21487-C-1
FCC ID: 2A47N-PRW3PI

Radiated Emission Measurement

Operator: Allen

File :bandedge

Data :#2


Date: 1/13/2022

Temperature:20.0 °C

132.0 dBuV/m

Time: 5:55:01 AM

Humidity:59.4 %



Site : Chamber

Condition : FCC 15.247 PK (Bandedge)

EUT : W6M22201-21487

M/N:

Test Mode : TX 802.11n40 CH1


Note :

Polarization: **Vertical**

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	2390.000	33.84	peak	38.42	72.26	74.00	150	55	-1.74	
	2390.000	3.72	AVG	38.42	42.14	54.00	150	55	-11.86	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22201-21487-C-1
FCC ID: 2A47N-PRW3PI

Radiated Emission Measurement

Operator: Allen

File :bandedge


Data :#1

Date: 1/13/2022

Temperature:20.0 °C

Time: 6:04:51 AM

Humidity:59.4 %



Site : Chamber

Condition : FCC 15.247 PK (Bandedge)

EUT : W6M22201-21487

M/N:

Test Mode : TX 802.11n40 CH7


Note :

Polarization: *Horizontal*

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	2483.500	25.05	peak	38.75	63.80	74.00	150	180	-10.20	
	2483.500	3.74	AVG	38.75	42.49	54.00	150	180	-11.51	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22201-21487-C-1
FCC ID: 2A47N-PRW3PI

Radiated Emission Measurement

Operator: Allen

File :bandedge

Data :#2


Date: 1/13/2022

Temperature:20.0 °C

132.0 dBuV/m

Time: 6:10:14 AM

Humidity:59.4 %



Site : Chamber

Condition : FCC 15.247 PK (Bandedge)

Polarization: **Vertical**

EUT : W6M22201-21487

Power : 120 V.a.c.

M/N:

Distance: 3m

Test Mode : TX 802.11n40 CH7


Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	2483.500	33.03	peak	38.75	71.78	74.00	150	300	-2.22	
	2483.500	3.92	AVG	38.75	42.67	54.00	150	300	-11.33	

Limit:

Frequency Range / MHz	Limit
902 – 928	- 20 dB
2400 – 2483.5	
5725 - 5850	

Test equipment used: ETSTW-RE 055, ETSTW-RE 050



Registration number: W6M22201-21487-C-1

FCC ID: 2A47N-PRW3PI

3.8 Minimum 6 dB Bandwidth

The analyzer ResBW was set to 100 kHz. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK reading was taken, two markers were set 6 dB below the maximum level on the right and the left side of the emission.

The 6 dB bandwidth is the frequency difference between the two markers.


Test date: January 18, 2022

Temperature: 20.3 °C

Humidity: 54.2 %


Tester: Spencer

Mode A




6DB BANDWIDTH 802.11B CH01

Date: 18.JAN.2022 08:39:54




Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M22201-21487-C-1
FCC ID: 2A47N-PRW3PI



6DB BANDWIDTH 802.11B CH06
Date: 18.JAN.2022 08:40:39



6DB BANDWIDTH 802.11B CH11
Date: 18.JAN.2022 08:41:19




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22201-21487-C-1


FCC ID: 2A47N-PRW3PI

Mode B




6DB BANDWIDTH 802.11G CH01

Date: 18. JAN. 2022 08:43:11




6DB BANDWIDTH 802.11G CH06

Date: 18. JAN. 2022 08:44:28




Registration number: W6M22201-21487-C-1
FCC ID: 2A47N-PRW3PI




6DB BANDWIDTH 802.11G CH11
Date: 18.JAN.2022 08:45:09


Mode C




6DB BANDWIDTH 802.11N 20MHz CH1
Date: 18.JAN.2022 09:01:58




Registration number: W6M22201-21487-C-1
FCC ID: 2A47N-PRW3PI



6DB BANDWIDTH 802.11N 20MHZ CH6
Date: 18.JAN.2022 09:02:42



6DB BANDWIDTH 802.11N 20MHZ CH11
Date: 18.JAN.2022 09:05:31




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22201-21487-C-1


FCC ID: 2A47N-PRW3PI

Mode D




6DB BANDWIDTH 802.11N 40MHz CH1

Date: 18.JAN.2022 09:06:38




6DB BANDWIDTH 802.11N 40MHz CH4

Date: 18.JAN.2022 09:07:58



Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M22201-21487-C-1
FCC ID: 2A47N-PRW3PI



Limits:

Frequency Range MHz	Limits
902-928	min 500 kHz
2400-2483.5	min 500 kHz
5725-5850	min 500 kHz

Test equipment used: ETSTW-RE 055, ETSTW-RE 050



Registration number: W6M22201-21487-C-1

FCC ID: 2A47N-PRW3PI

3.9 Peak Power Spectral Density

Peak Power Spectral density is a measured at low, middle and high channel.

The peak output power is measured with a measurement bandwidth of 10 MHz and displayed on diagram together with Peak Power Spectral Density result which was measured with a bandwidth of 3 kHz, appreciate frequency span and sweep time.


Test date: January 18, 2022

Temperature: 20.3 °C

Humidity: 54.2 %


Tester: Spencer

Mode A




POWER DENSITY 802.11B CH01


Date: 18.JAN.2022 08:40:03




Registration number: W6M22201-21487-C-1
FCC ID: 2A47N-PRW3PI



POWER DENSITY 802.11B CH06
Date: 18. JAN.2022 08:40:48




POWER DENSITY 802.11B CH11
Date: 18. JAN.2022 08:41:28



Registration number: W6M22201-21487-C-1


FCC ID: 2A47N-PRW3PI

Mode B




POWER DENSITY 802.11G CH01

Date: 18.JAN.2022 08:43:20




POWER DENSITY 802.11G CH06

Date: 18.JAN.2022 08:44:37




Registration number: W6M22201-21487-C-1
FCC ID: 2A47N-PRW3PI




POWER DENSITY 802.11G CH11
Date: 18.JAN.2022 08:45:18


Mode C




POWER DENSITY 802.11N 20MHZ CH1
Date: 18.JAN.2022 09:02:07




Registration number: W6M22201-21487-C-1
FCC ID: 2A47N-PRW3PI



POWER DENSITY 802.11N 20MHZ CH6
Date: 18.JAN.2022 09:02:51




POWER DENSITY 802.11N 20MHZ CH11
Date: 18.JAN.2022 09:05:40



Registration number: W6M22201-21487-C-1


FCC ID: 2A47N-PRW3PI

Mode D




POWER DENSITY 802.11N 40MHZ CH1

Date: 18.JAN.2022 09:06:54




POWER DENSITY 802.11N 40MHZ CH4

Date: 18.JAN.2022 09:08:14



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22201-21487-C-1
FCC ID: 2A47N-PRW3PI




POWER DENSITY 802.11N 40MHZ CH7
Date: 18.JAN.2022 09:10:24

Limits:

Frequency Range MHz	dBm
902-928	8
2400-2483.5	8
5725-5850	8

Test equipment used: ETSTW-RE 055, ETSTW-RE 050



Registration number: W6M22201-21487-C-1

FCC ID: 2A47N-PRW3PI


3.10 Radiated Emission from Receiver Part

Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency of Emission (MHz)	Field Strength (microvolts/meter)	Field Strength (dBmicrovolts/meter)
30 – 88	100	40.0
88 – 216	150	43.5
216 – 960	200	46.0
Above 960	500	54.0

Test equipment used: ETSTW-RE 055, ETSTW-RE 064, ETSTW-RE 004, ETSTW-RE 030
ETSTW-RE 062, ETSTW-RE 142, ETSTW-RE 147

Explanation: Please see attached diagrams in appendix.




Registration number: W6M22201-21487-C-1

FCC ID: 2A47N-PRW3PI


3.11 Power Line Conducted Emission

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the table bellows with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

This measurement was transact first with instrumentation using an average and peak detector and a 10 kHz bandwidth. If the peak detector achieves a calculated level, the measurement is repeated by an instrumentation using a quasi-peak detector.




Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Comment
	0.4730	35.24	QP	9.47	44.71	56.46	-11.75	
*	0.4730	30.84	AVG	9.47	40.31	46.46	-6.15	
	0.5450	31.12	QP	9.50	40.62	56.00	-15.38	
	0.5450	28.07	AVG	9.50	37.57	46.00	-8.43	
	0.5922	25.82	QP	9.52	35.34	56.00	-20.66	
	0.5922	20.89	AVG	9.52	30.41	46.00	-15.59	
	0.8577	24.82	QP	9.63	34.45	56.00	-21.55	
	0.8577	18.61	AVG	9.63	28.24	46.00	-17.76	
	1.2245	24.06	QP	9.71	33.77	56.00	-22.23	
	1.2245	18.20	AVG	9.71	27.91	46.00	-18.09	
	12.3250	25.37	QP	10.11	35.48	60.00	-24.52	
	12.3250	16.13	AVG	10.11	26.24	50.00	-23.76	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22201-21487-C-1

FCC ID: 2A47N-PRW3PI



Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Comment
	0.4681	27.61	QP	9.48	37.09	56.55	-19.46	
	0.4681	18.52	AVG	9.48	28.00	46.55	-18.55	
	0.5495	31.55	QP	9.51	41.06	56.00	-14.94	
*	0.5495	28.53	AVG	9.51	38.04	46.00	-7.96	
	0.8150	25.91	QP	9.62	35.53	56.00	-20.47	
	0.8150	20.67	AVG	9.62	30.29	46.00	-15.71	
	1.2424	24.16	QP	9.70	33.86	56.00	-22.14	
	1.2424	18.52	AVG	9.70	28.22	46.00	-17.78	
	10.3625	25.59	QP	9.98	35.57	60.00	-24.43	
	10.3625	16.75	AVG	9.98	26.73	50.00	-23.27	
	11.9125	25.65	QP	10.00	35.65	60.00	-24.35	
	11.9125	16.86	AVG	10.00	26.86	50.00	-23.14	

Note:

1. The formula of measured value as: Test Result = Reading + Correction Factor
2. The Correction Factor = Cable Loss + LISN Insertion Loss + Pulse Limit Loss
3. Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average
4. All not in the table noted test results are more than 20 dB below the relevant limits.
5. Up Line: QP Limit Line, Down Line: Ave Limit Line.

Limits:

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi Peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

Test equipment used: ETSTW-CE 001, ETSTW-CE 016, ETSTW-RE 045