



SAR Test Report

Report No.: STS2505157H01

Issued for

August International Ltd

Rawmec Business Park, Plumpton Road, Hoddesdon,
Hertfordshire, EN11 0EE, United Kingdom

Product Name: Vital Sign Monitor Watch

Brand Name: AUDAR

Model Name: E2

Series Model(s): N/A

FCC ID: 2A4RA-E2

Test Standard: ANSI/IEEE Std. C95.1
FCC 47 CFR Part 2 (2.1093)
IEEE Std. 1528-2013

Max. Report SAR (1g) Front of face: 0.110 W/kg (1g)
Wrist: 0.107 W/kg(10g)

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

**TEST REPORT CERTIFICATION**

Applicant's name : August International Ltd
Address : Rawmec Business Park, Plumpton Road, Hoddesdon,
Hertfordshire, EN11 0EE, United Kingdom
Manufacturer's Name : August International Ltd
Address : Rawmec Business Park, Plumpton Road, Hoddesdon,
Hertfordshire, EN11 0EE, United Kingdom

Product description

Product name : Vital Sign Monitor Watch
Brand name : AUDAR
Model name : E2
Series Model(s) : N/A

Standards : ANSI/IEEE Std. C95.1
FCC 47 CFR Part 2 (2.1093)
IEEE Std. 1528-2013

The device was tested by Shenzhen STS Test Services Co., Ltd. in accordance with the measurement methods and procedures specified in KDB 865664 The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Date of Test

Date (s) of performance of tests..... : 29th May 2025 ~ 30th May 2025

Date of Issue..... : 13th June 2025

Test Result..... : **Pass**

Testing Engineer :

Xin Liu

(Xin.Liu)

Technical Manager :

Shi fan-long

(Shifan. Long)

Authorized Signatory :

Bovey Yang

(Bovey Yang)





Table of Contents

1. General Information	5
1.1 EUT Description	5
1.2 Test Environment	6
1.3 Test Factory	6
2. Test Standards and Limits	7
3. SAR Measurement System	8
3.1 Definition of Specific Absorption Rate (SAR)	8
3.2 SAR System	8
4. Tissue Simulating Liquids	11
4.1 Simulating Liquids Parameter Check	11
5. SAR System Validation	14
5.1 Validation System	14
5.2 Validation Result	15
6. SAR Evaluation Procedures	16
7. EUT Test Position	17
8. Uncertainty	18
8.1 Measurement Uncertainty	18
9. Conducted Power Measurement	21
9.1 Test Result	21
10. EUT and Test Setup Photo	26
10.1 EUT Photo	26
10.2 Setup Photo	27
11. SAR Result Summary	29
11.1 Front of face SAR	29
11.2 Wrist SAR	30
12. Equipment List	31
Appendix A. System Validation Plots	32
Appendix B. SAR Test Plots	38
Appendix C. Probe Calibration and Dipole Calibration Report	62



Revision History

Rev.	Issue Date	Report No.	Effect Page	Contents
00	13th June 2025	STS2505157H01	ALL	Initial Issue



1. General Information

Environmental evaluation measurements of specific absorption rate (SAR) distributions in emulated human head and body tissues exposed to radio frequency (RF) radiation from wireless portable devices for compliance with the rules and regulations of the U.S. Federal Communications Commission (FCC).

1.1 EUT Description

Product Name	Vital Sign Monitor Watch		
Brand Name	AUDAR		
Model Name	E2		
Series Model	N/A		
Model Difference	N/A		
Sample number	250520005-5		
Battery	Rated Voltage:3.8V Charge Limit Voltage:4.35V Capacity:280mAh		
Device Category	Wearable		
Product stage	Production unit		
RF Exposure Environment	General Population / Uncontrolled		
Hardware Version	E2-V3		
Software Version	V3.4.5_250519EUF3.4.2		
Frequency Range	LTE Band 2: 1850MHz ~ 1910 MHz LTE Band 4: 1710 MHz ~ 1755 MHz LTE Band 12: 699MHz ~ 716 MHz		
Max. Reported SAR(1g): (Limit:1.6W/kg/ 4.0W/kg) Test distance: Front of face:5mm Body:0mm	Band	Mode	Front of face-1g (W/kg)
	NB-IoT		
	PCT	LTE Band 2	0.014
	PCT	LTE Band 4	0.110
	PCT	LTE Band 12	0.021
	LTE-M		
	PCT	LTE Band 2	0.027
	PCT	LTE Band 4	0.047
	PCT	LTE Band 12	0.012
	Limit(W/kg)		1.6
FCC Equipment Class	PCS Licensed Transmitter worn on body (PCT)		
Operating Mode:	LTE:QPSK,16QAM		
Antenna Specification:	LTE: PIFA Antenna		
Hotspot Mode	Not Support		
DTM Mode	Not Support		

**Note:**

1. The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power

1.2 Test Environment

Ambient conditions in the SAR laboratory:

Items	Required
Temperature (°C)	18-25
Humidity (%RH)	30-70

1.3 Test Factory

ShenZhen STS Test Services Co.,Ltd.

101, Building B, Zhuoke Science Park, No.190 Chongqing Road, ZhanChengShequ, Fuhai Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration No.: 625569

IC Registration No.: 12108A

A2LA Certificate No.: 4338.01



2. Test Standards and Limits

No.	Identity	Document Title
1	47 CFR Part 2	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	IEEE Std C95.1, 2019	IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz. It specifies the maximum exposure limit of 1.6 W/kg as averaged over any 1 gram of tissue for portable devices being used within 20 cm of the user in the uncontrolled environment.
3	IEEE Std. 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
4	FCC KDB 447498 D04 v01	RF Exposure Procedures and Equipment Authorization Policies for Mobile and Portable Devices
5	FCC KDB 865664 D01v01r04	SAR Measurement 100 MHz to 6 GHz
6	FCC KDB 865664 D02 v01r02	RF Exposure Reporting
7	FCC KDB 941225 D05 v02r05	SAR for LTE Devices
8	FCC KDB 648474 D04 v01r03	SAR Evaluation Considerations for Wireless Handsets

(A). Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

(B). Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

NOTE: Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Population/Uncontrolled Environments:

Are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Occupational/Controlled Environments:

Are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

NOTE

GENERAL POPULATION/UNCONTROLLED EXPOSURE

PARTIAL BODY LIMIT

1.6 W/kg/4.0 W/kg

3. SAR Measurement System

3.1 Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by

$$SAR = \frac{\sigma E^2}{\rho}$$

Where: σ is the conductivity of the tissue,
 ρ is the mass density of the tissue and E is the RMS electrical field strength.

3.2 SAR System

MVG SAR System Diagram:



COMOSAR is a system that is able to determine the SAR distribution inside a phantom of human being according to different standards. The COMOSAR system consists of the following items:

- Main computer to control all the system
- 6 axis robot
- Data acquisition system
- Miniature E-field probe
- Phone holder
- Head simulating tissue

The following figure shows the system.



The EUT under test operating at the maximum power level is placed in the phone holder, under the phantom, which is filled with head simulating liquid. The E-Field probe measures the electric field inside the phantom. The Open SAR software computes the results to give a SAR value in a 1g or 10g mass.

3.2.1 Probe

For the measurements the Specific Dosimetric E-Field Probe SN 08/21 EPGO352 with following specifications is used

- Probe Length: 330 mm
- Length of Individual Dipoles: 2 mm
- Maximum external diameter: 8 mm
- Probe Tip External Diameter: 2.5 mm
- Distance between dipole/probe extremity: 1 mm
- Dynamic range: 0.01-100 W/kg
- Probe linearity: 3%
- Axial Isotropy: <0.10 dB
- Spherical Isotropy: <0.10 dB
- Calibration range: 150 MHz to 6 GHz for head & body simulating liquid.
- Angle between probe axis (evaluation axis) and surface normal line: less than 30°



Figure 1-MVG COMOSAR Dosimetric E field Dipole

3.2.2 Phantom

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.


SN 32/14 SAM115



Figure-SN 21/21 ELLI48



3.2.3 Device Holder



The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5 mm distance, a positioning uncertainty of ± 0.5 mm would produce a SAR uncertainty of ± 20 %. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.



4. Tissue Simulating Liquids

4.1 Simulating Liquids Parameter Check

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values

The uncertainty due to the liquid conductivity and permittivity arises from two different sources. The first source of error is the deviation of the liquid conductivity from its target value (max _ 5 %) and the second source of error arises from the measurement procedures used to assess conductivity. The uncertainty shall be assessed using a rectangular probability. For 1 g averaging, the maximum weighting coefficient for SAR is 0.5.

IEEE SCC-34/SC-2 RECOMMENDED TISSUE DIELECTRIC PARAMETERS

The head and body tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 have been incorporated in the following table.

Frequency	ϵ_r	σ 10g S/m
300	45.3	0.87
450	43.5	0.87
750	41.9	0.89
835	41.5	0.90
900	41.5	0.97
1450	40.5	1.20
1800 to 2000	40.0	1.40
2100	39.8	1.49
2450	39.2	1.56
2600	39.0	1.96
3000	38.5	2.40
3500	37.9	2.91
4000	37.4	3.43
4500	36.8	3.94
5000	36.2	4.45
5200	36.0	4.66
5400	35.8	4.86
5600	35.5	5.07
5800	35.3	5.27



The following table gives the recipes for tissue simulating liquid and the theoretical Conductivity/Permittivity.

Head (Reference IEEE1528)								
Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity σ (S/m)	Permittivity ϵ
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.4	40.0
2450	55.0	0	0	0.1	0	44.9	1.56	39.2
2600	54.9	0	0	0.1	0	45.0	1.96	39.0
Frequency (MHz)	Water (%)	Hexyl Carbitol (%)			Triton X-100 (%)		Conductivity σ (S/m)	Permittivity ϵ
5200	62.52	17.24			17.24		4.66	36.0
5800	62.52	17.24			17.24		5.27	35.3
Body (From instrument manufacturer)								
Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity σ (S/m)	Permittivity ϵ
750	51.7	47.2	0	0.9	0.1	0	0.96	55.5
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
900	50.8	48.2	0	0.9	0.1	0	1.05	55.0
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0.1	0	31.3	1.95	52.7
2600	68.2	0	0	0.1	0	31.7	2.16	52.5
Frequency(MHz)	Water	DGBE (%)			Salt (%)		Conductivity σ (S/m)	Permittivity ϵ
5200	78.60	21.40			/		5.30	49.00
5800	78.50	21.40			0.1		6.00	48.20

**LIQUID MEASUREMENT RESULTS**


Date	Ambient		Simulating Liquid		Parameters	Target	Measured	Deviation %	Limited %
	Temp. [°C]	Humidity %	Frequency (MHz)	Temp. [°C]					
29th May 2025	21.3	44	708	21.0	Permittivity	42.13	42.13	0.01	±5
					Conductivity	0.89	0.93	4.83	±5
29th May 2025	21.4	44	711	21.1	Permittivity	42.11	42.52	0.98	±5
					Conductivity	0.89	0.88	-0.83	±5
29th May 2025	21.4	44	750	21.1	Permittivity	41.90	42.92	2.43	±5
					Conductivity	0.89	0.90	1.12	±5
29th May 2025	21.4	44	1732.5	21.0	Permittivity	40.10	41.28	2.95	±5
					Conductivity	1.36	1.41	3.57	±5
29th May 2025	21.4	44	1745	21.0	Permittivity	40.08	40.79	1.78	±5
					Conductivity	1.37	1.35	-1.36	±5
29th May 2025	21.4	44	1800	21.0	Permittivity	40.00	41.32	3.30	±5
					Conductivity	1.40	1.40	0.00	±5
30th May 2025	20.5	43	1880	20.2	Permittivity	40.00	40.52	1.30	±5
					Conductivity	1.40	1.44	2.86	±5
30th May 2025	20.5	43	1900	20.3	Permittivity	40.00	40.66	1.65	±5
					Conductivity	1.40	1.38	-1.43	±5

5. SAR System Validation

5.1 Validation System

Each MVG system is equipped with one or more system validation kits. These units, together with the predefined measurement procedures within the MVG software, enable the user to conduct the system performance check and system validation. System kit includes a dipole, and dipole device holder.

The system check verifies that the system operates within its specifications. It's performed daily or before every SAR measurement. The system check uses normal SAR measurement in the flat section of the phantom with a matched dipole at a specified distance. The system validation setup is shown as below.





5.2 Validation Result

Justification for Extended SAR Dipole Calibrations

Usage of SAR dipoles calibrated less than 3 years ago but more than 1 year ago were confirmed in maintaining return loss (>20 dB, within 20% of prior calibration) and impedance (within 5 ohm from prior calibration) requirements per extended calibrations in KDB 865664 D01:

Dipole		Date of Measurement	Return Loss (dB)	Delta (%)	Impedance	Delta(ohm)
SN 30/14 DIP0G750-331	Head Liquid	2023-07-04	-25.47	/	55.2	/
		2024-07-01	-25.98	2.00	54.86	-0.62
5023-DIP1G800-747	Head Liquid	2023-12-20	-27.38	/	50.2	/
		2024-12-11	-29.08	6.21	46.36	-7.65
SN 30/14 DIP1G900-333	Head Liquid	2023-07-04	-23.66	/	51.4	/
		2024-07-01	-23.62	-0.17	50.73	-1.30

Comparing to the original SAR value provided by MVG, the validation data should be within its specification of 10 %.

Date	Freq.	Power	Tested Value	Normalized SAR	Target SAR	Tolerance	Limit
	(MHz)	(mW)	(W/Kg)	(W/kg)	1g(W/kg)	(%)	(%)
29th May 2025	750	100	0.853	8.53	8.49	0.47	10
29th May 2025	1800	100	3.973	39.73	38.40	3.46	10
30th May 2025	1900	100	4.160	41.60	39.84	4.42	10

Note:

1. The tolerance limit of System validation $\pm 10\%$.
2. The dipole input power (forward power) was 100 mW.
3. The results are normalized to 1 W input power.



6. SAR Evaluation Procedures

The procedure for assessing the average SAR value consists of the following steps:

The following steps are used for each test position

- Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- Measurement of the SAR distribution with a grid of 8 to 16mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

➤ Area Scan& Zoom Scan

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01 quoted below. When the 1-g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.

7. EUT Test Position

This EUT was tested in Front Face and Rear Face.

Limb-worn Position Conditions

Transmitters that are built-in within a wrist watch or similar wrist-worn devices typically operate in speaker mode for voice communication, with the device worn on the wrist and positioned next to the mouth. Next to the mouth exposure requires 1-g SAR and the wrist-worn condition requires 10-g extremity SAR

(1) Next to the mouth use is evaluated with the front of the device positioned at 10 mm from a flat phantom filled with head tissue-equivalent medium



Test position for limb-worn devices



8. Uncertainty

8.1 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in IEEE 1528: 2013. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

SATIMO Uncertainty- SN 08/21 EPG0352									
Measurement uncertainty for DUT averaged over 1 gram / 10 gram.									
Uncertainty Component	Sec.	Tol (+ - %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+ %)	10g Ui (+ %)	vi
Measurement System									
Probe calibration	E.2.1	5.72	N	1.00	1.00	1.00	5.72	5.72	∞
Axial Isotropy	E.2.2	0.18	R	1.73	0.71	0.71	0.07	0.07	∞
Hemispherical Isotropy	E.2.2	1.04	R	1.73	0.71	0.71	0.42	0.42	∞
Boundary effect	E.2.3	0.80	R	1.73	1.00	1.00	0.46	0.46	∞
Linearity	E.2.4	1.25	R	1.73	1.00	1.00	0.72	0.72	∞
System detection limits	E.2.4	1.20	R	1.73	1.00	1.00	0.69	0.69	∞
Modulation response	E.2.5	3.42	R	1.73	1.00	1.00	1.97	1.97	∞
Readout Electronics	E.2.6	0.26	N	1.00	1.00	1.00	0.26	0.26	∞
Response Time	E.2.7	0.17	R	1.73	1.00	1.00	0.10	0.10	∞
Integration Time	E.2.8	1.43	R	1.73	1.00	1.00	0.83	0.83	∞
RF ambient conditions-Noise	E.6.1	3.51	R	1.73	1.00	1.00	2.03	2.03	∞
RF ambient conditions- reflections	E.6.1	3.15	R	1.73	1.00	1.00	1.82	1.82	∞
Probe positioner mechanical tolerance	E.6.2	1.20	R	1.73	1.00	1.00	0.69	0.69	∞
Probe positioning with respect to phantom shell	E.6.3	1.40	R	1.73	1.00	1.00	0.81	0.81	∞
Extrapolation, interpolation, and integrations algorithms for max. SAR evaluation	E.5	2.10	R	1.73	1.00	1.00	1.21	1.21	∞
Test sample Related									
Test sample positioning	E.4.2	3.10	N	1.00	1.00	1.00	3.10	3.10	∞
Device holder uncertainty	E.4.1	3.80	N	1.00	1.00	1.00	3.80	3.80	∞
Output power variation— SAR drift measurement	E.2.9	4.50	R	1.73	1.00	1.00	2.60	2.60	∞
SAR scaling	E.6.5	1.56	R	1.73	1.00	1.00	1.04	1.04	∞
Phantom and tissue parameters									
Phantom shell uncertainty— shape, thickness, and permittivity	E.3.1	3.70	R	1.73	1.00	1.00	2.14	2.14	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	E.3.2	1.90	N	1.00	1.00	0.84	1.90	1.60	∞
Liquid conductivity measurement	E.3.3	2.40	R	1.73	0.78	0.71	1.08	0.98	M
Liquid permittivity measurement	E.3.3	4.10	N	1.00	0.78	0.71	3.20	2.91	M
Liquid conductivity— temperature uncertainty	E.3.4	2.70	R	1.73	0.23	0.26	0.36	0.41	∞
Liquid permittivity— temperature uncertainty	E.3.4	4.80	N	1.00	0.23	0.26	1.10	1.25	∞
Combined Standard Uncertainty			RSS				10.08	9.59	
Expanded Uncertainty (95% Confidence interval)			K=2				19.58	19.18	



SATIMO Uncertainty- SN 08/21 EPGO352									
System Validation uncertainty for DUT averaged over 1 gram / 10 gram.									
Uncertainty Component	Sec.	Tol (+/- %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+ %)	10g Ui (+/-%)	vi
Measurement System									
Probe calibration	E.2.1	5.72	N	1.00	1.00	1.00	5.72	5.72	∞
Axial Isotropy	E.2.2	0.18	R	1.73	1.00	1.00	0.10	0.10	∞
Hemispherical Isotropy	E.2.2	1.04	R	1.73	0.00	0.00	0.00	0.00	∞
Boundary effect	E.2.3	0.80	R	1.73	1.00	1.00	0.46	0.46	∞
Linearity	E.2.4	1.25	R	1.73	1.00	1.00	0.72	0.72	∞
System detection limits	E.2.4	1.20	R	1.73	1.00	1.00	0.69	0.69	∞
Modulation response	E.2.5	3.42	R	1.73	0.00	0.00	0.00	0.00	∞
Readout Electronics	E.2.6	0.26	N	1.00	1.00	1.00	0.26	0.26	∞
Response Time	E.2.7	0.17	R	1.73	0.00	0.00	0.00	0.00	∞
Integration Time	E.2.8	1.43	R	1.73	0.00	0.00	0.00	0.00	∞
RF ambient conditions- Noise	E.6.1	3.51	R	1.73	1.00	1.00	2.03	2.03	∞
RF ambient conditions- reflections	E.6.1	3.15	R	1.73	1.00	1.00	1.82	1.82	∞
Probe positioner mechanical tolerance	E.6.2	1.20	R	1.73	1.00	1.00	0.69	0.69	∞
Probe positioning with respect to phantom shell	E.6.3	1.40	R	1.73	1.00	1.00	0.81	0.81	∞
Extrapolation, interpolation, and integrations algorithms for max. SAR evaluation	E.5	2.10	R	1.73	1.00	1.00	1.21	1.21	∞
System validation source									
Deviation of experimental dipole from numerical dipole	E.6.4	4.80	N	1.00	1.00	1.00	4.80	4.80	∞
Input power and SAR drift measurement	8,6.6.4	5.10	R	1.73	1.00	1.00	2.94	2.94	∞
Dipole axis to liquid distance	8,E.6.6	2.40	R	1.73	1.00	1.00	1.39	1.39	∞
Phantom and set-up									
Phantom shell uncertainty— shape, thickness, and permittivity	E.3.1	3.70	R	1.73	1.00	1.00	2.14	2.14	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	E.3.2	1.90	N	1.00	1.00	0.84	1.90	1.60	∞
Liquid conductivity (temperature uncertainty)	E.3.3	2.40	R	1.73	0.78	0.71	1.08	0.98	∞
Liquid conductivity (measured)	E.3.3	4.10	N	1.00	0.78	0.71	3.20	2.91	M
Liquid permittivity (temperature uncertainty)	E.3.4	2.70	R	1.73	0.23	0.26	0.36	0.41	∞
Liquid permittivity (measured)	E.3.4	4.80	N	1.00	0.23	0.26	1.10	1.25	M
Combined Standard Uncertainty			RSS				9.72	9.52	
Expanded Uncertainty (95% Confidence interval)			K=2				19.44	19.03	



System Check uncertainty for DUT averaged over 1 gram / 10 gram.									
Uncertainty Component	Sec.	Tol	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	vi
		(+-%)							
Measurement System									
Probe calibration drift	E.2.1.3	5.72	N	1.00	1.00	1.00	5.72	5.72	∞
Axial Isotropy	E.2.2	0.18	R	1.73	0.00	0.00	0.00	0.00	∞
Hemispherical Isotropy	E.2.2	1.04	R	1.73	0.00	0.00	0.00	0.00	∞
Boundary effect	E.2.3	0.8	R	1.73	0.00	0.00	0.00	0.00	∞
Linearity	E.2.4	1.25	R	1.73	0.00	0.00	0.00	0.00	∞
System detection limits	E.2.4	1.20	R	1.73	0.00	0.00	0.00	0.00	∞
Modulation response	E.2.5	3.42	R	1.73	0.00	0.00	0.00	0.00	∞
Readout Electronics	E.2.6	0.26	N	1.00	0.00	0.00	0.00	0.00	∞
Response Time	E.2.7	0.17	R	1.73	0.00	0.00	0.00	0.00	∞
Integration Time	E.2.8	1.43	R	1.73	0.00	0.00	0.00	0.00	∞
RF ambient conditions-Noise	E.6.1	3.51	R	1.73	0.00	0.00	0.00	0.00	∞
RF ambient conditions-reflections	E.6.1	3.15	R	1.73	0.00	0.00	0.00	0.00	∞
Probe positioner mechanical tolerance	E.6.2	1.2	R	1.73	1.00	1.00	0.69	0.69	∞
Probe positioning with respect to phantom shell	E.6.3	1.4	R	1.73	1.00	1.00	0.81	0.81	∞
Extrapolation, interpolation, and integrations algorithms for max. SAR evaluation	E.5	3.9	R	1.73	0.00	0.00	0.00	0.00	∞
System check source (dipole)									
Deviation of experimental dipoles	E.6.4	4.8	N	1.00	1.00	1.00	4.80	4.80	∞
Input power and SAR drift measurement	8,6.6.4	5.1	R	1.73	1.00	1.00	2.94	2.94	∞
Dipole axis to liquid distance	8,E.6.6	2.4	R	1.73	1.00	1.00	1.39	1.39	∞
Phantom and tissue parameters									
Phantom shell uncertainty—shape, thickness, and permittivity	E.3.1	3.7	R	1.73	1.00	1.00	2.14	2.14	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	E.3.2	1.9	N	1.00	1.00	0.84	1.90	1.60	∞
Liquid conductivity measurement	E.3.3	2.4	R	1.73	0.78	0.71	1.08	0.98	∞
Liquid permittivity measurement	E.3.3	4.1	N	1.00	0.78	0.71	3.20	2.91	M
Liquid conductivity—temperature uncertainty	E.3.4	2.7	R	1.73	0.23	0.26	0.36	0.41	∞
Liquid permittivity—temperature uncertainty	E.3.4	4.8	N	1.00	0.23	0.26	1.10	1.25	M
Combined Standard Uncertainty			RSS				5.56	5.20	
Expanded Uncertainty (95% Confidence interval)			K=2				11.12	10.41	



9. Conducted Power Measurement

9.1 Test Result

NB-LoT

LTE Band 2 Maximum Average Power [dBm]					
BW [MHz]	RB Configure	Mod	Lowest	Middle	Highest
3.75	1#0	BPSK	23.51	23.70	23.68
3.75	1#47		23.48	23.62	23.63
15	1#0		23.42	23.06	23.01
15	1#11		23.40	23.03	23.56
3.75	1#0	QPSK	23.52	23.69	23.68
3.75	1#47		23.47	23.64	23.62
15	1#0		23.39	23.06	23.51
15	1#11		23.41	23.50	23.52
15	12#0		21.50	21.53	21.58

LTE Band 4 Maximum Average Power [dBm]					
BW [MHz]	RB Configure	Mod	Lowest	Middle	Highest
3.75	1#0	BPSK	23.23	23.33	23.37
3.75	1#47		23.18	23.30	23.30
15	1#0		23.31	23.26	23.54
15	1#11		23.33	23.31	23.47
3.75	1#0	QPSK	23.14	23.37	23.36
3.75	1#47		23.08	23.31	23.29
15	1#0		23.34	23.32	23.45
15	1#11		23.38	23.33	23.46
15	12#0		21.25	21.37	21.43



LTE Band 12 Maximum Average Power [dBm]					
BW [MHz]	RB Configure	Mod	Lowest	Middle	Highest
3.75	1#0	BPSK	23.51	23.70	23.68
3.75	1#47		23.48	23.62	23.63
15	1#0		22.58	23.85	22.63
15	1#11		23.59	23.77	22.64
3.75	1#0	QPSK	23.52	23.69	23.68
3.75	1#47		23.47	23.64	23.62
15	1#0		22.64	23.78	23.64
15	1#11		22.65	22.78	22.65
15	12#0		21.65	21.77	21.74

LTE-M

LTE Band 2

LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	22.26	23.41	21.86
1.4	6	0		21.71	21.65	22.86
1.4	1	0	16-QAM	22.37	22.46	21.78
1.4	5	0		21.53	21.55	22.3

LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
3	1	0	QPSK	23.59	23.45	23.71
3	6	0		21.7	21.58	21.86
3	1	0	16-QAM	22.35	22.4	22.96
3	5	0		21.52	21.61	21.78

LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.55	23.62	23.71
5	6	0		22.62	22.68	22.83
5	1	0	16-QAM	22.29	22.71	22.93
5	5	0		21.6	21.58	21.83



LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	23.52	23.66	23.65
10	6	0		23.71	23.64	23.65
10	1	0	16-QAM	22.3	22.71	22.99
10	5	0		22.6	22.61	22.79

LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	23.57	23.67	23.76
15	6	0		23.64	23.72	23.86
15	1	0	16-QAM	22.29	22.72	23.01
15	5	0		22.55	22.59	22.72

LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	23.59	23.73	23.73
20	6	0		23.64	23.78	23.88
20	1	0	16-QAM	22.34	22.79	23.06
20	5	0		22.47	22.63	22.81

LTE Band 4

LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	21.9	23.41	23.53
1.4	6	0		21.27	21.5	21.45
1.4	1	0	16-QAM	21.96	22.39	22.56
1.4	5	0		21.16	21.35	21.4

LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
3	1	0	QPSK	23.32	23.26	23.57
3	6	0		21.35	21.26	21.59
3	1	0	16-QAM	22.01	21.99	22.53
3	5	0		21.24	21.29	21.44



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.3	23.33	23.69
5	6	0		22.27	22.29	22.63
5	1	0	16-QAM	22.05	22.28	22.59
5	5	0		21.22	21.18	21.53

LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	23.29	23.46	23.67
10	6	0		23.53	23.46	23.58
10	1	0	16-QAM	22.07	22.36	22.58
10	5	0		22.37	22.24	22.59

LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	23.49	23.37	23.61
15	6	0		23.43	23.37	23.6
15	1	0	16-QAM	22.05	22.35	22.55
15	5	0		22.19	22.2	22.32

LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	23.34	23.47	23.73
20	6	0		23.28	23.47	23.63
20	1	0	16-QAM	22.08	22.34	22.58
20	5	0		22.2	22.2	22.47



LTE Band 12

LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	22.06	23.81	23.92
1.4	6	0		21.86	21.87	21.85
1.4	1	0	16-QAM	22.67	22.83	22.99
1.4	5	0		21.78	21.86	21.81

LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
3	1	0	QPSK	23.67	23.8	23.89
3	6	0		21.7	21.82	21.87
3	1	0	16-QAM	22.57	22.63	22.85
3	5	0		21.73	21.74	21.73


LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.74	23.87	23.98
5	6	0		22.74	22.85	22.91
5	1	0	16-QAM	23.17	23.47	23.46
5	5	0		21.69	21.71	21.89

LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	23.74	23.73	23.98
10	6	0		23.88	23.8	23.84
10	1	0	16-QAM	23.17	23.54	23.6
10	5	0		22.83	22.79	22.9

10. EUT and Test Setup Photo

10.1 EUT Photo

Front side




Back side






10.2 Setup Photo

Wrist side(separation distance is 0mm)




Front of face Side (separation distance is 5mm)





Liquid depth (15 cm)





11. SAR Result Summary

11.1 Front of face SAR

NB-LoT

Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Freq.	Result 1g (W/Kg)	Power Drift(%)	Max. Turn-up Power(dBm)	Meas. Output Power(dBm)	Scaling Factor	Scaled SAR (W/Kg)	Measurement No.
LTE Band 2	20M	QPSK	3.75	0	Front of face	1880	0.013	3.68	24	23.69	1.074	0.014	1
			15	0	Front of face	1900	0.010	0.36	24	23.52	1.117	0.011	/
LTE Band 4	20M	QPSK	3.75	0	Front of face	1732.5	0.107	3.76	23.5	23.37	1.030	0.110	3
			15	0	Front of face	1745	0.098	-0.52	23.5	23.46	1.009	0.099	/
LTE Band 12	10M	QPSK	3.75	0	Front of face	707.5	0.020	1.18	24	23.69	1.074	0.021	5
			15	0	Front of face	707.5	0.017	1.07	24	23.78	1.052	0.018	/

LTE-M

Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Freq.	Result 1g (W/Kg)	Power Drift(%)	Max. Turn-up Power(dBm)	Meas. Output Power(dBm)	Scaling Factor	Scaled SAR (W/Kg)	Measurement No.
LTE Band 2	20M	QPSK	1	0	Front of face	1900	0.026	2.86	24	23.88	1.028	0.027	7
LTE Band 4	20M	QPSK	1	0	Front of face	1745	0.044	-0.69	24	23.73	1.064	0.047	9
LTE Band 12	10M	QPSK	1	0	Front of face	711	0.012	-2.58	24	23.98	1.005	0.012	11

Note:

1. The test separation of all above table is 10mm.
2. Per KDB865664 D01, Repeated measurement is not required when the original highest measured SAR is <0.80 W/kg



11.2 Wrist SAR

NB-LoT

Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Freq.	Result 1g (W/Kg)	Power Drift(%)	Max. Turn-up Power(dBm)	Meas. Output Power(dBm)	Scaling Factor	Scaled SAR (W/Kg)	Measurements No.
LTE Band 2	20M	QPSK	3.75	0	Wrist	1880	0.037	-0.40	24	23.69	1.074	0.040	2
			15	0	Wrist	1900	0.031	2.24	24	23.52	1.117	0.035	/
LTE Band 4	20M	QPSK	3.75	0	Wrist	1732.5	0.104	-2.36	23.5	23.37	1.030	0.107	4
			15	0	Wrist	1745	0.097	2.87	23.5	23.46	1.009	0.098	/
LTE Band 12	10M	QPSK	3.75	0	Wrist	707.5	0.056	1.67	24	23.69	1.074	0.060	6
			15	0	Wrist	707.5	0.051	2.48	24	23.78	1.052	0.054	/

LTE-M

Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Freq.	Result 1g (W/Kg)	Power Drift(%)	Max. Turn-up Power(dBm)	Meas. Output Power(dBm)	Scaling Factor	Scaled SAR (W/Kg)	Measurements No.
LTE Band 2	20M	QPSK	1	0	Wrist	1900	0.025	0.30	24	23.88	1.028	0.026	8
LTE Band 4	20M	QPSK	1	0	Wrist	1745	0.079	2.45	24	23.73	1.064	0.084	10
LTE Band 12	10M	QPSK	1	0	Wrist	711	0.027	0.51	24	23.98	1.005	0.027	12

Note:

- The test separation of all above table is 0mm.
- Per KDB865664 D01, Repeated measurement is not required when the original highest measured SAR is <2.00 W/kg



12. Equipment List

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
750MHz Dipole	MVG	SID750	SN 30/14 DIP0G750-331	2023.07.04	2026.07.03
1800MHz Dipole	MVG	SID1800	5023-DIP1G800- 747	2023.12.20	2026.12.19
1900MHz Dipole	MVG	SID1900	SN 30/14 DIP1G900-333	2023.09.14	2026.09.13
E-Field Probe	MVG	SSE2	SN 08/21 EPGO352	2024.09.18	2025.09.17
Dielectric Probe Kit	MVG	SCLMP	SN 32/14 OCPG67	2024.09.18	2025.09.17
Antenna	MVG	ANTA3	SN 07/13 ZNTA52	N/A	N/A
Phantom1	MVG	SAM	SN 32/14 SAM115	N/A	N/A
Phantom3	MVG	SAM	SN 21/21 ELLI48	N/A	N/A
Phone holder	MVG	N/A	SN 32/14 MSH97	N/A	N/A
Laptop holder	MVG	N/A	SN 32/14 LSH29	N/A	N/A
Attenuator	Agilent	HXT-10-8-SMA	240327017	2025-02-22	2026-02-21
Directional coupler	Xi'an Xingbo	XBOH-OA08- 20dB	211123-4-3	2025-02-22	2026-02-21
Network Analyzer	Agilent	E5071C	MY46520378	2024-09-25	2025-09-26
Multi Meter	Keithley	Multi Meter 2000	4050073	2024-09-25	2025-09-26
Signal Generator	Agilent	N5182A	MY50140530	2024-09-25	2025-09-26
Wireless Communication Test Set	Agilent	8960-E5515C	MY48360751	2025-02-22	2026-02-21
Wireless Communication Test Set	R&S	CMW500	156324	2024-09-25	2025-09-26
Power Amplifier	DESAY	ZHL-42W	9638	2024-09-25	2025-09-26
Power Meter	R&S	NRP	100510	2024-09-25	2025-09-26
Power Sensor	R&S	NRP-Z11	101919	2024-09-25	2025-09-26
Power Sensor	Keysight	U2021XA	MY56280002	2024-09-25	2025-09-26
Temperature hygrometer	SuWei	SW-108	N/A	2024.10.15	2025.10.14
Thermograph	Elitech	RC-4	S/N EF7176501537	2024.10.15	2025.10.14



Appendix A. System Validation Plots

System Performance Check Data (750MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 29th May 2025

Experimental conditions.


Device Position	Validation plane
Band	750 MHz
Channels	-
Signal	CW
Frequency (MHz)	750
Relative permittivity	42.92
Conductivity (S/m)	0.90
Probe	SN 08/21 EPGO352
ConvF	1.56
Crest factor:	1:1



Maximum location: X=1.00, Y=0.00

SAR 10g (W/Kg)	0.579
SAR 1g (W/Kg)	0.853
Horizontal validation criteria: minimum distance (mm)	-1.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	71.836045

Z Axis Scan



**System Performance Check Data (1800MHz)**

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 29th May 2025


Experimental conditions.

Device Position	Validation plane
Band	1800 MHz
Channels	-
Signal	CW
Frequency (MHz)	1800
Relative permittivity	41.32
Conductivity (S/m)	1.40
Probe	SN 08/21 EPGO352
ConvF	1.58
Crest factor:	1:1

**Maximum location: X=1.00, Y=0.00**

SAR 10g (W/Kg)	1.829
SAR 1g (W/Kg)	3.973
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	59.940876

Z Axis Scan



**System Performance Check Data (1900MHz)**

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 30th May 2025


Experimental conditions.

Device Position	Validation plane
Band	1900 MHz
Channels	-
Signal	CW
Frequency (MHz)	1900
Relative permittivity	40.66
Conductivity (S/m)	1.38
Probe	SN 08/21 EPGO352
ConvF	1.72
Crest factor:	1:1

**Maximum location: X=1.00, Y=0.00**

SAR 10g (W/Kg)	2.181
SAR 1g (W/Kg)	4.160
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	60.076304

Z Axis Scan






Appendix B. SAR Test Plots

Plot 1: DUT: Vital Sign Monitor Watch; EUT Model: E2

Test Date	30th May 2025
ConF	1.72
Probe	SN 08/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm
Phantom	Validation plane
Device Position	Front of face
Band	LTE Band 2
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	1880
Relative permittivity (real part)	40.52
Conductivity (S/m)	1.44




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.007
SAR 1g (W/Kg)	0.013
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	68.996579

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.019	0.015	0.010	0.006	0.004	0.002	0.001




F. 3D Image



**Plot 2: DUT: Vital Sign Monitor Watch; EUT Model: E2**


Test Date	30th May 2025
ConF	1.72
Probe	SN 08/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm
Phantom	Validation plane
Device Position	Wrist
Band	LTE Band 2
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	1880
Relative permittivity (real part)	40.52
Conductivity (S/m)	1.44

**D. SAR 1g & 10g**


SAR 10g (W/Kg)	0.037
SAR 1g (W/Kg)	0.079
Horizontal validation criteria: minimum distance (mm)	8.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	56.782332

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.141	0.091	0.052	0.030	0.017	0.010	0.006




F. 3D Image



**Plot 3: DUT: Vital Sign Monitor Watch; EUT Model: E2**

Test Date	29th May 2025
ConF	1.58
Probe	SN 08/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm
Phantom	Validation plane
Device Position	Front of face
Band	LTE Band 4
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	1732.5
Relative permittivity (real part)	41.28
Conductivity (S/m)	1.41




Maximum location: X=-24.00, Y=-8.00 ; SAR Peak: 0.20 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.049
SAR 1g (W/Kg)	0.107
Horizontal validation criteria: minimum distance (mm)	11.313708
Vertical validation criteria: SAR ratio M2/M1 (%)	47.481405

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.206	0.119	0.056	0.030	0.016	0.008	0.004




F. 3D Image



**Plot 4: DUT: Vital Sign Monitor Watch; EUT Model: E2**


Test Date	29th May 2025
ConF	1.58
Probe	SN 08/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm
Phantom	Validation plane
Device Position	Wrist
Band	LTE Band 4
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	1732.5
Relative permittivity (real part)	41.28
Conductivity (S/m)	1.41

**D. SAR 1g & 10g**


SAR 10g (W/Kg)	0.104
SAR 1g (W/Kg)	0.233
Horizontal validation criteria: minimum distance (mm)	11.313708
Vertical validation criteria: SAR ratio M2/M1 (%)	49.286848

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.465	0.255	0.126	0.110	0.075	0.052	0.036




F. 3D Image



**Plot 5: DUT: Vital Sign Monitor Watch; EUT Model: E2**

Test Date	29th May 2025
ConF	1.56
Probe	SN 08/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm
Phantom	Validation plane
Device Position	Front of face
Band	LTE Band 12
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	707.5
Relative permittivity (real part)	42.13
Conductivity (S/m)	0.93




Maximum location: X=-6.00, Y=1.00 ; SAR Peak: 0.03 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.012
SAR 1g (W/Kg)	0.020
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	60.590172

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.033	0.021	0.012	0.009	0.006	0.004	0.003




F. 3D Image



**Plot 6: DUT: Vital Sign Monitor Watch; EUT Model: E2**

Test Date	29th May 2025
ConF	1.56
Probe	SN 08/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm
Phantom	Validation plane
Device Position	Wrist
Band	LTE Band 12
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	707.5
Relative permittivity (real part)	42.13
Conductivity (S/m)	0.93




Maximum location: X=15.00, Y=-18.00 ; SAR Peak: 0.10 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.025
SAR 1g (W/Kg)	0.056
Horizontal validation criteria: minimum distance (mm)	8.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	61.697974

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.087	0.061	0.038	0.020	0.012	0.007	0.004




F. 3D Image



**Plot 7: DUT: Vital Sign Monitor Watch; EUT Model: E2**

Test Date	30th May 2025
ConF	1.72
Probe	SN 08/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm
Phantom	Validation plane
Device Position	Front of face
Band	LTE Band 2
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	1900
Relative permittivity (real part)	40.66
Conductivity (S/m)	1.38




Maximum location: X=-30.00, Y=-16.00 ; SAR Peak: 0.07 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.011
SAR 1g (W/Kg)	0.026
Horizontal validation criteria: minimum distance (mm)	8.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	64.418224

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.056	0.027	0.008	0.012	0.009	0.006	0.009




F. 3D Image



**Plot 8: DUT: Vital Sign Monitor Watch; EUT Model: E2**

Test Date	30th May 2025
ConF	1.72
Probe	SN 08/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm
Phantom	Validation plane
Device Position	Wrist
Band	LTE Band 2
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	1900
Relative permittivity (real part)	40.66
Conductivity (S/m)	1.38




Maximum location: X=15.00, Y=-18.00 ; SAR Peak: 0.10 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.025
SAR 1g (W/Kg)	0.056
Horizontal validation criteria: minimum distance (mm)	8.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	61.697974

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.087	0.061	0.038	0.020	0.012	0.007	0.004




F. 3D Image



**Plot 9: DUT: Vital Sign Monitor Watch; EUT Model: E2**

Test Date	29th May 2025
ConF	1.58
Probe	SN 08/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm
Phantom	Validation plane
Device Position	Front of face
Band	LTE Band 4
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	1745
Relative permittivity (real part)	40.79
Conductivity (S/m)	1.35




Maximum location: X=-29.00, Y=-14.00 ; SAR Peak: 0.18 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.044
SAR 1g (W/Kg)	0.089
Horizontal validation criteria: minimum distance (mm)	11.313708
Vertical validation criteria: SAR ratio M2/M1 (%)	65.431471

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.167	0.095	0.046	0.034	0.019	0.013	0.008




F. 3D Image



**Plot 10: DUT: Vital Sign Monitor Watch; EUT Model: E2**


Test Date	29th May 2025
ConF	1.58
Probe	SN 08/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm
Phantom	Validation plane
Device Position	Wrist
Band	LTE Band 4
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	1745
Relative permittivity (real part)	40.79
Conductivity (S/m)	1.35

**D. SAR 1g & 10g**


SAR 10g (W/Kg)	0.079
SAR 1g (W/Kg)	0.169
Horizontal validation criteria: minimum distance (mm)	11.313708
Vertical validation criteria: SAR ratio M2/M1 (%)	61.448104

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.259	0.186	0.114	0.056	0.030	0.016	0.009




F. 3D Image



**Plot 11: DUT: Vital Sign Monitor Watch; EUT Model: E2**

Test Date	29th May 2025
ConF	1.56
Probe	SN 08/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm
Phantom	Validation plane
Device Position	Front of face
Band	LTE Band 12
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	711
Relative permittivity (real part)	42.52
Conductivity (S/m)	0.88




Maximum location: X=-6.00, Y=1.00 ; SAR Peak: 0.03 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.012
SAR 1g (W/Kg)	0.020
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	60.590172

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.033	0.021	0.012	0.009	0.006	0.004	0.003




F. 3D Image



**Plot 12: DUT: Vital Sign Monitor Watch; EUT Model: E2**

Test Date	29th May 2025
ConF	1.56
Probe	SN 08/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm
Phantom	Validation plane
Device Position	Wrist
Band	LTE Band 12
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	711
Relative permittivity (real part)	42.52
Conductivity (S/m)	0.88




Maximum location: X=2.00, Y=-5.00 ; SAR Peak: 0.12 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.027
SAR 1g (W/Kg)	0.059
Horizontal validation criteria: minimum distance (mm)	11.313708
Vertical validation criteria: SAR ratio M2/M1 (%)	46.765178

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.121	0.065	0.028	0.020	0.011	0.006	0.004



F. 3D Image





Appendix C. Probe Calibration and Dipole Calibration Report

Refer the appendix Calibration Report.

※※※※※END OF THE REPORT※※※※※