



TEST REPORT

Reference No...... : WTZ21F12134165E
FCC ID : 2A4SG-AIRCUBE
Applicant..... : Guangdong Cinotex Environmental Sci-Tech Co., Ltd.
Address..... : First Card, 5th Floor, No.122, Yulong 3rd Road, Dongsheng Town,
Zhongshan City, Guangdong Province, China
Manufacturer : The same as above
Address..... : The same as above
Product Name..... : K BOX Air Monitor
Model No...... : 433
Standards..... : FCC CFR47 Part 15 Subpart C (Section 15.231):2020
Date of Receipt sample : 2022-02-09
Date of Test : 2022-02-13
Date of Issue..... : 2022-02-24
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Testing Group (Foshan) Co., Ltd.

Address: No.13-19, 2/F., 2nd Building, Sunlink International Machinery City,
Chencun, Shunde District, Foshan, Guangdong, China

Tel:+86-757-23811398

Fax:+86-757-23811381

E-mail:info@waltek.com.cn

Compiled by:

Roy Hong / Project Engineer

Approved by:

Danny Zhou / Manager



1 Revision History

Test Report No.	Date of Issue	Description	Status
WTZ21F12134165E	2022-02-24	Original	Valid

WALTEK



2 Contents

	Page
1 REVISION HISTORY.....	2
2 CONTENTS.....	3
3 GENERAL INFORMATION.....	4
3.1 GENERAL DESCRIPTION OF E.U.T	4
3.2 TECHNICAL CHARACTERISTICS OF EUT	4
3.3 STANDARDS APPLICABLE FOR TESTING.....	4
3.4 TEST FACILITY	5
3.5 SUBCONTRACTED	5
3.6 ABNORMALITIES FROM STANDARD CONDITIONS.....	5
4 EUT SETUP AND TEST MODE.....	6
5 EQUIPMENT USED DURING TEST.....	7
5.1 EQUIPMENT LIST.....	7
5.2 SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	8
5.3 MEASUREMENT UNCERTAINTY.....	8
6 SUMMARY OF TEST RESULT	9
6.1 ANTENNA REQUIREMENT.....	10
6.2 RADIATED SPURIOUS EMISSIONS	11
6.3 20dB BANDWIDTH.....	15
6.4 TRANSMISSION TIME	16
6.5 DUTY CYCLE.....	17
6.6 CONDUCTED EMISSIONS.....	19
7 PHOTOGRAPHS TEST SETUP.....	23
7.1 PHOTOGRAPHS - RADIATED EMISSION TEST SETUP.....	23
7.2 PHOTOGRAPHS - CONDUCTED EMISSION TEST SETUP	24
8 PHOTOGRAPHS - CONSTRUCTIONAL DETAILS.....	25
8.1 EUT - EXTERNAL PHOTOS.....	25
8.2 EUT - INTERNAL PHOTOS.....	28



3 General Information

3.1 General Description of E.U.T

Product Name : K BOX Air Monitor

Model No. : 433

Model Description : ---

Rated Voltage..... : USB input: DC 5V

Battery Capacity : ---

Power Adapter : ---

3.2 Technical Characteristics of EUT

Operational Frequency Band : 433.05MHz-434.79MHz

Operating Frequency : 433.97MHz

Max. Field Strength : 73.26 dBuV/m (at 3m distance)

Modulation : ASK

Type of Antenna : Spring Antenna

Antenna Gain : 0dBi

Lowest oscillator : 433MHz

3.3 Standards Applicable for Testing

The tests were performed according to following standards:

FCC Rules Part 15.231 Periodic operation in the band 40.66–40.70 MHz and above 70 MHz.

558074 D01 15.247 Meas Guidance For Compliance Measurements On Digital Transmission System,
Guidance v05r02 Frequency Hopping Spread Spectrum System, And Hybrid System Devices
Operating Under Section 15.247 Of The FCC Rules

ANSI C63.10-2013 American National Standard for Testing Unlicensed Wireless Devices



3.4 Test Facility

The test facility has a test site registered with the following organizations:

● **IC – Registration No.: 21895-1**

Waltek Testing Group (Foshan) Co., Ltd. has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files. Registration IC number: 21895-1, Nov. 14, 2016.

● **FCC – Registration No.: 820106**

Waltek Testing Group (Foshan) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 820106, August 16, 2018

● **FCC – Designation No.: CN5034**

Waltek Testing Group (Foshan) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation No. CN5034.

● **NVLAP – Lab Code: 600191-0**

Waltek Testing Group (Foshan) Co., Ltd. EMC Laboratory is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 600191-0.

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

3.5 Subcontracted

Whether parts of tests for the product have been subcontracted to other labs:

☐ Yes ☒ No

If Yes, list the related test items and lab information:

Test items: ---

Lab information: ---

3.6 Abnormalities from Standard Conditions

None.



4 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List

Test Mode	Description	Remark
TM1	Transmitting	With modulation(433.97MHz)

Test Conditions

Temperature:	22~25°C
Relative Humidity:	50~55%
Atmospheric pressure:	101.9kPa

WALTEK



5 Equipment Used during Test

5.1 Equipment List

3m Semi-anechoic Chamber for Radiation Emissions						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMI Test Receiver	RS	ESR7	101566	2022-01-07	2023-01-06
2.	EMC Analyzer	Agilent	N9020A	MY48011796	2021-06-04	2022-06-03
3.	Active Loop Antenna	SCHWARZBECK	FMZB1519B	00004	2022-01-09	2023-01-08
4.	Trilog Broadband Antenna	SCHWARZBECK	VULB 9162	9162-117	2022-01-07	2023-01-06
5.	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	01561	2022-01-09	2023-01-08
6.	Amplifier	Lunar E M	LNA1G18-40	20160501002	2022-01-06	2023-01-05
7.	Coaxial Cable (below 1GHz)	H+S	CBL3-NN-12+3 m	214NN320	2022-01-06	2023-01-05
8.	Coaxial Cable (above 1GHz)	Times-Microwave	CBL5-NN	-	2022-01-07	2023-01-06
9.	Test Software	FARATRONIC	EZ-EMC RA-03A1-1	-	-	-
RF Conducted Testing						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	Spectrum Analyzer	Agilent	N9020A	MY48011796	2022-01-08	2023-01-07
2.	Spectrum Analyzer	R&S	FSP40	100501	2021-06-04	2022-06-03
3.	Analog Signal Generator	Agilent	N5181A	MY48180720	2022-01-06	2023-01-05
4.	Environmental Chamber	KSON	THS-D4C-100	5244K	2022-01-06	2023-01-05
5.	RF Control Unit	CHANGCHUANG	JS0806-2	-	2021-07-09	2022-07-08



5.2 Special Accessories and Auxiliary Equipment

Item	Equipment	Rating	Manufacturer	Model No.
1.	Adapter	Input: AC 100-240V~, 50/60Hz, 0.5A Output: DC 5V, 2A or DC 9V, 2A	HUAWEI	HW-090200CH0

5.3 Measurement Uncertainty

Parameter	Uncertainty
RF Output Power	$\pm 0.95\text{dB}$
Occupied Bandwidth	$\pm 1.5\%$
Conducted Spurious Emission	$\pm 2.7\text{dB}$
Conducted Emission	$\pm 2.7\text{dB}$
Transmitter Spurious Emission	$\pm 3.8\text{dB}$ (for 25MHz-1GHz)
	$\pm 5.0\text{dB}$ (for 1GHz-18GHz)

WALTEK



6 Summary of Test Result

Test Items	FCC Rules	Result
Antenna Requirement	§15.203	Compliant
Restricted Band of Operation	§15.205	Compliant
Conducted Emissions	§15.207(a)	Compliant
Radiated Spurious Emissions	§15.209	Compliant
Deactivation Testing	§15.231(a)	Compliant
Radiated Emissions	§15.231(b)	Compliant
20dB Bandwidth Testing	§15.231(c)	Compliant

Remark:

Pass	Test item meets the requirement
Fail	Test item does not meet the requirement
N/A	Test case does not apply to the test object

WALTEK




6.1 Antenna Requirement

6.1.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

6.1.2 Evaluation Information

The EUT has a Spring Antenna, the gain is 0 dBi, fulfil the requirement of this section.





6.2 Radiated Spurious Emissions

6.2.1 Standard Applicable

According to §15.231(b), the field strength of emissions from intentional radiators operated under this section shall not exceed the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental (microvolts/meter)	Field Strength of Spurious Emissions (microvolts/meter)
40.66 - 40.70	2,250	225
70 - 130	1,250	125
130 - 174	1,250 to 3,750 **	125 to 375 **
174 - 260	3,750	375
260 - 470	3,750 to 12,500 **	375 to 1,250 **
Above 470	12,500	1,250

** linear interpolations

The limits on the field strength of the spurious emissions in the above table are based on the fundamental frequency of the intentional radiator. Spurious emissions shall be attenuated to the average (or, alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in §15.209, whichever limit permits a higher field strength.



The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

Compliance with the provisions of §15.205 shall be demonstrated using the measurement instrumentation specified in that section.



6.2.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.231(b) and FCC Part 15.209 Limit.





6.2.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Loss} + \text{Cab. Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB V means the emission is 6dB V below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15C Limit}$$

6.2.4 Test Results

Test Frequency : 30MHz ~ 5GHz

Lower channel: 433.97MHz

Frequency (MHz)	Receiver Reading (PK) (dBμV)	Turn table Angle Degree	RX Antenna		Corrected Factor (dB/m)	Corrected Amplitude (PK) (dBμV/m)	FCC Part 15.231/15.209/205	
			Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
433.97	60.68	105	1.8	H	18.93	79.61	100.82	-21.21
433.97	68.71	198	1.4	V	18.93	87.64	100.82	-13.18
868.22	31.05	292	1.4	H	26.13	57.18	80.82	-23.64
868.22	31.06	204	1.3	V	26.13	57.19	80.82	-23.63
4688.50	8.22	136	1.9	H	38.48	46.70	74	-27.30
4688.50	8.95	319	1.0	V	38.48	47.43	74	-26.57
5904.00	11.98	167	1.9	H	40.95	52.93	74	-21.07
5904.00	11.66	232	1.4	V	40.95	52.61	74	-21.39



AV = Peak +20Log₁₀(duty cycle) =PK+(-14.38) [refer to section 6.5 for more detail]

Frequency (MHz)	PK (dBμV/m)	RX Antenna Polar (H/V)	Duty cycle Factor (dB)	Calculated AV (dBμV/m)	FCC Part 15.231/209/205	
					Limit (dBμV/m)	Margin (dB)
433.97	79.61	H	-14.38	65.23	80.82	-15.59
433.97	87.64	V	-14.38	73.26	80.82	-7.56
868.22	57.18	H	-14.38	42.80	60.82	-18.02
868.22	57.19	V	-14.38	42.81	60.82	-18.01
4688.50	46.70	H	-14.38	32.32	54	-21.68
4688.50	47.43	V	-14.38	33.05	54	-20.95
5904.00	52.93	H	-14.38	38.55	54	-15.45
5904.00	52.61	V	-14.38	38.23	54	-15.77

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 6th Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured. The fundamental frequency is 433.97MHz, so the fundamental and spurious emissions radiated limit base on the the operating frequency 433.97MHz.

WALTEK



6.3 20dB Bandwidth

6.3.1 Standard Applicable

According to FCC Part 15.231(c), The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. Bandwidth is determined at the points 20 dB down from the modulated carrier.

6.3.2 Test Procedure

With the EUT's antenna attached, the EUT's 20dB Bandwidth power was received by the test antenna, which was connected to the spectrum analyzer with the START, and STOP frequencies set to the EUT's operation band.


6.3.3 Test Result

Test Frequency (MHz)	20dB Bandwidth (kHz)	Limit (kHz)	Result
433.97	2.008	1084.8	Pass

Limit = Fundamental Frequency x 0.25% = 433.9748 MHz x 0.25% = 1085 kHz

Test Plots:

20dB Bandwidth Test Plot





6.4 Transmission Time

6.4.1 Standard Applicable


According to FCC Part 15.231 (a), the transmitter shall be complied the following requirements:

- 1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.
- (2) A transmitter activated automatically shall cease transmission within 5 seconds after activation.
- (3) Periodic transmissions at regular predetermined intervals are not permitted. However, polling or supervision transmissions, including data, to determine system integrity of transmitters used in security or safety applications are allowed if the total duration of transmissions does not exceed more than two seconds per hour for each transmitter. There is no limit on the number of individual transmissions, provided the total transmission time does not exceed two seconds per hour.

6.4.2 Test Procedure

With the EUT's antenna attached, the EUT's output signal was received by the test antenna, which was connected to the spectrum analyzer. Set the center frequency to 433.9748MHz, than set the spectrum analyzer to Zero Span for the release time reading. During the testing, the switch was released then the EUT automatically deactivated.

6.4.3 Test Result





6.5 Duty Cycle

6.5.1 Standard Applicable

According to FCC Part 15.231 (b)(2) and 15.35 (c), For pulse operation transmitter, the averaging pulsed emissions are calculated by peak value of measured emission plus duty cycle factor.

6.5.2 Test Procedure


With the EUT's antenna attached, the EUT's output signal was received by the test antenna, which was connected to the spectrum analyzer. Set the center frequency to 433.97MHz, than set the spectrum analyzer to Zero Span for the release time reading. During the testing, the switch was released then the EUT automatically deactivated.


6.5.3 Test Result

Total transmission time(ms)	1.9*4+3.9+7.6=19.1
Length of a complete transmission period(ms)	100
Duty Cycle(%)	19.10%
Duty Cycle Correction Factor(dB)	-14.38

Remark: Duty Cycle Factor= $20 \times \log(\text{Duty Cycle})$

Test Plots:





WALTEK




6.6 Conducted Emissions

6.6.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

6.6.2 Basic Test Setup Block Diagram



6.6.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency.....150 kHz
Stop Frequency.....30 MHz
Sweep Speed.....Auto
IF Bandwidth.....10 kHz
Quasi-Peak Adapter Bandwidth.....9 kHz
Quasi-Peak Adapter Mode.....Normal



6.6.4 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

6.6.5 Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF(Voltage Division Facotr), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Measurement} = \text{Reading Level} + \text{Correct Factor}$$

$$\text{Correct Facotor} = \text{LISN VDF} + \text{Cable Loss}$$

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:


$$\text{Margin} = \text{Limit} - \text{Measurement}$$

WALTEK



6.6.6 Test Result


Test Mode Communication mode
(AC 120V/60Hz with adapter) **Polarity** **Line**



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1539	36.57	9.62	46.19	65.79	-19.60	QP	
2		0.1539	16.25	9.62	25.87	55.79	-29.92	AVG	
3	*	0.2340	33.53	9.64	43.17	62.31	-19.14	QP	
4		0.2340	14.49	9.64	24.13	52.31	-28.18	AVG	
5		0.3180	29.03	9.64	38.67	59.76	-21.09	QP	
6		0.3180	13.57	9.64	23.21	49.76	-26.55	AVG	
7		0.4780	26.67	9.66	36.33	56.37	-20.04	QP	
8		0.4780	14.58	9.66	24.24	46.37	-22.13	AVG	
9		3.9700	20.21	9.79	30.00	56.00	-26.00	QP	
10		3.9700	10.05	9.79	19.84	46.00	-26.16	AVG	
11		12.1899	12.55	10.08	22.63	60.00	-37.37	QP	
12		12.1899	2.80	10.08	12.88	50.00	-37.12	AVG	

**Test Mode**Communication mode
(AC 120V/60Hz with adapter)**Polarity**

Neutral




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1580	36.62	9.61	46.23	65.57	-19.34	QP	
2		0.1580	17.57	9.61	27.18	55.57	-28.39	AVG	
3		0.2300	30.90	9.63	40.53	62.45	-21.92	QP	
4		0.2300	12.73	9.63	22.36	52.45	-30.09	AVG	
5	*	0.3140	30.95	9.64	40.59	59.86	-19.27	QP	
6		0.3140	16.60	9.64	26.24	49.86	-23.62	AVG	
7		0.4660	27.32	9.66	36.98	56.58	-19.60	QP	
8		0.4660	15.52	9.66	25.18	46.58	-21.40	AVG	
9		4.0020	23.30	9.80	33.10	56.00	-22.90	QP	
10		4.0020	12.56	9.80	22.36	46.00	-23.64	AVG	
11		12.2060	15.06	10.11	25.17	60.00	-34.83	QP	
12		12.2060	3.93	10.11	14.04	50.00	-35.96	AVG	



7 Photographs Test Setup

7.1 Photographs - Radiated Emission Test Setup

30MHz-1GHz



Above 1GHz





7.2 Photographs - Conducted Emission Test Setup





WALTEK





8 Photographs - Constructional Details

8.1 EUT - External Photos

















8.2 EUT - Internal Photos

















=====End of Report=====

WALTEK