

FCC ID: 2A5HP-Z185C

RF exposure evaluation

§ 2.1093 Radiofrequency radiation exposure evaluation: Portable Devices.

According to § 15.247(i) and § 1.1307b(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the commission's guidance.

The 1-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

- $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR, where
- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
 - Power and distance are rounded to the nearest mW and mm before calculation
 - When the minimum test separation distance is $<$ 5 mm, a distance of 5 mm according is applied to determine SAR test exclusion.
 - The result is rounded to one decimal place for comparison

Modulation	Frequency (MHz)	Conducted Power (dBm)	Tune-up Power (dBm)	Tune-up Power (mW)	Test Distance (mm)	Result	Exclusion Thresholds for 1-g SAR
8DPSK	2402	2.09	2.5	1.78	5	0.56	3.0
GFSK(2Mbps)	2402	3.73	4.0	2.51	5	0.79	3.0