

# 60mm

Specification	
MODEL I Shutter	
Communication	Version 3.0
Transmit frequency	2.4GHz-2.4835GHz
Communication distance	10m(30ft)
Battery life	CR 2032X1 cell/about 6 months under working in 10 times a day
Dimension	60mmx36mmx11mm
Weight	About 11.7g

## Battery



Positive pole upwards to install the battery.

# 60mm

## How To Use

### Easy to set up, Easy to use



1. Pairing
  - a. Turn on the shutter by switching the on/off button, the shutter will enter into pairing mode and indicator LED starts flash quickly at the same time
  - b. Activate the Wireless function on your phone and sourcing the devices around
  - c. Select the device of "AB Shutter3" from the list and pairing will be finished automatically in few seconds

# 43mm

## 2. Shooting

Select a correct APP and press the proper button on the shutter for IOS and Android id phones to taking the photos.

## Compatible devices

Compatible with Android 4.2.2 OS or newer and iOS 6.0 or newer

changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) This device must accept any interference received, including interference that may cause undesired operation.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy, and if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

## Owner's Manual

### Remote Shutter

#### Product illustration

