

# TEST REPORT

Report No.: BCTC2507158912-2E

---

Applicant: Shenzhen Telesin Digital Co.,Ltd.

---

Product Name: Magnetic selfie monitor screen

---

Test Model: TPRMT07-01

---

Tested Date: 2025-07-16 to 2025-09-15

---

Issued Date: 2025-09-15

---


**Shenzhen BCTC Testing Co., Ltd.**



# FCC ID: 2A6I2-P5RMT07

Product Name: Magnetic selfie monitor screen  
Trademark: TELESIN  
Model/Type reference: TPRMT07-01  
TPRMT07-02, TPRMT07-03, TPRMT07-04, TPRMT07-05, TPRMT07-06  
Prepared For: Shenzhen Telesin Digital Co.,Ltd.  
Address: Room 522, 5/F, Block B, Bairuida Building, Vanke City Community, Bantian Street, Longgang District, Shenzhen, Guangdong, China. 518000  
Manufacturer: Shenzhen Telesin Digital Co.,Ltd.  
Address: Room 522, 5/F, Block B, Bairuida Building, Vanke City Community, Bantian Street, Longgang District, Shenzhen, Guangdong, China. 518000  
Prepared By: Shenzhen BCTC Testing Co., Ltd.  
Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China  
Sample Received Date: 2025-07-16  
Sample tested Date: 2025-07-16 to 2025-09-15  
Issue Date: 2025-09-15  
Report No.: BCTC2507158912-2E  
Test Standards: FCC Part15 15.407  
ANSI C63.10:2020  
KDB 789033 D02 v02r01  
Test Results: PASS

Tested by:



Brave Zeng/ Project Handler

Approved by:



Zero Zhou/Reviewer


The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen BCTC Testing Co., Ltd, this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client.

## Table Of Content

	Page
Test Report Declaration	
1. Version .....	5
2. Test Summary .....	6
3. Measurement Uncertainty .....	7
4. Product Information And Test Setup .....	8
4.1 Product Information.....	8
4.2 Test Setup Configuration .....	8
4.3 Support Equipment .....	8
4.4 Channel List.....	9
4.5 Test Mode .....	9
5. Test Facility And Test Instrument Used.....	10
5.1 Test Facility.....	10
5.2 Test Instrument Used.....	10
6. Conducted Emissions.....	12
6.1 Block Diagram Of Test Setup.....	12
6.2 Limit .....	12
6.3 Test Procedure .....	12
6.4 EUT Operating Conditions .....	12
6.5 Test Result.....	13
7. Radiated Emissions.....	15
7.1 Block Diagram Of Test Setup.....	15
7.2 Limit .....	16
7.3 Test Procedure .....	17
7.4 EUT Operating Conditions .....	18
7.5 Test Result.....	18
8. Power Spectral Density Test .....	24
8.1 Block Diagram Of Test Setup.....	24
8.2 Limit .....	24
8.3 Test Procedure .....	25
8.4 EUT Operating Conditions .....	25
8.5 Test Result.....	26
9. 26dB & 6dB & 99% Emission Bandwidth .....	31
9.1 Block Diagram Of Test Setup.....	31
9.2 Limit .....	31
9.3 Test Procedure .....	31
9.4 EUT Operating Conditions .....	32
9.5 Test Result.....	32
10. Maximum Conducted Output Power.....	41
10.1 Block Diagram Of Test Setup.....	41
10.2 Limit .....	41
10.3 Test Procedure .....	41
10.4 EUT Operating Conditions .....	42
10.5 Test Result.....	42
11. Out Of Band Emissions .....	43


11.1	Block Diagram Of Test Setup.....	43
11.2	Limit .....	43
11.3	Test Procedure .....	43
11.4	EUT Operating Conditions .....	43
11.5	Test Result.....	44
12.	Spurious RF Conducted Emissions.....	47
12.1	Block Diagram Of Test Setup.....	47
12.2	Limit .....	47
12.3	Test Procedure .....	47
12.4	Test Result.....	47
13.	Frequency Stability Measurement .....	52
13.1	Block Diagram Of Test Setup.....	52
13.2	Limit .....	52
13.3	Test Procedure .....	52
13.4	Test Result.....	53
14.	Duty Cycle Of Test Signal .....	56
14.1	Standard Requirement .....	56
14.2	Formula.....	56
14.3	Test Procedure .....	56
14.4	Test Result.....	56
15.	Antenna Requirement .....	59
15.1	Limit .....	59
15.2	Test Result.....	59
16.	EUT Photographs.....	60
17.	EUT Test Setup Photographs.....	61

(Note: N/A Means Not Applicable)



**1. Version**


<b>Report No.</b>	<b>Issue Date</b>	<b>Description</b>	<b>Approved</b>
BCTC2507158912-2E	2025-09-15	Original	Valid



## 2. Test Summary

The Product has been tested according to the following specifications:


No.	Test Parameter	Clause No.	Results
1	Spurious Radiated Emissions	15.209(a), 15.407 (b)(1) 15.407 (b)(4) 15.407 (b)(8)	PASS
2	Conducted Emission	15.207	PASS
3	26 dB and 99% Emission Bandwidth	15.407 (a)(12) 15.1049	PASS
4	Minimum 6 dB bandwidth	15.407(e)	PASS
5	Maximum Conducted Output Power	15.407 (a)(1) 15.407 (a)(3)	PASS
6	Band Edge	2.1051, 15.407(b)(1) 15.407(b)(4)	PASS
7	Power Spectral Density	15.407 (a)(1) 15.407 (a)(3)	PASS
8	Spurious Emissions at Antenna Terminals	2.1051, 15.407(b)	PASS
9	Antenna Requirement	15.203	PASS



### 3. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

No.	Item	Uncertainty
1	3m chamber Radiated spurious emission(9kHz-30MHz)	U=3.7dB
2	3m chamber Radiated spurious emission(30MHz-1GHz)	U=4.3dB
3	3m chamber Radiated spurious emission(1GHz-18GHz)	U=4.5dB
4	3m chamber Radiated spurious emission(18GHz-40GHz)	U=3.34dB
5	Conducted Emission(150kHz-30MHz)	U=3.20dB
6	Conducted Adjacent channel power	U=1.38dB
7	Conducted output power uncertainty Above 1G	U=1.576dB
8	Conducted output power uncertainty below 1G	U=1.28dB
9	humidity uncertainty	U=5.3%
10	Temperature uncertainty	U=0.59°C



## 4. Product Information And Test Setup

### 4.1 Product Information

Model/Type reference:	TPRMT07-01 TPRMT07-02, TPRMT07-03, TPRMT07-04, TPRMT07-05, TPRMT07-06
Model differences:	All the model are the same circuit and RF module, except model names.
Hardware Version:	N/A
Software Version:	N/A
IEEE 802.11 WLAN Mode Supported:	802.11a/n(20MHz channel bandwidth) 802.11n(40MHz channel bandwidth)
Operation Frequency:	5745-5825 MHz for 802.11a/n (HT20); 5755-5795 MHz for 802.11n (HT40);
Data Rate:	802.11a: 6,9,12,18,24,36,48,54Mbps; 802.11n(HT20/HT40):MCS0-MCS15;
Type of Modulation:	OFDM with BPSK/QPSK/16QAM/64QAM/256QAM for 802.11a/n;
Number Of Channel:	5 channels for 802.11a/n20 in the 5745-5825MHz band ; 2 channels for 802.11 n40 in the 5755-5795MHz band ;
Antenna installation:	Internal antenna 4.69 dBi
Antenna Gain:	Remark: <input checked="" type="checkbox"/> The antenna gain of the product comes from the antenna report provided by the customer, and the test data is affected by the customer information. <input type="checkbox"/> The antenna gain of the product is provided by the customer, and the test data is affected by the customer information.
Ratings:	DC 5V from adapter/ DC 3.7V from battery

### 4.2 Test Setup Configuration

See test photographs attached in *EUT TEST SETUP PHOTOGRAPHS* for the actual connections between Product and support equipment.

### 4.3 Support Equipment

No.	Device Type	Brand	Model	Series No.	Note
E-1	Magnetic selfie monitor screen	TELESIN	TPRMT07-01	N/A	EUT
E-2	ADAPTER	UGREEN	CD122	N/A	Auxiliary

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	0M	DC cable unshielded

**Notes:**

- All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

#### 4.4 Channel List

Frequency and Channel list for 802.11a/n (5745-5825MHz):

802.11a/n ( 20 MHz) Carrier Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	153	5765	157	5785	161	5805
165	5825	-	-	-	-	-	-

802.11n 40MHz Carrier Frequency Channel					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
151	5755	159	5795	-	-

#### 4.5 Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	802.11a /n20 CH149/ CH157/ CH165
Mode 2	802.11n40 CH151 / CH159
Mode 3	WIFI Link Mode


Note:

1. The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.

#### 4.6 Table Of Parameters Of Text Software Setting

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters

Test software Version	CMD		
Parameters	DEF	DEF	DEF



## 5. Test Facility And Test Instrument Used

### 5.1 Test Facility

All measurement facilities used to collect the measurement data are located at Shenzhen BCTC Testing Co., Ltd. Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.

FCC Test Firm Registration Number: 712850

A2LA certificate registration number is: CN1212

ISED Registered No.: 23583


ISED CAB identifier: CN0017

### 5.2 Test Instrument Used

Conducted Emissions Test					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Receiver	R&S	ESR3	102075	May 08, 2025	May 07, 2026
LISN	R&S	ENV216	101375	May 14, 2025	May 13, 2026
Software	Frad	EZ-EMC	EMC-CON 3A1	\	\
Pulse limiter	Schwarzbeck	VTSD9561-F	01323	May 14, 2025	May 13, 2026


RF Conducted Test					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Power meter	Keysight	E4419	\	May 14, 2025	May 13, 2026
Power Sensor (AV)	Keysight	E9300A	\	May 14, 2025	May 13, 2026
Signal Analyzer20kHz-26.5GHz	Keysight	N9020A	MY49100060	May 14, 2025	May 13, 2026
Spectrum Analyzer9kHz-40GHz	R&S	FSP40	100363	May 14, 2025	May 13, 2026
Radio frequency control box	MAIWEI	MW100-RFC B	\	\	\
Software	MAIWEI	MTS 8310	\	\	\

Radiated Emissions Test (966 Chamber01)					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
966 chamber	ChengYu	966 Room	966	May 15, 2023	May 14, 2026
Receiver	R&S	ESR3	102075	May 08, 2025	May 07, 2026
Receiver	R&S	ESR3P	101154	May 14, 2025	May 13, 2026
Amplifier	Schwarzbeck	BBV9744	9744-0037	May 14, 2025	May 13, 2026
TRILOG Broadband Antenna	Schwarzbeck	VULB9163	942	May 24, 2025	May 23, 2026
Loop Antenna(9KHz-30MHz)	Schwarzbeck	FMZB1519B	00014	May 24, 2025	May 23, 2026
Amplifier	SKET	LAPA_01G18 G-45dB	SK2021040901	May 14, 2025	May 13, 2026
Horn Antenna	Schwarzbeck	BBHA9120D	1541	May 24, 2025	May 23, 2026
Amplifier(18G Hz-40GHz)	MITEQ	TTA1840-35-HG	2034381	May 24, 2025	May 23, 2026
Horn Antenna(18G Hz-40GHz)	Schwarzbeck	BBHA9170	00822	May 24, 2025	May 23, 2026
Spectrum Analyzer9kHz-40GHz	R&S	FSP40	100363	May 14, 2025	May 13, 2026
Software	Frad	EZ-EMC	FA-03A2 RE	\	\



## 6. Conducted Emissions

### 6.1 Block Diagram Of Test Setup



### 6.2 Limit

Frequency (MHz)	Limit (dBuV)	
	Quas-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Notes:

- \*Decreasing linearly with logarithm of frequency.
- The lower limit shall apply at the transition frequencies.

### 6.3 Test Procedure

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


- The Product was placed on a nonconductive table 0.8 m above the horizontal ground reference plane, and 0.4 m from the vertical ground reference plane, and connected to the main through Line Impedance Stability Network (L.I.S.N).
- The RBW of the receiver was set at 9 kHz in 150 kHz ~ 30MHz with Peak and AVG detector in Max Hold mode. Run the receiver's pre-scan to record the maximum disturbance generated from Product in all power lines in the full band.
- For each frequency whose maximum record was higher or close to limit, measure its QP and AVG values and record.

### 6.4 EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

### 6.5 Test Result

Temperature:	24.1 °C	Relative Humidity:	52 %
Pressure:	101KPa	Phase :	L
Test Mode:	Mode 3	Test Voltage :	AC 120V/60Hz




**Remark:**

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. Measurement=Reading Level+ Correct Factor
4. Over= Measurement-Limit

No.	Mk.	Freq. MHz	Reading Level	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1995	25.49	20.04	45.53	63.63	-18.10	QP
2		0.1995	16.65	20.04	36.69	53.63	-16.94	AVG
3		0.4425	24.16	20.06	44.22	57.01	-12.79	QP
4	*	0.4425	16.86	20.06	36.92	47.01	-10.09	AVG
5		0.8969	22.24	20.27	42.51	56.00	-13.49	QP
6		0.8969	15.31	20.27	35.58	46.00	-10.42	AVG
7		1.7789	13.61	20.20	33.81	56.00	-22.19	QP
8		1.7789	1.48	20.20	21.68	46.00	-24.32	AVG
9		3.6870	11.28	20.54	31.82	56.00	-24.18	QP
10		3.6870	-1.06	20.54	19.48	46.00	-26.52	AVG
11		17.7540	6.97	23.09	30.06	60.00	-29.94	QP
12		17.7540	-5.30	23.09	17.79	50.00	-32.21	AVG

Temperature:	24.1 °C	Relative Humidity:	52 %
Pressure:	101KPa	Phase :	N
Test Mode:	Mode 3	Test Voltage :	AC 120V/60Hz


**Remark:**


1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. Measurement=Reading Level+ Correct Factor
4. Over1 Measurement-Limit

No.	Mk.	Freq. MHz	Reading Level	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1986	25.87	20.04	45.91	63.67	-17.76	QP
2		0.1986	17.91	20.04	37.95	53.67	-15.72	AVG
3		0.4421	21.90	20.06	41.96	57.02	-15.06	QP
4		0.4421	13.22	20.06	33.28	47.02	-13.74	AVG
5	*	0.9684	25.70	20.27	45.97	56.00	-10.03	QP
6		0.9684	13.53	20.27	33.80	46.00	-12.20	AVG
7		1.7623	15.26	20.20	35.46	56.00	-20.54	QP
8		1.7623	2.16	20.20	22.36	46.00	-23.64	AVG
9		4.9519	11.58	20.71	32.29	56.00	-23.71	QP
10		4.9519	-0.27	20.71	20.44	46.00	-25.56	AVG
11		13.9886	15.68	22.25	37.93	60.00	-22.07	QP
12		13.9886	3.64	22.25	25.89	50.00	-24.11	AVG


## 7. Radiated Emissions

### 7.1 Block Diagram Of Test Setup


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



## (C) Radiated Emission Test-Up Frequency Above 1GHz



## 7.2 Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency (MHz)	Field Strength uV/m	Distance (m)	Field Strength Limit at 3m Distance	
			uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	$20\log^{(2400/F(kHz))} + 80$
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	$20\log^{(24000/F(kHz))} + 40$
1.705 ~ 30	30	30	100 * 30	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

### Limits Of Radiated Emission Measurement (Above 1000MHz)

Frequency (MHz)	Limit (dBuV/m) (at 3M)	
	Peak	Average
Above 1000	74	54

#### Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

### 7.3 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10:2020. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10:2020 and CAN/CSA-CEI/IEC CISPR 22.

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT.

Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where  $RBWCF [dB] = 10 \cdot \lg(100 [kHz]/\text{narrower RBW [kHz]})$ . , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

## 7.4 EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

## 7.5 Test Result

Below 30MHz

Temperature:	24.8 °C	Relative Humidity:	56 %
Pressure:	101KPa	Test Voltage:	AC 120V/60Hz
Test Mode:	Mode 3	Polarization :	--


Freq. (MHz)	Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	State P/F
--	--	--	--	PASS
--	--	--	--	PASS

**Note:**

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor =  $40 \log(\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.



Between 30MHz – 1GHz

Temperature:	24.8 °C	Relative Humidity:	56 %
Pressure:	101KPa	Phase :	Horizontal
Test Mode:	Mode 3	Test Voltage :	AC 120V/60Hz




Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Measurement=Reading Level+ Correct Factor
3. Over=Measurement-Limit

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1	!	123.6984	58.02	-16.11	41.91	43.50	-1.59	QP
2	!	148.4410	58.92	-17.51	41.41	43.50	-2.09	QP
3	!	197.8925	54.51	-14.53	39.98	43.50	-3.52	QP
4	!	272.2776	56.91	-12.67	44.24	46.00	-1.76	QP
5	*	396.2412	54.40	-9.50	44.90	46.00	-1.10	QP
6	!	744.8659	48.63	-3.87	44.76	46.00	-1.24	QP

Temperature:	24.8 °C	Relative Humidity:	56 %
Pressure:	101KPa	Phase :	Vertical
Test Mode:	Mode 3	Test Voltage :	AC 120V/60Hz


**Remark:**

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Measurement=Reading Level+ Correct Factor
3. Over= Measurement-Limit

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dB/m	dB	
1	!	124.1329	57.14	-16.13	41.01	43.50	-2.49	QP
2	!	148.4410	58.26	-17.51	40.75	43.50	-2.75	QP
3	!	247.6819	56.56	-13.26	43.30	46.00	-2.70	QP
4	!	396.2412	52.52	-9.50	43.02	46.00	-2.98	QP
5	*	446.4141	52.88	-8.47	44.41	46.00	-1.59	QP
6	!	711.6734	45.87	-4.63	41.24	46.00	-4.76	QP

Between 1GHz – 40GHz

Test Mode:	TX (5.8G) -- 802.11a
------------	----------------------

Polar (H/V)	Frequency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Measurement (dBuV/m)	Limits (dBuV/m)	Over (dB)	Detector Type
Low Channel (5745 MHz)-Above 1G							
Vertical	4679.121	72.17	-20.24	51.92	74.00	-22.08	PK
Vertical	4679.121	59.82	-20.24	39.58	54.00	-14.42	AV
Vertical	11490.113	63.77	-8.79	54.98	68.20	-13.22	PK
Vertical	11490.113	49.31	-8.79	40.52	54.00	-13.48	AV
Vertical	17235.081	55.59	-3.18	52.41	68.20	-15.79	PK
Vertical	17235.081	44.97	-3.18	41.79	54.00	-12.21	AV
Horizontal	4679.041	73.10	-20.73	52.37	74.00	-21.63	PK
Horizontal	4679.041	59.77	-20.73	39.04	54.00	-14.96	AV
Horizontal	11490.168	64.60	-8.79	55.81	68.20	-12.39	PK
Horizontal	11490.168	49.24	-8.79	40.45	54.00	-13.55	AV
Horizontal	17235.115	59.05	-3.18	55.87	68.20	-12.33	PK
Horizontal	17235.115	44.80	-3.18	41.62	54.00	-12.38	AV
Middle Channel (5785 MHz)-Above 1G							
Vertical	4592.067	72.41	-20.42	51.99	74.00	-22.01	PK
Vertical	4592.067	59.50	-20.42	39.09	54.00	-14.91	AV
Vertical	11570.010	61.55	-8.86	52.69	68.20	-15.51	PK
Vertical	11570.010	49.16	-8.86	40.30	54.00	-13.70	AV
Vertical	17355.102	55.31	-2.52	52.79	68.20	-15.41	PK
Vertical	17355.102	44.93	-2.52	42.41	54.00	-11.59	AV
Horizontal	4592.196	71.19	-20.42	50.77	74.00	-23.23	PK
Horizontal	4592.196	59.10	-20.42	38.68	54.00	-15.32	AV
Horizontal	11570.060	64.74	-8.86	55.88	68.20	-12.32	PK
Horizontal	11570.060	49.34	-8.86	40.48	54.00	-13.52	AV
Horizontal	17355.082	55.43	-2.52	52.91	68.20	-15.29	PK
Horizontal	17355.082	44.36	-2.52	41.84	54.00	-12.16	AV
High Channel (5825 MHz)-Above 1G							
Vertical	6039.065	74.94	-18.93	56.01	68.20	-12.19	PK
Vertical	6039.065	59.03	-18.93	40.10	54.00	-13.90	AV
Vertical	11650.047	64.89	-8.92	55.97	74.00	-18.03	PK
Vertical	11650.047	49.54	-8.92	40.62	54.00	-13.38	AV
Vertical	17475.195	57.16	-1.86	55.30	68.20	-12.90	PK
Vertical	17475.195	44.15	-1.86	42.29	54.00	-11.71	AV
Horizontal	6039.196	73.64	-18.93	54.71	68.20	-13.49	PK
Horizontal	6039.196	59.30	-18.93	40.37	54.00	-13.63	AV
Horizontal	11650.108	64.69	-8.92	55.77	74.00	-18.23	PK
Horizontal	11650.108	49.75	-8.92	40.83	54.00	-13.17	AV
Horizontal	17475.099	55.82	-1.86	53.96	68.20	-14.24	PK
Horizontal	17475.099	44.05	-1.86	42.19	54.00	-11.81	AV

Note: PK value is lower than the Average value limit, So average didn't record.  
 The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.  
 Emission level (dBuV/m) = 20 log Emission level (uV/m).  
 Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX (5.8G) --802.11n-HT20
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5745 MHz)-Above 1G							
Vertical	4679.022	74.86	-20.24	54.62	74.00	-19.38	PK
Vertical	4679.022	59.41	-20.24	39.17	54.00	-14.83	AV
Vertical	11490.052	60.80	-8.79	52.01	68.20	-16.19	PK
Vertical	11490.052	49.72	-8.79	40.93	54.00	-13.07	AV
Vertical	17235.172	57.10	-3.18	53.92	68.20	-14.28	PK
Vertical	17235.172	44.90	-3.18	41.72	54.00	-12.28	AV
Horizontal	4679.153	74.46	-20.24	54.22	74.00	-19.78	PK
Horizontal	4679.153	59.19	-20.24	38.95	54.00	-15.05	AV
Horizontal	11490.064	64.46	-8.79	55.67	68.20	-12.53	PK
Horizontal	11490.064	49.50	-8.79	40.71	54.00	-13.29	AV
Horizontal	17235.104	55.32	-3.18	52.14	68.20	-16.06	PK
Horizontal	17235.104	44.15	-3.18	40.97	54.00	-13.03	AV
Middle Channel (5785 MHz)-Above 1G							
Vertical	4592.098	74.72	-20.42	54.31	74.00	-19.69	PK
Vertical	4592.098	59.39	-20.42	38.97	54.00	-15.03	AV
Vertical	11570.014	60.89	-8.86	52.03	68.20	-16.17	PK
Vertical	11570.014	49.49	-8.86	40.63	54.00	-13.37	AV
Vertical	17355.100	56.03	-2.52	53.51	68.20	-14.69	PK
Vertical	17355.100	44.32	-2.52	41.80	54.00	-12.20	AV
Horizontal	4592.043	71.50	-20.42	51.09	74.00	-22.91	PK
Horizontal	4592.043	59.17	-20.42	38.76	54.00	-15.24	AV
Horizontal	11570.051	64.82	-8.86	55.96	68.20	-12.24	PK
Horizontal	11570.051	49.35	-8.86	40.49	54.00	-13.51	AV
Horizontal	17355.093	55.14	-2.52	52.62	68.20	-15.58	PK
Horizontal	17355.093	44.11	-2.52	41.59	54.00	-12.41	AV
High Channel (5825 MHz)-Above 1G							
Vertical	6039.144	73.10	-18.93	54.16	68.20	-14.04	PK
Vertical	6039.144	59.85	-18.93	40.92	54.00	-13.08	AV
Vertical	11650.181	62.53	-8.92	53.61	74.00	-20.39	PK
Vertical	11650.181	49.45	-8.92	40.53	54.00	-13.47	AV
Vertical	17475.069	56.28	-1.86	54.42	68.20	-13.78	PK
Vertical	17475.069	44.56	-1.86	42.70	54.00	-11.30	AV
Horizontal	6039.032	73.10	-18.93	54.16	68.20	-14.04	PK
Horizontal	6039.032	59.14	-18.93	40.21	54.00	-13.79	AV
Horizontal	11650.053	60.90	-8.92	51.98	74.00	-22.02	PK
Horizontal	11650.053	49.41	-8.92	40.49	54.00	-13.51	AV
Horizontal	17475.184	58.30	-1.86	56.44	68.20	-11.76	PK
Horizontal	17475.184	44.10	-1.86	42.24	54.00	-11.76	AV

Note: PK value is lower than the Average value limit, So average didn't record.  
 The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.  
 Emission level (dBuV/m) = 20 log Emission level (uV/m).  
 Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX (5.8G) -- 802.11n-HT40
------------	---------------------------

Polar (H/V)	Frequency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Measurement (dBuV/m)	Limits (dBuV/m)	Over (dB)	Detector Type
Low Channel (5755 MHz)-Above 1G							
Vertical	4679.111	72.59	-20.24	52.35	74.00	-21.65	PK
Vertical	4679.111	59.49	-20.24	39.25	54.00	-14.75	AV
Vertical	11510.138	62.35	-8.81	53.54	74.00	-20.46	PK
Vertical	11510.138	49.64	-8.81	40.83	54.00	-13.17	AV
Vertical	17265.033	57.41	-3.01	54.40	68.20	-13.80	PK
Vertical	17265.033	44.02	-3.01	41.01	54.00	-12.99	AV
Horizontal	4679.174	72.85	-20.24	52.61	74.00	-21.39	PK
Horizontal	4679.174	59.95	-20.24	39.71	54.00	-14.29	AV
Horizontal	11510.053	62.21	-8.81	53.40	74.00	-20.60	PK
Horizontal	11510.053	49.30	-8.81	40.49	54.00	-13.51	AV
Horizontal	17265.179	57.75	-3.01	54.74	68.20	-13.46	PK
Horizontal	17265.179	44.60	-3.01	41.59	54.00	-12.41	AV
Middle Channel (5795 MHz)-Above 1G							
Vertical	6039.089	72.40	-18.93	53.47	68.20	-14.73	PK
Vertical	6039.089	59.25	-18.93	40.32	54.00	-13.68	AV
Vertical	11590.150	62.36	-8.87	53.49	74.00	-20.51	PK
Vertical	11590.150	49.45	-8.87	40.58	54.00	-13.42	AV
Vertical	17385.047	59.38	-2.35	57.03	68.20	-11.17	PK
Vertical	17385.047	44.64	-2.35	42.29	54.00	-11.71	AV
Horizontal	6039.031	71.89	-18.93	52.96	68.20	-15.24	PK
Horizontal	6039.031	59.68	-18.93	40.75	54.00	-13.25	AV
Horizontal	11590.172	60.73	-8.87	51.86	74.00	-22.14	PK
Horizontal	11590.172	49.09	-8.87	40.22	54.00	-13.78	AV
Horizontal	17385.187	58.68	-2.35	56.33	68.20	-11.87	PK
Horizontal	17385.187	44.89	-2.35	42.54	54.00	-11.46	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

## 8. Power Spectral Density Test

### 8.1 Block Diagram Of Test Setup



### 8.2 Limit

For the band 5.15-5.25 GHz,

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz

(3) For the band 5.725-5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### 8.3 Test Procedure


For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:

- a) Set  $RBW \geq 1/T$ , where T is defined in section II.B.I.a).
- b) Set  $VBW \geq 3 RBW$ .
- c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add  $10\log(500\text{kHz}/RBW)$  to the measured result, whereas RBW (< 500 KHz) is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add  $10\log(1\text{MHz}/RBW)$  to the measured result, whereas RBW (< 1 MHz) is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 kHz for the sections 5.c) and 5.d) above, since RBW=100 KHZ is available on nearly all spectrum analyzers.

### 8.4 EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.






## 8.5 Test Result



Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101kPa	Test Voltage:	DC 3.7V
Test Mode:	TX Frequency (U-NII-3) 5745MHz-5825MHz		



Condition	Mode	Frequency (MHz)	Conducted PSD (dBm/510KHz)	Conducted PSD (dBm/500KHz)	Limit (dBm)	Verdict
NVNT	a	5745	-5.7	-5.786	30	Pass
NVNT	a	5785	-7.45	-7.536	30	Pass
NVNT	a	5825	-8.16	-8.246	30	Pass
NVNT	n20	5745	-7.23	-7.316	30	Pass
NVNT	n20	5785	-8.79	-8.876	30	Pass
NVNT	n20	5825	-8.69	-8.776	30	Pass
NVNT	n40	5755	-12	-12.086	30	Pass
NVNT	n40	5795	-13.06	-13.146	30	Pass



Note: Correction Factor =  $10\log(500\text{KHz}/\text{RBW in measurement}) = -0.086$












## 9. 26dB & 6dB & 99% Emission Bandwidth

### 9.1 Block Diagram Of Test Setup



### 9.2 Limit

The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.  
(6dB bandwidth)>500kHz

### 9.3 Test Procedure

- a) Set RBW = approximately 1% of the emission bandwidth.
- b) Set the VBW > RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW  $\geq 3 \cdot$  RBW
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).
7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.

6dB

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.

6. Allow the trace to stabilize.

7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



#### 9.4 EUT Operating Conditions



The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



#### 9.5 Test Result



Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101KPa	Test Voltage:	DC 3.7V
Test Mode:	(U-NII-3) 5745MHz-5825MHz		



Condition	Mode	Frequency (MHz)	99% bandwidth (MHz)	-6dB bandwidth (MHz)	Limit -6dB bandwidth (MHz)	Result
NVNT	a	5745	16.308	16.334	0.5	Pass
NVNT	a	5785	16.323	16.328	0.5	Pass
NVNT	a	5825	16.281	16.295	0.5	Pass
NVNT	n20	5745	17.48	17.183	0.5	Pass
NVNT	n20	5785	17.492	17.042	0.5	Pass
NVNT	n20	5825	17.463	17.053	0.5	Pass
NVNT	n40	5755	35.397	35.05	0.5	Pass
NVNT	n40	5795	35.424	35.027	0.5	Pass























## 10. Maximum Conducted Output Power

### 10.1 Block Diagram Of Test Setup



### 10.2 Limit

#### According to FCC §15.407

The maximum conducted output power should not exceed:

Frequency Band(MHz)	Limit
5150~5250	250mW
5725~5850	1W

### 10.3 Test Procedure

Maximum conducted output power may be measured using a spectrum analyzer/EMI receiver or an RF power meter.

#### 1. Device Configuration

If possible, configure or modify the operation of the EUT so that it transmits continuously at its maximum power control level (see section II.B.).

- a) The intent is to test at 100 percent duty cycle; however a small reduction in duty cycle (to no lower than 98 percent) is permitted if required by the EUT for amplitude control purposes. Manufacturers are expected to provide software to the test lab to permit such continuous operation.
- b) If continuous transmission (or at least 98 percent duty cycle) cannot be achieved due to hardware limitations (e.g., overheating), the EUT shall be operated at its maximum power control level with the transmit duration as long as possible and the duty cycle as high as possible.

#### 2. Measurement using a Spectrum Analyzer or EMI Receiver (SA)

Measurement of maximum conducted output power using a spectrum analyzer requires integrating the spectrum across a frequency span that encompasses, at a minimum, either the EBW or the 99-percent occupied bandwidth of the signal.<sup>1</sup> However, the EBW must be used to determine bandwidth dependent limits on maximum conducted output power in accordance with § 15.407(a).

a) The test method shall be selected as follows: (i) Method SA-1 or SA-1 Alternative (averaging with the EUT transmitting at full power throughout each sweep) shall be applied if either of the following conditions can be satisfied:

- The EUT transmits continuously (or with a duty cycle  $\geq 98$  percent).
- Sweep triggering or gating can be implemented in a way that the device transmits at the maximum power control level throughout the duration of each of the instrument sweeps to be averaged. This condition can generally be achieved by triggering the instrument's sweep if the duration of the sweep (with the analyzer configured as in Method SA-1, below) is equal to or shorter than the duration T of each transmission from the EUT and if those transmissions exhibit full power throughout their durations.

(ii) Method SA-2 or SA-2 Alternative (averaging across on and off times of the EUT transmissions, followed by duty cycle correction) shall be applied if the conditions of (i) cannot be achieved and the transmissions exhibit a constant duty cycle during the measurement duration. Duty cycle will be considered to be constant if variations are less than  $\pm 2$  percent.

(iii) Method SA-3 (RMS detection with max hold) or SA-3 Alternative (reduced VBW with max hold) shall be applied if the conditions of (i) and (ii) cannot be achieved.

b) Method SA-1 (trace averaging with the EUT transmitting at full power throughout each sweep): (i) Set span to encompass the entire emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.

(ii) Set RBW = 1 MHz.

(iii) Set VBW  $\geq 3$  MHz.

(iv) Number of points in sweep  $\geq 2$  Span / RBW. (This ensures that bin-to-bin spacing is  $\leq$  RBW/2, so that narrowband signals are not lost between frequency bins.)

(v) Sweep time = auto.

(vi) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.

(vii) If transmit duty cycle < 98 percent, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle  $\geq 98$  percent, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run".

(viii) Trace average at least 100 traces in power averaging (i.e., RMS) mode.

(ix) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument's band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum

## 10.4 EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

## 10.5 Test Result

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101kPa	Test Voltage:	DC 3.7V
Test Mode :	TX (5.8G) Mode Frequency U-NII-3 (5745-5825MHz)		

Condition	Mode	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	a	5745	6.53	30	Pass
NVNT	a	5785	6.76	30	Pass
NVNT	a	5825	6.23	30	Pass
NVNT	n20	5745	6.39	30	Pass
NVNT	n20	5785	6.54	30	Pass
NVNT	n20	5825	6.53	30	Pass
NVNT	n40	5755	6.29	30	Pass
NVNT	n40	5795	5.3	30	Pass

## 11. Out Of Band Emissions

### 11.1 Block Diagram Of Test Setup



### 11.2 Limit

According to FCC §15.407(b)

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of  $-27$  dBm/MHz.
- (2) All emissions shall be limited to a level of  $-27$  dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

### 11.3 Test Procedure



1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



### 11.4 EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data

## 11.5 Test Result







## 12. Spurious RF Conducted Emissions

### 12.1 Block Diagram Of Test Setup



### 12.2 Limit

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of  $-27$  dBm/MHz.

(2) For transmitters operating in the 5.725-5.85 GHz band(i) All emissions shall be limited to a level of  $-27$  dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge..



### 12.3 Test Procedure



1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



### 12.4 Test Result



Remark: The measurement frequency range is from 9KHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandedge measurement data.

About: 26.5GHz-40GHz, The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.









## 13. Frequency Stability Measurement

### 13.1 Block Diagram Of Test Setup



### 13.2 Limit

Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

The transmitter center frequency tolerance shall be  $\pm 20$  ppm maximum for the 5 GHz band (IEEE 802.11n specification)..

### 13.3 Test Procedure

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. EUT have transmitted absence of modulation signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
4. Set RBW = 10 kHz, VBW = 10 kHz with peak detector and maxhold settings.
5.  $f_c$  is declaring of channel frequency. Then the frequency error formula is  $(f_c - f) / f_c \times 10^6$  ppm and he limit is less than  $\pm 20$  ppm (IEEE 802.11n specification).
6. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
7. Extreme temperature is  $-20^\circ\text{C} \sim 70^\circ\text{C}$ .

## 13.4 Test Result

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101KPa	Test Voltage:	DC 3.7V
Test Mode:	TX (5.8G) Mode Frequency U-NII-3 (5745-5825MHz)		

## Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5745MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	3.70	5745.00010	5745	0.00010	0.0174
		V max (V)	4.26	5745.00250	5745	0.00250	0.4352
		V min (V)	3.15	5745.01190	5745	0.01190	2.0714
Limits				5725-5850 MHz			
Result				Complies			

## Temperature vs. Frequency Stability


TEST CONDITIONS				Reference Frequency: 5745MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	3.7	T (°C)	-20	5745.00080	5745	0.00080	0.1393
		T (°C)	-10	5745.00180	5745	0.00180	0.3133
		T (°C)	0	5745.00980	5745	0.00980	1.7058
		T (°C)	10	5745.00320	5745	0.00320	0.5570
		T (°C)	20	5745.00080	5745	0.00080	0.1393
		T (°C)	30	5745.01090	5745	0.01090	1.8973
		T (°C)	40	5745.00220	5745	0.00220	0.3829
		T (°C)	50	5745.00710	5745	0.00710	1.2359
		T (°C)	60	5745.01130	5745	0.01130	1.9669
		T (°C)	70	5745.00080	5745	0.00080	0.1393
Limits				5725-5850 MHz			
Result				Complies			

## Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5785MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	3.70	5785.00400	5785	0.00400	0.6914
		V max (V)	4.26	5785.01040	5785	0.01040	1.7978
		V min (V)	3.15	5785.00830	5785	0.00830	1.4347
Limits				5725-5850 MHz			
Result				Complies			

## Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5785MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	3.7	T (°C)	-20	5785.00800	5785	0.00800	1.3829
		T (°C)	-10	5785.00440	5785	0.00440	0.7606
		T (°C)	0	5785.00780	5785	0.00780	1.3483
		T (°C)	10	5785.00470	5785	0.00470	0.8124
		T (°C)	20	5785.01250	5785	0.01250	2.1608
		T (°C)	30	5785.00970	5785	0.00970	1.6768
		T (°C)	40	5785.00280	5785	0.00280	0.4840
		T (°C)	50	5785.00730	5785	0.00730	1.2619
		T (°C)	60	5785.01040	5785	0.01040	1.7978
		T (°C)	70	5785.00450	5785	0.00450	0.7779
Limits				5725-5850 MHz			
Result				Complies			




## Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5825MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	3.70	5825.00560	5825	0.00560	0.9614
		V max (V)	4.26	5825.00090	5825	0.00090	0.1545
		V min (V)	3.15	5825.01060	5825	0.01060	1.8197
Limits				5725-5850 MHz			
Result				Complies			

## Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5825MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	3.7	T (°C)	-20	5825.00630	5825	0.00630	1.0815
		T (°C)	-10	5825.00470	5825	0.00470	0.8069
		T (°C)	0	5825.00770	5825	0.00770	1.3219
		T (°C)	10	5825.00700	5825	0.00700	1.2017
		T (°C)	20	5825.01110	5825	0.01110	1.9056
		T (°C)	30	5825.00490	5825	0.00490	0.8412
		T (°C)	40	5825.00020	5825	0.00020	0.0343
		T (°C)	50	5825.01310	5825	0.01310	2.2489
		T (°C)	60	5825.00210	5825	0.00210	0.3605
		T (°C)	70	5825.00420	5825	0.00420	0.7210
Limits				5725-5850 MHz			
Result				Complies			



## 14. Duty Cycle Of Test Signal

### 14.1 Standard Requirement

Pre-analysis Check: While conducting average power measurement, duty cycle of each mode shall be checked to ensure its duty cycle in order to compensate for the loss due to insufficient ratio of duty cycle. All duty cycle is pre-scanned, and result as obtained below shows only the most representative ones where duty cycle is conducted as the given transmission with given virtual operation that expresses the percentage.

### 14.2 Formula



Duty Cycle =  $T_{on} / (T_{on} + T_{off})$



### 14.3 Test Procedure

1. Set span = Zero
2. RBW = 8MHz
3. VBW = 8MHz,
4. Detector = Peak

### 14.4 Test Result

Condition	Mode	Frequency (MHz)	Duty Cycle (%)	Correction Factor (dB)
NVNT	a	5745	100	0
NVNT	n20	5745	100	0
NVNT	n40	5755	100	0






## 15. Antenna Requirement

### 15.1 Limit

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### 15.2 Test Result

The EUT antenna is Internal antenna (antenna gain: 4.69 dBi ). It comply with the standard requirement.




### 16. EUT Photographs

EUT Photo 1



EUT Photo 2




NOTE: Appendix-Photographs Of EUT Constructional Details.



### 17. EUT Test Setup Photographs

#### Conducted Emissions Photo



#### Radiated Measurement Photos





**STATEMENT**

1. The equipment lists are traceable to the national reference standards.
2. The test report can not be partially copied unless prior written approval is issued from our lab.
3. The test report is invalid without the "special seal for inspection and testing".
4. The test report is invalid without the signature of the approver.
5. The test process and test result is only related to the Unit Under Test.
6. Sample information is provided by the client and the laboratory is not responsible for its authenticity.
7. The quality system of our laboratory is in accordance with ISO/IEC17025.
8. If there is any objection to this test report, the client should inform issuing laboratory within 15 days from the date of receiving test report.

**Address:**

1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

TEL: 400-788-9558

P.C.: 518103

FAX: 0755-33229357

Website: <http://www.chnbctc.com>

Consultation E-mail: [bctc@bctc-lab.com.cn](mailto:bctc@bctc-lab.com.cn)

Complaint/Advice E-mail: [advice@bctc-lab.com.cn](mailto:advice@bctc-lab.com.cn)

※※※※※ END ※※※※※

