

1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 General Information

Client Information

Applicant: Shenzhen Excelland Technology Co. Ltd.
Address of applicant: Shenzhen Excelland Technology Co. Ltd.. 5D, Building #1, Tingwei IndustrialPark, Liufang Road #6, 67 Zone of Xingdong Community. Xin'an Street, BaoanDistrict,Shenzhen,China

Manufacturer: Shenzhen Excelland Technology Co. Ltd.
Address of manufacturer: Shenzhen Excelland Technology Co. Ltd.. 5D, Building #1, Tingwei IndustrialPark, Liufang Road #6, 67 Zone of Xingdong Community. Xin'an Street, BaoanDistrict,Shenzhen,China

General Description of EUT:

Product Name: LORA
Trade Name: /
Model No.: UDL0700
Adding Model(s): UDL07XX
Rated Voltage: DC5V-36V
Power Adapter Model:SW0038
Input:AC100-240V, 50/60Hz, 0.2A
Output:DC12.0V,0.5A
FCC ID: 2A7P8-UDL07XX

Technical Characteristics of EUT:

LoRa

Frequency Range: 915MHz
RF Output Power: 15.18dBm (Conducted)
Modulation: LORA
Quantity of Channels: 1
Type of Antenna: External antenna
Antenna Gain: 1.5dBi

1.2 Standard Applicable

According to § 1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

(a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz: * = Plane-wave equivalents power density

1.3 MPE Calculation Method

$$S = (30*P*G) / (377*R^2)$$

S = power density (in appropriate units, e.g., mw/cm²)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator,
the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

1.4 MPE Calculation Result

For LoRa

Maximum Tune-Up output power: 15.50(dBm)

Maximum peak output power at antenna input terminal: 35.48(mW)

Prediction distance: >20(cm)

Prediction frequency: 915 (MHz)

Antenna gain: 1.5 (dBi)

Directional gain (numeric gain): 1.41

The worst case is power density at prediction frequency at 20cm: 0.0100(mw/cm²)

MPE limit for general population exposure at prediction frequency: 0.6100 (mw/cm²)

Result: Pass