

FCC Test Report

Report No. : 1812C50144412501

Applicant : Shenzhen Qianyan Technology LTD

Address : No. 3301, Block C, Section 1, Chuangzhi
Yuncheng Building, Liuxian Avenue, Xili
Community, Xili Street, Nanshan District,
Shenzhen, 518000, China

Product Name : Govee Recessed Downlight

Report Date : 2025-08-28

Shenzhen Anbotek Compliance Laboratory Limited

Shenzhen Anbotek Compliance Laboratory Limited

Any unauthorized modification, forgery, or falsification of this document constitutes a violation of law and is subject to legal penalties. If you have any questions, you may scan the QR code to download the report for verification or contact us via email.

Hotline: 400-003-0500 web: www.anbotek.com E-mail: service@anbotek.com



Contents

1. General Information	6
1.1. Client Information	6
1.2. Description of Device (EUT).....	6
1.3. Auxiliary Equipment Used During Test.....	7
1.4. Description of Test Configuration	7
1.5. Description Of Test Setup	8
1.6. Test Equipment List.....	9
1.7. Measurement Uncertainty	10
1.8. Additional Instructions	10
1.9. Description of Test Facility	11
1.10. Disclaimer.....	11
2. Summary of Test Results	12
3. Conducted Emission Test.....	13
3.1. Test Standard and Limit	13
3.2. Test Setup	13
3.3. Test Procedure.....	13
3.4. Test Data.....	13
4. Radiated Spurious Emission and Band Edge Test.....	18
4.1. Test Standard and Limit	18
4.2. Test Setup	18
4.3. Test Procedure.....	19
4.4. Test Data.....	20
5. Maximum Conducted Output Power Test.....	30
5.1. Test Standard and Limit	30
5.2. Test Setup	30
5.3. Test Procedure.....	30
5.4. Test Data.....	30
6. 6dB Bandwidth and 99% Occupied Bandwidth Test	31
6.1. Test Standard and Limit	31
6.2. Test Setup	31
6.3. Test Procedure.....	31
6.4. Test Data.....	31
7. Maximum Power Spectral Density Test.....	32
7.1. Test Standard and Limit	32
7.2. Test Setup	32
7.3. Test Procedure.....	32
7.4. Test Data.....	32
8. Conducted Spurious Emission Band Edge Test.....	33

8.1. Test Standard and Limit	33
8.2. Test Setup	33
8.3. Test Procedure	33
8.4. Test Data	33
9. Antenna Requirement.....	34
9.1. Test Standard and Requirement	34
9.2. Antenna Connected Construction	34
APPENDIX I -- TEST SETUP PHOTOGRAPH	35
APPENDIX II -- EXTERNAL PHOTOGRAPH	35
APPENDIX III -- INTERNAL PHOTOGRAPH.....	35

TEST REPORT

Applicant : Shenzhen Qiannyan Technology LTD
Manufacturer : Shenzhen Qiannyan Technology LTD
Product Name : Govee Recessed Downlight
Model No. : H601A, H601B, H801A, H801D
Trade Mark : Govee
Rating(s) : Input: AC 120-240V

Test Standard(s) : FCC Part15 Subpart C, Section 15.247

Test Method(s) : ANSI C63.10: 2020, KDB 558074 D01 15.247 Meas Guidance v05r02

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Receipt 2025-04-08

Date of Test 2025-04-08 to 2025-04-29

Prepared By



(Cecilia Chen)

Approved & Authorized Signer



(Hugo Chen)

Revision History

Report Version	Description	Issued Date
R00	Original Issue.	2025-08-28

1. General Information

1.1. Client Information

Applicant	:	Shenzhen Qiyan Technology LTD
Address	:	No. 3301, Block C, Section 1, Chuangzhi Yuncheng Building, Liuxian Avenue, Xili Community, Xili Street, Nanshan District, Shenzhen, 518000, China
Manufacturer	:	Shenzhen Qiyan Technology LTD
Address	:	No. 3301, Block C, Section 1, Chuangzhi Yuncheng Building, Liuxian Avenue, Xili Community, Xili Street, Nanshan District, Shenzhen, 518000, China

1.2. Description of Device (EUT)

Product Name	:	Govee Recessed Downlight
Model No.	:	H601A, H601B, H801A, H801D (Note: All samples are the same except the model number and size and appearance. The model differences please refer to page 6, based on the model differences, we prepare H601A for all tests, and prepared H601B for conducted emission and radiated spurious emissions (below 1GHz) difference testing.)
Trade Mark	:	Govee
Test Power Supply	:	AC 120V/60Hz
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)
Adapter	:	N/A

RF Specification

Operation Mode	:	<input checked="" type="checkbox"/> BT BLE
Support Rate	:	<input checked="" type="checkbox"/> 1Mbps <input type="checkbox"/> 2Mbps
Operation Frequency	:	2402~2480MHz
Number of Channel	:	40 Channels
Modulation Type	:	GFSK
Antenna Type	:	FPC Antenna
Antenna Gain(Peak)	:	2.37dBi

Remark: 1) All of the RF specification are provided by customer. 2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

Model differences:

Product Name	Model No.	Sales Channels
Govee Recessed Downlight	H601A	Online : Amazon
	H801A	Offline: To D&H Canada
	H601B	Online : Amazon
	H801D	Offline: To D&H Canada

1.3. Auxiliary Equipment Used During Test

Description	Rating(s)
--	--

1.4. Description of Test Configuration


Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
00	2402	09	2420	18	2438	27	2456	36	2474
01	2404	10	2422	19	2440	28	2458	37	2476
02	2406	11	2424	20	2442	29	2460	38	2478
03	2408	12	2426	21	2444	30	2462	39	2480
04	2410	13	2428	22	2446	31	2464		
05	2412	14	2430	23	2448	32	2466		
06	2414	15	2432	24	2450	33	2468		
07	2416	16	2434	25	2452	34	2470		
08	2418	17	2436	26	2454	35	2472		

Note:


1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.
2. EUT was tested with channel 0, 19 and 39.

1.5. Description Of Test Setup

CE



RE



1.6. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	2024-09-09	1 Year
2.	Three Phase V-type Artificial Power Network	CYBERTEK	EM5040DT	E215040DT0 01	2025-01-13	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	2025-01-13	1 Year
4.	EMI Test Receiver	Rohde & Schwarz	ESR26	101481	2025-01-14	1 Year
5.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	2024-09-09	1 Year
6.	EMI Preamplifier	SKET Electronic	LNPA-0118G- 45	SKET-PA-00 2	2025-01-13	1 Year
7.	Double Ridged Horn Antenna	SCHWARZBECK	BBHA 9120D	02555	2022-10-16	3 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	345	2022-10-23	3 Year
9.	Loop Antenna	Schwarzbeck	FMZB1519B	00053	2024-09-12	1 Year
10.	Horn Antenna	A-INFO	LB-180400-K F	J211060628	2024-01-22	3 Year
11.	Pre-amplifier	SONOMA	310N	186860	2025-01-14	1 Year
12.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
13.	MXA Spectrum Analysis	KEYSIGHT	N9020A	MY53280032	2024-09-09	1 Year
14.	MXG RF Vector Signal Generator	Agilent	N5182A	MY47420647	2025-01-14	1 Year
15.	Signal Generator	Agilent	E4421B	MY41000743	2024-10-10	1 Year
16.	DC Power Supply	IVYTECH	IV3605	1804D36051 0	2024-09-09	1 Year
17.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80B	N/A	2024-10-14	1 Year
18.	Spectrum Analyzer	Rohde & Schwarz	FSV40-N	102150	2024-05-06	1 Year

1.7. Measurement Uncertainty

Parameter	Uncertainty
Conducted emissions (AMN 150kHz~30MHz)	3.8dB
Occupied Bandwidth	925Hz
Conducted Output Power	0.76dB
Power Spectral Density	0.76dB
Conducted Spurious Emission	1.24dB
Radiated spurious emissions (Below 30MHz)	3.53dB
Radiated spurious emissions (30MHz~1GHz)	Horizontal: 3.92dB; Vertical: 4.52dB
Radiated spurious emissions (above 1GHz)	1G-6GHz: 4.78dB; 6G-18GHz: 4.88dB 18G-40GHz: 5.68dB
The measurement uncertainty and decision risk evaluated according to AB/WI-RF-F-032. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

1.8. Additional Instructions

Power level setup in software: Bluetooth RF Test Tool 5.2.3.58

Operation Band:

Mode	Channel(MHz)	Power level	Transmitting type
BLE_1M	2402	default	data pack TX
BLE_1M	2440	default	data pack TX
BLE_1M	2480	default	data pack TX

1.9. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 279531

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 279531.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

Sogood Industrial Zone Laboratory & 1/F. of Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Subdistrict, Bao'an District, Shenzhen, Guangdong, China.

1.10. Disclaimer

1. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
2. The test report is invalid if there is any evidence and/or falsification.
3. The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
4. This document may not be altered or revised in any way unless done so by Anbotek and all revisions are duly noted in the revisions section.
5. Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
6. The authenticity of the information provided by the customer is the responsibility of the customer and the laboratory is not responsible for its authenticity.
7. The data in this report will be synchronized with the corresponding national market supervision and management departments and cross-border e-commerce platforms as required by regulatory agencies.

The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

2. Summary of Test Results

Standard Section	Test Item	Result
15.203/15.247(c)	Antenna Requirement	PASS
15.207	Conducted Emission	PASS
15.205/15.209	Radiated Spurious Emission and Band Edge	PASS
15.247(b)(3)	Maximum Conducted Output Power	PASS
15.247(a)(2)	6dB Bandwidth	PASS
N/A	99% Occupied Bandwidth	Report only
15.247(e)	Maximum Power Spectral Density	PASS
15.247(d)	Conducted Spurious Emission and Band Edge	PASS

Remark: "N/A" is an abbreviation for Not Applicable.


3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
150kHz~500kHz	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50

Remark:(1) *Decreasing linearly with logarithm of the frequency.
(2) The lower limit shall apply at the transition frequency.

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10: 2020 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

3.4. Test Data


During the test, pre-scan all modes, only the worst case is recorded in the report.

Please to see the following pages.

Conducted Emission Test Data

Model: H601A

Test Site: 1# Shielded Room
 Operating Condition: 2440MHz
 Test Specification: AC 120V/60Hz
 Comment: Live Line
 Temp.(°C)/Hum.(%RH): 24.6°C/59%RH




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1500	36.80	17.82	54.62	65.99	-11.37	QP	
2	0.1539	25.45	17.83	43.28	55.78	-12.50	AVG	
3	0.2900	26.46	17.84	44.30	60.52	-16.22	QP	
4	0.5500	25.42	17.86	43.28	56.00	-12.72	QP	
5	0.5580	15.06	17.86	32.92	46.00	-13.08	AVG	
6	1.3020	24.64	17.86	42.50	56.00	-13.50	QP	
7	1.3340	14.23	17.86	32.09	46.00	-13.91	AVG	
8	1.6340	22.45	17.85	40.30	56.00	-15.70	QP	
9	1.8020	10.88	17.86	28.74	46.00	-17.26	AVG	
10	1.9460	20.53	17.85	38.38	56.00	-17.62	QP	
11	2.2460	9.21	17.85	27.06	46.00	-18.94	AVG	
12	3.6660	8.56	17.86	26.42	46.00	-19.58	AVG	

Conducted Emission Test Data

Model: H601A

Test Site: 1# Shielded Room
 Operating Condition: 2440MHz
 Test Specification: AC 120V/60Hz
 Comment: Neutral Line
 Temp.(°C)/Hum.(%RH): 24.6°C/59%RH



No.	Freq. (MHz)	Reading (dB μ V)	Factor (dB)	Result (dB μ V)	Limit (dB μ V)	Over Limit (dB)	Detector	Remark
1	0.1500	25.08	17.82	42.90	55.99	-13.09	AVG	
2	0.1539	36.49	17.83	54.32	65.78	-11.46	QP	
3	0.2140	16.88	17.82	34.70	53.04	-18.34	AVG	
4	0.5780	28.67	17.86	46.53	56.00	-9.47	QP	
5	0.6100	16.82	17.87	34.69	46.00	-11.31	AVG	
6	1.3220	13.40	17.86	31.26	46.00	-14.74	AVG	
7	1.3460	23.46	17.86	41.32	56.00	-14.68	QP	
8	1.6220	9.28	17.85	27.13	46.00	-18.87	AVG	
9	1.6540	19.10	17.85	36.95	56.00	-19.05	QP	
10	1.9660	16.90	17.85	34.75	56.00	-21.25	QP	
11	1.9660	7.78	17.85	25.63	46.00	-20.37	AVG	
12	2.3460	17.36	17.85	35.21	56.00	-20.79	QP	


Note:

Result(dB μ V) = Reading(dB μ V) + Factor(dB);
 Over Limit(dB) = Result(dB μ V) - Limit(dB μ V)

Conducted Emission Test Data

Model: H601B

Test Site: 1# Shielded Room
 Operating Condition: 2440MHz
 Test Specification: AC 120V/60Hz
 Comment: Live Line
 Temp.(°C)/Hum.(%RH): 22.1°C/50%RH




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1780	23.14	17.82	40.96	54.57	-13.61	AVG	
2	0.3820	35.18	17.81	52.99	58.23	-5.24	QP	
3	0.4100	25.50	17.81	43.31	47.65	-4.34	AVG	
4	0.5420	28.09	17.86	45.95	56.00	-10.05	QP	
5	0.5420	18.47	17.86	36.33	46.00	-9.67	AVG	
6	0.8580	17.20	17.86	35.06	46.00	-10.94	AVG	
7	0.8620	27.12	17.86	44.98	56.00	-11.02	QP	
8	1.1620	27.92	17.86	45.78	56.00	-10.22	QP	
9	1.2020	17.05	17.85	34.90	46.00	-11.10	AVG	
10	1.5220	14.79	17.85	32.64	46.00	-13.36	AVG	
11	1.5660	25.95	17.85	43.80	56.00	-12.20	QP	
12	1.9420	24.67	17.85	42.52	56.00	-13.48	QP	

Conducted Emission Test Data

Model: H601B

Test Site: 1# Shielded Room
 Operating Condition: 2440MHz
 Test Specification: AC 120V/60Hz
 Comment: Neutral Line
 Temp.(°C)/Hum.(%RH): 22.1°C/50%RH



No.	Freq. (MHz)	Reading (dB μ V)	Factor (dB)	Result (dB μ V)	Limit (dB μ V)	Over Limit (dB)	Detector	Remark
1	0.1660	21.13	17.83	38.96	55.15	-16.19	AVG	
2	0.3820	31.54	17.81	49.35	58.23	-8.88	QP	
3	0.4100	23.03	17.81	40.84	47.65	-6.81	AVG	
4	0.5380	26.90	17.86	44.76	56.00	-11.24	QP	
5	0.5380	16.80	17.86	34.66	46.00	-11.34	AVG	
6	0.8500	23.69	17.86	41.55	56.00	-14.45	QP	
7	0.8620	15.33	17.86	33.19	46.00	-12.81	AVG	
8	1.2100	15.11	17.85	32.96	46.00	-13.04	AVG	
9	1.2180	24.46	17.85	42.31	56.00	-13.69	QP	
10	1.5580	23.42	17.85	41.27	56.00	-14.73	QP	
11	1.5580	12.95	17.85	30.80	46.00	-15.20	AVG	
12	1.8820	21.81	17.85	39.66	56.00	-16.34	QP	

Note:

Result(dB μ V) = Reading(dB μ V) + Factor(dB);
 Over Limit(dB) = Result(dB μ V) - Limit(dB μ V)

4. Radiated Spurious Emission and Band Edge Test

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz~1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz~30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
	-	74.0	Peak		3

Remark:

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

4.2. Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW =300kHz,Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For above 1GHz, Set the spectrum analyzer as:

RBW =1MHz, VBW =3MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.

For average measurement:

-VBW=3*RBW, Detector= RMS, When duty cycle is no less than 98 percent

-VBW=3*RBW, Detector= RMS, When duty cycle is less than 98 percent and dutycycle is constant, average=peak level+correction factor(20log(dutycycle)).

- $\text{VBW} \geq 1/T$, when duty cycle is less than 98 percent and dutycycle is not constant, where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation, so refer to this clause duty cycle result.

4.4. Test Data

PASS

During the test, Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis is the worst case.


The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

During the test, pre-scan all modes, only the worst case is recorded in the report.

Test Results (30~1000MHz)

Model: H601A


Test Mode: 2440MHz
 Power Source: AC 120V/60Hz
 Polarization: Horizontal
 Temp.(°C)/Hum.(%RH): 22.5°C/55%RH



Test Results (30~1000MHz)

Model: H601A

Test Mode: 2440MHz
 Power Source: AC 120V/60Hz
 Polarization: Vertical
 Temp.(°C)/Hum.(%RH): 22.5°C/55%RH




Note:

Result(dB μ V/m) = Reading(dB μ V) + Factor(dB/m);Over Limit(dB) = Result(dB μ V/m) - Limit(dB μ V/m)

Test Results (30~1000MHz)

Model: H601B

Test Mode: 2440MHz
 Power Source: AC 120V/60Hz
 Polarization: Horizontal
 Temp.(°C)/Hum.(%RH): 22.5°C/55%RH




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Remark
1	47.6584	41.44	-16.98	24.46	40.00	-15.54	QP	
2	191.7450	46.75	-20.59	26.16	43.50	-17.34	QP	
3	207.1226	45.70	-19.87	25.83	43.50	-17.67	QP	
4	451.1349	44.91	-12.55	32.36	46.00	-13.64	QP	
5	916.0687	32.40	-6.49	25.91	46.00	-20.09	QP	
6	948.7609	32.28	-6.02	26.26	46.00	-19.74	QP	

Test Results (30~1000MHz)

Model: H601B

Test Mode: 2440MHz
 Power Source: AC 120V/60Hz
 Polarization: Vertical
 Temp.(°C)/Hum.(%RH): 22.5°C/55%RH



Note:

Result(dB μ V/m) = Reading(dB μ V) + Factor(dB/m);Over Limit(dB) = Result(dB μ V/m) - Limit(dB μ V/m)

Test Results (1GHz-25GHz)

Test Mode: CH00		Test channel: Lowest				
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4804.00	30.83	15.27	46.10	74.00	-27.90	Vertical
7206.00	30.48	18.09	48.57	74.00	-25.43	Vertical
9608.00	32.15	23.76	55.91	74.00	-18.09	Vertical
12010.00	*			74.00		Vertical
14412.00	*			74.00		Vertical
4804.00	30.29	15.27	45.56	74.00	-28.44	Horizontal
7206.00	31.89	18.09	49.98	74.00	-24.02	Horizontal
9608.00	29.13	23.76	52.89	74.00	-21.11	Horizontal
12010.00	*			74.00		Horizontal
14412.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4804.00	19.10	15.27	34.37	54.00	-19.63	Vertical
7206.00	19.53	18.09	37.62	54.00	-16.38	Vertical
9608.00	21.62	23.76	45.38	54.00	-8.62	Vertical
12010.00	*			54.00		Vertical
14412.00	*			54.00		Vertical
4804.00	18.62	15.27	33.89	54.00	-20.11	Horizontal
7206.00	20.92	18.09	39.01	54.00	-14.99	Horizontal
9608.00	18.64	23.76	42.40	54.00	-11.60	Horizontal
12010.00	*			54.00		Horizontal
14412.00	*			54.00		Horizontal

Test Results (1GHz-25GHz)

Test Mode: CH19		Test channel: Middle				
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4880.00	30.38	15.42	45.80	74.00	-28.20	Vertical
7320.00	30.45	18.02	48.47	74.00	-25.53	Vertical
9760.00	31.65	23.80	55.45	74.00	-18.55	Vertical
12200.00	*			74.00		Vertical
14640.00	*			74.00		Vertical
4880.00	30.10	15.42	45.52	74.00	-28.48	Horizontal
7320.00	31.76	18.02	49.78	74.00	-24.22	Horizontal
9760.00	28.85	23.80	52.65	74.00	-21.35	Horizontal
12200.00	*			74.00		Horizontal
14640.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4880.00	19.19	15.42	34.61	54.00	-19.39	polarization
7320.00	19.39	18.02	37.41	54.00	-16.59	Vertical
9760.00	21.47	23.80	45.27	54.00	-8.73	Vertical
12200.00	*			54.00		Vertical
14640.00	*			54.00		Vertical
4880.00	18.73	15.42	34.15	54.00	-19.85	Vertical
7320.00	21.27	18.02	39.29	54.00	-14.71	Horizontal
9760.00	18.94	23.80	42.74	54.00	-11.26	Horizontal
12200.00	*			54.00		Horizontal
14640.00	*			54.00		Horizontal


Test Results (1GHz-25GHz)

Test Mode: CH39		Test channel: Highest				
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4960.00	30.51	15.58	46.09	74.00	-27.91	Vertical
7440.00	30.61	17.93	48.54	74.00	-25.46	Vertical
9920.00	32.35	23.83	56.18	74.00	-17.82	Vertical
12400.00	*			74.00		Vertical
14880.00	*			74.00		Vertical
4960.00	30.24	15.58	45.82	74.00	-28.18	Horizontal
7440.00	31.97	17.93	49.90	74.00	-24.10	Horizontal
9920.00	29.23	23.83	53.06	74.00	-20.94	Horizontal
12400.00	*			74.00		Horizontal
14880.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4960.00	20.31	15.58	35.89	54.00	-18.11	Vertical
7440.00	20.66	17.93	38.59	54.00	-15.41	Vertical
9920.00	22.12	23.83	45.95	54.00	-8.05	Vertical
12400.00	*			54.00		Vertical
14880.00	*			54.00		Vertical
4960.00	19.91	15.58	35.49	54.00	-18.51	Horizontal
7440.00	22.07	17.93	40.00	54.00	-14.00	Horizontal
9920.00	19.09	23.83	42.92	54.00	-11.08	Horizontal
12400.00	*			54.00		Horizontal
14880.00	*			54.00		Horizontal

Remark:

- 1.Result =Reading + Factor
2. “*” means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Radiated Band Edge:



CH: L						
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
2326.710	37.220	9.73	46.950	74	-27.050	Vertical
2390.000	34.600	9.73	44.330	74	-29.670	Vertical
2371.870	37.380	9.73	47.110	74	-26.890	Horizontal
2390.000	34.100	9.73	43.830	74	-30.170	Horizontal
CH: H						
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
2499.041	39.790	9.91	49.700	74	-24.300	Vertical
2483.500	35.400	9.91	45.310	74	-28.690	Vertical
2499.005	38.900	9.91	48.810	74	-25.190	Horizontal
2483.500	35.960	9.91	45.870	74	-28.130	Horizontal

Remark: When the PK measure result value is less than the AVG limit value, the AV measure result values test not applicable.

Additional test for duty cycle.


Please refer to Appendix G of the Appendix Test Data.

5. Maximum Conducted Output Power Test

5.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (b)(3)
Test Limit	1W (30dBm)

5.2. Test Setup



5.3. Test Procedure

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

1. Set the RBW \geq DTS bandwidth.
2. Set the VBW $\geq 3 \times$ RBW.
3. Set the span $\geq 3 \times$ RBW.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use peak marker function to determine the peak amplitude level.

5.4. Test Data

Pass


Please refer to Appendix C of the Appendix Test Data.

6. 6dB Bandwidth and 99% Occupied Bandwidth Test

6.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(2)
Test Limit	$\geq 500\text{kHz}$

6.2. Test Setup



6.3. Test Procedure

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as:
6dB Bandwidth:
 - a) Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
 - b) Set the VBW $\geq [3 \times \text{RBW}]$.
 - c) Detector = peak.
 - d) Trace mode = max-hold.
 - e) Sweep = No faster than coupled (auto) time.
 - f) Allow the trace to stabilize.
 - g) Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6 dB down amplitude”. If a marker is below this “-6 dB down amplitude” value, then it shall be as close as possible to this value.

99% Occupied Bandwidth:

RBW=1~5% OBW, VBW=3*RBW, Sweep Time= Auto, Detector= Peak, Trace= Max hold

6.4. Test Data

Pass


Please refer to Appendix A & Appendix B of the Appendix Test Data.

7. Maximum Power Spectral Density Test

7.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (e)
Test Limit	8dBm/3kHz

7.2. Test Setup



7.3. Test Procedure

1. Place the EUT on the table and set it in transmitting mode. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set the spectrum analyzer as $RBW = 3\text{kHz}$, $VBW \geq 3 * RBW$, $Span = 1.5 \times DTS\text{ BW}$
3. Record the max. reading.
4. Repeat the above procedure until the measurements for all frequencies are completed.

7.4. Test Data

Pass


Please refer to Appendix D of the Appendix Test Data.

8. Conducted Spurious Emission Band Edge Test

8.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (d)
Test Limit	In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

8.2. Test Setup



8.3. Test Procedure

Using the following spectrum analyzer setting:

1. Set the RBW = 100kHz.
2. Set the VBW = 300kHz.
3. Sweep time = auto couple.
4. Detector function = peak.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.

8.4. Test Data

Pass

Please refer to Appendix E & Appendix F of the Appendix Test Data.

9. Antenna Requirement

9.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203 /247(c)
Requirement	<p>1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>2) 15.247(c) (1)(i) requirement: Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.</p>

9.2. Antenna Connected Construction

The antenna is a FPC Antenna which permanently attached, and the best case gain of the antenna is 2.37dBi. It complies with the standard requirement.

APPENDIX I -- TEST SETUP PHOTOGRAPH

Please refer to separated files Appendix I -- Test Setup Photograph_RF

APPENDIX II -- EXTERNAL PHOTOGRAPH

Please refer to separated files Appendix II -- External Photograph

APPENDIX III -- INTERNAL PHOTOGRAPH

Please refer to separated files Appendix III -- Internal Photograph

----- End of Report -----