

## RF EXPOSURE EVALUATION

### 1. PRODUCT INFORMATION

|                     |                                                 |
|---------------------|-------------------------------------------------|
| Product Description | ULTRA WIRELESS 2 - Wireless Over-Ear Headphones |
| Model Name          | ULTRA WIRELESS 2                                |
| FCC ID              | 2A84F-SU76                                      |

### 2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

Where  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

### 3. CALCULATION

#### BR/EDR

$P_t = 4.374 \text{ dBm} = 2.74 \text{ mW}$

The value of the Maximum output power  $P_t$  is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation  $\text{SAR} = (2.74 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.480 \text{ GHz}}] = 0.86 < 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.  
.5 for 10-g extremity SAR.

### 4. CONCLUSION

The SAR evaluation is not required.