

TEST REPORT

Applicant Name : Shenzhen Mike Morgan Technology Co.,Ltd.
Address : Room 302, Building 5, Zone C, Jinxiu Huacheng Park, Bantian Street, Longgang District, ShenZhen, China
Report Number : 2504U21956E-RFA
FCC ID: 2A88F-NJ10-L

Test Standard (s)

47 CFR §1.1307& §2.1093

Sample Description

Product Type: WIZARD 2
Model No.: NJ10
Trade Mark: NYXI
Date Received: 2025-06-24
Report Date: 2025-08-05


Test Result:	The EUT complied with the standards above.
--------------	--

Prepared and Checked By:



Roger Ling
EMC Engineer

Approved By:



Bob Liao
EMC Engineer

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA, or any agency of the Federal Government. The information marked “#” is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included but no need marked.
This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

Tel: +86 755-26503290

Web: www.atc-lab.com

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	3
GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
TEST FACILITY	4
RF EXPOSURE	5
APPLICABLE STANDARD.....	5
TEST RESULT	5
EXHIBIT A-EUT PHOTOGRAPHS	6

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
Rev.00	2504U21956E-RFA	Original Report	2025-08-05

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	WIZARD 2
Tested Model	NJ10
Frequency Range	Bluetooth: 2402-2480MHz
Maximum Conducted Output Power	-0.50dBm
Antenna Specification [#]	Internal Antenna: -1.42445dBi (It is provided by the applicant.)
Voltage Range [#]	DC 3.7V from rechargeable battery or DC 5V USB Port
Sample Serial Number	357T-4 (Assigned by ATC, Shenzhen)
Sample/EUT Status	Good condition

Note 1: The product (WIZARD 2) consists of three parts, as below:
a middle bridge, a left controller(FCC ID: 2A88F-NJ10-L), a right controller(FCC ID: 2A88F-NJ10-R).
Only the left/right controller have wireless functionality.
Note 2: The left controller was recorded in this report.

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts C and Part 2-Subpart J, Radiofrequency Radiation Exposure of the Federal Communication Commission rules.

The tests were performed in order to determine compliance with FCC §2.1093 rules.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

Accredited by American Association for Laboratory Accreditation (A2LA).The Certificate Number is 4297.01.

RF EXPOSURE

Applicable Standard

According to FCC §2.1093, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.

2. Power and distance are rounded to the nearest mW and mm before calculation.

3. The result is rounded to one decimal place for comparison.

4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

Test result

For worst case:

Left Controller

Frequency (MHz)	Tune-Up Conducted Output Power [#] (dBm)	Tune-Up Conducted Output Power [#] (mW)	Distance (mm)	Calculated Value	Threshold (1-g SAR)	SAR Test Exclusion
2480	0	1.0	5.0	0.3	3.0	Yes

Note: The tune-up conducted power is declared by the applicant.

Result: No SAR test is required.

EXHIBIT A-EUT PHOTOGRAPHS

Please refer to the Attachment No.1 2504U21956E-RF-00A EUT External Photos and Attachment No.2 2504U21956E-RF-00A EUT Internal Photos.

***** END OF REPORT *****