

# FCC MPE Evaluation Report

**Report No:** WD-RF-R-220226-D0

**Product Name** : Action Camera  
**Model Name** : LVPRO2  
**Series Model Name** : LVPRO2 Plus  
**FCC ID** : 2A8BT-LVPRO2  
**Applicant** : Live View Sports, Inc.  
**Received Date** : Jun. 17, 2022  
**Tested Date** : Jul. 27, 2022 ~ Aug. 09, 2022  
**Applicable Standard** : 47 CFR FCC Part 2.1091  
47 CFR FCC Part 1.1310  
KDB 447498 D01  
OET Bulletin 65 Supplement C



**Wendell Industrial Co., Ltd**  
**Wendell EMC & RF Laboratory**

**Caution:**

This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted.

The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment.

Please note that the measurement uncertainty are provided for informational purpose only and are not used in determining the Pass/Fail results.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of Wendell Industrial Co., Ltd..

# Test Report

Issued Date: August 10, 2022

Project No.: 22Q061702


<b>Product Name</b>	Action Camera
<b>Trade Name</b>	LIVEVIEWSPORTS
<b>Model Name</b>	LVPRO2
<b>Series Model Name</b>	LVPRO2 Plus
<b>FCC ID</b>	2A8BT-LVPRO2
<b>Applicant</b>	Live View Sports, Inc.
<b>Manufacturer</b>	GWAN KUEN TECHNOLOGY CO., LTD.
<b>EUT Rated Voltage</b>	USB Power 5V / Battery 3.7V
<b>EUT Test Voltage</b>	USB Power 5V
<b>EUT Supports Radios Application</b>	WLAN 802.11b/g WLAN 802.11n (HT20/HT40) Bluetooth BR/EDR/LE
<b>Applicable Standard</b>	47 CFR FCC Part 2.1091 47 CFR FCC Part 1.1310 KDB 447498 D01 OET Bulletin 65 Supplement C
<b>RF Evaluation</b>	0.02956 mW/cm <sup>2</sup>
<b>Test Result</b>	Complied

Documented :




( Specialist / Emma Lu )

Technical Engineer :



( Section Manager / Jack Chang )

Approved :



( Project Manager / Gary Wu )

## Table of Contents

<b>Document Revision History .....</b>	<b>4</b>
<b>Reference Testing Standard.....</b>	<b>5</b>
<b>1    Generation Information .....</b>	<b>6</b>
1.1   Applicant.....	6
1.2   Manufacturer.....	6
1.3   Description of Equipment under Test.....	6
1.4   Test Facility .....	7
<b>2    Mobile device Assessment Procedure.....</b>	<b>8</b>
<b>3    RF Exposure Assessment.....</b>	<b>8</b>
<b>4    Limit Requirement .....</b>	<b>9</b>
<b>5    Test Results.....</b>	<b>10</b>

## Document Revision History

Report No.	Issue date	Description
WD-RF-R-220226-D0	August 10, 2022	Initial report

### Reference Testing Standard

Standard	Description	Version
47 CFR FCC Part 2.1091	Radiofrequency radiation exposure evaluation: mobile devices.	--
47 CFR FCC Part 1.1310	Radiofrequency radiation exposure limits.	--
KDB 447498 D01	RF Exposure procedures and equipment authorization policies for mobile and portable devices.	V06
OET Bulletin 65 Supplement C	Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields.	Edition 01-01

# 1 Generation Information

## 1.1 Applicant

Live View Sports, Inc.  
10061 Bubb Road, #200, Cupertino, CA 95014

## 1.2 Manufacturer

GWAN KUEN TECHNOLOGY CO., LTD.  
No. 105, Liye Rd., Zhonghe Dist., New Taipei City 235, Taiwan

## 1.3 Description of Equipment under Test

<b>Product Name</b>	Action Camera
<b>Model No.</b>	LVPRO2
<b>Series Model Name</b>	LVPRO2 Plus
<b>Model Difference</b>	LVPRO2: AP mode only. LVPRO2 PLUS: AP mode or Client mode. This series only has software differences, everything else is the same.
<b>FCC ID</b>	2A8BT-LVPRO2
<b>Frequency Range</b>	802.11b/g/n-20MHz: 2412~2462MHz 802.11n-40MHz: 2422~2452MHz
<b>Antenna Information</b>	Refer to the table "Antenna List"

The above equipment was tested by Wendell EMC & RF Laboratory For compliance with the requirements set forth in 47 CFR § 2.1091 / 47 CFR § 1.1310. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties

### Antenna List

No.	Manufacturer	Model No.	Antenna Type	Peak Gain
1	Liteconn Co.,Ltd	520101-7040-23R	PCB Antenna	2.44 dBi for 2.4GHz

## 1.4 Test Facility

Items	Required (IEC 60068-1)	Actual
Temperature (°C)	15-35	25
Humidity (% RH)	25-75	65
Barometric pressure (mbar)	860-1060	1001

**Description:** Accredited by TAF

Accredited Number: 2965

**Issued by:** Wendell Industrial Co., Ltd

**Lab Address:** 6F/6F-1, No.188, Baoqiao Rd., Xindian Dist.,  
New Taipei City 23145, Taiwan (R.O.C)

**Test Lab:** Wendell EMC & RF Laboratory

**Test Location:** 1F., No. 119, Wugong 3rd Rd., Wugu Dist.,  
New Taipei City 248, Taiwan (R.O.C.)

**Designation Number:** TW0025

**Test Firm Registration Number:** 665221

## 2 Mobile device Assessment Procedure

In 47 CFR § 2.1091, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. In this context, the term “fixed location” means that the device is physically secured at one location and is not able to be easily moved to another location.

## 3 RF Exposure Assessment

Estimation of the expected exposure in power density can be made with the following equation:

$$S = \frac{P \times G}{4\pi \times R^2} = \frac{\text{EIRP}}{4\pi \times R^2}$$

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna.

EIRP: Effective Isotropic Radiated Power



## 4 Limit Requirement

In 47 CFR § 1.1310, use of the device as based upon the user's awareness and ability to exercise control over human exposure. The two categories defined are Occupational/Controlled Exposure and General Population/Uncontrolled. These two categories are defined as follow:

### Occupational/Controlled Exposure:

Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure.

### General Population/Uncontrolled:

General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

Limits for Occupational / Controlled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1,842 / f	4.89 / f	(900 / f <sup>2</sup> )*	6
30-300	61.4	0.163	1.0	6
300-1,500	--	--	f / 300	6
1,500-100,000	--	--	5	6

Note :

(1) f = frequency in MHz

(2) \* = Plane-wave equivalent power density

Limits for General Population / Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824 / f	2.19 / f	(180 / f <sup>2</sup> )*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f / 1,500	30
1,500-100,000	--	--	1.0	30

Note :

(1) f = frequency in MHz

(2) \* = Plane-wave equivalent power density

## 5 Test Results

Mode	Max. Power (E.I.R.P)		Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
	dBm	mW				
BT	9.26	8.43	20	0.00168	1.00	Pass
LE	8.65	7.33	20	0.00146	1.00	Pass
WLAN 2.4G	21.72	148.5936	20	0.02956	1.00	Pass

Note :

- \* Each Function of the max power which perform MPE of any configurations.
- \* The BT 、LE and WLAN 2.4G cannot be transmitted at the same time.
- \* The frequency (range) used by the radio frequency function is 1.5GHz~100GHz, the RF field strength limits is e.i.r.p. less than or equal to 1mW/cm<sup>2</sup>.
- \* The limit is equal to the minimum value.
- \* The Max total MPE = WLAN 2.4G = 0.02956 (mW/cm<sup>2</sup>)

--- END ---