

FCC Test Report

Report No.: AGC08791220806FE03

FCC ID : 2A8JCA5

APPLICATION PURPOSE : Original Equipment

PRODUCT DESIGNATION: Unmanned aerial vehicle

BRAND NAME : N/A

A5, A1, A2, A3, A4, A6, A7, A8, A9, A10, A11, A12, A13, A14, A15, X1, X2, X3, X4, X5, X6, X7, X8, X9, X10, X11, X12, X13, X14, X15, Q1, Q2, Q3, Q4, Q5, Q6, Q7, Q8, Q9, Q10, Q11, Q12,

MODEL NAME : Q13, Q14, Q15, M1, M2, M3, M4, M5, M6, M7, M8, M9, M10,

M11, M12, M13, M14, M15, W1, W2, W3, W4, W5, W6, W7, W8, W9, W10, W11, W12, W13, W14, W15, F1, F2, F3, F4, F5,

F6, F7, F8, F9, F10, F11, F12, F13, F14, F15

APPLICANT: TENG SU TOYS FACTORY

DATE OF ISSUE : Sep. 15, 2022

STANDARD(S)

TEST PROCEDURE(S) : FCC Part 15 Rules

REPORT VERSION : V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd





Page 2 of 32


REPORT REVISE RECORD

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Sep. 15, 2022	Valid	Initial Release




TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY	5
2. GENERAL INFORMATION	6
2.1. PRODUCT DESCRIPTION	6
2.2. TABLE OF CARRIER FREQUENCY	7
3. MEASUREMENT UNCERTAINTY	8
4. DESCRIPTION OF TEST MODES	9
5. SYSTEM TEST CONFIGURATION	10
5.1. CONFIGURATION OF EUT SYSTEM	10
5.2 EQUIPMENT USED IN TESTED SYSTEM	10
5.3. SUMMARY OF TEST RESULTS	10
6. TEST FACILITY	11
7. RADIATED EMISSION	12
7.1TEST LIMIT	12
7.2. MEASUREMENT PROCEDURE	13
7.3. TEST SETUP	15
7.4. TEST RESULT	16
8. BAND EDGE EMISSION	22
8.1TEST LIMIT	22
8.2. MEASUREMENT PROCEDURE	22
8.3 TEST SETUP	22
8.4 TEST RESULT	22
9. 20DB BANDWIDTH	27
9.1. MEASUREMENT PROCEDURE	27
9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	27
9.3. MEASUREMENT RESULTS	28
10. FCC LINE CONDUCTED EMISSION TEST	30
10.1 LIMITS OF LINE CONDUCTED EMISSION TEST	30





APPENDIX B: PHOTOGRAPHS OF THE EUT	32
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	32
10.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST	31
10.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	31
10.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	31
10.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST	30





1. VERIFICATION OF CONFORMITY

Applicant	TENG SU TOYS FACTORY	
Address	No. 23, Middle Road, Huaize Dongguahu Industrial Zone, Lianxia Town, Chenghai District, Shantou City, Guangdong Province, China	
Manufacturer	facturer TENG SU TOYS FACTORY	
No. 23, Middle Road, Huaize Dongguahu Industrial Zone, Lianxia Town, ODistrict, Shantou City, Guangdong Province, China		
Factory	TENG SU TOYS FACTORY	
Address	No. 23, Middle Road, Huaize Dongguahu Industrial Zone, Lianxia Town, Chenghai District, Shantou City, Guangdong Province, China	
Product Designation	Unmanned aerial vehicle	
Brand Name	N/A	
Test Model	A5	
Series Model	A1, A2, A3, A4, A6, A7, A8, A9, A10, A11, A12, A13, A14, A15, X1, X2, X3, X4, X5, X6, X7, X8, X9, X10, X11, X12, X13, X14, X15, Q1, Q2, Q3, Q4, Q5, Q6, Q7, Q8, Q9, Q10, Q11, Q12, Q13, Q14, Q15, M1, M2, M3, M4, M5, M6, M7, M8, M9, M10, M11, M12, M13, M14, M15, W1, W2, W3, W4, W5, W6, W7, W8, W9, W10, W11, W12, W13, W14, W15, F1, F2, F3, F4, F5, F6, F7, F8, F9, F10, F11, F12, F13, F14, F15	
Difference description	All the series models are the same as the test model except for the model names.	
Date of test	Aug. 24, 2022 to Sep. 15, 2022	
Deviation No any deviation from the test method		
Condition of Test Sample	Normal	
Test Result	Pass	
Report Template	AGCRT-US-BR/RF	

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC Rules Part 15.249.

Alan Duan (Project Engineer)

Reviewed By

Calvin Liu (Reviewer)

Approved By

Max Zhang (Authorized Officer)

Sep. 15, 2022

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/




Page 6 of 32

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

A major technical description of EUT is described as following

Operation Frequency	2420 MHz to 2473 MHz
Maximum field strength	92.72dBuV/m(average)@3m
Modulation GFSK	
Number of channels	54
Antenna Gain	0dBi
Antenna Designation Wire Antenna (Met 15.203 Antenna requirement)	
Hardware Version	V3
Software Version	V2
Power Supply	DC 4.5V by battery





2.2. TABLE OF CARRIER FREQUENCY

Channel Number	Frequency (MHz)	Channel Number	Frequency (MHz)
1	2420	28	2447
2	2421	29	2448
3	2422	30	2449
4	2423	31	2450
5	2424	32	2451
6	2425	33	2452
7	2426	34	2453
8	2427	35	2454
9	2428	36	2455
10	2429	37	2456
11	2430	38	2457
12	2431	39	2458
13	2432	40	2459
14	2433	41	2460
15	2434	42	2461
16	2435	43	2462
17	2436	44	2463
18	2437	45	2464
19	2438	46	2465
20	2439	47	2466
21	2440	48	2467
22	2441	49	2468
23	2442	50	2469
24	2443	51	2470
25	2444	52	2471
26	2445	53	2472
27	2446	54	2473



Page 8 of 32

3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

- Uncertainty of Conducted Emission, Uc = ±3.2 dB
- Uncertainty of Radiated Emission below 1GHz, Uc = ±3.9 dB
- Uncertainty of Radiated Emission above 1GHz, Uc = ±4.8 dB
- Uncertainty of Occupied Channel Bandwidth: Uc = ±2 %



Page 9 of 32

4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION	
1	Low channel GFSK	
2	Middle channel GFSK	
3	High channel GFSK	

Note:

- 1. Only the result of the worst case was recorded in the report, if no other cases.
- 2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 3. The EUT adjusts the frequency through the button.



Page 10 of 32

5. SYSTEM TEST CONFIGURATION

5.1. CONFIGURATION OF EUT SYSTEM

Radiated Emission Configure:

EUT	

5.2 EQUIPMENT USED IN TESTED SYSTEM

Iten	Equipment	Model No.	ID or Specification	Remark
1	Unmanned aerial vehicle	A5	2A8JCA5	EUT

5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.249&15.209	Radiated Emission	Compliant
§15.249	Band Edges	Compliant
§15.215	20dB bandwidth	Compliant
§15.207 Conducted Emission		Not applicable

Note: The EUT is battery operated without AC mains.



Page 11 of 32

6. TEST FACILITY

Test Site	Attestation of Global Compliance (Shenzhen) Co., Ltd
Location 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Fuhai Street, Bao'an District, Shenzhen, Guangdong, China	
Designation Number CN1259	
FCC Test Firm Registration Number	975832
A2LA Cert. No.	5054.02
Description	Attestation of Global Compliance(Shenzhen) Co., Ltd is accredited by A2LA

TEST EQUIPMENT OF RADIATED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	Mar. 28, 2022	Mar. 27, 2023
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Nov. 17, 2021	Nov. 16, 2022
2.4GHz Fliter	EM Electronics	2400-2500MHz	N/A	Mar. 22, 2022	Mar. 21, 2024
Attenuator	ZHINAN	E-002	N/A	Aug. 03, 2022	Aug. 02, 2024
Horn antenna	SCHWARZBECK	BBHA 9170	#768	Oct. 31, 2021	Oct. 30, 2023
Active loop antenna (9K-30MHz)	ZHINAN	ZN30900C	18051	Mar. 12, 2022	Mar. 11, 2024
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	Apr. 23, 2021	Apr. 22, 2023
Broadband Preamplifier	ETS LINDGREN	3117PA	00225134	Aug. 03, 2022	Aug. 02, 2024
ANTENNA	SCHWARZBECK	VULB9168	494	Jan. 08, 2020	Jan. 07, 2023



Page 12 of 32

7. RADIATED EMISSION

7.1TEST LIMIT

Standard FCC15.249

Fundamental Frequency	Field Strength of Fundamental	Field Strength of Harmonics
	(millivolts/meter)	(microvolts/meter)
900-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

Standard FCC 15.209

Frequency	Distance	Field Strengths Limit			
(MHz)	Meters	μ V/m	dB(μV)/m		
0.009 ~ 0.490	300	2400/F(kHz)			
0.490 ~ 1.705	30	24000/F(kHz)			
1.705 ~ 30	30	30			
30 ~ 88	3	100	40.0		
88 ~ 216	3	150	43.5		
216 ~ 960	3	200	46.0		
960 ~ 1000	3	500	54.0		
Above 1000	3	Other:74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)			

Remark:

- (1) Emission level dB μ V = 20 log Emission level μ V/m
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.



Report No.: AGC08791220806FE03 Page 13 of 32

7.2. MEASUREMENT PROCEDURE

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use minimum resolution bandwidth of 1 MHz. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8.If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.



Page 14 of 32

The following table is the setting of spectrum analyzer and receiver.


Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
	1GHz~26.5GHz
Start ~Stop Frequency	RBW 2.4MHz/ VBW 8MHz for Peak,
	RBW 2.4MHz/10Hz for Average

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP




7.3. TEST SETUP


Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz






7.4. TEST RESULT

RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION 30MHz-1GHZ

EUT:	Unmanned aerial vehicle	Model Name. :	A5
Temperature:	20℃	Relative Humidity:	52%
Pressure:	1010 hPa	Test Voltage :	DC 4.5V
Test Mode :	Mode 1	Polarization :	Horizontal




No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		60.4919	5.66	16.22	21.88	40.00	-18.12	peak
2		140.8351	5.68	19.58	25.26	43.50	-18.24	peak
3		202.8104	5.32	19.80	25.12	43.50	-18.38	peak
4		281.9946	5.44	21.49	26.93	46.00	-19.07	peak
5		383.9318	7.98	22.68	30.66	46.00	-15.34	peak
6	*	922.5157	6.13	30.76	36.89	46.00	-9.11	peak

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



EUT:	Unmanned aerial vehicle	Model Name. :	A5
Temperature:	20℃	Relative Humidity:	52%
Pressure :	1010 hPa	Test Voltage :	DC 4.5V
Test Mode :	Mode 1	Polarization:	Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		40.4172	6.32	16.02	22.34	40.00	-17.66	peak
2		69.1141	6.37	18.09	24.46	40.00	-15.54	peak
3		118.6014	6.97	18.62	25.59	43.50	-17.91	peak
4		383.9318	8.11	19.22	27.33	46.00	-18.67	peak
5		645.1195	7.20	25.49	32.69	46.00	-13.31	peak
6	*	900.1474	6.08	34.64	40.72	46.00	-5.28	peak

RESULT: PASS

Note:

Factor=Antenna Factor + Cable loss, Over=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system.



Report No.: AGC08791220806FE03 Page 18 of 32

FIELD STRENGTH OF FUNDAMENTAL

EUT:	Unmanned aerial vehicle	Model Name. :	A5
Temperature:	25 ℃	Relative Humidity:	52%
Pressure :	1010 hPa	Test Voltage :	DC 4.5V
Test Modulation :	GFSK	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type	
2420	106.95	-9.61	97.34	114.00	-16.66	peak	
2420	102.33	-9.61	92.72	94.00	-1.28	AVG	
2450	96.94	-9.61	87.33	114.00	-26.68	peak	
2450	93.45	-9.61	83.84	94.00	-10.16	AVG	
2473 103.69 -9.61 94.08 114.00 -19.92 peak							
2473 98.89 -9.61 89.28 94.00 -4.72 AVG							
Remark:							
Factor = Ante	Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

EUT:	Unmanned aerial vehicle	Model Name. :	A5
Temperature:	25 ℃	Relative Humidity:	52%
Pressure :	1010 hPa	Test Voltage :	DC 4.5V
Test Modulation :	GFSK	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type	
2420	106.06	-9.61	96.45	114.00	-17.55	peak	
2420	101.60	-9.61	91.99	94.00	-2.01	AVG	
2450	91.24	-9.61	81.63	114.00	-32.37	peak	
2450	88.44	-9.61	78.83	94.00	-15.17	AVG	
2473	102.13	-9.61	92.52	114.00	-21.48	peak	
2473 97.11 -9.61 87.50 94.00 -6.50 AVG							
Remark:							
Factor = Ante	Factor = Antenna Factor + Cable Loss – Pre-amplifier.						



Report No.: AGC08791220806FE03 Page 19 of 32


RADIATED EMISSION ABOVE 1GHZ

EUT:	Unmanned aerial vehicle	Model Name. :	A5
Temperature:	25 ℃	Relative Humidity:	52%
Pressure :	1010 hPa	Test Voltage :	DC 4.5V
Test Mode :	Mode 1	Polarization:	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4840	48.71	3.76	52.47	74.00	-21.53	peak
4840	43.49	3.76	47.25	54.00	-6.75	AVG
7260	42.55	8.17	50.72	74.00	-23.28	peak
7260 38.67 8.17 46.84 54.00 -7.16 AVG						
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

EUT:	Unmanned aerial vehicle	Model Name. :	A5
Temperature:	25 ℃	Relative Humidity:	52%
Pressure :	1010 hPa	Test Voltage :	DC 4.5V
Test Mode :	Mode 1	Polarization:	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type	
4840	47.93	3.76	51.69	74.00	-22.31	peak	
4840	43.85	3.76	47.61	54.00	-6.39	AVG	
7260	42.14	8.17	50.31	74.00	-23.69	peak	
7260 37.55 8.17 45.72 54.00 -8.28 AVG							
Remark:							
Factor = Antenna Factor + Cable Loss – Pre-amplifier.							






EUT:	Unmanned aerial vehicle	Model Name. :	A5
Temperature:	25℃	Relative Humidity:	52%
Pressure :	1010 hPa	Test Voltage :	DC 4.5V
Test Mode :	Mode 2	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type	
4900	47.22	3.78	51.00	74.00	-23.00	peak	
4900	43.53	3.78	47.31	54.00	-6.69	AVG	
7350	43.85	8.23	52.08	74.00	-21.92	peak	
7350 39.59 8.23 47.82 54.00 -6.18 AVG							
Remark:							
Factor = Ante	Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

EUT:	Unmanned aerial vehicle	Model Name. :	A5
Temperature:	25 ℃	Relative Humidity:	52%
Pressure :	1010 hPa	Test Voltage :	DC 4.5V
Test Mode :	Mode 2	Polarization:	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type	
4900	48.98	3.78	52.76	74.00	-21.24	peak	
4900	42.63	3.78	46.41	54.00	-7.59	AVG	
7350	44.15	8.23	52.38	74.00	-21.62	peak	
7350	7350 39.97 8.23 48.20 54.00 -5.80 AVG						
Remark:							
Factor = Antenna Factor + Cable Loss – Pre-amplifier.							





EUT:	Unmanned aerial vehicle	Model Name. :	A5
Temperature:	25 ℃	Relative Humidity:	52%
Pressure :	1010 hPa	Test Voltage :	DC 4.5V
Test Mode :	Mode 3	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4946	47.84	3.81	51.65	74.00	-22.35	peak
4946	44.23	3.81	48.04	54.00	-5.96	AVG
7419	42.18	8.27	50.45	74.00	-23.55	peak
7419 38.63 8.27 46.90 54.00 -7.10 AVG						
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

EUT:	Unmanned aerial vehicle	Model Name. :	A5
Temperature:	25 ℃	Relative Humidity:	52%
Pressure:	1010 hPa	Test Voltage :	DC 4.5V
Test Mode :	Mode 3	Polarization:	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type	
4946	48.63	3.81	52.44	74.00	-21.56	peak	
4946	43.17	3.81	46.98	54.00	-7.02	AVG	
7419	44.52	8.27	52.79	74.00	-21.21	peak	
7419	7419 40.26 8.27 48.53 54.00 -5.47 AVG						
Remark:							
Factor = Antenna Factor + Cable Loss – Pre-amplifier.							

Note: Other emissions from 8G to 25 GHz are considered as ambient noise. No recording in the test report. Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Level-Limit.

The "Factor" value can be calculated automatically by software of measurement system.



8. BAND EDGE EMISSION

8.1TEST LIMIT


	Limit of the Field Strength (dBμV/m)	
Frequency Band	Peak	Average
f≤2390MHz	74	54
f≥2483.5MHz	74	54

8.2. MEASUREMENT PROCEDURE

- 1. The EUT operates at transmitting mode. The operate channel is tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.
- 2. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission: (a) PEAK: RBW=1MHz, VBW=3MHz / Sweep=AUTO
- (b) AVERAGE: RBW=1MHz; VBW=1/on time(1KHz) / Sweep=AUTO
- 3. Other procedures refer to clause 7.2.

8.3 TEST SETUP


RADIATED EMISSION TEST SETUP



8.4 TEST RESULT


Note:

- 1. Factor=Antenna Factor + Cable loss Amplifier gain. Field Strength=Factor + Reading level
- 2. The factor had been edited in the "Input Correction" of the Spectrum Analyzer. So the Amplitude of test plots is equal to Reading level plus the Factor in dB. Use the A dB(μ V) to represent the Amplitude. Use the F dB(μ V/m) to represent the Field Strength. So A=F.







EUT:	Unmanned aerial vehicle	Model Name. :	A5
Temperature:	25 ℃	Relative Humidity:	52%
Pressure:	1010 hPa	Test Voltage :	DC 4.5V
Test Mode :	Mode 1	Polarization :	Horizontal




Average Value








EUT:	Unmanned aerial vehicle	Model Name. :	A5
Temperature:	25 ℃	Relative Humidity:	52%
Pressure:	1010 hPa	Test Voltage :	DC 4.5V
Test Mode :	Mode 1	Polarization :	Vertical




Average Value







EUT:	Unmanned aerial vehicle	Model Name. :	A5
Temperature:	25 ℃	Relative Humidity:	52%
Pressure :	1010 hPa	Test Voltage :	DC 4.5V
Test Mode :	Mode 3	Polarization :	Horizontal




Average Value









EUT:	Unmanned aerial vehicle	Model Name. :	A5
Temperature:	25℃	Relative Humidity:	52%
Pressure :	1010 hPa	Test Voltage :	DC 4.5V
Test Mode :	Mode 3	Polarization :	Vertical



Average Value









9. 20DB BANDWIDTH

9.1. MEASUREMENT PROCEDURE

- 1. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 2. Set SPA Centre Frequency = Operation Frequency, RBW= 30 KHz, VBW ≥ 3 × RBW.
- 3. Set SPA Trace 1 Max hold, then View.

9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)








9.3. MEASUREMENT RESULTS

TEST ITEM	20DB BANDWIDTH
TEST MODULATION	GFSK

Test Data (MHz)		Criteria
Low Channel	1.297	PASS
Middle Channel	1.294	PASS
High Channel	1.295	PASS

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL






TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



10. FCC LINE CONDUCTED EMISSION TEST


10.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Francisco	Maximum RF Line Voltage	
Frequency	Q.P.(dBuV)	Average(dBuV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50MHz.

10.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST





Report No.: AGC08791220806FE03 Page 31 of 32

10.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipments received AC120VV/60Hz power from a LISN, if any.
- 5. The EUT received charging voltage by adapter which received 120V/60Hzpower by a LISN..
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.


10.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.

10.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

N/A

Note: The EUT is battery operated without AC mains.





APPENDIX A: PHOTOGRAPHS OF TEST SETUP

Refer to the Report No.: AGC08791220806AP01

APPENDIX B: PHOTOGRAPHS OF THE EUT

Refer to the Report No.: AGC08791220806AP02

----END OF REPORT----



Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd. (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.