

Report No.: TBR-C-202311-0363-8
Page: 1 of 4

Maximum Permissible Exposure Evaluation

FCC ID: 2A8O2-SMYC40

1. Client Information

Applicant	:	Shenzhen Senma Utrend Technology Co., Ltd.
Address	:	Floor 2, Building 9, Rundongsheng Industrial Zone, No. 467, Section Xixiang, 107 National Road, Longteng Community, Xixiang Street, Bao'an District, Shenzhen, China
Manufacturer	:	Shenzhen Senma Utrend Technology Co., Ltd.
Address	:	Floor 2, Building 9, Rundongsheng Industrial Zone, No. 467, Section Xixiang, 107 National Road, Longteng Community, Xixiang Street, Bao'an District, Shenzhen, China

2. General Description of EUT

EUT Name	3D Printer		
Models No.	SMYC40, SMYC40 Pro, SMYC60		
Model Different	All these models are identical in the same PCB, layout and electrical circuit, the only difference is Different names, different customers.		
Product Description	Operation Frequency:	Bluetooth LE V5.0 2402MHz~2480MHz 802.11b/g/n(HT20): 2412MHz~2462MHz 802.11n(HT40): 2422MHz~2452MHz	
	Antenna Gain:	5.54dBi FPC Antenna	
Power Rating	:	Adapter(TS-A053-2402201) Input: 100-240V~50/60Hz 1.5A Output: 24.0V/2.2A 52.8W	
Software Version	:	V1.0.0	
Hardware Version	:	V3.4	
Connecting I/O Port(S)	:	Please refer to the User's Manual	
Remark	:	the evaluation report used the EUT(HC-C-202311-0363-02-01-2#).	

TB-RF-074-1.0

Method of Measurement for FCC

1. EUT Operation Condition:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

2. Exposure Evaluation:

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = (PG) / 4\pi R^2$$

Where

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna

3. Simultaneous transmission MPE Considerations

According to KDB447498: All transmitters and antennas in the host must be either evaluated for MPE compliance, by measurement or computational modeling, or qualify for the standalone MPE test exclusion in section 7.1. Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0 .

This means that:

$$\sum \text{MPE ratios} \leq 1.0$$



4. Test Result:

Bluetooth LE Worst Maximum MPE Result								
Mode	N _{TX}	Freq. (MHz)	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/cm ²) [S]
GFSK-1M	1	2402	4.971	4±1	5	5.54	20	0.00225
		2440	4.815	4±1	5	5.54	20	0.00225
		2480	4.783	4±1	5	5.54	20	0.00225
GFSK-2M	1	2402	4.915	4±1	5	5.54	20	0.00225
		2440	4.855	4±1	5	5.54	20	0.00225
		2480	4.692	4±1	5	5.54	20	0.00225

Note:

N_{TX}= Number of Transmit Antennas
 RF Output power specifies that Maximum Conducted Peak Output Power.

2.4G WiFi Worst Maximum MPE Result								
Mode	N _{TX}	Freq. (MHz)	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/cm ²) [S]
802.11b	1	2412	16.53	16±1	17	5.54	20	0.0357
		2437	16.38	16±1	17	5.54	20	0.0357
		2462	16.37	16±1	17	5.54	20	0.0357
802.11g	1	2412	13.70	13±1	14	5.54	20	0.0179
		2437	16.06	16±1	17	5.54	20	0.0357
		2462	13.96	13±1	14	5.54	20	0.0179
802.11n (HT20)	1	2412	13.12	13±1	14	5.54	20	0.0179
		2437	14.26	14±1	15	5.54	20	0.0225
		2462	12.57	12±1	13	5.54	20	0.0142
802.11n (HT40)	1	2422	11.52	11±1	12	5.54	20	0.0113
		2437	14.40	14±1	15	5.54	20	0.0225
		2452	10.49	10±1	11	5.54	20	0.0089

Note:

N_{TX}= Number of Transmit Antennas
 RF Output power specifies that Maximum Conducted Peak Output Power.



5. Conclusion:

As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),

Limits for General Population/ Uncontrolled Exposure

Frequency Range (MHz)	Power density (mW/ cm ²)
300-1,500	F/1500
1,500-100,000	1.0

For Bluetooth LE&2.4G WIFI: 2402MHz~2480MHz&2412MHz~2462MHz

MPE limit S: 1mW/ cm²

The worst MPE is calculated as **0.0357mW/cm² < limit 1mW/cm²**. So, RF exposure limit warning or SAR test are not required. The EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47 CFR2.1091 (b).

The RF Exposure Information page from the manual is included here for reference.

For a more detailed features description, please refer to the RF Test Report.

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----END OF THE REPORT-----

