



MPE/RF EXPOSURE REPORT

FCC CFR 47 Part 1.1310

Report No.: RFXP01-U3 Rev A

Company: Drum Workshop

Model: DWE-DLM-1

MPE/RF EXPOSURE REPORT

Company: Drum Workshop

Model: DWE-DLM-1

To: FCC CFR 47 Part 1.1310

Test Report Serial No.: RFXP01-U3 Rev A

This report supersedes: NONE

Applicant: Drum Workshop
3450 Lunar Ct
Oxnard, California 93030
USA

Issue Date: 21st November 2022

This Report is Issued Under the Authority of:

MiCOM Labs, Inc.
575 Boulder Court
Pleasanton California 94566
USA
Phone: +1 (925) 462-0304
Fax: +1 (925) 462-0306
www.micomlabs.com



MiCOM Labs is an ISO 17025 Accredited Testing Laboratory

1. MAXIMUM PERMISSABLE EXPOSURE

Calculations for Maximum Permissible Exposure Levels

$$\text{Power Density} = P_d (\text{mW/cm}^2) = \text{EIRP} / (4 * \pi * d^2)$$

$$\text{EIRP} = P * G$$

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

$$\text{Numeric Gain} = 10 ^ { (G (\text{dBi}) / 10)}$$

The calculations in the table below use the highest conducted power values together with the highest antenna gain specified for the EUT. These calculations represent worst case in terms of the exposure levels.

The following technologies never operate simultaneously

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density (mW/cm ²) @ 20cm	Power Density Limit (mW/cm ²)	Min Calculated safe distance for Limit (cm)
2400.0 - 2483.5	2.82	1.91	8.35	6.84	0.003	1.00	1.02

NOTE: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

Specification - Maximum Permissible Exposure Limits

The Limit is defined in Table 1 of FCC §1.1310.

FCC CFR 47 Part 1.1310 Power Density Limits for General Population/Uncontrolled Exposure:

300-1,500 MHz; Power Density = $f / 1500 \text{ mW/cm}^2$

1,500-100,000 MHz; Power Density = 1.0 mW/cm^2

f = frequency in MHz.



575 Boulder Court
Pleasanton, California 94566, USA
Tel: +1 (925) 462 0304
Fax: +1 (925) 462 0306
www.micomlabs.com