



RF EXPOSURE REPORT FOR FCC

RZBG(W) 20230110001-5

Applicant : Zhejiang Tianze Communication Technology Co., Ltd
Address : 8F, 3760 Nanhuan Road, Binjiang District, Hangzhou ,Zhejiang,
China
Product Name : T900
Type/Model : T900-30-IPEX
FCC ID : 2A9NZ-T900
TEST RESULT : PASS

SUMMARY

The equipment complies with the requirements according to the following standard(s):

FCC KDB 447498 D04: Interim General RF Exposure Guidance v01

Date of issue: Apr. 12, 23

Prepared by

Hao Wei (Project engineer)

Hao Wei

Reviewed by:

Haohui Qiu (Reviewer)

Haohui Qiu

Issued by

Bing Cai (General Manager)

Bing Cai





Content

SUMMARY	1
CONTENT	2
1. GENERAL INFORMATION OF EUT	3
1.1 Applicant information	3
1.2 Manufacture information	3
1.3 General description for equipment under test(EUT)	3
1.4 Technical information of equipment under test (EUT)	4
2. DESCRIPTION OF TEST FACILITY	5
3. SUMMARY OF TEST RESULT	6
3.1 Test standard	6
4. DEVICE CATEGORY AND LEVELS LIMITS	7
5. MPE ASSESSMENT	10
ANNEX A REVISION HISTORY	11



1. GENERAL INFORMATION OF EUT

1.1 Applicant information

Applicant	Zhejiang Tianze Communication Technology Co., Ltd
Address	8F, 3760 Nanhuan Road, Binjiang District, Hangzhou , Zhejiang, China
Contact person	Shanxue Ke
Phone number	+86 571 28118173

1.2 Manufacture information

Manufacture	Zhejiang Tianze Communication Technology Co., Ltd
Address	8F, 3760 Nanhuan Road, Binjiang District, Hangzhou , Zhejiang, China

1.3 General description for equipment under test(EUT)

EUT name	T900
Trade name	TianZe
Under test mode name	T900-30-IPEX
Series model name	N/A
Description of different model name	N/A
Hardware version	60136C-30-IPEX
Software version	0030-20221017-0A
Network and Wireless connectivity	902MHz-928MHz



1.4 Technical information of equipment under test (EUT)

The requirement for the following technical information of the EUT was tested in this report:

Test channel	57600bps: Low(902.3 MHz), Middle (914.9MHz), High(927.5MHz) 172800bps: Low(902.3 MHz), Middle (915.05MHz), High(927.8MHz) 230400bps: Low(902.3 MHz), Middle (915.06MHz), High(927.82MHz) 276400bps: Low(902.3 MHz), Middle (914.9MHz), High(927.5MHz)
Modulation Technology	FHSS
Modulation Type	GFSK
FCC ID	2A9NZ-T900
Equipment type	<input checked="" type="checkbox"/> Mobile <input type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Transfer Rate	57600kbps, 115200kbps,172800kbps, 230400kbps, 276400kbps
Frequency Range	The frequency range used is 902 MHz to 928 MHz.
Number of Channel	57600bps:127 115200bps:127 172800bps: 103 230400bps: 89 276400bps: 73
Maximum RF Output Power(dBm)	57600kbps:27.76 172800kbps:27.48 230400kbps:27.42 276400kbps:26.52
Antenna Type	Rubber rod antenna
Antenna Gain	2.5dbi

Note:The antenna gain is obtained from the antenna specification provided by the customer.



2. DESCRIPTION OF TEST FACILITY

<input checked="" type="checkbox"/> Company Name	Hangzhou TDT Technologies Co., Ltd.
Address	Room 101, Building 3, No. 12, Binwen Road, Xixing Street, Binjiang district, Hangzhou, Zhejiang, China
Telephone	+86571-88317620
Telefax	+86571-88316350
Test Location	Hangzhou TDT Technologies Co., Ltd.
Address	Room 101, Building 3, No. 12, Binwen Road, Xixing Street, Binjiang district, Hangzhou, Zhejiang, China
Telephone	+86571-88317620
Telefax	+86571-88316350
A2LA Certification number	4037.01
CNAS Certification number	CNAS L7728
VCCI Site registration number	C-14683, G-10832, R-14200, T-12223
FCC Site registration number	645845

Announce:

- 1 The test report reference to the report template version v1.0
- 2 The test report is invalid if not marked with the signatures of the persons responsible For preparing and approving the test report.
- 3 The test report is invalid if there is any evidence and/or falsification.
- 4 The result documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein
- 5 Content of the test report, in part or in full, cannot be used for publicity and/or promotional purpose without prior written approval from the laboratory
- 6 This document may not be altered or revised in any way unless done so by TDT Technologies Co., Ltd and all revisions are duly noted in the revisions section.
This test report of test results only related to testing samples, which can be duplicated completely for the legal use with the approval of the applicant; The laboratory be responsible for all the information provided in the report, except when
- 7 information is provided by the customer. it shall not be reproduced except in full, without the written approval of Hangzhou TDT Technologies Co., Ltd. Any objections should be raised within thirty days from the date of issue. To validate the report, please contact us.



3. SUMMARY OF TEST RESULT

3.1 Test standard

No.	Identify	Document title
1	47 CFR Part 15 Sub-part 2.1091	Radio frequency radiation exposure evaluation: mobile devices
2	FCC KDB 447498 D04	Interim General RF Exposure Guidance v01



4. DEVICE CATEGORY AND LEVELS LIMITS

According to FCC §§1.1307 and KDB 447498 D04, the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW).

The definition of the category as following:

1) Option A. 1-mW Test Exemption

Per § 1.1307(b)(3)(i)(A), a single RF source is exempt RF device (from the requirement to show data demonstrating compliance to RF exposure limits, as previously mentioned) if the available maximum time-averaged power is no more than 1 mW, regardless of separation distance.

This exemption applies to all operating configurations and exposure conditions, for the frequency range 100 kHz to 100 GHz, regardless of fixed, mobile, or portable device exposure conditions. This is a standalone exemption, and it cannot be applied in conjunction with any other test exemption.

2) Option B. SAR-Based Exemption

A more comprehensive exemption, considering a variable power threshold that depends on both the separation distance and power, is provided in § 1.1307(b)(3)(i)(B). This exemption is applicable to the frequency range between 300 MHz and 6 GHz, with test separation distances between 0.5 cm and 40 cm, and for all RF sources in fixed, mobile, and portable device exposure conditions.

Accordingly, a RF source is considered an RF exempt device if its available maximum time-averaged (matched conducted) power or its effective radiated power (ERP), whichever is greater, are below a specified threshold.

This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

11/29/2021

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B. 2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).

The example values shown in Table B.2 are for illustration only.



Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B. 1})$$

3) Option C MPE-Based Exemption

An alternative to the SAR-based exemption is provided in § 1.1307(b)(3)(i)(C), for a much wider frequency range, from 300 kHz to 100 GHz, applicable for separation distances greater or equal to $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. The MPE-based test exemption condition is in terms of ERP, defined as the product of the maximum antenna gain and the delivered maximum time-averaged power. For this case, a RF source is an RF exempt device if its ERP (watts) is no more than a frequency-dependent value, as detailed tabular form in Appendix B. These limits have been derived based on the basic specifications on Maximum Permissible Exposure (MPE) considered for the FCC rules in § 1.1310(e)(1).

**TABLE B.1—THRESHOLDS FOR SINGLE RF SOURCES
SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION**

RF Source Frequency			Minimum Distance			Threshold ERP
f_L MHz		f_H MHz	$\lambda_L / 2\pi$		$\lambda_H / 2\pi$	W
0.3	–	1.34	159 m	–	35.6 m	$1,920 R^2$
1.34	–	30	35.6 m	–	1.6 m	$3,450 R^2/f^2$
30	–	300	1.6 m	–	159 mm	$3.83 R^2$
300	–	1,500	159 mm	–	31.8 mm	$0.0128 R^2 f$
1,500	–	100,000	31.8 mm	–	0.5 mm	$19.2 R^2$
Subscripts L and H are low and high; λ is wavelength. From § 1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.						



Either SAR-based or MPE-based exemption may be considered for test exemption for fixed, mobile, or portable device exposure conditions; therefore, the contributions from each exemption in conjunction with the measured SAR (*Evaluated_k* term) shall be used to determine exemption for simultaneous transmission according to Formula (C.1) [repeated from § 1.1307(b)(3)(ii)(B)].

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1 \quad (C.1)$$

- a* number of fixed, mobile, or portable RF sources claiming exemption using the § 1.1307(b)(3)(i)(B) formula for P_{th} , including existing exempt transmitters and those being added.
- b* number of fixed, mobile, or portable RF sources claiming exemption using the applicable § 1.1307(b)(3)(i)(C) Table 1 formula for Threshold ERP, including existing exempt transmitters and those being added.
- c* number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance.
- P_i the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source *i* at a distance between 0.5 cm and 40 cm (inclusive).
- $P_{th,i}$ the exemption threshold power (P_{th}) according to the § 1.1307(b)(3)(i)(B) formula for fixed, mobile, or portable RF source *i*.
- ERP_j the available maximum time-averaged power or the ERP, whichever is greater, of fixed, mobile, or portable RF source *j*.
- $ERP_{th,j}$ exemption threshold ERP for fixed, mobile, or portable RF source *j*, at a distance of at least $\lambda/2\pi$, according to the applicable § 1.1307(b)(3)(i)(C) Table 1 formula at the location in question.
- Evaluated_k* the maximum reported SAR or MPE of fixed, mobile, or portable RF source *k* either in the device or at the transmitter site from an existing evaluation.
- Exposure Limit_k* either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable sources, as applicable



5. MPE ASSESSMENT

Output power test data

2.4G WIFI		
Mode	57600kbps	172800kbps
	Out put power	Out put power
output power (dBm)	27.76	27.48
Mode	230400kbps	276400kbps
	Out put power	Out put power
output power (dBm)	27.42	26.52
Note: This report listed the worst case peak output power value, please refer to RF test report for more details.		

Assessment result

Evolution mode	Freq (MHz)	Maximum output power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	Maximum ERP (dBm)	Distance (mm)	Maximum ERP (mw)	Threshold ERP Limit (mw)
57600kbps	927.5	30	2.5	32.5	30.35	250	1084	1200

Note:Maximum power according to customer claims

Conclusion:

RF exposure evaluation results: **Compliance**

Note:

1. Output power including tune up tolerance.
2. More power list please refer to RF test report.



Annex A Revision History

Version	Issue Date	Revisions Content
Rev.01	Mar.20.2023	Initial Issue

-----END-----