# 80X80mm



T010



Please read this user manual thoroughly before using the product.

- Medical purpose
   The hearing aid intends to compensate for impaired hearing.
   Intended patients and environment
   The hearing aid uses for indoor and outdoor environment, and patients under 18 years old must require the doctors's approval.

## PRODUCT PROFILE Touch Panel ---

Contacts	Charging Case Indicator Light	Type-C USB Cable Outle

magnetic Charging	Contacts Charg	ng Case Indicator Light Ty	pe-C USB Cable Outlet
IN THE PAC	KAGE		
Name	Quantity	Name	Quantity
User Manual	1	In-Ear Tip L	2
Hearing aids	2	In-Ear Tip S	2
Charging Case	1	Charging Cable	1

the following icon or search "amplifier" from Google Play.



In the incoming call state, short press the LorR touch panel for 1 second to connect the incoming call. In the call state, long press the L or R touch panel for 2 seconds to hang up the call.

Reject the call Flect the Carl. In the incoming call state, long press the Lor R touch panel for 2 seconds to reject the incoming call.

- ①Calling volume needs to be manually adjusted by phone volume,
- ② 🎜 Music playing function needs to be manually adjusted by phone, 3The volume of music playing is also amplified according to the hearing amplifier standard, Please follow the normal listening

### volume to adjust to your own volume, too much volume will further damage your hearing.

FCC STATEMENT:

(1) This device may not cause harmful interference, and

Warning: Changes or modifications not expressly approved by the party

responsible for compliance could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a

agianst harmful interference in a residential installation. This equipment generate uses and can radiate radio frequency energy and, if not installed and used in


If this equipment does cause harmful interference to radio or television reception.

Increase the separation between the equipment and receiver. Connect the equipment into an outlet on a circuit different from that to which the

Consult the dealer or an experienced radio/TV technician for help

### **INTENDED USE**

- -For patients with sensitive skin, the silicone material may irritate your ear canals -First use may cause slight pain to the ear canal due to maladjestment.



tic Charging Contacts	Charging Case Indicator Light	Type-C USB Cable Outle
PACKAGE		

Name	Quantity	Name	Quantity
User Manual	1	In-Ear Tip L	2
Hearing aids	2	In-Ear Tip S	2
Charging Case	1	Charging Cable	1


### How to download the APP.

1.APP can be installed on Android phones by scanning the following QR code with



2.APP can be installed on Apple phones by scanning the following QR code with the following icon or search "BT -Amplifier" from the Apple Store





PERFÖRMANCE PARAMETE RS

115dB

8mA

BT5.0

SBC.AAC

>10M

>6 Hours

>18Hours

DC3.7V

DC 5V/1 A

3.7V/50 mAh

3.7V/400mAh

35±3dB

30dB±3dB

250 Hz-6500 Hz

Product Model

Output.OSPL90 Max

Frequency Range(Not narrower than

FOG50 MAX Gain

Working Current

Bluetooth

Music Model

Standby Time

Charging Port

Charging In-put

Total Harmonic Distort

Hearing Aid Battery Level

Charging Case Battery Level

EQ Input Noise



(3) Click Search Device to start searching, select " T010" from your device as shown in (Figure 3), and then click to connect it in (Figure 4).

Notice: The above parameter index testing is on basis of FONIX8000 Hearing Aid Test System; Inspection standard: IEC 60118-72005, 2CC ooupling cavity SB-1.




(3)



## CHARGING HEARING AMPLIFIERS

PUT the devices into the charging case, close the lid, connect the cable and charge for  $2.7\,\mathrm{hours}$ . Your devices can be charged at any time by returning them to the portable charging case,the chargingcase can hold 2.5 times full charges and both hearing amplifiers can befully recharged in around 2 hours.



### Note: Please fully charge the hearing amplifier when using for the first time. NOTES:

1. When hearing amplifiers are charging, the two indicator lights will still on, 2. When hearing amplifiers are fully charged, the two indicator lights will go off. 3. When the power of the hearing amplifiers are low, pls charge will be broadcast every 2 minutes.

4.When charging case is charging, the red indicator lightwill still on.

5. When charging case is fully charged, the blue indicator light will still on. 6. When you are not using the hearing amplifier, please put them back into

the charging case to charge.

7. For the first time using, we recommend that fully charge your hearing amplifier first.

This device has Outdoor mode, Indoor mode, Normal mode can be chose, you can

choose the right mode according to your environment as below shown in (Figure 1).

(2) votable Collitors.

The Volume of the Left or Right Hearing Amplifier can be adjusted by sliding up and down the knob, you can adjust the most suitable volume according to your hearing condition as below shown in (Figure 2).

## WEARING YOUR MEARING AMPLIFIERS

Remove the devices from the case and grasp it from the sides.
 Pinch the urethane ear tip with your fingers so it shrinks, it will expand once fit into your ear, creating a tight fit.

③ Insert the devices into yourear canal, gently twisting and rotating them to ensure a deep and secure fit.





When Hearing Amplifiers turn on, you may hear a beeping sound.
 The beeping sound will stop once it is correctly inserted into thee ar.

Note: The Hearing Amplifiers are installed on M model ear tips. please choose the right eartips to use according to your need.



(4) Far Protection

(3)Frequency Response Adjustment: The Frequency Response of the Left or Right Hearing Amplifiercan be adjusted by

This APP comes with hearing protection function, excessive external or harsh nois

rins are comes with meaning protection function, excessive external of harsh not can be compressed by slding the bar switch to the left or right to achieve the best hearing aids effect as below shown in (Figure 2).

sliding up and down the knob to achieve the best hearing aids effect as below


① Ensure the Hearing Amplifier has power or full power,  $\ensuremath{\texttt{2}} \ensuremath{\texttt{Ensure}} \ensuremath{\texttt{the}} \ensuremath{\texttt{ear}} \ensuremath{\texttt{tipsare}} \ensuremath{\texttt{firmly}} \ensuremath{\texttt{fixed}},$ 3 Ensurethe Hearing Amplifiersturnon;

(4) If the Hearing Amplifiers fail to turn on pleaseput themback into the charging case and cover the lid to charge, and repeat the first step again.

## /!\ Caution:

Hold the Hearing Amplifier in your hand, if it produces whistling (beeping), it means the Hearing Amplifier is working properly.

### HEARING AMPLIFIER VOLUME CONT




①You can touch the left and right Hearing Amplifier to control the volume of them.

②The volume of the two Hearing Amplifiers are independent adjustment, please adjust each one separately when using: 3 The Hearing Amplifiers have a memory function, It will automatically return to the volume you used before when using it next time: Factory default for Hearing Amplifiers are Maximum Volume,

## PAIRING BLUETOOTH

Open the charging case, the device will automatically enter into Bluetooth pairling mode, select "H010" from the Bluetooth list of your device and click to connect.



## IMPORTANT NOTICE FOR PROSPECTIVE HEA

Important Safety Precautions The following section contains important information regarding safe use. Please read the following carefully before using

- Never attempt to disassemble,remodelor repair the product yourself. (There is a possibility of fire and/or injury.)
- 2. Do not use an unnecessarily loud volume.
  Use at a high volume for extended periods of time may cause hearing loss or exacerbate existing hearing loss.
- 3. Do not expose this product to water, liquids, or moisture. Do not use wet hands to handle the product.

  Contact with liquids may result in electrical shock, failure
- 4. Do not attempt to use outlets or outleet strips that would exceed the safe, rated value... Overloading an electrical circuit can result in fires.
- 5. Do not hit, crush, or use excessive force with the product. Also, do not handle the parts roughly, such as forcibly Rough and improper use can cause damage, electric shock, fire, and accidents.

- 6. If you experience or notice any of the following, stop using the product immediately, ignoring the following and continuit to use the product may cause unexpected accidents and injuries. The product is broken or degraded. The product is damaged by chemicals. The product is deformed by heat.
- Use of the product in the following ways can cause unexpected accidents, injuries, or physical damage. Do not all ow children or people who require supervision to use.
- B. Furthermore, the product contains small pieces which should be kept out of reach of children due to choking hazards.

  Do not lend or borrow this product. Do not continue to use if broken or damaged. Do not use while sleeping.

	Consult instructions for using
Å	B type applied part
X	Disposal  Please dispose of the device under the directive 2002/98/EC-WEEE(Waste Electrical and Electronic Equipment) and Don't dispose with domestic weste
Δ	Warning/Danger: Improper use might cause serious injuries.
IP41	IP code of the device: this device's grade of against ingress of solid foreign objects- the access probe of 2,5 mm Ø shall not penetrate; the grade of waterproof is vertically falling drops shall have no harmful offects.

PHONE CALL

Answer the call

Hang up the Call

This device complies with Part 15 of the FCC Rules. Operation is subject to the

(2) This device must accept any interference received, including interference

Class B digital device, pursuant to
Part 15 of the FCC Rules. These limits are designed to provide reasonable protection

accordance with the instructions, may cause harmful interference to radio However, there is no guarantee that interference will not occur in a particular installation

which can be determined by tuming the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

Reorient or relocate the receiving antenna.

**(4)** 

Q

(1) Mode Selection









• • •