

SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR221200049302

Page: 1 of 8

Human Exposure Report

Application No.: FYCR2212000493BA

Applicant: VLC DISTRIBUTION COMPANY, LLC

Address of Applicant: 16255 Port Northwest Dr Suite 150, Houston, Texas 77041 United States

Manufacturer: VLC DISTRIBUTION COMPANY, LLC

Address of Manufacturer: 16255 Port Northwest Dr Suite 150, Houston, Texas 77041 United States

Factory: Hunan Hametech Technology Co., Limited

Address of Factory: 1-5 Building, Innovation Science Park, High Tech. Industrial Development

District, Wuxi Town, Luxi, Hunan, China

Equipment Under Test (EUT):

EUT Name: Power Bank
Model No.: CORE 10
Trade Mark: Duracell

FCC ID: 2A9OH-DMPCORE10

Standards: 47 CFR PART 1, Subpart I, Section 1.1310

47 CFR PART 2, Subpart J, Section 2.1091

Date of Receipt: 2022-12-06

Date of Test: 2022-12-17 to 2023-02-05

Date of Issue: 2023-02-08

Test Result : Pass*

EMC Technical Manager

WinkeyWarg



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed coverlead, variable on request or accessible at http://www.sgs.com/len/terms.and-Conditions.gr. and-Conditions.gr. and-Conditions for Electronic Documents at http://www.sgs.com/len/Terms.and-Conditions/Terms.and-Condi

Fiyong lab. Xirlong TechnoPart, Fingding Road, Fiyong Subdishid, Bao'an, Shenzhen, China 518103 t (86-755) 88663988 f (86-755) 26710594 www.sgs.group.com.c 中国 - 深刻 - 宝安区福永委道风境大道直发科技园祖永实验室 邮编: 518103 t (86-755) 88663988 f (86-755) 26710594 sgs.china@sgs.com

^{*} In the configuration tested, the EUT complied with the standards specified above



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR221200049302

Page: 2 of 8

	Revision Record							
Version	Chapter	Date	Modifier	Remark				
01		2023-02-08		Original				

Authorized for issue by:		
	Tree Zhan	
	Tree Zhan/Project Engineer	-
	WinkeyWang	
	Winkey Wang/Reviewer	-





SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR221200049302

Page: 3 of 8

2 Contents

1	C	OVER PAGE	1
-	·		
2	C	ONTENTS	3
_			Ī
3	G	ENERAL INFORMATION	4
	2 1	DETAILS OF E.U.T.	1
	3.1 3.2	DESCRIPTION OF SUPPORT UNITS	4
	3.3	TEST LOCATION	F
	3.4	TEST FACILITY DEVIATION FROM STANDARDS.	5
	3.5	DEVIATION FROM STANDARDS	5
	3.6	ABNORMALITIES FROM STANDARD CONDITIONS	5
1	=	QUIPMENTS USED DURING TEST	6
4		QUIFMENTS USED DURING TEST	U
5	TI	EST RESULTS	7
•			
	5.1	RF Exposure test	7
	5.	.1.1 E.U.T. Operation	7



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printer overlead, available on request of accessible at http://www.pg.com/en/Terms-dnd-Conditions.aspx and, for electronic format documents at Atlention is of around the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exponent experts to it transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduce except in fail, without prior written approval of the Company, Any unauthorized alteration, forger or institutional provides the Company Any unauthorized alteration. Forger of relational contained the content of the



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR221200049302

Page: 4 of 8

3 General Information

3.1 Details of E.U.T.

3.2 Description of Support Units

Power supply:	Lithium-ion rechargeable battery (DC 3.7V 10000mAh) which can be
	charged from Type-C port.
	Input: USB-C 5V/3A, 9V/2.22A
	Output: USB-A 5V/2.4A, 9V/2A,12V/1.5A
	USB-C 5V/3A, 9V/2.78A,12V/2.1A
	WPC: 5W/7.5W/10W/15W
	Two or more outputs:15W Max.
Cable(s):	USB-C to USB-C 29cm unshielded
Frequency Range	112.00-148.00KHz
Modulation type:	Load modulation
Antenna type:	Loop Antenna

Remark: The information in this section is provided by the applicant or manufacturer, CCS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

Description	Manufacturer	Model No.	Serial No.
Mobile Phone	Nexus	MRA58K	REF. No.SEA16P00
iPhone 8	Apple	A1863	REF. No.SEA16J00
Mobile Phone	SAMSUNG	SM-G9810	REF. No.SEA16K00
E-loading	SGS	N/A	REF. No.SEA42A00





SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR221200049302

Page: 5 of 8

3.3 Test Location

All tests were performed at:

Compliance Certification Services (Kunshan) Inc. Shenzhen branch.

Fuyong lab. Xinlong TechnoPark, Fengtang Road, Fuyong Subdistrict, Bao'an, Shenzhen, China

Tel: +86 755 8866 3988 Fax: +86 755 2671 0594

No tests were sub-contracted.

3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 6606.01)

Compliance Certification Services (Kunshan) Inc. Shenzhen branch is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 6606.01.

• FCC -Designation Number: CN1322

Compliance Certification Services (Kunshan) Inc. Shenzhen branch has been recognized as an accredited testing laboratory.

Designation Number: CN1322. Test Firm Registration Number: 718073

• Innovation, Science and Economic Development Canada

Compliance Certification Services (Kunshan) Inc. Shenzhen branch has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0129.

IC#: 28189.

3.5 Deviation from Standards

None.

3.6 Abnormalities from Standard Conditions

None.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printe overlead, available on request of accessible at http://www.spi.com/en/Terms-dnd-Conditions_assa and, for electronic format documents of a document of the control of



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR221200049302

Page: 6 of 8

4 Equipments Used during Test

Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Due date
1	3m Anechoic Chamber	CRT	N/A	SEM001-13	2025-07-11
2	Electric and Magnetic Field Analyzer	Narda	EHP-200AC	SEM022-20	2023-04-01

Test Mode Description

1 CSt WOOd	, 5000.	iption
Pre-scan /	Mode	Description
Final test	Code	
Pre-scan	00	Charging+Discharge mode_Keep the EUT discharging(WPC 5W) while charging with adapter.
Pre-scan	01	Discharge mode_Keep the EUT discharging(WPC 5W)
Pre-scan	02	Discharge mode_Keep the EUT_discharging(WPC 7.5W)
Pre-scan	03	Discharge mode_Keep the EUT_discharging(WPC 10W)
Final test	04	Discharge mode_Keep the EUT_discharging(WPC 15W)





SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR221200049302

Page: 7 of 8

5 Test Results

5.1 RF Exposure test

Test Requirement: 47 CFR PART 1, Subpart I, Section 1.1310

47 CFR PART 2, Subpart J, Section 2.1091

Measurement Distance: 15cm

Limit:

Frequency range (MHz)			Power density (mW/cm²)	Averaging time (minutes)					
(A) Limits for Occupational/Controlled Exposures									
0.3-3.0	614	1.63	*(100)	6					
3.0-30	1842/f	4.89/f	*(900/f²)	6					
30-300	61.4	0.163	1.0	6					
300-1500	/	/	f/300	6					
1500-100,000	/	/	5	6					
	(B) Limits for Genera	l Population/Uncontrolle	d Exposure						
0.3-1.34	614	1.63	*(100)	30					
1.34-30	824/f	2.19/f	*(180/f²)	30					
30-300	27.5	0.073	0.2	30					
300-1500	/	/	f/1500	30					
1500-100,000	/	/	1.0	30					

F=frequency in MHz

5.1.1 E.U.T. Operation

Operating Environment:

Temperature: 22.3 °C Humidity: 52.9 % RH Atmospheric Pressure: 1020 mbar This device has been tested the worst status of full load and the device has been tested with mobile phone at zero charge, intermediate charge, and full charge.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overlead, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents. Attention is a drawn to the limitation of liability, incrementarily and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exponent aparties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced appearance of this document is unlawfull and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authersticity of Insting inspection report & certificate, please reclaimed for 30 days only.

Fujorajáb. Xirking Yedno-Park, Fenglang Road, Fujoraj Subdahid, Baolan, Shenzhen, China 518103 t (86-755) 88663988 f (86-755) 26710594 www.sgsgroup.com.c 中國 - 深圳 - 宝安区福永街道风塘大道盒龙科技园福永实验室 邮稿: 518103 t (86-755) 88663988 f (86-755) 26710594 sgs.china@sgs.com

^{*=}Plane-wave equivalent power density

RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR221200049302

Page: 8 of 8

5.1.2 Measurement Data

Input Voltage=DC 9V; The max output power =15W

Magnetic Field Emissions

Operation frequency	Test Distance (cm)	Test Position	Probe	Probe Measure Result (A/m)			10 % Limit (A/m)
			unload	Half load	full load		
124 kHz		Side 1	0.093	0.110	0.130	0.815	0.163
which is the worst		Side 2	0.115	0.131	0.154		
case within the operation frequency range	15	Side 3	0.097	0.110	0.135		
		Side 4	0.118	0.132	0.161		
		Тор	0.102	0.119	0.136		

Magnetic Field Emissions

Operation frequency	Test Distance	Test	Probe M	easure Result(50 % Limit	10 % Limit	
	(cm)	Position	zero charge	intermediate charge	full charge	(A/m)	(A/m)
132 kHz	e 15 –	Side 1	0.128	0.107	0.085	0.815	0.163
which is the worst		Side 2	0.156	0.131	0.104		
case		Side 3	0.132	0.111	0.088		
within the operation frequency range		Side 4	0.160	0.135	0.107		
		Тор	0.145	0.122	0.097		

- End of the Report -



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overlead, available on request of accessible at http://www.pg.com/en/Terms-dnd-Conditions_aspx and, for electronic formal documents. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any bolder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exponent parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in fail, without prior written approval of the Company, Any unauthorized alteration, forgety of failsfication of the context or execution and the context of the co