

FCC ID TEST REPORT

for

Bluetooth Speaker

Model: Bluetooth Speaker

FCC ID: 2AA28SPEAKER

Prepared for: Benway Electronics Co., Ltd
FLAT/RM 1301 13/F NAN FUNG TOWER 173
DES VOEUX RD CENTRAL HK

Prepared by: Shenzhen TCT Testing Technology Co.,Ltd
1F, Building 1, Yibaolai Industrial Park, Qiaotou Village, Fuyong Town,
Baoan District, Shenzhen, Guangdong, China

TEL: +86-0755-27673339

FAX: +86-0755-27673332

Report Number: TCT130912017F2-1

Date of Test: Sept. 18~Sept. 29, 2013

Date of Report: Sept. 29, 2013

The results detailed in this test report relate only to the specific sample(s) tested. It is the Application's responsibility to ensure that all production units are manufactured with equivalent EMC characteristics. This report is not to be reproduced except in full, without written approval from TCT Testing Technology.

Table of Contents

| | | |
|-------------|--|-----------|
| 1.0 | General Details | 3 |
| 1.1 | Test Lab Details..... | 3 |
| 1.2 | Applicant Details..... | 3 |
| 1.3 | Description of EUT | 4 |
| 1.4 | Submitted Sample..... | 4 |
| 1.5 | Test By..... | 4 |
| 2.0 | List of Measurement Equipment..... | 5 |
| 3.0 | Technical Details..... | 6 |
| 3.1 | Summary of Test Results..... | 6 |
| 3.2 | Test Standards..... | 6 |
| 4.0 | EUT Modification..... | 6 |
| 5.0 | Measurement Uncertainty..... | 6 |
| 6.0 | Power Line Conducted Emission Test..... | 7 |
| 6.1 | Schematics of the test..... | 7 |
| 6.2 | Test Method and Test Procedure..... | 7 |
| 6.3 | EUT Operating Condition..... | 7 |
| 6.4 | Test Equipment..... | 7 |
| 6.5 | Conducted Emission Limit..... | 8 |
| 6.6 | Photo documentation of the test set-up | 8 |
| 6.7 | Test specification..... | 8 |
| 6.8 | Test result..... | 8 |
| 7.0 | 20 dB Bandwidth Measurement..... | 11 |
| 7.1 | Test Equipment..... | 11 |
| 7.2 | Test Specification..... | 11 |
| 7.3 | Limit..... | 11 |
| 7.4 | Test status..... | 11 |
| 7.5 | Test Result..... | 11 |
| 8.0 | Maximum Peak Output Power..... | 15 |
| 9.0 | Carrier Frequency Separation..... | 21 |
| 10.0 | Number of Hopping Channels..... | 25 |
| 11.0 | Time of Occupancy (Dwell Time)..... | 27 |
| 12.0 | Band age Measurement..... | 31 |
| 13.0 | Spurious Emission Test..... | 40 |
| 14.0 | Antenna Requirement..... | 52 |
| 15.0 | FCC ID Label..... | 53 |

1.0 General Details

1.1 Test Lab Details

| | |
|------------|--|
| Name : | Shenzhen TCT Testing Technology Co.,Ltd |
| Address: | 1F, Building 1, Yibaolai Industrial Park, Qiaotou Village, Fuyong Town, Baoan District, Shenzhen, Guangdong, China |
| Telephone: | +86-0755-27673339 |
| Fax: | +86-0755-27673332 |

Site Listed with Federal Communication Commission

Registration Number: 572331

For 3m chamber

Site Listed with Industry Canada of Ottawa, Canada

Registration Number IC: 10668A-1

For 3m chamber

1.2 Applicant Details

| | |
|------------|--|
| Applicant: | Benway Electronics Co., Ltd |
| Address: | FLAT/RM 1301 13/F NAN FUNG TOWER 173 DES VOEUX RD CENTRAL HK |
| Telephone: | 83048953 |
| Fax: | 83464897 |

| | |
|---------------|---|
| Manufacturer: | Shenzhen Benway Electronics Co., Ltd. |
| Address: | 3/F, Block C6, Zone C, Fuhai Industrial Zone, FuHai Road East, Fuyong, Bao'an, Shenzhen |
| Telephone: | 83048953 |
| Fax: | 83464897 |

1.3 Description of EUT

| | |
|-----------------------|---|
| Product: | Bluetooth Speaker |
| Model No.: | Bluetooth Speaker |
| Additional Model No.: | N/A |
| Brand Name: | Benway |
| Rating: | DC 5V via USB line or DC 3.7V via Battery |
| Modulation Type: | GFSK, Pi/4QDPSK, 8DPSK |
| Transfer Data Rate | 1/2/3 Mbps |
| Channel number: | 79 |
| Channel spacing: | 1 MHz |
| Operation Frequency: | 2402~2480MHz |
| Antenna Designation: | An integral antenna and the maximum antenna gain is 1.0dBi. |

1.4 Statement: N/A

1.5 Test Engineer

The sample tested by



Printed name: Jack Kang

2.0 Test equipments and Associated Equipment used during the test.

2.1 Test Equipments

| No. | Instrument Type | Manufacturer | Model | Serial No. | Date of Cal. | Due Date |
|-----|---------------------|--------------|---------|-------------|--------------|--------------|
| 1 | ESPI Test Receiver | R&S | ESPI 3 | 100379 | July 7, 2013 | July 6, 2014 |
| 2 | Ultra Broadband ANT | R&S | HL562 | 100157 | July 8, 2013 | July 7, 2014 |
| 3 | System Controller | CT | SC100 | - | July 8, 2013 | July 7, 2014 |
| 4 | Spectrum Analyzer | R&S | FSEM | 848597/001 | July 7, 2013 | July 6, 2014 |
| 5 | Pre-amplifier | Teseq | LAN6900 | -- | July 8, 2013 | July 7, 2014 |
| 6 | Pre-amplifier | Agilent | 8447D | 83153007374 | July 8, 2013 | July 7, 2014 |
| 7 | Pre-amplifier | Agilent | 8449B | 3008A01738 | July 8, 2013 | July 7, 2014 |
| 8 | Triple-loop antenna | R&S | HM020 | 843885/002 | July 8, 2013 | July 7, 2014 |
| 9 | Horn Antenna | ETS LINDGREN | 3117 | -- | July 8, 2013 | July 7, 2014 |
| 10 | Horn Antenna | ETS LINDGREN | 3160 | -- | July 8, 2013 | July 7, 2014 |
| 11 | EMI Test Receiver | R&S | ESCS30 | 100139 | July 7, 2013 | July 6, 2014 |
| 12 | LISN | AFJ | LS16C | 16010222119 | July 7, 2013 | July 6, 2014 |

2.2 AE used during the test

| Equipment type | Manufacturer | Model |
|----------------|--------------|-------|
| Notebook | acer | ZQ1A |
| N/A | | |
| N/A | | |
| N/A | | |

3.0 Technical Details

3.1 Summary of test results

The EUT has been tested according to the following specifications

| Requirement | CFR 47 Section | Result |
|---|------------------------------------|--------|
| Power Line Conducted Emission Test | 15.207(a) | PASS |
| 20dB Channel Bandwidth | 15.247 (a)(1), 15.215(c) | PASS |
| Maximum Peak Output Power | 15.247(b)(1) | PASS |
| Carrier Frequency Separation | 15.247 (a)(1) | PASS |
| Number of Hopping Channels | 15.247(a)(iii) | PASS |
| Time of Occupancy (Dwell Time) | 15.247(a)(iii) | PASS |
| Band age Measurement, Spurious Emission Test | 15.247 (d), 15.205 (a), 15.209 (a) | PASS |
| Antenna Requirement | 15.203 | PASS |

3.2 Test Standards

FCC Part 15:2012 Subpart C, Paragraph 15.247

4.0 EUT Modification

No modification by Shenzhen TCT Testing Technology Co., Ltd

5.0 Measurement Uncertainty (95% confidence levels, k=2)


| No. | Item | MU |
|-----|-------------------------------|---------------------------|
| 1. | Radio Frequency | $\pm 1 \times 10^{-9}$ |
| 2. | Temperature | $\pm 0.1^{\circ}\text{C}$ |
| 3. | Humidity | $\pm 1.0\%$ |
| 4. | RF power, conducted | $\pm 0.34\text{dB}$ |
| 5. | RF power density, conducted | $\pm 1.45\text{dB}$ |
| 6. | Spurious emissions, conducted | $\pm 3.70\text{dB}$ |
| 7. | All emissions, radiated | $\pm 4.50\text{dB}$ |

Note: 1) Low channel: 2402MHz, Middle channel: 2441MHz, High channel: 2480MHz

2) The Bluetooth version is Bluetooth 3.0, which has an EDR function.

6.0 Power Line Conducted Emission Test

6.1 Schematics of the test




EUT: Equipment Under Test

6.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.10-2009. The Frequency spectrum From 0.15MHz to 30MHz was investigated.

Test Voltage: 120V~, 60Hz

Block diagram of Test setup



6.3 EUT Operating Condition

Operating condition is according to ANSI C63.10 -2009

- 1) Setup the EUT and simulators as shown on the following
- 2) Enable AF signal and confirm EUT active to normal condition

6.4 Test Equipment

| No. | Instrument Type | Manufacturer | Model | Serial No. | Date of Cal. | Due Date |
|-----|-------------------|--------------|--------|-------------|--------------|--------------|
| 11 | EMI Test Receiver | R&S | ESCS30 | 100139 | July 7, 2013 | July 6, 2014 |
| 12 | LISN | AFJ | LS16C | 16010222119 | July 7, 2013 | July 6, 2014 |

6.5 Conducted Emission Limit

| Frequency(MHz) | Class A Limits (dB μ V) | | Class B Limits (dB μ V) | |
|----------------|-----------------------------|---------------|-----------------------------|---------------|
| | Quasi-peak Level | Average Level | Quasi-peak Level | Average Level |
| 0.15 ~ 0.50 | 79.0 | 66.0 | 66.0~56.0* | 56.0~46.0* |
| 0.50 ~ 5.00 | 73.0 | 60.0 | 56.0 | 46.0 |
| 5.00 ~ 30.00 | 73.0 | 60.0 | 60.0 | 50.0 |

Notes: 1) *Decreasing linearly with logarithm of frequency.
2) The tighter limit shall apply at the transition frequencies

6.6 Photo documentation of the test set-up

Please refer to the Section 17

6.7 Test specification:

Environmental conditions: Temperature: 23° C Humidity: 51% Atmospheric pressure: 103kPa

Frequency range: 0.15 MHz – 30 MHz

The test was carried out in the following operation mode(s):

- Tx mode

6.8 Test result

Min. limit margin >10dB from 0.15MHz to 30MHz

The requirements are FULFILLED

Remarks:

A Conducted Emission on Line Terminal of the power line (150kHz to 30MHz)


EUT Description: Bluetooth Speaker

Operation Mode: Tx mode

Tested By: Beryl Zhao

Test Date: Sept. 28, 2013

| Start Frequency | Stop Frequency | Step | IF BW | Detector | Final M-Time |
|-----------------|----------------|--------|-------|----------|--------------|
| 0.15MHz | 30MHz | 4.5KHz | 10KHz | QP+AV | 1s |



| Frequency (MHz) | Reading(dB μ V) | | | | Limit (dB μ V) | |
|--------------------|-----------------|---------|------------|---------|-------------------|-------|
| | Live | | Neutral | | | |
| | Quasi-peak | Average | Quasi-peak | Average | | |
| 0.1499 | 55.19 | 22.18 | -- | -- | 66.00 | 56.00 |
| 0.5988 | 48.44 | 33.03 | -- | -- | 56.00 | 46.00 |
| 1.0443 | 45.20 | 28.17 | -- | -- | 56.00 | 46.00 |
| 2.0913 | 43.96 | 31.05 | -- | -- | 56.00 | 46.00 |
| 2.4937 | 44.09 | 31.01 | -- | -- | 56.00 | 46.00 |
| 17.2652 | 36.08 | 30.28 | -- | -- | 60.00 | 50.00 |

B Conducted Emission on Neutral Terminal of the power line (150kHz to 30MHz)


EUT Description: Bluetooth Speaker

Operation Mode: Tx mode

Tested By: Beryl Zhao

Test Date: Sept. 28, 2013

| Start Frequency | Stop Frequency | Step | IF BW | Detector | Final M-Time |
|-----------------|----------------|--------|-------|----------|--------------|
| 0.15MHz | 30MHz | 4.5KHz | 10KHz | QP+AV | 1s |



| Frequency (MHz) | Reading(dB μ V) | | | | Limit (dB μ V) | |
|--------------------|---------------------|---------|------------|---------|-----------------------|-------|
| | Live | | Neutral | | Quasi-peak | |
| | Quasi-peak | Average | Quasi-peak | Average | | |
| 0.1499 | -- | -- | 54.53 | 12.58 | 66.00 | 56.00 |
| 0.3392 | -- | -- | 45.75 | 33.12 | 59.22 | 49.22 |
| 0.5914 | -- | -- | 45.79 | 35.77 | 56.00 | 46.00 |
| 1.0326 | -- | -- | 45.43 | 29.83 | 56.00 | 46.00 |
| 2.5209 | -- | -- | 45.52 | 34.25 | 56.00 | 46.00 |
| 17.2890 | -- | -- | 48.46 | 30.08 | 60.00 | 50.00 |

7.0 20dB Bandwidth Measurement

7.1 Test Equipment

| No. | Instrument Type | Manufacturer | Model | Serial No. | Date of Cal. | Due Date |
|-----|-------------------|--------------|-------|------------|--------------|--------------|
| 4 | Spectrum Analyzer | R&S | FSEM | 848597/001 | July 7, 2013 | July 6, 2014 |

7.2 Test Specification:

Environmental conditions: Temperature 23° C Humidity: 52% Atmospheric pressure: 103kPa

7.3 Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

7.4 Test status:


Pre-tests were made in continuous transmitting mode at lowest (2402 MHz), middle (2441 MHz) and highest (2480MHz) channel with GFSK, Pi/4 QDPSK and 8DPSK mode, which indicates that the worst case is 8DPSK mode, so it is reported GFSK and 8DPSK mode only.

7.5 Test Result:


| Modulation Type | Channel number | 20dB Bandwidth (kHz) | Limit (kHz) | Conclusion |
|-----------------|----------------|----------------------|-------------|------------|
| GFSK | Low | 871.7 | --- | PASS |
| | Middle | 865.7 | --- | PASS |
| | High | 865.7 | --- | PASS |
| 8DPSK | Low | 1214.4 | --- | PASS |
| | Middle | 1208.4 | --- | PASS |
| | High | 1214.4 | --- | PASS |

Modulation: GFSK


Low channel



Middle channel




High channel




Modulation: 8DPSK


Low channel



Middle channel



High channel



8.0 Maximum Peak Output Power

8.1 Test Equipment

| No. | Instrument Type | Manufacturer | Model | Serial No. | Date of Cal. | Due Date |
|-----|-------------------|--------------|-------|------------|--------------|--------------|
| 4 | Spectrum Analyzer | R&S | FSEM | 848597/001 | July 7, 2013 | July 6, 2014 |

8.2 Test specification:

Environmental conditions: Temperature 23° C Humidity: 52% Atmospheric pressure: 103kPa

8.3 Test Procedure

- 1) Check the calibration of the measuring instrument (spectrum analyzer) using either an internal calibrator or a known signal from an external generator.
- 2) Set the spectrum analyzer as follows: Span = approximately 5 times the 20 dB bandwidth, centred on a hopping channel; RBW > the 20 dB bandwidth of the emission being measured; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold
- 3) Measure the highest amplitude appearing on spectral display and record the level to calculate results.
- 4) Repeat above procedures until all frequencies measured were complete.

8.4 Limits


According to §15.247(b)(1), for frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5MHz band: 0.125 watts. According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

8.5 Test Result


| Modulation Type | Channel Frequency (MHz) | Peak Power Output (dBm) | Peak Power Limit (mW) | Peak Power Limit (dBm) | Pass/ Fail |
|-----------------|-------------------------|-------------------------|-----------------------|------------------------|------------|
| GFSK | 2402 | -1.47 | 125 | 20.97 | Pass |
| | 2441 | -2.47 | 125 | 20.97 | Pass |
| | 2480 | -1.76 | 125 | 20.97 | Pass |
| Pi/4 QDPSK | 2402 | -3.45 | 125 | 20.97 | Pass |
| | 2441 | -3.92 | 125 | 20.97 | Pass |
| | 2480 | -3.10 | 125 | 20.97 | Pass |
| 8 DPSK | 2402 | -2.70 | 125 | 20.97 | Pass |
| | 2441 | -3.81 | 125 | 20.97 | Pass |
| | 2480 | -2.88 | 125 | 20.97 | Pass |

Modulation: GFSK


Low channel



Middle channel




High channel




Modulation: Pi/4DQPSK


Low channel



Middle channel




High channel




Modulation: 8DPSK


Low channel



Middle channel



High channel



9.0 Carrier Frequency Separation

9.1 Test Equipment

| No. | Instrument Type | Manufacturer | Model | Serial No. | Date of Cal. | Due Date |
|-----|-------------------|--------------|-------|------------|--------------|--------------|
| 4 | Spectrum Analyzer | R&S | FSEM | 848597/001 | July 7, 2013 | July 6, 2014 |

9.2 Test specification:

Environmental conditions: Temperature 23° C Humidity: 52% Atmospheric pressure: 103kPa

9.3 Test Procedure

1. Set the spectrum analyzer as follows: Span = wide enough to capture the peaks of two adjacent channels: Resolution (or IF) Bandwidth (RBW) \geq 1% of the span; Video (or Average) Bandwidth (VBW) \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold
2. Measure the separation between the peaks of the adjacent channels using the marker-delta function.
3. Repeat above procedures until all frequencies measured were complete.

9.4 Limits

According to §15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

9.5 Test status:

Pre-tests were made in continuous transmitting mode at lowest (2402 MHz), middle (2441 MHz) and highest (2480MHz) channel with GFSK, Pi/4 QDPSK and 8DPSK mode, which indicates that the worst case is 8DPSK mode, so it is reported GFSK and 8DPSK mode only.


9.6 Test Result

| Modulation Type | Channel number | Carrier Frequency Separation | Limit | Pass/ Fail |
|-----------------|----------------|------------------------------|---|------------|
| GFSK | Low | 1.000MHz | \geq 25 kHz or two-thirds 20 dB bandwidth | Pass |
| | Middle | 1.000MHz | | Pass |
| | High | 1.000MHz | | Pass |
| 8DPSK | Low | 1.000MHz | \geq 25 kHz or two-thirds 20 dB bandwidth | Pass |
| | Middle | 1.000MHz | | Pass |
| | High | 1.000MHz | | Pass |


Note: Two-thirds 20 dB bandwidth: GFSK: 581.1 kHz 8DPSK: 809.6 kHz

Modulation: GFSK


Low channel



Middle channel




High channel




Modulation: 8DPSK


Low channel



Middle channel



High channel



10.0 Number of Hopping Channels

10.1 Test Equipment

| No. | Instrument Type | Manufacturer | Model | Serial No. | Date of Cal. | Due Date |
|-----|-------------------|--------------|-------|------------|--------------|--------------|
| 4 | Spectrum Analyzer | R&S | FSEM | 848597/001 | July 7, 2013 | July 6, 2014 |

10.2 Test specification:

Environmental conditions: Temperature 22° C Humidity: 52% Atmospheric pressure: 103kPa

10.3 Test Procedure

Set the spectrum analyzer as follows: Span = the frequency band of operation; RBW \geq 1% of the span;
VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold

10.4 Limits

According to §15.247(a)(1)(iii), frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

10.5 Test status:


Pre-tests were made in continuous transmitting mode at lowest (2402 MHz), middle (2441 MHz) and highest (2480MHz) channel with GFSK, Pi/4 QDPSK and 8DPSK mode, which indicates that the worst case is 8DPSK mode, so it is reported GFSK and 8DPSK mode only.

10.6 Test Result


| Modulation Type | Operating Frequency | Number of hopping channels | Limit | Pass/ Fail |
|-----------------|---------------------|----------------------------|-----------|------------|
| GFSK | 2402-2480MHz | 79 | ≥ 15 | Pass |
| 8-DPSK | 2402-2480MHz | 79 | ≥ 15 | Pass |

Test Plot:

Modulation Type: GFSK



Modulation Type: 8DPSK



11.0 Time of Occupancy (Dwell Time)

11.1 Test Equipment

| No. | Instrument Type | Manufacturer | Model | Serial No. | Date of Cal. | Due Date |
|-----|-------------------|--------------|-------|------------|--------------|--------------|
| 4 | Spectrum Analyzer | R&S | FSEM | 848597/001 | July 7, 2013 | July 6, 2014 |

11.2 Test specification:

Environmental conditions: Temperature 23° C Humidity: 52% Atmospheric pressure: 103kPa

11.3 Test Procedure

Span = zero span, centred on a hopping channel; RBW = 1 MHz; VBW \geq RBW; Detector function = peak;

Sweep = as necessary to capture the entire dwell time per hopping channel; Trace = max hold

Measure the dwell time using the marker-delta function.

Repeat this test for different modes of operation (e.g., data rate, modulation format, etc.), if applicable.

11.4 Limits

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed

11.5 Test status:

Pre-tests were made in continuous transmitting mode at lowest (2402 MHz), middle (2441 MHz) and highest (2480MHz) channel with GFSK, Pi/4 QDPSK and 8DPSK mode, which indicates that the worst case is 8DPSK mode, so it is reported GFSK and 8DPSK mode only.

11.6 Test Result

| Modulation Type | Packet | Reading (ms) | Hopping Rate | Actual (s) | Limit (s) |
|-----------------|--------|--------------|--------------|------------|-----------|
| GFSK | DH1 | 0.415 | 800hop/s | 0.1328 | 0.4 |
| | DH3 | 1.691 | 400hop/s | 0.2701 | 0.4 |
| | DH5 | 2.939 | 266.667hop/s | 0.3135 | 0.4 |
| 8DPSK | DH1 | 0.435 | 800hop/s | 0.1392 | 0.4 |
| | DH3 | 1.720 | 400hop/s | 0.2752 | 0.4 |
| | DH5 | 3.000 | 266.667hop/s | 0.3200 | 0.4 |


Note: 1) The measurements were conducted in High, Middle, Low channel. The Low channel could represent the character of the other channels, so the low channel measurement was submitted in the report only.

2) Actual = Reading \times (Hopping rate / Number of channels) \times Test period


3) The EUT makes worst case 1600 hops per second or 1 time slot has a length of 625 μ s with 79 channels. A DH5 Packet needs 5 time slot for transmitting and 1 time slot for receiving. So the EUT makes worst case 266.667 hops per second with 79 channels, and the DH5 is the worst case.

Modulation Type: GFSK


Packet Type: DH1



Packet Type: DH3




Packet Type: DH5




Modulation Type: 8DPSK


Packet Type: 3-DH1



Packet Type: 3-DH3



Packet Type: 3-DH5



12.0 Band age Measurement

12.1 Test Equipment

| No. | Instrument Type | Manufacturer | Model | Serial No. | Date of Cal. | Due Date |
|-----|-------------------|--------------|-------|------------|--------------|--------------|
| 4 | Spectrum Analyzer | R&S | FSEM | 848597/001 | July 7, 2013 | July 6, 2014 |
| 7 | Pre-amplifier | Agilent | 8449B | 3008A01738 | July 8, 2013 | July 7, 2014 |
| 9 | Horn Antenna | ETS LINDGREN | 3117 | -- | July 8, 2013 | July 7, 2014 |

12.2 Test specification:

Environmental conditions: Temperature 22° C Humidity: 52% Atmospheric pressure: 103kPa

12.3 Test Procedure

For bandage test, the spectrum set as follows: RBW=VBW=100 kHz. A conducted measure method is used
For signals allocated in the restricted bands above and below the 2.4-2.483GHz, a radiated measurement is made
(Peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz
and PK detector)

12.4 Limit


Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).
Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in
section 15.209.

12.5 Test status:

Pre-tests were made in continuous transmitting mode at lowest (2402 MHz), middle (2441 MHz) and highest
(2480MHz) channel with GFSK, Pi/4 DPSK and 8DPSK mode, which indicates that the worst case is 8DPSK
mode, so it is reported GFSK and 8DPSK mode only.

Modulation: GFSK

EUT operation mode: Keep transmitting in low channel




Remark: 1) The radiated measurement was made in horizontal and vertical polarity;

2) The maximum emission was 52.38dBuV at 2389.8 MHz, which is less than the Average limit.


3) Radiated emissions which fall in the restricted band, as defined in 15.205(a), comply with the radiated emission limits specified in 15.209(a).

EUT operation mode: Keep hopping



- Remark: 1) The radiated measurement was made in horizontal and vertical polarity;
- 2) The maximum emission was 53.42dBuV at 2375.6MHz, which is less than the Average limit.
- 3) Radiated emissions which fall in the restricted band, as defined in 15.205(a), comply with the radiated emission limits specified in 15.209(a).


EUT operation mode: Keep hopping



- Remark: 1) The radiated measurement was made in horizontal and vertical polarity;
- 2) The maximum emission was 51.84dBuV at 2492.1MHz, which is less than the Average limit.
- 3) Radiated emissions which fall in the restricted band, as defined in 15.205(a), comply with the radiated emission limits specified in 15.209(a).


Modulation: 8DPSK

EUT operation mode: Keep transmitting in low channel




- Remark: 1) The radiated measurement was made in horizontal and vertical polarity;
- 2) The maximum emission was 52.65dBuV at 2369.9MHz, which is less than the Average limit.
- 3) Radiated emissions which fall in the restricted band, as defined in 15.205(a), comply with the radiated emission limits specified in 15.209(a).

EUT operation mode: Keep transmitting in high channel



- Remark: 1) The radiated measurement was made in horizontal and vertical polarity;
- 2) The maximum emission was 51.01dBuV at 2489.3MHz, which is less than the Average limit.
- 3) Radiated emissions which fall in the restricted band, as defined in 15.205(a), comply with the radiated emission limits specified in 15.209(a).

EUT operation mode: Keep hopping



- Remark: 1) The radiated measurement was made in horizontal and vertical polarity;
- 2) The maximum emission was 51.43dBuv at 2492.1MHz, which is less than the Average limit.
- 3) Radiated emissions which fall in the restricted band, as defined in 15.205(a), comply with the radiated emission limits specified in 15.209(a).


13.0 Spurious Emission Test

13.1 Radiated emissions


13.1.1 Test Method and test Procedure:

- 1) The EUT was tested according to ANSI C63.10 –2009.
- 2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.10-2009.
- 3) The frequency spectrum from 30 MHz to 25 GHz was investigated. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 kHz. All readings are above 1 GHz, peak values with a resolution bandwidth of 1 MHz . Measurements were made at 3 meters.
- 4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- 5) The antenna polarization: Vertical polarization and Horizontal polarization.


13.1.2 Block diagram of Test setup



Block diagram of Test setup for frequency below 30MHz



Block diagram of Test setup for frequency above 1GHz



13.1.3 EUT Operating Condition

Operating condition is according to ANSI C63.10 -2009

13.1.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

Frequencies in restricted band are complied to limit on Paragraph 15.209.

| Frequency Range (MHz) | Distance (m) | Field strength (dB μ V/m) |
|-----------------------|--------------|-------------------------------|
| 0.009-0.490 | 3 | $20\log 2400/F$ (kHz) + 80 |
| 0.490-1.705 | 3 | $20\log 24000/F$ (kHz) + 40 |
| 1.705-30 | 3 | $20\log 30$ + 40 |
| 30-88 | 3 | 40.0 |
| 88-216 | 3 | 43.5 |
| 216-960 | 3 | 46.0 |
| Above 960 | 3 | 54.0 |

- Note:
- 1) RF Voltage (dBuV) = 20 log RF Voltage (uV)
 - 2) In the Above Table, the tighter limit applies at the band edges.
 - 3) Distance refers to the distance in meters between the measuring instrument antenna and the EUT
 - 4) This is a handheld device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.
 - 5) All scanning using PK detector. And the final emission level was get using QP detector for frequency range from 30-1000MHz. As to 1G-25G, the final emission level got using PK and AV detector.
 - 6) If measurement is made at 3m distance, then F.S Limitation at 3m distance is adjusted by using the formula $Ld1 = Ld2 * (d2/d1)$

13.1.5 Photo documentation of the test set-up

Please refer to the Section 16

13.1.6 Test Equipment:

| No. | Instrument Type | Manufacturer | Model | Serial No. | Date of Cal. | Due Date |
|-----|---------------------|--------------|---------|-------------|--------------|--------------|
| 1 | ESPI Test Receiver | R&S | ESPI 3 | 100379 | July 7, 2013 | July 6, 2014 |
| 2 | Ultra Broadband ANT | R&S | HL562 | 100157 | July 8, 2013 | July 7, 2014 |
| 4 | Spectrum Analyzer | R&S | FSEM | 848597/001 | July 7, 2013 | July 6, 2014 |
| 5 | Pre-amplifier | Teseq | LAN6900 | -- | July 8, 2013 | July 7, 2014 |
| 6 | Pre-amplifier | Agilent | 8447D | 83153007374 | July 8, 2013 | July 7, 2014 |
| 7 | Pre-amplifier | Agilent | 8449B | 3008A01738 | July 8, 2013 | July 7, 2014 |
| 8 | Triple-loop antenna | R&S | HM020 | 843885/002 | July 8, 2013 | July 7, 2014 |
| 9 | Horn Antenna | ETS LINDGREN | 3117 | -- | July 8, 2013 | July 7, 2014 |
| 10 | Horn Antenna | ETS LINDGREN | 3160 | -- | July 8, 2013 | July 7, 2014 |

13.1.7 Test specification:

Environmental conditions: Temperature 23° C Humidity: 51% Atmospheric pressure: 103kPa

13.1.8 Test result

A Radiated Emission (9 kHz----30 MHz)

Note: 1) Emission Level=Reading+ Cable loss+ Antenna factor-Amp factor
2) The emission levels are 20 dB below the limit value, which are not reported. It is deemed to comply with the requirement

Result: Pass


| Frequency (MHz) | Level@3m (dB μ V/m) | Limit@3m (dB μ V/m) |
|-----------------|-------------------------|-------------------------|
| -- | -- | -- |
| -- | -- | -- |
| -- | -- | -- |
| -- | -- | -- |

B General Radiated Emissions Data

Radiated Emission In Horizontal (30MHz----1000MHz)

Please refer to following diagram for individual

High channel: 2480 MHz




| Frequency (MHz) | Level@3m (dB μ V/m) | Antenna Polarity | Limit@3m (dB μ V/m) |
|-----------------|-------------------------|------------------|-------------------------|
| 31.9438 | 29.43 | H | 40.00 |
| 99.9800 | 28.09 | H | 43.50 |
| 203.0060 | 30.91 | H | 43.50 |
| 249.6593 | 35.40 | H | 46.00 |
| 292.4248 | 36.64 | H | 46.00 |
| 391.5631 | 31.60 | H | 46.00 |

Radiated Emission In Vertical (30MHz----1000MHz)

Please refer to following diagram for individual

High channel: 2480 MHz



| Frequency (MHz) | Level@3m (dB μ V/m) | Antenna Polarity | Limit@3m (dB μ V/m) |
|-----------------|-------------------------|------------------|-------------------------|
| 33.8877 | 29.05 | V | 40.00 |
| 99.9800 | 27.64 | V | 43.50 |
| 125.2505 | 24.56 | V | 43.50 |
| 253.5471 | 27.08 | V | 46.00 |
| 290.4810 | 28.64 | V | 46.00 |
| 399.3387 | 26.17 | V | 46.00 |

Note: Measurements were conducted in all three channels (high, middle, low), and the worst case (high channel) was submitted only.

C Fundamental & Harmonics Radiated Emission Data (1000MHz-25000MHz)

Pre-tests were made in continuous transmitting mode at lowest (2402 MHz), middle (2441 MHz) and highest (2480MHz) channel with GFSK, Pi/4 QDPSK and 8DPSK mode, which indicates that the worst case is 8DPSK mode, so it is reported GFSK and 8DPSK mode only.

Modulation Type: GFSK

| Low channel: 2402 MHz | | | | | | | | | |
|------------------------------|---------------|---------------------|-------------------|------------------------|----------------|-------------|---------------------|-------------------|-------------|
| Freq. (MHz) | Ant. Pol. H/V | Peak reading (dBuV) | AV reading (dBuV) | Correction Factor (dB) | Emission Level | | Peak limit (dBuV/m) | AV limit (dBuV/m) | Margin (dB) |
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | |
| 1301.58 | H | 52.97 | --- | -4.20 | 48.77 | --- | 74.00 | 54.00 | -5.23 |
| 4804.00 | H | 52.69 | --- | -3.94 | 48.75 | --- | 74.00 | 54.00 | -5.25 |
| 5600.68 | H | 51.10 | --- | -2.83 | 48.27 | --- | 74.00 | 54.00 | -5.73 |
| 7206.00 | H | 47.64 | --- | 0.52 | 48.16 | --- | 74.00 | 54.00 | -5.84 |
| 16814.00 | H | 43.00 | --- | 6.73 | 49.73 | --- | 74.00 | 54.00 | -4.27 |
| 24020.00 | H | 40.99 | --- | 8.11 | 49.10 | --- | 74.00 | 54.00 | -4.90 |
| | | | | | | | | | |
| 1308.16 | V | 53.56 | --- | -4.25 | 49.31 | --- | 74.00 | 54.00 | -4.69 |
| 4804.00 | V | 52.79 | --- | -3.94 | 48.85 | --- | 74.00 | 54.00 | -5.15 |
| 5620.44 | V | 50.80 | --- | -2.87 | 47.93 | --- | 74.00 | 54.00 | -6.07 |
| 7206.00 | V | 45.83 | --- | 0.52 | 46.35 | --- | 74.00 | 54.00 | -7.65 |
| 16814.00 | V | 40.21 | --- | 6.73 | 46.94 | --- | 74.00 | 54.00 | -7.06 |
| 24020.00 | V | 41.85 | --- | 8.11 | 49.96 | --- | 74.00 | 54.00 | -4.04 |

Notes: 1) Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.

2) Radiated emissions measured in frequencies above 1GHz were made with peak detector and Average (AV) detector.

3) Average test would be performed if the peak readings were greater than the average limit.

4) Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

5) Emission Level=Peak (AV) Reading + Correction Factor;

Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

6) Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

Middle channel: 2441 MHz

| Freq. (MHz) | Ant. Pol. H/V | Peak reading (dBuV) | AV reading (dBuV) | Correction Factor (dB) | Emission Level | | Peak limit (dBuV/m) | AV limit (dBuV/m) | Margin (dB) |
|----------------|------------------|---------------------------|-------------------------|------------------------------|------------------|----------------|------------------------|----------------------|----------------|
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | |
| 1301.49 | H | 51.55 | --- | -4.20 | 47.35 | --- | 74.00 | 54.00 | -6.65 |
| 4882.00 | H | 52.27 | --- | -3.98 | 48.29 | --- | 74.00 | 54.00 | -5.71 |
| 5600.07 | H | 52.13 | --- | -2.83 | 49.30 | --- | 74.00 | 54.00 | -4.70 |
| 7323.00 | H | 48.18 | --- | 0.57 | 48.75 | --- | 74.00 | 54.00 | -5.25 |
| 17087.00 | H | 43.57 | --- | 6.79 | 50.36 | --- | 74.00 | 54.00 | -3.64 |
| 24410.00 | H | 41.95 | --- | 8.16 | 50.11 | --- | 74.00 | 54.00 | -3.89 |
| | | | | | | | | | |
| 1308.09 | V | 52.45 | --- | -4.25 | 48.20 | --- | 74.00 | 54.00 | -5.80 |
| 4882.00 | V | 53.33 | --- | -3.98 | 49.35 | --- | 74.00 | 54.00 | -4.65 |
| 5623.39 | V | 51.34 | --- | -2.87 | 48.47 | --- | 74.00 | 54.00 | -5.53 |
| 7323.00 | V | 48.94 | --- | 0.57 | 49.51 | --- | 74.00 | 54.00 | -4.49 |
| 17087.00 | V | 42.12 | --- | 6.79 | 48.91 | --- | 74.00 | 54.00 | -5.09 |
| 24410.00 | V | 33.93 | --- | 8.16 | 42.09 | --- | 74.00 | 54.00 | -11.91 |

Notes: 1) Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.

2) Radiated emissions measured in frequencies above 1GHz were made with peak detector and Average (AV) detector.

3) Average test would be performed if the peak result were greater than the average limit.

4) Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

5) Emission Level=Peak (AV) Reading + Correction Factor;

Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

6) Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

| High channel: 2480 MHz | | | | | | | | | |
|------------------------|------------------|---------------------------|-------------------------|------------------------------|------------------|----------------|------------------------|----------------------|----------------|
| Freq. (MHz) | Ant. Pol. H/V | Peak reading (dBuV) | AV reading (dBuV) | Correction Factor (dB) | Emission Level | | Peak limit (dBuV/m) | AV limit (dBuV/m) | Margin (dB) |
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | |
| 1302.66 | H | 51.47 | --- | -4.20 | 47.27 | --- | 74.00 | 54.00 | -6.73 |
| 4960.00 | H | 51.71 | --- | -3.98 | 47.73 | --- | 74.00 | 54.00 | -6.27 |
| 5601.71 | H | 52.05 | --- | -2.83 | 49.22 | --- | 74.00 | 54.00 | -4.78 |
| 7440.00 | H | 48.79 | --- | 0.57 | 49.36 | --- | 74.00 | 54.00 | -4.64 |
| 17360.00 | H | 42.79 | --- | 6.79 | 49.58 | --- | 74.00 | 54.00 | -4.42 |
| 24800.00 | H | 40.33 | --- | 8.16 | 48.49 | --- | 74.00 | 54.00 | -5.51 |
| | | | | | | | | | |
| 1309.16 | V | 51.29 | --- | -4.25 | 47.04 | --- | 74.00 | 54.00 | -6.96 |
| 4960.00 | V | 51.67 | --- | -3.98 | 47.69 | --- | 74.00 | 54.00 | -6.31 |
| 5624.33 | V | 49.83 | --- | -2.87 | 46.96 | --- | 74.00 | 54.00 | -7.04 |
| 7440.00 | V | 49.96 | --- | 0.57 | 50.53 | --- | 74.00 | 54.00 | -3.47 |
| 17360.00 | V | 41.94 | --- | 6.79 | 48.73 | --- | 74.00 | 54.00 | -5.27 |
| 24800.00 | V | 40.62 | --- | 8.16 | 48.78 | --- | 74.00 | 54.00 | -5.22 |

Notes: 1) Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.

2) Radiated emissions measured in frequencies above 1GHz were made with peak detector and Average (AV) detector.

3) Average test would be performed if the peak result were greater than the average limit.

4) Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

5) Emission Level=Peak (AV) Reading + Correction Factor;

Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

6) Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

Modulation Type: 8DPSK

| Low channel: 2402 MHz | | | | | | | | | |
|-----------------------|------------------|---------------------------|-------------------------|------------------------------|------------------|----------------|------------------------|----------------------|----------------|
| Freq. (MHz) | Ant. Pol. H/V | Peak reading (dBuV) | AV reading (dBuV) | Correction Factor (dB) | Emission Level | | Peak limit (dBuV/m) | AV limit (dBuV/m) | Margin (dB) |
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | |
| 1301.23 | H | 51.04 | --- | -4.20 | 46.84 | --- | 74.00 | 54.00 | -7.16 |
| 4804.00 | H | 53.00 | --- | -3.94 | 49.06 | --- | 74.00 | 54.00 | -4.94 |
| 5600.96 | H | 50.38 | --- | -2.83 | 47.55 | --- | 74.00 | 54.00 | -6.45 |
| 7206.00 | H | 46.55 | --- | 0.52 | 47.07 | --- | 74.00 | 54.00 | -6.93 |
| 16814.00 | H | 41.97 | --- | 6.73 | 48.70 | --- | 74.00 | 54.00 | -5.30 |
| 24020.00 | H | 40.38 | --- | 8.11 | 48.49 | --- | 74.00 | 54.00 | -5.51 |
| | | | | | | | | | |
| 1308.54 | V | 52.50 | --- | -4.25 | 48.25 | --- | 74.00 | 54.00 | -5.75 |
| 4804.00 | V | 52.80 | --- | -3.94 | 48.86 | --- | 74.00 | 54.00 | -5.14 |
| 5620.37 | V | 49.70 | --- | -2.87 | 46.83 | --- | 74.00 | 54.00 | -7.17 |
| 7206.00 | V | 44.78 | --- | 0.52 | 45.30 | --- | 74.00 | 54.00 | -8.70 |
| 16814.00 | V | 39.99 | --- | 6.73 | 46.72 | --- | 74.00 | 54.00 | -7.28 |
| 24020.00 | V | 41.14 | --- | 8.11 | 49.25 | --- | 74.00 | 54.00 | -4.75 |

Notes: 1) Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.

2) Radiated emissions measured in frequencies above 1GHz were made with peak detector and Average (AV) detector.

3) Average test would be performed if the peak readings were greater than the average limit.

4) Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

5) Emission Level=Peak (AV) Reading + Correction Factor;

Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

6) Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

Middle channel: 2441 MHz

| Freq. (MHz) | Ant. Pol. H/V | Peak reading (dBuV) | AV reading (dBuV) | Correction Factor (dB) | Emission Level | | Peak limit (dBuV/m) | AV limit (dBuV/m) | Margin (dB) |
|----------------|------------------|---------------------------|-------------------------|------------------------------|------------------|----------------|------------------------|----------------------|----------------|
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | |
| 1301.12 | H | 50.73 | --- | -4.20 | 46.53 | --- | 74.00 | 54.00 | -7.47 |
| 4882.00 | H | 51.28 | --- | -3.98 | 47.30 | --- | 74.00 | 54.00 | -6.70 |
| 5600.45 | H | 50.88 | --- | -2.83 | 48.05 | --- | 74.00 | 54.00 | -5.95 |
| 7323.00 | H | 46.35 | --- | 0.57 | 46.92 | --- | 74.00 | 54.00 | -7.08 |
| 17087.00 | H | 42.95 | --- | 6.79 | 49.74 | --- | 74.00 | 54.00 | -4.26 |
| 24410.00 | H | 41.21 | --- | 8.16 | 49.37 | --- | 74.00 | 54.00 | -4.63 |
| 1308.78 | V | 51.57 | --- | -4.25 | 47.32 | --- | 74.00 | 54.00 | -6.68 |
| 4882.00 | V | 52.36 | --- | -3.98 | 48.38 | --- | 74.00 | 54.00 | -5.62 |
| 5623.57 | V | 50.42 | --- | -2.87 | 47.55 | --- | 74.00 | 54.00 | -6.45 |
| 7323.00 | V | 47.99 | --- | 0.57 | 48.56 | --- | 74.00 | 54.00 | -5.44 |
| 17087.00 | V | 41.74 | --- | 6.79 | 48.53 | --- | 74.00 | 54.00 | -5.47 |
| 24410.00 | V | 33.54 | --- | 8.16 | 41.70 | --- | 74.00 | 54.00 | -12.30 |

Notes: 1) Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.

2) Radiated emissions measured in frequencies above 1GHz were made with peak detector and Average (AV) detector.

3) Average test would be performed if the peak result were greater than the average limit.

4) Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

5) Emission Level=Peak (AV) Reading + Correction Factor;

Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

6) Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

| High channel: 2480 MHz | | | | | | | | | |
|------------------------|------------------|---------------------------|-------------------------|------------------------------|------------------|----------------|------------------------|----------------------|----------------|
| Freq. (MHz) | Ant. Pol. H/V | Peak reading (dBuV) | AV reading (dBuV) | Correction Factor (dB) | Emission Level | | Peak limit (dBuV/m) | AV limit (dBuV/m) | Margin (dB) |
| | | | | | Peak (dBuV/m) | AV (dBuV/m) | | | |
| 1302.66 | H | 50.66 | --- | -4.20 | 46.46 | --- | 74.00 | 54.00 | -7.54 |
| 4960.00 | H | 50.96 | --- | -3.98 | 46.98 | --- | 74.00 | 54.00 | -7.02 |
| 5601.35 | H | 50.70 | --- | -2.83 | 47.87 | --- | 74.00 | 54.00 | -6.13 |
| 7440.00 | H | 47.58 | --- | 0.57 | 48.15 | --- | 74.00 | 54.00 | -5.85 |
| 17360.00 | H | 40.74 | --- | 6.79 | 47.53 | --- | 74.00 | 54.00 | -6.47 |
| 24800.00 | H | 39.8 | --- | 8.16 | 47.96 | --- | 74.00 | 54.00 | -6.04 |
| | | | | | | | | | |
| 1309.27 | V | 50.38 | --- | -4.25 | 46.13 | --- | 74.00 | 54.00 | -7.87 |
| 4960.00 | V | 50.57 | --- | -3.98 | 46.59 | --- | 74.00 | 54.00 | -7.41 |
| 5624.71 | V | 49.37 | --- | -2.87 | 46.50 | --- | 74.00 | 54.00 | -7.50 |
| 7440.00 | V | 48.77 | --- | 0.57 | 49.34 | --- | 74.00 | 54.00 | -4.66 |
| 17360.00 | V | 41.09 | --- | 6.79 | 47.88 | --- | 74.00 | 54.00 | -6.12 |
| 24800.00 | V | 39.19 | --- | 8.16 | 47.35 | --- | 74.00 | 54.00 | -6.65 |

Notes: 1) Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.

2) Radiated emissions measured in frequencies above 1GHz were made with peak detector and Average (AV) detector.

3) Average test would be performed if the peak result were greater than the average limit.

4) Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

5) Emission Level=Peak (AV) Reading + Correction Factor;

Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

6) Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

14.0 Antenna Requirement


14.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitter antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

14.2 Antenna Specification

According to the manufacturer declared, the EUT has an integral antenna; the directional gain of antenna is 1.0 dBi, and no consideration of replacement. Therefore the EUT is considered sufficient to comply with the provision.




ANTENNA

15.0 FCC ID Label

FCC ID: 2AA28SPEAKER

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Mark Location:



--End of the report--