

Maximum Permissible Exposure (MPE)

Standard Applicable

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

RSS 102 issue 5.

This is a Mobile device, the MPE is required.

FCC: According to §1.1310 and §2.1091 RF exposure is calculated.

Limits for Maximum Permissive Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-15000	/	/	1.0	30

F = frequency in MHz

* = Plane-wave equipment power density

RSS 102 Issue 5 Mar. 2015

2.5.2 Exemption Limits for Routine Evaluation – RF Exposure Evaluation

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz⁶ and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $22.48/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

Tune-Up Power and Tolerance:

WLAN: 1TX, 1RX

Wi-Fi	Frequency Range (MHz)	Channels	Average Tune-Up Power	Modulation Technology
802.11b	2412 – 2462(DTS)	11	Channel 1-11 19.0 dBm (AV)	DSSS
802.11g	2412 – 2462(DTS)	11	Channel 1-11 13.0 dBm (AV)	DSSS, OFDM
802.11n	HT20 2412 – 2462(DTS)	11	Channel 3-9 10.0 dBm (AV)	OFDM
	HT40 2422 – 2452(DTS)	7	Channel 3-9 10.0 dBm (AV)	
Power Tolerance:		+/- 1 dBm		

FCC: 2.4GHz mode: 802.11g mode

Maximum Permissible Exposure (MPE) Evaluation: The worst case of Average power

Power measurement: refer to Prt15.247 and RSS 210 report for details.

802.11g

Cable loss = 0		Output Power		Limit (dBm)	
CH	Detector				
	PK (dBm)	AV (dBm)			
Low	21.37	11.83	30	30	
Mid	22.25	12.65			
High	22.93	13.37			

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = Power density

P = Power input to antenna

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

	CH 1-11	
Tune-Up power at antenna input terminal:	13.37	(dBm)
Tune-Up power at antenna input terminal:	21.73	(mW)
Tune-Up power Tolerance:	1.00	dB
Duty cycle:	100.00	(%)
Maximum Pav :	27.35	(mW)
Antenna gain (typical):	-1.91	(dBi)
Maximum antenna gain:	0.64	(numeric)
Prediction distance:	20.00	(cm)
MPE limit for uncontrolled exposure at prediction frequency:	1.00	(mW/cm^2)
Power density at predication frequency at 20 (cm) distance	0.0035	(mW/cm^2)

Measurement Result:

The worst power density is 0.0035 mW/cm^2 which is less than 1 mW/cm^2.

IC EIRP/Conducted Power level: 802.11g mode

	CH 1-11 2462	MHz
Tune-UP power at antenna input terminal:	13.37	(dBm)
Tune-Up power Tolerance:	1	dB
Duty cycle:	100	(%)
Antenna gain (typical):	-1.91	(dBi)
Conducted Power:	27.353	mW
Conducted Power:	0.02735	W
EIRP:	17.620	mW
EIRP:	0.01762	W
EIRP Limit	2.722	W

Measurement Result:

The Conducted Power level is 0.01762W which less than RSS102 section 2.5.2 Exemption Limits (2.722W) above 300 MHz and below 6 GHz condition .

~~ End ~~