



飛宏科技股份有限公司

PHIHONG TECHNOLOGY CO., LTD.

4G +WIFI Module User Manual

Product Name: EV charging system module 4G with WI-FI

Manufacturer: Phihong Technology Co., Ltd.

Model name: DLWPH-8M-RW , DLWPH-8M

Power	DC 10-25V for LTE Selectable 1.8 V or 3.3 V IO levels for WiFi
Energy consumption	200-500mA
Interface	Micro USB Type B
Support band	LTE:B2/B4/B5/B12/B13/B14/B66/B71 WCDMA: B2/B4/B5 IEEE 802.11b/g/n
Operating temperature	-30 ° C to 50 ° C

Federal Communication Commission Interference Statement

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

FCC Caution: Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment.

This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.

Radiation Exposure Statement:

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator & your body.

This module is intended for OEM integrators only. Per FCC KDB 996369 D03 OEM Manual v01 guidance, the following conditions must be strictly followed when using this certified module:

KDB 996369 D03 OEM Manual v01 rule sections:

2.2 List of applicable FCC rules

This module has been tested for compliance to FCC Part 15.247, 22H, 24E, 27, 90R

2.3 Summarize the specific operational use conditions

The module is tested for standalone mobile RF exposure use condition. Any other usage conditions such as co-location with other transmitter(s) or being used in a portable condition will need a separate reassessment through a class II permissive change application or new certification.

2.4 Limited module procedures

Not applicable.

2.5 Trace antenna designs

Not applicable.

2.6 RF exposure considerations

This equipment complies with FCC mobile radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance of 20cm between the radiator & your body. If the module is installed in a portable host, a separate SAR evaluation is required to confirm compliance with relevant FCC portable RF exposure rules.

2.7 Antennas

The following antennas have been certified for use with this module; antennas of the same type with equal or lower gain may also be used with this module. The antenna must be installed such that 20 cm can be maintained between the antenna and users.

Antenna Type	External PCB Antenna	Internal PCB Antenna														
Manufacturer	Gortec	ublox														
Antenna Connector	Wi-Fi: R-SMA Male WWAN: SMA Male	Wi-Fi: N/A WWAN: N/A, External Only														
Antenna Gain	Brand: Gortec, Model: DR0727-4201BSM <table border="1" data-bbox="486 443 933 936"> <tr> <td>Wi-Fi:</td> <td>3.15 dBi</td> </tr> <tr> <td>WCDMA/LTE B2:</td> <td>1.47 dBi</td> </tr> <tr> <td>WCDMA B4 & LTE B4/B66:</td> <td>1.70 dBi</td> </tr> <tr> <td>WCDMA/LTE B5:</td> <td>-0.37 dBi</td> </tr> <tr> <td>LTE B12:</td> <td>-1.09 dBi</td> </tr> <tr> <td>LTE B13/B14:</td> <td>-3.11 dBi</td> </tr> <tr> <td>LTE B71:</td> <td>-2.45 dBi</td> </tr> </table>	Wi-Fi:	3.15 dBi	WCDMA/LTE B2:	1.47 dBi	WCDMA B4 & LTE B4/B66:	1.70 dBi	WCDMA/LTE B5:	-0.37 dBi	LTE B12:	-1.09 dBi	LTE B13/B14:	-3.11 dBi	LTE B71:	-2.45 dBi	Wi-Fi: 2 dBi WWAN: N/A, External Only
Wi-Fi:	3.15 dBi															
WCDMA/LTE B2:	1.47 dBi															
WCDMA B4 & LTE B4/B66:	1.70 dBi															
WCDMA/LTE B5:	-0.37 dBi															
LTE B12:	-1.09 dBi															
LTE B13/B14:	-3.11 dBi															
LTE B71:	-2.45 dBi															

2.8 Label and compliance information

The final end product must be labeled in a visible area with the following: “Contains FCC ID: 2AARN-DLWPH-8M”. The grantee's FCC ID can be used only when all FCC compliance requirements are met.

2.9 Information on test modes and additional testing requirements

This transmitter is tested in a standalone mobile RF exposure condition and any co-located or simultaneous transmission with other transmitter(s) or portable use will require a separate class II permissive change re-evaluation or new certification.

2.10 Additional testing, Part 15 Subpart B disclaimer

This transmitter module is tested as a subsystem and its certification does not cover the FCC Part 15 Subpart B (unintentional radiator) rule requirement applicable to the final host. The final host will still need to be reassessed for compliance to this portion of rule requirements if applicable.

As long as all conditions above are met, further transmitter test will not be required. However, the OEM integrator is still responsible for testing their end-product for any additional compliance requirements required with this module installed.

IMPORTANT NOTE: In the event that these conditions can not be met (for example certain laptop configurations or co-location with another transmitter), then the FCC authorization is no longer considered valid and the FCC ID can not be used on the final product. In these circumstances, the OEM integrator will be responsible for re-evaluating the end product (including the transmitter) and

obtaining a separate FCC authorization.

Manual Information To the End User

The OEM integrator has to be aware not to provide information to the end user regarding how to install or remove this RF module in the user's manual of the end product which integrates this module.

The end user manual shall include all required regulatory information/warning as show in this manual.

OEM/Host manufacturer responsibilities

OEM/Host manufacturers are ultimately responsible for the compliance of the Host and Module. The final product must be reassessed against all the essential requirements of the FCC rule such as FCC Part 15 Subpart B before it can be placed on the US market. This includes reassessing the transmitter module for compliance with the Radio and EMF essential requirements of the FCC rules. This module must not be incorporated into any other device or system without retesting for compliance as multi-radio and combined equipment.



飛宏科技股份有限公司

PHIHONG TECHNOLOGY CO., LTD.

Industry Canada statement:

This device complies with ISED's licence-exempt RSSs. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Le présent appareil est conforme aux CNR d'ISED applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes : (1) le dispositif ne doit pas produire de brouillage préjudiciable, et (2) ce dispositif doit accepter tout brouillage reçu, y compris un brouillage susceptible de provoquer un fonctionnement indésirable.

Radiation Exposure Statement:

This equipment complies with ISED radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with greater than 20cm between the radiator & your body.

Déclaration d'exposition aux radiations:

Cet équipement est conforme aux limites d'exposition aux rayonnements ISED établies pour un environnement non contrôlé. Cet équipement doit être installé et utilisé à plus de 20 cm entre le radiateur et votre corps.



飛宏科技股份有限公司

PHIHONG TECHNOLOGY CO., LTD.

This device is intended only for OEM integrators under the following conditions: (For module device use)

- 1) The antenna must be installed and operated with greater than 20cm between the antenna and users, and
- 2) The transmitter module may not be co-located with any other transmitter or antenna.

As long as 2 conditions above are met, further transmitter test will not be required. However, the OEM integrator is still responsible for testing their end-product for any additional compliance requirements required with this module installed.

Cet appareil est conçu uniquement pour les intégrateurs OEM dans les conditions suivantes: (Pour utilisation de dispositif module)

- 1) L'antenne doit être installé et exploité avec plus de 20 cm entre l'antenne et les utilisateurs, et
- 2) Le module émetteur peut ne pas être coimplanté avec un autre émetteur ou antenne.

Tant que les 2 conditions ci-dessus sont remplies, des essais supplémentaires sur l'émetteur ne seront pas nécessaires. Toutefois, l'intégrateur OEM est toujours responsable des essais sur son produit final pour toutes exigences de conformité supplémentaires requis pour ce module installé.

IMPORTANT NOTE:

In the event that these conditions can not be met (for example certain laptop configurations or co-location with another transmitter), then the Canada authorization is no longer considered valid and the IC ID can not be used on the final product. In these circumstances, the OEM integrator will be responsible for re-evaluating the end product (including the transmitter) and obtaining a separate Canada authorization.

NOTE IMPORTANTE:

Dans le cas où ces conditions ne peuvent être satisfaites (par exemple pour certaines configurations d'ordinateur portable ou de certaines co-localisation avec un autre émetteur), l'autorisation du Canada n'est plus considéré comme valide et l'ID IC ne peut pas être utilisé sur le produit final. Dans ces circonstances, l'intégrateur OEM sera chargé de réévaluer le produit final (y compris l'émetteur) et l'obtention d'une autorisation distincte au Canada.



飛宏科技股份有限公司

PHIHONG TECHNOLOGY CO., LTD.

End Product Labeling

This transmitter module is authorized only for use in device where the antenna may be installed and operated with greater than 20cm between the antenna and users. The final end product must be labeled in a visible area with the following: “Contains IC: **26049-DLWPH8M**”.

Plaque signalétique du produit final

Ce module émetteur est autorisé uniquement pour une utilisation dans un appareil où l’antenne peut être installée et utilisée à plus de 20 cm entre l’antenne et les utilisateurs. Le produit final doit être étiqueté dans un endroit visible avec l’inscription suivante: "Contient des IC: **26049-DLWPH8M** ".

Manual Information To the End User

The OEM integrator has to be aware not to provide information to the end user regarding how to install or remove this RF module in the user’s manual of the end product which integrates this module.

The end user manual shall include all required regulatory information/warning as show in this manual.

Manuel d'information à l'utilisateur final

L'intégrateur OEM doit être conscient de ne pas fournir des informations à l'utilisateur final quant à la façon d'installer ou de supprimer ce module RF dans le manuel de l'utilisateur du produit final qui intègre ce module.

Le manuel de l'utilisateur final doit inclure toutes les informations réglementaires requises et avertissements comme indiqué dans ce manuel.



飛宏科技股份有限公司

PHIHONG TECHNOLOGY CO., LTD.

This radio transmitter [IC: 26049-DLWPH8M] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Le présent émetteur radio [IC: 26049-DLWPH8M] a été approuvé par Innovation, Sciences et Développement économique Canada pour fonctionner avec les types d'antenne énumérés ci-dessous et ayant un gain admissible maximal. Les types d'antenne non inclus dans cette liste, et dont le gain est supérieur au gain maximal indiqué pour tout type figurant sur la liste, sont strictement interdits pour l'exploitation de l'émetteur.

Antenna Type	External PCB Antenna	Internal PCB Antenna														
Manufacturer	Gortec	ublox														
Antenna Connector	Wi-Fi: R-SMA Male WWAN: SMA Male	Wi-Fi: N/A WWAN: N/A, External Only														
Antenna Gain	Brand: Gortec, Model: DR0727-4201BSM <table border="1"><tr><td>Wi-Fi:</td><td>3.15 dBi</td></tr><tr><td>WCDMA/LTE B2:</td><td>1.47 dBi</td></tr><tr><td>WCDMA B4 & LTE B4/B66:</td><td>1.70 dBi</td></tr><tr><td>WCDMA/LTE B5:</td><td>-0.37 dBi</td></tr><tr><td>LTE B12:</td><td>-1.09 dBi</td></tr><tr><td>LTE B13/B14:</td><td>-3.11 dBi</td></tr><tr><td>LTE B71:</td><td>-2.45 dBi</td></tr></table>	Wi-Fi:	3.15 dBi	WCDMA/LTE B2:	1.47 dBi	WCDMA B4 & LTE B4/B66:	1.70 dBi	WCDMA/LTE B5:	-0.37 dBi	LTE B12:	-1.09 dBi	LTE B13/B14:	-3.11 dBi	LTE B71:	-2.45 dBi	Wi-Fi: 2 dBi WWAN: N/A, External Only
Wi-Fi:	3.15 dBi															
WCDMA/LTE B2:	1.47 dBi															
WCDMA B4 & LTE B4/B66:	1.70 dBi															
WCDMA/LTE B5:	-0.37 dBi															
LTE B12:	-1.09 dBi															
LTE B13/B14:	-3.11 dBi															
LTE B71:	-2.45 dBi															