

# RF Exposure Report

Report No.: AGC00288200302FH03

**APPLICATION PURPOSE** : Original Equipment  
**PRODUCT DESIGNATION** : JOINT LED TABLE LAMP WITH WIRELESS CHARGING  
**BRAND NAME** : N/A  
**MODEL NAME** : HSD9051E-5, HSD9051E-10, HSD9051E  
**APPLICANT** : SHENZHEN HIGHSTAR ELECTRICAL CO.,LTD  
**DATE OF ISSUE** : Apr. 30, 2020  
**STANDARD(S)** : KDB680106 D01 RF Exposure Wireless Charging Base  
App v03  
**REPORT VERSION** : V1.0

## Attestation of Global Compliance(Shenzhen) Co., Ltd

### CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,  
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline:400 089 2118

## REPORT REVISE RECORD

| Report Version | Revise Time | Issued Date   | Valid Version | Notes           |
|----------------|-------------|---------------|---------------|-----------------|
| V1.0           | /           | Apr. 30, 2020 | Valid         | Initial Release |



## TABLE OF CONTENTS

|                                             |    |
|---------------------------------------------|----|
| 1. VERIFICATION OF CONFORMITY .....         | 4  |
| 2. GENERAL INFORMATION.....                 | 5  |
| 2.1. PRODUCT DESCRIPTION .....              | 5  |
| 3. DESCRIPTION OF TEST MODES.....           | 6  |
| 4. SYSTEM TEST CONFIGURATION .....          | 6  |
| 5. TEST FACILITY .....                      | 7  |
| 6. RADIO FREQUENCY (RF) EXPOSURE TEST ..... | 8  |
| 6.1. LIMITS.....                            | 8  |
| 6.2. TEST SETUP.....                        | 8  |
| APPENDIX A: PHOTOGRAPHS OF TEST SETUP ..... | 11 |



## 1. VERIFICATION OF CONFORMITY

|                                 |                                                                                                                        |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------|
| <b>Applicant</b>                | SHENZHEN HIGHSTAR ELECTRICAL CO.,LTD                                                                                   |
| <b>Address</b>                  | 2F,4&5F, Building6,Ya Lian Highstar Industrial Zone,5022 Wuhe Avenue,Bantian Street,Longgang District, Shenzhen China. |
| <b>Manufacturer</b>             | SHENZHEN HIGHSTAR ELECTRICAL CO.,LTD                                                                                   |
| <b>Address</b>                  | 2F,4&5F, Building6,Ya Lian Highstar Industrial Zone,5022 Wuhe Avenue,Bantian Street,Longgang District, Shenzhen China. |
| <b>Factory</b>                  | SHENZHEN HIGHSTAR ELECTRICAL CO.,LTD                                                                                   |
| <b>Address</b>                  | 2F,4&5F, Building6,Ya Lian Highstar Industrial Zone,5022 Wuhe Avenue,Bantian Street,Longgang District, Shenzhen China. |
| <b>Product Designation</b>      | JOINT LED TABLE LAMP WITH WIRELESS CHARGING                                                                            |
| <b>Brand Name</b>               | N/A                                                                                                                    |
| <b>Test Model:</b>              | HSD9051E-5                                                                                                             |
| <b>Series Model</b>             | HSD9051E-10, HSD9051E                                                                                                  |
| <b>Model Difference</b>         | All the same except for the model name                                                                                 |
| <b>Date of test</b>             | Mar. 20, 2020 to Apr. 30, 2020                                                                                         |
| <b>Deviation</b>                | No any deviation from the test method                                                                                  |
| <b>Condition of Test Sample</b> | Normal                                                                                                                 |
| <b>Report Template</b>          | AGCRT-US-BR/RF                                                                                                         |

We hereby certify that:

The above equipment was tested by Attestation of GlobalCompliance(Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in KDB680106 D01.

The results of testing in this report apply to the product/system which was tested only.

Prepared By

*Nini Guo*

Nini Guo  
(Project Engineer)

Apr. 30, 2020

Reviewed By

*Max Zhang*

Max Zhang  
(Reviewer)

Apr. 30, 2020

Approved By

*Forrest Lei*

Forrest Lei  
(Authorized Officer)

Apr. 30, 2020

## 2. GENERAL INFORMATION

### 2.1.PRODUCT DESCRIPTION

A major technical description of EUT is described as following

|                        |                                                     |
|------------------------|-----------------------------------------------------|
| Operation Frequency    | 110-205 kHz                                         |
| Test Frequency         | 125.6kHz                                            |
| Maximum field strength | 54.63dBuV/m(PK)@3m                                  |
| Number of channels     | 1                                                   |
| Antenna Designation    | Integrated Antenna (Met 15.203 Antenna requirement) |
| Hardware Version       | V1.0                                                |
| Software Version       | V1.0                                                |
| Power Supply           | DC 12V by adapter                                   |



### 3. DESCRIPTION OF TEST MODES

| NO.                                                                                         | TEST MODE DESCRIPTION             |
|---------------------------------------------------------------------------------------------|-----------------------------------|
| 1                                                                                           | Wireless charging Mode(Full load) |
| 2                                                                                           | Wireless charging Mode(Half load) |
| 3                                                                                           | Wireless charging Mode(Null load) |
| Note:                                                                                       |                                   |
| 1. The mode 1 was the worst case and only the data of the worst case record in this report. |                                   |

### 4. SYSTEM TEST CONFIGURATION

| Item | Equipment                               | Model No.     | ID or Specification                                  | Remark |
|------|-----------------------------------------|---------------|------------------------------------------------------|--------|
| 1    | Promo Wireless Charger with Phone Stand | SA307         | 2AAZRHSD9051E-5                                      | EUT    |
| 2    | Adapter                                 | TY1200200A1mn | Input:100-240v, 50/60Hz, 0.8A<br>Output: 12.0V, 2.0A | AE     |
| 3    | Wireless Load                           | N/A           | 5W                                                   | AE     |

## 5. TEST FACILITY

|                                          |                                                                                                                          |
|------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| <b>TestSite</b>                          | Attestation of Global Compliance(Shenzhen) Co., Ltd                                                                      |
| <b>Location</b>                          | 1-2/F,Building19,JunfengIndustrialPark,ChongqingRoad,HepingCommunity,FuhaiStreet,Bao'anDistrict,Shenzhen,Guangdong,China |
| <b>Designation Number</b>                | CN1259                                                                                                                   |
| <b>FCC Test Firm Registration Number</b> | 975832                                                                                                                   |
| <b>A2LA Cert. No.</b>                    | 5054.02                                                                                                                  |
| <b>Description</b>                       | Attestation of Global Compliance(Shenzhen) Co., Ltd is accredited by A2LA                                                |

## TEST EQUIPMENT LIST

| Description           | Manufacturer                     | Model   | S/N    | Cal. Date   | Cal. Due    |
|-----------------------|----------------------------------|---------|--------|-------------|-------------|
| Broadband Field Meter | Narda Safety Test Solutions GmbH | NBM-550 | J-0004 | Jun.12,2019 | Jun.11,2020 |
| Probe FHP             | Narda Safety Test Solutions GmbH | EHP-50F | J-0015 | Jun.12,2019 | Jun.11,2020 |




## 6. RADIO FREQUENCY(RF) EXPOSURETEST

### 6.1. LIMITS

For devices designed for typical desktop applications, such a wireless charging pads, RF exposure evaluation should be conducted assuming a user separation distance of 15 cm. E and H field strength measurements or numerical modeling may be used to demonstrate compliance. Measurements should be made from all sides and the top of the primary/client pair, with the 15 cm measured from the center of the probe(s) to the edge of the device. Emissions between 100 kHz to 300 kHz should be assessed versus the limits at 300 kHz in Table 1 of Section 1.1310: 614 V/m and 1.63 A/m.

### 6.2. TEST SETUP



Note: Position A: Front of EUT; Position B: Left of EUT; Position C: back of EUT; Position D: Right of EUT; Position E: Top of EUT(20 cm measure distance);

### 6.3. TEST PROCEDURE

The EUT was placed on a non-conductive table top and the ancillary equipment (e.g. mobile phone) was placed on the EUT for charging.

Maximum E-field and H-field measurements were tested 15cm from each side of the EUT. For top side the measure distance is 20cm.

Along the side of the EUT to center of E-field probe and H-field probe were positioned at the location to search maximum field strength.



#### 6.4. TEST RESULT

Test condition: Mode 1

E-field strength test result:

| Frequency Range | Probe Position A (V/m) | Probe Position B (V/m) | Probe Position C (V/m) | Probe Position D (V/m) | Probe Position E (V/m) | Limit (V/m) |
|-----------------|------------------------|------------------------|------------------------|------------------------|------------------------|-------------|
| 125.6kHz        | 1.01                   | 1.01                   | 1.02                   | 1.01                   | 1.42                   | 614         |

H-field strength test result:

| Frequency Range | Probe Position A (A/m) | Probe Position B (A/m) | Probe Position C (A/m) | Probe Position D (A/m) | Probe Position E (A/m) | Limit (A/m) |
|-----------------|------------------------|------------------------|------------------------|------------------------|------------------------|-------------|
| 125.6kHz        | 0.45                   | 0.44                   | 0.51                   | 0.49                   | 0.60                   | 1.63        |

Test condition: Mode 2

E-field strength test result:

| Frequency Range | Probe Position A (V/m) | Probe Position B (V/m) | Probe Position C (V/m) | Probe Position D (V/m) | Probe Position E (V/m) | Limit (V/m) |
|-----------------|------------------------|------------------------|------------------------|------------------------|------------------------|-------------|
| 129.3kHz        | 0.85                   | 0.86                   | 0.84                   | 0.85                   | 0.94                   | 614         |

H-field strength test result:

| Frequency Range | Probe Position A (A/m) | Probe Position B (A/m) | Probe Position C (A/m) | Probe Position D (A/m) | Probe Position E (A/m) | Limit (A/m) |
|-----------------|------------------------|------------------------|------------------------|------------------------|------------------------|-------------|
| 129.3kHz        | 0.26                   | 0.27                   | 0.30                   | 0.28                   | 0.44                   | 1.63        |



Test condition: Mode 3

E-field strength test result:

| Frequency Range | Probe Position A (V/m) | Probe Position B (V/m) | Probe Position C (V/m) | Probe Position D (V/m) | Probe Position E (V/m) | Limit (V/m) |
|-----------------|------------------------|------------------------|------------------------|------------------------|------------------------|-------------|
| 134.8kHz        | 0.66                   | 0.65                   | 0.65                   | 0.64                   | 0.72                   | 614         |

H-field strength test result:

| Frequency Range | Probe Position A (A/m) | Probe Position B (A/m) | Probe Position C (A/m) | Probe Position D (A/m) | Probe Position E (A/m) | Limit (A/m) |
|-----------------|------------------------|------------------------|------------------------|------------------------|------------------------|-------------|
| 134.8kHz        | 0.12                   | 0.12                   | 0.10                   | 0.10                   | 0.14                   | 1.63        |



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,  
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China


Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com


Service Hotline: 400 089 2118

## APPENDIX A: PHOTOGRAPHS OF TEST SETUP

Position E



Position A



Attestation of Global Compliance

Attestation of Global Compliance(Shenzhen)Co.,Ltd.


Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,  
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088


E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118


Position B



Position C



Position D



----END OF REPORT----



**Attestation of Global Compliance**

Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, Sanwei Chaxi Industrial Park, Sanwei Community,  
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755 2523 4088

E-mail: agc@agc-cert.com

Service Hotline: 400 089 2118