



中国认可
国际互认
检测
TESTING
CNAS L5313



RF Exposure Evaluation Declaration

Product Name : August Smart Door Lock

Model No. : ASL-03

FCC ID : 2AB6UASL3

Applicant : August Home, Inc.

Address : 657 Bryant Street, San Francisco, 94107, USA

Date of Receipt : Feb. 21st, 2017

Test Date : Feb. 21st, 2017~ Mar. 27th, 2017

Issued Date : Apr. 13th, 2017

Report No. : 1722089R-RF-US- P20V02

Report Version : V1.1

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by CNAS, TAF or any agency of the government.

The test report shall not be reproduced without the written approval of DEKRA Testing & Certification (Suzhou) Co., Ltd.

Test Report Certification

Issued Date : Apr. 13th, 2017

Report No. : 1722089R-RF-US-P20V02



Product Name : August Smart Door Lock
Applicant : August Home Inc.
Address : 657 Bryant Street, San Francisco, 94107, USA
Manufacturer : GoerTek Inc
Address : No.8877 Yingqian Street, High-Tech Industrial Development District, Weifang, Shandong, 261031, P.R.China
Model No. : ASL-03
FCC ID : 2AB6UASL3
EUT Voltage : DC 6V
Applicable Standard : KDB 447498D01V06
Test Result : Complied
Performed Location : DEKRA Testing & Certification (Suzhou) Co., Ltd.
No.99 Hongye Rd., Suzhou Industrial Park, Suzhou, 215006, Jiangsu, China
TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098
FCC Registration Number: 800392

Documented By : 

(Adm. Specialist: Kathy Feng)

Reviewed By : 

(Senior Engineer: Frank He)

Approved By : 

(Engineering Manager : Harry Zhao)

RF Exposure Evaluation

1.1. Limits

According to **KDB 447498 D01 General RF Exposure Guidance v06**

4.3.1 Standalone SAR test exclusion considerations

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$
 ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

2) At 100 MHz to 6 GHz and for test separation distances > 50 mm, the SAR test exclusion threshold is determined according to the following, and as illustrated in Appendix B:

- a) $[\text{Power allowed at numeric threshold for } 50 \text{ mm in step 1} + (\text{test separation distance} - 50 \text{ mm}) \cdot (f(\text{MHz})/150)] \text{ mW}$, at 100 MHz to 1500 MHz
- b) $[\text{Power allowed at numeric threshold for } 50 \text{ mm in step 1} + (\text{test separation distance} - 50 \text{ mm}) \cdot 10] \text{ mW}$ at $> 1500 \text{ MHz}$ and $\leq 6 \text{ GHz}$

3) The 1-g and 10-g SAR test exclusion thresholds for below 100 MHz at test separation distances ≤ 50 mm are determined by:

- a) The power threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by $[1 + \log(100/f(\text{MHz}))]$ for test separation distances > 50 mm and < 200 mm
- b) The power threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by $\frac{1}{2}$ for test separation distances ≤ 50 mm
- c) SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable. Note: when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product	:	August Smart Door Lock
Test Item	:	RF Exposure Evaluation
Test Site	:	AC-6

● Antenna Information:

Model No.	N/A					
Antenna manufacturer	N/A					
Antenna Delivery	<input checked="" type="checkbox"/>	1*TX+1*RX	<input type="checkbox"/>	2*TX+2*RX	<input type="checkbox"/>	3*TX+3*RX
Antenna technology	<input checked="" type="checkbox"/>	SISO				
	<input type="checkbox"/>	MIMO	<input type="checkbox"/>	Basic		
	<input type="checkbox"/>		<input type="checkbox"/>	CDD		
	<input type="checkbox"/>		<input type="checkbox"/>	Sectorized		
	<input type="checkbox"/>		<input type="checkbox"/>	Beam-forming		
Antenna Type	<input type="checkbox"/>	External	<input type="checkbox"/>	Dipole		
	<input type="checkbox"/>		<input type="checkbox"/>	Sectorized		
	<input checked="" type="checkbox"/>	Internal	<input type="checkbox"/>	PIFA		
	<input checked="" type="checkbox"/>		<input type="checkbox"/>	PCB		
	<input type="checkbox"/>		<input type="checkbox"/>	Ceramic Chip Antenna		
	<input type="checkbox"/>		<input type="checkbox"/>	Metal plate type F antenna		
Antenna Technology	Ant Gain (dBi)					
<input checked="" type="checkbox"/> SISO	4					

Based on The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm and the formula below:

$$\text{Estimated SAR} = \sqrt{f(\text{GHz})} * \frac{(\text{Max Power of channel, mW})}{\text{Min. Separation Distance, mm}}$$

The Maximum tune-up power of BLE is 0dBm and -0.5dBm for Z-wave.

Band	Exposure Condition	Pmax Conducted	Gain	Pmax	Distance	f(GHz)	calculation result	Stand-alone Test exclusion threshold	SAR Test
		(dBm)	(dBi)	(mw)	(mm)				
BLE	Body	0	4	2.51	5	2.402	0.78	3.00	No
Z-Wave	Body	-0.5	4	2.24	5	0.9084	0.43	3.00	No

Conclusion: 908MHz-916MHz, 2402MHz-2480MHz SAR was not required.

— The End —