



# FCC PART 15, SUBPART C ISED C RSS-247, ISSUE 2, FEBRUARY 2017

## TEST AND MEASUREMENT REPORT

For

### August Home, Inc

657 Bryant Street,  
San Francisco, CA 94107, USA

**FCC ID: 2AB6UMD02  
IC: 12163A-MD02**

<b>Report Type:</b> Original Report	<b>Product Type:</b> BLE Radio module
<b>Prepared By:</b> Rita Yang RF Test Technician	
<b>Report Number:</b> R2107236-247	
<b>Report Date:</b> 2021-08-23	
<b>Reviewed By:</b> Christian McCaig RF Project Engineer 	
Bay Area Compliance Laboratories Corp. 1274 Anvilwood Avenue, Sunnyvale, CA 94089, USA Tel: +1 (408) 732-9162, Fax: +1 (408) 732-9164	



**Note:** This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by A2LA\*, NIST, or any agency of the Federal Government.

\* This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “\*” (Rev.2)

## TABLE OF CONTENTS

<b>1 General Description.....</b>	<b>5</b>
1.1 Product Description for Equipment Under Test (EUT) .....	5
1.2 Mechanical Description of EUT .....	5
1.3 Objective .....	5
1.4 Related Submittal(s)/Grant(s) .....	5
1.5 Test Methodology .....	5
1.6 Measurement Uncertainty .....	6
1.7 Test Facility Registrations .....	6
1.8 Test Facility Accreditations .....	7
<b>2 System Test Configuration.....</b>	<b>9</b>
2.1 Justification .....	9
2.2 EUT Exercise Software.....	9
2.3 Duty Cycle Correction Factor .....	9
2.4 Equipment Modifications.....	11
2.5 Local Support Equipment .....	11
2.6 Remote Support Equipment.....	11
2.7 Interface Ports and Cabling.....	11
<b>3 Summary of Test Results .....</b>	<b>12</b>
<b>4 FCC §15.203 &amp; ISEDC RSS-Gen §6.8 - Antenna Requirements .....</b>	<b>13</b>
4.1 Applicable Standards .....	13
4.2 Antenna Description .....	13
<b>5 FCC §2.1091, §15.247(i) &amp; ISEDC RSS-102 – RF Exposure.....</b>	<b>14</b>
5.1 Applicable Standards .....	14
5.2 MPE Prediction.....	15
5.3 MPE Results .....	15
5.4 RF exposure evaluation exemption for IC .....	15
<b>6 FCC §15.209, §15.247(d) &amp; ISEDC RSS-247 §5.5, RSS-Gen §8.9, §8.10 - Spurious Radiated Emissions.....</b>	<b>16</b>
6.1 Applicable Standards .....	16
6.2 Test Setup .....	17
6.3 Test Procedure .....	18
6.4 Corrected Amplitude & Margin Calculation.....	18
6.5 Test Equipment List and Details .....	19
6.6 Test Environmental Conditions .....	19
6.7 Summary of Test Results .....	20
6.8 Radiated Emissions Test Results .....	20
<b>7 FCC §15.247(a) (2) &amp; ISEDC RSS-247 §5.2, RSS-Gen §6.7 - Emission Bandwidth.....</b>	<b>25</b>
7.1 Applicable Standards .....	25
7.2 Measurement Procedure.....	25
7.3 Test Equipment List and Details .....	25
7.4 Test Environmental Conditions .....	25
7.5 Test Results.....	26
<b>8 FCC §15.247(b) (3) &amp; ISEDC RSS-247 §5.4 – Maximum Output Power.....</b>	<b>33</b>
8.1 Applicable Standards .....	33
8.2 Measurement Procedure.....	33
8.3 Test Equipment List and Details .....	33
8.4 Test Environmental Conditions .....	33
8.5 Test Results.....	34
<b>9 FCC §15.247(e) &amp; ISEDC RSS-247 §5.2(2) – Peak Power Spectral Density .....</b>	<b>38</b>
9.1 Applicable Standards .....	38
9.2 Measurement Procedure.....	38
9.3 Test Equipment List and Details .....	38
9.4 Test Environmental Conditions .....	38
9.5 Test Results.....	39
<b>10 FCC §15.247(d) &amp; ISEDC RSS-247 §5.5 - 100 kHz Bandwidth of Band Edges.....</b>	<b>44</b>
10.1 Applicable Standards .....	44

---

10.2	Measurement Procedure.....	44
10.3	Test Equipment List and Details .....	44
10.4	Test Environmental Conditions .....	44
10.5	Test Results.....	45
<b>11</b>	<b>FCC §15.247(d) &amp; ISEDC RSS-247 §5.5 - Spurious Emissions at Antenna Terminals .....</b>	<b>47</b>
11.1	Applicable Standards .....	47
11.2	Test Procedure .....	47
11.3	Test Equipment List and Details .....	47
11.4	Test Environmental Conditions .....	47
11.5	Test Results.....	48
<b>12</b>	<b>Annex A (Normative) - Test Setup Photographs.....</b>	<b>52</b>
<b>13</b>	<b>Annex B (Normative) - EUT External Photographs.....</b>	<b>53</b>
<b>14</b>	<b>Annex C (Normative) - EUT Internal Photographs .....</b>	<b>54</b>
<b>15</b>	<b>Annex D (Normative) - A2LA Electrical Testing Certificate.....</b>	<b>55</b>

## DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	R2107236-247	Original Report	2021-08-23

## 1 General Description

---

### 1.1 Product Description for Equipment Under Test (EUT)

This test and measurement report was prepared on behalf of *August Home, Inc.*, and their product model: *MD-02, FCC ID: 2AB6UMD02, IC: 12163A-MD02* or the “EUT” as referred to in this report. It is a BLE Radio module

### 1.2 Mechanical Description of EUT

EUT measures approximately 5.67 cm (Length), 2.80 cm (Width), 1.29 cm (Height) and 0.015 weight(kg).

*The data gathered is from a production sample provided by August Home, Inc with the assigned serial numbers: M1FXQOOOK5.*

### 1.3 Objective

This report was prepared on behalf of *August Home, Inc* in accordance with Part 2, Subpart J, and Part 15, Subpart C of the Federal Communication Commission’s rules and ISED RSS-247 Issue 2, February 2017.

The objective was to determine compliance with FCC Part 15.247 and ISED RSS-247 for Antenna Requirement, RF Exposure, AC Line Conducted Emissions, Emission Bandwidth, Radiated & Conducted Spurious Emissions, 100 kHz Band Edges, Maximum Output Power, and Peak Power Spectrum Density

### 1.4 Related Submittal(s)/Grant(s)

N/A

### 1.5 Test Methodology

All measurements contained in this report were conducted in accordance with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

## 1.6 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in the field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Parameter	Measurement uncertainty
Occupied Channel Bandwidth	$\pm 5\%$
RF output power, conducted	$\pm 0.57\text{ dB}$
Power Spectral Density, conducted	$\pm 1.48\text{ dB}$
Unwanted Emissions, conducted	$\pm 1.57\text{ dB}$
All emissions, radiated	$\pm 4.0\text{ dB}$
AC power line Conducted Emission	$\pm 2.0\text{ dB}$
Temperature	$\pm 2\text{ }^{\circ}\text{C}$
Humidity	$\pm 5\%$
DC and low frequency voltages	$\pm 1.0\%$
Time	$\pm 2\%$
Duty Cycle	$\pm 3\%$

## 1.7 Test Facility Registrations

BACL's test facilities that are used to perform Radiated and Conducted Emissions tests are currently recognized by the Federal Communications Commission as Accredited with NIST Designation Number US1129.

BACL's test facilities that are used to perform Radiated and Conducted Emissions tests are currently registered with Industry Canada under Registration Numbers: 3062A-1, 3062A-2, and 3062A-3.

BACL is a Chinese Taipei Bureau of Standards Metrology and Inspection (BSMI) validated Conformity Assessment Body (CAB), under Appendix B, Phase I Procedures of the APEC Mutual Recognition Arrangement (MRA). BACL's BSMI Lab Code Number is: SL2-IN-E-1002R

BACL's test facilities that are used to perform AC Line Conducted Emissions, Telecommunications Line Conducted Emissions, Radiated Emissions from 30 MHz to 1 GHz, and Radiated Emissions from 1 GHz to 6 GHz are currently recognized as Accredited in accordance with the Voluntary Control Council for Interference [VCCI] Article 15 procedures under Registration Number A-0027.

## 1.8 Test Facility Accreditations

Bay Area Compliance Laboratories Corp. (BACL) is:

**A- An independent, 3<sup>rd</sup>-Party, Commercial Test Laboratory accredited to ISO/IEC 17025:2005 by A2LA (Test Laboratory Accreditation Certificate Number 3297.02)**, in the fields of: Electromagnetic Compatibility and Telecommunications. Unless noted by an Asterisk (\*) in the Compliance Matrix (See Section 3 of this Test Report), BACL's ISO/IEC 17025:2005 Scope of Accreditation includes all of the Test Method Standards and/or the Product Family Standards detailed in this Test Report.

BACL's ISO/IEC 17025:2005 Scope of Accreditation includes a comprehensive suite of EMC Emissions, EMC Immunity, Radio, RF Exposure, Safety and wireline Telecommunications test methods applicable to a wide range of product categories. These product categories include Central Office Telecommunications Equipment [including NEBS - Network Equipment Building Systems], Unlicensed and Licensed Wireless and RF devices, Information Technology Equipment (ITE); Telecommunications Terminal Equipment (TTE); Medical Electrical Equipment; Industrial, Scientific and Medical Test Equipment; Professional Audio and Video Equipment; Industrial and Scientific Instruments and Laboratory Apparatus; Cable Distribution Systems, and Energy Efficient Lighting.

**B- A Product Certification Body accredited to ISO/IEC 17065:2012 by A2LA (Product Certification Body Accreditation Certificate Number 3297.03)** to certify

- For the USA (Federal Communications Commission):

- 1- All Unlicensed radio frequency devices within FCC Scopes A1, A2, A3, and A4;
- 2- All Licensed radio frequency devices within FCC Scopes B1, B2, B3, and B4;
- 3- All Telephone Terminal Equipment within FCC Scope C.

- For the Canada (Industry Canada):

- 1 All Scope 1-Licence-Exempt Radio Frequency Devices;
- 2 All Scope 2-Licensed Personal Mobile Radio Services;
- 3 All Scope 3-Licensed General Mobile & Fixed Radio Services;
- 4 All Scope 4-Licensed Maritime & Aviation Radio Services;
- 5 All Scope 5-Licensed Fixed Microwave Radio Services
- 6 All Broadcasting Technical Standards (BETS) in the Category I Equipment Standards List.

- For Singapore (Info-Communications Development Authority (IDA)):

- 1 All Line Terminal Equipment: All Technical Specifications for Line Terminal Equipment – Table 1 of IDA MRA Recognition Scheme: 2011, Annex 2
2. All Radio-Communication Equipment: All Technical Specifications for Radio-Communication Equipment – Table 2 of IDA MRA Recognition Scheme: 2011, Annex 2

- For the Hong Kong Special Administrative Region:

- 1 All Radio Equipment, per KHCA 10XX-series Specifications;
- 2 All GMDSS Marine Radio Equipment, per HKCA 12XX-series Specifications;
- 3 All Fixed Network Equipment, per HKCA 20XX-series Specifications.

- For Japan:

- 1 MIC Telecommunication Business Law (Terminal Equipment):
  - All Scope A1 - Terminal Equipment for the Purpose of Calls;
  - All Scope A2 - Other Terminal Equipment
- 2 Radio Law (Radio Equipment):
  - All Scope B1 - Specified Radio Equipment specified in Article 38-2-2, paragraph 1, item 1 of the Radio Law
  - All Scope B2 - Specified Radio Equipment specified in Article 38-2-2, paragraph 1, item 2 of the Radio Law
  - All Scope B3 - Specified Radio Equipment specified in Article 38-2-2, paragraph 1, item 3 of the Radio Law

**C- A Product Certification Body accredited to ISO/IEC 17065:2012 by A2LA (Product Certification Body Accreditation Certificate Number 3297.01)** to certify Products to USA's Environmental Protection Agency (EPA) ENERGY STAR Product Specifications for:

- 1 Electronics and Office Equipment:
  - for Telephony (ver. 3.0)
  - for Audio/Video (ver. 3.0)
  - for Battery Charging Systems (ver. 1.1)

- for Set-top Boxes & Cable Boxes (ver. 4.1)
- for Televisions (ver. 6.1)
- for Computers (ver. 6.0)
- for Displays (ver. 6.0)
- for Imaging Equipment (ver. 2.0)
- for Computer Servers (ver. 2.0)
- 2 Commercial Food Service Equipment
  - for Commercial Dishwashers (ver. 2.0)
  - for Commercial Ice Machines (ver. 2.0)
  - for Commercial Ovens (ver. 2.1)
  - for Commercial Refrigerators and Freezers
- 3 Lighting Products
  - For Decorative Light Strings (ver. 1.5)
  - For Luminaires (including sub-components) and Lamps (ver. 1.2)
  - For Compact Fluorescent Lamps (CFLs) (ver. 4.3)
  - For Integral LED Lamps (ver. 1.4)
- 4 Heating, Ventilation, and AC Products
  - for Residential Ceiling Fans (ver. 3.0)
  - for Residential Ventilating Fans (ver. 3.2)
- 5 Other
  - For Water Coolers (ver. 3.0)

**D- A NIST Designated Phase-I and Phase-II Conformity Assessment Body (CAB) for the following economies and regulatory authorities under the terms of the stated MRAs/Treaties:**

- Australia: ACMA (Australian Communication and Media Authority) – APEC Tel MRA -Phase I;
- Canada: (Innovation, Science and Economic development Canada - ISEDC) Foreign Certification Body – FCB – APEC Tel MRA -Phase I & Phase II;
- Chinese Taipei (Republic of China – Taiwan):
  - o BSMI (Bureau of Standards, Metrology and Inspection) APEC Tel MRA -Phase I;
  - o NCC (National Communications Commission) APEC Tel MRA -Phase I;
- European Union:
  - o EMC Directive 2014/30/EU US-EU EMC & Telecom MRA CAB (NB)
  - o Radio Equipment (RE) Directive 2014/53/EU US-EU EMC & Telecom MRA CAB (NB)
  - o Low Voltage Directive (LVD) 2014/35/EU
- Hong Kong Special Administrative Region: (Office of the Telecommunications Authority – OFTA)  
APEC Tel MRA -Phase I & Phase II
- Israel – US-Israel MRA Phase I
- Republic of Korea (Ministry of Communications - Radio Research Laboratory) APEC Tel MRA -Phase I
- Singapore: (Infocomm Media Development Authority - IMDA) APEC Tel MRA -Phase I & Phase II;
- Japan: VCCI - Voluntary Control Council for Interference US-Japan Telecom Treaty VCCI Side Letter-USA:
  - o ENERGY STAR Recognized Test Laboratory – US EPA
  - o Telecommunications Certification Body (TCB) – US FCC;
  - o Nationally Recognized Test Laboratory (NRTL) – US OSHA
- Vietnam: APEC Tel MRA -Phase I;

## 2 System Test Configuration

### 2.1 Justification

The EUT was configured for testing in accordance to ANSI C63.10.

### 2.2 EUT Exercise Software

The software “Realtime” was used to transmit signal for all the modules. The software was provided by *August Home, Inc* and verified by Rita Yang to comply with the standard requirements being tested against. The following channels and power settings were selected for testing.

Channel Frequency (MHz)	Power Setting	
	1Mbps	2Mbps
2402	default	default
2440	default	default
2480	default	default

### 2.3 Duty Cycle Correction Factor

According to KDB 558074 D01 DTS Meas Guidance v05r02 section 6.0:

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be utilized to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration ( $T$ ) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed  $T$  at any time that data is being acquired (i.e., no transmitter off-time is to be considered).


Data Rate	On Time (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)
1Mbps	0.3993	0.6291	63.47	1.97
2Mbps	0.2153	0.6266	34.36	4.64

Duty Cycle = On Time (ms)/ Period (ms)


Duty Cycle Correction Factor (dB) =  $10 \log(1/\text{Duty Cycle})$

Please refer to the following plots.

1Mbps



2Mbps



## 2.4 Equipment Modifications

N/A

## 2.5 Local Support Equipment

Manufacturer	Description	Model
Dell	Laptop	LATITUDE E6410

## 2.6 Remote Support Equipment

Manufacturer	Description	Model
Debug Board	USB to TTL Serial Cable with connected battery pack	N/A

## 2.7 Interface Ports and Cabling

Description	Length (m)	To	From
FFC cable	< 1	Debug Board	EUT
USB to TTL serial cable	< 1	Laptop	Debug Board

### 3 Summary of Test Results

Results reported relate only to the product tested.

FCC & ISEDC Rules	Description of Test	Results
FCC §15.203 ISEDC RSS-Gen §6.8	Antenna Requirements	Compliant
FCC §2.1093, §15.247(i) ISEDC RSS-102	RF Exposure	Compliant
FCC §15.207 ISEDC RSS-Gen §8.8	AC Line Conducted Emissions	N/A <sup>1</sup>
FCC §15.209, §15.247(d) ISEDC RSS-247 §5.5 RSS-Gen §8.9, §8.10	Radiated Spurious Emissions	Compliant
FCC §15.247(a)(2) ISEDC RSS-247 §5.2 RSS-Gen §6.7	6 dB & 99% Emission Bandwidth	Compliant
FCC §15.247(b)(3) ISEDC RSS-247 §5.4	Maximum Output Power	Compliant
FCC §15.247(e) ISEDC RSS-247 §5.2(2)	Peak Power Spectral Density	Compliant
FCC §15.247(d) ISEDC RSS-247 §5.5	100 kHz Bandwidth of Frequency Band Edge	Compliant
FCC §2.1051, §15.247 (d) ISEDC RSS-247 §5.5	Spurious Emissions at Antenna Port	Compliant

Note<sup>1</sup>: Device is powered by battery.

## 4 FCC §15.203 & ISED RSS-Gen §6.8 - Antenna Requirements

### 4.1 Applicable Standards

According to FCC §15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

And according to FCC §15.247 (b) (4), if transmitting antennas of directional gain greater than 6 dBi are used the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

According to ISED RSS-Gen §6.8: Transmitter Antenna

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For license-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

### 4.2 Antenna Description

External/Internal/ Integral	Frequency Range (MHz)	Antenna Type	Maximum Antenna Gain (dBi)
Integral	2400-2500 MHz	PCB, Meandering Inverted E type	0

Antenna information provided by customer.

## 5 FCC §2.1091, §15.247(i) & ISED RSS-102 – RF Exposure

### 5.1 Applicable Standards

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

#### Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	* (100)	30
1.34-30	824/f	2.19/f	* (180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

**f = frequency in MHz**

\* = Plane-wave equivalent power density

According to ISED RSS-102 Issue 5:

### 2.5.2 Exemption Limits for Routine Evaluation – RF Exposure Evaluation

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz<sup>6</sup> and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $4.49/f^{0.5}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $1.31 \times 10^{-2} f^{0.6834}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

## 5.2 MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

## 5.3 MPE Results

### BLE

<u>Maximum peak output power at antenna input terminal (dBm):</u>	<u>-0.43</u>
<u>Maximum peak output power at antenna input terminal (mW):</u>	<u>0.9057</u>
<u>Prediction distance (cm):</u>	<u>20</u>
<u>Prediction frequency (MHz):</u>	<u>2480</u>
<u>Maximum Antenna Gain, typical (dBi):</u>	<u>0</u>
<u>Maximum Antenna Gain (numeric):</u>	<u>1</u>
<u>Power density of prediction frequency at 20.0 cm (mW/cm<sup>2</sup>):</u>	<u>0.00018</u>
<u>FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm<sup>2</sup>):</u>	<u>1.0</u>

The device is compliant with the requirement MPE limit for uncontrolled exposure. The maximum power density at the distance of 20 cm is 0.00018 mW/cm<sup>2</sup>. Limit is 1.0 mW/cm<sup>2</sup>.

## 5.4 RF exposure evaluation exemption for IC

### 2.4 GHz BLE

$$-0.43 + 0 \text{ dBi} = -0.43 \text{ dBm} < 1.31 \times 10^{-2} f^{0.6834} = 2.736 \text{ W} = 34.37 \text{ dBm}$$

Therefore the RF exposure is not required.

## 6 FCC §15.209, §15.247(d) & ISEDC RSS-247 §5.5, RSS-Gen §8.9, §8.10 - Spurious Radiated Emissions

### 6.1 Applicable Standards

As per FCC §15.35(d): Unless otherwise specified, on any frequency or frequencies above 1000 MHz, the radiated emission limits are based on the use of measurement instrumentation employing an average detector function. Unless otherwise specified, measurements above 1000 MHz shall be performed using a minimum resolution bandwidth of 1 MHz.

As Per FCC §15.205(a) and RSS-Gen except as show in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 – 0.110	16.42 – 16.423	960 – 1240	4.5 – 5.15
0.495 – 0.505	16.69475 – 16.69525	1300 – 1427	5.35 – 5.46
2.1735 – 2.1905	25.5 – 25.67	1435 – 1626.5	7.25 – 7.75
4.125 – 4.128	37.5 – 38.25	1645.5 – 1646.5	8.025 – 8.5
4.17725 – 4.17775	73 – 74.6	1660 – 1710	9.0 – 9.2
4.20725 – 4.20775	74.8 – 75.2	1718.8 – 1722.2	9.3 – 9.5
6.215 – 6.218	108 – 121.94	2200 – 2300	10.6 – 12.7
6.26775 – 6.26825	123 – 138	2310 – 2390	13.25 – 13.4
6.31175 – 6.31225	149.9 – 150.05	2483.5 – 2500	14.47 – 14.5
8.291 – 8.294	156.52475 – 156.52525	2690 – 2900	15.35 – 16.2
8.362 – 8.366	156.7 – 156.9	3260 – 3267	17.7 – 21.4
8.37625 – 8.38675	162.0125 – 167.17	3.332 – 3.339	22.01 – 23.12
8.41425 – 8.41475	167.72 – 173.2	3 3458 – 3 358	23.6 – 24.0
12.29 – 12.293	240 – 285	3.600 – 4.400	31.2 – 31.8
12.51975 – 12.52025	322 – 335.4		36.43 – 36.5
12.57675 – 12.57725	399.9 – 410		Above 38.6
13.36 – 13.41	608 – 614		

As per FCC §15.209(a): Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (micro volts/meter)	Measurement Distance (meters)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100**	3
88 - 216	150**	3
216 - 960	200**	3
Above 960	500	3

\*\* Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

As per FCC §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

As per ISEDC RSS-Gen 8.9,

Except when the requirements applicable to a given device state otherwise, emission from licence-exempt transmitters shall comply with the field strength limits shown in the table below. Additional, the level of any transmitter emission shall not exceed the level of the transmitter's fundamental emission.

General Field Strength Limits for Licence-Exemption Transmitters at Frequencies above 30 MHz

Frequency (MHz)	Field Strength (μv/m at 3 meters)
30-88	100
88-216	150
216-960	200
Above 960*	500

\* Unless otherwise specified, for all frequencies greater than 1 GHz, the radiated emission limits for licence-exempt radio apparatus stated in applicable RSSs (including RSS-Gen) are based on measurements using a linear average detector function having a minimum resolution bandwidth of 1 MHz. If an average limit is specified for the EUT, then the peak emission shall also be measured with instrumentation properly adjusted for such factors as pulse desensitization to ensure the peak emission is less than 20 dB above the average limit.

Note: Transmitting devices are not permitted in restricted frequency bands unless stated otherwise in the specific RSS.

As per ISEDC RSS-247 §5.5, in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

## 6.2 Test Setup

The radiated emissions tests were performed in the 5-meter Chamber, using the setup in accordance with ANSI C63.10-2013. The specification used was the FCC 15 Subpart C and ISEDC RSS-247 limits.

The spacing between the peripherals was 10 centimeters.

External I/O cables were draped along the edge of the test table and bundle when necessary.

### 6.3 Test Procedure

For the radiated emissions test, the EUT host, and all support equipment power cords was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The EUT was set 3 meter away from the testing antenna, which was varied from 1-4 meter, and the EUT was placed on a turntable, which was 0.8 meter and 1.5 meter above the ground plane for below and above 1000 MHz measurements, the table shall be rotated for 360 degrees to find out the highest emission. The receiving antenna should be changed the polarization both of horizontal and vertical.

The spectrum analyzer or receiver is set as:

Below 1000 MHz:

$$\text{RBW} = 100 \text{ kHz} / \text{VBW} = 300 \text{ kHz} / \text{Sweep} = \text{Auto}$$

Above 1000 MHz:

- (1) Peak:  $\text{RBW} = 1\text{MHz} / \text{VBW} = 1\text{MHz} / \text{Sweep} = \text{Auto}$
- (2) Average:  $\text{RBW} = 1\text{MHz} / \text{VBW} = 10\text{Hz} / \text{Sweep} = \text{Auto}$

### 6.4 Corrected Amplitude & Margin Calculation

For emissions below 1 GHz,

The Corrected Amplitude (CA) is calculated by adding the Correction Factor to the S.A. Reading. The basic equation is as follows:

$$\text{CA} = \text{S.A. Reading} + \text{Correction Factor}$$

For example, a corrected amplitude of 40.3 dBuV/m = S.A. Reading (32.5 dBuV) + Correction Factor (7.8 dB/m)

The Correction Factor is calculated by adding the Antenna Factor (AF), the Cable Loss (CL), the Attenuator Factor (Atten) and subtracting the Amplifier Gain (Ga) together. This calculation is done in the measurement software, and reported in the test result section. The basic equation is as follows:

$$\text{Correction Factor} = \text{AF} + \text{CL} + \text{Atten} - \text{Ga}$$

The “Margin” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of -7 dB means the emission is 7 dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corrected Amplitude} - \text{Limit}$$

For emission above 1 GHz,

The Corrected Amplitude (CA) is calculated by adding the Antenna Factor (AF), the Cable Loss (CL), the Attenuator Factor (Atten) and subtracting the Amplifier Gain (Ga) to indicated Amplitude (Ai) reading. The basic equation is as follows:

$$\text{CA} = \text{Ai} + \text{AF} + \text{CL} + \text{Atten} - \text{Ga}$$

For example, a corrected amplitude of 40.3 dBuV/m = Indicated Reading (32.5 dBuV) + Antenna Factor (+23.5dB) + Cable Loss (3.7 dB) + Attenuator (10 dB) - Amplifier Gain (29.4 dB)

The “Margin” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of -7 dB means the emission is 7 dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corrected Amplitude} - \text{Limit}$$

## 6.5 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Agilent	Spectrum Analyzer	E4440A	US45303156	2020-04-20	18 months
Rohde & Schwarz	EMI Test Receiver	ESCI 1166.5950K03	100337	2021-03-09	2 years
IW Incorporated	157 Series 2.92 SM (x2) Armored 33 ft. Cable	KPS-1571AN-3960-KPS	DC 1917	2021-03-03	1 year
MDP Digital	Times Microwave LMR 400 UltraFlex Coaxial Cable 35'	LMR400UF	BACL1904161	2021-06-18	1 year
BACL	5m3 Sensitivity Box	1	2	2020-10-27	1 year
Agilent	Pre-Amplifier	8449B	3147A00400	2021-03-02	1 year
AH Systems	Pre-Amplifier	PAM 1840 VH	170	2020-11-09	1 year
HP	Pre-Amplifier	8447D	2443A04374	2020-08-17	18 months
ETS Lindgren	Horn Antenna	3117	00218973	2019-02-13	25 months
Wisewave	Horn Antenna	ARH-4223-02	10555-02	2020-02-05	2 years
Sunol Sciences Corp	Biconilog Antenna	JB3	A020106-2	2019-11-20	2 years
Sunol Sciences Corp	System Controller	SC110V	122303-1	N/R	N/A
Keysight Technologies	RF Limiter	11867A	MY42242932	2021-03-03	1 year
-	RF cable	-	-	Each time <sup>1</sup>	N/A
-	Notch Filter	-	-	Each time <sup>1</sup>	N/A

Note<sup>1</sup>: cable and notch filter included in the test set-up will be checked each time before testing.

**Statement of Traceability:** **BACL Corp.** attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with the latest version of A2LA policy P102 “A2LA Policy on Metrological Traceability”.

## 6.6 Test Environmental Conditions

Temperature:	19 °C
Relative Humidity:	34 %
ATM Pressure:	102.2 kPa

The testing was performed by Allen Huang and Rita Yang from 2021-08-12 to 2021-08-18 at 5 meter chamber 3.


## 6.7 Summary of Test Results

According to the data hereinafter, the EUT complied with FCC Part 15C and ISED RSS-247 standard's radiated emissions limits, and had the worst margin of:

Mode: Transmitting			
Margin (dB)	Frequency (MHz)	Polarization (Horizontal/Vertical)	Transmitting Channel (MHz)
-2.91	17924.1	Horizontal	2480. 2Mbps

## 6.8 Radiated Emissions Test Results

### 1) 30 MHz – 1 GHz Worst Case, Measured at 3 meters




Frequency (MHz)	S.A. Reading (dB $\mu$ V)	Correction Factor (dB/m)	Corrected Amplitude (dB $\mu$ V/m)	Antenna Height (cm)	Antenna Polarity (H/V)	Turntable Azimuth (degrees)	Limit (dB $\mu$ V/m)	Margin (dB)	Comment
31.4255	21.33	1.2	22.7	282	H	285	40	-17.3	Pass
148.1503	27.19	-6.36	21.46	169	H	319	43.5	-22.04	Pass
37.481	21.41	-3.45	18.17	192	V	100	40	-21.83	Pass
167.3195	24.21	-6.98	17.92	274	H	279	43.5	-25.58	Pass


## 2) 1-26.5 GHz, Measured at 3 Meters

Frequency (MHz)	S.A. Reading (dB $\mu$ V)	Turntable Azimuth (degrees)	Test Antenna			Cable Loss (dB)	Pre-Amp. (dB)	Cord. Reading (dB $\mu$ V/m)	FCC/ISEDC		Note
			Height (cm)	Polarity (H/V)	Factor (dB/m)				Limit (dB $\mu$ V/m)	Margin (dB)	
1Mbps Low Channel Frequency: 2402 MHz											
2402	97.52	340	140	H	32.6	4.913	36.863	98.17	-	-	Peak
2402	90.54	257	250	V	32.6	4.913	36.863	91.19	-	-	Peak
2390	51.62	335	180	H	32.6	4.913	36.863	52.27	74	-21.73	Peak
2390	49.10	90	150	V	32.6	4.913	36.863	49.75	74	-24.25	Peak
2390	40.20	335	180	H	32.6	4.913	36.863	40.85	54	-13.15	Ave
2390	39.54	90	150	V	32.6	4.913	36.863	40.19	54	-13.81	Ave
4804	47.91	255	150	H	35	8.336	35.707	55.54	74	-18.46	Peak
4804	47.36	360	150	V	35	8.336	35.707	54.99	74	-19.01	Peak
4804	38.22	255	150	H	35	8.336	35.707	45.85	54	-8.15	Ave
4804	38.07	360	150	V	35	8.336	35.707	45.70	54	-8.30	Ave
7206	46.40	65	150	H	36.1	10.779	36.388	56.89	68.17	-11.28	Peak
7206	46.93	235	175	V	36.1	10.779	36.388	57.42	61.19	-3.77	Peak
1Mbps Middle Channel Frequency: 2440 MHz											
4880	47.33	190	150	H	35.3	8.336	35.707	55.26	74	-18.74	Peak
4880	47.35	30	160	V	35.3	8.336	35.707	55.28	74	-18.72	Peak
4880	37.31	190	150	H	35.3	8.336	35.707	45.24	54	-8.76	Ave
4880	37.52	30	160	V	35.3	8.336	35.707	45.45	54	-8.55	Ave
7320	47.78	95	100	H	36.1	10.779	36.483	58.18	74	-15.82	Peak
7320	45.55	50	150	V	36.1	10.779	36.483	55.95	74	-18.05	Peak
7320	39.81	95	100	H	36.1	10.779	36.483	50.20	54	-3.80	Ave
7320	36.64	50	150	V	36.1	10.779	36.483	47.03	54	-6.97	Ave
1Mbps High Channel Frequency: 2480 MHz											
2483.5	57.67	0	180	H	33	4.913	36.863	58.72	74	-15.28	Peak
2483.5	50.68	275	265	V	33	4.913	36.863	51.73	74	-22.27	Peak
2483.5	43.87	0	180	H	33	4.913	36.863	44.92	54	-9.08	Ave
2483.5	36.54	275	265	V	33	4.913	36.863	37.59	54	-16.41	Ave
4960	46.70	330	150	H	35.4	8.336	35.707	54.73	74	-19.27	Peak
4960	46.45	10	150	H	35.4	8.336	35.707	54.48	74	-19.52	Peak
4960	37.21	330	150	H	35.4	8.336	35.707	45.24	54	-8.76	Ave
4960	34.83	10	150	H	35.4	8.336	35.707	42.86	54	-11.14	Ave
7440	48.33	75	265	H	36.1	10.779	36.483	58.73	74	-15.27	Peak
7440	46.62	50	230	V	36.1	10.779	36.483	57.02	74	-16.98	Peak
7440	39.47	75	265	H	36.1	10.779	36.483	49.86	54	-4.14	Ave
7440	34.94	50	230	V	36.1	10.779	36.483	45.34	54	-8.66	Ave

Frequency (MHz)	S.A. Reading (dB $\mu$ V)	Turntable Azimuth (degrees)	Test Antenna			Cable Loss (dB)	Pre-Amp. (dB)	Cord. Reading (dB $\mu$ V/m)	FCC/ISEDC		Note
			Height (cm)	Polarity (H/V)	Factor (dB/m)				Limit (dB $\mu$ V/m)	Margin (dB)	
2Mbps Low Channel Frequency: 2402 MHz											
2402	97.07	340	195	H	32.6	4.913	36.863	97.72	-	-	Peak
2402	90.59	255	290	V	32.6	4.913	36.863	91.24	-	-	Peak
2390	52.15	320	170	H	32.6	4.913	36.863	52.80	74	-21.20	Peak
2390	49.14	360	150	V	32.6	4.913	36.863	49.79	74	-24.21	Peak
2390	41.02	320	170	H	32.6	4.913	36.863	41.67	54	-12.33	Ave
2390	39.69	360	150	V	32.6	4.913	36.863	40.34	54	-13.66	Ave
4804	47.05	160	150	H	35	8.336	35.707	54.68	74	-19.32	Peak
4804	47.10	180	150	V	35	8.336	35.707	54.73	74	-19.27	Peak
4804	37.97	160	150	H	35	8.336	35.707	45.60	54	-8.40	Ave
4804	37.94	180	150	V	35	8.336	35.707	45.57	54	-8.43	Ave
7206	48.35	75	125	H	36.1	10.779	36.388	58.84	67.72	-8.88	Peak
7206	46.93	120	150	V	36.1	10.779	36.388	57.42	61.24	-3.82	Peak
2Mbps Middle Channel Frequency: 2440 MHz											
4880	46.65	185	150	H	35.3	8.336	35.707	54.58	74	-19.42	Peak
4880	45.81	45	150	V	35.3	8.336	35.707	53.74	74	-20.26	Peak
4880	37.20	185	150	H	35.3	8.336	35.707	45.13	54	-8.87	Ave
4880	37.00	45	150	V	35.3	8.336	35.707	44.93	54	-9.07	Ave
7320	47.64	80	205	H	36.1	10.779	36.483	58.04	74	-15.96	Peak
7320	45.00	190	150	V	36.1	10.779	36.483	55.40	74	-18.60	Peak
7320	37.67	80	205	H	36.1	10.779	36.483	48.06	54	-5.94	Ave
7320	36.34	190	150	V	36.1	10.779	36.483	46.73	54	-7.27	Ave
2Mbps High Channel Frequency: 2480 MHz											
2483.5	58.29	360	155	H	33	4.913	36.863	59.34	74	-14.66	Peak
2483.5	49.74	225	225	V	33	4.913	36.863	50.79	74	-23.21	Peak
2483.5	41.74	360	155	H	33	4.913	36.863	42.79	54	-11.21	Ave
2483.5	38.44	225	225	V	33	4.913	36.863	39.49	54	-14.51	Ave
4960	46.41	320	150	H	35.4	8.336	35.707	54.44	74	-19.56	Peak
4960	45.07	335	150	V	35.4	8.336	35.707	53.10	74	-20.90	Peak
4960	36.87	320	150	H	35.4	8.336	35.707	44.90	54	-9.10	Ave
4960	36.49	335	150	V	35.4	8.336	35.707	44.52	54	-9.48	Ave
7440	48.39	85	100	H	36.1	10.779	36.483	58.79	74	-15.21	Peak
7440	46.87	360	150	V	36.1	10.779	36.483	57.27	74	-16.73	Peak
7440	38.09	85	100	H	36.1	10.779	36.483	48.48	54	-5.52	Ave
7440	36.80	360	150	V	36.1	10.779	36.483	47.19	54	-6.81	Ave

**1 – 18 GHz Worst Case Pre-Scan, Measured at 1 meter**

Frequency (MHz)	S.A. Reading (dBuV)	Correction Factor (dB/m)	Corrected Amplitude (dB $\mu$ V/m)	Antenna Height (cm)	Antenna Polarity (H/V)	Turntable Azimuth (degrees)	Limit (dB $\mu$ V/m)	Margin (dB)	Comment
17924.1	40.79	22.39	71.59	116	H	330	64	-12.41	Pass
17924.1	30.29	22.39	61.09	116	H	330	64	-2.91	Pass

**18 – 26.5 GHz Worst Case Pre-Scan, Measured at 1 meter**

## 7 FCC §15.247(a) (2) & ISEDC RSS-247 §5.2, RSS-Gen §6.7 - Emission Bandwidth

### 7.1 Applicable Standards

According to FCC §15.247(a) (2) and ISEDC RSS-247 §5.2: the minimum 6 dB bandwidth shall be 500 kHz.

### 7.2 Measurement Procedure

The measurements are based on FCC KDB 558074 D01 DTS Meas Guidance v05r02: Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 8: DTS bandwidth.

### 7.3 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Rohde & Schwarz	Signal Analyzer	FSV40	101203	2021-04-26	12 months
-	RF cable	-	-	Each time <sup>1</sup>	N/A

Note<sup>1</sup>: cable included in the test set-up will be checked each time before testing.

**Statement of Traceability:** *BACL Corp.* attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with the latest version of A2LA policy P102 "A2LA Policy on Metrological Traceability".

### 7.4 Test Environmental Conditions


Temperature:	21° C
Relative Humidity:	39 %
ATM Pressure:	102.0 KPa

The testing was performed by Rita Yang from 2021-08-13 to 2021-08-17 at RF test site.


## 7.5 Test Results

Channel	Frequency (MHz)	99% OBW (MHz)	6 dB OBW (kHz)	6dB OBW limit (kHz)
1 Mbps				
Low	2402	1.04	687.40	> 500
Middle	2440	1.04	680.40	> 500
High	2480	1.04	687.40	> 500
2 Mbps				
Low	2402	2.06	1143.20	> 500
Middle	2440	2.07	1150.50	> 500
High	2480	2.06	1143.29	> 500


Please refer to the following plots for detailed test results.

**1 Mbps 2402 MHz, 99% OBW**


Date: 13 AUG 2021 14:14:29

**1 Mbps 2402 MHz, -6 dB OBW**


Date: 17.AUG.2021 09:41:54

**1 Mbps 2440 MHz, 99% OBW**


Date: 13.AUG.2021 14:11:03

**1 Mbps 2440 MHz, -6 dB OBW**


Date: 17.AUG.2021 09:43:19

**1 Mbps 2480 MHz, 99% OBW**


Date: 13.AUG.2021 14:26:40

**1 Mbps 2480 MHz, -6 dB OBW**

Date: 17.AUG.2021 09:44:50

**2 Mbps 2402 MHz, 99% OBW**


Date: 13.AUG.2021 14:20:44

**2 Mbps 2402 MHz, -6 dB OBW**


Date: 17.AUG.2021 09:39:42

**2 Mbps 2440 MHz, 99% OBW**


Date: 13 AUG 2021 14:21:45

**2 Mbps 2440 MHz, -6 dB OBW**

Date: 17 AUG 2021 09:37:58

**2 Mbps 2480 MHz, 99% OBW**

Date: 13.AUG.2021 14:23:31

**2 Mbps 2480 MHz, -6 dB OBW**

Date: 17.AUG.2021 09:35:52

## 8 FCC §15.247(b) (3) & ISEDC RSS-247 §5.4 – Maximum Output Power

### 8.1 Applicable Standards

According to FCC §15.247(b) (3): For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

According to RSS-247 §5.4: For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).

### 8.2 Measurement Procedure

The measurements are based on ANSI C63.10-2013, Section 11.9.2.2.2.

### 8.3 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Rohde & Schwarz	Signal Analyzer	FSV40	101203	2021-04-26	12 months
-	RF cable	-	-	Each time <sup>1</sup>	N/A

Note<sup>1</sup>: cable included in the test set-up will be checked each time before testing.

**Statement of Traceability:** *BACL Corp.* attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with the latest version of A2LA policy P102 “A2LA Policy on Metrological Traceability”.

### 8.4 Test Environmental Conditions


Temperature:	21° C
Relative Humidity:	39 %
ATM Pressure:	102.0 KPa

The testing was performed by Rita Yang on 2021-08-13 at RF test site.


## 8.5 Test Results

Channel	Frequency (MHz)	Conducted Output Power (dBm)	FCC/ISEDC Limit (dBm)
1Mbps			
Low	2402	-0.73	30
Middle	2440	-0.6	30
High	2480	-0.44	30
2Mbps			
Low	2402	-0.76	30
Middle	2440	-0.6	30
High	2480	-0.43	30


### 1 Mbps Low Channel: 2402 MHz




Date: 13.AUG.2021 08:38:52

**1 Mbps Middle Channel: 2440 MHz**


Date: 13.AUG.2021 08:42:36

**1 Mbps High Channel: 2480 MHz**


Date: 13.AUG.2021 08:45:02

**2 Mbps Low Channel: 2402 MHz**

Date: 13.AUG.2021 08:46:54

**2 Mbps Middle Channel: 2440 MHz**

Date: 13.AUG.2021 08:48:32

**2 Mbps High Channel: 2480 MHz**

Date: 13 AUG 2021 08:50:14

## 9 FCC §15.247(e) & ISEDC RSS-247 §5.2(2) – Peak Power Spectral Density

### 9.1 Applicable Standards

According to ECFR §15.247(e) and RSS-247 §5.2 ( 2 ) , for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### 9.2 Measurement Procedure

The measurements are based on FCC KDB 558074 D01 DTS Meas Guidance v05r02: Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 10: Maximum power spectral density level in the fundamental emission.

### 9.3 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Rohde & Schwarz	Signal Analyzer	FSV40	101203	2021-04-26	12 months
-	RF cable	-	-	Each time <sup>1</sup>	N/A

Note<sup>1</sup>: cable included in the test set-up will be checked each time before testing.

**Statement of Traceability:** *BACL Corp.* attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with the latest version of A2LA policy P102 “A2LA Policy on Metrological Traceability”.

### 9.4 Test Environmental Conditions


Temperature:	23° C
Relative Humidity:	42 %
ATM Pressure:	102.7 KPa

*The testing was performed by Rita Yang on 2021-08-13 at RF test site.*


## 9.5 Test Results

Channel	Frequency (MHz)	Conducted PSD (dBm/3 kHz)	FCC/ISEDC Limit (dBm/3 kHz)
1Mbps			
Low	2402	-16.67	8
Middle	2440	-16.55	8
High	2480	-16.49	8
2Mbps			
Low	2402	-16.42	8
Middle	2440	-16.23	8
High	2480	-16.25	8


Please refer to the following measurement plots.

**1 Mbps Low Channel: 2402 MHz**


Date: 16.AUG.2021 09:06:41

**1 Mbps Middle Channel: 2440 MHz**


Date: 16.AUG.2021 09:08:05

**1 Mbps High Channel: 2480 MHz**


Date: 16.AUG.2021 09:09:19

**2 Mbps Low Channel: 2402 MHz**

Date: 16.AUG.2021 09:10:18

**2 Mbps Middle Channel: 2440 MHz**

Date: 16.AUG.2021 09:11:11

**2 Mbps High Channel: 2480 MHz**

Date: 16 AUG 2021 09:11:58

## 10 FCC §15.247(d) & ISEDC RSS-247 §5.5 - 100 kHz Bandwidth of Band Edges

### 10.1 Applicable Standards

According to FCC §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emissions limits specified in §15.209(a) see §15.205(c).

According to ISEDC RSS-247 §5.5. In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

### 10.2 Measurement Procedure

Span = wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation

RBW = 100 kHz

VBW = 300 kHz

Sweep = coupled

Detector function = peak

Trace = max hold

### 10.3 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Rohde & Schwarz	Signal Analyzer	FSV40	101203	2021-04-26	12 months
-	RF cable	-	-	Each time <sup>1</sup>	N/A

Note<sup>1</sup>: cable included in the test set-up will be checked each time before testing.

**Statement of Traceability:** **BACL Corp.** attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with the latest version of A2LA policy P102 "A2LA Policy on Metrological Traceability".


### 10.4 Test Environmental Conditions

Temperature:	21° C
Relative Humidity:	39 %
ATM Pressure:	102.0 KPa

The testing was performed by Rita Yang on 2021-08-12 at RF test site.


## 10.5 Test Results

### 1 Mbps Low Channel: 2402 MHz




Date: 16 AUG 2021 08:43:42


### 1 Mbps High Channel: 2480 MHz



Date: 16 AUG 2021 08:47:21

**2 Mbps Low Channel: 2402 MHz**

Date: 16.AUG.2021 08:49:47

**2 Mbps High Channel: 2480 MHz**

Date: 16.AUG.2021 08:51:45

## 11 FCC §15.247(d) & ISEDC RSS-247 §5.5 - Spurious Emissions at Antenna Terminals

### 11.1 Applicable Standards

For FCC §15.247(d) and ISEDC RSS-247 §5.5, in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### 11.2 Test Procedure

The RF output of the EUT was connected to a spectrum analyzer through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100 kHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.

### 11.3 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Interval
Rohde & Schwarz	Signal Analyzer	FSQ26	200749	2019-11-07	2 years
-	RF cable	-	-	Each time <sup>1</sup>	N/A

Note<sup>1</sup>: cable included in the test set-up will be checked each time before testing.

**Statement of Traceability:** *BACL Corp.* attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with the latest version of A2LA policy P102 "A2LA Policy on Metrological Traceability".


### 11.4 Test Environmental Conditions

Temperature:	21° C
Relative Humidity:	39 %
ATM Pressure:	102.0 KPa

*The testing was performed by Rita Yang on 2021-08-13 at RF test site.*


## 11.5 Test Results

### 1 Mbps Low Channel: 2402 MHz




Date: 13.AUG.2021 15:49:14


### 1 Mbps Middle Channel: 2440 MHz




Date: 13.AUG.2021 15:51:17

**1 Mbps High Channel: 2480 MHz**


Date: 13.AUG.2021 15:58:37

**2 Mbps Low Channel: 2402 MHz**

Date: 16 AUG 2021 11:06:05

**2 Mbps Middle Channel: 2440 MHz**

Date: 13 AUG 2021 15:56:08

**2 Mbps High Channel: 2480 MHz**

Date: 16 AUG 2021 11:00:01

## **12 Annex A (Normative) - Test Setup Photographs**

Please refer to the attachment

## **13 Annex B (Normative) - EUT External Photographs**

Please refer to the attachment

## **14 Annex C (Normative) - EUT Internal Photographs**

Please refer to the attachment

## 15 Annex D (Normative) - A2LA Electrical Testing Certificate



### Accredited Laboratory

A2LA has accredited

**BAY AREA COMPLIANCE LABORATORIES CORP.**

Sunnyvale, CA

for technical competence in the field of

### Electrical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. This laboratory also meets A2LA R222

- Specific Requirements EPA ENERGY STAR Accreditation Program. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).

Presented this 10<sup>th</sup> day of March 2021.

A blue ink signature of the name 'Trace McInturff'.

Trace McInturff, Vice President, Accreditation Services  
For the Accreditation Council  
Certificate Number 3297.02  
Valid to September 30, 2022

For the tests to which this accreditation applies, please refer to the laboratory's Electrical Scope of Accreditation.

Please follow the web link below for a full ISO 17025 scope

<https://www.a2la.org/scopepdf/3297-02.pdf>

**--- END OF REPORT ---**