

FCC Radio Test Report

FCC ID: 2ABDK-VB2

This report concerns: Original Grant

Project No. : 1911C006
Equipment : Smart Watch
Brand Name : VitalThec
Test Model : VB2
Series Model : N/A
Applicant : Borqs BeiJing Ltd
Address : TowerA BuildingB23 Universal Business Park No 10 jiuxianqiao Road
 Chaoyang District Beijing China
Manufacturer : Borqs BeiJing Ltd
Address : TowerA BuildingB23 Universal Business Park No 10 jiuxianqiao Road
 Chaoyang District Beijing China
Factory : Borqs BeiJing Ltd
Address : TowerA BuildingB23 Universal Business Park No 10 jiuxianqiao Road
 Chaoyang District Beijing China
Date of Receipt : Nov. 04, 2019
Date of Test : Oct. 28, 2020 ~ Jan. 01, 2022
Issued Date : Jan. 07, 2022
Report Version : R01
Test Sample : Engineering Sample No.: DG2020102826 and DG20211022168 for
 conducted, DG20211022165-3 for radiated.
Standard(s) : 47 CFR FCC Part 24 Subpart E
 47 CFR FCC Part 2
 ANSI C63.26-2015
 ANSI/TIA/EIA-603-E-2016
 FCC KDB 971168 D01 Power Meas License Digital Systems v03r01

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

Gabriel Zhu

Prepared by : Gabriel Zhu

Steven Lu

Approved by : Steven Lu



Add: No. 3 Jinshagang 1st Rd. Shixia, Dalang Town Dongguan City, Guangdong 523792
 People's Republic of China
 Tel: +86-769-8318-3000
 Web: www.newbtl.com

Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

The report must not be used by the client to claim product certification, approval, or endorsement by NIST, A2LA, or any agency of the U.S. Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO/IEC 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

BTL is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Please note that the measurement uncertainty is provided for informational purpose only and is not use in determining the Pass/Fail results.

Table of Contents	Page
REPORT ISSUED HISTORY	5
1 . SUMMARY OF TEST RESULTS	6
1.1 TEST FACILITY	7
1.2 MEASUREMENT UNCERTAINTY	7
1.3 TEST ENVIRONMENT CONDITIONS	8
2 . GENERAL INFORMATION	9
2.1 GENERAL DESCRIPTION OF EUT	9
2.2 DESCRIPTION OF TEST MODES	11
2.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	13
2.4 DESCRIPTION OF SUPPORT UNITS	13
3 . TEST RESULT	14
3.1 OUTPUT POWER MEASUREMENT	14
3.1.1 LIMIT	14
3.1.2 TEST PROCEDURE	14
3.1.3 TEST SETUP LAYOUT	14
3.1.4 TEST DEVIATION	14
3.1.5 TEST RESULTS	14
3.2 OCCUPIED BANDWIDTH MEASUREMENT	15
3.2.1 TEST PROCEDURE	15
3.2.2 TEST SETUP LAYOUT	15
3.2.3 TEST DEVIATION	15
3.2.4 TEST RESULTS	15
3.3 CONDUCTED SPURIOUS EMISSIONS MEASUREMENT	16
3.3.1 LIMIT	16
3.3.2 TEST PROCEDURES	16
3.3.3 TEST SETUP LAYOUT	16
3.3.4 TEST DEVIATION	16
3.3.5 TEST RESULTS	16
3.4 RADIATED SPURIOUS EMISSIONS MEASUREMENT	17
3.4.1 LIMIT	17
3.4.2 TEST PROCEDURES	17
3.4.3 TEST SETUP LAYOUT	18
3.4.4 TEST DEVIATION	19
3.4.5 TEST RESULTS (9KHZ TO 30MHZ)	19
3.4.6 TEST RESULTS (30MHZ TO 1000MHZ)	19
3.4.7 TEST RESULTS (ABOVE 1000MHZ)	19
3.5 BAND EDGE MEASUREMENT	20
3.5.1 LIMIT	20
3.5.2 TEST PROCEDURES	20

Table of Contents	Page
3.5.3 TEST SETUP LAYOUT	20
3.5.4 TEST DEVIATION	20
3.5.5 TEST RESULTS	20
3.6 PEAK TO AVERAGE RATIO MEASUREMENT	21
3.6.1 LIMIT	21
3.6.2 TEST PROCEDURES	21
3.6.3 TEST SETUP LAYOUT	21
3.6.4 TEST DEVIATION	21
3.6.5 TEST RESULTS	21
3.7 FREQUENCY STABILITY MEASUREMENT	22
3.7.1 LIMIT	22
3.7.2 TEST PROCEDURES	22
3.7.3 TEST SETUP LAYOUT	22
3.7.4 TEST DEVIATION	22
3.7.5 TEST RESULTS	22
4. LIST OF MEASUREMENT EQUIPMENTS	23
5. EUT TEST PHOTO	25
APPENDIX A - OUTPUT POWER	28
APPENDIX B - OCCUPIED BANDWIDTH	37
APPENDIX C - CONDUCTED SPURIOUS EMISSIONS	45
APPENDIX D - RADIATED SPURIOUS EMISSIONS (9KHZ TO 30MHZ)	48
APPENDIX E - RADIATED SPURIOUS EMISSIONS (30MHZ TO 1000MHZ)	50
APPENDIX F - RADIATED SPURIOUS EMISSIONS (ABOVE 1000MHZ)	53
APPENDIX G - BAND EDGE	56
APPENDIX H - PEAK TO AVERAGE RATIO	64
APPENDIX I - FREQUENCY STABILITY	72

REPORT ISSUED HISTORY

Report Version	Description	Issued Date
R00	Original Issue.	Jan. 01, 2022
R01	Modified the comments of TCB.	Jan. 07, 2022

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

FCC Part 24 Subpart E & Part 2			
Standard(s) Section	Test Item	Judgment	Remark
2.1046 24.232(c)	Equivalent Isotropic Radiated Power	PASS	-----
2.1049	Occupied Bandwidth	PASS	-----
2.1051 24.238(a)	Conducted Spurious Emissions	PASS	-----
2.1053 24.238(a)	Radiated Spurious Emissions	PASS	-----
24.238(a)	Band Edge Measurements	PASS	-----
24.232(d)	Peak To Average Ratio	PASS	-----
2.1055 24.235	Frequency Stability	PASS	-----

Note:

(1) "N/A" denotes test is not applicable in this test report.

1.1 TEST FACILITY

The test facilities used to collect the test data of radiated in this report is at the location of No. 3 Jinshagang 1st Rd. Shixia, Dalang Town Dongguan City, Guangdong 523792 People's Republic of China.

The test facilities used to collect the test data of frequency stability and output power(WCDMA) in this report is at the location of Room 108, Building 2, No.1, Yile Road, Songshan Lake Zone, Dongguan City, Guangdong, People's Republic of China.

BTL's Test Firm Registration Number for FCC: 357015

BTL's Designation Number for FCC: CN1240

1.2 MEASUREMENT UNCERTAINTY

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

The BTL measurement uncertainty as below table:

A. Radiated Measurement:

Test Site	Method	Measurement Frequency Range	U,(dB)
DG-CB01	CISPR	9kHz ~ 30MHz	2.36

Test Site	Method	Measurement Frequency Range	Ant. H / V	U,(dB)
DG-CB03	CISPR	30MHz ~ 200MHz	V	4.36
		30MHz ~ 200MHz	H	3.32
		200MHz ~ 1,000MHz	V	4.08
		200MHz ~ 1,000MHz	H	3.96
		1GHz ~ 6GHz	-	3.80
		6GHz ~ 18GHz	-	4.82
		18 GHz ~ 26.5 GHz	-	3.62

B. Other Measurement:

Parameter	Uncertainty
Spectrum Bandwidth	±3.8 %
Maximum Output Power	±0.95 dB
Power Spectral Density	±0.86 dB
Frequency Stability	±0.16 dB
Temperature	±0.08 °C
Time	±0.58 %
Supply voltages	±0.3 %

Note: Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

1.3 TEST ENVIRONMENT CONDITIONS

Test Item	Temperature	Humidity	Test Voltage	Tested By
Output Power & EIRP	23.2°C	45%	DC 3.8V	Tate Liu/Rick Liao
Occupied Bandwidth	23.2°C	45%	DC 3.8V	Tate Liu/Tim Yang
Conducted Spurious Emissions	23.2°C	45%	DC 3.8V	Tate Liu/Tim Yang
Radiated Spurious Emissions (9 kHz to 30 MHz)	25°C	60%	DC 3.8V	Sparrow Liu
Radiated Spurious Emissions (30 MHz to 1000 MHz)	26°C	52%	DC 3.8V	Kwok Guo
Radiated Spurious Emissions (Above 1000 MHz)	26°C	52%	DC 3.8V	Kwok Guo
Band Edge	23.2°C	45%	DC 3.8V	Tate Liu/Tim Yang
Peak To Average Ratio	23.2°C	45%	DC 3.8V	Tate Liu/Tim Yang
Frequency Stability	Normal & Extreme	45%	Normal & Extreme	Rick Liao

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Smart Watch			
Brand Name	VitalThec			
Test Model	VB2			
Series Model	N/A			
Model Difference(s)	N/A			
Hardware Version	DVT2			
Software Version	SW_VB2_286.00_i_USERDEBUG			
Power Source	1# Supplied from USB port. 2# Battery supplied. Model: ZWD462527V			
Power Rating	1# DC 5V 2# DC 3.8V, 400mAh			
IEMI No.	Conducted	866027030892968/004400152020000		
	Radiated	004400152020002		
Modulation Type	WCDMA/HSDPA/HSUPA		UL: QPSK DL: QPSK,16QAM	
	LTE		UL: QPSK,16QAM DL: QPSK,16QAM,64QAM	
Max. EIRP	WCDMA Band II		QPSK	16.51 dBm
	HSDPA Band II		QPSK	15.65 dBm
	HSUPA Band II		QPSK	15.67 dBm
	LTE	Channel Bandwidth (MHz)	QPSK (dBm)	16QAM (dBm)
	Band 2	1.4	16.18	15.35
		3	16.31	15.73
		5	16.33	15.36
		10	16.57	15.61
		15	16.16	16.03
		20	16.68	15.83

Note:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

2. Channel List:

WCDMA Band II				
Test Frequency ID	UARFCN	Frequency of Uplink (MHz)	UARFCN	Frequency of Downlink (MHz)
Low Range	9262	1852.4	9662	1932.4
Mid Range	9400	1880.0	9800	1960.0
High Range	9538	1907.6	9938	1987.6

LTE Band 2					
Test Frequency ID	Bandwidth (MHz)	N _{UL}	Frequency of Uplink (MHz)	N _{DL}	Frequency of Downlink (MHz)
Low Range	1.4	18607	1850.7	607	1930.7
	3	18615	1851.5	615	1931.5
	5	18625	1852.5	625	1932.5
	10	18650	1855	650	1935
	15	18675	1857.5	675	1937.5
	20	18700	1860	700	1940
Mid Range	1.4/3/5/10/15/20	18900	1880	900	1960
High Range	1.4	19193	1909.3	1193	1989.3
	3	19185	1908.5	1185	1988.5
	5	19175	1907.5	1175	1987.5
	10	19150	1905	1150	1985
	15	19125	1902.5	1125	1982.5
	20	19100	1900	1100	1980

3. Table for Filed Antenna:

Brand	Model Name	Antenna Type	Connector	Gain (dBi)	Note
N/A	N/A	Loop	N/A	-6.3	WCDMA Band II
N/A	N/A	Loop	N/A	-6.3	LTE Band 2

Note: The antenna gain is provided by the manufacturer.


2.2 DESCRIPTION OF TEST MODES

Following mode(s) is (were) found to be the worst case(s) and selected for the final test.

WCDMA BAND II MODE			
Test Item	Available Channel	Tested Channel	Mode
Output Power & EIRP	9262 to 9538	9262, 9400, 9538	WCDMA, HSDPA, HSUPA
Occupied Bandwidth	9262 to 9538	9262, 9400, 9538	WCDMA
Conducted Spurious Emissions	9262 to 9538	9400	WCDMA
Radiated Spurious Emissions	9262 to 9538	9400	WCDMA
Band Edge	9262 to 9538	9262, 9538	WCDMA
Peak To Average Ratio	9262 to 9538	9262, 9400, 9538	WCDMA
Frequency Stability	9262 to 9538	9262, 9538	WCDMA

LTE BAND 2 MODE					
Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
Output Power & EIRP	18607 to 19193	18607, 18900, 19193	1.4MHz	QPSK, 16QAM	1RB/3RB/6RB
	18615 to 19185	18615, 18900, 19185	3MHz	QPSK, 16QAM	1RB/8RB/15RB
	18625 to 19175	18625, 18900, 19175	5MHz	QPSK, 16QAM	1RB/12RB/25RB
	18650 to 19150	18650, 18900, 19150	10MHz	QPSK, 16QAM	1RB/25RB/50RB
	18675 to 19125	18675, 18900, 19125	15MHz	QPSK, 16QAM	1RB/36RB/75RB
	18700 to 19100	18700, 18900, 19100	20MHz	QPSK, 16QAM	1RB/50RB/100RB
Occupied Bandwidth	18607 to 19193	18607, 18900, 19193	1.4MHz	QPSK, 16QAM	6RB
	18615 to 19185	18615, 18900, 19185	3MHz	QPSK, 16QAM	15RB
	18625 to 19175	18625, 18900, 19175	5MHz	QPSK, 16QAM	25RB
	18650 to 19150	18650, 18900, 19150	10MHz	QPSK, 16QAM	50RB
	18675 to 19125	18675, 18900, 19125	15MHz	QPSK, 16QAM	75RB
	18700 to 19100	18700, 18900, 19100	20MHz	QPSK, 16QAM	100RB
Conducted Spurious Emissions	18607 to 19193	18900	1.4 MHz	QPSK	1RB
	18625 to 19175	18900	5MHz	QPSK	1RB
	18700 to 19100	18900	20MHz	QPSK	1RB
Radiated Spurious Emissions	18607 to 19193	18900	1.4 MHz	QPSK	1RB
	18625 to 19175	18900	5MHz	QPSK	1RB
	18700 to 19100	18900	20MHz	QPSK	1RB
Band Edge	18607 to 19193	18607, 19193	1.4MHz	QPSK	1RB/6RB
	18615 to 19185	18615, 19185	3MHz	QPSK	1RB/15RB
	18625 to 19175	18625, 19175	5MHz	QPSK	1RB/25RB
	18650 to 19150	18650, 19150	10MHz	QPSK	1RB/50RB
	18675 to 19125	18675, 19125	15MHz	QPSK	1RB/75RB
	18700 to 19100	18700, 19100	20MHz	QPSK	1RB/100RB
Peak To Average Ratio	18607 to 19193	18607, 18900, 19193	1.4MHz	QPSK, 16QAM	1RB
	18615 to 19185	18615, 18900, 19185	3MHz	QPSK, 16QAM	1RB
	18625 to 19175	18625, 18900, 19175	5MHz	QPSK, 16QAM	1RB
	18650 to 19150	18650, 18900, 19150	10MHz	QPSK, 16QAM	1RB
	18675 to 19125	18675, 18900, 19125	15MHz	QPSK, 16QAM	1RB
	18700 to 19100	18700, 18900, 19100	20MHz	QPSK, 16QAM	1RB
Frequency Stability	18700 to 19100	18700, 19100	20MHz	QPSK	1RB

2.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.
-	-	-	-	-

Item	Cable Type	Shielded Type	Ferrite Core	Length
1	USB Cable	NO	NO	1.2m

3. TEST RESULT

3.1 OUTPUT POWER MEASUREMENT

3.1.1 LIMIT

Mobile / Portable station are limited to 2 watts e.i.r.p.

3.1.2 TEST PROCEDURE

The testing follows FCC KDB 971168 v03r01 Section 5.

EIRP:


$EIRP = \text{Output Power} + \text{Antenan gain}$

Output Power:

The EUT was set up for the maximum power with GSM, GPRS, EDGE, WCDMA and LTE link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

3.1.3 TEST SETUP LAYOUT

Output Power Measurement



3.1.4 TEST DEVIATION

No deviation

3.1.5 TEST RESULTS

Please refer to the APPENDIX A.


3.2 OCCUPIED BANDWIDTH MEASUREMENT

3.2.1 TEST PROCEDURE

The testing follows FCC KDB 971168 v03r01 Section 4.

1. The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth and 26dB bandwidth.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. $RBW = (1\% \sim 5\%) \cdot EBW$
 $VBW \geq 3 \cdot RBW$
4. Set spectrum analyzer with Peak detector.

3.2.2 TEST SETUP LAYOUT



3.2.3 TEST DEVIATION

No deviation

3.2.4 TEST RESULTS

Please refer to the APPENDIX B.

3.3 CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

3.3.1 LIMIT


The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm.

3.3.2 TEST PROCEDURES

The testing follows FCC KDB 971168 v03r01 Section 6.

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The band edges of low and high channels for the highest RF powers were measured. Set RBW $\geq 1\%$ EBW in the 1MHz band immediately outside and adjacent to the band edge.
3. Set spectrum analyzer with Peak detector.
4. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.3.3 TEST SETUP LAYOUT



3.3.4 TEST DEVIATION

No deviation

3.3.5 TEST RESULTS

Please refer to the APPENDIX C.

3.4 RADIATED SPURIOUS EMISSIONS MEASUREMENT

3.4.1 LIMIT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm.


3.4.2 TEST PROCEDURES

The testing follows FCC KDB 971168 v03r01 Section 6.2.


1. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
2. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value " of step a. Record the power level of S.G
3. $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}.$
4. ERP can be calculated form EIRP by subtracting the gain of dipole, $ERP = EIPR - 2.15\text{dBi}.$
5. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.


3.4.3 TEST SETUP LAYOUT

Below 30MHz



30MHz to 1000MHz





3.4.4 TEST DEVIATION

No deviation

3.4.5 TEST RESULTS (9KHZ TO 30MHZ)

Please refer to the APPENDIX D.

3.4.6 TEST RESULTS (30MHZ TO 1000MHZ)

Please refer to the APPENDIX E.

3.4.7 TEST RESULTS (ABOVE 1000MHZ)

Please refer to the APPENDIX F.

3.5 BAND EDGE MEASUREMENT

3.5.1 LIMIT


A Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

3.5.2 TEST PROCEDURES

The testing follows FCC KDB 971168 v03r01 Section 6.

1. All measurements were done at low and high operational frequency range.
2. Record the max trace plot into the test report.

3.5.3 TEST SETUP LAYOUT



3.5.4 TEST DEVIATION

No deviation

3.5.5 TEST RESULTS

Please refer to the APPENDIX G.

3.6 PEAK TO AVERAGE RATIO MEASUREMENT

3.6.1 LIMIT


In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.6.2 TEST PROCEDURES

The testing follows FCC KDB 971168 v03r01 Section 5.7.

1. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.

3.6.3 TEST SETUP LAYOUT



3.6.4 TEST DEVIATION

No deviation

3.6.5 TEST RESULTS

Please refer to the APPENDIX H.

3.7 FREQUENCY STABILITY MEASUREMENT

3.7.1 LIMIT


The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

3.7.2 TEST PROCEDURES

The testing follows ANSI C63.26-2015 Section 5.6.

1. A reference point shall be established at the applicable unwanted emissions limit using a RBW equal to the RBW required by the unwanted emissions specification of the applicable regulatory standard. These reference points measured using the lowest and highest channel of operation shall be identified as f_L and f_H respectively. The worst-case frequency offset determined in the above methods shall be added or subtracted from the values of f_L and f_H and the resulting frequencies must remain within the band.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.7.3 TEST SETUP LAYOUT



3.7.4 TEST DEVIATION

No deviation

3.7.5 TEST RESULTS

Please refer to the APPENDIX I.

4. LIST OF MEASUREMENT EQUIPMENTS

Radiated Emissions - 9 kHz to 30 MHz					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	MXE EMI Receiver	Keysight	N9038A	MY56400091	Feb. 27, 2022
2*	Active Loop Antenna	R&S	HFH2-Z2	830749/020	Aug. 23, 2024
3	Cable	N/A	RG 213/U(9kHz~1GHz)	N/A	May 27, 2022
4	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
5	wideband radio communication tester	R&S	CMW500	152372	Feb. 27, 2022
6	Wireless Communication Test SET	Agilent	E5515C	MY48364183	Feb. 28, 2022
7	966 Chamber Room	ETS	9*6*6	N/A	Jul. 17, 2022

Radiated Emissions - 30 MHz to 1 GHz					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Antenna	Schwarzbeck	VULB9160	9160-3232	Mar. 15, 2022
2	Amplifier	HP	8447D	2944A08742	Feb. 28, 2022
3	Cable	emci	LMR-400	N/A	Nov. 30, 2022
4	Controller	CT	SC100	N/A	N/A
5	Controller	MF	MF-7802	MF780208416	N/A
6	Receiver	Agilent	N9038A	MY52130039	Mar. 19, 2022
7	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
8	wideband radio communication tester	R&S	CMW500	152372	Feb. 27, 2022
9	Wireless Communication Test SET	Agilent	E5515C	MY48364183	Feb. 28, 2022
10	966 Chamber Room	RM	9*6*6	N/A	Jul. 24, 2022

Radiated Emissions - Above 1 GHz					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Double Ridged Horn Antenna	ARA	DRG-118A	16554	Apr. 21, 2022
2	Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170319	Jun. 30, 2022
3	Amplifier	Agilent	8449B	3008A02584	Jul. 10, 2022
4	Controller	CT	SC100	N/A	N/A
5	Controller	MF	MF-7802	MF780208416	N/A
6	Receiver	Agilent	N9038A	MY52130039	Mar. 19, 2022
7	EXA Spectrum Analyzer	Keysight	N9010A	MY56480488	Feb. 28, 2022
8	Low Noise Amplifier	CONNPHY	CLN-18G40G-4330-K	619413	Jul. 16, 2022
9	Cable	N/A	A81-SMAMSMAM-12.5M	N/A	Oct. 15, 2022
10	Cable	Talent microwave	A40-2.92M2.92M-2.5M	N/A	Nov. 30, 2022
11	Filter	STI	STI15-9912	N/A	Jul. 10, 2022
12	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
13	wideband radio communication tester	R&S	CMW500	152372	Feb. 27, 2022
14	Wireless Communication Test SET	Agilent	E5515C	MY48364183	Feb. 28, 2022
15	966 Chamber Room	RM	9*6*6	N/A	Jul. 24, 2022



Conducted Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	8960 Series 10 Wireless Com Test set	Agilent	E5515E	MY52112163	Jul. 24, 2022
2	MXA Signal Analyzer	Keysight	N9020A	MY49100060	Jul. 24, 2022
3	Power Splitter	Mini-Circuits	ZFRSC-183-S+	SF103501511S	Jul. 24, 2022
4	wideband radio communication tester	R&S	CMW500	104462	Jul. 24, 2022
5	Const Temp. & Humidity Chamber	Bell	BTH-50C	20170306001	Feb. 27, 2022
6*	Multi-output DC Power Supply	GW Instek	GPC-3030DN	EK880675	Jul. 25, 2023


Remark: "N/A" denotes no model name, serial no. or calibration specified.
Except * item, all calibration period of equipment list is one year.
"***" calibration period of equipment list is three year.

5. EUT TEST PHOTO

Radiated Emissions Test Photos

9 kHz to 30 MHz



Radiated Emissions Test Photos**30 MHz to 1 GHz**

Radiated Emissions Test Photos**Above 1 GHz**

APPENDIX A - OUTPUT POWER

Output Power (dBm)

Modulation	Band	WCDMA Band II		
	Tx Channel	9262CH	9400CH	9538CH
	Frequency	1852.4MHz	1880MHz	1907.6MHz
QPSK	RMC 12.2K	22.65	22.81	22.79
	RMC 64K	22.52	22.73	22.69
	RMC 144K	22.49	22.68	22.71
	RMC 384K	22.53	22.54	22.66
	HSDPA Subtest-1	21.71	21.68	21.86
	HSDPA Subtest-2	21.72	21.71	21.95
	HSDPA Subtest-3	21.16	21.30	21.41
	HSDPA Subtest-4	21.25	21.26	21.32
	HSUPA Subtest-1	21.43	21.68	21.41
	HSUPA Subtest-2	20.63	20.34	20.90
	HSUPA Subtest-3	19.79	20.05	20.22
	HSUPA Subtest-4	21.05	20.77	20.91
	HSUPA Subtest-5	21.68	21.76	21.97

LTE Band / BW	Modulation	RB Size	RB Offset	Low CH	Mid CH	High CH
				18607CH	18900CH	19193CH
				1850.7MHz	1880MHz	1909.3MHz
2 / 1.4M	QPSK	1	0	22.28	22.30	22.23
		1	2	22.45	22.41	22.29
		1	5	22.26	22.31	22.28
		3	0	22.20	22.32	22.26
		3	1	22.40	22.45	22.39
		3	2	22.35	22.48	22.25
		6	0	21.31	21.40	21.28
	16QAM	1	0	21.27	21.41	21.54
		1	2	21.65	21.54	21.44
		1	5	21.37	21.39	21.49
		3	0	21.48	21.41	21.54
		3	1	21.46	21.35	21.52
		3	2	21.40	21.32	21.37
		6	0	20.47	20.87	20.18

LTE Band / BW	Modulation	RB Size	RB Offset	Low CH	Mid CH	High CH
				18615CH	18900CH	19185CH
				1851.5MHz	1880MHz	1908.5MHz
2 / 3M	QPSK	1	0	22.61	22.41	22.52
		1	7	22.60	22.58	22.44
		1	14	22.58	22.53	22.11
		8	0	21.46	21.47	21.55
		8	4	21.48	21.49	21.48
		8	7	21.42	21.54	21.36
		15	0	21.35	21.52	21.41
	16QAM	1	0	21.19	20.99	21.58
		1	7	21.77	22.03	21.59
		1	14	21.67	21.85	21.18
		8	0	20.83	20.52	20.67
		8	4	20.86	20.64	20.51
		8	7	20.82	20.60	20.41
		15	0	20.35	20.59	20.48

LTE Band / BW	Modulation	RB Size	RB Offset	Low CH	Mid CH	High CH
				18625CH	18900CH	19175CH
				1852.5MHz	1880MHz	1907.5MHz
2 / 5M	QPSK	1	0	22.26	22.25	22.63
		1	13	22.40	22.44	22.53
		1	24	22.45	22.29	22.17
		12	0	21.43	21.45	21.52
		12	6	21.47	21.60	21.54
		12	11	21.41	21.55	21.44
		25	0	21.40	21.50	21.51
	16QAM	1	0	21.66	21.22	21.49
		1	13	21.37	21.31	21.56
		1	24	21.20	21.06	21.11
		12	0	20.30	20.32	20.66
		12	6	20.24	20.27	20.68
		12	11	20.17	20.27	20.63
		25	0	20.26	20.36	20.50

LTE Band / BW	Modulation	RB Size	RB Offset	Low CH	Mid CH	High CH
				18650CH	18900CH	19150CH
				1855MHz	1880MHz	1905MHz
2 / 10M	QPSK	1	0	22.40	22.53	22.24
		1	25	22.66	22.87	22.61
		1	49	22.71	22.30	22.14
		25	0	21.60	21.53	21.46
		25	13	21.52	21.67	21.43
		25	25	21.41	21.38	21.29
		50	0	21.42	21.37	21.35
	16QAM	1	0	21.76	21.22	21.18
		1	25	21.78	21.91	21.58
		1	49	21.89	21.08	21.40
		25	0	20.38	20.58	20.72
		25	13	20.29	20.84	20.81
		25	25	20.33	20.63	20.51
		50	0	20.42	20.53	20.43

LTE Band / BW	Modulation	RB Size	RB Offset	Low CH	Mid CH	High CH
				18675CH	18900CH	19125CH
				1857.5MHz	1880MHz	1902.5MHz
2 / 15M	QPSK	1	0	22.39	22.32	22.24
		1	38	22.39	22.46	22.44
		1	74	22.35	22.29	22.22
		36	0	21.34	21.34	21.30
		36	18	21.28	21.49	21.41
		36	39	21.18	21.39	21.27
		75	0	21.29	21.40	21.28
	16QAM	1	0	21.63	21.29	21.88
		1	38	22.00	21.80	22.33
		1	74	21.65	20.93	21.92
		36	0	20.52	20.45	20.25
		36	18	20.44	20.55	20.46
		36	39	20.45	20.45	20.31
		75	0	20.42	20.50	20.32

LTE Band / BW	Modulation	RB Size	RB Offset	Low CH	Mid CH	High CH
				18700CH	18900CH	19100CH
				1860MHz	1880MHz	1900MHz
2 / 20M	QPSK	1	0	22.20	22.20	22.21
		1	50	22.13	22.76	22.98
		1	99	21.81	22.25	22.12
		50	0	21.46	21.40	21.36
		50	25	21.39	21.61	21.48
		50	50	21.33	21.38	21.42
		100	0	21.40	21.38	21.45
	16QAM	1	0	20.97	20.88	20.91
		1	50	21.57	21.78	22.13
		1	99	20.94	21.25	21.16
		50	0	20.42	20.34	20.31
		50	25	20.39	20.64	20.40
		50	50	20.43	20.31	20.30
		100	0	20.44	20.41	20.37

EIRP (dBm)

Modulation	Band	WCDMA Band II		
	Tx Channel	9262CH	9400CH	9538CH
	Frequency	1852.4MHz	1880MHz	1907.6MHz
QPSK	RMC 12.2K	16.35	16.51	16.49
	RMC 64K	16.22	16.43	16.39
	RMC 144K	16.19	16.38	16.41
	RMC 384K	16.23	16.24	16.36
	HSDPA Subtest-1	15.41	15.38	15.56
	HSDPA Subtest-2	15.42	15.41	15.65
	HSDPA Subtest-3	14.86	15.00	15.11
	HSDPA Subtest-4	14.95	14.96	15.02
	HSUPA Subtest-1	15.13	15.38	15.11
	HSUPA Subtest-2	14.33	14.04	14.60
	HSUPA Subtest-3	13.49	13.75	13.92
	HSUPA Subtest-4	14.75	14.47	14.61
	HSUPA Subtest-5	15.38	15.46	15.67

LTE Band / BW	Modulation	RB Size	RB Offset	Low CH	Mid CH	High CH
				18607CH	18900CH	19193CH
				1850.7MHz	1880MHz	1909.3MHz
2 / 1.4M	QPSK	1	0	15.98	16.00	15.93
		1	2	16.15	16.11	15.99
		1	5	15.96	16.01	15.98
		3	0	15.90	16.02	15.96
		3	1	16.10	16.15	16.09
		3	2	16.05	16.18	15.95
		6	0	15.01	15.10	14.98
	16QAM	1	0	14.97	15.11	15.24
		1	2	15.35	15.24	15.14
		1	5	15.07	15.09	15.19
		3	0	15.18	15.11	15.24
		3	1	15.16	15.05	15.22
		3	2	15.10	15.02	15.07
		6	0	14.17	14.57	13.88

LTE Band / BW	Modulation	RB Size	RB Offset	Low CH	Mid CH	High CH
				18615CH	18900CH	19185CH
				1851.5MHz	1880MHz	1908.5MHz
2 / 3M	QPSK	1	0	16.31	16.11	16.22
		1	7	16.30	16.28	16.14
		1	14	16.28	16.23	15.81
		8	0	15.16	15.17	15.25
		8	4	15.18	15.19	15.18
		8	7	15.12	15.24	15.06
		15	0	15.05	15.22	15.11
	16QAM	1	0	14.89	14.69	15.28
		1	7	15.47	15.73	15.29
		1	14	15.37	15.55	14.88
		8	0	14.53	14.22	14.37
		8	4	14.56	14.34	14.21
		8	7	14.52	14.30	14.11
		15	0	14.05	14.29	14.18

LTE Band / BW	Modulation	RB Size	RB Offset	Low CH	Mid CH	High CH
				18625CH	18900CH	19175CH
				1852.5MHz	1880MHz	1907.5MHz
2 / 5M	QPSK	1	0	15.96	15.95	16.33
		1	13	16.10	16.14	16.23
		1	24	16.15	15.99	15.87
		12	0	15.13	15.15	15.22
		12	6	15.17	15.30	15.24
		12	11	15.11	15.25	15.14
		25	0	15.10	15.20	15.21
	16QAM	1	0	15.36	14.92	15.19
		1	13	15.07	15.01	15.26
		1	24	14.90	14.76	14.81
		12	0	14.00	14.02	14.36
		12	6	13.94	13.97	14.38
		12	11	13.87	13.97	14.33
		25	0	13.96	14.06	14.20


LTE Band / BW	Modulation	RB Size	RB Offset	Low CH	Mid CH	High CH
				18650CH	18900CH	19150CH
				1855MHz	1880MHz	1905MHz
2 / 10M	QPSK	1	0	16.10	16.23	15.94
		1	25	16.36	16.57	16.31
		1	49	16.41	16.00	15.84
		25	0	15.30	15.23	15.16
		25	13	15.22	15.37	15.13
		25	25	15.11	15.08	14.99
		50	0	15.12	15.07	15.05
	16QAM	1	0	15.46	14.92	14.88
		1	25	15.48	15.61	15.28
		1	49	15.59	14.78	15.10
		25	0	14.08	14.28	14.42
		25	13	13.99	14.54	14.51
		25	25	14.03	14.33	14.21
		50	0	14.12	14.23	14.13

LTE Band / BW	Modulation	RB Size	RB Offset	Low CH	Mid CH	High CH
				18675CH	18900CH	19125CH
				1857.5MHz	1880MHz	1902.5MHz
2 / 15M	QPSK	1	0	16.09	16.02	15.94
		1	38	16.09	16.16	16.14
		1	74	16.05	15.99	15.92
		36	0	15.04	15.04	15.00
		36	18	14.98	15.19	15.11
		36	39	14.88	15.09	14.97
		75	0	14.99	15.10	14.98
	16QAM	1	0	15.33	14.99	15.58
		1	38	15.70	15.50	16.03
		1	74	15.35	14.63	15.62
		36	0	14.22	14.15	13.95
		36	18	14.14	14.25	14.16
		36	39	14.15	14.15	14.01
		75	0	14.12	14.20	14.02


LTE Band / BW	Modulation	RB Size	RB Offset	Low CH	Mid CH	High CH
				18700CH	18900CH	19100CH
				1860MHz	1880MHz	1900MHz
2 / 20M	QPSK	1	0	15.90	15.90	15.91
		1	50	15.83	16.46	16.68
		1	99	15.51	15.95	15.82
		50	0	15.16	15.10	15.06
		50	25	15.09	15.31	15.18
		50	50	15.03	15.08	15.12
		100	0	15.10	15.08	15.15
	16QAM	1	0	14.67	14.58	14.61
		1	50	15.27	15.48	15.83
		1	99	14.64	14.95	14.86
		50	0	14.12	14.04	14.01
		50	25	14.09	14.34	14.10
		50	50	14.13	14.01	14.00
		100	0	14.14	14.11	14.07

APPENDIX B - OCCUPIED BANDWIDTH


WCDMA Band II_WCDMA			
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26dB Bandwidth (MHz)
		QPSK	QPSK
9262	1852.4	4.1399	4.747
9400	1880	4.1394	4.704
9538	1907.6	4.1239	4.717




LTE Band 2_1.4MHz					
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)		26dB Bandwidth (MHz)	
		QPSK	16QAM	QPSK	16QAM
18607	1850.7	1.0858	1.0905	1.345	1.340
18900	1880	1.0998	1.0941	1.316	1.310
19193	1909.3	1.0875	1.0917	1.301	1.297




LTE Band 2_3MHz					
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)		26dB Bandwidth (MHz)	
		QPSK	16QAM	QPSK	16QAM
18615	1851.5	2.6992	2.7022	2.996	3.007
18900	1880	2.7032	2.7046	2.978	2.979
19185	1908.5	2.7012	2.6958	2.978	2.984




LTE Band 2_5MHz					
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)		26dB Bandwidth (MHz)	
		QPSK	16QAM	QPSK	16QAM
18625	1852.5	4.5254	4.4977	4.984	5.031
18900	1880	4.5016	4.5042	5.001	4.984
19175	1907.5	4.5076	4.5032	4.994	4.953




LTE Band 2_10MHz					
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)		26dB Bandwidth (MHz)	
		QPSK	16QAM	QPSK	16QAM
18650	1855	8.9619	8.9579	9.959	9.923
18900	1880	8.9555	8.9453	9.900	9.905
19150	1905	8.9705	8.9429	9.851	9.854



LTE Band 2_15MHz					
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)		26dB Bandwidth (MHz)	
		QPSK	16QAM	QPSK	16QAM
18675	1857.5	13.432	13.423	14.69	14.73
18900	1880	13.405	13.413	14.63	14.61
19125	1902.5	13.396	13.389	14.69	14.66




LTE Band 2_20MHz					
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)		26dB Bandwidth (MHz)	
		QPSK	16QAM	QPSK	16QAM
18700	1860	17.908	17.907	19.47	19.56
18900	1880	17.852	17.848	19.28	19.40
19100	1900	17.852	17.862	19.42	19.50




APPENDIX C - CONDUCTED SPURIOUS EMISSIONS


WCDMA Band II_WCDMA_CH9400 Spectrum Plot



Date: 9.NOV.2020 09:30:24






Date: 9.NOV.2020 09:31:00






Date: 9.NOV.2020 09:31:51




LTE Band 2_1.4MHz_CH18900 Spectrum Plot



LTE Band 2_5MHz_CH18900 Spectrum Plot




LTE Band 2_20MHz_CH18900 Spectrum Plot



APPENDIX D - RADIATED SPURIOUS EMISSIONS (9KHZ TO 30MHZ)


Test Mode : TX Mode

Ant 0°




Test Mode : TX Mode

Ant 0°




Test Mode : TX Mode

Ant 90°



Test Mode : TX Mode


Ant 90°



APPENDIX E - RADIATED SPURIOUS EMISSIONS (30MHZ TO 1000MHZ)

Test Mode : WCDMA Band II_TX CH9400


Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	Comment
1		76.075	-52.06	-17.55	-69.61	-13.00	-56.61	peak		
2		156.100	-56.97	-12.47	-69.44	-13.00	-56.44	peak		
3		244.370	-58.92	-13.19	-72.11	-13.00	-59.11	peak		
4		523.730	-63.82	-6.23	-70.05	-13.00	-57.05	peak		
5		678.930	-62.16	-3.35	-65.51	-13.00	-52.51	peak		
6 *		929.190	-63.02	1.16	-61.86	-13.00	-48.86	peak		

Test Mode : WCDMA Band II_TX CH9400


Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	Comment
1		89.655	-56.64	-18.50	-75.14	-13.00	-62.14	peak		
2		156.585	-59.54	-12.45	-71.99	-13.00	-58.99	peak		
3		288.505	-60.64	-11.28	-71.92	-13.00	-58.92	peak		
4		469.410	-62.74	-7.06	-69.80	-13.00	-56.80	peak		
5		773.990	-61.67	-1.34	-63.01	-13.00	-50.01	peak		
6 *		958.775	-64.49	1.81	-62.68	-13.00	-49.68	peak		

Test Mode : LTE Band 2_TX CH18900_1.4MHz


Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	Comment
1		78.985	-51.83	-18.17	-70.00	-13.00	-57.00	peak		
2		126.515	-56.70	-13.66	-70.36	-13.00	-57.36	peak		
3		157.070	-57.69	-12.45	-70.14	-13.00	-57.14	peak		
4		249.705	-60.31	-12.94	-73.25	-13.00	-60.25	peak		
5		496.570	-62.10	-6.60	-68.70	-13.00	-55.70	peak		
6 *		860.805	-62.63	-0.44	-63.07	-13.00	-50.07	peak		

Test Mode : LTE Band 2_TX CH18900_1.4MHz


Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree	Comment
1		87.715	-57.38	-18.58	-75.96	-13.00	-62.96	peak		
2		154.645	-60.95	-12.51	-73.46	-13.00	-60.46	peak		
3		284.140	-59.97	-11.43	-71.40	-13.00	-58.40	peak		
4		508.210	-62.90	-6.44	-69.34	-13.00	-56.34	peak		
5		651.770	-62.80	-3.70	-66.50	-13.00	-53.50	peak		
6 *		853.530	-62.31	-0.58	-62.89	-13.00	-49.89	peak		


Test Mode : LTE Band 2_TX CH18900_5MHz

Vertical




Test Mode : LTE Band 2_TX CH18900_5MHz

Horizontal




Test Mode : LTE Band 2_TX CH18900_20MHz

Vertical



Test Mode : LTE Band 2_TX CH18900_20MHz


Horizontal



APPENDIX F - RADIATED SPURIOUS EMISSIONS (ABOVE 1000MHZ)

Test Mode : WCDMA Band II_TX CH9400


Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree
		MHz	dBm	dB	dBm	dBm	dB	cm	degree
1 *		3754.000	-41.55	2.28	-39.27	-13.00	-26.27	peak	

Test Mode : WCDMA Band II_TX CH9400


Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree
		MHz	dBm	dB	dBm	dBm	dB	cm	degree
1 *		3754.000	-47.12	2.28	-44.84	-13.00	-31.84	peak	

Test Mode : LTE Band 2_TX CH18900_1.4MHz


Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree
		MHz	dBm	dB	dBm	dBm	dB	cm	degree
1 *		3754.000	-51.80	2.28	-49.52	-13.00	-36.52	peak	

Test Mode : LTE Band 2_TX CH18900_1.4MHz


Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Antenna Height	Table Degree
		MHz	dBm	dB	dBm	dBm	dB	cm	degree
1 *		3754.000	-54.76	2.28	-52.48	-13.00	-39.48	peak	


Test Mode : LTE Band 2_TX CH18900_5MHz

Vertical




Test Mode : LTE Band 2_TX CH18900_5MHz

Horizontal




Test Mode : LTE Band 2_TX CH18900_20MHz

Vertical



Test Mode : LTE Band 2_TX CH18900_20MHz

Horizontal



APPENDIX G - BAND EDGE

