



MRT Technology (Suzhou) Co., Ltd  
Phone: +86-512-66308358  
Fax: +86-512-66308368  
Web: www.mrt-cert.com

Report No.: 1404RSU00302  
Report Version: V01  
Issue Date: 04-08-2014

## RF Exposure Evaluation Declaration

---

FCC ID: 2ABHDASP2800X

APPLICANT: ShenZhen Soundpower Technology Co., Ltd.

Application Type: Certification

Product: LED Lamp + Bluetooth Wireless Speaker  
Combo

Model No.: ASP2800X, ASP2810X, ASP2820X, ASP2830X,  
ASP2840X, ASP2850X, ASP2860X, ASP2870X,  
ASP2880X, ASP2890X

FCC Classification: FCC Part 15 Spread Spectrum Transmitter  
(DSS)

Test Date: April 03 ~ 05, 2014

Reviewed By : Robin Wu  
( Robin Wu )

Approved By : Marlin Chen  
( Marlin Chen )

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

## Revision History

Report No.	Version	Description	Issue Date
1404RSU00302	Rev. 01	Initial report	04-08-2014

## 1. RF Exposure Evaluation

### 1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)  
LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	f/1500	6
1500-100,000	--	--	1	30

f= Frequency in MHz

Calculation Formula:  $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$r$  = distance between observation point and center of the radiator in cm (The minimum distance is 20cm)

$P_d$  is the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance  $r$  where the MPE limit is reached.

## 1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

## 1.3. Test Result of RF Exposure Evaluation

Product	LED Lamp + Bluetooth Wireless Speaker Combo
Test Item	RF Exposure Evaluation

Antenna Gain: The maximum Gain measured in fully anechoic chamber is -1.0dBi in logarithm scale.

Freq. Band (MHz)	Max. Output power (dBm)	Max. Output power (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit S(mW/cm <sup>2</sup> )
2402 ~ 2480	6.713	4.613	0.00074	1

————— The End —————