




# FCC Radio Test Report

## FCC ID: 2ABM5-MS115BT

This report concerns (check one): Original Grant Class II Change

<b>Project No.</b>	:	1410C073
<b>Equipment</b>	:	CLOCK RADIO WITH BLUETOOTH
<b>Model Name</b>	:	MS115BT; MS115BTyy(y=A-Z or blank, "y" denotes colour)
<b>Applicant</b>	:	Zhong Shan City LI TAI Electronic Industrial Co., Ltd
<b>Address</b>	:	No.3 Industrial District,Wuguishan Town,Zhongshan,Guangdong,China
<b>Date of Receipt</b>	:	Oct. 16, 2014
<b>Date of Test</b>	:	Oct. 16, 2014~Nov. 06, 2014
<b>Issued Date</b>	:	Nov. 07, 2014
<b>Tested by</b>	:	BTL Inc.

<b>Testing Engineer</b>	:	 (David Mao)
<b>Technical Manager</b>	:	 (Leo Hung)
<b>Authorized Signatory</b>	:	 (Steven Lu)

**B T L I N C .**

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan,  
Guangdong, China.

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

## **Declaration**

**BTL** represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measurement Laboratory (**NML**) of **CHINA**, or National Institute of Standards and Technology (**NIST**) of **U.S.A**.

**BTL**'s reports apply only to the specific samples tested under conditions. It is manufacturer's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

**BTL**'s reports must not be used by the client to claim product endorsement by the authorities or any agency of the Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **BTL-self**, extracts from the test report shall not be reproduced except in full with **BTL**'s authorized written approval.

**BTL**'s laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

## **Limitation**

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Table of Contents	Page
<b>1 . CERTIFICATION</b>	<b>7</b>
<b>2 . SUMMARY OF TEST RESULTS</b>	<b>8</b>
<b>2.1 TEST FACILITY</b>	<b>9</b>
<b>2.2 MEASUREMENT UNCERTAINTY</b>	<b>9</b>
<b>3 . GENERAL INFORMATION</b>	<b>10</b>
<b>3.1 GENERAL DESCRIPTION OF EUT</b>	<b>10</b>
<b>3.2 DESCRIPTION OF TEST MODES</b>	<b>12</b>
<b>3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING</b>	<b>12</b>
<b>3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED</b>	<b>13</b>
<b>3.5 DESCRIPTION OF SUPPORT UNITS</b>	<b>13</b>
<b>4 . EMC EMISSION TEST</b>	<b>14</b>
<b>4.1 CONDUCTED EMISSION MEASUREMENT</b>	<b>14</b>
<b>4.1.1 POWER LINE CONDUCTED EMISSION LIMITS</b>	<b>14</b>
<b>4.1.2 TEST PROCEDURE</b>	<b>14</b>
<b>4.1.3 DEVIATION FROM TEST STANDARD</b>	<b>14</b>
<b>4.1.4 TEST SETUP</b>	<b>15</b>
<b>4.1.5 EUT OPERATING CONDITIONS</b>	<b>15</b>
<b>4.1.6 EUT TEST CONDITIONS</b>	<b>15</b>
<b>4.1.7 TEST RESULTS</b>	<b>15</b>
<b>4.2 RADIATED EMISSION MEASUREMENT</b>	<b>16</b>
<b>4.2.1 RADIATED EMISSION LIMITS</b>	<b>16</b>
<b>4.2.2 TEST PROCEDURE</b>	<b>17</b>
<b>4.2.3 DEVIATION FROM TEST STANDARD</b>	<b>17</b>
<b>4.2.4 TEST SETUP</b>	<b>18</b>
<b>4.2.5 EUT OPERATING CONDITIONS</b>	<b>19</b>
<b>4.2.6 EUT TEST CONDITIONS</b>	<b>19</b>
<b>4.2.7 TEST RESULTS (9KHZ TO 30MHZ)</b>	<b>19</b>
<b>4.2.8 TEST RESULTS (BETWEEN 30MHZ TO 1000 MHZ)</b>	<b>20</b>
<b>4.2.9 TEST RESULTS (ABOVE 1000 MHZ)</b>	<b>20</b>
<b>5 . NUMBER OF HOPPING CHANNEL</b>	<b>21</b>
<b>5.1 APPLIED PROCEDURES</b>	<b>21</b>
<b>5.1.1 TEST PROCEDURE</b>	<b>21</b>
<b>5.1.2 DEVIATION FROM STANDARD</b>	<b>21</b>
<b>5.1.3 TEST SETUP</b>	<b>21</b>
<b>5.1.4 EUT OPERATION CONDITIONS</b>	<b>21</b>
<b>5.1.5 EUT TEST CONDITIONS</b>	<b>21</b>
<b>5.1.6 TEST RESULTS</b>	<b>21</b>

Table of Contents	Page
<b>6 . AVERAGE TIME OF OCCUPANCY</b>	<b>22</b>
<b>6.1 APPLIED PROCEDURES / LIMIT</b>	<b>22</b>
<b>6.1.1 TEST PROCEDURE</b>	22
<b>6.1.2 DEVIATION FROM STANDARD</b>	22
<b>6.1.3 TEST SETUP</b>	22
<b>6.1.4 EUT OPERATION CONDITIONS</b>	23
<b>6.1.5 EUT TEST CONDITIONS</b>	23
<b>6.1.6 TEST RESULTS</b>	23
<b>7 . HOPPING CHANNEL SEPARATION MEASUREMENT</b>	<b>24</b>
<b>7.1 APPLIED PROCEDURES / LIMIT</b>	<b>24</b>
<b>7.1.1 TEST PROCEDURE</b>	24
<b>7.1.2 DEVIATION FROM STANDARD</b>	24
<b>7.1.3 TEST SETUP</b>	24
<b>7.1.4 EUT TEST CONDITIONS</b>	24
<b>7.1.5 TEST RESULTS</b>	24
<b>8 . BANDWIDTH TEST</b>	<b>25</b>
<b>8.1 APPLIED PROCEDURES</b>	<b>25</b>
<b>8.1.1 TEST PROCEDURE</b>	25
<b>8.1.2 DEVIATION FROM STANDARD</b>	25
<b>8.1.3 TEST SETUP</b>	25
<b>8.1.4 EUT OPERATION CONDITIONS</b>	25
<b>8.1.5 EUT TEST CONDITIONS</b>	25
<b>8.1.6 TEST RESULTS</b>	25
<b>9 . PEAK OUTPUT POWER TEST</b>	<b>26</b>
<b>9.1 APPLIED PROCEDURES / LIMIT</b>	<b>26</b>
<b>9.1.1 TEST PROCEDURE</b>	26
<b>9.1.2 DEVIATION FROM STANDARD</b>	26
<b>9.1.3 TEST SETUP</b>	26
<b>9.1.4 EUT OPERATION CONDITIONS</b>	26
<b>9.1.5 EUT TEST CONDITIONS</b>	26
<b>9.1.6 TEST RESULTS</b>	26
<b>10 . ANTENNA CONDUCTED SPURIOUS EMISSION</b>	<b>27</b>
<b>10.1 APPLIED PROCEDURES / LIMIT</b>	<b>27</b>
<b>10.1.1 TEST PROCEDURE</b>	27
<b>10.1.2 DEVIATION FROM STANDARD</b>	27
<b>10.1.3 TEST SETUP</b>	27
<b>10.1.4 EUT OPERATION CONDITIONS</b>	27
<b>10.1.5 EUT TEST CONDITIONS</b>	27
<b>10.1.6 TEST RESULTS</b>	27
<b>11 . MEASUREMENT INSTRUMENTS LIST</b>	<b>28</b>

Table of Contents	Page
<b>12 . EUT TEST PHOTO</b>	<b>30</b>
<b>ATTACHMENT A - CONDUCTED EMISSION</b>	<b>34</b>
<b>ATTACHMENT B - RADIATED EMISSION (9KHZ-30MHZ)</b>	<b>37</b>
<b>ATTACHMENT C - RADIATED EMISSION (30MHZ TO 1000MHZ)</b>	<b>39</b>
<b>ATTACHMENT D - RADIATED EMISSION (ABOVE 1000MHZ)</b>	<b>46</b>
<b>ATTACHMENT E - NUMBER OF HOPPING CHANNEL</b>	<b>71</b>
<b>ATTACHMENT F - AVERAGE TIME OF OCCUPANCY</b>	<b>73</b>
<b>ATTACHMENT G - HOPPING CHANNEL SEPARATION MEASUREMENT</b>	<b>86</b>
<b>ATTACHMENT H - BANDWIDTH</b>	<b>91</b>
<b>ATTACHMENT I - PEAK OUTPUT POWER</b>	<b>96</b>
<b>ATTACHMENT J - ANTENNA CONDUCTED SPURIOUS EMISSION</b>	<b>101</b>

**REPORT ISSUED HISTORY**

Issued No.	Description	Issued Date
BTL-FCCP-1-1410C073	Original Issue.	Nov. 07, 2014

## 1. CERTIFICATION

Equipment : CLOCK RADIO WITH BLUETOOTH  
Brand Name : neon  
Model Name : MS115BT; MS115BTyy(y=A-Z or blank, "y" denotes colour)  
Applicant : Zhong Shan City LI TAI Electronic Industrial Co., Ltd  
Manufacturer : Zhong Shan City LI TAI Electronic Industrial Co., Ltd  
Address : No.3 Industrial District,Wuguishan Town,Zhongshan,Guangdong,China  
Factory : Zhong Shan City LI TAI Electronic Industrial Co., Ltd  
Address : No.3 Industrial District,Wuguishan Town,Zhongshan,Guangdong,China  
Date of Test : Oct. 16, 2014~Nov. 06, 2014  
Test Sample : ENGINEERING SAMPLE  
Standard(s) : FCC Part15, Subpart C : 2013 (15.247) / ANSI C63.4 : 2009 /  
FCC Public Notice DA 00-705, March 30, 2000.

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL-FCCP-1-1410C073) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO-17025 quality assessment standard and technical standard(s).

## 2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

<b>Applied Standard(s): 47 CFR Part 15, Subpart C: 2013;</b>			
<b>Standard(s) Section</b>	<b>Test Item</b>	<b>Judgment</b>	<b>Remark</b>
15.207	Conducted Emission	PASS	
15.247(d)	Antenna conducted Spurious Emission	PASS	
15.247 (a)(1)	Hopping Channel Separation	PASS	
15.247 (b)(1)	Peak Output Power	PASS	
15.247(d) 15.209	Radiated Spurious Emission	PASS	
15.247 (a)(1)(iii)	Number of Hopping Frequency	PASS	
15.247 (a)(1)(iii)	Dwell Time	PASS	
15.205	Restricted Bands	PASS	
15.203	Antenna Requirement	PASS	

Note:

- (1)" N/A" denotes test is not applicable in this test report
- (2) According to FCC Public Notice DA 00-705, March 30, 2000.

## 2.1 TEST FACILITY

The test facilities used to collect the test data in this report is **DG-C02/DG-CB03** at the location of No.3,Jinshagang 1st Road, Shixia, Dalang Town, Dong Guan, Guangdong, China.523792  
BTL's test firm number for FCC: 319330

## 2.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty **U** is based on a standard uncertainty multiplied by a coverage factor of **k=2**, providing a level of confidence of approximately **95 %**.

### A. Conducted Measurement :

Test Site	Method	Measurement Frequency Range	U , (dB)	Note
DG-C02	CISPR	150 KHz ~ 30MHz	3.40	

### B. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	Ant. H / V	U , (dB)	Note
DG-CB03	CISPR	9KHz~30MHz	V	3.79	
		9KHz~30MHz	H	3.57	
		30MHz ~ 200MHz	V	3.82	
		30MHz ~ 200MHz	H	3.60	
		200MHz ~ 1,000MHz	V	3.86	
		200MHz ~ 1,000MHz	H	3.94	
		1GHz~18GHz	V	3.12	
		1GHz~18GHz	H	3.68	
		18GHz~40GHz	V	4.15	
		18GHz~40GHz	H	4.14	

### 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

Equipment	CLOCK RADIO WITH BLUETOOTH	
Brand Name	neon	
Model Name	MS115BT; MS115BTyy(y=A-Z or blank, "y" denotes colour)	
OEM Model Name	SCR13E	
OEM Brand Name	Sandstrom	
Model Difference	Brand name and colour	
Output Power (Max.)	Operation Frequency	2402~2480 MHz
	Modulation Technology	GFSK(1Mbps) $\pi/4$ -DQPSK(2Mbps) 8-DPSK(3Mbps)
	Bit Rate of Transmitter	
	Output Power Max.	-1.92dBm(1Mbps) -2.11 dBm(3Mbps)
Power Source	DC Voltage supplied from AC/DC adapter. Brand/ Model: INTERTEK/ Y12FE-050-2000G	
Power Rating	I/P AC 100-240V~ 50-60Hz 0.35A O/P DC 5V 2000mA	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

## 3 Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	Printed	N/A	2.12

### 3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX Mode <b>Note (1)</b>
Mode 2	Bluetooth

The EUT system operated these modes were found to be the worst case during the pre-scanning test as following:

For Conducted Emission	
Final Test Mode	Description
Mode 2	Bluetooth

For Radiated Emission	
Final Test Mode	Description
Mode 1	TX Mode <b>Note (1)</b>

**Note:**

- (1) The measurements are performed at the high, middle, low available channels.
- (2) The measurements for Hopping Channel Separation, Bandwidth and Peak Output Power were tested during 1Mbps, 2Mbps and 3Mbps, the worst case are 1Mbps and 3Mbps, only worst case was documented.

### 3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

1Mbps


Test Software Version	RDA_BT_Tester		
Frequency (MHz)	2402	2441	2480
Parameters	15	15	15

3Mbps

Test Software Version	RDA_BT_Tester		
Frequency (MHz)	2402	2441	2480
Parameters	15	15	15

### 3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

**Radiated TX Mode:**



### 3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID/IC	Series No.	Note
-	-	-	-	-	-	

Item	Shielded Type	Ferrite Core	Length	Note
-	-	-	-	

## 4. EMC EMISSION TEST

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

Frequency of Emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15 -0.5	66 to 56*	56 to 46*
0.50 -5.0	56	46
5.0 -30.0	60	50

Note:

(1) The limit of " \* " decreases with the logarithm of the frequency

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz


#### 4.1.2 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 4.1.3 DEVIATION FROM TEST STANDARD

No deviation

#### 4.1.4 TEST SETUP



**Note:**

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

#### 4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical function (as a customer would normally use it), EUT was programmed to be in continuously transmitting/receiving data or hopping on mode.

#### 4.1.6 EUT TEST CONDITIONS

Temperature: 25°C

Relative Humidity: 55%

Test Voltage: AC 120V/60Hz

#### 4.1.7 TEST RESULTS

Please refer to the Attachment A.

Remark:

- (1) All readings are QP Mode value unless otherwise stated AVG in column of <sup>†</sup>Note. If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform in this case, a "\*" marked in AVG Mode column of Interference Voltage Measured.
- (2) Measuring frequency range from 150KHz to 30MHz.

## 4.2 RADIATED EMISSION MEASUREMENT

### 4.2.1 RADIATED EMISSION LIMITS (Frequency Range 9KHz -1000MHz)

20dB in any 100 KHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

Frequency (MHz)	dB(uV/m) (at 3 meters)	
	Peak	Average
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m) = 20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Spectrum Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9KHz ~90KHz for PK/AVG detector
Start ~ Stop Frequency	90KHz ~110KHz for QP detector
Start ~ Stop Frequency	110KHz ~490KHz for PK/AVG detector
Start ~ Stop Frequency	490KHz ~30MHz for QP detector
Start ~ Stop Frequency	30MHz~1000MHz for QP detector

#### **4.2.2 TEST PROCEDURE**


- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### **4.2.3 DEVIATION FROM TEST STANDARD**


No deviation

#### 4.2.4 TEST SETUP


(A) Radiated Emission Test Set-Up Frequency Below 1 GHz



(B) Radiated Emission Test Set-Up Frequency Above 1 GHz



(C) For radiated emissions below 30MHz



#### 4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing

#### 4.2.6 EUT TEST CONDITIONS

Temperature: 25°C

Relative Humidity: 55%

Test Voltage: AC 120V/60Hz

#### 4.2.7 TEST RESULTS (9KHZ TO 30MHZ)

**Please refer to the Attachment B**

Remark:

- (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
- (2) Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB).
- (3) Limit line = specific limits (dBuV) + distance extrapolation factor.

#### **4.2.8 TEST RESULTS (BETWEEN 30MHZ TO 1000 MHZ)**

**Please refer to the Attachment C.**

Remark:

- (1) Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode or Peak Mode with Detector BW=120KHz ; SPA setting in RBW=120KHz, VBW =120KHz, Swp. Time = 0.3 sec./MHz.
- (2) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- (3) Measuring frequency range from 30MHz to 1000MHz.
- (4) If the peak scan value lower limit more than 20dB, then this signal data does not show in table.

#### **4.2.9 TEST RESULTS (ABOVE 1000 MHZ)**

**Please refer to the Attachment D.**

Remark:

- (1) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- (2) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission
- (3) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (4) EUT Orthogonal Axis:  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (5) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (6) No limit: This is fundamental signal, the judgment is not applicable.  
For fundamental signal judgment was referred to Peak output test.

## 5. NUMBER OF HOPPING CHANNEL

### 5.1 APPLIED PROCEDURES

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Frequency Range (MHz)	Result
15.247(a)(1)(iii)	Number of Hopping Channel	2400-2483.5	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> Operating Frequency Range
RBW	100 KHz
VBW	100 KHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

#### 5.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW=100KHz, VBW=100KHz, Sweep time = Auto.

#### 5.1.2 DEVIATION FROM STANDARD

No deviation.

#### 5.1.3 TEST SETUP



#### 5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing.

#### 5.1.5 EUT TEST CONDITIONS

Temperature: 25°C

Relative Humidity: 55%

Test Voltage: AC 120V/60Hz

#### 5.1.6 TEST RESULTS

Please refer to the Attachment E

## 6. AVERAGE TIME OF OCCUPANCY

### 6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(1)(iii)	Average Time of Occupancy	0.4sec	2400-2483.5	PASS

#### 6.1.1 TEST PROCEDURE

- a. The transmitter output (antenna port) was connected to the spectrum analyzer
- b. Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz.
- c. Use a video trigger with the trigger level set to enable triggering only on full pulses.
- d. Sweep Time is more than once pulse time.
- e. Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- f. Measure the maximum time duration of one single pulse.
- g. Set the EUT for DH5, DH3 and DH1 packet transmitting.
- h. Measure the maximum time duration of one single pulse.
- i. DH5 Packet permit maximum  $1600 / 79 / 6 = 3.37$  hops per second in each channel (5 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times  $3.37 \times 31.6 = 106.6$  within 31.6 seconds.
- j. DH3 Packet permit maximum  $1600 / 79 / 4 = 5.06$  hops per second in each channel (3 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times  $5.06 \times 31.6 = 160$  within 31.6 seconds.
- k. DH1 Packet permit maximum  $1600 / 79 / 2 = 10.12$  hops per second in each channel (1 time slot TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times  $10.12 \times 31.6 = 320$  within 31.6 seconds.

#### 6.1.2 DEVIATION FROM STANDARD

No deviation.

#### 6.1.3 TEST SETUP



#### **6.1.4 EUT OPERATION CONDITIONS**

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing.

#### **6.1.5 EUT TEST CONDITIONS**

Temperature: 25°C

Relative Humidity: 55%

Test Voltage: AC 120V/60Hz

#### **6.1.6 TEST RESULTS**

**Please refer to the Attachment F**

## 7. HOPPING CHANNEL SEPARATION MEASUREMENT

### 7.1 APPLIED PROCEDURES / LIMIT

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 KHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RBW	30 KHz
VBW	100 KHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


#### 7.1.1 TEST PROCEDURE

- The EUT must have its hopping function enabled
- Span = wide enough to capture the peaks of two adjacent channels  
Resolution (or IF) Bandwidth (RBW)  $\geq$  1% of the span  
Video (or Average) Bandwidth (VBW)  $\geq$  RBW  
Sweep = Auto  
Detector function = Peak  
Trace = Max Hold

#### 7.1.2 DEVIATION FROM STANDARD

No deviation.

#### 7.1.3 TEST SETUP



#### 7.1.4 EUT TEST CONDITIONS

Temperature: 25°C  
Relative Humidity: 55%  
Test Voltage: AC 120V/60Hz

#### 7.1.5 TEST RESULTS

Please refer to the Attachment G

## 8. BANDWIDTH TEST

### 8.1 APPLIED PROCEDURES

FCC Part15 (15.247) , Subpart C		
Section	Test Item	Frequency Range (MHz)
15.247(a)(2)	Bandwidth	2400-2483.5

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RBW	30 KHz (20dB Bandwidth) / 30 KHz (Channel Separation)
VBW	100 KHz (20dB Bandwidth) / 100 KHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


#### 8.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW= 30KHz, VBW=100KHz, Sweep Time = Auto.

#### 8.1.2 DEVIATION FROM STANDARD

No deviation.

#### 8.1.3 TEST SETUP



#### 8.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing.

#### 8.1.5 EUT TEST CONDITIONS

Temperature: 25°C

Relative Humidity: 55%

Test Voltage: AC 120V/60Hz

#### 8.1.6 TEST RESULTS

Please refer to the Attachment H

## 9. PEAK OUTPUT POWER TEST

### 9.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(1)	Peak Output Power	1 Watt or 30dBm	2400-2483.5	PASS

#### 9.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 1MHz/3MHz, VBW= 1MHz/3MHz, Sweep time = Auto.

#### 9.1.2 DEVIATION FROM STANDARD

No deviation.

#### 9.1.3 TEST SETUP



#### 9.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing.

#### 9.1.5 EUT TEST CONDITIONS

Temperature: 25°C

Relative Humidity: 55%

Test Voltage: AC 120V/60Hz

#### 9.1.6 TEST RESULTS

Please refer to the Attachment I

## 10. ANTENNA CONDUCTED SPURIOUS EMISSION

### 10.1 APPLIED PROCEDURES / LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

#### 10.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 100KHz, VBW=100KHz, Sweep time = Auto.

#### 10.1.2 DEVIATION FROM STANDARD

No deviation.

#### 10.1.3 TEST SETUP



#### 10.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing.

#### 10.1.5 EUT TEST CONDITIONS

Temperature: 25°C

Relative Humidity: 55%

Test Voltage: AC 120V/60Hz

#### 10.1.6 TEST RESULTS

Please refer to the Attachment J

## 11. MEASUREMENT INSTRUMENTS LIST

Conducted Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	LISN	EMCO	3816/2	00052765	Mar. 29, 2015
2	LISN	R&S	ENV216	101447	Mar. 29, 2015
3	Test Cable	N/A	C_17	N/A	Mar. 14, 2015
4	EMI TEST RECEIVER	R&S	ESCS30	833364/017	Mar. 29, 2015
5	50Ω Terminator	SHX	TF2-3G-A	08122902	Mar. 29, 2015
6	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-0 1	N/A	N/A

Radiated Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Antenna	Schwarbeck	VULB9160	9160-3232	Mar. 29, 2015
2	Amplifier	HP	8447D	2944A09673	Mar. 29, 2015
3	Test Receiver	R&S	ESCI	100382	Mar. 29, 2015
4	Test Cable	N/A	C-01_CB03	N/A	Jul. 01, 2015
5	Antenna	ETS	3115	00075789	Mar. 29, 2015
6	Amplifier	Agilent	8449B	3008A02274	Mar. 29, 2015
7	Spectrum	Agilent	E4408B	US39240143	Nov. 09, 2015
8	Test Cable	HUBER+SUHNER	C-45	N/A	Mar. 29, 2015
9	Controller	CT	SC100	N/A	N/A
10	Horn Antenna	EMCO	3115	9605-4803	Mar. 29, 2015
11	Active Loop Antenna	R&S	HFH2-Z2	830749/020	Mar. 29, 2015

**Number of Hopping Channel**

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov. 11, 2014

**Average Time of Occupancy**

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov. 11, 2014

**Hopping Channel Separation Measurement**

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov. 11, 2014

**Bandwidth**

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov. 11, 2014

**Peak Output Power**


Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov. 11, 2014

**Antenna Conducted Spurious Emission**

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov. 11, 2014

Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of equipment list is one year.

**12. EUT TEST PHOTO****Conducted Measurement Photos**

## Radiated Measurement Photos

**9KHz to 30MHz**



## Radiated Measurement Photos

30MHz to 1000MHz



## Radiated Measurement Photos


### Above 1000MHz



## ATTACHMENT A - CONDUCTED EMISSION


Test Mode: TX Mode

## Line



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.1578	23.10	9.52	32.62	65.58	-32.96	peak	
2 *	0.3141	28.52	9.60	38.12	59.86	-21.74	peak	
3	0.5406	21.58	9.68	31.26	56.00	-24.74	peak	
4	0.8220	20.10	9.66	29.76	56.00	-26.24	peak	
5	1.5992	20.12	9.70	29.82	56.00	-26.18	peak	
6	18.7695	25.27	10.41	35.68	60.00	-24.32	peak	

Test Mode: TX Mode

**Neutral**

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1		0.1695	21.72	9.62	31.34	64.98	-33.64	peak	
2		0.3141	24.02	9.62	33.64	59.86	-26.22	peak	
3		0.5797	19.71	9.65	29.36	56.00	-26.64	peak	
4		1.5406	18.68	9.71	28.39	56.00	-27.61	peak	
5		9.2227	17.67	10.06	27.73	60.00	-32.27	peak	
6	*	18.1290	24.53	10.38	34.91	60.00	-25.09	peak	

## ATTACHMENT B - RADIATED EMISSION (9KHZ-30MHZ)

Test Mode:	TX Mode
------------	---------

Frequency (MHz)	Ant 0°/90°	Read level dBuV/m	Factor (dB)	Measured(FS) (dBuV/m)	Limit(QP) (dBuV/m)	Margin (dB)	Note
0.0217	0°	5.63	24.19	29.82	100.88	-71.05	AVG
0.0217	0°	7.14	24.19	31.33	120.88	-89.54	PEAK
0.0362	0°	2.18	23.27	25.45	96.43	-70.98	AVG
0.0362	0°	3.85	23.27	27.12	116.43	-89.31	PEAK
0.0436	0°	0.39	22.81	23.20	94.81	-71.62	AVG
0.0436	0°	1.57	22.81	24.38	114.81	-90.44	PEAK
0.0575	0°	-0.17	22.25	22.08	92.41	-70.33	AVG
0.0575	0°	1.95	22.25	24.20	112.41	-88.21	PEAK
1.7126	0°	23.34	19.53	42.87	69.54	-26.67	QP
2.0167	0°	28.55	19.49	48.04	69.54	-21.50	QP

Frequency (MHz)	Ant 0°/90°	Read level dBuV/m	Factor (dB)	Measured(FS) (dBuV/m)	Limit(QP) (dBuV/m)	Margin (dB)	Note
0.0189	90°	5.17	24.30	29.47	122.07	-92.60	AVG
0.0189	90°	6.52	24.30	30.82	142.07	-111.25	PEAK
0.0373	90°	2.15	23.20	25.35	116.17	-90.82	AVG
0.0373	90°	3.46	23.20	26.66	136.17	-109.51	PEAK
0.0425	90°	0.82	22.88	23.70	115.04	-91.34	AVG
0.0425	90°	1.57	22.88	24.45	135.04	-110.59	PEAK
0.0593	90°	-0.42	22.21	21.79	112.14	-90.35	AVG
0.0593	90°	1.86	22.21	24.07	132.14	-108.07	PEAK
1.6168	90°	24.25	19.54	43.79	63.43	-19.64	QP
2.4752	90°	29.57	19.21	48.78	69.54	-20.76	QP

## ATTACHMENT C - RADIATED EMISSION (30MHZ TO 1000MHZ)

Test Mode: TX 2402MHz\_CH00\_1Mbps

## Vertical



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1	*	92.0800	52.86	-17.36	35.50	43.50	-8.00	peak	
2		318.0900	48.83	-11.27	37.56	46.00	-8.44	peak	
3		395.6900	44.62	-9.73	34.89	46.00	-11.11	peak	
4		497.5400	43.90	-10.43	33.47	46.00	-12.53	peak	
5		813.7600	34.73	-2.97	31.76	46.00	-14.24	peak	
6		995.1500	33.91	-0.39	33.52	54.00	-20.48	peak	

Test Mode: TX 2402MHz\_CH00\_1Mbps

## Horizontal



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dB			
1		97.9000	50.52	-16.68	33.84	43.50	-9.66	peak	
2		191.9900	49.54	-14.48	35.06	43.50	-8.44	peak	
3		292.8700	49.14	-11.12	38.02	46.00	-7.98	peak	
4	*	395.6900	50.99	-9.73	41.26	46.00	-4.74	peak	
5		480.0800	45.58	-9.76	35.82	46.00	-10.18	peak	
6		683.7800	39.97	-5.00	34.97	46.00	-11.03	peak	

Test Mode: TX 2441MHz\_CH39\_1Mbps

## Vertical



No.	Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Detector	Comment
			dBuV	dB	dBuV/m	dBuV/m	dB		
1		96.9300	53.65	-16.84	36.81	43.50	-6.69	peak	
2		144.4600	48.13	-13.16	34.97	43.50	-8.53	peak	
3		310.3300	49.80	-11.15	38.65	46.00	-7.35	peak	
4	*	395.6900	49.26	-9.73	39.53	46.00	-6.47	peak	
5		540.2200	43.12	-8.44	34.68	46.00	-11.32	peak	
6		912.7000	33.84	-1.20	32.64	46.00	-13.36	peak	

Test Mode: TX 2441MHz \_CH39\_1Mbps

### Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB	Detector	Comment
1		96.9300	50.83	-16.84	33.99	43.50	-9.51	peak
2		191.9900	50.48	-14.48	36.00	43.50	-7.50	peak
3		294.8100	49.19	-11.09	38.10	46.00	-7.90	peak
4	*	431.5800	49.01	-8.95	40.06	46.00	-5.94	peak
5		480.0800	44.77	-9.76	35.01	46.00	-10.99	peak
6		944.7100	34.83	-0.35	34.48	46.00	-11.52	peak

Test Mode: TX 2480MHz \_CH78\_1Mbps

## Vertical



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		97.9000	53.41	-16.68	36.73	43.50	-6.77	peak	
2	*	144.4600	50.02	-13.16	36.86	43.50	-6.64	peak	
3		302.5700	49.83	-11.03	38.80	46.00	-7.20	peak	
4		419.9400	43.86	-9.17	34.69	46.00	-11.31	peak	
5		564.4700	42.44	-7.93	34.51	46.00	-11.49	peak	
6		660.5000	38.23	-5.10	33.13	46.00	-12.87	peak	

Test Mode: TX 2480MHz \_CH78\_1Mbps

**Horizontal**


No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB	Detector	Comment
1		97.9000	49.46	-16.68	32.78	43.50	-10.72	peak
2		203.6300	50.01	-15.14	34.87	43.50	-8.63	peak
3		300.6300	50.13	-11.01	39.12	46.00	-6.88	peak
4	*	395.6900	49.46	-9.73	39.73	46.00	-6.27	peak
5		468.4400	46.91	-9.32	37.59	46.00	-8.41	peak
6		971.8700	35.39	-0.29	35.10	54.00	-18.90	peak

## ATTACHMENT D - RADIATED EMISSION (ABOVE 1000MHZ)

Orthogonal Axis : X


Test Mode : TX 2402MHz \_CH00\_1Mbps

## Vertical



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
		MHz	dBuV	dB	dBuV/m	dB	Detector	
1		2390.000	24.68	31.88	56.56	74.00	-17.44	peak
2		2390.000	13.92	31.88	45.80	54.00	-8.20	AVG
3	X	2401.850	68.25	31.89	100.14	74.00	26.14	peak NO Limit
4	*	2401.850	58.59	31.89	90.48	54.00	36.48	AVG NO Limit


Orthogonal Axis :	X
Test Mode :	TX 2402MHz _CH00_1Mbps

**Vertical**

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1	*	4803.700	42.93	3.58	46.51	54.00	-7.49
		4803.750	54.74	3.58	58.32	74.00	-15.68
							AVG
							peak

Orthogonal Axis : X

Test Mode : TX 2402MHz \_CH00\_1Mbps

**Horizontal**

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		2390.000	22.98	31.88	54.86	74.00	-19.14	peak	
2		2390.000	13.86	31.88	45.74	54.00	-8.26	AVG	
3	X	2401.800	65.47	31.89	97.36	74.00	23.36	peak	NO Limit
4	*	2401.850	55.74	31.89	87.63	54.00	33.63	AVG	NO Limit

Orthogonal Axis :	X
Test Mode :	TX 2402MHz _CH00_1Mbps


**Horizontal**

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1	*	4803.690	38.98	3.58	42.56	54.00	-11.44	AVG	
2		4803.785	50.41	3.58	53.99	74.00	-20.01	peak	

Orthogonal Axis : X

Test Mode : TX 2441MHz \_CH39\_1Mbps

## Vertical



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dB			
1		2390.000	22.98	31.88	54.86	74.00	-19.14	peak	
2		2390.000	13.86	31.88	45.74	54.00	-8.26	AVG	
3	X	2401.800	65.47	31.89	97.36	74.00	23.36	peak	NO Limit
4	*	2401.850	55.74	31.89	87.63	54.00	33.63	AVG	NO Limit


Orthogonal Axis :	X
Test Mode :	TX 2441MHz _CH39_1Mbps

**Vertical**

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1	*	4881.690	44.33	3.73	48.06	54.00	-5.94
2		4881.775	55.05	3.73	58.78	74.00	-15.22
						Detector	Comment
						AVG	
						peak	


Orthogonal Axis : X

Test Mode : TX 2441MHz \_CH39\_1Mbps

**Horizontal**


No.	Mk.	Reading		Correct Factor	Measure- ment	Limit	Over	Detector	Comment
		Freq.	Level						
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	X	2440.850	63.52	31.95	95.47	74.00	21.47	peak	NO Limit
2	*	2440.850	53.88	31.95	85.83	54.00	31.83	AVG	NO Limit

Orthogonal Axis :	X
Test Mode :	TX 2441MHz _CH39_1Mbps

**Horizontal**

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1	*	4881.695	39.13	3.73	42.86	54.00	-11.14
2		4881.860	49.94	3.73	53.67	74.00	-20.33
							AVG
							peak

Orthogonal Axis :	X
Test Mode :	TX 2480MHz _CH78_1Mbps

**Vertical**

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	X	2479.850	64.29	32.00	96.29	74.00	22.29	peak	NO Limit
2	*	2479.850	54.62	32.00	86.62	54.00	32.62	AVG	NO Limit
3		2483.500	24.23	32.01	56.24	74.00	-17.76	peak	
4		2483.500	14.26	32.01	46.27	54.00	-7.73	AVG	


Orthogonal Axis :	X
Test Mode :	TX 2480MHz _CH78_1Mbps

**Vertical**

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1		4959.635	56.00	3.88	59.88	74.00	-14.12
2	*	4959.695	45.56	3.88	49.44	54.00	-4.56
							AVG

Orthogonal Axis : X

Test Mode : TX 2480MHz \_CH78\_1Mbps

**Horizontal**

No.	Mk.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
		Freq.	Level	Factor				
		MHz	dBuV	dB	dBuV/m	dB		
1	X	2479.800	62.65	32.00	94.65	74.00	20.65	peak NO Limit
2	*	2479.850	53.03	32.00	85.03	54.00	31.03	AVG NO Limit
3		2483.500	23.90	32.01	55.91	74.00	-18.09	peak
4		2483.500	14.15	32.01	46.16	54.00	-7.84	AVG

Orthogonal Axis :	X
Test Mode :	TX 2480MHz _CH78_1Mbps


**Horizontal**

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1	*	4959.680	33.99	3.88	37.87	54.00	-16.13
2		4959.740	44.23	3.88	48.11	74.00	-25.89
						AVG	peak

Orthogonal Axis : X


Test Mode : TX 2402MHz \_CH00\_3Mbps

## Vertical



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dB			
1		2390.000	27.61	31.88	59.49	74.00	-14.51	peak	
2		2390.000	13.88	31.88	45.76	54.00	-8.24	AVG	
3	X	2401.850	68.05	31.89	99.94	74.00	25.94	peak	NO Limit
4	*	2402.000	57.36	31.89	89.25	54.00	35.25	AVG	NO Limit


Orthogonal Axis :	X
Test Mode :	TX 2402MHz _CH00_3Mbps

**Vertical**

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1	*	4803.690	45.67	3.58	49.25	54.00	-4.75
2		4803.820	54.83	3.58	58.41	74.00	-15.59
						AVG	peak

Orthogonal Axis : X

Test Mode : TX 2402MHz \_CH00\_3Mbps

**Horizontal**

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		2390.000	24.98	31.88	56.86	74.00	-17.14	peak	
2		2390.000	13.83	31.88	45.71	54.00	-8.29	AVG	
3	*	2401.950	54.98	31.89	86.87	54.00	32.87	AVG	NO Limit
4	X	2402.150	65.62	31.89	97.51	74.00	23.51	peak	NO Limit

Orthogonal Axis :	X
Test Mode :	TX 2402MHz _CH00_3Mbps


**Horizontal**

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	4803.870	41.28	3.58	44.86	54.00	-9.14	AVG	
2		4804.185	50.63	3.58	54.21	74.00	-19.79	peak	

Orthogonal Axis : X

Test Mode : TX 2441MHz \_CH39\_3Mbps


## Vertical



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dB			
1	X	2440.850	65.93	31.95	97.88	74.00	23.88	peak	NO Limit
2	*	2440.950	55.12	31.95	87.07	54.00	33.07	AVG	NO Limit

Orthogonal Axis : X


Test Mode : TX 2441MHz \_CH39\_3Mbps

**Vertical**

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
			Level	Factor	ment			
		MHz	dBuV	dB	dBuV/m	dB	Detector	Comment
1	*	4881.570	42.83	3.73	46.56	54.00	-7.44	AVG
2		4881.865	54.05	3.73	57.78	74.00	-16.22	peak


Orthogonal Axis : X

Test Mode : TX 2441MHz \_CH39\_3Mbps

**Horizontal**

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	2440.950	52.30	31.95	84.25	54.00	30.25	AVG	NO Limit
2	X	2441.150	63.13	31.95	95.08	74.00	21.08	peak	NO Limit

Orthogonal Axis :	X
Test Mode :	TX 2441MHz _CH39_3Mbps


**Horizontal**

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1	*	4881.785	40.23	3.73	43.96	54.00	-10.04	AVG	
2		4881.950	50.04	3.73	53.77	74.00	-20.23	peak	

Orthogonal Axis : X

Test Mode : TX 2480MHz \_CH78\_3Mbps

## Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB	Detector	Comment
1	X	2479.850	64.02	32.00	96.02	74.00	22.02	peak NO Limit
2	*	2479.950	53.01	32.00	85.01	54.00	31.01	AVG NO Limit
3		2483.500	25.68	32.01	57.69	74.00	-16.31	peak
4		2483.500	14.19	32.01	46.20	54.00	-7.80	AVG


Orthogonal Axis :	X
Test Mode :	TX 2480MHz _CH78_3Mbps

**Vertical**

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1		4959.910	51.56	3.88	55.44	74.00	-18.56
2	*	4959.940	41.11	3.88	44.99	54.00	-9.01
							AVG

Orthogonal Axis : X

Test Mode : TX 2480MHz \_CH78\_3Mbps

**Horizontal**

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Comment
			Level	Factor	ment			
		MHz	dBuV	dB	dBuV/m	dB	Detector	
1	X	2479.800	62.36	32.00	94.36	74.00	20.36	peak NO Limit
2	*	2479.950	51.25	32.00	83.25	54.00	29.25	AVG NO Limit
3		2483.500	23.46	32.01	55.47	74.00	-18.53	peak
4		2483.500	14.09	32.01	46.10	54.00	-7.90	AVG

Orthogonal Axis :	X
Test Mode :	TX 2480MHz _CH78_3Mbps

**Horizontal**

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1		4959.915	45.30	3.88	49.18	74.00	-24.82
2	*	4959.935	34.62	3.88	38.50	54.00	-15.50
							peak
							AVG


## ATTACHMENT E - NUMBER OF HOPPING CHANNEL

## Test Mode

## Hopping Mode\_1Mbps

### Number of Hopping Channel

79




Date: 1.NOV.2014 18:18:52

# Test Mode

## Hopping Mode\_3Mbps

### Number of Hopping Channel

79




Date: 1.NOV.2014 19:54:52

## ATTACHMENT F - AVERAGE TIME OF OCCUPANCY

Test Mode :	TX Mode_1Mbps
-------------	---------------


Data Packet	Frequency (MHz)	Pulse Duration (ms)	Dwell Time (s)	Limits (s)	Test Result
DH5	2402	3.1190	0.3327	0.4000	Complies
DH3	2402	1.7590	0.2814	0.4000	Complies
DH1	2402	0.4490	0.1437	0.4000	Complies
DH5	2441	3.0400	0.3243	0.4000	Complies
DH3	2441	1.7800	0.2848	0.4000	Complies
DH1	2441	0.4490	0.1437	0.4000	Complies
DH5	2480	3.0000	0.3200	0.4000	Complies
DH3	2480	1.8190	0.2910	0.4000	Complies
DH1	2480	0.4440	0.1421	0.4000	Complies

## CH00-DH1




Date: 1.NOV.2014 17:51:59


## CH00-DH3



Date: 1.NOV.2014 18:35:07


**CH00-DH5**

Date: 1.NOV.2014 18:55:49

**CH39-DH1**


Date: 1.NOV.2014 17:52:14

## CH39-DH3




Date: 1.NOV.2014 18:33:35

## CH39-DH5




Date: 1.NOV.2014 19:09:36

CH78-DH1




Date: 1.NOV.2014 17:52:26

**CH78-DH3**



Date: 1.NOV.2014 18:33:58

## CH78-DH5




Date: 1.NOV.2014 19:21:24

Test Mode :	TX Mode_3Mbps
-------------	---------------


Data Packet	Frequency (MHz)	Pulse Duration (ms)	Dwell Time (s)	Limits (s)	Test Result
DH5	2402	3.0400	0.3243	0.4000	Complies
DH3	2402	1.7790	0.2846	0.4000	Complies
DH1	2402	0.4440	0.1421	0.4000	Complies
DH5	2441	3.0400	0.3243	0.4000	Complies
DH3	2441	1.7590	0.2814	0.4000	Complies
DH1	2441	0.4440	0.1421	0.4000	Complies
DH5	2480	3.0400	0.3243	0.4000	Complies
DH3	2480	1.8200	0.2912	0.4000	Complies
DH1	2480	0.4490	0.1437	0.4000	Complies

## CH00-DH1




Date: 1.NOV.2014 19:35:22

## CH00-DH3




Date: 1.NOV.2014 20:00:54

## CH00-DH5




Date: 1.NOV.2014 20:07:12

## CH39-DH1




Date: 1.NOV.2014 19:35:37

## CH39-DH3




Date: 1.NOV.2014 20:01:42

## CH39-DH5




Date: 1.NOV.2014 20:07:46

## CH78-DH1




Date: 1.NOV.2014 19:35:50

## CH78-DH3



Date: 1.NOV.2014 20:01:58

## CH78-DH5




Date: 1.NOV.2014 20:08:20

## **ATTACHMENT G - HOPPING CHANNEL SEPARATION MEASUREMENT**


Test Mode : Hopping on \_1Mbps

Frequency (MHz)	Channel Separation (MHz)	2/3 of 20dB Bandwidth (MHz)	Test Result
2402	0.996	0.547	Complies
2441	0.996	0.492	Complies
2480	1.002	0.497	Complies




Date: 1.NOV.2014 18:16:03

## CH39



Date: 1.NOV.2014 18:10:18


## CH78



Date: 1.NOV.2014 18:13:27


Test Mode : Hopping on \_3Mbps

Frequency (MHz)	Channel Separation (MHz)	2/3 of 20dB Bandwidth (MHz)	Test Result
2402	1.000	0.732	Complies
2441	1.002	0.735	Complies
2480	1.002	0.712	Complies




Date: 1.NOV.2014 19:38:13

## CH39



Date: 1.NOV.2014 19:40:27

## CH78




Date: 1.NOV.2014 19:42:42

## ATTACHMENT H - BANDWIDTH

Test Mode : TX Mode \_1Mbps


Frequency (MHz)	20dB Bandwidth (MHz)	99% Occupied BW (MHz)	Test Result
2402	0.820	0.820	Complies
2441	0.738	0.812	Complies
2480	0.745	0.820	Complies

### CH00




Date: 1.NOV.2014 17:44:43

## CH39



Date: 1.NOV.2014 17:46:54

## CH78




Date: 1.NOV.2014 17:48:13

Test Mode : TX Mode \_3Mbps


Frequency (MHz)	20dB Bandwidth (MHz)	99% Occupied BW (MHz)	Test Result
2402	1.098	1.072	Complies
2441	1.102	1.068	Complies
2480	1.067	1.032	Complies

### CH00




Date: 1.NOV.2014 19:31:05

## CH39



Date: 1.NOV.2014 19:32:52

## CH78




Date: 1.NOV.2014 19:34:03

## ATTACHMENT I - PEAK OUTPUT POWER


Test Mode : TX Mode \_1Mbps

Frequency (MHz)	Conducted Power (dBm)	Conducted Power (Watt)	Max. Limit (dBm)	Max. Limit (Watt)	Test Result
2402	-1.92	0.0006	30.00	1.0000	Complies
2441	-2.29	0.0006	30.00	1.0000	Complies
2480	-2.19	0.0006	30.00	1.0000	Complies




Date: 1.NOV.2014 17:45:56

## CH39



Date: 1.NOV.2014 17:47:30


## CH78



Date: 1.NOV.2014 17:48:56


Test Mode :	TX Mode _3Mbps
-------------	----------------

Frequency (MHz)	Conducted Power (dBm)	Conducted Power (Watt)	Max. Limit (dBm)	Max. Limit (Watt)	Test Result
2402	-2.11	0.0006	30.00	1.0000	Complies
2441	-2.41	0.0006	30.00	1.0000	Complies
2480	-2.28	0.0006	30.00	1.0000	Complies




Date: 1.NOV.2014 19:31:49

CH39




Date: 1.NOV.2014 19:33:28

CH78




Date: 1.NOV.2014 19:34:48


**ATTACHMENT J - ANTENNA CONDUCTED SPURIOUS  
EMISSION**

**CH00 (Lower) \_1Mbps**


Date: 1.NOV.2014 17:45:20

**CH78 (Upper) \_1Mbps**


Date: 1.NOV.2014 17:48:20

**CH00 Hopping on mode (Lower) \_1Mbps**


Date: 1.NOV.2014 18:20:17

**CH78 Hopping on mode (Upper) \_1Mbps**


Date: 1.NOV.2014 18:23:52

**CH00 (10 Harmonic of the frequency) \_1Mbps**


Date: 1.NOV.2014 17:44:01

**CH39 (10 Harmonic of the frequency) \_1Mbps**


Date: 1.NOV.2014 17:46:43

**CH78 (10 Harmonic of the frequency) \_1Mbps**


Date: 6.NOV.2014 18:41:39

**CH00 (Lower) \_3Mbps**


Date: 1.NOV.2014 19:31:12

**CH78 (Upper) \_3Mbps**


Date: 1.NOV.2014 19:34:11

**CH00 Hopping on mode (Lower) \_3Mbps**


Date: 1.NOV.2014 19:55:58

**CH78 Hopping on mode (Upper) \_3Mbps**

Date: 1.NOV.2014 19:57:03


**CH00 (10 Harmonic of the frequency) \_3Mbps**

Date: 1.NOV.2014 19:30:53

**CH39 (10 Harmonic of the frequency) \_3Mbps**

Date: 1.NOV.2014 19:32:27

## CH78 (10 Harmonic of the frequency) \_3Mbps



Date: 1.NOV.2014 19:33:53