

# FCC RF Test Report

**APPLICANT** : Nyle Oswind Parry Limited Liability Company  
**EQUIPMENT** : Tablet PC  
**MODEL NAME** : GQY56XZ  
**FCC ID** : 2ABO6-0725  
**STANDARD** : FCC Part 15 Subpart C §15.247  
**CLASSIFICATION** : (DTS) Digital Transmission System

The testing completed on Jul. 14, 2014. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



***SPORTON INTERNATIONAL INC.***  
No. 52, Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

Report No. : FR432436-09B

Report Version : Rev. 01

Page Number : 1 of 44

Report Template No.: BU5-FR15CBT4.0 Version 1.0

# TABLE OF CONTENTS

<b>REVISION HISTORY.....</b>	<b>3</b>
<b>SUMMARY OF TEST RESULT .....</b>	<b>4</b>
<b>1 GENERAL DESCRIPTION.....</b>	<b>5</b>
1.1 Applicant .....	5
1.2 Product Feature of Equipment Under Test.....	5
1.3 Product Specification subjective to this standard .....	5
1.4 Modification of EUT .....	5
1.5 Testing Location .....	6
1.6 Applicable Standards.....	6
<b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....</b>	<b>7</b>
2.1 Descriptions of Test Mode .....	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System .....	8
2.4 Support Unit used in test configuration and system .....	10
2.5 EUT Operation Test Setup .....	10
2.6 Measurement Results Explanation Example.....	10
<b>3 TEST RESULT .....</b>	<b>11</b>
3.1 6dB Bandwidth Measurement .....	11
3.2 Peak Output Power Measurement .....	14
3.3 Power Spectral Density Measurement .....	15
3.4 Conducted Band Edges and Spurious Emission Measurement .....	20
3.5 Radiated Band Edges and Spurious Emission Measurement .....	28
3.6 AC Conducted Emission Measurement.....	37
3.7 Antenna Requirements.....	42
<b>4 LIST OF MEASURING EQUIPMENT.....</b>	<b>43</b>
<b>5 UNCERTAINTY OF EVALUATION.....</b>	<b>44</b>

# REVISION HISTORY

## SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.2	15.247(b)(1)	Peak Output Power	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}$	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 6.25 dB at 4803.000 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 5.10 dB at 1.622 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

# 1 General Description

## 1.1 Applicant

**Nyle Oswind Parry Limited Liability Company**  
7027 Old Madison Pike, Suite 108, Huntsville, Alabama 35806

## 1.2 Product Feature of Equipment Under Test

Product Feature	
Equipment	Tablet PC
Model Name	GQY56XZ
FCC ID	2ABO6-0725
EUT supports Radios application	GSM/EGPRS/WCDMA/HSPA/LTE <b>&lt;2.4GHz band&gt;</b> WLAN 11b/g/n HT20 WLAN 11ac VHT20 Bluetooth v4.0 EDR/LE <b>&lt;5GHz band&gt;</b> WLAN 11a/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.3 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel(37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	7.4 dBm (0.0055 W)
Antenna Type	Fixed internal Antenna Type with gain 2.37 dBi
Type of Modulation	Bluetooth LE : GFSK

## 1.4 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.5 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

<b>Test Site</b>	SPORTON INTERNATIONAL INC.		
<b>Test Site Location</b>	No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978		
<b>Test Site No.</b>	<b>Sporton Site No.</b>		
	TH02-HY	CO05-HY	03CH08-HY

## 1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02
- ANSI C63.4-2003

### Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

## 2 Test Configuration of Equipment Under Test

### 2.1 Descriptions of Test Mode

The RF output power was recorded in the following table:

Channel	Frequency	Bluetooth 4.0 – LE RF Output Power
		Data Rate / Modulation
		GFSK
		1Mbps
Ch00	2402MHz	6.6 dBm
Ch19	2440MHz	7.4 dBm
Ch39	2480MHz	7.0 dBm

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). Pre-scanned tests, X, Y, Z in three orthogonal panels to determine the final configuration (X plane as worst plane) from all possible combinations.
- b. AC power line Conducted Emission was tested under maximum output power.

## 2.2 Test Mode


The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth 4.0 – LE / GFSK
Conducted TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
Radiated TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
AC Conducted Emission	Mode 1: GSM850 (GPRS Class 8) Idle + WLAN (2.4GHz) Link + Bluetooth Link + Earphone + HDMI Cable with Monitor + HDMI to uUSB Dongle + USB Cable (Charging from Adapter) + Camera (Front) Mode 2: GSM850 (GPRS Class 8) Idle + WLAN (2.4GHz) Link + Earphone + HDMI Cable with Monitor + HDMI to uUSB Dongle + USB Cable (Charging from Adapter) + Camera (Front)


**Remark:** The worst case of conducted emission is mode 2; only the test data of it was reported.

## 2.3 Connection Diagram of Test System


<Bluetooth 4.0 – LE Tx Mode>



**<EUT with Adapter and Bluetooth Earphone Mode for AC Conducted Emission>**



**<EUT with Adapter Mode for AC Conducted Emission>**



## 2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
3.	WLAN AP	D-Link	DIR-628	KA2DIR628A2	N/A	Unshielded, 1.8 m
4.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	LCD Monitor	DELL	U2410	FCC DoC	Shielded, 1.6 m	Unshielded, 1.8 m
6.	HDMI to uUSB Dongle	N/A	PS56GR	N/A	Unshielded, 0.17 m	N/A
7.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A

## 2.5 EUT Operation Test Setup

For Bluetooth function, programmed RF utility, “ADB” installed in the EUT make the EUT provide functions like channel selection and power level for continuous transmitting and receiving signals.

## 2.6 Measurement Results Explanation Example

### For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\text{Offset(dB)} = \text{RF cable loss(dB)} + \text{attenuator factor(dB)}.$$

$$= 4.2 + 10 = 14.2 \text{ (dB)}$$

## 3 Test Result

### 3.1 6dB Bandwidth Measurement

#### 3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


#### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.

#### 3.1.4 Test Setup




### 3.1.5 Test Result of 6dB Bandwidth

Test Mode :	Bluetooth 4.0 - LE	Temperature :	22~25°C
Test Engineer :	Bill Kuo and Stuart Lin	Relative Humidity :	51~55%


Channel	Frequency (MHz)	6dB Bandwidth (MHz)	6dB Bandwidth Min. Limit (MHz)	Pass/Fail
00	2402	0.71	0.5	Pass
19	2440	0.71	0.5	Pass
39	2480	0.70	0.5	Pass

6 dB Bandwidth Plot on Channel 00




Date: 16.APR.2014 18:15:31

## 6 dB Bandwidth Plot on Channel 19



Date: 16.APR.2014 18:12:58

## 6 dB Bandwidth Plot on Channel 39



Date: 16.APR.2014 18:10:12

## 3.2 Peak Output Power Measurement

### 3.2.1 Limit of Peak Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


### 3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r02.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Peak Output Power

Test Mode :	Bluetooth 4.0 - LE	Temperature :	22~25°C	
Test Engineer :	Bill Kuo and Stuart Lin	Relative Humidity :	51~55%	
Channel	Frequency (MHz)	RF Power (dBm)		
		GFSK	Max. Limits (dBm)	Pass/Fail
		1 Mbps		
00	2402	6.6	30.00	Pass
19	2440	7.4	30.00	Pass
39	2480	7.0	30.00	Pass

### 3.3 Power Spectral Density Measurement

#### 3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


#### 3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

#### 3.3.4 Test Setup



### 3.3.5 Test Result of Power Spectral Density

Test Mode :	Bluetooth 4.0 - LE	Temperature :	22~25°C
Test Engineer :	Bill Kuo and Stuart Lin	Relative Humidity :	51~55%


Channel	Frequency (MHz)	Power Density		Max. Limits (dBm/3kHz)	Pass/Fail
		PSD/100kHz (dBm)	PSD/3kHz (dBm)		
00	2402	3.89	-9.80	8	Pass
19	2440	5.17	-8.51	8	Pass
39	2480	4.64	-9.05	8	Pass

**Note:**


1. Measured power density (dBm) has offset with cable loss.
2. The Measured power density (dBm)/ 100kHz is reference level and used as 20dBc down for Conducted Band Edges and Conducted Spurious Emission limit line.

### 3.3.6 Test Result of Power Spectral Density Plots (100kHz)

PSD 100kHz Plot on Channel 00




### PSD 100kHz Plot on Channel 19



Date: 16.APR.2014 18:13:25


### PSD 100kHz Plot on Channel 39



Date: 16.APR.2014 18:10:40


### 3.3.7 Test Result of Power Spectral Density Plots (3kHz)

PSD 3kHz Plot on Channel 00




Date: 16.APR.2014 18:15:50

PSD 3kHz Plot on Channel 19



Date: 16.APR.2014 18:13:17

### PSD 3kHz Plot on Channel 39



Date: 16.APR.2014 18:10:31

## 3.4 Conducted Band Edges and Spurious Emission Measurement

### 3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


### 3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.4.3 Test Procedure

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


### 3.4.4 Test Setup



### 3.4.5 Test Result of Conducted Band Edges


Test Mode :	Bluetooth 4.0 - LE	Temperature :	22~25°C
Test Channel :	00 and 39	Relative Humidity :	51~55%
		Test Engineer :	Bill Kuo and Stuart Lin

Low Band Edge Plot on Channel 00



Date: 16.APR.2014 18:16:13

High Band Edge Plot on Channel 39



Date: 16.APR.2014 18:10:53

Report No. : FR432436-09B

Report Version : Rev. 01

Page Number : 21 of 44


Report Template No.: BU5-FR15CBT4.0 Version 1.0

### 3.4.6 Test Result of Conducted Spurious Emission

Test Mode :	Bluetooth 4.0 - LE	Temperature :	22~25°C
Test Channel :	00	Relative Humidity :	51~55%
		Test Engineer :	Bill Kuo and Stuart Lin

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 00



Date: 16.APR.2014 18:16:32


Report No. : FR432436-09B

Report Version : Rev. 01

Page Number : 22 of 44

Report Template No.: BU5-FR15CBT4.0 Version 1.0

## Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00




Date: 16.APR.2014 18:16:50

<b>Test Mode :</b>	Bluetooth 4.0 - LE	<b>Temperature :</b>	22~25°C
<b>Test Channel :</b>	19	<b>Relative Humidity :</b>	51~55%
		<b>Test Engineer :</b>	Bill Kuo and Stuart Lin

### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

#### GFSK Channel 19



Date: 16.APR.2014 18:13:45


Report No. : FR432436-09B

Report Version : Rev. 01

Page Number : 24 of 44

Report Template No.: BU5-FR15CBT4.0 Version 1.0

## Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19



Date: 16.APR.2014 18:14:03

---

Report No. : FR432436-09B

Report Version : Rev. 01


Page Number : 25 of 44

Report Template No.: BU5-FR15CBT4.0 Version 1.0

<b>Test Mode :</b>	Bluetooth 4.0 - LE	<b>Temperature :</b>	22~25°C
<b>Test Channel :</b>	39	<b>Relative Humidity :</b>	51~55%
		<b>Test Engineer :</b>	Bill Kuo and Stuart Lin


### Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

#### GFSK Channel 39



Date: 16.APR.2014 18:11:12

## Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 16.APR.2014 18:11:31

---

Report No. : FR432436-09B

Report Version : Rev. 01

Page Number : 27 of 44

Report Template No.: BU5-FR15CBT4.0 Version 1.0

## 3.5 Radiated Band Edges and Spurious Emission Measurement

### 3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

### 3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.5.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak;  
Trace = max hold;
  - (3) Set RBW = 1 MHz, VBW= 3MHz for  $f \geq 1$  GHz for peak measurement.


For average measurement:

- VBW = 10 Hz, when duty cycle is no less than 98 percent.
- VBW  $\geq 1/T$ , when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


Band	Duty Cycle(%)	T(μs)	1/T(kHz)	VBW Setting
Bluetooth 4.0 - LE	62.66	396.00	2.53	3kHz

### 3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



### 3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

### 3.5.6 Test Result of Radiated Spurious at Band Edges

Test Mode :	Mode 1			Temperature :	22~24°C				
Test Channel :	00			Relative Humidity :	46~48%				
				Test Engineer :	Ivan Chiang and Kyle Jhuang				

ANTENNA POLARITY : HORIZONTAL										
Frequency ( MHz )	Level (dB $\mu$ V /m )	Over Limit ( dB )	Limit Line (dB $\mu$ V /m )	Read Level (dB $\mu$ V)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2354.55	53.74	-20.26	74	48.16	32.22	7.5	34.14	128	11	Peak
2368.95	42.77	-11.23	54	37.14	32.26	7.52	34.15	128	11	Average

ANTENNA POLARITY : VERTICAL										
Frequency ( MHz )	Level (dB $\mu$ V /m )	Over Limit ( dB )	Limit Line (dB $\mu$ V /m )	Read Level (dB $\mu$ V)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2352.75	53.71	-20.29	74	48.13	32.22	7.5	34.14	129	102	Peak
2383.26	42.86	-11.14	54	37.2	32.26	7.55	34.15	129	102	Average

Test Mode :	Mode 3			Temperature :	22~24°C				
Test Channel :	39			Relative Humidity :	46~48%				
				Test Engineer :	Ivan Chiang and Kyle Jhuang				

ANTENNA POLARITY : HORIZONTAL										
Frequency ( MHz )	Level (dB $\mu$ V /m )	Over Limit ( dB )	Limit Line (dB $\mu$ V /m )	Read Level (dB $\mu$ V)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2488.72	54.17	-19.83	74	48.18	32.5	7.71	34.22	122	8	Peak
2484.07	43.14	-10.86	54	37.18	32.47	7.71	34.22	122	8	Average

ANTENNA POLARITY : VERTICAL										
Frequency ( MHz )	Level (dB $\mu$ V /m )	Over Limit ( dB )	Limit Line (dB $\mu$ V /m )	Read Level (dB $\mu$ V)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2494.39	54.15	-19.85	74	48.18	32.5	7.71	34.24	100	110	Peak
2498.2	43	-11	54	37.03	32.5	7.71	34.24	100	110	Average

### 3.5.7 Test Result of Radiated Spurious Emission (30MHz ~ 10<sup>th</sup> Harmonic)

**Note:** Pre-scanned all test modes and only choose the worst case mode recorded in the test report for radiated spurious emission below 1GHz.

<b>Test Mode :</b>	Mode 1	<b>Temperature :</b>	22~24°C
<b>Test Channel :</b>	00	<b>Relative Humidity :</b>	46~48%
<b>Test Engineer :</b>	Ivan Chiang and Kyle Jhuang	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	1. 2402 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dB $\mu$ V/m )	Over Limit ( dB )	Limit Line ( dB $\mu$ V/m )	Read Level ( dB $\mu$ V )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2402	108.53	-	-	102.86	32.29	7.55	34.17	128	11	Average
2402	109.61	-	-	103.94	32.29	7.55	34.17	128	11	Peak
4803	42.17	-11.83	54	57.7	34.89	8.55	58.97	100	0	Peak

**Note:** Other harmonics are lower than background noise.

<b>Test Mode :</b>	Mode 1	<b>Temperature :</b>	22~24°C
<b>Test Channel :</b>	00	<b>Relative Humidity :</b>	46~48%
<b>Test Engineer :</b>	Ivan Chiang and Kyle Jhuang	<b>Polarization :</b>	Vertical
<b>Remark :</b>	1. 2402 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dB $\mu$ V/m )	Over Limit ( dB )	Limit Line ( dB $\mu$ V/m )	Read Level ( dB $\mu$ V )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2402	99.38	-	-	93.71	32.29	7.55	34.17	129	102	Average
2402	100.49	-	-	94.82	32.29	7.55	34.17	129	102	Peak
4803	47.75	-6.25	54	63.28	34.89	8.55	58.97	100	0	Peak

**Note:** Other harmonics are lower than background noise.

<b>Test Mode :</b>	Mode 2			<b>Temperature :</b>			22~24°C		
<b>Test Channel :</b>	19			<b>Relative Humidity :</b>			46~48%		
<b>Test Engineer :</b>	Ivan Chiang and Kyle Jhuang			<b>Polarization :</b>			Horizontal		
<b>Remark :</b>	1. 2440 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.								

Frequency ( MHz )	Level ( dB $\mu$ V/m )	Over Limit ( dB )	Limit Line ( dB $\mu$ V/m )	Read Level ( dB $\mu$ V )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2440	109.5	-	-	103.66	32.4	7.63	34.19	154	10	Average
2440	110.54	-	-	104.7	32.4	7.63	34.19	154	10	Peak
4881	42.96	-11.04	54	58.27	34.93	8.63	58.87	100	0	Peak
7320	43.46	-10.54	54	52.38	36.63	12.94	58.49	100	0	Peak

**Note:** Other harmonics are lower than background noise.

<b>Test Mode :</b>	Mode 2			<b>Temperature :</b>			22~24°C		
<b>Test Channel :</b>	19			<b>Relative Humidity :</b>			46~48%		
<b>Test Engineer :</b>	Ivan Chiang and Kyle Jhuang			<b>Polarization :</b>			Vertical		
<b>Remark :</b>	1. 2440 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.								

Frequency ( MHz )	Level ( dB $\mu$ V/m )	Over Limit ( dB )	Limit Line ( dB $\mu$ V/m )	Read Level ( dB $\mu$ V )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2440	100.61	-	-	94.77	32.4	7.63	34.19	186	98	Average
2440	101.67	-	-	95.83	32.4	7.63	34.19	186	98	Peak
4881	46.66	-7.34	54	61.97	34.93	8.63	58.87	100	0	Peak
7320	44.1	-9.9	54	53.02	36.63	12.94	58.49	100	0	Peak

**Note:** Other harmonics are lower than background noise.

<b>Test Mode :</b>	Mode 3	<b>Temperature :</b>	22~24°C
<b>Test Channel :</b>	39	<b>Relative Humidity :</b>	46~48%
<b>Test Engineer :</b>	Ivan Chiang and Kyle Jhuang	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	1. 2481 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dB $\mu$ V/m )	Over Limit ( dB )	Limit Line ( dB $\mu$ V/m )	Read Level ( dB $\mu$ V )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
89.4	27.76	-15.74	43.5	48.24	8.54	1.4	30.42	100	71	Peak
115.32	16.2	-27.3	43.5	33.22	11.8	1.58	30.4	-	-	Peak
243.57	14.69	-31.31	46	31	11.66	2.28	30.25	-	-	Peak
429.5	17.91	-28.09	46	28.32	16.5	3.03	29.94	-	-	Peak
549.9	19.31	-26.69	46	26.76	18.8	3.46	29.71	-	-	Peak
710.9	20.77	-25.23	46	27.38	18.92	3.94	29.47	-	-	Peak
2481	105	-	-	99.04	32.47	7.71	34.22	122	8	Average
2481	105.88	-	-	99.92	32.47	7.71	34.22	122	8	Peak
4961	43.53	-10.47	54	58.6	34.98	8.7	58.75	100	0	Peak
7440	43.62	-10.38	54	52.67	36.61	13.05	58.71	100	0	Peak

**Note:** Other harmonics are lower than background noise.

<b>Test Mode :</b>	Mode 3	<b>Temperature :</b>	22~24°C
<b>Test Channel :</b>	39	<b>Relative Humidity :</b>	46~48%
<b>Test Engineer :</b>	Ivan Chiang and Kyle Jhuang	<b>Polarization :</b>	Vertical
<b>Remark :</b>	1. 2480 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dB $\mu$ V/m )	Over Limit ( dB )	Limit Line ( dB $\mu$ V/m )	Read Level ( dB $\mu$ V )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
90.48	30.44	-13.06	43.5	50.75	8.7	1.41	30.42	100	185	Peak
111	22.02	-21.48	43.5	38.87	12	1.55	30.4	-	-	Peak
243.57	13.73	-32.27	46	30.04	11.66	2.28	30.25	-	-	Peak
577.9	19.67	-26.33	46	27.16	18.6	3.56	29.65	-	-	Peak
658.4	21.77	-24.23	46	28.59	18.91	3.8	29.53	-	-	Peak
793.5	22.05	-23.95	46	27.35	19.9	4.19	29.39	-	-	Peak
2480	96.39	-	90.43	32.47	7.71	34.22	100	110	Average	
2480	97.51	-	91.55	32.47	7.71	34.22	100	110	Peak	
4959	45.27	-8.73	54	60.34	34.98	8.7	58.75	100	0	Peak
7440	43.78	-10.22	54	52.83	36.61	13.05	58.71	100	0	Peak

**Note:** Other harmonics are lower than background noise.

## 3.6 AC Conducted Emission Measurement

### 3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


### 3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.6.3 Test Procedures


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

### 3.6.4 Test Setup



### 3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 2	Temperature :	20~22°C
Test Engineer :	Cosmo Xu	Relative Humidity :	46~48%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 (GPRS Class 8) Idle + WLAN (2.4GHz) Link + Earphone + HDMI Cable with Monitor + HDMI to uUSB Dongle + USB Cable (Charging from Adapter) + Camera (Front)		




#### Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.174000	46.7	Off	L1	19.3	18.1	64.8
0.214000	36.8	Off	L1	19.4	26.2	63.0
0.334000	32.9	Off	L1	19.4	26.5	59.4
0.854000	30.1	Off	L1	19.6	25.9	56.0
1.118000	30.3	Off	L1	19.5	25.7	56.0
4.070000	33.4	Off	L1	19.6	22.6	56.0

#### Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.174000	37.9	Off	L1	19.3	16.9	54.8
0.214000	22.3	Off	L1	19.4	30.7	53.0
0.334000	22.2	Off	L1	19.4	27.2	49.4
0.854000	18.8	Off	L1	19.6	27.2	46.0
1.118000	22.5	Off	L1	19.5	23.5	46.0
4.070000	24.8	Off	L1	19.6	21.2	46.0


<b>Test Mode :</b>	Mode 2	<b>Temperature :</b>	20~22°C
<b>Test Engineer :</b>	Cosmo Xu	<b>Relative Humidity :</b>	46~48%
<b>Test Voltage :</b>	120Vac / 60Hz	<b>Phase :</b>	Neutral
<b>Function Type :</b>	GSM850 (GPRS Class 8) Idle + WLAN (2.4GHz) Link + Earphone + HDMI Cable with Monitor + HDMI to uUSB Dongle + USB Cable (Charging from Adapter) + Camera (Front)		



#### Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dB $\mu$ V)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
1.230000	38.0	Off	N	19.5	18.0	56.0
1.382000	42.8	Off	N	19.5	13.2	56.0
1.462000	43.6	Off	N	19.6	12.4	56.0
1.574000	45.3	Off	N	19.5	10.7	56.0
1.622000	46.3	Off	N	19.5	9.7	56.0
1.822000	42.7	Off	N	19.6	13.3	56.0
1.950000	41.8	Off	N	19.5	14.2	56.0
2.078000	45.1	Off	N	19.5	10.9	56.0
2.206000	42.6	Off	N	19.6	13.4	56.0
2.334000	46.2	Off	N	19.5	9.8	56.0
2.438000	46.3	Off	N	19.6	9.7	56.0
2.566000	43.0	Off	N	19.5	13.0	56.0
2.854000	43.7	Off	N	19.6	12.3	56.0
2.926000	43.0	Off	N	19.5	13.0	56.0
3.182000	44.6	Off	N	19.6	11.4	56.0
3.310000	43.1	Off	N	19.6	12.9	56.0
3.574000	42.7	Off	N	19.6	13.3	56.0

<b>Test Mode :</b>	Mode 2	<b>Temperature :</b>	20~22°C
<b>Test Engineer :</b>	Cosmo Xu	<b>Relative Humidity :</b>	46~48%
<b>Test Voltage :</b>	120Vac / 60Hz	<b>Phase :</b>	Neutral
<b>Function Type :</b>	GSM850 (GPRS Class 8) Idle + WLAN (2.4GHz) Link + Earphone + HDMI Cable with Monitor + HDMI to uUSB Dongle + USB Cable (Charging from Adapter) + Camera (Front)		



**Final Result : Average**

Frequency (MHz)	Average (dB $\mu$ V)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
1.230000	32.4	Off	N	19.5	13.6	46.0
1.382000	36.3	Off	N	19.5	9.7	46.0
1.462000	37.1	Off	N	19.6	8.9	46.0
1.574000	39.9	Off	N	19.5	6.1	46.0
1.622000	40.9	Off	N	19.5	5.1	46.0
1.822000	34.5	Off	N	19.6	11.5	46.0
1.950000	36.1	Off	N	19.5	9.9	46.0
2.078000	37.7	Off	N	19.5	8.3	46.0
2.206000	37.4	Off	N	19.6	8.6	46.0
2.334000	34.7	Off	N	19.5	11.3	46.0
2.438000	32.8	Off	N	19.6	13.2	46.0
2.566000	31.8	Off	N	19.5	14.2	46.0
2.854000	36.1	Off	N	19.6	9.9	46.0
2.926000	38.7	Off	N	19.5	7.3	46.0
3.182000	40.3	Off	N	19.6	5.7	46.0
3.310000	39.2	Off	N	19.6	6.8	46.0
3.574000	40.6	Off	N	19.6	5.4	46.0

## **3.7 Antenna Requirements**

### **3.7.1 Standard Applicable**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

### **3.7.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.7.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Jun. 07, 2013	Apr. 15, 2014~Apr. 16, 2014	Jun. 06, 2014	Conducted (TH02-HY)
Power Meter	Agilent	E4416A	GB4129234 4	300MHz~40GHz	Jan. 28, 2014	Apr. 15, 2014~Apr. 16, 2014	Jan. 27, 2015	Conducted (TH02-HY)
Power Sensor	Agilent	E9327A	US4044154 8	300MHz~40GHz	Jan. 28, 2014	Apr. 15, 2014~Apr. 16, 2014	Jan. 27, 2015	Conducted (TH02-HY)
EMI Test Receiver	Rohde & Schwarz	ESU26	100472	20Hz – 26.5GHz	Jan. 15, 2014	May 01, 2014	Jan. 14, 2015	Radiation (03CH08-HY)
Bilog Antenna	Teseq GmbH	CBL6112D	35379	30MHz~2GHz	Oct. 10, 2013	May 01, 2014	Oct. 09, 2014	Radiation (03CH08-HY)
Horn Antenna	ESCO	3117	000143261	1GHz~18GHz	Jan. 16, 2014	May 01, 2014	Jan. 15, 2015	Radiation (03CH08-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA91702 51	BBHA91702 51	15GHz~40GHz	Oct. 03, 2013	May 01, 2014	Oct. 02, 2014	Radiation (03CH08-HY)
Amplifier	SONOMA	310N	187231	9kHz~1GHz	May 15, 2013	May 01, 2014	May 14, 2014	Radiation (03CH08-HY)
Preamplifier	MITEQ	AMF-7D-00 101800-30-10P	1590074	1GHz~18GHz	Jul. 09, 2013	May 01, 2014	Jul. 08, 2014	Radiation (03CH08-HY)
Pre Amplifier	Agilent	8449B	3008A0266 5	1GHz~26.5GHz	Sep. 04, 2013	May 01, 2014	Sep. 03, 2014	Radiation (03CH08-HY)
Turn Table	Chaintek	Chaintek 3000	N/A	0~360 Degree	N/A	May 01, 2014	N/A	Radiation (03CH08-HY)
Antenna Mast	MF	MFA520BS	N/A	1m~4m	N/A	May 01, 2014	N/A	Radiation (03CH08-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	860004/000 1	9 kHz~30 MHz	Jul. 03, 2012	May 01, 2014	Jul. 03, 2014	Radiation (03CH08-HY)
EMI Test Receiver	Rohde & Schwarz	ESCS 30	100356	9kHz ~ 2.75GHz	Nov. 15, 2013	Jul. 14, 2014	Nov. 14, 2014	Conduction (CO05-HY)
LISN (for auxiliary equipment)	Rohde & Schwarz	ENV216	100081	9kHz ~ 30MHz	Dec. 12, 2013	Jul. 14, 2014	Dec. 11, 2014	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz ~ 30MHz	Dec. 04, 2013	Jul. 14, 2014	Dec. 03, 2014	Conduction (CO05-HY)
AC Power Source	ChainTek	APC-1000 W	N/A	N/A	N/A	Jul. 14, 2014	N/A	Conduction (CO05-HY)

## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_{C(y)}$ )	2.26
---	------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_{C(y)}$ )	4.30
---	------