



FCC PART 27
FCC PART 22H, PART 24E
TEST REPORT

For

Sky Phone LLC

1348 Washington Av. Suite 350 Miami Beach Florida United States

FCC ID: 2ABOSSKYELITE60P

Report Type: Original Report	Product Type: Mobile Phone
Report Number: RSZ161128002-00D	
Report Date: 2017-01-22	
Oscar Ye	
Reviewed By: Engineer	
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
MEASUREMENT UNCERTAINTY.....	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
DESCRIPTION OF TEST CONFIGURATION	5
EQUIPMENT MODIFICATIONS	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
BLOCK DIAGRAM OF TEST SETUP	5
SUMMARY OF TEST RESULTS	6
TEST EQUIPMENT LIST	7
FCC §1.1307 & §2.1093 - RF EXPOSURE.....	9
APPLICABLE STANDARD	9
TEST RESULT	9
FCC §2.1047 - MODULATION CHARACTERISTIC	10
FCC § 2.1046, § 22.913 (A) & § 24.232 (C); §27.50(C) (D) (H) - RF OUTPUT POWER.....	11
APPLICABLE STANDARD	11
TEST PROCEDURE	11
TEST DATA	11
FCC §2.1049, §22.917, §22.905 & §24.238 & §27.53 - OCCUPIED BANDWIDTH	34
APPLICABLE STANDARD	34
TEST PROCEDURE	34
TEST DATA	34
FCC §2.1051, §22.917(A) & §24.238(A); §27.53 (H) (M) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS	82
APPLICABLE STANDARD	82
TEST PROCEDURE	82
TEST DATA	82
FCC § 2.1053; § 22.917 (A);§ 24.238 (A); §27.53 (H)(M) SPURIOUS RADIATED EMISSIONS	116
APPLICABLE STANDARD	116
TEST PROCEDURE	116
TEST DATA	116
FCC § 22.917 (A);§ 24.238 (A); §27.53 (H)(M) - BAND EDGES	120
APPLICABLE STANDARD	120
TEST PROCEDURE	120
TEST DATA	120
FCC § 2.1055; § 22.355; § 24.235; §27.54; - FREQUENCY STABILITY	170
APPLICABLE STANDARD	170
TEST PROCEDURE	170
TEST DATA	171

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Sky Phone LLC*'s product, model number: *Elite 6.0L+ (FCC ID: 2ABOSSKYELITE60P)* in this report is a *Mobile Phone* which was measured approximately: 16.59 cm (L) * 8.38 cm (W) * 0.96 cm (H), rated with input voltage: DC 3.8 V battery or DC 5.0V from adapter.

Adapter Information:

Model: Elite 6.0L+

Input: AC 100-240V, 50/60Hz, 0.3A

Output: DC 5.0V, 1.5A

** All measurement and test data in this report was gathered from production sample serial number: 1603766 (Assigned by BACL, Kunshan). The EUT supplied by the applicant was received on 2016-11-28.*

Objective

This test report is prepared on behalf of *Sky Phone LLC* in accordance with Part 2-Subpart J, Part 22-Subpart H and Part 24-Subpart E of the Federal Communication Commissions rules.

The objective is to determine the compliance of the EUT with FCC rules for output power, modulation characteristic, occupied bandwidth, and spurious emission at antenna terminal, spurious radiated emission, frequency stability and band edge.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DTS & DSS and Part 15B JBP submissions with FCC ID: 2ABOSSKYELITE60P.

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2-Subpart J as well as the following parts:

Part 22 Subpart H - Public Mobile Services

Part 24 Subpart E - Personal Communication Services

Part 27 – Miscellaneous wireless communications services

Applicable Standards: TIA/EIA 603-D, ANSI C63.4-2014.

All radiated and conducted emissions measurements were performed at Bay Area Compliance Laboratories Corp. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		± 3.26 dB
RF conducted test with spectrum		± 0.9 dB
RF Output Power with Power meter		± 0.5 dB
Radiated emission	30MHz~1GHz	± 5.91 dB
	Above 1G	± 4.92 dB
Occupied Bandwidth		± 0.5 kHz
Temperature		± 1.0 °C
Humidity		$\pm 6\%$

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Test site at Bay Area Compliance Laboratories Corp. (Kunshan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 06, 2014. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 815570. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The EUT was configured for testing according to TIA/EIA-603-D.
The final qualification test was performed with the EUT operating at normal mode.


Equipment Modifications

No modification was made to the EUT.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Rohde & Schwarz	Wideband Radio Communication Tester	CMW500	1201.002K50-116218-UY
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	110605

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307, §2.1093	RF Exposure (SAR)	Compliance
§2.1046; § 22.913 (a); § 24.232 (c); §27.50 (c) (d) (h)	RF Output Power	Compliance
§ 2.1047	Modulation Characteristics	Not Applicable
§ 2.1049; § 22.905; § 22.917; § 24.238; §27.53	Occupied Bandwidth	Compliance
§ 2.1051; § 22.917 (a); § 24.238 (a); §27.53 (h)(m)	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053; § 22.917 (a); § 24.238 (a); §27.53 (h)(m)	Field Strength of Spurious Radiation	Compliance
§ 22.917 (a); § 24.238 (a); §27.53 (h)(m)	Band Edge	Compliance
§ 2.1055; § 22.355; § 24.235; §27.54;	Frequency stability	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test					
Sonoma Instrument	Amplifier	330	171377	2016-12-12	2017-12-12
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2016-11-25	2017-11-25
Sunol Sciences	Broadband Antenna	JB3	A090314-2	2016-01-09	2019-01-08
Sunol Sciences	Broadband Antenna	JB3	A090314-1	2016-01-09	2019-01-08
Narda	Pre-amplifier	AFS42-00101800	2001270	2016-09-08	2017-09-08
EMCO	Horn Antenna	3116	00084159	2016-10-18	2019-10-17
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2016-11-25	2017-11-25
ETS	Horn Antenna	3115	6229	2016-01-11	2017-01-10
ETS	Horn Antenna	3115	9311-4159	2016-01-11	2017-01-10
R&S	Auto test Software	EMC32	V 09.10.0	NCR	NCR
haojintech	Coaxial Cable	Cable-1	001	2016-12-12	2017-12-12
haojintech	Coaxial Cable	Cable-2	002	2016-12-12	2017-12-12
haojintech	Coaxial Cable	Cable-3	003	2016-12-12	2017-12-12
MICRO-COAX	Coaxial Cable	Cable-4	004	2016-12-12	2017-12-12
MICRO-COAX	Coaxial Cable	Cable-5	005	2016-12-12	2017-12-12
MICRO-COAX	Coaxial Cable	Cable-7	007	2016-12-12	2017-12-12
HP	Signal Generator	8341B	2624A00116	2016-08-29	2017-08-29

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted test					
BACL	TS 8997 Cable-01	T-KS-EMC086	T-KS-EMC086	2015-12-10	2016-12-09
BACL	TS 8997 Cable-01	T-KS-EMC086	T-KS-EMC086	2016-12-09	2017-12-08
BACL	RF cable	KS-LAB-012	KS-LAB-012	2015-12-16	2016-12-15
BACL	RF cable	KS-LAB-012	KS-LAB-012	2016-12-15	2017-12-14
WEINSCHL	3dB Attenuator	5326	N/A	2016-06-18	2017-06-18
Rohde & Schwarz	OSP120 BASE UNIT	OSP120	101247	2016-07-04	2017-07-03
Rohde & Schwarz	Signal Analyzer	FSIQ26	836131/009	2016-09-21	2017-09-21
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	110605	2015-11-25	2016-11-25
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	110605	2016-11-25	2017-11-25
R&S	Wideband Radio Communication tester	CMW500	1201.002K50-116218-UY	2016-10-08	2017-10-08
HONOVA	Power Splitter	ZFRSC-14-S+	019411452	2016-06-12	2017-06-12
WEINSCHL	10dB Attenuator	5328	N/A	2016-06-18	2017-06-18

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1307 & §2.1093 - RF EXPOSURE

Applicable Standard

FCC§1.1310 and §2.1093.

Test Result

Compliance, please refer to the SAR report: RSZ161128002-20.

FCC §2.1047 - MODULATION CHARACTERISTIC

According to FCC § 2.1047(d), Part 22H, 24E & Part 27 there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

FCC § 2.1046, § 22.913 (a) & § 24.232 (c); §27.50(c) (d) (h) - RF OUTPUT POWER

Applicable Standard

According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC §2.1046 and §24.232 (c), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

According to §27.50(d), the maximum EIRP must not exceed 1Watts (30dBm) for 1710-1755MHz. The peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB.


According to §27.50(c), Portable stations (hand-held devices) in the 600 MHz uplink band and the 698-746 MHz band, and fixed and mobile stations in the 600 MHz uplink band are limited to 3 watts ERP.

According to §27.50(h), the maximum EIRP must not exceed 2Watts (33dBm) for 2500-2570MHz.

Test Procedure

Conducted method:

The RF output of the transmitter was connected to the CMW500/CMU200 through sufficient attenuation.



Radiated method:

TIA 603-D section 2.2.17

Test Data

Environmental Conditions

Temperature:	23 °C
Relative Humidity:	53 %
ATM Pressure:	101.5 kPa

The testing was performed by Echo Wu on 2016-12-12.

Conducted Power**Cellular Band (Part 22H)**

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)	Limit (dBm)
GSM	128	824.2	31.15	38.45
	190	836.6	31.25	38.45
	251	848.8	31.31	38.45

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
GPRS	128	824.2	31.15	30.52	28.88	27.75	38.45
	190	836.6	31.24	30.63	28.98	27.89	38.45
	251	848.8	31.32	30.70	29.08	27.99	38.45

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
EGPRS	128	824.2	25.97	24.89	22.66	21.51	38.45
	190	836.6	26.05	24.97	22.70	21.57	38.45
	251	848.8	26.01	25.02	22.83	21.65	38.45

Mode	Test Condition	Test Mode	3GPP Sub Test	Average Output Power (dBm)		
				Low Frequency	Middle Frequency	High Frequency
WCDMA (Band V)	Normal	RMC12.2k		22.44	22.48	22.44
		HSDPA	1	21.36	21.40	21.40
			2	21.28	21.30	21.34
			3	21.41	21.47	21.47
			4	21.26	21.27	21.30
		HSUPA	1	21.29	21.32	21.35
			2	21.23	21.23	21.31
			3	21.39	21.37	21.47
			4	21.17	21.23	21.30
			5	21.33	21.39	21.39
		HSPA+	1	21.30	21.26	21.37

PCS Band (Part 24E)

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)	Limit (dBm)
GSM	512	1850.2	28.83	33
	661	1880.0	28.82	33
	810	1909.8	28.85	33

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
GPRS	512	1850.2	28.85	28.14	26.54	25.48	33
	661	1880.0	28.86	28.14	26.57	25.45	33
	810	1909.8	28.85	28.14	26.56	25.46	33

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
EGPRS	512	1850.2	26.34	25.59	24.09	23.05	33
	661	1880.0	26.48	25.74	24.23	23.21	33
	810	1909.8	26.41	25.69	24.08	23.11	33

Mode	Test Condition	Test Mode	3GPP Sub Test	Average Output Power (dBm)		
				Low Frequency	Middle Frequency	High Frequency
WCDMA (Band II)	Normal	RMC12.2k		22.80	22.74	22.66
		HSDPA	1	21.67	21.77	21.57
			2	21.61	21.68	21.48
			3	21.72	21.84	21.69
			4	21.59	21.72	21.49
		HSUPA	1	21.64	21.74	21.42
			2	21.59	21.63	21.35
			3	21.76	21.82	21.46
			4	21.54	21.70	21.38
			5	21.67	21.84	21.49
		HSPA+	1	21.72	21.74	21.47

AWS Band (Part 27)

Mode	Test Condition	Test Mode	3GPP Sub Test	Average Output Power (dBm)		
				Low Frequency	Middle Frequency	High Frequency
WCDMA (Band IV)	Normal	RMC		22.54	22.51	22.61
		HSDPA	1	21.44	21.42	21.46
			2	21.33	21.37	21.37
			3	21.52	21.49	21.58
			4	21.39	21.34	21.34
		HSUPA	1	21.40	21.42	21.48
			2	21.32	21.35	21.42
			3	21.53	21.52	21.57
			4	21.29	21.35	21.40
			5	21.47	21.48	21.60
		HSPA+	1	21.40	21.39	21.53

Peak-to-average ratio (PAR)

Cellular Band

Mode	Channel	PAR (dB)	Limit (dB)
GSM	Low	0.48	13
	Middle	0.36	13
	High	0.43	13

Mode	Channel	PAR (dB)	Limit (dB)
EGPRS	Low	0.26	13
	Middle	0.41	13
	High	0.36	13

Mode	Channel	PAR (dB)	Limit (dB)
RMC (BPSK)	Low	3.25	13
	Middle	3.14	13
	High	3.27	13
HSDPA (16QAM)	Low	3.21	13
	Middle	3.17	13
	High	3.26	13
HSUPA (BPSK)	Low	3.24	13
	Middle	3.16	13
	High	3.28	13

PCS Band

Mode	Channel	PAR (dB)	Limit (dB)
GSM	Low	0.46	13
	Middle	0.32	13
	High	0.43	13

Mode	Channel	PAR (dB)	Limit (dB)
EGPRS	Low	0.56	13
	Middle	0.42	13
	High	0.55	13

Mode	Channel	PAR (dB)	Limit (dB)
RMC (BPSK)	Low	2.95	13
	Middle	2.80	13
	High	2.93	13
HSDPA (16QAM)	Low	2.97	13
	Middle	2.82	13
	High	2.94	13
HSUPA (BPSK)	Low	2.99	13
	Middle	2.83	13
	High	2.96	13

AWS Band

Mode	Channel	PAR (dB)	Limit (dB)
WCDMA (BPSK)	Low	3.02	13
	Middle	2.95	13
	High	3.05	13
HSDPA (16QAM)	Low	3.04	13
	Middle	2.92	13
	High	3.07	13
HSUPA (BPSK)	Low	3.08	13
	Middle	2.99	13
	High	3.03	13

Radiated Power**GSM Mode:**

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	FCC Part 22H/24E	
			Height (m)	Polar (H/V)	S.G. Level (dBm)	Cable loss (dB)	Antenna Gain (dB)		Limit (dBm)	Margin (dB)
ERP for Cellular Band (Part 22H), Middle Channel										
836.6	96.13	236	1.9	H	25.9	0.26	4.75	30.39	38.45	8.06
836.6	93.15	34	1.5	V	18.9	0.26	4.75	23.39	38.45	15.06
EIRP for PCS Band (Part 24E), Middle Channel										
1880.0	81.09	48	1.9	H	19.6	0.45	8.84	27.99	33	5.01
1880.0	81.12	147	1.2	V	17.4	0.45	8.84	25.79	33	7.21

EDGE Mode:

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)	S.G. Level (dBm)	Cable loss (dB)	Antenna Gain (dB)			
ERP, Cellular Band (Part 22H), Middle Channel										
836.6	90.83	136	1.7	H	20.6	0.26	4.75	25.09	38.45	13.36
836.6	89.55	178	1.8	V	15.3	0.26	4.75	19.79	38.45	18.66
EIRP, PCS Band (Part 24E), Middle Channel										
1880.0	76.99	268	2.2	H	15.5	0.45	8.84	23.89	33	9.11
1880.0	76.22	188	2.3	V	12.5	0.45	8.84	20.89	33	12.11

WCDMA Mode:

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	FCC Part 22H/24E/27	
			Height (m)	Polar (H/V)	S.G. Level (dBm)	Cable loss (dB)	Antenna Gain (dB)		Limit (dBm)	Margin (dB)
ERP for WCDMA Band V (Part 22H), Middle Channel										
836.6	91.06	148	1.7	H	16.4	0.26	4.75	20.89	38.45	17.56
836.6	88.23	245	1.5	V	12.5	0.26	4.75	16.99	38.45	21.46
EIRP for WCDMA Band II (Part 24E), Middle Channel										
1880.0	74.79	277	2.2	H	13.3	0.45	8.84	21.69	33	11.31
1880.0	73.32	156	2.1	V	9.6	0.45	8.84	17.99	33	15.01
EIRP for WCDMA Band IV (Part 27), Middle Channel										
1732.6	77.07	210	1.6	H	13.5	0.40	8.52	21.62	30	8.38
1732.6	74.54	273	1.0	V	9.0	0.40	8.52	17.12	30	12.88

Note:

All above data were tested with no amplifier.

Absolute Level = SG Level - Cable loss + Antenna Gain

Margin = Limit- Absolute Level

LTE Band 2**Maximum Output Power**

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4	QPSK	RB Size=1, RB Offset=0	23.02	23.30	23.07
		RB Size=1, RB Offset=2	22.90	23.23	22.97
		RB Size=1, RB Offset=5	23.09	23.39	23.17
		RB Size=3, RB Offset=0	22.54	22.78	22.48
		RB Size=3, RB Offset=1	22.45	22.68	22.41
		RB Size=3, RB Offset=2	22.59	22.90	22.59
		RB Size=6, RB Offset=0	21.84	22.26	21.92
	16QAM	RB Size=1, RB Offset=0	23.07	23.26	23.04
		RB Size=1, RB Offset=2	22.94	23.14	22.95
		RB Size=1, RB Offset=5	23.19	23.30	23.11
		RB Size=3, RB Offset=0	22.54	22.71	22.42
		RB Size=3, RB Offset=1	22.43	22.65	22.36
		RB Size=3, RB Offset=2	22.65	22.82	22.49
		RB Size=6, RB Offset=0	21.94	22.25	21.87
3.0	QPSK	RB Size=1, RB Offset=0	22.86	23.23	22.93
		RB Size=1, RB Offset=7	22.81	23.14	22.83
		RB Size=1, RB Offset=14	22.95	23.29	23.05
		RB Size=8, RB Offset=0	22.37	22.64	22.28
		RB Size=8, RB Offset=4	22.30	22.58	22.23
		RB Size=8, RB Offset=7	22.48	22.67	22.37
		RB Size=15, RB Offset=0	21.84	22.29	21.79
	16QAM	RB Size=1, RB Offset=0	22.86	23.23	22.79
		RB Size=1, RB Offset=7	22.77	23.17	22.75
		RB Size=1, RB Offset=14	22.92	23.33	22.87
		RB Size=8, RB Offset=0	22.34	22.79	22.35
		RB Size=8, RB Offset=4	22.25	22.75	22.25
		RB Size=8, RB Offset=7	22.38	22.91	22.45
		RB Size=15, RB Offset=0	21.75	22.29	21.84

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5.0	QPSK	RB Size=1, RB Offset=0	22.81	23.19	22.72
		RB Size=1, RB Offset=12	22.75	23.09	22.59
		RB Size=1, RB Offset=24	22.93	23.30	22.78
		RB Size=12, RB Offset=0	22.24	22.63	22.27
		RB Size=12, RB Offset=6	22.13	22.56	22.14
		RB Size=12, RB Offset=11	22.33	22.66	22.35
		RB Size=25, RB Offset=0	21.63	21.99	21.72
	16QAM	RB Size=1, RB Offset=0	22.89	23.27	22.94
		RB Size=1, RB Offset=12	22.86	23.18	22.84
		RB Size=1, RB Offset=24	22.94	23.31	23.04
		RB Size=12, RB Offset=0	22.36	22.69	22.42
		RB Size=12, RB Offset=6	22.24	22.59	22.35
		RB Size=12, RB Offset=11	22.46	22.72	22.47
		RB Size=25, RB Offset=0	21.78	22.22	21.86
10.0	QPSK	RB Size=1, RB Offset=0	22.94	23.29	22.98
		RB Size=1, RB Offset=24	22.86	23.25	22.88
		RB Size=1, RB Offset=49	23.02	23.41	23.03
		RB Size=25, RB Offset=0	22.42	22.79	22.48
		RB Size=25, RB Offset=12	22.32	22.68	22.41
		RB Size=25, RB Offset=24	22.46	22.85	22.54
		RB Size=50, RB Offset=0	22.15	22.37	22.09
	16QAM	RB Size=1, RB Offset=0	22.87	23.23	22.84
		RB Size=1, RB Offset=24	22.78	23.13	22.78
		RB Size=1, RB Offset=49	22.98	23.27	22.88
		RB Size=25, RB Offset=0	22.47	22.74	22.42
		RB Size=25, RB Offset=12	22.42	22.67	22.35
		RB Size=25, RB Offset=24	22.59	22.81	22.52
		RB Size=50, RB Offset=0	21.94	22.26	21.97

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
15.0	QPSK	RB Size=1, RB Offset=0	22.83	23.2	22.82
		RB Size=1, RB Offset=37	22.73	23.10	22.73
		RB Size=1, RB Offset=74	22.90	23.26	22.90
		RB Size=36, RB Offset=0	22.43	22.77	22.49
		RB Size=36, RB Offset=18	22.35	22.64	22.38
		RB Size=36, RB Offset=37	22.50	22.87	22.61
		RB Size=75, RB Offset=0	22.14	22.38	22.25
	16QAM	RB Size=1, RB Offset=0	22.88	23.24	22.85
		RB Size=1, RB Offset=37	22.84	23.17	22.79
		RB Size=1, RB Offset=74	22.97	23.27	22.89
		RB Size=36, RB Offset=0	22.57	22.82	22.62
		RB Size=36, RB Offset=18	22.51	22.76	22.57
		RB Size=36, RB Offset=37	22.68	22.85	22.68
		RB Size=75, RB Offset=0	22.15	22.38	22.27
20.0	QPSK	RB Size=1, RB Offset=0	22.95	23.29	22.97
		RB Size=1, RB Offset=49	22.88	23.18	22.91
		RB Size=1, RB Offset=99	23.04	23.36	23.07
		RB Size=50, RB Offset=0	22.53	22.87	22.67
		RB Size=50, RB Offset=24	22.44	22.83	22.58
		RB Size=50, RB Offset=49	22.62	22.91	22.74
		RB Size=100, RB Offset=0	22.28	22.39	22.17
	16QAM	RB Size=1, RB Offset=0	22.98	23.29	22.92
		RB Size=1, RB Offset=49	22.91	23.18	22.88
		RB Size=1, RB Offset=99	23.04	23.32	23.04
		RB Size=50, RB Offset=0	22.59	22.84	22.62
		RB Size=50, RB Offset=24	22.46	22.80	22.51
		RB Size=50, RB Offset=49	22.67	22.97	22.69
		RB Size=100, RB Offset=0	21.95	22.24	21.92

Peak-to-average ratio (PAR)

Modulation	Middle Channel (dB)	PAR Limit (dB)	Result
QPSK (1RB Size)	9.56	13	Pass
QPSK (100%RB Size)	8.86	13	Pass
16QAM (1RB Size)	10.28	13	Pass
16QAM (100%RB Size)	8.67	13	Pass

QPSK:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
1.4 MHz Bandwidth									
1880.00	76.73	151	2.5	H	15.3	0.45	8.84	23.69	33
1880.00	75.24	57	1.9	V	11.5	0.45	8.84	19.89	33
3 MHz Bandwidth									
1880.00	77.04	264	2.1	H	15.6	0.45	8.84	23.99	33
1880.00	74.81	225	2.1	V	11.1	0.45	8.84	19.49	33
5 MHz Bandwidth									
1880.00	76.99	146	2.3	H	15.5	0.45	8.84	23.89	33
1880.00	74.32	276	1.3	V	10.6	0.45	8.84	18.99	33
10 MHz Bandwidth									
1880.00	77.10	11	1.6	H	15.7	0.45	8.84	24.09	33
1880.00	74.80	339	2.3	V	11.0	0.45	8.84	19.39	33
15 MHz Bandwidth									
1880.00	78.29	101	1.9	H	16.8	0.45	8.84	25.19	33
1880.00	74.72	162	2.1	V	10.7	0.45	8.84	19.09	33
20 MHz Bandwidth									
1880.00	76.99	124	2.0	H	15.5	0.45	8.84	23.89	33
1880.00	73.72	6	1.7	V	10.0	0.45	8.84	18.39	33

16QAM:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
1.4 MHz Bandwidth									
1880.00	76.80	253	1.6	H	15.4	0.45	8.84	23.79	33
1880.00	75.19	244	1.3	V	11.4	0.45	8.84	19.79	33
3 MHz Bandwidth									
1880.00	77.01	296	2.4	H	15.6	0.45	8.84	23.99	33
1880.00	75.07	2	1.4	V	11.3	0.45	8.84	19.69	33
5 MHz Bandwidth									
1880.00	76.83	320	2.5	H	15.4	0.45	8.84	23.79	33
1880.00	74.03	137	2.3	V	10.3	0.45	8.84	18.69	33
10 MHz Bandwidth									
1880.00	77.29	39	1.3	H	15.8	0.45	8.84	24.19	33
1880.00	74.12	173	2.4	V	10.4	0.45	8.84	18.79	33
15 MHz Bandwidth									
1880.00	78.18	101	1.9	H	16.7	0.45	8.84	25.09	33
1880.00	74.79	162	2.1	V	11.0	0.45	8.84	19.39	33
20 MHz Bandwidth									
1880.00	77.09	153	1.6	H	15.6	0.45	8.84	23.99	33
1880.00	74.12	161	2.1	V	10.4	0.45	8.84	18.79	33

LTE Band 4:**Maximum Output Power**

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4	QPSK	RB Size=1, RB Offset=0	22.84	23.12	22.72
		RB Size=1, RB Offset=2	22.73	23.00	22.67
		RB Size=1, RB Offset=5	22.93	23.18	22.84
		RB Size=3, RB Offset=0	22.32	22.65	22.37
		RB Size=3, RB Offset=1	22.20	22.58	22.31
		RB Size=3, RB Offset=2	22.38	22.68	22.46
		RB Size=6, RB Offset=0	21.84	22.07	21.93
	16QAM	RB Size=1, RB Offset=0	22.72	23.12	22.77
		RB Size=1, RB Offset=2	22.60	23.03	22.73
		RB Size=1, RB Offset=5	22.78	23.20	22.88
		RB Size=3, RB Offset=0	22.37	22.61	22.34
		RB Size=3, RB Offset=1	22.31	22.54	22.21
		RB Size=3, RB Offset=2	22.47	22.67	22.41
		RB Size=6, RB Offset=0	21.82	22.05	21.87
3.0	QPSK	RB Size=1, RB Offset=0	22.78	23.11	22.75
		RB Size=1, RB Offset=7	22.71	23.03	22.69
		RB Size=1, RB Offset=14	22.83	23.18	22.84
		RB Size=8, RB Offset=0	22.33	22.67	22.42
		RB Size=8, RB Offset=4	22.24	22.61	22.32
		RB Size=8, RB Offset=7	22.45	22.74	22.47
		RB Size=15, RB Offset=0	21.83	22.14	21.92
	16QAM	RB Size=1, RB Offset=0	22.75	23.1	22.72
		RB Size=1, RB Offset=7	22.70	23.01	22.68
		RB Size=1, RB Offset=14	22.83	23.20	22.80
		RB Size=8, RB Offset=0	22.34	22.62	22.47
		RB Size=8, RB Offset=4	22.21	22.58	22.41
		RB Size=8, RB Offset=7	22.45	22.74	22.52
		RB Size=15, RB Offset=0	21.93	22.11	22.89

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5.0	QPSK	RB Size=1, RB Offset=0	22.79	23.17	22.76
		RB Size=1, RB Offset=12	22.74	23.09	22.65
		RB Size=1, RB Offset=24	22.86	23.20	22.81
		RB Size=12, RB Offset=0	22.38	22.65	22.42
		RB Size=12, RB Offset=6	22.29	22.57	22.33
		RB Size=12, RB Offset=11	22.46	22.73	22.49
		RB Size=25, RB Offset=0	21.89	22.01	22.39
	16QAM	RB Size=1, RB Offset=0	22.87	23.23	22.86
		RB Size=1, RB Offset=12	22.77	23.11	22.78
		RB Size=1, RB Offset=24	22.95	23.35	22.98
		RB Size=12, RB Offset=0	22.42	22.72	22.48
		RB Size=12, RB Offset=6	22.31	22.66	22.38
		RB Size=12, RB Offset=11	22.45	22.84	22.53
		RB Size=25, RB Offset=0	21.89	22.13	21.84
10.0	QPSK	RB Size=1, RB Offset=0	22.84	23.28	22.89
		RB Size=1, RB Offset=24	22.75	23.24	22.81
		RB Size=1, RB Offset=49	22.95	23.34	22.98
		RB Size=25, RB Offset=0	22.45	22.79	22.42
		RB Size=25, RB Offset=12	22.33	22.73	22.33
		RB Size=25, RB Offset=24	22.53	22.82	22.48
		RB Size=50, RB Offset=0	22.04	22.21	22.05
	16QAM	RB Size=1, RB Offset=0	22.86	23.2	22.87
		RB Size=1, RB Offset=24	22.74	23.13	22.77
		RB Size=1, RB Offset=49	22.96	23.30	22.98
		RB Size=25, RB Offset=0	22.42	22.63	22.47
		RB Size=25, RB Offset=12	22.31	22.59	22.34
		RB Size=25, RB Offset=24	22.52	22.75	22.54
		RB Size=50, RB Offset=0	21.85	22.13	21.92

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
15.0	QPSK	RB Size=1, RB Offset=0	22.82	23.24	22.83
		RB Size=1, RB Offset=37	22.71	23.14	22.71
		RB Size=1, RB Offset=74	22.91	23.33	22.90
		RB Size=36, RB Offset=0	22.48	22.69	22.41
		RB Size=36, RB Offset=18	22.40	22.62	22.32
		RB Size=36, RB Offset=37	22.56	22.74	22.52
		RB Size=75, RB Offset=0	21.92	22.25	21.86
	16QAM	RB Size=1, RB Offset=0	23.15	23.35	23.04
		RB Size=1, RB Offset=37	23.08	23.23	22.93
		RB Size=1, RB Offset=74	23.26	23.38	23.16
		RB Size=36, RB Offset=0	22.45	22.64	22.43
		RB Size=36, RB Offset=18	22.37	22.60	22.34
		RB Size=36, RB Offset=37	22.57	22.67	22.52
		RB Size=75, RB Offset=0	22.15	22.36	22.17
20.0	QPSK	RB Size=1, RB Offset=0	23.19	23.49	23.24
		RB Size=1, RB Offset=49	23.10	23.41	23.19
		RB Size=1, RB Offset=99	23.32	23.56	23.32
		RB Size=50, RB Offset=0	22.63	22.85	22.52
		RB Size=50, RB Offset=24	22.57	22.80	22.42
		RB Size=50, RB Offset=49	22.72	22.97	22.57
		RB Size=100, RB Offset=0	22.05	22.32	22.73
	16QAM	RB Size=1, RB Offset=0	23.12	23.35	23.05
		RB Size=1, RB Offset=49	23.06	23.29	23.01
		RB Size=1, RB Offset=99	23.25	23.43	23.09
		RB Size=50, RB Offset=0	22.51	22.73	22.48
		RB Size=50, RB Offset=24	22.45	22.68	22.38
		RB Size=50, RB Offset=49	22.63	22.84	22.58
		RB Size=100, RB Offset=0	21.83	22.14	22.92

Peak-to-average ratio (PAR)

Modulation	Middle Channel (dB)	PAR Limit (dB)	Result
QPSK (1RB Size)	9.66	13	Pass
QPSK (100%RB Size)	8.31	13	Pass
16QAM (1RB Size)	10.35	13	Pass
16QAM (100%RB Size)	8.82	13	Pass

QPSK:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
1.4 MHz Bandwidth									
1732.50	79.97	255	2.0	H	16.4	0.40	8.52	24.52	30
1732.50	73.94	262	2.3	V	8.4	0.40	8.52	16.52	30
3 MHz Bandwidth									
1732.50	79.87	209	1.0	H	16.3	0.40	8.52	24.42	30
1732.50	76.34	258	1.9	V	10.8	0.40	8.52	18.92	30
5 MHz Bandwidth									
1732.50	77.77	145	1.8	H	14.2	0.40	8.52	22.32	30
1732.50	76.83	1	1.2	V	11.3	0.40	8.52	19.42	30
10 MHz Bandwidth									
1732.50	79.97	360	2.1	H	16.4	0.40	8.52	24.52	30
1732.50	75.04	126	1.1	V	9.5	0.40	8.52	17.62	30
15 MHz Bandwidth									
1732.50	80.32	233	1.6	H	16.8	0.40	8.52	24.92	30
1732.50	76.16	52	1.9	V	10.6	0.40	8.52	18.72	30
20 MHz Bandwidth									
1732.50	81.37	245	1.1	H	17.8	0.40	8.52	25.92	30
1732.50	74.34	352	1.4	V	8.8	0.40	8.52	16.92	30

16QAM:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
1.4 MHz Bandwidth									
1732.50	79.69	246	1.1	H	16.1	0.40	8.52	24.22	30
1732.50	74.56	252	1.4	V	9.0	0.40	8.52	17.12	30
3 MHz Bandwidth									
1732.50	79.34	234	2.1	H	15.8	0.40	8.52	23.92	30
1732.50	75.24	317	1.9	V	9.7	0.40	8.52	17.82	30
5 MHz Bandwidth									
1732.50	78.19	245	2.3	H	14.6	0.40	8.52	22.72	30
1732.50	75.12	301	2.1	V	9.6	0.40	8.52	17.72	30
10 MHz Bandwidth									
1732.50	79.98	320	1.1	H	16.4	0.40	8.52	24.52	30
1732.50	74.93	142	1.8	V	9.4	0.40	8.52	17.52	30
15 MHz Bandwidth									
1732.50	79.76	302	2.1	H	16.2	0.40	8.52	24.32	30
1732.50	74.69	239	1.4	V	9.1	0.40	8.52	17.22	30
20 MHz Bandwidth									
1732.50	80.59	245	1.1	H	17.0	0.40	8.52	25.12	30
1732.50	74.56	352	1.4	V	9.0	0.40	8.52	17.12	30

LTE Band 7

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5	QPSK	RB Size=1, RB Offset=0	22.26	22.53	22.32
		RB Size=1, RB Offset=12	22.16	22.48	22.20
		RB Size=1, RB Offset=24	22.35	22.62	22.41
		RB Size=12, RB Offset=0	21.84	22.05	21.78
		RB Size=12, RB Offset=6	21.73	21.98	21.69
		RB Size=12, RB Offset=11	21.96	22.18	21.88
		RB Size=25, RB Offset=0	21.23	21.49	21.25
	16QAM	RB Size=1, RB Offset=0	22.22	22.55	22.27
		RB Size=1, RB Offset=12	22.11	22.48	22.19
		RB Size=1, RB Offset=24	22.35	22.66	22.30
		RB Size=12, RB Offset=0	21.89	22.14	21.82
		RB Size=12, RB Offset=6	21.82	22.07	21.70
		RB Size=12, RB Offset=11	21.97	22.17	21.91
		RB Size=25, RB Offset=0	21.32	21.52	21.27
10	QPSK	RB Size=1, RB Offset=0	22.24	22.57	22.26
		RB Size=1, RB Offset=24	22.19	22.48	22.22
		RB Size=1, RB Offset=49	22.31	22.68	22.39
		RB Size=25, RB Offset=0	21.82	22.19	21.87
		RB Size=25, RB Offset=12	21.76	22.10	21.82
		RB Size=25, RB Offset=24	21.89	22.30	21.90
		RB Size=50, RB Offset=0	21.24	21.68	21.37
	16QAM	RB Size=1, RB Offset=0	22.22	22.51	22.23
		RB Size=1, RB Offset=24	22.14	22.47	22.20
		RB Size=1, RB Offset=49	22.35	22.56	22.33
		RB Size=25, RB Offset=0	21.36	21.75	21.52
		RB Size=25, RB Offset=12	21.33	21.72	21.45
		RB Size=25, RB Offset=24	21.44	21.83	21.61
		RB Size=50, RB Offset=0	20.54	20.99	20.72

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
15	QPSK	RB Size=1, RB Offset=0	22.25	22.61	22.34
		RB Size=1, RB Offset=37	22.17	22.52	22.21
		RB Size=1, RB Offset=74	22.34	22.72	22.40
		RB Size=36, RB Offset=0	21.94	22.23	21.96
		RB Size=36, RB Offset=18	21.86	22.17	21.88
		RB Size=36, RB Offset=37	22.04	22.27	22.01
		RB Size=75, RB Offset=0	21.32	21.70	21.45
	16QAM	RB Size=1, RB Offset=0	22.28	22.64	22.37
		RB Size=1, RB Offset=37	22.22	22.51	22.32
		RB Size=1, RB Offset=74	22.40	22.72	22.46
		RB Size=36, RB Offset=0	21.96	22.28	21.99
		RB Size=36, RB Offset=18	21.90	22.24	21.91
		RB Size=36, RB Offset=37	22.00	22.37	22.06
		RB Size=75, RB Offset=0	21.42	21.76	21.38
20	QPSK	RB Size=1, RB Offset=0	22.34	22.76	22.32
		RB Size=1, RB Offset=49	22.24	22.65	22.29
		RB Size=1, RB Offset=99	22.41	22.83	22.38
		RB Size=50, RB Offset=0	21.92	22.22	21.95
		RB Size=50, RB Offset=24	21.84	22.19	21.85
		RB Size=50, RB Offset=49	22.04	22.28	22.03
		RB Size=100, RB Offset=0	21.35	21.74	21.53
	16QAM	RB Size=1, RB Offset=0	22.15	22.35	22.03
		RB Size=1, RB Offset=49	22.02	22.31	21.97
		RB Size=1, RB Offset=99	22.22	22.45	22.11
		RB Size=50, RB Offset=0	21.72	22.05	21.74
		RB Size=50, RB Offset=24	21.67	21.94	21.68
		RB Size=50, RB Offset=49	21.83	22.13	21.86
		RB Size=100, RB Offset=0	21.23	21.60	21.35

Peak-to-average ratio (PAR)

Modulation	Middle Channel (dB)	PAR Limit (dB)	Result
QPSK (1RB Size)	9.88	13	Pass
QPSK (100%RB Size)	9.57	13	Pass
16QAM (1RB Size)	10.43	13	Pass
16QAM (100%RB Size)	9.03	13	Pass

EIRP:**QPSK:**

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
5 MHz Bandwidth									
2535.0	74.86	247	1.6	H	12.3	0.49	10.10	21.91	33
2535.0	71.37	317	1.3	V	8.1	0.49	10.10	17.71	33
10 MHz Bandwidth									
2535.0	74.38	242	1.7	H	11.8	0.49	10.10	21.41	33
2535.0	70.91	309	1.5	V	7.7	0.49	10.10	17.31	33
15 MHz Bandwidth									
2535.0	73.79	17	2.1	H	11.2	0.49	10.10	20.81	33
2535.0	70.47	94	2.0	V	7.2	0.49	10.10	16.81	33
20 MHz Bandwidth									
2535.0	73.38	11	2.2	H	10.8	0.49	10.10	20.41	33
2535.0	69.85	304	2.4	V	6.6	0.49	10.10	16.21	33

16QAM:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
5 MHz Bandwidth									
2535.0	74.16	246	1.1	H	11.6	0.49	10.10	21.21	33
2535.0	71.77	252	1.4	V	8.5	0.49	10.10	18.11	33
10 MHz Bandwidth									
2535.0	73.84	234	2.1	H	11.3	0.49	10.10	20.91	33
2535.0	71.34	317	1.9	V	8.1	0.49	10.10	17.71	33
15 MHz Bandwidth									
2535.0	73.39	245	2.3	H	10.8	0.49	10.10	20.41	33
2535.0	70.92	301	2.1	V	7.7	0.49	10.10	17.31	33
20 MHz Bandwidth									
2535.0	73.06	320	1.1	H	10.5	0.49	10.10	20.11	33
2535.0	70.57	142	1.8	V	7.3	0.49	10.10	16.91	33

LTE Band 17:

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5.0	QPSK	RB Size=1, RB Offset=0	22.24	22.66	22.32
		RB Size=1, RB Offset=12	22.21	22.59	22.26
		RB Size=1, RB Offset=24	22.30	22.73	22.37
		RB Size=12, RB Offset=0	21.79	22.08	21.82
		RB Size=12, RB Offset=6	21.72	21.99	21.77
		RB Size=12, RB Offset=11	21.86	22.21	21.86
		RB Size=25, RB Offset=0	21.24	21.65	21.32
	16QAM	RB Size=1, RB Offset=0	22.36	22.66	22.37
		RB Size=1, RB Offset=12	22.24	22.58	22.26
		RB Size=1, RB Offset=24	22.46	22.79	22.47
		RB Size=12, RB Offset=0	21.72	22.03	21.76
		RB Size=12, RB Offset=6	21.65	21.91	21.65
		RB Size=12, RB Offset=11	21.79	22.13	21.80
		RB Size=25, RB Offset=0	21.35	21.67	21.23
10.0	QPSK	RB Size=1, RB Offset=0	22.32	22.64	22.33
		RB Size=1, RB Offset=24	22.24	22.59	22.27
		RB Size=1, RB Offset=49	22.35	22.73	22.45
		RB Size=25, RB Offset=0	21.78	22.07	21.79
		RB Size=25, RB Offset=12	21.67	21.96	21.66
		RB Size=25, RB Offset=24	21.84	22.13	21.85
		RB Size=50, RB Offset=0	21.34	21.73	21.24
	16QAM	RB Size=1, RB Offset=0	22.27	22.55	22.37
		RB Size=1, RB Offset=24	22.14	22.48	22.31
		RB Size=1, RB Offset=49	22.31	22.63	22.42
		RB Size=25, RB Offset=0	21.93	22.25	21.98
		RB Size=25, RB Offset=12	21.90	22.18	21.91
		RB Size=25, RB Offset=24	22.04	22.29	22.09
		RB Size=50, RB Offset=0	21.42	21.92	22.63

Peak-to-average ratio (PAR)

Modulation	Middle Channel (dB)	PAR Limit (dB)	Result
QPSK (1RB Size)	6.75	13	Pass
QPSK (100%RB Size)	8.13	13	Pass
16QAM (1RB Size)	6.27	13	Pass
16QAM (100%RB Size)	8.54	13	Pass

ERP:**QPSK:**

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
5 MHz Bandwidth									
710.00	95.70	236	1.6	H	17.4	0.26	4.25	21.39	34.77
710.00	88.46	116	1.7	V	13.2	0.26	4.25	17.19	34.77
10 MHz Bandwidth									
710.00	95.00	158	1.8	H	16.7	0.26	4.25	20.69	34.77
710.00	87.96	103	1.5	V	12.7	0.26	4.25	16.69	34.77

16QAM:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
5 MHz Bandwidth									
710.00	95.57	124	1.9	H	17.3	0.26	4.25	21.29	34.77
710.00	89.07	287	1.4	V	13.8	0.26	4.25	17.79	34.77
10 MHz Bandwidth									
710.00	95.10	116	1.7	H	16.8	0.26	4.25	20.79	34.77
710.00	87.56	158	1.4	V	12.3	0.26	4.25	16.29	34.77

Note:

All above data were tested with no amplifier

Absolute Level = SG Level - Cable loss + Antenna Gain

Margin = Limit- Absolute Level

FCC §2.1049, §22.917, §22.905 & §24.238 & §27.53 - OCCUPIED BANDWIDTH


Applicable Standard

FCC 47 §2.1049, §22.917, §22.905, §24.238 and §27.53.

Test Procedure

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 1% to 5% of the anticipated emission bandwidth and the 26 dB & 99% bandwidth was recorded.



Test Data

Environmental Conditions

Temperature:	23 °C
Relative Humidity:	47 %
ATM Pressure:	101.0 kPa

The testing was performed by Echo Wu on 2016-12-02.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to the following tables and plots.

Cellular Band (Part 22H)

Mode	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM(GMSK)	836.6	244.5	316.6
EGPRS(8PSK)	836.6	248.5	312.6

Mode	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
RMC (BPSK)	836.6	4.188	4.850
HSUPA (BPSK)	836.6	4.208	4.890
HSDPA (16QAM)	836.6	4.228	4.870

PCS Band (Part 24E)

Mode	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM(GMSK)	1880.0	248.5	312.6
EGPRS(8PSK)	1880.0	260.5	328.7


Mode	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
RMC (BPSK)	1880.0	4.208	4.890
HSUPA (BPSK)	1880.0	4.208	4.890
HSDPA (16QAM)	1880.0	4.228	4.870

AWS Band (Part 27)


Mode	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
RMC (BPSK)	1732.6	4.208	4.890
HSUPA (BPSK)	1732.6	4.208	4.910
HSDPA (16QAM)	1732.6	4.208	4.910



Cellular Band (Part 22H)

26 dB Emissions & 99% Occupied Bandwidth for GSM (GMSK) Mode




26 dB Emissions & 99% Occupied Bandwidth for EDGE Mode




26 dB Emissions & 99% Occupied Bandwidth for RMC (BPSK) Mode**26 dB Emissions & 99% Occupied Bandwidth for HSUPA (BPSK) Mode**

26 dB Emissions & 99% Occupied Bandwidth for HSDPA (16QAM) Mode




PCS Band (Part 24E)


26 dB Emissions & 99% Occupied Bandwidth for GSM (GMSK) Mode





26 dB Emissions & 99% Occupied Bandwidth for EDGE Mode




26 dB Emissions & 99% Occupied Bandwidth for RMC (BPSK) Mode




26 dB Emissions & 99% Occupied Bandwidth for HSUPA (BPSK) Mode**26 dB Emissions & 99% Occupied Bandwidth for HSDPA (16QAM) Mode**

AWS Band (Part 27)


26 dB Emissions Bandwidth & 99% Occupied Bandwidth for RMC (BPSK) Mode



26 dB Emissions Bandwidth & 99% Occupied Bandwidth for HSUPA (BPSK) Mode







26 dB Emissions Bandwidth & 99% Occupied Bandwidth for HSDPA (16QAM) Mode





LTE Band 2: (Middle Channel)


Bandwidth (MHz)	Modulation	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
1.4	QPSK	1.100	1.279
	16QAM	1.105	1.274
3.0	QPSK	2.693	2.922
	16QAM	2.693	2.934
5.0	QPSK	4.529	5.090
	16QAM	4.529	5.070
10.0	QPSK	8.978	9.780
	16QAM	8.978	9.699
15.0	QPSK	13.527	14.910
	16QAM	13.527	14.970
20.0	QPSK	17.956	19.319
	16QAM	17.956	19.238

QPSK (1.4 MHz) - 99% Occupied Bandwidth, Middle channel**QPSK (1.4 MHz) - 26 dB Bandwidth, Middle channel**


16-QAM (1.4 MHz) - 99% Occupied Bandwidth, Middle channel**16-QAM (1.4 MHz) - 26 dB Bandwidth, Middle channel**



QPSK (3.0 MHz) - 99% Occupied Bandwidth, Middle channel**QPSK (3.0 MHz) - 26 dB Bandwidth, Middle channel**



16-QAM (3.0 MHz) - 99% Occupied Bandwidth, Middle channel





16-QAM (3.0 MHz) - 26 dB Bandwidth, Middle channel







16-QAM (5.0 MHz) - 99% Occupied Bandwidth, Middle channel**16-QAM (5.0 MHz) - 26 dB Bandwidth, Middle channel**

QPSK (10.0 MHz) - 99% Occupied Bandwidth, Middle channel**QPSK (10.0 MHz) - 26 dB Bandwidth, Middle channel**


16-QAM (10.0 MHz) - 99% Occupied Bandwidth, Middle channel




16-QAM (10.0 MHz) - 26 dB Bandwidth, Middle channel



QPSK (15.0 MHz) - 99% Occupied Bandwidth, Middle channel



QPSK (15.0 MHz) - 26 dB Bandwidth, Middle channel



Ref Lvl 34 dBm
 Marker 1 [T1] 16.09 dBm
 1.87720441 GHz
 RBW 300 kHz
 VBW 1 MHz
 SWT 5 ms
 RF Att 30 dB
 Unit dBm

Marker	Frequency (GHz)	Power (dBm)
1	1.87720441	16.09
2	1.877205411	13.43
3	1.87323647	16.97
4	1.88676353	13.43

Center 1.88 GHz
 Span 30 MHz
 3 MHz/

Date: 30.NOV.2016 08:27:27

Ref Lvl 34 dBm

Marker 1 [T1 ndB] 26.00 dB

RBW 300 kHz

VBW 1 MHz

RF Att 30 dB

BW 14.96993988 MHz

SWT 5 ms

Unit dBm

14 dB Offset

1 [T1] 16.40 dBm

1.88273547 GHz

26.00 dB

14.96993988 MHz

-8.44 dBm

1.87251503 GHz

-8.99 dBm

1.88748497 GHz

1MAX



1MA



Center 1.88 GHz

3 MHz/

Span 30 MHz



Date: 30.NOV.2016 09:38:05

QPSK (20.0 MHz) - 99% Occupied Bandwidth, Middle channel**QPSK (20.0 MHz) - 26 dB Bandwidth, Middle channel**

16-QAM (20.0 MHz) - 99% Occupied Bandwidth, Middle channel**16-QAM (20.0 MHz) - 26 dB Bandwidth, Middle channel**

LTE Band 4: (Middle Channel)

Bandwidth (MHz)	Modulation	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
1.4	QPSK	1.094	1.274
	16QAM	1.100	1.268
3.0	QPSK	2.681	2.934
	16QAM	2.693	2.934
5.0	QPSK	4.529	5.050
	16QAM	4.529	5.030
10.0	QPSK	8.978	9.659
	16QAM	8.978	9.619
15.0	QPSK	13.587	14.970
	16QAM	13.527	14.790
20.0	QPSK	17.956	19.319
	16QAM	17.956	19.319

QPSK (1.4 MHz) - 99% Occupied Bandwidth, Middle channel**QPSK (1.4 MHz) - 26 dB Bandwidth, Middle channel**

[illegible]

Ref Lvl 34 dBm

Marker 1 [T1 ndB] 26.00 dB

RBW 30 kHz RF Att 30 dB

VBW 100 kHz

SWT 8 ms Unit dBm

14 dB Offset

15.72 dBm

1.73287876 GHz

26.00 dB

1.26813627 MHz

-16.38 dBm

1.73186874 GHz

-9.78 dBm

1.73313687 GHz

1MAX

1 [T1]

1 BW

T1

T2

Center 1.7325 GHz

280 kHz/

Span 2.8 MHz

Date: 30.NOV.2016 09:47:26

Ref Lvl 34 dBm

Marker 1 [T1] 13.13 dBm

1.73165230 GHz

RBW 30 kHz

VBW 100 kHz

RF Att 30 dB

SWT 17 ms

Unit dBm

14 dB Offset

OP8

1 13.13 dBm

1.73165230 GHz

2 6.06 dBm

1.73385271 GHz

Center 1.7325 GHz

600 kHz/

Span 6 MHz

Date: 30.NOV.2016 08:37:20

Ref Lvl 34 dBm

Marker 1 [T1 ndB] 26.00 dB

RBW 30 kHz RF Att 30 dB

VBW 100 kHz

SWT 17 ms Unit dBm

14 dB Offset

1

2

1MAX



1MA



Center 1.7325 GHz



600 kHz/



Span 6 MHz



Date: 30.NOV.2016 09:44:41



16-QAM (3.0 MHz) - 99% Occupied Bandwidth, Middle channel**16-QAM (3.0 MHz) - 26 dB Bandwidth, Middle channel**



QPSK (5.0 MHz) - 99% Occupied Bandwidth, Middle channel**QPSK (5.0 MHz) - 26 dB Bandwidth, Middle channel**

16-QAM (5.0 MHz) - 99% Occupied Bandwidth, Middle channel**16-QAM (5.0 MHz) - 26 dB Bandwidth, Middle channel**

QPSK (10.0 MHz) - 99% Occupied Bandwidth, Middle channel**QPSK (10.0 MHz) - 26 dB Bandwidth, Middle channel**

16-QAM (10.0 MHz) - 99% Occupied Bandwidth, Middle channel**16-QAM (10.0 MHz) - 26 dB Bandwidth, Middle channel**





Ref Lvl 34 dBm
 34 dBm
 Marker 1 [T1] 13.99 dBm
 1.73294088 GHz
 RBW 300 kHz
 VBW 1 MHz
 RF Att 30 dB
 Unit dBm
 5 ms
 1.7325 GHz
 4 MHz/
 Span 40 MHz
 Date: 30.NOV.2016 08:35:50

Ref Lvl 34 dBm

Marker 1 [T1 ndB] 26.00 dB

RBW 300 kHz RF Att 30 dB

VBW 1 MHz

SWT 5 ms Unit dBm

14 dB Offset

13.52 dBm

1.72636774 GHz

ndB 26.00 dB

BW 19.31863727 MHz

T1 [T1] -13.43 dBm

T2 [T1] -12.39 dBm

1.72284068 GHz

1.74215932 GHz

1MA


Center 1.7325 GHz

4 MHz/


Span 40 MHz

Date: 30.NOV.2016 09:46:11

16-QAM (20.0 MHz) - 99% Occupied Bandwidth, Middle channel






16-QAM (20.0 MHz) - 26 dB Bandwidth, Middle channel







LTE BAND 7:

Bandwidth (MHz)	Modulation	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
5.0	QPSK	4.549	5.030
	16QAM	4.529	5.050
10.0	QPSK	8.938	9.659
	16QAM	8.978	9.780
15.0	QPSK	13.527	14.850
	16QAM	13.527	14.970
20.0	QPSK	17.956	19.479
	16QAM	17.956	19.559

QPSK (5 MHz) - 99% Occupied Bandwidth, Middle channel

QPSK (5 MHz) - 26 dB Bandwidth, Middle channel**16-QAM (5 MHz) - 99% Occupied Bandwidth, Middle channel**

16-QAM (5MHz) - 26 dB Bandwidth, Middle channel**QPSK (10 MHz) - 99% Occupied Bandwidth, Middle channel**

QPSK (10 MHz) - 26 dB Bandwidth, Middle channel**16-QAM (10MHz) - 99% Occupied Bandwidth, Middle channel**

Ref Lvl 34 dBm

Marker 1 [T1 ndB]

ndB 26.00 dB

BW 14.84969940 MHz

RBW 300 kHz

VBW 1 MHz

SWT 5 ms

RF Att 30 dB

Unit dBm

14 dB Offset

1 14.22 dBm

2.52949900 GHz

26.00 dB

34.84969940 MHz

-16.99 dBm

2.52757515 GHz

-12.51 dBm

2.54242485 GHz

1MAX

1MA

Center 2.535 GHz

3 MHz/

Span 30 MHz

Date: 30.NOV.2016 09:07:20

Ref Lvl 34 dBm

Marker 1 [T1] 14.87 dBm

2.53304609 GHz

RBW 300 kHz RF Att 30 dB

VBW 1 MHz

SWT 5 ms Unit dBm

14 dB Offset

1 [T1] 14.87 dBm

2.53304609 GHz

OPB 13.52705411 MHz

1 [T1] 9.03 dBm

2.52823647 GHz

1 [T1] 9.09 dBm



2.54176353 GHz



1MAX

1MA


Center 2.535 GHz 3 MHz/ Span 30 MHz

Date: 30.NOV.2016 08:47:55

16-QAM (15 MHz) - 26 dB Bandwidth, Middle channel**QPSK (20 MHz) - 99% Occupied Bandwidth, Middle channel**



QPSK (20 MHz) - 26 dB Bandwidth, Middle channel**16-QAM (20 MHz) - 99% Occupied Bandwidth, Middle channel**

16-QAM (20 MHz) - 26 dB Bandwidth, Middle channel




LTE Band 17: (Middle Channel)


Bandwidth (MHz)	Modulation	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
5.0	QPSK	4.549	5.050
	16QAM	4.549	5.050
10.0	QPSK	9.018	9.619
	16QAM	9.018	9.739

QPSK (5.0 MHz) - 99% Occupied Bandwidth, Middle channel**QPSK (5.0 MHz) - 26 dB Bandwidth, Middle channel**


16-QAM (5.0 MHz) - 99% Occupied Bandwidth, Middle channel




16-QAM (5.0 MHz) - 26 dB Bandwidth, Middle channel





QPSK (10.0 MHz) - 99% Occupied Bandwidth, Middle channel



QPSK (10.0 MHz) - 26 dB Bandwidth, Middle channel



16-QAM (10.0 MHz) - 99% Occupied Bandwidth, Middle channel**16-QAM (10.0 MHz) - 26 dB Bandwidth, Middle channel**

FCC §2.1051, §22.917(a) & §24.238(a); §27.53 (h) (m) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS


Applicable Standard

FCC §2.1051, §22.917(a) and §24.238(a) and §27.53(h) (m).

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1051.

Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 1MHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.



Test Data

Environmental Conditions

Temperature:	23~24 °C
Relative Humidity:	44~53 %
ATM Pressure:	100.0~101.5 kPa


The testing was performed by Echo Wu on 2016-12-02 and 2016-12-28

EUT operation mode: Transmitting


Test result: Compliance, please refer to the following plots.



Cellular Band (Part 22H)

30 MHz – 1 GHz (GSM Mode)




1 GHz – 10 GHz (GSM Mode)




30 MHz – 1 GHz (WCDMA Mode)**1 GHz – 10 GHz (WCDMA Mode)**

PCS Band (Part 24E)


30 MHz – 1 GHz (GSM Mode)




1 GHz – 2 GHz (GSM Mode)




2 GHz – 20 GHz (GSM Mode)




30 MHz – 1 GHz (WCDMA Mode)



1 GHz – 2 GHz (WCDMA Mode)




2 GHz – 20 GHz (WCDMA Mode)




AWS Band (Part 27)


30 MHz – 1 GHz (WCDMA Mode)



1 GHz – 2 GHz (WCDMA Mode)




2 GHz – 20 GHz (WCDMA Mode)






LTE Band 2:

30 MHz - 1 GHz (1.4 MHz, Middle Channel)




1 GHz - 2 GHz (1.4 MHz, Middle Channel)




2 GHz – 20 GHz (1.4 MHz, Middle Channel)**30 MHz - 1 GHz (3.0 MHz, Middle Channel)**


1 GHz – 2 GHz (3.0 MHz, Middle Channel)




2 GHz – 20 GHz (3.0 MHz, Middle Channel)




30 MHz - 1 GHz (5.0 MHz, Middle Channel)




1 GHz - 2 GHz (5.0 MHz, Middle Channel)




2 GHz – 20 GHz (5.0 MHz, Middle Channel)




30 MHz - 1 GHz (10.0 MHz, Middle Channel)




1 GHz – 2 GHz (10.0 MHz, Middle Channel)




2 GHz – 20 GHz (10.0 MHz, Middle Channel)




30 MHz - 1 GHz (15.0 MHz, Middle Channel)




1 GHz – 2 GHz (15.0 MHz, Middle Channel)




2 GHz – 20 GHz (15.0 MHz, Middle Channel)




30 MHz - 1 GHz (20.0 MHz, Middle Channel)



1 GHz – 2 GHz (20.0 MHz, Middle Channel)




2 GHz – 20 GHz (20.0 MHz, Middle Channel)




LTE Band 4:


30 MHz - 1 GHz (1.4 MHz, Middle Channel)




1 GHz - 2 GHz (1.4 MHz, Middle Channel)




2 GHz – 20 GHz (1.4 MHz, Middle Channel)




30 MHz - 1 GHz (3.0 MHz, Middle Channel)




1 GHz – 2 GHz (3.0 MHz, Middle Channel)




2 GHz – 20 GHz (3.0 MHz, Middle Channel)




30 MHz - 1 GHz (5.0 MHz, Middle Channel)




1 GHz - 2 GHz (5.0 MHz, Middle Channel)




2 GHz – 20 GHz (5.0 MHz, Middle Channel)




30 MHz - 1 GHz (10.0 MHz, Middle Channel)




1 GHz – 2 GHz (10.0 MHz, Middle Channel)




2 GHz – 20 GHz (10.0 MHz, Middle Channel)




30 MHz - 1 GHz (15.0 MHz, Middle Channel)




1 GHz - 2 GHz (15.0 MHz, Middle Channel)




2 GHz – 20 GHz (15.0 MHz, Middle Channel)




30 MHz - 1 GHz (20.0 MHz, Middle Channel)




1 GHz – 2 GHz (20.0 MHz, Middle Channel)




2 GHz – 20 GHz (20.0 MHz, Middle Channel)




LTE Band 7:**30 MHz – 1 GHz (5.0 MHz, Middle Channel)****1 GHz – 3.0 GHz (5.0 MHz, Middle Channel)**


3.0 GHz – 26 GHz (5.0 MHz, Middle Channel)



30 MHz – 1.0 GHz (10.0 MHz, Middle Channel)



1 GHz – 3 GHz (10.0 MHz, Middle Channel)




3 GHz – 26 GHz (10.0 MHz, Middle Channel)




30 MHz – 1 GHz (15.0 MHz, Middle Channel)




1 GHz – 3 GHz (15.0 MHz, Middle Channel)




3 GHz – 26 GHz (15.0 MHz, Middle Channel)




30 MHz – 1 GHz (20.0 MHz, Middle Channel)



1 GHz – 3 GHz (20.0 MHz, Middle Channel)




3 GHz – 26 GHz (20.0 MHz, Middle Channel)



LTE Band 17:


30 MHz - 1 GHz (5.0 MHz, Middle Channel)




1 GHz - 10 GHz (5.0 MHz, Middle Channel)



30 MHz - 1 GHz (10.0 MHz, Middle Channel)



1 GHz - 10 GHz (10.0 MHz, Middle Channel)



FCC § 2.1053; § 22.917 (a); § 24.238 (a); § 27.53 (h)(m) SPURIOUS RADIATED EMISSIONS**Applicable Standard**

FCC § 2.1053, § 22.917(a) and § 24.238(a) and § 27.53(h)(m)

For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the receiving antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = $10 \lg (\text{TX pwr in Watts}/0.001)$ – the absolute level

Spurious attenuation limit in dB = $43 + 10 \log_{10} (\text{power out in Watts})$

Spurious attenuation limit in dB = $55 + 10 \log_{10} (\text{power out in Watts})$

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	46 %
ATM Pressure:	101.0 kPa

The testing was performed by Layne Li on 2016-12-16

EUT operation mode: Transmitting

Pre-scan with Low, Middle and High channel, the worst case as below:

30 MHz ~ 10 GHz:

Cellular Band (Part 22H)

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)			
GSM Mode, Middle channel										
172.24	46.75	308	1.9	H	-61.3	0.14	2.05	-59.39	-13	46.39
172.24	45.99	348	1.5	V	-62.5	0.14	2.05	-60.59	-13	47.59
1673.20	54.70	271	2.1	H	-47.1	0.40	8.52	-38.98	-13	25.98
1673.20	51.57	182	2.3	V	-52.2	0.40	8.52	-44.08	-13	31.08
WCDMA Mode, Middle channel										
172.24	46.65	344	2.2	H	-61.4	0.14	2.05	-59.49	-13	46.49
172.24	45.99	307	2.3	V	-62.5	0.14	2.05	-60.59	-13	47.59
1673.20	53.60	204	1.9	H	-48.2	0.40	8.52	-40.08	-13	27.08
1673.20	51.67	266	2.1	V	-52.1	0.40	8.52	-43.98	-13	30.98

30 MHz ~ 20 GHz:**PCS Band (Part 24E)**

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)			
GSM Mode, Middle channel										
172.24	46.35	111	1.1	H	-61.7	0.14	2.05	-59.79	-13	46.79
172.24	45.69	42	1.6	V	-62.8	0.14	2.05	-60.89	-13	47.89
3760	53.22	288	1.0	H	-42.8	0.59	9.72	-33.67	-13	20.67
3760	53.61	120	2.1	V	-43.5	0.59	9.72	-34.37	-13	21.37
WCDMA Mode, Middle channel										
172.24	46.45	6	2.4	H	-61.6	0.14	2.05	-59.69	-13	46.69
172.24	45.79	65	1.9	V	-62.7	0.14	2.05	-60.79	-13	47.79
3760	43.62	259	1.3	H	-52.4	0.59	9.72	-43.27	-13	30.27
3760	44.81	109	1.6	V	-52.3	0.59	9.72	-43.17	-13	30.17

30 MHz ~ 18 GHz:**AWS Band (Part 27)**

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)			
WCDMA Mode										
172.24	47.25	290	2.0	H	-60.8	0.14	2.05	-58.89	-13	45.89
172.24	45.59	39	1.6	V	-62.9	0.14	2.05	-60.99	-13	47.99
3465	45.33	356	2.4	H	-51.7	0.54	9.90	-42.34	-13	29.34
3465	45.83	267	2.2	V	-52.5	0.54	9.90	-43.14	-13	30.14

LTE Band:

Test mode: Transmitting (Pre-scan with all the bandwidth, and worse case as below)

Frequency	Receiver	Turntable	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
(MHz)	Reading (dBμV)	Angle Degree	Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)			
Band 2										
Test frequency range:30 MHz ~ 20 GHz										
172.24	46.88	348	2.3	H	-61.2	0.14	2.05	-59.29	-13	46.29
172.24	45.82	319	2.3	V	-62.7	0.14	2.05	-60.79	-13	47.79
3760.00	41.32	22	2.3	H	-54.7	0.59	9.72	-45.57	-13	32.57
3760.00	43.91	122	2.1	V	-53.2	0.59	9.72	-44.07	-13	31.07
Band 4										
Test frequency range:30 MHz ~ 20 GHz										
172.24	46.48	50	2.3	H	-61.6	0.14	2.05	-59.69	-13	46.69
172.24	45.62	250	1.4	V	-62.9	0.14	2.05	-60.99	-13	47.99
3465.00	41.53	1	2.5	H	-55.5	0.54	9.90	-46.14	-13	33.14
3465.00	44.03	263	1.3	V	-54.3	0.54	9.90	-44.94	-13	31.94
Band 7										
Test frequency range: 30 MHz ~ 26 GHz										
172.24	41.57	175	2.2	H	-61.8	0.14	2.05	-59.89	-25	34.89
172.24	41.30	289	1.4	V	-62.9	0.14	2.05	-60.99	-25	35.99
5070.00	41.74	244	1.8	H	-51.4	0.64	10.30	-41.74	-25	16.74
5070.00	44.07	124	1.0	V	-50.6	0.64	10.30	-40.94	-25	15.94
Band 17										
Test frequency range: 30 MHz ~ 10GHz										
172.24	46.48	47	1.9	H	-61.6	0.14	2.05	-59.69	-13	46.69
172.24	45.92	314	1.1	V	-62.6	0.14	2.05	-60.69	-13	47.69
1420.00	41.57	178	1.5	H	-62.5	0.34	7.92	-54.92	-13	41.92
1420.00	41.30	215	1.9	V	-64.5	0.34	7.92	-56.92	-13	43.92

Note:

- 1) Absolute Level = SG Level - Cable loss + Antenna Gain
- 2) Margin = Limit- Absolute Level

FCC § 22.917 (a); § 24.238 (a); § 27.53 (h)(m) - BAND EDGES**Applicable Standard**

According to § 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to § 24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.


According to FCC § 27.53 (h)(m), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log(P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log(P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log(P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log(P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log(P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency

**Test Data****Environmental Conditions**


Temperature:	23 °C
Relative Humidity:	53 %
ATM Pressure:	101.5 kPa

The testing was performed by Echo Wu on 2016-12-02.


EUT operation mode: Transmitting

Test Result: Compliance. Please refer to the following plots.


Cellular Band, Left Band Edge for GSM (GMSK) Mode




Cellular Band, Right Band Edge for GSM (GMSK) Mode







Cellular Band, Left Band Edge for EDGE Mode




Cellular Band, Right Band Edge for EDGE Mode




Cellular Band, Left Band Edge for WCDMA (BPSK) Mode**Cellular Band, Right Band Edge for WCDMA (BPSK) Mode**

Cellular Band, Left Band Edge for HSDPA (16QAM) Mode**Cellular Band, Right Band Edge for HSDPA (16QAM) Mode**


Cellular Band, Left Band Edge for HSUPA (BPSK) Mode




Cellular Band, Right Band Edge for HSUPA (BPSK) Mode




PCS Band, Left Band Edge for GSM (GMSK) Mode




PCS Band, Right Band Edge for GSM (GMSK) Mode




PCS Band, Left Band Edge for EDGE Mode




PCS Band, Right Band Edge for EDGE Mode




PCS Band, Left Band Edge for WCDMA (BPSK) Mode




PCS Band, Right Band Edge for WCDMA (BPSK) Mode




PCS Band, Left Band Edge for HSDPA (16QAM) Mode




PCS Band, Right Band Edge for HSDPA (16QAM) Mode




PCS Band, Left Band Edge for HSUPA (BPSK) Mode




PCS Band, Right Band Edge for HSUPA (BPSK) Mode




AWS Band, Left Band Edge for RMC (BPSK) Mode




AWS Band, Right Band Edge for RMC (BPSK) Mode




AWS Band, Left Band Edge for HSDPA (16QAM) Mode




AWS Band, Right Band Edge for HSDPA (16QAM) Mode



AWS Band, Left Band Edge for HSUPA (BPSK) Mode




AWS Band, Right Band Edge for HSUPA (BPSK) Mode






LTE Band 2:

QPSK (1.4 MHz, FULL RB) - Left Band Edge




QPSK (1.4 MHz, FULL RB) - Right Band Edge






16-QAM (1.4 MHz, FULL RB) - Left Band Edge**16-QAM (1.4 MHz, FULL RB) - Right Band Edge**

QPSK (3.0 MHz, FULL RB) - Left Band Edge




QPSK (3.0 MHz, FULL RB) - Right Band Edge






16-QAM (3.0 MHz, FULL RB) - Left Band Edge**16-QAM (3.0 MHz, FULL RB) - Right Band Edge**

QPSK (5.0 MHz, FULL RB) - Left Band Edge




QPSK (5.0 MHz, FULL RB) - Right Band Edge






16-QAM (5.0 MHz, FULL RB) - Left Band Edge**16-QAM (5.0 MHz, FULL RB) - Right Band Edge**

QPSK (10.0 MHz, FULL RB) - Left Band Edge




QPSK (10.0 MHz, FULL RB) - Right Band Edge






16-QAM (10.0 MHz, FULL RB) - Left Band Edge**16-QAM (10.0 MHz, FULL RB) - Right Band Edge**

QPSK (15.0 MHz, FULL RB) - Left Band Edge




QPSK (15.0 MHz, FULL RB) - Right Band Edge






16-QAM (15.0 MHz, FULL RB) - Left Band Edge**16-QAM (15.0 MHz, FULL RB) - Right Band Edge**

QPSK (20.0 MHz, FULL RB) - Left Band Edge




QPSK (20.0 MHz, FULL RB) - Right Band Edge



16-QAM (20.0 MHz, FULL RB) - Left Band Edge**16-QAM (20.0 MHz, FULL RB) - Right Band Edge**



LTE Band 4:



QPSK (1.4 MHz, FULL RB) - Left Band Edge





QPSK (1.4 MHz, FULL RB) - Right Band Edge




16-QAM (1.4 MHz, FULL RB) - Left Band Edge**16-QAM (1.4 MHz, FULL RB) - Right Band Edge**


QPSK (3.0 MHz, FULL RB) - Left Band Edge**QPSK (3.0 MHz, FULL RB) - Right Band Edge**



16-QAM (3.0 MHz, FULL RB) - Left Band Edge**16-QAM (3.0 MHz, FULL RB) - Right Band Edge**

QPSK (5.0 MHz, FULL RB) - Left Band Edge




QPSK (5.0 MHz, FULL RB) - Right Band Edge






16-QAM (5.0 MHz, FULL RB) - Left Band Edge**16-QAM (5.0 MHz, FULL RB) - Right Band Edge**

QPSK (10.0 MHz, FULL RB) - Left Band Edge



QPSK (10.0 MHz, FULL RB) - Right Band Edge



16-QAM (10.0 MHz, FULL RB) - Left Band Edge**16-QAM (10.0 MHz, FULL RB) - Right Band Edge**

Ref Lvl 34 dBm
 Marker 1 [T1] -23.84 dBm
 3.170781563 GHz
 RBW 300 kHz
 VBW 1 MHz
 SWT 20 ms
 RF Att 30 dB
 Unit dBm

14 dB Offset
 -23.84 dBm
 1.70781563 GHz

-13 dBm
 -13 dBm

Center 1.71 GHz
 3 MHz/
 Span 30 MHz

Marker 1 [T1]
 -28.70 dBm
 1.75707415 GHz

RBW 300 kHz RF Att 30 dB
 VBW 1 MHz
 SWT 20 ms Unit dBm

Ref Lvl 34 dBm
 14 dB Offset


-28.70 dBm
 1.75707415 GHz

-13 dBm


Center 1.755 GHz
 3 MHz/
 Span 30 MHz

Date: 19.DEC.2016 09:24:34


16-QAM (15.0 MHz, FULL RB) - Left Band Edge




16-QAM (15.0 MHz, FULL RB) - Right Band Edge





QPSK (20.0 MHz, FULL RB) - Left Band Edge




QPSK (20.0 MHz, FULL RB) - Right Band Edge




16-QAM (20.0 MHz, FULL RB) - Left Band Edge**16-QAM (20.0 MHz, FULL RB) - Right Band Edge**

LTE Band 7:


QPSK (5.0 MHz, FULL RB) - Left Band Edge




QPSK (5.0 MHz, FULL RB) - Right Band Edge




16-QAM (5.0 MHz, FULL RB) - Left Band Edge




16-QAM (5.0 MHz, FULL RB) - Right Band Edge





QPSK (10.0 MHz, FULL RB) - Left Band Edge




QPSK (10.0 MHz, FULL RB) - Right Band Edge




16-QAM (10.0 MHz, FULL RB) - Left Band Edge**16-QAM (10.0 MHz, FULL RB) - Right Band Edge**


QPSK (15 MHz, FULL RB) - Left Band Edge




QPSK (15 MHz, FULL RB) - Right Band Edge




16-QAM (15 MHz, FULL RB) - Left Band Edge




16-QAM (15 MHz, FULL RB) - Right Band Edge




QPSK (20 MHz, FULL RB) - Left Band Edge




QPSK (20 MHz, FULL RB) - Right Band Edge



16-QAM (20 MHz, FULL RB) - Left Band Edge




16-QAM (20 MHz, FULL RB) - Right Band Edge



LTE Band 17:


QPSK (5.0 MHz, FULL RB) - Left Band Edge




QPSK (5.0 MHz, FULL RB) - Right Band Edge




16-QAM (5.0 MHz, FULL RB) - Left Band Edge




16-QAM (5.0 MHz, FULL RB) - Right Band Edge




QPSK (10.0 MHz, FULL RB) - Left Band Edge




QPSK (10.0 MHz, FULL RB) - Right Band Edge



16-QAM (10.0 MHz, FULL RB) - Left Band Edge



16-QAM (10.0 MHz, FULL RB) - Right Band Edge



FCC § 2.1055; § 22.355; § 24.235; §27.54; - FREQUENCY STABILITY

Applicable Standard

FCC § 2.1055, §22.355, §24.235 and §27.54.

According to FCC §2.1055, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Transmitters in the Public Mobile Services

Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile > 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929.	5.0	N/A	N/A
929 to 960.	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A


According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: For hand carried, battery powered equipment; reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.



Test Data**Environmental Conditions**

Temperature:	26 °C
Relative Humidity:	48 %
ATM Pressure:	101.5 kPa

The testing was performed by Echo Wu on 2016-11-25.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to the following tables.

Cellular Band (Part 22H)**GSM Mode**

Middle Channel, $f_0 = 836.6\text{MHz}$				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.8	7	0.00837	2.5
-20		5	0.00598	2.5
-10		5	0.00598	2.5
0		3	0.00359	2.5
10		3	0.00359	2.5
20		1	0.00120	2.5
30		2	0.00239	2.5
40		4	0.00478	2.5
50		4	0.00478	2.5
25	V _{min} = 3.6	6	0.00717	2.5
25	V _{max} = 4.2	9	0.01076	2.5

EDGE Mode

Middle Channel, $f_0 = 836.6\text{MHz}$				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.8	6	0.00717	2.5
-20		5	0.00598	2.5
-10		5	0.00598	2.5
0		2	0.00239	2.5
10		2	0.00239	2.5
20		1	0.00120	2.5
30		3	0.00359	2.5
40		3	0.00359	2.5
50		6	0.00717	2.5
25	$V_{min.} = 3.6$	6	0.00717	2.5
25	$V_{max.} = 4.2$	8	0.00956	2.5

WCDMA Mode

Middle Channel, $f_0 = 836.6\text{MHz}$				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.8	-4	-0.00478	2.5
-20		-3	-0.00359	2.5
-10		-3	-0.00359	2.5
0		-3	-0.00359	2.5
10		-2	-0.00239	2.5
20		-2	-0.00239	2.5
30		-2	-0.00239	2.5
40		-4	-0.00478	2.5
50		-4	-0.00478	2.5
25	$V_{min.} = 3.6$	-4	-0.00478	2.5
25	$V_{max.} = 4.2$	-5	-0.00598	2.5

PCS Band (Part 24E)**GSM Mode**

Middle Channel, $f_0 = 1880.0$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.8	18	0.00957	pass
-20		16	0.00851	pass
-10		14	0.00745	pass
0		10	0.00532	pass
10		10	0.00532	pass
20		9	0.00479	pass
30		11	0.00585	pass
40		11	0.00585	pass
50		17	0.00904	pass
25	V _{min} = 3.6	19	0.01011	pass
25	V _{max} = 4.2	21	0.01117	pass

EDGE Mode

Middle Channel, $f_0 = 1880.0$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.8	-13	-0.00691	pass
-20		-12	-0.00638	pass
-10		-10	-0.00532	pass
0		-10	-0.00532	pass
10		-8	-0.00426	pass
20		-7	-0.00372	pass
30		-9	-0.00479	pass
40		-9	-0.00479	pass
50		-11	-0.00585	pass
25	V _{min} = 3.6	-15	-0.00798	pass
25	V _{max} = 4.2	-20	-0.01064	pass

WCDMA Mode

Middle Channel, $f_0 = 1880.0$ MHz				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.8	6	0.00319	pass
-20		5	0.00266	pass
-10		5	0.00266	pass
0		2	0.00106	pass
10		2	0.00106	pass
20		-1	-0.00053	pass
30		1	0.00053	pass
40		3	0.00160	pass
50		4	0.00213	pass
25	$V_{min} = 3.6$	5	0.00266	pass
25	$V_{max} = 4.2$	7	0.00372	pass

AWS Band (Part 27)**WCDMA Mode**

Middle Channel, $f_0 = 1732.6$ MHz				
Temperature (°C)	Voltage Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.8	-8	-0.00462	pass
-20		-8	-0.00462	pass
-10		-8	-0.00462	pass
0		-7	-0.00404	pass
10		-7	-0.00404	pass
20		-5	-0.00289	pass
30		-6	-0.00346	pass
40		-6	-0.00346	pass
50		-6	-0.00346	pass
25	$V_{min} = 3.6$	-8	-0.00462	pass
25	$V_{max} = 4.2$	-9	-0.00519	pass

LTE Band 2:

20.0 MHz Middle Channel, $f_0=1880\text{MHz}$				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.8	12	0.00638	pass
-20		10	0.00532	pass
-10		8	0.00426	pass
0		6	0.00319	pass
10		3	0.00160	pass
20		2	0.00106	pass
30		4	0.00213	pass
40		7	0.00372	pass
50		11	0.00585	pass
20	$V_{min}=3.6$	15	0.00798	pass
	$V_{max}=4.2$	17	0.00904	pass

LTE Band 4:

20.0 MHz Middle Channel, $f_0=1732.5\text{ MHz}$				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.8	11	0.00639	pass
-20		8	0.00462	pass
-10		6	0.00346	pass
0		4	0.00231	pass
10		2	0.00115	pass
20		1	0.00058	pass
30		3	0.00173	pass
40		5	0.00289	pass
50		7	0.00404	pass
20	$V_{min}=3.6$	10	0.00577	pass
	$V_{max}=4.2$	15	0.00866	pass

LTE Band 7:

10.0 MHz Middle Channel, $f_o = 2535$ MHz				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.8	18	0.00710	pass
-20		15	0.00592	pass
-10		11	0.00434	pass
0		8	0.00158	pass
10		5	0.00197	pass
20		2	0.00079	pass
30		6	0.00237	pass
40		10	0.00394	pass
50		14	0.00552	pass
20	$V_{min} = 3.6$	20	0.00789	pass
	$V_{max} = 4.2$	26	0.01026	pass

LTE Band 17:

10.0 MHz Middle Channel, $f_o = 710$ MHz (QPSK)				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.8	7	0.00986	pass
-20		5	0.00704	pass
-10		5	0.00704	pass
0		2	0.00282	pass
10		2	0.00282	pass
20		1	0.00141	pass
30		3	0.00423	pass
40		3	0.00423	pass
50		4	0.00563	pass
25	$V_{min} = 3.6$	6	0.00845	pass
25	$V_{max} = 4.2$	8	0.01127	pass

***** END OF REPORT *****