

FCC REPORT

Applicant: SKY PHONE LLC

Address of Applicant: 1348 Washington Av. Suite 350, Miami Beach, FL 33139

Equipment Under Test (EUT)

Product Name: Smart phone

Model No.: PLATINUM E5, PLATINUM F5

Trade mark: SKY DEVICES

FCC ID: 2ABOSSKYPLATE5

Applicable standards: FCC CFR Title 47 Part 15 Subpart B

Date of sample receipt: 14 Sep., 2018

Date of Test: 14 Sep., 2018 to 07 Jan., 2019

Date of report issued: 07 Jan., 2019

Test Result: PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.


This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	07 Jan., 2019	Original

Tested by:



Test Engineer

Date:

07 Jan., 2019

Reviewed by:



Project Engineer

Date:

07 Jan., 2019

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY.....	4
5 GENERAL INFORMATION.....	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF E.U.T.	5
5.3 TEST MODE.....	5
5.4 MEASUREMENT UNCERTAINTY.....	5
5.5 DESCRIPTION OF SUPPORT UNITS	7
5.6 RELATED SUBMITTAL(s) / GRANT (s).....	7
5.7 LABORATORY FACILITY	7
5.8 LABORATORY LOCATION	7
5.9 TEST INSTRUMENTS LIST.....	8
6 TEST RESULTS AND MEASUREMENT DATA.....	9
6.1 CONDUCTED EMISSION.....	9
6.2 RADIATED EMISSION	14
7 TEST SETUP PHOTO	24
8 EUT CONSTRUCTIONAL DETAILS	25

4 Test Summary

Test Item	Section in CFR 47	Result
Conducted Emission	Part 15.107	Pass
Radiated Emission	Part 15.109	Pass
<i>Remark:</i> <i>Pass: The EUT complies with the essential requirements in the standard.</i> <i>N/A: The EUT not applicable of the test item.</i>		

5 General Information

5.1 Client Information

Applicant:	SKY PHONE LLC
Address of Applicant:	1348 Washington Av. Suite 350, Miami Beach, FL 33139
Manufacturer:	OBO ELECTRONICS GROUP LIMITED
Address:	Room 01B5, 10/F, Carnival Commercial Building 18, Java Road North Point, Hong Kong

5.2 General Description of E.U.T.

Product Name:	Smart phone
Model No.:	PLATINUM E5, PLATINUM F5
Power supply:	Rechargeable Li-ion Battery DC3.7V-2000mAh
AC adapter :	Model: SSB-LW-001 Input: AC100-240V, 50/60Hz, 0.2A Output: DC 5.0V, 1000mA
Remark:	Model No.: PLATINUM E5, PLATINUM F5 were identical inside, the electrical circuit design, layout, components used and internal wiring, Different model. Only difference is memory between PLATINUM E5 and PLATINUM F5, the other hardware is exactly the same.: PLATINUM E5 memory is 512MB + 4GB PLATINUM F5 memory is 512MB + 8GB
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

5.3 Test Mode

Operating mode	Detail description
PC mode	Keep the EUT in Downloading mode(Worst case)
Charging+Recording mode	Keep the EUT in Charging+Recording mode
Charging+Playing mode	Keep the EUT in Charging+Playing mode
FM mode	Keep the EUT in FM receiver mode
GPS mode	Keep the EUT in GPS receiver mode

The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

5.4 Measurement Uncertainty

Parameters	Expanded Uncertainty
Conducted Emission (9kHz ~ 30MHz)	±2.22 dB (k=2)
Radiated Emission (9kHz ~ 30MHz)	±2.76 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	±4.28 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	±5.72 dB (k=2)
Radiated Emission (18GHz ~ 40GHz)	±2.88 dB (k=2)

5.5 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC ID/DoC
DELL	PC	OPTIPLEX745	N/A	DoC
DELL	MONITOR	E178FPC	N/A	DoC
DELL	KEYBOARD	SK-8115	N/A	DoC
DELL	MOUSE	MOC5UO	N/A	DoC
LENOVO	Laptop	SL510	2847A65	DoC

5.6 Related Submittal(s) / Grant (s)

This is an original grant, no related submittals and grants.

5.7 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Registration No.: 727551**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been accredited as a testing laboratory by FCC (Federal Communications Commission). The Registration No. is 727551.

- **IC - Registration No.: 10106A-1**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

- **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

- **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

5.8 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.
Address: No. B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,
Bao'an District, Shenzhen, Guangdong, China
Tel: +86-755-23118282, Fax: +86-755-23116366
Email: info@ccis-cb.com, Website: <http://www.ccis-cb.com>


5.9 Test Instruments list

Radiated Emission:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	SAEMC	9m*6m*6m	966	07-22-2017	07-21-2020
Loop Antenna	SCHWARZBECK	FMZB1519B	00044	03-16-2018	03-15-2019
BiConiLog Antenna	SCHWARZBECK	VULB9163	497	03-16-2018	03-15-2019
Horn Antenna	SCHWARZBECK	BBHA9120D	916	03-16-2018	03-15-2019
Horn Antenna	SCHWARZBECK	BBHA9120D	1805	06-22-2017	06-21-2020
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170582	11-21-2017	11-20-2018
EMI Test Software	AUDIX	E3	Version: 6.110919b		
Pre-amplifier	HP	8447D	2944A09358	03-07-2018	03-06-2019
Pre-amplifier	CD	PAP-1G18	11804	03-07-2018	03-06-2019
Spectrum analyzer	Rohde & Schwarz	FSP30	101454	03-07-2018	03-06-2019
Spectrum analyzer	Rohde & Schwarz	FSP40	100363	11-21-2017	11-20-2018
EMI Test Receiver	Rohde & Schwarz	ESRP7	101070	03-07-2018	03-06-2019
Cable	ZDECL	Z108-NJ-NJ-81	1608458	03-07-2018	03-06-2019
Cable	MICRO-COAX	MFR64639	K10742-5	03-07-2018	03-06-2019
Cable	SUHNER	SUCOFLEX100	58193/4PE	03-07-2018	03-06-2019

Conducted Emission:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
EMI Test Receiver	Rohde & Schwarz	ESCI	101189	03-07-2018	03-06-2019
Pulse Limiter	SCHWARZBECK	OSRAM 2306	9731	03-07-2018	03-06-2019
LISN	CHASE	MN2050D	1447	03-19-2018	03-18-2019
LISN	Rohde & Schwarz	ESH3-Z5	8438621/010	07-21-2018	07-20-2019
Cable	HP	10503A	N/A	03-07-2018	03-06-2019
EMI Test Software	AUDIX	E3	Version: 6.110919b		


6 Test results and Measurement Data

6.1 Conducted Emission

Test Requirement:	FCC Part 15 B Section 15.107					
Test Method:	ANSI C63.4:2014					
Test Frequency Range:	150kHz to 30MHz					
Class / Severity:	Class B					
Receiver setup:	RBW=9kHz, VBW=30kHz					
Limit:	Frequency range (MHz)	Limit (dBμV)				
		Quasi-peak		Average		
		0.15-0.5		66 to 56*		56 to 46*
		0.5-5		56		46
	0.5-30		60		50	
* Decreases with the logarithm of the frequency.						
Test setup:	Reference Plane  Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m					
Test procedure	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network(L.I.S.N.). The provide a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2014 on conducted measurement.					
Test environment:	Temp.:	23 °C	Humid.:	56%	Press.:	101kPa
Test Instruments:	Refer to section 5.9 for details					
Test mode:	Refer to section 5.3 for details					
Test results:	Pass					

(1) Measurement data:

Product name:	Smart phone	Product model:	PLATINUM E5
Test by:	Caffrey	Test mode:	PC mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5℃ Humi: 55%




Trace: 27

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.158	27.28	0.17	10.77	38.22	55.56	-17.34	Average
2	0.162	36.27	0.17	10.77	47.21	65.34	-18.13	QP
3	0.258	35.69	0.14	10.75	46.58	61.51	-14.93	QP
4	0.258	25.57	0.14	10.75	36.46	51.51	-15.05	Average
5	4.092	24.47	0.18	10.89	35.54	46.00	-10.46	Average
6	4.746	27.80	0.20	10.86	38.86	56.00	-17.14	QP
7	10.019	29.93	0.32	10.94	41.19	60.00	-18.81	QP
8	10.179	26.12	0.32	10.94	37.38	50.00	-12.62	Average
9	16.839	36.73	0.30	10.91	47.94	60.00	-12.06	QP
10	17.291	27.82	0.30	10.91	39.03	50.00	-10.97	Average
11	23.018	32.95	0.31	10.89	44.15	60.00	-15.85	QP
12	23.018	28.32	0.31	10.89	39.52	50.00	-10.48	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss.

Product name:	Smart phone	Product model:	PLATINUM E5
Test by:	Caffrey	Test mode:	PC mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Neutral
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5℃ Humi: 55%



Trace: 29


	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.154	34.11	0.98	10.78	45.87	65.78	-19.91	QP
2	0.158	30.04	0.98	10.77	41.79	55.56	-13.77	Average
3	0.190	32.70	0.93	10.76	44.39	64.02	-19.63	QP
4	0.258	30.99	0.95	10.75	42.69	61.51	-18.82	QP
5	0.258	28.03	0.95	10.75	39.73	51.51	-11.78	Average
6	1.680	19.92	0.98	10.94	31.84	46.00	-14.16	Average
7	9.552	21.37	1.02	10.92	33.31	50.00	-16.69	Average
8	9.809	26.39	1.02	10.93	38.34	60.00	-21.66	QP
9	16.486	27.75	0.83	10.91	39.49	50.00	-10.51	Average
10	16.573	37.15	0.83	10.91	48.89	60.00	-11.11	QP
11	23.018	34.86	0.68	10.89	46.43	60.00	-13.57	QP
12	23.140	27.62	0.68	10.89	39.19	50.00	-10.81	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss.

(2) Measurement data:

Product name:	Smart phone	Product model:	PLATINUM E5
Test by:	Caffrey	Test mode:	PC mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5℃ Humi: 55%




Trace: 31

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.158	27.28	0.17	10.77	38.22	55.56	-17.34	Average
2	0.162	36.27	0.17	10.77	47.21	65.34	-18.13	QP
3	0.258	35.69	0.14	10.75	46.58	61.51	-14.93	QP
4	0.258	27.57	0.14	10.75	38.46	51.51	-13.05	Average
5	3.454	29.78	0.17	10.91	40.86	56.00	-15.14	QP
6	4.092	26.47	0.18	10.89	37.54	46.00	-8.46	Average
7	10.019	30.93	0.32	10.94	42.19	60.00	-17.81	QP
8	10.179	27.12	0.32	10.94	38.38	50.00	-11.62	Average
9	16.839	37.73	0.30	10.91	48.94	60.00	-11.06	QP
10	17.291	27.82	0.30	10.91	39.03	50.00	-10.97	Average
11	23.263	32.15	0.32	10.89	43.36	60.00	-16.64	QP
12	23.263	26.92	0.32	10.89	38.13	50.00	-11.87	Average

Notes:

- An initial pre-scan was performed on the line and neutral lines with peak detector.
- Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- Final Level = Receiver Read level + LISN Factor + Cable Loss.

Product name:	Smart phone	Product model:	PLATINUM E5
Test by:	Caffrey	Test mode:	PC mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Neutral
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5°C Humi: 55%





Trace: 33

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.154	33.11	0.98	10.78	44.87	65.78	-20.91	QP
2	0.158	31.04	0.98	10.77	42.79	55.56	-12.77	Average
3	0.258	30.99	0.95	10.75	42.69	61.51	-18.82	QP
4	0.258	30.03	0.95	10.75	41.73	51.51	-9.78	Average
5	1.680	24.92	0.98	10.94	36.84	46.00	-9.16	Average
6	1.810	26.81	0.98	10.95	38.74	56.00	-17.26	QP
7	9.552	24.37	1.02	10.92	36.31	50.00	-13.69	Average
8	9.809	26.39	1.02	10.93	38.34	60.00	-21.66	QP
9	16.486	29.75	0.83	10.91	41.49	50.00	-8.51	Average
10	16.573	35.15	0.83	10.91	46.89	60.00	-13.11	QP
11	23.018	32.86	0.68	10.89	44.43	60.00	-15.57	QP
12	23.140	29.62	0.68	10.89	41.19	50.00	-8.81	Average

Notes:

- An initial pre-scan was performed on the line and neutral lines with peak detector.
- Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- Final Level = Receiver Read level + LISN Factor + Cable Loss.

6.2 Radiated Emission


Test Requirement:	FCC Part 15 B Section 15.109				
Test Method:	ANSI C63.4:2014				
Test Frequency Range:	30MHz to 6000MHz				
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		RMS	1MHz	3MHz	Average Value
Limit:	Frequency		Limit (dBuV/m @3m)		Remark
	30MHz-88MHz		40.0		Quasi-peak Value
	88MHz-216MHz		43.5		Quasi-peak Value
	216MHz-960MHz		46.0		Quasi-peak Value
	960MHz-1GHz		54.0		Quasi-peak Value
	Above 1GHz		54.0		Average Value
			74.0		Peak Value
Test setup:	Below 1GHz				
					
Test setup:	Above 1GHz				
					

Test Procedure:	1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.					
Test environment:	Temp.:	25 °C	Humid.:	55%	Press.:	1 01kPa
Test Instruments:	Refer to section 5.9 for details					
Test mode:	Refer to section 5.3 for details					
Test results:	Passed					
Remark:	All of the observed value above 6GHz were the noise floor , which were no recorded					

Measurement Data:

(1) Below 1GHz:

Product Name:	Smart phone	Product model:	PLATINUM E5
Test By:	Caffrey	Test mode:	PC mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Humi: 57%




	Freq	Read	Antenna	Cable	Aux	Preamp	Level	Limit	Over	Remark
	MHz	Level	Factor	Loss	Factor	Factor	Level	Line	Limit	
		dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	104.536	49.62	11.98	1.99	0.00	29.50	34.09	43.50	-9.41	QP
2	142.324	55.69	8.22	2.43	0.00	29.26	37.08	43.50	-6.42	QP
3	170.793	58.51	9.43	2.66	0.00	29.04	41.56	43.50	-1.94	QP
4	207.850	47.43	11.81	2.86	0.00	28.78	33.32	43.50	-10.18	QP
5	480.528	51.64	16.97	3.46	0.00	28.92	43.15	46.00	-2.85	QP
6	962.162	43.53	22.50	4.27	0.00	27.65	42.65	54.00	-11.35	QP

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	Smart phone	Product model:	PLATINUM E5
Test By:	Caffrey	Test mode:	PC mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




	Freq	ReadAntenna	Cable	Aux	Preamp	Level	Limit	Over	Remark
	MHz	Level	Factor	Loss	Factor	Factor	Line	Limit	
		dBuV	dB/m	dB	dB	dB	dBuV/m	dB	
1	165.487	58.52	9.27	2.62	0.00	29.09	41.32	43.50	-2.18 QP
2	207.850	53.11	11.81	2.86	0.00	28.78	39.00	43.50	-4.50 QP
3	255.623	51.60	13.34	2.82	0.00	28.53	39.23	46.00	-6.77 QP
4	480.528	54.04	16.97	3.46	0.00	28.92	45.55	46.00	-0.45 QP
5	833.317	46.64	21.20	4.24	0.00	28.07	44.01	46.00	-1.99 QP
6	962.162	47.35	22.50	4.27	0.00	27.65	46.47	54.00	-7.53 QP

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Above 1GHz:

Product Name:	Smart phone	Product model:	PLATINUM E5
Test By:	Caffrey	Test mode:	PC mode
Test Frequency:	1 GHz ~ 6 GHz	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




	Freq	ReadAntenna	Cable	Aux	Preamp	Level	Limit	Over	Remark
	MHz	Level	Factor	Loss	Factor	Factor	Line	Limit	
		dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB
1	3097.515	46.42	28.66	5.39	0.00	41.46	39.01	74.00	-34.99 Peak
2	3097.515	38.23	28.66	5.39	0.00	41.46	30.82	54.00	-23.18 Average
3	4253.498	47.88	30.67	6.48	0.00	41.85	43.18	74.00	-30.82 Peak
4	4253.498	38.41	30.67	6.48	0.00	41.85	33.71	54.00	-20.29 Average
5	4926.683	48.24	31.79	6.89	0.00	41.86	45.06	74.00	-28.94 Peak
6	4926.683	38.36	31.79	6.89	0.00	41.86	35.18	54.00	-18.82 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	Smart phone	Product model:	PLATINUM E5
Test By:	Caffrey	Test mode:	PC mode
Test Frequency:	1 GHz ~ 6 GHz	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




	Freq	ReadAntenna	Cable	Aux	Preamp	Level	Limit	Over	Remark
	MHz	Level	Factor	Loss	Factor	Factor	Line	Limit	
		dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB
1	2999.209	48.06	28.60	5.35	0.00	41.51	40.50	74.00	-33.50 Peak
2	2999.209	39.32	28.60	5.35	0.00	41.51	31.76	54.00	-22.24 Average
3	4261.126	49.47	30.68	6.50	0.00	41.86	44.79	74.00	-29.21 Peak
4	4261.126	40.22	30.68	6.50	0.00	41.86	35.54	54.00	-18.46 Average
5	5264.368	51.27	32.17	7.10	0.00	41.92	48.62	74.00	-25.38 Peak
6	5264.368	40.78	32.17	7.10	0.00	41.92	38.13	54.00	-15.87 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

(2) Below 1GHz:

Product Name:	Smart phone	Product model:	PLATINUM E5
Test By:	Caffrey	Test mode:	PC mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	121.549	52.87	9.96	2.19	29.38	35.64	43.50	-7.86	QP
2	164.908	52.40	9.25	2.62	29.09	35.18	43.50	-8.32	QP
3	207.850	52.70	11.81	2.86	28.78	38.59	43.50	-4.91	QP
4	404.667	46.05	15.56	3.09	28.79	35.91	46.00	-10.09	QP
5	480.528	50.75	16.97	3.46	28.92	42.26	46.00	-3.74	QP
6	962.162	40.46	22.50	4.27	27.65	39.58	54.00	-14.42	QP

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	Smart phone	Product model:	PLATINUM E5
Test By:	Caffrey	Test mode:	PC mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%



	Freq	ReadAntenna	Cable Preamp	Limit	Over	
	Level	Factor	Loss	Factor	Level	Line
	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m
	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m
1	165.487	55.45	9.27	2.62	29.09	38.25
2	239.987	53.36	12.97	2.82	28.59	40.56
3	434.065	44.22	15.92	3.16	28.84	34.46
4	480.528	48.36	16.97	3.46	28.92	39.87
5	661.151	39.10	19.80	3.93	28.75	34.08
6	962.162	47.90	22.50	4.27	27.65	47.02


Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.

4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Above 1GHz:

Product Name:	Smart phone	Product model:	PLATINUM E5
Test By:	Caffrey	Test mode:	PC mode
Test Frequency:	1 GHz ~ 6 GHz	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




	Read	Antenna	Cable	Preamp	Level	Limit	Over	
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
-----	-----	-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2956.525	47.82	28.52	5.30	41.54	40.10	74.00	-33.90 Peak
2	2956.525	38.67	28.52	5.30	41.54	30.95	54.00	-23.05 Average
3	4067.171	48.58	30.33	6.20	41.81	43.30	74.00	-30.70 Peak
4	4067.171	39.21	30.33	6.20	41.81	33.93	54.00	-20.07 Average
5	5535.214	49.24	32.47	7.24	41.81	47.14	74.00	-26.86 Peak
6	5535.214	39.45	32.47	7.24	41.81	37.35	54.00	-16.65 Average

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	Smart phone	Product model:	PLATINUM E5
Test By:	Caffrey	Test mode:	PC mode
Test Frequency:	1 GHz ~ 6 GHz	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2999.209	49.06	28.60	5.35	41.51	41.50	74.00	-32.50	Peak
2	2999.209	39.23	28.60	5.35	41.51	31.67	54.00	-22.33	Average
3	4030.897	49.49	30.26	6.15	41.81	44.09	74.00	-29.91	Peak
4	4030.897	39.75	30.26	6.15	41.81	34.35	54.00	-19.65	Average
5	5161.626	50.88	32.07	7.06	41.94	48.07	74.00	-25.93	Peak
6	5161.626	41.20	32.07	7.06	41.94	38.39	54.00	-15.61	Average

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.

4. The emission levels of other frequencies are very lower than the limit and not show in test report.