

INTERTEK TESTING SERVICES

Analysis Report

The equipment under test (EUT) is a Motorized Auto-feeding Portable Scanner. The EUT was powered by The EUT can be powered by 3.7Vdc rechargeable battery and charged by Adapter (The Adapter was powered by AC 120V/60Hz). For more detail information pls. refer to the user manual.

Modulation Type: BPSK, QPSK, 16QAM, 64QAM, CCK, DQPSK, DBPSK.

Antenna Type: Integral antenna

Antenna Gain: 2.0dBi

The nominal conducted output power is 6.0dBm (Tolerance: +/- 3dB)

According to the KDB 447498:

The maximum peak conducted output power for the EUT is 8.24dBm in the frequency 2412MHz (802.11b) which is within the product variation.

The minimum peak conducted output power for the EUT is 5.01dBm in the frequency 2412MHz (802.11g) which is within the production variation.

The maximum conducted output power specified is 9dBm = 7.94mW

The source-based time-averaging conducted output power
= 7.94 * Duty factor mW= 7.94 mW

The SAR Exclusion Threshold Level:

= 3.0 * (min. test separation distance, mm) / sqrt(freq. in GHz)
= 3.0 * 5 / sqrt (2.462) mW
= 9.6 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

Transmitter Duty Cycle Calculation

The EUT transmit continuously during the test, the duty cycle is 1.

This requirement is according to KDB 865664 D02