

APPLICATION CERTIFICATION FCC Part 15C
On Behalf of
SHENZHEN AINOL ELECTRON CO.,LTD

Numy 3G serials-AX1 SPEC
Model No.: Numy 3G AX1

FCC ID: 2ABTP-NUMY-3G

Prepared for : SHENZHEN AINOL ELECTRON CO.,LTD
Address : Room 606,Bldg B,7 Star Business Plaza, Minzhi Street,
Longhua District, Shenzhen, China
Prepared by : ACCURATE TECHNOLOGY CO., LTD
Address : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.
Science & Industry Park, Nanshan, Shenzhen, Guangdong
P.R. China

Tel: (0755) 26503290
Fax: (0755) 26503396

Report No. : ATE201312564
Date of Test : Dec 02, 2013-Feb 15, 2014
Date of Report : Feb 15, 2014

TABLE OF CONTENTS

Description	Page
Test Report Certification	
1. GENERAL INFORMATION	5
1.1. Description of Device (EUT).....	5
1.2. Carrier Frequency of Channels.....	6
1.3. Accessory and Auxiliary Equipment	6
1.4. Description of Test Facility	6
1.5. Measurement Uncertainty.....	7
2. MEASURING DEVICE AND TEST EQUIPMENT	8
3. OPERATION OF EUT DURING TESTING	9
3.1. Operating Mode.....	9
3.2. Configuration and peripherals	9
4. TEST PROCEDURES AND RESULTS	10
5. POWER LINE CONDUCTED MEASUREMENT	11
5.1. Block Diagram of Test Setup.....	11
5.2. Power Line Conducted Emission Measurement Limits.....	11
5.3. Configuration of EUT on Measurement	11
5.4. Operating Condition of EUT	11
5.5. Test Procedure	12
5.6. Power Line Conducted Emission Measurement Results	13
6. 6DB BANDWIDTH MEASUREMENT	16
6.1. Block Diagram of Test Setup.....	16
6.2. The Requirement For Section 15.247(a)(2).....	16
6.3. EUT Configuration on Measurement	16
6.4. Operating Condition of EUT	16
6.5. Test Procedure	16
6.6. Test Result	17
7. MAXIMUM PEAK OUTPUT POWER	24
7.1. Block Diagram of Test Setup.....	24
7.2. The Requirement For Section 15.247(b)(3).....	24
7.3. EUT Configuration on Measurement	24
7.4. Operating Condition of EUT	24
7.5. Test Procedure	24
7.6. Test Result	25
8. POWER SPECTRAL DENSITY MEASUREMENT.....	32
8.1. Block Diagram of Test Setup.....	32
8.2. The Requirement For Section 15.247(e).....	32
8.3. EUT Configuration on Measurement	32
8.4. Operating Condition of EUT	32
8.5. Test Procedure	32
8.6. Test Result	33
9. BAND EDGE COMPLIANCE TEST	40
9.1. Block Diagram of Test Setup.....	40
9.2. The Requirement For Section 15.247(d)	40

9.3.	EUT Configuration on Measurement	40
9.4.	Operating Condition of EUT	40
9.5.	Test Procedure	40
9.6.	Test Result	41
10.	RADIATED SPURIOUS EMISSION TEST	62
10.1.	Block Diagram of Test Setup.....	62
10.2.	The Limit For Section 15.247(d)	62
10.3.	Restricted bands of operation	63
10.4.	Configuration of EUT on Measurement	63
10.5.	Operating Condition of EUT	64
10.6.	Test Procedure	64
10.7.	The Field Strength of Radiation Emission Measurement Results	64
11.	CONDUCTED SPURIOUS EMISSION COMPLIANCE TEST	112
11.1.	Block Diagram of Test Setup.....	112
11.2.	The Requirement For Section 15.247(d)	112
11.3.	EUT Configuration on Measurement	112
11.4.	Operating Condition of EUT	112
11.5.	Test Procedure	113
11.6.	Test Result	113
12.	ANTENNA REQUIREMENT.....	120
12.1.	The Requirement	120
12.2.	Antenna Construction	120

Test Report Certification

Applicant : SHENZHEN AINOL ELECTRON CO.,LTD
Manufacturer : SHENZHEN AINOL ELECTRON CO.,LTD
EUT Description : Numy 3G serials-AX1 SPEC
(A) MODEL NO.: Numy 3G AX1
(B) Trade Name.: Ainol
(C) POWER SUPPLY: DC 3.7V (Powered by battery) or AC 120V/60Hz
(Powered by adapter)

Measurement Procedure Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247
ANSI C63.4: 2009


The EUT was tested according to DTS test procedure of April 09, 2013 KDB558074 D01 DTS Meas Guidance v03 for compliance to FCC 47CFR 15.247 requirements

The device described above is tested by ACCURATE TECHNOLOGY CO. LTD to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.247 limits. The measurement results are contained in this test report and ACCURATE TECHNOLOGY CO. LTD is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of ACCURATE TECHNOLOGY CO. LTD.

Date of Test : Dec 02, 2013-Feb 15, 2014

Prepared by :



(Tim.zhang, Engineer)

Approved & Authorized Signer :



(Sean Liu, Manager)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT	:	Numy 3G serials-AX1 SPEC
Model Number	:	Numy 3G AX1
Frequency Range	:	802.11b/g/n(20MHz): 2412-2462MHz 802.11n(40MHz): 2422-2452MHz
Number of Channels	:	802.11b/g/n (20MHz):11 802.11n (40MHz): 7
Antenna Gain	:	1.5dBi
Type of Antenna	:	Integral Antenna
Power Supply	:	DC 3.7V (Powered by Battery) AC 120V/60Hz (Powered by Adapter)
Data Rate	:	802.11b: 11, 5.5, 2, 1 Mbps 802.11g: 54, 48, 36, 24, 18, 12, 9, 6 Mbps 802.11n: up to 150Mbps
Adapter	:	Model:SJ-0520-E Input: AC 100-240V 50/60Hz 0.3A Output: 5.0V 2.0A
Modulation Type	:	CCK, OFDM
Applicant	:	SHENZHEN AINOL ELECTRON CO.,LTD
Address	:	Room 606,Bldg B,7 Star Business Plaza, Minzhi Street, Longhua District, Shenzhen, China
Manufacturer	:	SHENZHEN AINOL ELECTRON CO.,LTD
Address	:	Room 606,Bldg B,7 Star Business Plaza, Minzhi Street, Longhua District, Shenzhen, China
Date of sample received	:	Dec 02, 2013
Date of Test	:	Dec 02, 2013-Feb 15, 2014

1.2.Carrier Frequency of Channels

802.11b, 802.11g, 802.11n (20MHz)

Channel	Frequency(MHz)	Channel	Frequency(MHz)
01	2412	07	2442
02	2417	08	2447
03	2422	09	2452
04	2427	10	2457
05	2432	11	2462
06	2437	---	---

802.11n (40MHz)

Channel	Frequency(MHz)	Channel	Frequency(MHz)
---	---	07	2442
---	---	08	2447
03	2422	09	2452
04	2427	---	---
05	2432	---	---
06	2437	---	---

1.3.Accessory and Auxiliary Equipment

N/A

1.4.Description of Test Facility

EMC Lab : Accredited by TUV Rheinland Shenzhen

Listed by FCC
The Registration Number is 752051

Listed by Industry Canada
The Registration Number is 5077A-2

Accredited by China National Accreditation Committee
for Laboratories
The Certificate Registration Number is L3193

Name of Firm : ACCURATE TECHNOLOGY CO. LTD

Site Location : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.
Science & Industry Park, Nanshan, Shenzhen, Guangdong
P.R. China

1.5.Measurement Uncertainty

Conducted Emission Expanded Uncertainty = 2.23dB, k=2

Radiated emission expanded uncertainty
(9kHz-30MHz) = 3.08dB, k=2

Radiated emission expanded uncertainty
(30MHz-1000MHz) = 4.42dB, k=2

Radiated emission expanded uncertainty
(Above 1GHz) = 4.06dB, k=2

2. MEASURING DEVICE AND TEST EQUIPMENT

Table 1: List of Test and Measurement Equipment

Kind of equipment	Manufacturer	Type	S/N	Calibrated dates	Calibrated until
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	Jan. 11, 2014	Jan. 10, 2015
EMI Test Receiver	Rohde&Schwarz	ESPI3	101526/003	Jan. 11, 2014	Jan. 10, 2015
Spectrum Analyzer	Agilent	E7405A	MY45115511	Jan. 11, 2014	Jan. 10, 2015
Pre-Amplifier	Rohde&Schwarz	CBLU118354 0-01	3791	Jan. 11, 2014	Jan. 10, 2015
Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan. 15, 2014	Jan. 14, 2015
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan. 15, 2014	Jan. 14, 2015
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan. 15, 2014	Jan. 14, 2015
Horn Antenna	Schwarzbeck	BBHA9170	9170-359	Jan. 15, 2014	Jan. 14, 2015
LISN	Rohde&Schwarz	ESH3-Z5	100305	Jan. 11, 2014	Jan. 10, 2015
LISN	Schwarzbeck	NSLK8126	8126431	Jan. 11, 2014	Jan. 10, 2015
Highpass Filter	Wainwright Instruments	WHKX3.6/18 G-10SS	N/A	Jan. 11, 2014	Jan. 10, 2015
Band Reject Filter	Wainwright Instruments	WRCG2400/2 485-2375/2510 -60/11SS	N/A	Jan. 11, 2014	Jan. 10, 2015

3. OPERATION OF EUT DURING TESTING

3.1.Operating Mode

The mode is used: **1.802.11b Transmitting mode**

Low Channel: 2412MHz

Middle Channel: 2437MHz

High Channel: 2462MHz

2.802.11g Transmitting mode

Low Channel: 2412MHz

Middle Channel: 2437MHz

High Channel: 2462MHz

3.802.11n (20MHz) Transmitting mode

Low Channel: 2412MHz

Middle Channel: 2437MHz

High Channel: 2462MHz

4.802.11n (40MHz) Transmitting mode

Low Channel: 2422MHz

Middle Channel: 2437MHz

High Channel: 2452MHz

3.2.Configuration and peripherals





Figure 1 Setup: Transmitting mode

4. TEST PROCEDURES AND RESULTS

FCC Rules	Description of Test	Result
Section 15.207	Power Line Conducted Emission	Compliant
Section 15.247(a)(2)	6dB Bandwidth Test	Compliant
Section 15.247(e)	Power Spectral Density Test	Compliant
Section 15.247(b)(3)	Maximum Peak Output Power Test	Compliant
Section 15.247(d)	Band Edge Compliance Test	Compliant
Section 15.247(d) Section 15.209	Radiated Spurious Emission Test	Compliant
Section 15.247(d)	Conducted Spurious Emission Test	Compliant
Section 15.203	Antenna Requirement	Compliant

5. POWER LINE CONDUCTED MEASUREMENT

5.1. Block Diagram of Test Setup



(EUT: Nummy 3G serials-AX1 SPEC)

5.2. Power Line Conducted Emission Measurement Limits

Frequency (MHz)	Limit dB(μV)	
	Quasi-peak Level	Average Level
0.15 - 0.50	66.0 – 56.0 *	56.0 – 46.0 *
0.50 - 5.00	56.0	46.0
5.00 - 30.00	60.0	50.0
NOTE1: The lower limit shall apply at the transition frequencies. NOTE2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz.		

5.3. Configuration of EUT on Measurement

The following equipments are installed on Power Line Conducted Emission Measurement to meet the commission requirement and operating regulations in a manner, which tends to maximize its emission characteristics in a normal application.

5.4. Operating Condition of EUT

- 5.4.1. Setup the EUT and simulator as shown as Section 5.1.
- 5.4.2. Turn on the power of all equipment.
- 5.4.3. Let the EUT work in test mode and measure it.

5.5. Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.4: 2009 on Conducted Emission Measurement.

The bandwidth of test receiver (R & S ESCS30) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

5.6.Power Line Conducted Emission Measurement Results

PASS.

The frequency range from 150kHz to 30MHz is checked.

Test mode : Charging&WIFI communicating								
MEASUREMENT RESULT: "AN17_fin"								
2013-12-4 13:52								
Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE	
0.180613	48.00	10.7	65	16.5	QP	L1	GND	
0.497124	41.50	12.5	56	14.5	QP	L1	GND	
2.388655	39.90	12.3	56	16.1	QP	L1	GND	
MEASUREMENT RESULT: "AN17_fin2"								
2013-12-4 13:52								
Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE	
0.497124	36.40	12.5	46	9.6	AV	L1	GND	
2.388655	33.50	12.3	46	12.5	AV	L1	GND	
6.574591	32.00	12.2	50	18.0	AV	L1	GND	
MEASUREMENT RESULT: "AN18_fin"								
2013-12-4 13:54								
Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE	
0.451684	42.40	12.3	57	14.4	QP	N	GND	
2.339089	42.80	12.3	56	13.2	QP	N	GND	
28.617181	40.90	12.0	60	19.1	QP	N	GND	
MEASUREMENT RESULT: "AN18_fin2"								
2013-12-4 13:54								
Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE	
0.451684	38.10	12.3	47	8.7	AV	N	GND	
2.339089	37.20	12.3	46	8.8	AV	N	GND	
4.858190	34.70	12.2	46	11.3	AV	N	GND	

Emissions attenuated more than 20 dB below the permissible value are not reported.

The spectral diagrams are attached as below.


ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART 15

EUT: Nummy 3G serials-AX1 SPEC M/N:Numy 3G
 Manufacturer: AINOL
 Operating Condition: WiFi Operation
 Test Site: 2#Shielding Room
 Operator: star
 Test Specification: L 120V/60Hz
 Comment: Report No.:ATE20132564
 Start of Test: 2013-12-4 / 13:51:08

SCAN TABLE: "V 150K-30MHz fin"

Short Description: _SUB_STD_VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 150.0 kHz 30.0 MHz 0.4 % QuasiPeak 1.0 s 9 kHz LISN(ESH3-Z5)
 Average



MEASUREMENT RESULT: "AN17_fin"

2013-12-4 13:52

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.180613	48.00	10.7	65	16.5	QP	L1	GND
0.497124	41.50	12.5	56	14.5	QP	L1	GND
2.388655	39.90	12.3	56	16.1	QP	L1	GND

MEASUREMENT RESULT: "AN17_fin2"

2013-12-4 13:52

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.497124	36.40	12.5	46	9.6	AV	L1	GND
2.388655	33.50	12.3	46	12.5	AV	L1	GND
6.574591	32.00	12.2	50	18.0	AV	L1	GND


ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART 15

EUT: Nummy 3G serials-AX1 SPEC M/N:Numy 3G
 Manufacturer: AINOL
 Operating Condition: WiFi Operation
 Test Site: 2#Shielding Room
 Operator: star
 Test Specification: N 120V/60Hz
 Comment: Report No.:ATE20132564
 Start of Test: 2013-12-4 / 13:52:53

SCAN TABLE: "V 150K-30MHz fin"

Short Description: _SUB_STD_VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 150.0 kHz 30.0 MHz 0.4 % QuasiPeak 1.0 s 9 kHz LISN (ESH3-Z5)
 Average



MEASUREMENT RESULT: "AN18_fin"

2013-12-4 13:54

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.451684	42.40	12.3	57	14.4	QP	N	GND
2.339089	42.80	12.3	56	13.2	QP	N	GND
28.617181	40.90	12.0	60	19.1	QP	N	GND


MEASUREMENT RESULT: "AN18_fin2"

2013-12-4 13:54

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.451684	38.10	12.3	47	8.7	AV	N	GND
2.339089	37.20	12.3	46	8.8	AV	N	GND
4.858190	34.70	12.2	46	11.3	AV	N	GND

6. 6DB BANDWIDTH MEASUREMENT

6.1. Block Diagram of Test Setup



6.2. The Requirement For Section 15.247(a)(2)

Section 15.247(a)(2): Systems using digital modulation techniques may operate in the 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

6.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

6.4. Operating Condition of EUT

6.4.1. Setup the EUT and simulator as shown as Section 6.1.

6.4.2. Turn on the power of all equipment.

6.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2412-2462 and 2422-2452MHz. We select 2412MHz, 2437MHz, 2462MHz and 2422MHz, 2437MHz, 2452MHz TX frequency to transmit.

6.5. Test Procedure

1. Set resolution bandwidth (RBW) = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.6.Test Result

The test was performed with 802.11b			
Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
Low	2412	10.12	> 0.5MHz
Middle	2437	10.12	> 0.5MHz
High	2462	10.12	> 0.5MHz


The test was performed with 802.11g			
Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
Low	2412	16.60	> 0.5MHz
Middle	2437	16.60	> 0.5MHz
High	2462	16.60	> 0.5MHz

The test was performed with 802.11n (Bandwidth: 20 MHz)			
Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
Low	2412	17.88	> 0.5MHz
Middle	2437	17.88	> 0.5MHz
High	2462	17.88	> 0.5MHz

The test was performed with 802.11n (Bandwidth: 40 MHz)			
Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
Low	2422	36.56	> 0.5MHz
Middle	2437	36.56	> 0.5MHz
High	2452	36.56	> 0.5MHz


The spectrum analyzer plots are attached as below.

802.11b Channel Low 2412MHz



Date: 9.DEC.2013 08:51:30

802.11b Channel Middle 2437MHz



Date: 9.DEC.2013 08:55:52

The screenshot displays a spectrum analyzer interface. At the top, the following settings are visible: Ref 20 dBm, Att 50 dB, RBW 100 kHz, VBW 300 kHz, and SWT 2.5 ms. The center frequency is 2.462 GHz, and the span is 20 MHz. The signal is shown as a blue trace with a red horizontal line at -11.58 dBm. A green arrow points to the 3dB bandwidth measurement, which is indicated by a green bracket and labeled '3dB'. The peak level is marked as '1 PK MAXH' at -5.58 dBm. The 3dB bandwidth is marked as 'Delta 3 [T1]' at -5.95 dBm. The signal is identified as 'Delta 3 [T1]' at 5.560000000 MHz.

Date: 9.DEC.2013 09:00:52

Ref 20 dBm Att 50 dB

SWT 2.5 ms

Delta 3 [T1] -6.80 dB

13.880000000 MHz

Marker 1 [T1] -9.81 dBm

2.406440000 GHz

Delta 2 [T1] -6.61 dB

-2.720000000 MHz

1 PK MAXH


Center 2.412 GHz

2 MHz/

Span 20 MHz


Date: 9.DEC.2013 09:13:17

802.11g Channel Middle 2437MHz




Date: 9.DEC.2013 09:09:59

802.11g Channel High 2462MHz




Date: 9.DEC.2013 09:06:06

802.11n Channel Low 2412MHz (20MHz)




Date: 9.DEC.2013 09:20:18

802.11n Channel Middle 2437MHz(20MHz)




Date: 9.DEC.2013 09:21:27

802.11n Channel High 2462MHz(20MHz)




Date: 9.DEC.2013 09:24:55

802.11n Channel Low 2422MHz (40MHz)




Date: 9.DEC.2013 09:36:03

802.11n Channel Middle 2437MHz(40MHz)



Date: 9.DEC.2013 09:31:51


802.11n Channel High 2452MHz(40MHz)



Date: 9.DEC.2013 09:28:29

7. MAXIMUM PEAK OUTPUT POWER

7.1. Block Diagram of Test Setup



7.2. The Requirement For Section 15.247(b)(3)

Section 15.247(b)(3): For systems using digital modulation in the 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz bands: 1 Watt.

7.3. EUT Configuration on Measurement

The equipment is installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.4. Operating Condition of EUT

7.4.1. Setup the EUT and simulator as shown as Section 7.1.

7.4.2. Turn on the power of all equipment.

7.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2412-2462 and 2422-2452MHz. We select 2412MHz, 2437MHz, 2462MHz and 2422MHz, 2437MHz, 2452MHz TX frequency to transmit.

7.5. Test Procedure

7.5.1. The EUT was tested according to DTS test procedure of April 09, 2013 KDB558074 D01 DTS Meas Guidance v03 for compliance to FCC 47CFR 15.247 requirements.

7.5.2. The transmitter output was connected to the spectrum analyzer through a low loss cable.

7.5.3. Set RBW of spectrum analyzer to 1MHz and VBW to 3MHz.

7.5.4. Measurement the maximum peak output power.

7.6.Test Result

The test was performed with 802.11b				
Channel	Frequency (MHz)	Peak Output Power (dBm)	Peak Output Power (mW)	Limits dBm / W
Low	2412	9.11	8.15	30 dBm / 1 W
Middle	2437	8.76	7.52	30 dBm / 1 W
High	2462	8.08	6.43	30 dBm / 1 W


The test was performed with 802.11g				
Channel	Frequency (MHz)	Peak Output Power (dBm)	Peak Output Power (mW)	Limits dBm / W
Low	2412	7.94	6.22	30 dBm / 1 W
Middle	2437	7.81	6.04	30 dBm / 1 W
High	2462	7.47	5.58	30 dBm / 1 W

The test was performed with 802.11n (20MHz)				
Channel	Frequency (MHz)	Peak Output Power (dBm)	Peak Output Power (mW)	Limits dBm / W
Low	2412	7.73	5.93	30 dBm / 1 W
Middle	2437	7.19	5.24	30 dBm / 1 W
High	2462	6.71	4.69	30 dBm / 1 W

The test was performed with 802.11n (40MHz)				
Channel	Frequency (MHz)	Peak Output Power (dBm)	Peak Output Power (mW)	Limits dBm / W
Low	2422	7.48	5.60	30 dBm / 1 W
Middle	2437	7.08	5.11	30 dBm / 1 W
High	2452	6.11	4.08	30 dBm / 1 W


The spectrum analyzer plots are attached as below.

802.11b Channel Low 2412MHz




Date: 9.DEC.2013 09:50:20

802.11b Channel Middle 2437MHz




Date: 9.DEC.2013 09:51:10

802.11b Channel High 2462MHz




Date: 9.DEC.2013 09:53:50

802.11g Channel Low 2412MHz




Date: 9.DEC.2013 10:01:24

802.11g Channel Middle 2437MHz




Date: 9.DEC.2013 09:59:43

802.11g Channel High 2462MHz




Date: 9.DEC.2013 09:57:12

802.11n Channel Low 2412MHz (20MHz)




Date: 9.DEC.2013 10:03:56

802.11n Channel Middle 2437MHz (20MHz)




Date: 9.DEC.2013 10:05:28

802.11n Channel High 2462MHz (20MHz)




Date: 9.DEC.2013 10:07:13

802.11n Channel Low 2422MHz (40MHz)




Date: 9.DEC.2013 09:42:07

802.11n Channel Middle 2437MHz (40MHz)



Date: 9.DEC.2013 09:43:59

802.11n Channel High 2452MHz (40MHz)



Date: 9.DEC.2013 09:45:59

8. POWER SPECTRAL DENSITY MEASUREMENT

8.1. Block Diagram of Test Setup



8.2. The Requirement For Section 15.247(e)

Section 15.247(e): For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

8.3. EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

8.4. Operating Condition of EUT

8.4.1. Setup the EUT and simulator as shown as Section 8.1.

8.4.2. Turn on the power of all equipment.

8.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2412-2462 and 2422-2452MHz. We select 2412MHz, 2437MHz, 2462MHz and 2422MHz, 2437MHz, 2452MHz TX frequency to transmit.

8.5. Test Procedure

8.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

8.5.2. Measurement Procedure PKPSD:

This procedure must be used if maximum peak conducted output power was used to demonstrate compliance to the fundamental output power limit, and is optional if the maximum (average) conducted output power was used to demonstrate compliance.

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.

3. Set the RBW $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

8.5.3.Measurement the maximum power spectral density.

8.6.Test Result

The test was performed with 802.11b			
Channel	Frequency (MHz)	Power Spectral Density (dBm)	Limits (dBm)
Low	2412	-23.99	8 dBm
Middle	2437	-24.69	8 dBm
High	2462	-27.49	8 dBm


The test was performed with 802.11g			
Channel	Frequency (MHz)	Power Spectral Density (dBm)	Limits (dBm)
Low	2412	-26.26	8 dBm
Middle	2437	-26.62	8 dBm
High	2462	-27.19	8 dBm

The test was performed with 802.11n (20MHz)			
Channel	Frequency (MHz)	Power Spectral Density (dBm)	Limits (dBm)
Low	2412	-26.17	8 dBm
Middle	2437	-27.60	8 dBm
High	2462	-27.19	8 dBm

The test was performed with 802.11n (40MHz)			
Channel	Frequency (MHz)	Power Spectral Density (dBm)	Limits (dBm)
Low	2422	-28.45	8 dBm
Middle	2437	-29.09	8 dBm
High	2452	-29.40	8 dBm


The spectrum analyzer plots are attached as below.

802.11b Channel Low 2412MHz




Date: 9.DEC.2013 10:21:39

802.11b Channel Middle 2437MHz




Date: 9.DEC.2013 10:22:44

802.11b Channel High 2462MHz




Date: 9.DEC.2013 10:24:06

802.11g Channel Low 2412MHz




Date: 9.DEC.2013 10:28:38

802.11g Channel Middle 2437MHz




Date: 9.DEC.2013 10:27:16

802.11g Channel High 2462MHz




Date: 9.DEC.2013 10:26:01

802.11n Channel Low 2412MHz (20MHz)




Date: 9.DEC.2013 10:19:07

802.11n Channel Middle 2437MHz (20MHz)




Date: 9.DEC.2013 10:17:45

802.11n Channel High 2462MHz(20MHz)




Date: 9.DEC.2013 10:16:01

802.11n Channel Low 2422MHz (40MHz)




Date: 9.DEC.2013 10:30:47

802.11n Channel Middle 2437MHz(40MHz)



Date: 9.DEC.2013 10:32:17

802.11n Channel High 2452MHz(40MHz)



Date: 9.DEC.2013 10:34:03

9. BAND EDGE COMPLIANCE TEST

9.1. Block Diagram of Test Setup



9.2. The Requirement For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

9.3. EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

9.4. Operating Condition of EUT

9.4.1. Setup the EUT and simulator as shown as Section 9.1.

9.4.2. Turn on the power of all equipment.

9.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2412-2462 and 2422-2452MHz MHz. We select 2412MHz, 2462MHz and 2422MHz, 2452MHz TX frequency to transmit.

9.5. Test Procedure

Conducted Band Edge:

9.5.1. The transmitter output was connected to the spectrum analyzer via a low loss cable.

9.5.2. Set RBW of spectrum analyzer to 100kHz and VBW to 300kHz.

Radiate Band Edge:

9.5.3. The EUT is placed on a turntable, which is 0.8m above the ground plane and worked at highest radiated power.

9.5.4. The turntable was rotated for 360 degrees to determine the position of maximum emission level.

9.5.5. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.

9.5.6. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:

9.5.7. RBW=1MHz, VBW=1MHz

9.5.8. The band edges were measured and recorded.

9.6. Test Result


The test was performed with 802.11b		
Frequency (MHz)	Result of Band Edge (dBc)	Limit of Band Edge (dBc)
2412	44.61	> 20dBc
2462	52.87	> 20dBc

The test was performed with 802.11g		
Frequency (MHz)	Result of Band Edge (dBc)	Limit of Band Edge (dBc)
2412	34.95	> 20dBc
2462	40.66	> 20dBc

The test was performed with 802.11n (20MHz)		
Frequency (MHz)	Result of Band Edge (dBc)	Limit of Band Edge (dBc)
2412	36.25	> 20dBc
2462	41.87	> 20dBc


The test was performed with 802.11n (40MHz)		
Frequency (MHz)	Result of Band Edge (dBc)	Limit of Band Edge (dBc)
2422	31.15	> 20dBc
2452	37.70	> 20dBc

802.11b Channel Low 2412MHz




Date: 25.JAN.2014 11:30:33

802.11b Channel High 2462MHz




Date: 25.JAN.2014 11:31:15

802.11g Channel Low 2412MHz




Date: 25.JAN.2014 11:33:12

802.11g Channel High 2462MHz




Date: 25.JAN.2014 11:32:11

802.11n Channel Low 2412MHz (20MHz)




Date: 25.JAN.2014 11:34:58

802.11n Channel High 2462MHz (20MHz)




Date: 25.JAN.2014 11:35:41

802.11n Channel Low 2422MHz (40MHz)



Date: 25.JAN.2014 11:28:23

802.11n Channel High 2452MHz (40MHz)



Date: 25.JAN.2014 11:29:10

Radiated Band Edge Result

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

3. Display the measurement of peak values.



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: STAR #4181

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Nummy 3G serials-AX1 SPEC

Mode: TX Channel 1(802.11b)

Model: Nummy 3G

Manufacturer: AINOL

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 13/12/12/

Time: 10/30/32

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20132564



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2310.000	42.33	-6.99	35.34	74.00	-38.66	peak			
2	2310.000	34.80	-6.99	27.81	54.00	-26.19	AVG			
3	2390.000	46.09	-6.78	39.31	74.00	-34.69	peak			
4	2390.000	39.20	-6.78	32.42	54.00	-21.58	AVG			

Job No.: STAR #4180

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Nummy 3G serials-AX1 SPEC

Mode: TX Channel 1(802.11b)

Model: Nummy 3G

Manufacturer: AINOL

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 13/12/12/

Time: 10/29/37

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20132564



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2310.000	42.94	-6.99	35.95	74.00	-38.05	peak			
2	2310.000	35.11	-6.99	28.12	54.00	-25.88	AVG			
3	2390.000	47.75	-6.78	40.97	74.00	-33.03	peak			
4	2390.000	40.57	-6.78	33.79	54.00	-20.21	AVG			

Job No.: STAR #4190

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Nummy 3G serials-AX1 SPEC

Mode: TX Channel 11(802.11b)

Model: Nummy 3G

Manufacturer: AINOL

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 13/12/12/

Time: 10/48/47

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20132564



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	48.94	-6.54	42.40	74.00	-31.60	peak			
2	2483.500	41.14	-6.54	34.60	54.00	-19.40	AVG			
3	2500.000	44.37	-6.50	37.87	74.00	-36.13	peak			
4	2500.000	38.10	-6.50	31.60	54.00	-22.40	AVG			

Job No.: STAR #4191

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Nummy 3G serials-AX1 SPEC

Mode: TX Channel 11(802.11b)

Model: Nummy 3G

Manufacturer: AINOL

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 13/12/12/

Time: 10/50/22

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20132564



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	51.51	-6.54	44.97	74.00	-29.03	peak			
2	2483.500	45.25	-6.54	38.71	54.00	-15.29	AVG			
3	2500.000	47.26	-6.50	40.76	74.00	-33.24	peak			
4	2500.000	42.00	-6.50	35.50	54.00	-18.50	AVG			

Job No.: STAR #4182

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Nummy 3G serials-AX1 SPEC

Mode: TX Channel 1(802.11g)

Model: Nummy 3G

Manufacturer: AINOL

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 13/12/12/

Time: 10/31/49

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20132564



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2310.000	42.73	-6.99	35.74	74.00	-38.26	peak			
2	2310.000	35.80	-6.99	28.81	54.00	-25.19	AVG			
3	2390.000	54.85	-6.78	48.07	74.00	-25.93	peak			
4	2390.000	45.25	-6.78	38.47	54.00	-15.53	AVG			

Job No.: STAR #4183

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Nummy 3G serials-AX1 SPEC

Mode: TX Channel 1(802.11g)

Model: Nummy 3G

Manufacturer: AINOL

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 13/12/12/

Time: 10/33/03

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20132564




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2310.000	42.63	-6.99	35.64	74.00	-38.36	peak			
2	2310.000	38.55	-6.99	31.56	54.00	-22.44	AVG			
3	2390.000	54.18	-6.78	47.40	74.00	-26.60	peak			
4	2390.000	47.60	-6.78	40.82	54.00	-13.18	AVG			

Job No.: STAR #4189
Standard: FCC PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Nummy 3G serials-AX1 SPEC
Mode: TX Channel 11(802.11g)
Model: Nummy 3G
Manufacturer: AINOL

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 13/12/12/
Time: 10/47/26
Engineer Signature:
Distance: 3m

Note: Report No.:ATE20132564



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	61.10	-6.54	54.56	74.00	-19.44	peak			
2	2483.500	53.80	-6.54	47.26	54.00	-6.74	AVG			
3	2500.000	45.14	-6.50	38.64	74.00	-35.36	peak			
4	2500.000	37.00	-6.50	30.50	54.00	-23.50	AVG			

Job No.: STAR #4188

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Nummy 3G serials-AX1 SPEC

Mode: TX Channel 11(802.11g)

Model: Nummy 3G

Manufacturer: AINOL

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 13/12/12/

Time: 10/46/22

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20132564



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	63.23	-6.54	56.69	74.00	-17.31	peak			
2	2483.500	56.70	-6.54	50.16	54.00	-3.84	AVG			
3	2500.000	46.28	-6.50	39.78	74.00	-34.22	peak			
4	2500.000	39.14	-6.50	32.64	54.00	-21.36	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: STAR #4185

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Nummy 3G serials-AX1 SPEC

Mode: TX Channel 1(802.11n20)

Model: Nummy 3G

Manufacturer: AINOL

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 13/12/12/

Time: 10/37/32

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20132564



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2310.000	43.29	-6.99	36.30	74.00	-37.70	peak			
2	2310.000	35.58	-6.99	28.59	54.00	-25.41	AVG			
3	2390.000	43.25	-6.78	36.47	74.00	-37.53	peak			
4	2390.000	46.87	-6.78	40.09	54.00	-13.91	AVG			

Job No.: STAR #4184

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Nummy 3G serials-AX1 SPEC

Mode: TX Channel 1(802.11n20)

Model: Nummy 3G

Manufacturer: AINOL

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 13/12/12/

Time: 10/36/32

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20132564



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2310.000	42.62	-6.99	35.63	74.00	-38.37	peak			
2	2310.000	36.00	-6.99	29.01	54.00	-24.99	AVG			
3	2390.000	56.47	-6.78	49.69	74.00	-24.31	peak			
4	2390.000	48.90	-6.78	42.12	54.00	-11.88	AVG			

Job No.: STAR #4186

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Nummy 3G serials-AX1 SPEC

Mode: TX Channel 11(802.11n20)

Model: Nummy 3G

Manufacturer: AINOL

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 13/12/12/

Time: 10/42/15

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20132564



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	56.29	-6.54	49.75	74.00	-24.25	peak			
2	2483.500	49.78	-6.54	43.24	54.00	-10.76	AVG			
3	2500.000	46.37	-6.50	39.87	74.00	-34.13	peak			
4	2500.000	38.97	-6.50	32.47	54.00	-21.53	AVG			

Job No.: STAR #4187

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Nummy 3G serials-AX1 SPEC

Mode: TX Channel 11(802.11n20)

Model: Nummy 3G

Manufacturer: AINOL

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 13/12/12/

Time: 10/43/38

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20132564




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	58.13	-6.54	51.59	74.00	-22.41	peak			
2	2483.500	51.45	-6.54	44.91	54.00	-9.09	AVG			
3	2500.000	48.08	-6.50	41.58	74.00	-32.42	peak			
4	2500.000	42.10	-6.50	35.60	54.00	-18.40	AVG			

Job No.: STAR #4193
Standard: FCC PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Nummy 3G serials-AX1 SPEC
Mode: TX Channel 3(802.11n)40MHz
Model: Nummy 3G
Manufacturer: AINOL

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 13/12/12/
Time: 11/01/15
Engineer Signature:
Distance: 3m

Note: Report No.:ATE20132564



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2310.000	42.66	-6.99	35.67	74.00	-38.33	peak			
2	2310.000	37.41	-6.99	30.42	54.00	-23.58	AVG			
3	2390.000	48.48	-6.78	41.70	74.00	-32.30	peak			
4	2390.000	40.55	-6.78	33.77	54.00	-20.23	AVG			

Job No.: STAR #4192

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Nummy 3G serials-AX1 SPEC

Mode: TX Channel 3(802.11n)40MHz

Model: Nummy 3G

Manufacturer: AINOL

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 13/12/12/

Time: 11/00/13

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20132564



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2310.000	43.53	-6.99	36.54	74.00	-37.46	peak			
2	2310.000	36.47	-6.99	29.48	54.00	-24.52	AVG			
3	2390.000	51.36	-6.78	44.58	74.00	-29.42	peak			
4	2390.000	43.80	-6.78	37.02	54.00	-16.98	AVG			

Job No.: STAR #4194

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Nummy 3G serials-AX1 SPEC

Mode: TX Channel 9(802.11n)40MHz

Model: Nummy 3G

Manufacturer: AINOL

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 13/12/12/

Time: 11/02/23

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20132564



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	47.18	-6.54	40.64	74.00	-33.36	peak			
2	2483.500	40.39	-6.54	33.85	54.00	-20.15	AVG			
3	2500.000	44.27	-6.50	37.77	74.00	-36.23	peak			
4	2500.000	35.99	-6.50	29.49	54.00	-24.51	AVG			

Job No.: STAR #4195

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Nummy 3G serials-AX1 SPEC

Mode: TX Channel 9(802.11n)40MHz

Model: Nummy 3G

Manufacturer: AINOL

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 13/12/12/

Time: 11/03/25

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20132564




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	52.16	-6.54	45.62	74.00	-28.38	peak			
2	2483.500	47.89	-6.54	41.35	54.00	-12.65	AVG			
3	2500.000	46.30	-6.50	39.80	74.00	-34.20	peak			
4	2500.000	39.64	-6.50	33.14	54.00	-20.86	AVG			


10.RADIATED SPURIOUS EMISSION TEST

10.1.Block Diagram of Test Setup

10.1.1.Block diagram of connection between the EUT and peripherals



10.1.2.Semi-Anechoic Chamber Test Setup Diagram



10.2.The Limit For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the

transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

10.3.Restricted bands of operation

10.3.1.FCC Part 15.205 Restricted bands of operation

(a) Except as shown in paragraph (d) of this section, Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510

²Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emission appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000MHz, Compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

10.4.Configuration of EUT on Measurement

The equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

10.5. Operating Condition of EUT

10.5.1. Setup the EUT and simulator as shown as Section 10.1.

10.5.2. Turn on the power of all equipment.

10.5.3. Let the EUT work in TX modes measure it. The transmit frequency are 2412-2462 and 2422-2452MHz. We select 2412MHz, 2437MHz, 2462MHz and 2422MHz, 2437MHz, 2452MHz TX frequency to transmit.

10.6. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4: 2009 on radiated emission measurement. The EUT was tested in 3 orthogonal planes.

The worst-case data rate for this channel to be 1Mbps for 802.11b mode and 6Mbps for 802.11g mode and 150Mbps for 802.11n mode, based on previous with 802.11 WLAN product design architectures.

The bandwidth of test receiver is set at 9kHz in below 30MHz. and set at 120kHz in 30-1000MHz, and 1MHz in above 1000MHz.

The frequency range from 9kHz to 25GHz is checked.

The final measurement in band 9-90kHz, 110-490kHz and above 1000MHz is performed with Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.

The field strength is calculated by adding the antenna factor, and cable loss, and subtracting the amplifier gain from the measured reading. The basic equation calculation is as follows: $\text{Result} = \text{Reading} + \text{Corrected Factor}$

Where $\text{Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$

10.7. The Field Strength of Radiation Emission Measurement Results

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.

2. *: Denotes restricted band of operation.

3. The fundamental radiated emissions were reduced by Band Reject Filter in the attached plots.

4. The EUT is tested radiation emission at each test mode(802.11 b/g/n) in three axes. The worst emissions are reported in all test mode and channels.

5. The radiation emissions from 18-25GHz are not reported, because the test values lower than the limits of 20dB.

Below 1G



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: STAR #4132
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Nummy 3G serials-AX1 SPEC
Mode: TX Channel 1(802.11b)
Model: Nummy 3G
Manufacturer: AINOL

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 13/12/12/
Time: 9/52/10
Engineer Signature:
Distance: 3m

Note: Report No.:ATE20132564




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	34.0365	54.94	-19.17	35.77	40.00	-4.23	peak			
2	69.1141	58.64	-21.32	37.32	40.00	-2.68	peak			
3	266.6089	61.79	-18.81	42.98	46.00	-3.02	peak			

Job No.: STAR #4133
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Nummy 3G serials-AX1 SPEC
Mode: TX Channel 1(802.11b)
Model: Nummy 3G
Manufacturer: AINOL

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 13/12/12/
Time: 9/52/50
Engineer Signature:
Distance: 3m

Note: Report No.:ATE20132564



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	34.3964	56.28	-19.30	36.98	40.00	-3.02	peak			
2	45.3755	55.33	-20.40	34.93	40.00	-5.07	peak			
3	69.1141	57.97	-21.32	36.65	40.00	-3.35	peak			

Job No.: STAR #4135

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Nummy 3G serials-AX1 SPEC

Mode: TX Channel 6(802.11b)

Model: Nummy 3G

Manufacturer: AINOL

Polarization: Horizontal

Power Source: AC 120V/60Hz


Date: 13/12/12/

Time: 9/54/08

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20132564




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	33.9174	55.91	-19.14	36.77	40.00	-3.23	peak			
2	69.1141	58.55	-21.32	37.23	40.00	-2.77	peak			
3	264.7457	61.85	-18.87	42.98	46.00	-3.02	peak			

Job No.: STAR #4134
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Nummy 3G serials-AX1 SPEC
Mode: TX Channel 6(802.11b)
Model: Nummy 3G
Manufacturer: AINOL

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 13/12/12/
Time: 9/53/32
Engineer Signature:
Distance: 3m

Note: Report No.:ATE20132564




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	34.3963	56.75	-19.30	37.45	40.00	-2.55	peak			
2	45.6948	55.46	-20.43	35.03	40.00	-4.97	peak			
3	69.1140	58.18	-21.32	36.86	40.00	-3.14	peak			

Job No.: STAR #4136
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Nummy 3G serials-AX1 SPEC
Mode: TX Channel 11(802.11b)
Model: Nummy 3G
Manufacturer: AINOL

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 13/12/12/
Time: 9/55/05
Engineer Signature:
Distance: 3m

Note: Report No.:ATE20132564




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	34.0363	54.99	-19.17	35.82	40.00	-4.18	peak			
2	69.1140	57.61	-21.32	36.29	40.00	-3.71	peak			
3	264.7456	62.23	-18.87	43.36	46.00	-2.64	peak			

Job No.: STAR #4137
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Nummy 3G serials-AX1 SPEC
Mode: TX Channel 11(802.11b)
Model: Nummy 3G
Manufacturer: AINOL

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 13/12/12/
Time: 9/55/37
Engineer Signature:
Distance: 3m

Note: Report No.:ATE20132564




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	34.3964	56.80	-19.30	37.50	40.00	-2.50	peak			
2	60.0691	57.23	-21.09	36.14	40.00	-3.86	peak			
3	69.1141	58.12	-21.32	36.80	40.00	-3.20	peak			

Job No.: STAR #4139
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Nummy 3G serials-AX1 SPEC
Mode: TX Channel 1(802.11g)
Model: Nummy 3G
Manufacturer: AINOL

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 13/12/12/
Time: 9/56/51
Engineer Signature:
Distance: 3m

Note: Report No.:ATE20132564



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	33.9174	55.14	-19.14	36.00	40.00	-4.00	peak			
2	69.1140	57.16	-21.32	35.84	40.00	-4.16	peak			
3	267.5455	61.38	-18.78	42.60	46.00	-3.40	peak			

Job No.: STAR #4138

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Nummy 3G serials-AX1 SPEC

Mode: TX Channel 1(802.11g)

Model: Nummy 3G

Manufacturer: AINOL

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 13/12/12/

Time: 9/56/12

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20132564




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	34.5172	56.08	-19.34	36.74	40.00	-3.26	peak			
2	63.0915	55.21	-21.15	34.06	40.00	-5.94	peak			
3	69.1140	58.72	-21.32	37.40	40.00	-2.60	peak			

Job No.: STAR #4140
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Nummy 3G serials-AX1 SPEC
Mode: TX Channel 6(802.11g)
Model: Nummy 3G
Manufacturer: AINOL

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 13/12/12/
Time: 9/57/29
Engineer Signature:
Distance: 3m

Note: Report No.:ATE20132564



Job No.: STAR #4141

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Nummy 3G serials-AX1 SPEC

Mode: TX Channel 6(802.11g)

Model: Nummy 3G

Manufacturer: AINOL

Polarization: Vertical

Power Source: AC 120V/60Hz


Date: 13/12/12/

Time: 9/58/14

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20132564




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	34.3964	56.26	-19.30	36.96	40.00	-3.04	peak			
2	69.1141	58.77	-21.32	37.45	40.00	-2.55	peak			
3	81.2117	57.54	-21.42	36.12	40.00	-3.88	peak			

Job No.: STAR #4143
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Nummy 3G serials-AX1 SPEC
Mode: TX Channel 11(802.11g)
Model: Nummy 3G
Manufacturer: AINOL

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 13/12/12/
Time: 10/00/00
Engineer Signature:
Distance: 3m

Note: Report No.:ATE20132564



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	34.2760	52.12	-19.26	32.86	40.00	-7.14	peak			
2	81.2116	58.73	-21.42	37.31	40.00	-2.69	peak			
3	264.7456	61.31	-18.87	42.44	46.00	-3.56	peak			