

FCC RF Test Report

APPLICANT : OnePlus Technology (Shenzhen) Co., Ltd.
EQUIPMENT : Smart Phone
BRAND NAME : ONEPLUS
MODEL NAME : KB2005
FCC ID : 2ABZ2-EF009
STANDARD : 47 CFR Part 2, 27D
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Jun. 15, 2020 and completely tested on Jul. 12, 2020. We, Sporton International (ShenZhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (ShenZhen) Inc., the test report shall not be reproduced except in full.



Reviewed by: Derreck Chen / Supervisor



Approved by: Eric Shih / Manager



Sporton International (ShenZhen) Inc.

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055
People's Republic of China

TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT	6
1.6 Maximum Conducted power, Frequency Tolerance and Emission Designator	6
1.7 Testing Site	7
1.8 Test Software.....	7
1.9 Applied Standards	8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	9
2.1 Test Mode	9
2.2 Connection Diagram of Test System.....	10
2.3 Support Unit used in test configuration and system	10
2.4 Measurement Results Explanation Example.....	10
2.5 Frequency List of Low/Middle/High Channels	11
3 CONDUCTED TEST ITEMS	12
3.1 Measuring Instruments	12
3.2 Test Setup	12
3.3 Test Result of Conducted Test	12
3.4 Conducted Output Power Measurement	13
3.5 Peak-to-Average Ratio	14
3.6 EIRP Power Density	15
3.7 Occupied Bandwidth.....	16
3.8 Conducted Band Edge Measurement	17
3.9 Conducted Spurious Emission Measurement	18
3.10 Frequency Stability Measurement.....	19
4 RADIATED TEST ITEMS	20
4.1 Measuring Instruments	20
4.2 Test Setup	20
4.3 Test Result of Radiated Test	20
4.4 Radiated Spurious Emission Measurement	21
5 LIST OF MEASURING EQUIPMENT	22
6 UNCERTAINTY OF EVALUATION	23
APPENDIX A. TEST RESULTS OF CONDUCTED TEST	
APPENDIX B. TEST RESULTS OF RADIATED TEST	
APPENDIX C. TEST SETUP PHOTOGRAPHS	

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG061509-03F	Rev. 01	Initial issue of report	Aug. 25, 2020

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
3.5	-	Peak-to-Average Ratio	<13dB	N/A	Reporting only
3.6	§27.50 (a)(3)	EIRP	EIRP < 250mW/5MHz	PASS	-
3.7	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.8	§2.1051 §27.53 (a)(4)	Conducted Band Edge Measurement	Refer standard	PASS	-
3.9	§2.1051 §27.53 (a)(4)	Conducted Spurious Emission	< 70+10log ₁₀ (P[Watts])	PASS	-
3.10	§2.1055 §27.54	Frequency Stability Temperature & Voltage	Within the band	PASS	-
4.4	§2.1053 §27.53 (a)(4)	Radiated Spurious Emission	< 70+10log ₁₀ (P[Watts])	PASS	Under limit 14.43 dB at 11526.250 MHz

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Applicant

OnePlus Technology (Shenzhen) Co., Ltd.

18C02, 18C03, 18C04,18C05, Shum Yip Terra Building, Binhe Avenue North, Futian District, Shenzhen,Guangdong,China

1.2 Manufacturer

OnePlus Technology (Shenzhen) Co., Ltd.

18C02, 18C03, 18C04,18C05, Shum Yip Terra Building, Binhe Avenue North, Futian District, Shenzhen,Guangdong,China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Smart Phone
Brand Name	ONEPLUS
Model Name	KB2005
FCC ID	2ABZ2-EF009
EUT supports Radios application	CDMA/GSM/WCDMA/LTE/5G NR WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 2.4GHz 802.11ax HE20/HE40 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 WLAN 5GHz 802.11ax HE20/HE40/HE80 Bluetooth BR / EDR / LE / ANT+ GNSS/NFC
IMEI Code	Conducted: 990016770027769 Radiation: 990016770042024
HW Version	13
SW Version	OXYGEN OS 11. KB05AA
EUT Stage	Production Unit

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. This is a variant report for KB2005. For model change note, Please refer to the product equality declaration exhibit submitted. According to the PED, the change has no influence on the test results, all the test results are leveraged from original report FG061509F.

1.4 Product Specification of Equipment Under Test

Product Feature	
Tx Frequency	LTE Band 30 : 2307.5 MHz ~ 2312.5 MHz
Rx Frequency	LTE Band 30 : 2352.5 MHz ~ 2357.5 MHz
Bandwidth	5MHz / 10MHz
Maximum Output Power to Antenna	Top Antenna: LTE Band 30 : 20.46 dBm Bottom Antenna: LTE Band 30 : 22.41 dBm
Antenna Gain	Top Antenna: LTE Band 30 : -2 dBi Bottom Antenna: LTE Band 30 : -1.0 dBi
Type of Modulation	QPSK / 16QAM / 64QAM / 256QAM

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum EIRP, Frequency Tolerance and Emission Designator

LTE Band 30		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
5	2307.5 ~ 2312.5	4M51G7D	-	0.1377	4M50W7D	-	0.0893
10	2310.0	9M03G7D	0.0006	0.1384	8M95W7D	-	0.091
LTE Band 30		64QAM					
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)			
5	2307.5 ~ 2312.5	4M50W7D	-	0.0893			
10	2310.0	9M01W7D		0.0910			

1.7 Testing Site

<FCC>-SZ

Sporton International (Shenzhen) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International (Shenzhen) Inc.		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	TH01-SZ	CN1256	421272

Test Firm	Sporton International (Shenzhen) Inc.		
Test Site Location	No. 3 Bldg the third floor of south, Shahe River west, Fengzeyuan Warehouse, Nanshan Shenzhen, 518055 People's Republic of China TEL: +86-755-33202398		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH02-SZ	CN1256	421272

1.8 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH02-SZ	AUDIX	E3	6.2009-8-24a

1.9 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, Part 27(D)
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 Power Meas License Digital Systems D01 v03r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test


2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.

Conducted Test Cases	Band	Bandwidth (MHz)						Modulation				RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	256QAM	1	Half	Full	L	M	H
Max. Output Power	30	-	-	V		-	-	V	V	V	V	V	V	V	V	V	V
		-	-		V	-	-	V	V	V	V	V	V	V		V	
Peak-to-Average Ratio	30	-	-		V	-	-	V	V	V		V		V		V	
E.I.R.P	30	-	-	V		-	-	V	V	V		V			V	V	V
		-	-		V	-	-	V	V	V		V				V	
26dB and 99% Bandwidth	30	-	-	V		-	-	V	V	V				V	V	V	V
		-	-		V	-	-	V	V	V				V		V	
Conducted Band Edge	30	-	-	V		-	-	V	V	V		V		V	V		V
		-	-		V	-	-	V	V	V		V		V		V	
Conducted Spurious Emission	30	-	-	V		-	-	V	V	V		V			V	V	V
		-	-		V	-	-	V	V	V		V				V	
Frequency Stability	30	-	-		V	-	-	V						V		V	
Radiated Spurious Emission	30	-	-	V		-	-	V				V			V	V	V
					V			V				V				V	
Note	- The mark "v" means that this configuration is chosen for testing - The mark "-" means that this bandwidth is not supported. - The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported. - For QAM modulation mode, the whole testing has assessed 16QAM&64QAM mode by referring to their higher conducted power.																

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	Power Supply	GWINSTEK	PSS-2002	N/A	N/A	Unshielded, 1.8 m
2.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
3.	Fixture	INTEL	NGFF Card Carrier	N/A	N/A	N/A

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 5.0 dB and 10dB attenuator.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 5.0 + 10 = 15.0 \text{ (dB)} \end{aligned}$$

2.5 Frequency List of Low/Middle/High Channels

LTE Band 30 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	-	27710	-
	Frequency	-	2310	-
5	Channel	27685	27710	27735
	Frequency	2307.5	2310	2312.5


3 Conducted Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied / 26dB Bandwidth ,Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power Measurement

3.4.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.

3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.6 EIRP

3.6.1 Description of EIRP

For mobile and portable stations transmitting in the 2305-2315 MHz band or the 2350-2360 MHz band, the average EIRP must not exceed 50 milliwatts within any 1 megahertz of authorized bandwidth, *except that* for mobile and portable stations compliant with 3GPP LTE standards or another advanced mobile broadband protocol that avoids concentrating energy at the edge of the operating band the average EIRP must not exceed 250 milliwatts within any 5 megahertz of authorized bandwidth but may exceed 50 milliwatts within any 1 megahertz of authorized bandwidth. For mobile and portable stations using time division duplexing (TDD) technology, the duty cycle must not exceed 38 percent in the 2305-2315 MHz and 2350-2360 MHz bands. Mobile and portable stations using FDD technology are restricted to transmitting in the 2305-2315 MHz band. Power averaging shall not include intervals in which the transmitter is off.

3.6.2 Test Procedures

1. According to KDB 412172 D01 Power Approach,
2. $EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where
 P_T = transmitter output power in dBm
 G_T = gain of the transmitting antenna in dBi
 L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.7 Occupied Bandwidth

3.7.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.8 Conducted Band Edge Measurement

3.8.1 Description of Conducted Band Edge Measurement

27.53 (a)(4)

For mobile and portable stations operating in the 2305-2315 MHz and 2350-2360 MHz bands:

- (i) By a factor of not less than: $43 + 10 \log (P)$ dB on all frequencies between 2305 and 2320 MHz and on all frequencies between 2345 and 2360 MHz that are outside the licensed band(s) of operation, not less than $55 + 10 \log (P)$ dB on all frequencies between 2320 and 2324 MHz and on all frequencies between 2341 and 2345 MHz, not less than $61 + 10 \log (P)$ dB on all frequencies between 2324 and 2328 MHz and on all frequencies between 2337 and 2341 MHz, and not less than $67 + 10 \log (P)$ dB on all frequencies between 2328 and 2337 MHz;
- (ii) By a factor of not less than $43 + 10 \log (P)$ dB on all frequencies between 2300 and 2305 MHz, $55 + 10 \log (P)$ dB on all frequencies between 2296 and 2300 MHz, $61 + 10 \log (P)$ dB on all frequencies between 2292 and 2296 MHz, $67 + 10 \log (P)$ dB on all frequencies between 2288 and 2292 MHz, and $70 + 10 \log (P)$ dB below 2288 MHz;
- (iii) By a factor of not less than $43 + 10 \log (P)$ dB on all frequencies between 2360 and 2365 MHz, and not less than $70 + 10 \log (P)$ dB above 2365 MHz.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set RBW $\geq 1\%$ EBW in the 1MHz band immediately outside and adjacent to the band edge.
5. Beyond the 1 MHz band from the band edge, RBW=1MHz was used or a narrower RBW was used and the measured power was integrated over the full required measurement bandwidth of 1 MHz.
6. Set spectrum analyzer with RMS detector.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
8. Checked that all the results comply with the emission limit line.

Example:

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)} = -13\text{dBm}.$$

3.9 Conducted Spurious Emission Measurement

3.9.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $70 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 9 kHz up to a frequency including its 10^{th} harmonic.

3.9.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Taking the record of maximum spurious emission.
9. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
10. The limit line is derived from $70 + 10\log(P)$ dB below the transmitter power P(Watts)
= $P(W) - [70 + 10\log(P)]$ (dB)
= $[30 + 10\log(P)]$ (dBm) - $[70 + 10\log(P)]$ (dB)
= -40dBm

3.10 Frequency Stability Measurement

3.10.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.10.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.10.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5.
2. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

4.4 Radiated Spurious Emission Measurement

4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI/TIA-603-E. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $70 + 10 \log (P)$ dB.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.

$$\text{EIRP (dBm)} = \text{S.G. Power} - \text{Tx Cable Loss} + \text{Tx Antenna Gain}$$

$$\text{ERP (dBm)} = \text{EIRP} - 2.15$$

10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

The limit line is derived from $70 + 10\log(P)$ dB below the transmitter power P(Watts)

$$= P(W) - [70 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [70 + 10\log(P)] \text{ (dB)}$$

$$= -40\text{dBm}.$$

5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 17, 2020	Jul. 09, 2020	Apr. 16, 2021	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhanggroup	LP-150U	H2014081803	-40~+150°C	Dec. 23, 2019	Jul. 09, 2020	Dec. 22, 2020	Conducted (TH01-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Apr. 17, 2020	Jul. 12, 2020	Apr. 16, 2021	Radiation (03CH02-SZ)
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz~2GHz	Jul. 16, 2019	Jul. 12, 2020	Jul. 15, 2020	Radiation (03CH02-SZ)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00119436	1GHz~18GHz	Jul. 26, 2019	Jul. 12, 2020	Jul. 25, 2020	Radiation (03CH02-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz~40GHz	Apr. 17, 2020	Jul. 12, 2020	Apr. 16, 2021	Radiation (03CH02-SZ)
LF Amplifier	Burgeon	BPA-530	102211	0.01~3000Mhz	Oct. 18,2019	Jul. 12, 2020	Oct. 17,2020	Radiation (03CH02-SZ)
HF Amplifier	KEYSIGHT	83017A	MY53270105	0.5GHz~26.5Ghz	Oct. 18,2019	Jul. 12, 2020	Oct. 17,2020	Radiation (03CH02-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 22, 2019	Jul. 12, 2020	Jul. 21, 2020	Radiation (03CH02-SZ)
AC Power Source	Chroma	61601	616010002470	N/A	NCR	Jul. 12, 2020	NCR	Radiation (03CH02-SZ)
Turn Table	Chaintek	T-200	N/A	0~360 degree	NCR	Jul. 12, 2020	NCR	Radiation (03CH02-SZ)
Antenna Mast	Chaintek	MBS-400	N/A	1 m~4 m	NCR	Jul. 12, 2020	NCR	Radiation (03CH02-SZ)

NCR: No Calibration Required

6 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage $K=2$ to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.47dB
---	--------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.31dB
---	--------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.72dB
---	--------



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

Top antenna:

BW [MHz]	Modulation	RB Size	RB Offset	Lowest	Middle	Highest
Channel				27710		
Frequency (MHz)				2310		
10	QPSK	1	0		20.46	
10	QPSK	1	25		20.00	
10	QPSK	1	49		20.34	
10	QPSK	25	0		19.44	
10	QPSK	25	12		19.47	
10	QPSK	25	25		19.45	
10	QPSK	50	0		19.46	
10	16QAM	1	0		19.83	
10	16QAM	1	25		19.79	
10	16QAM	1	49		19.73	
10	16QAM	25	0		18.40	
10	16QAM	25	12		18.46	
10	16QAM	25	25		18.46	
10	16QAM	50	0		18.44	
10	64QAM	1	0		18.65	
10	64QAM	1	25		18.69	
10	64QAM	1	49		18.61	
10	64QAM	25	0		17.46	
10	64QAM	25	12		17.50	
10	64QAM	25	25		17.51	
10	64QAM	50	0		17.49	
10	256QAM	1	0		15.71	
10	256QAM	1	25		15.86	
10	256QAM	1	49		15.77	
10	256QAM	25	0		15.61	



10	256QAM	25	12		15.76	
10	256QAM	25	25		15.69	
10	256QAM	50	0		15.62	
Channel				27685	27710	27735
Frequency (MHz)				2307.5	2310	2312.5
5	QPSK	1	0	20.30	20.32	20.39
5	QPSK	1	12	20.42	20.45	20.44
5	QPSK	1	24	20.41	20.38	20.34
5	QPSK	12	0	19.40	19.45	19.46
5	QPSK	12	7	19.47	19.49	19.49
5	QPSK	12	13	19.48	19.42	19.51
5	QPSK	25	0	19.47	19.41	19.47
5	16QAM	1	0	19.61	19.69	19.72
5	16QAM	1	12	19.72	19.78	19.75
5	16QAM	1	24	19.82	19.74	19.72
5	16QAM	12	0	18.40	18.47	18.47
5	16QAM	12	7	18.57	18.49	18.51
5	16QAM	12	13	18.53	18.48	18.50
5	16QAM	25	0	18.47	18.43	18.48
5	64QAM	1	0	18.58	18.59	18.64
5	64QAM	1	12	18.67	18.68	18.67
5	64QAM	1	24	18.73	18.66	18.65
5	64QAM	12	0	17.47	17.50	17.54
5	64QAM	12	7	17.55	17.56	17.56
5	64QAM	12	13	17.59	17.53	17.55
5	64QAM	25	0	17.52	17.47	17.51
5	256QAM	1	0	15.80	15.73	15.63
5	256QAM	1	12	15.84	15.77	15.96
5	256QAM	1	24	15.87	15.72	15.81
5	256QAM	12	0	15.57	15.62	15.68
5	256QAM	12	7	15.71	15.72	15.68
5	256QAM	12	13	15.67	15.70	15.61
5	256QAM	25	0	15.53	15.68	15.71

**Bottom antenna:**

BW [MHz]	Modulation	RB Size	RB Offset	Lowest	Middle	Highest
Channel				27710		
Frequency (MHz)				2310		
10	QPSK	1	0		22.41	
10	QPSK	1	25		22.39	
10	QPSK	1	49		22.35	
10	QPSK	25	0		21.43	
10	QPSK	25	12		21.48	
10	QPSK	25	25		21.49	
10	QPSK	50	0		21.47	
10	16QAM	1	0		21.81	
10	16QAM	1	25		21.78	
10	16QAM	1	49		21.74	
10	16QAM	25	0		20.42	
10	16QAM	25	12		20.48	
10	16QAM	25	25		20.48	
10	16QAM	50	0		20.49	
10	64QAM	1	0		20.59	
10	64QAM	1	25		20.32	
10	64QAM	1	49		20.50	
10	64QAM	25	0		19.45	
10	64QAM	25	12		19.40	
10	64QAM	25	25		19.24	
10	64QAM	50	0		19.18	
10	256QAM	1	0		17.38	
10	256QAM	1	25		17.53	
10	256QAM	1	49		17.60	
10	256QAM	25	0		17.46	
10	256QAM	25	12		17.53	
10	256QAM	25	25		17.47	
10	256QAM	50	0		17.43	
Channel				27685	27710	27735



Frequency (MHz)				2307.5	2310	2312.5
5	QPSK	1	0	22.21	22.26	22.36
5	QPSK	1	12	22.37	22.37	22.37
5	QPSK	1	24	22.39	22.36	22.34
5	QPSK	12	0	21.37	21.46	21.47
5	QPSK	12	7	21.50	21.46	21.53
5	QPSK	12	13	21.47	21.46	21.53
5	QPSK	25	0	21.48	21.43	21.49
5	16QAM	1	0	21.54	21.63	21.66
5	16QAM	1	12	21.63	21.70	21.68
5	16QAM	1	24	21.71	21.68	21.67
5	16QAM	12	0	20.36	20.46	20.52
5	16QAM	12	7	20.50	20.51	20.56
5	16QAM	12	13	20.52	20.51	20.51
5	16QAM	25	0	20.48	20.47	20.52
5	64QAM	1	0	20.47	20.34	20.39
5	64QAM	1	12	20.46	20.14	20.39
5	64QAM	1	24	20.24	20.19	20.51
5	64QAM	12	0	19.42	19.17	19.26
5	64QAM	12	7	19.38	19.18	19.37
5	64QAM	12	13	19.23	19.17	19.41
5	64QAM	25	0	19.29	19.18	19.23
5	256QAM	1	0	17.48	17.58	17.50
5	256QAM	1	12	17.54	17.52	17.44
5	256QAM	1	24	17.60	17.50	17.54
5	256QAM	12	0	17.45	17.44	17.39
5	256QAM	12	7	17.56	17.53	17.49
5	256QAM	12	13	17.45	17.42	17.46
5	256QAM	25	0	17.33	17.49	17.36

ERP/EIRP

LTE Band 30 (GT - LC = -1.0 dB) QPSK (dBm/5MHz)			
Bandwidth	5M		
Channel	27685	27710	27735
	(Low)	(Mid)	(High)
Frequency	2307.5	2310	2312.5
(MHz)			
Conducted Power (dBm)	22.39	22.36	22.34
Conducted Power (Watts)	0.1734	0.1722	0.1714
EIRP(dBm)	21.39	21.36	21.34
EIRP(Watts)	0.1377	0.1368	0.1361
Limit	250mW / 5MHz = 24dBm / 5MHz		PASS

LTE Band 30 (GT - LC = -1.0 dB) QPSK (dBm/5MHz)			
Bandwidth	10M		
Channel		27710	
		(Mid)	
Frequency		2310	
(MHz)			
Conducted Power (dBm)		22.41	
Conducted Power (Watts)		0.1742	
EIRP(dBm)		21.41	
EIRP(Watts)		0.1384	
Limit	250mW / 5MHz = 24dBm / 5MHz		PASS



LTE Band 30 (GT - LC = -1.0 dB) 16QAM (dBm/5MHz)			
Bandwidth	5M		
Channel	27685	27710	27735
	(Low)	(Mid)	(High)
Frequency	2307.5	2310	2312.5
(MHz)			
Conducted Power (dBm)	21.71	21.68	21.67
Conducted Power (Watts)	0.1483	0.1472	0.1469
EIRP(dBm)	20.71	20.68	20.67
EIRP(Watts)	0.1178	0.1169	0.1167
Limit	250mW / 5MHz = 24dBm / 5MHz		PASS

LTE Band 30 (GT - LC = -1.0 dB) 16QAM (dBm/5MHz)			
Bandwidth	10M		
Channel		27710	
		(Mid)	
Frequency		2310	
(MHz)			
Conducted Power (dBm)		21.81	
Conducted Power (Watts)		0.1517	
EIRP(dBm)		20.81	
EIRP(Watts)		0.1205	
Limit	250mW / 5MHz = 24dBm / 5MHz		PASS

LTE Band 30 (GT - LC = -1.0 dB) 64QAM (dBm/5MHz)			
Bandwidth	5M		
Channel	27685	27710	27735
	(Low)	(Mid)	(High)
Frequency	2307.5	2310	2312.5
(MHz)			
Conducted Power (dBm)	20.24	20.19	20.51
Conducted Power (Watts)	0.1057	0.1045	0.1125
EIRP(dBm)	19.24	19.19	19.51
EIRP(Watts)	0.0839	0.0830	0.0893
Limit	250mW / 5MHz = 24dBm / 5MHz		PASS

LTE Band 30 (GT - LC = -1.0 dB) 64QAM (dBm/5MHz)			
Bandwidth	10M		
Channel		27710	
		(Mid)	
Frequency		2310	
(MHz)			
Conducted Power (dBm)		20.59	
Conducted Power (Watts)		0.1146	
EIRP(dBm)		19.59	
EIRP(Watts)		0.0910	
Limit	250mW / 5MHz = 24dBm / 5MHz		PASS




LTE Band 30

Peak-to-Average Ratio


Mode	LTE Band 30 / 10MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	-	-	-	-	PASS
Middle CH	3.59	4.90	5.36	5.80	
Highest CH	-	-	-	-	
Mode	LTE Band 30 / 10MHz				
Mod.	64QAM				Limit: 13dB
RB Size	1RB	Full RB			Result
Lowest CH	-	-	-	-	PASS
Middle CH	6.64	6.26	-	-	
Highest CH	-	-	-	-	

LTE Band 30 / 10MHz / QPSK

Middle Channel / 1RB




Middle Channel / Full RB




LTE Band 30 / 10MHz / 16QAM

Middle Channel / 1RB




Middle Channel / Full RB




LTE Band 30 / 10MHz / 64QAM

Middle Channel / 1RB



Middle Channel / Full RB




**26dB Bandwidth**

Mode	LTE Band 30 : 26dB BW(MHz)											
BW					5MHz		10MHz					
Mod.					QPSK	16QAM	QPSK	16QAM				
Lowest CH	-	-	-	-	4.86	4.98	-	-	-	-	-	-
Middle CH	-	-	-	-	4.90	4.87	9.81	9.79	-	-	-	-
Highest CH	-	-	-	-	4.98	4.95	-	-	-	-	-	-
Mode	LTE Band 30 : 26dB BW(MHz)											
BW					5MHz		10MHz					
Mod.					64QAM		64QAM					
Lowest CH	-	-	-	-	4.73	-	-	-				
Middle CH	-	-	-	-	4.95	-	9.67	-				
Highest CH	-	-	-	-	4.83	-	-	-				




LTE Band 30


Lowest Channel / 5MHz / QPSK




Lowest Channel / 5MHz / 16QAM




Middle Channel / 5MHz / QPSK




Middle Channel / 5MHz / 16QAM



Highest Channel / 5MHz / QPSK




Highest Channel / 5MHz / 16QAM






LTE Band 30

Middle Channel / 10MHz / QPSK



Date: 9.JUL.2020 07:48:55

Middle Channel / 10MHz / 16QAM




Date: 9.JUL.2020 07:48:29




LTE Band 30


Lowest Channel / 5MHz / 64QAM




Middle Channel / 5MHz / 64QAM



Middle Channel / 10MHz / 64QAM



Highest Channel / 5MHz / 64QAM




**Occupied Bandwidth**

Mode	LTE Band 30 : 99%OBW(MHz)											
BW					5MHz		10MHz					
Mod.					QPSK	16QAM	QPSK	16QAM				
Lowest CH	-	-	-	-	4.51	4.49	-	-	-	-	-	-
Middle CH	-	-	-	-	4.49	4.50	9.03	8.95	-	-	-	-
Highest CH	-	-	-	-	4.50	4.47	-	-	-	-	-	-
Mode	LTE Band 26 : 99%OBW(MHz)											
BW					5MHz		10MHz					
Mod.					64QAM		64QAM					
Lowest CH	-	-	-	-	4.49	-	-	-	-	-	-	-
Middle CH	-	-	-	-	4.50	-	9.01	-	-	-	-	-
Highest CH	-	-	-	-	4.49	-	-	-	-	-	-	-




LTE Band 30


Lowest Channel / 5MHz / QPSK




Lowest Channel / 5MHz / 16QAM




Middle Channel / 5MHz / QPSK




Middle Channel / 5MHz / 16QAM



Highest Channel / 5MHz / QPSK




Highest Channel / 5MHz / 16QAM






LTE Band 30

Middle Channel / 10MHz / QPSK



Date: 9_JUL_2020 07:49:29

Middle Channel / 10MHz / 16QAM




Date: 9_JUL_2020 07:48:10




LTE Band 30


Lowest Channel / 5MHz / 64QAM




Middle Channel / 5MHz / 64QAM



Middle Channel / 10MHz / 64QAM



Highest Channel / 5MHz / 64QAM






Conducted Band Edge




LTE Band 30 / 5MHz / QPSK

Lowest Band Edge / 1 RB




Date: 9.JUL.2020 04:52:10

Highest Band Edge / 1 RB




Date: 9.JUL.2020 04:58:28

Lowest Band Edge / Full RB



Date: 9.JUL.2020 04:55:19

Highest Band Edge / Full RB




Date: 9.JUL.2020 05:01:37




LTE Band 30 / 5MHz / 16QAM

Lowest Band Edge / 1RB




Date: 9.JUL.2020 04:53:13

Highest Band Edge / 1 RB




Date: 9.JUL.2020 04:59:30

Lowest Band Edge / Full RB



Date: 9.JUL.2020 04:56:22

Highest Band Edge / Full RB




Date: 9.JUL.2020 05:02:40




LTE Band 30 / 5MHz / 64QAM

Lowest Band Edge / 1RB




Date: 9.JUL.2020 04:54:16

Highest Band Edge / 1 RB




Date: 9.JUL.2020 05:00:33

Lowest Band Edge / Full RB



Date: 9.JUL.2020 04:57:25

Highest Band Edge / Full RB




Date: 9.JUL.2020 05:03:43




LTE Band 30 / 10MHz / QPSK

Lowest Band Edge / 1 RB




Date: 9.JUL.2020 05:04:46

Highest Band Edge / 1 RB



Date: 9.JUL.2020 05:07:58

Band Edge / Full RB




Date: 9.JUL.2020 05:11:07




LTE Band 30 / 10MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 9.JUL.2020 05:05:50

Highest Band Edge / 1 RB



Date: 9.JUL.2020 05:09:01

Band Edge / Full RB




Date: 9.JUL.2020 05:12:10




LTE Band 30 / 10MHz / 64QAM

Lowest Band Edge / 1 RB




Date: 9.JUL.2020 05:06:54

Highest Band Edge / 1 RB



Date: 9.JUL.2020 05:10:04

Band Edge / Full RB



Date: 9.JUL.2020 05:13:14




Conducted Spurious Emission




LTE Band 30 / 5MHz

Lowest Channel / QPSK




Date: 9.JUL.2020 06:41:09

Lowest Channel / 16QAM




Date: 9.JUL.2020 06:49:11

Middle Channel / QPSK



Date: 9.JUL.2020 06:42:15

Middle Channel / 16QAM




Date: 9.JUL.2020 06:47:31




LTE Band 30 / 5MHz

Highest Channel / QPSK



Date: 9.JUL.2020 06:43:24


Highest Channel / 16QAM



Date: 9.JUL.2020 06:45:23


LTE Band 30 / 10MHz

Middle Channel / QPSK



Date: 9.JUL.2020 06:58:34

Middle Channel / 16QAM




Date: 9.JUL.2020 06:57:30




LTE Band 30 / 5MHz

Lowest Channel / 64QAM




Date: 9 JUL 2020 06:50:29

Middle Channel / 64QAM



Date: 9 JUL 2020 06:51:36

Highest Channel / 64QAM




Date: 9 JUL 2020 06:53:19



LTE Band 30 / 10MHz

Middle Channel / 64QAM



Frequency Stability

Test Conditions		LTE Band 30 (QPSK) / Middle Channel	Limit
Temperature (°C)	Voltage (Volt)	BW 10MHz	Note 2.
		Deviation (ppm)	Result
50	Normal Voltage	0.0003	PASS
40	Normal Voltage	0.0003	
30	Normal Voltage	0.0002	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0006	
0	Normal Voltage	0.0005	
-10	Normal Voltage	0.0000	
-20	Normal Voltage	0.0001	
-30	Normal Voltage	0.0003	
20	Maximum Voltage	0.0003	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0002	

Note:

1. Normal Voltage =7.74 V. ; Battery End Point (BEP) =7.2 V. ; Maximum Voltage =8.9 V.
2. Note: The frequency fundamental emissions stay within the authorized frequency block.



Appendix B. Test Results of Radiated Test

Radiated Spurious Emission

Top antenna:

LTE Band 30 / 5MHz / QPSK / RB Size 1 Offset 0									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	4610.50	-63.50	-40	-23.50	-58.92	-69.75	6.30	12.55	H
	6915.75	-60.96	-40	-20.96	-60.34	-64.36	8.25	11.65	H
	9221.00	-57.77	-40	-17.77	-61.82	-60.12	9.50	11.85	H
	11526.25	-55.29	-40	-15.29	-63.04	-56.37	10.97	12.05	H
	4610.50	-63.21	-40	-23.21	-58.69	-69.46	6.30	12.55	V
	6915.75	-60.63	-40	-20.63	-60.15	-64.03	8.25	11.65	V
	9221.00	-58.94	-40	-18.94	-61.72	-61.29	9.50	11.85	V
	11526.25	-54.43	-40	-14.43	-62.6	-55.51	10.97	12.05	V
Middle	4615.50	-63.28	-40	-23.28	-58.73	-69.53	6.45	12.70	H
	6923.25	-59.80	-40	-19.80	-59.18	-63.20	8.40	11.80	H
	9231.00	-57.82	-40	-17.82	-61.87	-60.17	9.65	12.00	H
	11538.75	-55.43	-40	-15.43	-63.22	-56.51	11.12	12.20	H
	4615.50	-63.02	-40	-23.02	-58.54	-69.27	6.45	12.70	V
	6923.25	-60.31	-40	-20.31	-59.83	-63.71	8.40	11.80	V
	9231.00	-58.73	-40	-18.73	-61.51	-61.08	9.65	12.00	V
	11538.75	-54.78	-40	-14.78	-62.96	-55.86	11.12	12.20	V
Highest	4620.50	-63.39	-40	-23.39	-58.84	-69.64	6.61	12.86	H
	6930.75	-60.83	-40	-20.83	-60.28	-64.21	8.56	11.94	H
	9241.00	-57.87	-40	-17.87	-61.92	-60.22	9.81	12.16	H
	11551.25	-55.11	-40	-15.11	-62.93	-56.16	11.28	12.33	H
	4620.50	-63.19	-40	-23.19	-58.71	-69.44	6.61	12.86	V
	6930.75	-60.83	-40	-20.83	-60.39	-64.21	8.56	11.94	V
	9241.00	-58.86	-40	-18.86	-61.64	-61.21	9.81	12.16	V
	11551.25	-54.55	-40	-14.55	-62.75	-55.60	11.28	12.33	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



LTE Band 30 / 10MHz / QPSK / RB Size 1 Offset 0									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	4611.00	-63.58	-40	-23.58	-59.00	-69.83	6.45	12.70	H
	6916.50	-60.87	-40	-20.87	-60.25	-64.27	8.40	11.80	H
	9222.00	-57.17	-40	-17.17	-61.22	-59.52	9.65	12.00	H
	4611.00	-62.37	-40	-22.37	-57.85	-68.62	6.45	12.70	V
	6916.50	-60.68	-40	-20.68	-60.2	-64.08	8.40	11.80	V
	9222.00	-59.03	-40	-19.03	-61.81	-61.38	9.65	12.00	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.


Bottom antenna:

LTE Band 30 / 5MHz / QPSK / RB Size 1 Offset 0									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	4610.50	-61.13	-40	-21.13	-56.55	-67.38	6.30	12.55	H
	6915.75	-60.95	-40	-20.95	-60.33	-64.35	8.25	11.65	H
	9221.00	-57.10	-40	-17.10	-61.15	-59.45	9.50	11.85	H
	11526.25	-55.41	-40	-15.41	-63.16	-56.49	10.97	12.05	H
	4610.50	-60.96	-40	-20.96	-56.44	-67.21	6.30	12.55	V
	6915.75	-60.68	-40	-20.68	-60.2	-64.08	8.25	11.65	V
	9221.00	-59.03	-40	-19.03	-61.81	-61.38	9.50	11.85	V
	11526.25	-55.03	-40	-15.03	-63.2	-56.11	10.97	12.05	V
Middle	4615.50	-59.82	-40	-19.82	-55.27	-66.07	6.45	12.70	H
	6923.25	-60.54	-40	-20.54	-59.92	-63.94	8.40	11.80	H
	9231.00	-57.98	-40	-17.98	-62.03	-60.33	9.65	12.00	H
	11538.75	-55.42	-40	-15.42	-63.21	-56.50	11.12	12.20	H
	4615.50	-61.67	-40	-21.67	-57.19	-67.92	6.45	12.70	V
	6923.25	-60.51	-40	-20.51	-60.03	-63.91	8.40	11.80	V
	9231.00	-59.39	-40	-19.39	-62.17	-61.74	9.65	12.00	V
	11538.75	-54.92	-40	-14.92	-63.1	-56.00	11.12	12.20	V
Highest	4620.50	-61.00	-40	-21.00	-56.45	-67.25	6.61	12.86	H
	6930.75	-60.48	-40	-20.48	-59.93	-63.86	8.56	11.94	H
	9241.00	-57.68	-40	-17.68	-61.73	-60.03	9.81	12.16	H
	11551.25	-55.16	-40	-15.16	-62.98	-56.21	11.28	12.33	H
	4620.50	-62.18	-40	-22.18	-57.7	-68.43	6.61	12.86	V
	6930.75	-60.66	-40	-20.66	-60.22	-64.04	8.56	11.94	V
	9241.00	-59.08	-40	-19.08	-61.86	-61.43	9.81	12.16	V
	11551.25	-54.97	-40	-14.97	-63.17	-56.02	11.28	12.33	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

LTE Band 30 / 10MHz / QPSK / RB Size 1 Offset 0									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	4611.00	-63.39	-40	-23.39	-58.81	-69.64	6.45	12.70	H
	6916.50	-60.66	-40	-20.66	-60.04	-64.06	8.40	11.80	H
	9222.00	-57.17	-40	-17.17	-61.22	-59.52	9.65	12.00	H
	4611.00	-63.32	-40	-23.32	-58.8	-69.57	6.45	12.70	V
	6916.50	-60.74	-40	-20.74	-60.26	-64.14	8.40	11.80	V
	9222.00	-59.01	-40	-19.01	-61.79	-61.36	9.65	12.00	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.