

**SHENZHEN MIZAR TECHNOLOGY CO., LTD.**

**Bluetooth Speaker**

**Main Model: DC-0230-A**  
**Serial Model: DC-0337-A, MA-890-B, MA-860**

**March 20, 2014**

**Report No.: 13070095-FCC-H2**  
(This report supersedes NONE)



Modifications made to the product : None

This Test Report is Issued Under the Authority of:

|                                   |                               |   |
|-----------------------------------|-------------------------------|---|
| Herith shi                        | Alex Liu                      |  |
| Herith Shi<br>Compliance Engineer | Alex Liu<br>Technical Manager |   |

This test report may be reproduced in full only.  
Test result presented in this test report is applicable to the representative sample only.

**EMC Test Report**  
**To:FCC 2.1091**

**SIEMIC, INC.**  
Accessing global markets

**SIEMIC, INC.**

Accessing global markets

Title: EMC Test Report for Bluetooth Speaker  
Main Model: DC-0230-A  
Serial Model: DC-0337-A, MA-890-B, MA-860  
To: FCC 2.1091

Report No.: 13070095-FCC-H2  
Issue Date: March 20, 2014  
Page: 2 of 8  
www.siemic.com.cn

## Laboratory Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management through out a project. Our extensive experience with China, Asia Pacific, North America, European, and international compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

### SIEMIC (Shenzhen-China) Laboratories Accreditations for Conformity Assessment

| Country/Region | Scope                          |
|----------------|--------------------------------|
| USA            | EMC , RF/Wireless , Telecom    |
| Canada         | EMC, RF/Wireless , Telecom     |
| Taiwan         | EMC, RF, Telecom , Safety      |
| Hong Kong      | RF/Wireless , Telecom          |
| Australia      | EMC, RF, Telecom , Safety      |
| Korea          | EMI, EMS, RF , Telecom, Safety |
| Japan          | EMI, RF/Wireless, Telecom      |
| Singapore      | EMC , RF , Telecom             |
| Europe         | EMC, RF, Telecom , Safety      |



**SIEMIC, INC.**

*Accessing global markets*

Title: EMC Test Report for Bluetooth Speaker  
Main Model: DC-0230-A  
Serial Model: DC-0337-A, MA-890-B, MA-860  
To: FCC 2.1091

Report No.: 13070095-FCC-H2  
Issue Date: March 20, 2014  
Page: 3 of 8  
[www.siemic.com.cn](http://www.siemic.com.cn)

---

This page has been left blank intentionally.



**SIEMIC, INC.**

*Accessing global markets*

Title: EMC Test Report for Bluetooth Speaker  
Main Model: DC-0230-A  
Serial Model: DC-0337-A, MA-890-B, MA-860  
To: FCC 2.1091

Report No.: 13070095-FCC-H2  
Issue Date: March 20, 2014  
Page: 4 of 8  
[www.siemic.com.cn](http://www.siemic.com.cn)

## CONTENTS

|          |   |          |
|----------|---|----------|
| <b>1</b> | <b>EXECUTIVE SUMMARY &amp; EUT INFORMATION</b>          | <b>5</b> |
| <b>2</b> | <b>TECHNICAL DETAILS</b>                                | <b>6</b> |
| <b>3</b> | <b>FCC §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)</b> | <b>7</b> |



**SIEMIC, INC.**

*Accessing global markets*

Title: EMC Test Report for Bluetooth Speaker  
Main Model: DC-0230-A  
Serial Model: DC-0337-A, MA-890-B, MA-860  
To: FCC 2.1091

Report No.: 13070095-FCC-H2  
Issue Date: March 20, 2014  
Page: 5 of 8  
[www.siemic.com.cn](http://www.siemic.com.cn)

## **1 EXECUTIVE SUMMARY & EUT INFORMATION**

**The purpose of this test programmers was to demonstrate compliance of the SHENZHEN MIZAR TECHNOLOGY CO., LTD., Bluetooth Speaker and Model: DC-0230-A against the current Stipulated Standards. The Bluetooth Speaker has demonstrated compliance with the FCC 2.1091.**

### **EUT Information**

**EUT Description** : Bluetooth Speaker

**Main Model** : DC-0230-A

**Serial Model** : DC-0337-A, MA-890-B, MA-860 (the difference between Main Model and Serial Model is only the Model Number)

**Antenna Gain** : Bluetooth: 0 dBi

**Battery:**

**Input Power** : Model: 052530-450mAh  
Spec: 3.7V 450mAh  
Limited charger voltage: 4.2V

**Classification Per Stipulated Test Standard** : Class B Emission Product Per FCC 2.1091

**SIEMIC, INC.**

Accessing global markets

Title: EMC Test Report for Bluetooth Speaker  
Main Model: DC-0230-A  
Serial Model: DC-0337-A, MA-890-B, MA-860  
To: FCC 2.1091

Report No.: 13070095-FCC-H2  
Issue Date: March 20, 2014  
Page: 6 of 8  
www.siemic.com.cn

## **2 TECHNICAL DETAILS**

|  |  |
|--|--|
| <b>Purpose</b>                         | <b>Compliance testing of Bluetooth Speaker with stipulated standards</b>   |
| <b>Applicant / Client</b>              | <b>SHENZHEN MIZAR TECHNOLOGY CO., LTD.<br/>3F, Building B, NO.34 Gongyuan Road, jiabao Block22, Baoan District,<br/>Shenzhen P.R. China</b>  |
| <b>Manufacturer</b>                    | <b>SHENZHEN MIZAR TECHNOLOGY CO., LTD.<br/>3F, Building B, NO.34 Gongyuan Road, jiabao Block22, Baoan District,<br/>Shenzhen P.R. China</b>  |
| <b>Laboratory performing the tests</b> | <b>SIEMIC (Shenzhen-China) Laboratories<br/>Zone A, Floor 1, Building 2, Wan Ye Long Technology Park, South Side of<br/>Zhoushi Road, Bao'an District, Shenzhen, Guangdong, China<br/>Tel: +86-0755-2601 4629 / 2601 4953<br/>Fax: +86-0755-2601 4953-810<br/>Email: China@siemic.com.cn</b> |
| <b>Test report reference number</b>    | <b>13070095-FCC-H2</b>   |
| <b>Date EUT received</b>               | <b>March 10, 2014</b>  |
| <b>Standard applied</b>                | <b>FCC 2.1091</b>  |
| <b>Dates of test (from – to)</b>       | <b>March 20, 2014</b>  |
| <b>No of Units</b>                     | <b>#1</b>  |
| <b>Equipment Category</b>              | <b>DSS</b>   |
| <b>Trade Name</b>                      | <b>N/A</b>   |
| <b>RF Operating Frequency (ies)</b>    | <b>Bluetooth: 2402-2480 MHz</b>  |
| <b>Number of Channels</b>              | <b>Bluetooth: 79CH</b>   |
| <b>Modulation</b>                      | <b>Bluetooth: GFSK&amp; <math>\pi/4</math>DQPSK</b>  |
| <b>FCC ID</b>                          | <b>2ABZRDC0230A</b>  |



**SIEMIC, INC.**

Accessing global markets

Title: EMC Test Report for Bluetooth Speaker  
Main Model: DC-0230-A  
Serial Model: DC-0337-A, MA-890-B, MA-860  
To: FCC 2.1091

Report No.: 13070095-FCC-H2  
Issue Date: March 20, 2014  
Page: 7 of 8  
www.siemic.com.cn

### **3 FCC §2.1091 - Maximum Permissible exposure (MPE)**

#### **3.1 Applicable Standard**

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

Limits for General Population/Uncontrolled Exposure

| Limits for General Population/Uncontrolled Exposure |                               |                               |                                     |                          |
|---|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| Frequency Range (MHz)                               | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm <sup>2</sup> ) | Averaging Time (minutes) |
| 0.3-1.34  | 614                           | 1.63                          | *(100)                              | 30                       |
| 1.34-30   | 824/f                         | 2.19/f                        | *(180/f <sup>2</sup> )              | 30                       |
| 30-300  | 27.5                          | 0.073                         | 0.2                                 | 30                       |
| 300-1500  | /                             | /                             | f/1500                              | 30                       |
| 1500-100,000  | /                             | /                             | 1.0                                 | 30                       |

f = frequency in MHz

\* = Plane-wave equivalent power density

#### **3.2 Test Data**

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

Where: S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)



**SIEMIC, INC.**

*Accessing global markets*

Title: EMC Test Report for Bluetooth Speaker  
Main Model: DC-0230-A  
Serial Model: DC-0337-A, MA-890-B, MA-860  
To: FCC 2.1091

Report No.: 13070095-FCC-H2  
Issue Date: March 20, 2014  
Page: 8 of 8  
[www.siemic.com.cn](http://www.siemic.com.cn)

2.4GHz  
GFSK

Maximum peak output power at antenna input terminal: -4.876(dBm)  
Maximum peak output power at antenna input terminal: 0.325 (mW)

Prediction distance: >20 (cm)  
Predication frequency: 2402(MHz)  
Antenna Gain (typical): 0 (dBi)

Antenna Gain (typical): 1 (numeric)

The worst case is power density at predication frequency at 20 cm: 0.00006(mW/cm<sup>2</sup>)

MPE limit for general population exposure at prediction frequency: 1 (mW/cm<sup>2</sup>)

0.00006(mW/cm<sup>2</sup>) < 1 (mW/cm<sup>2</sup>)

**Result:** Pass