

FCC &ISED Radio Test Report**FCC ID: 2AC23-WC16****IC:12290A-WC16****The report concerns: Original Grant**

Report Reference No. : 20EFAS03132 1981
Date Sample(s) Received : 2020-03-21
Date of Tested : 2020-03-21 to 2020-04-08
Date of issue : 2020-04-08
Testing Laboratory : DongGuan ShuoXin Electronic Technology Co., Ltd.
Address : Zone A, 1F, No. 6, XinGang Road YuanGang Street,
XinAn District, ChangAn Town, DongGuan City,
GuangDong, China

Applicant's name : Hui Zhou Gaoshengda Technology Co., LTD
Address : NO.75 Zhongkai Development Area, Huizhou,
Guangdong
Manufacturer : Hui Zhou Gaoshengda Technology Co., LTD


Equipment : WIFI Module
Trade Mark : GSD
Model : WC16R2601
Ratings : I/P: DC 3.3V

Responsible Engineer :



Smile Wang

Authorized Signatory:



King Wang

Table of Contents	Page
1 . TEST REPORT DECLARE	4
2 . SUMMARY OF TEST RESULTS	5
2.1 MEASUREMENT UNCERTAINTY	6
3 . GENERAL INFORMATION	7
3.1 GENERAL DESCRIPTION OF EUT	7
3.2 TEST MODES	9
3.3 PARAMETERS OF TEST SOFTWARE	11
3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	12
3.5 SUPPORT UNITS	12
3.6 TEST ENVIRONMENT CONDITIONS	12
3.7 DUTY CYCLE	13
4 . AC POWER LINE CONDUCTED EMISSIONS TEST	14
4.1 LIMIT	14
4.2 TEST PROCEDURE	14
4.3 MEASUREMENT INSTRUMENTS LIST	14
4.4 TESTSETUP	15
4.5 EUT OPERATION CONDITIONS	15
4.6 TEST RESULTS	16
5 . RADIATED EMISSIONSTEST	18
5.1 LIMIT	18
5.2 TEST PROCEDURE	19
5.3 MEASUREMENT INSTRUMENTS LIST	19
5.4 TESTSETUP	20
5.5 EUT OPERATION CONDITIONS	20
5.6 TEST RESULTS - 9 KHZ to 30MHZ	21
5.7 TEST RESULTS - 30 MHz TO 1000 MHz	22
5.8 TEST RESULTS - ABOVE1000 MHz(BAND EDGE)	24
5.9 TEST RESULTS - ABOVE1000 MHz (HARMONIC)	74
6 . BANDWIDTH TEST	130
6.1 LIMIT	130
6.2 TEST PROCEDURE AND SETTING	130
6.3 MEASUREMENT INSTRUMENTS LIST	130
6.4 TEST SETUP	131

Table of Contents	Page
6.5 EUT OPERATION CONDITIONS	131
6.6 TEST RESULTS	132
7 . MAXIMUM OUTPUT POWER TEST	142
7.1 LIMIT	142
7.2 TEST PROCEDURE AND SETTING	142
7.3 MEASUREMENT INSTRUMENTS LIST	142
7.4 TEST SETUP	142
7.5 EUT OPERATION CONDITIONS	142
7.6 TEST RESULTS	143
8 . POWER SPECTRAL DENSITY TEST	155
8.1 LIMIT	155
8.2 TEST PROCEDURE AND SETTING	155
8.3 MEASUREMENT INSTRUMENTS LIST	155
8.4 TEST SETUP	155
8.5 EUT OPERATION CONDITIONS	155
8.6 TEST RESULTS	156
9 . FREQUENCY STABILITY MEASUREMENT	169
9.1 LIMIT	169
9.2 TEST PROCEDURE AND SETTING	169
9.3 MEASUREMENT INSTRUMENTS LIST	169
9.4 TEST SETUP	169
9.5 EUT OPERATION CONDITIONS	169
9.6 TEST RESULTS	170

1. TEST REPORT DECLARE

Applicant	Hui Zhou Gaoshengda Technology Co., LTD
Address	NO.75 Zhongkai Development Area, Huizhou, Guangdong
Manufacturer	Hui Zhou Gaoshengda Technology Co., LTD
Address	NO.75 Zhongkai Development Area, Huizhou, Guangdong
Factory	Hui Zhou Gaoshengda Technology Co., LTD
Address	NO.75 Zhongkai Development Area, Huizhou, Guangdong
Equipment	WIFI Module
Model No.	WC16R2601
Trade Mark	GSD
Standard	FCC Part15, Subpart E(15.407) RSS-247 Issue 2, Feb. 2017 RSS-Gen Issue 5, Apr. 2018 ANSI C63.10-2013 FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01

We Declare:

The equipment described above is tested by DongGuan ShuoXin Electronic Technology Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and DongGuan ShuoXin Electronic Technology Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

2. SUMMARY OF TEST RESULTS

The EUT have been tested according to the applicable standards as referenced below:

Standard(s) Section		Test Item	Judgment	Remark
FCC	IC			
15.207 15.407(b)	RSS-GEN 8.8	AC Power Line Conducted Emissions	PASS	-----
15.407(b) 15.205(a) 15.209(a)	RSS-247 6.2.1.2 RSS-247 6.2.4.2 RSS-GEN 8.9 RSS-GEN 8.10	Radiated Emissions	PASS	-----
15.407(a) 15.407(e)	RSS-247 6.2.1.1 RSS-247 6.2.2.1 RSS-247 6.2.3.1 RSS-247 6.2.4.1 RSS-GEN 6.7	Spectrum Bandwidth	PASS	-----
15.407(a)	RSS-247 6.2.1.1 RSS-247 6.2.2.1 RSS-247 6.2.3.1 RSS-247 6.2.4.1	Maximum Output Power	PASS	-----
15.407(a)	RSS-247 6.2.1.1 RSS-247 6.2.2.1 RSS-247 6.2.3.1 RSS-247 6.2.4.1	Power Spectral Density	PASS	-----
15.407(g)	RSS-GEN 6.11	Frequency Stability	PASS	-----
15.203	RSS-247 6.4(a)	Antenna Requirements	PASS	Note(4)
15.407(c)	RSS-GEN 8.8	Automatically Discontinue Transmission	PASS	Note(2)

Note:

- (1) "N/A" denotes test is not applicable in this test report.
- (2) During no any information transmission, the EUT can automatically discontinue transmission and become standby mode for power saving. the EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.
- (3) For UNII-1 this device was functioned as a
☐ Access point device ☒ Client device
- (4) The device what use a permanently attached antenna were considered sufficient to comply with the provisions of 15.203.

2.1 MEASUREMENT UNCERTAINTY

Test Item	Uncertainty
Uncertainty for Conduction emission test (9kHz-150kHz)	3.7 dB
Uncertainty for Conduction emission test (150kHz-30MHz)	3.3 dB
Uncertainty for Radiation Emission test (30MHz-200MHz)	4.60 dB (Polarize: V)
	4.60 dB (Polarize: H)
Uncertainty for Radiation Emission test (200MHz-1GHz)	6.10 dB (Polarize: V)
	5.08 dB (Polarize: H)
Uncertainty for Radiation Emission test (1GHz-6GHz)	5.01 dB (Polarize: V)
	5.01 dB (Polarize: H)
Uncertainty for Radiation Emission test (6GHz-18GHz)	5.26 dB (Polarize: V)
	5.26 dB (Polarize: H)
Uncertainty for Radiation Emission test (18GHz-40GHz)	5.06 dB (Polarize: V)
	5.06 dB (Polarize: H)
Uncertainty for radio frequency	$\pm 0.048\text{kHz}$
Uncertainty for conducted RF Power	$\pm 0.32\text{dB}$

Note:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	WIFI Module	
Brand Name	GSD	
Test Model	WC16R2601	
Series Model	N/A	
Model Difference(s)	N/A	
Hardware Version	V1.0	
Software Version	V1.0	
PowerSource	Supplied from USB.	
Power Rating	DC 3.3V	
Operation Frequency Bands	UNII-1: 5150 MHz~5250 MHz UNII-3: 5725 MHz~5850 MHz	
Modulation Type	OFDM	
Bit Rate of Transmitter	Up to 866.6Mbps	
Operating Mode	IEEE 802.11a: 1TX(Ant 1 or Ant 2) IEEE 802.11n (HT20): 2TX(Ant 1+Ant 2) IEEE 802.11n (HT40): 2TX(Ant 1+Ant 2) IEEE 802.11ac (VHT20): 2TX(Ant 1+Ant 2) IEEE 802.11ac (VHT40): 2TX(Ant 1+Ant 2) IEEE 802.11ac (VHT80): 2TX(Ant 1+Ant 2)	
Antenna Information	Antenna Type:PIFA	Maximum Peak Gain: 3dBi(Ant 1) 3dBi(Ant 2)
Maximum Output Power for UNII-1 For FCC	IEEE 802.11a: 16.26dBm (0.04230W) IEEE 802.11n (HT20): 18.27dBm (0.0671 W) IEEE 802.11n (HT40): 18.78dBm (0.0755 W) IEEE 802.11ac (VHT20): 18.68dBm (0.0738 W) IEEE 802.11ac (VHT40): 18.17dBm (0.0656 W) IEEE 802.11ac (VHT80): 16.18dBm (0.0415 W)	
Maximum EIRP Output Power for UNII-1 For IC	IEEE 802.11a: 19.26dBm (0.0843W) IEEE 802.11n (HT20): 21.27dBm (0.1340 W) IEEE 802.11n (HT40): 21.78dBm (0.1507 W) IEEE 802.11ac (VHT20): 21.68dBm (0.1472 W) IEEE 802.11ac (VHT40): 21.17dBm (0.1309 W) IEEE 802.11ac (VHT80): 19.18dBm (0.0828 W)	
Maximum Output Power for UNII-3	IEEE 802.11a: 15.43dBm (0.0349 W) IEEE 802.11n (HT20): 18.19dBm (0.0660 W) IEEE 802.11n (HT40): 18.44dBm (0.0698 W) IEEE 802.11ac (VHT20): 18.45dBm (0.0699 W) IEEE 802.11ac (VHT40): 18.43dBm (0.0697 W) IEEE 802.11ac (VHT80): 16.37dBm (0.0433 W)	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

2. Channel List:

IEEE 802.11a IEEE 802.11n (HT20) IEEE 802.11ac (VHT20)		IEEE 802.11n (HT40) IEEE 802.11ac (VHT40)		IEEE 802.11ac (VHT80)	
UNII-1		UNII-1		UNII-1	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	38	5190	42	5210
40	5200	46	5230		
44	5220				
48	5240				

IEEE 802.11a IEEE 802.11n (HT20) IEEE 802.11ac (VHT20)		IEEE 802.11n (HT40) IEEE 802.11ac (VHT40)		IEEE 802.11ac (VHT80)	
UNII-3		UNII-3		UNII-3	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	151	5755	155	5775
153	5765	159	5795		
157	5785				
161	5805				
165	5825				

3.2 TEST MODES

The test system was pre-tested based on the consideration of all possible combinations of EUT operation mode.

Pretest Mode	Description
Mode 1	TX A Mode / CH36, CH40, CH48 (UNII-1)
Mode 2	TX N (HT20) Mode / CH36, CH40, CH48 (UNII-1)
Mode 3	TX N (HT40) Mode / CH38, CH46 (UNII-1)
Mode 4	TX AC (VHT20) Mode / CH36, CH40, CH48 (UNII-1)
Mode 5	TX AC (VHT40) Mode / CH38, CH46 (UNII-1)
Mode 6	TX AC (VHT80) Mode / CH42 (UNII-1)
Mode 7	TX A Mode / CH149,CH157,CH165 (UNII-3)
Mode 8	TX N (HT20) Mode / CH149,CH157,CH165 (UNII-3)
Mode 9	TX N (HT40) Mode / CH151,CH159 (UNII-3)
Mode 10	TX AC (VHT20) Mode / CH149,CH157,CH165 (UNII-3)
Mode 11	TX AC (VHT40) Mode / CH151,CH159 (UNII-3)
Mode 12	TX AC (VHT80) Mode / CH155 (UNII-3)
Mode 13	TX N (HT40) Mode / CH46 (UNII-1)

Following mode(s) as (were) found to be the worst case(s) and selected for the final test.

AC power line conducted emissions test	
Final Test Mode	Description
Mode 13	TX N (HT40) Mode / CH46 (UNII-1)

Radiated emissions test - Below 1GHz	
Final Test Mode	Description
Mode 13	TX N (HT40) Mode / CH46 (UNII-1)

Radiated emissions test - Above 1GHz	
Final Test Mode	Description
Mode 1	TX A Mode / CH36, CH40, CH48 (UNII-1)
Mode 2	TX N (HT20) Mode / CH36, CH40, CH48 (UNII-1)
Mode 3	TX N (HT40) Mode / CH38, CH46 (UNII-1)
Mode 4	TX AC (VHT20) Mode / CH36, CH40, CH48 (UNII-1)
Mode 5	TX AC (VHT40) Mode / CH38, CH46 (UNII-1)
Mode 6	TX AC (VHT80) Mode / CH42 (UNII-1)
Mode 7	TX A Mode / CH149,CH157,CH165 (UNII-3)
Mode 8	TX N (HT20) Mode / CH149,CH157,CH165 (UNII-3)
Mode 9	TX N (HT40) Mode / CH151,CH159 (UNII-3)
Mode 10	TX AC (VHT20) Mode / CH149,CH157,CH165 (UNII-3)
Mode 11	TX AC (VHT40) Mode / CH151,CH159 (UNII-3)
Mode 12	TX AC (VHT80) Mode / CH155 (UNII-3)

Conducted test	
Final Test Mode	Description
Mode 1	TX A Mode / CH36, CH40, CH48 (UNII-1)
Mode 2	TX N (HT20) Mode / CH36, CH40, CH48 (UNII-1)
Mode 3	TX N (HT40) Mode / CH38, CH46 (UNII-1)
Mode 4	TX AC (VHT20) Mode / CH36, CH40, CH48 (UNII-1)
Mode 5	TX AC (VHT40) Mode / CH38, CH46 (UNII-1)
Mode 6	TX AC (VHT80) Mode / CH42 (UNII-1)
Mode 7	TX A Mode / CH149,CH157,CH165 (UNII-3)
Mode 8	TX N (HT20) Mode / CH149,CH157,CH165 (UNII-3)
Mode 9	TX N (HT40) Mode / CH151,CH159 (UNII-3)
Mode 10	TX AC (VHT20) Mode / CH149,CH157,CH165 (UNII-3)
Mode 11	TX AC (VHT40) Mode / CH151,CH159 (UNII-3)
Mode 12	TX AC (VHT80) Mode / CH155 (UNII-3)

Note:


- (1) For radiated emission below 1 GHz and AC power line conducted emissions test, the IEEE 802.11AC20channel 165is found to be the worst case and recorded.

3.3 PARAMETERS OF TEST SOFTWARE

UNII-1			
Test Software	MP_Kit_RTL11ac_8822CU		
Test Frequency (MHz)	5180	5200	5240
IEEE 802.11a	80	80	80
IEEE 802.11n (HT20)	80	75	70
IEEE 802.11ac (VHT20)	80	75	75
Test Frequency (MHz)	5190	5230	
IEEE 802.11n (HT40)	80	80	
IEEE 802.11ac (VHT40)	80	75	
Test Frequency (MHz)	5210		
IEEE 802.11ac (VHT80)	70		

UNII-3			
Test Software	MP_Kit_RTL11ac_8822CU		
Test Frequency (MHz)	5745	5785	5825
IEEE 802.11a	70	70	70
IEEE 802.11n (HT20)	67	70	70
IEEE 802.11ac (VHT20)	70	70	70
Test Frequency (MHz)	5755	5795	
IEEE 802.11n (HT40)	70	75	
IEEE 802.11ac (VHT40)	70	75	
Test Frequency (MHz)	5775		
IEEE 802.11ac (VHT80)	65		

3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



3.5 SUPPORT UNITS

Item	Equipment	Brand	Model No.	Series No.
AE	Notebook	ACER	MS2367	32807810766

Item	Cable Type	Shielded Type	Ferrite Core	Length
C1	DC Cable	NO	NO	0.5m

3.6 TEST ENVIRONMENT CONDITIONS

Test Item	Temperature	Humidity	Test Voltage
AC Power Line Conducted Emissions	25°C	53%	DC 3.3V
Radiated Emissions-9K-30MHz	25°C	60%	DC 3.3V
Radiated Emissions-30 MHz to 1GHz	24°C	68%	DC 3.3V
Radiated Emissions-Above 1000 MHz	24°C	68%	DC 3.3V
Spectrum Bandwidth	25.3°C	44.8%	DC 3.3V
Maximum Output Power	25.3°C	44.8%	DC 3.3V
Power Spectral Density	25.3°C	44.8%	DC 3.3V
Frequency Stability	Normal, Extreme	44.8%	Normal, Extreme

3.7 DUTY CYCLE

All tests are set to 100% duty cycle

IEEE 802.11a	IEEE 802.11n (HT20)	IEEE 802.11n (HT40)
0.00	0.00	0.00
IEEE 802.11ac (VHT20)	IEEE 802.11ac (VHT40)	IEEE 802.11ac (VHT80)
0.00	0.00	0.00

NOTE:

For IEEE 802.11a, IEEE 802.11n (HT20) and IEEE 802.11ac (VHT20):

For radiated emissions frequency above 1 GHz, the resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 1 kHz (Duty cycle < 98%).

For IEEE 802.11n (HT40) and IEEE 802.11ac (VHT40):

For radiated emissions frequency above 1 GHz, the resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 2 kHz (Duty cycle < 98%).

For IEEE 802.11ac (VHT80):

For radiated emissions frequency above 1 GHz, the resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 kHz (Duty cycle < 98%).

4. AC POWER LINE CONDUCTED EMISSIONS TEST

4.1 LIMIT

Frequency (MHz)	Limit (dBμV)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56*	56 to 46*
0.50 - 5.0	56	46
5.0 - 30.0	60	50

NOTE:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameter	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz


4.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.

4.3 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Pulse Limiter	MTS-system technik	MTS-IMP-136	261115-010-0024	12/11/2020
2	EMI Test Receiver	R&S	ESCI	101308	12/11/2020
3	LISN	AFJ	LS16	16011103219	06/09/2020
4	LISN	Schwarzbeck	NSLK 8127	8127-432	12/11/2020
5	Measurement Software	Farad	EZ-EMC (Ver.ATT-03A)	N/A	N/A

4.4 TESTSETUP




4.5 EUT OPERATION CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

The EUT was programmed to be in continuously transmitting/TX mode.

4.6 TEST RESULTS

Test Mode: TX N (HT40) Mode / CH46 (UNII-1)




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1539	46.14	11.77	57.91	65.78	-7.87	QP
2	0.1539	30.52	11.77	42.29	55.78	-13.49	AVG
3	0.1740	41.09	11.59	52.68	64.76	-12.08	QP
4	0.1740	31.50	11.59	43.09	54.76	-11.67	AVG
5	0.9580	29.54	10.09	39.63	56.00	-16.37	QP
6	0.9580	21.48	10.09	31.57	46.00	-14.43	AVG
7	2.1780	29.54	10.22	39.76	56.00	-16.24	QP
8	2.1780	20.59	10.22	30.81	46.00	-15.19	AVG
9	15.3419	33.08	11.00	44.08	60.00	-15.92	QP
10	15.3419	23.28	11.00	34.28	50.00	-15.72	AVG
11	16.2658	30.14	11.04	41.18	60.00	-18.82	QP
12	16.2658	25.25	11.04	36.29	50.00	-13.71	AVG

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode: TX N (HT40) Mode / CH46 (UNII-1)

Neutral



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1620	43.65	11.70	55.35	65.36	-10.01	QP
2	0.1620	27.41	11.70	39.11	55.36	-16.25	AVG
3	0.1780	41.08	11.55	52.63	64.57	-11.94	QP
4	0.1780	28.43	11.55	39.98	54.57	-14.59	AVG
5	0.2100	38.44	11.26	49.70	63.20	-13.50	QP
6	0.2100	25.73	11.26	36.99	53.20	-16.21	AVG
7	1.5220	29.18	10.15	39.33	56.00	-16.67	QP
8	1.5220	20.43	10.15	30.58	46.00	-15.42	AVG
9	1.6460	28.27	10.17	38.44	56.00	-17.56	QP
10	1.6460	20.47	10.17	30.64	46.00	-15.36	AVG
11	15.3499	32.31	11.00	43.31	60.00	-16.69	QP
12	15.3499	24.54	11.00	35.54	50.00	-14.46	AVG

Remarks:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

5. RADIATED EMISSIONSTEST

5.1 LIMIT

In case the emission fall within the restricted band specified on 15.205(a)&RSS-Gen 8.10, then the 15.209(a)&RSS-Gen 8.9 limit in the table below has to be followed.

LIMITS OF RADIATED EMISSIONS MEASUREMENT (9 kHz to 1000MHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

LIMITS OF UNWANTED EMISSION OUT OF THE RESTRICTED BANDS

Frequency (MHz)	EIRP Limit (dBm/MHz)	Equivalent Field Strength at 3m (dBμV/m)
5150-5250	-27	68.3
5250-5350	-27	68.3
5470-5725	-27	68.3
5725-5850	-27 Note(2)	68.3
	10 Note(2)	105.3
	15.6 Note(2)	110.9
	27 Note(2)	122.3

Note:

(1) The following formula is used to convert the equipment isotropic radiated power (eirp) to field

strength: $E = \frac{1000000 \sqrt{30P}}{3}$ μV/m, where P is the eirp (Watts)

(2) According to 15.407(b)(4)(i), all emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below theband edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above orbelow the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27dBm/MHz at the band edge.

(3) Radiation larger than 26.5GHz is background, so the following data only measures the maximum 26.5GHz

(4) Duty Cycle compensation less than 98% has been compensated in the test software prior to the implementation of the test

5.2 TEST PROCEDURE


- a. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- b. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- c. The height of the equipment or of the substitution antenna shall be 0.8m or 1.5m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- e. The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1GHz.
- f. The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- g. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform. (below 1GHz)
- h. All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1GHz)
- i. The test result is calculated as the following:
 - (1) Result = Reading + Correct Factor
 - (2) Correct Factor = Antenna Factor + Cable Loss – Amplifier Gain + Attenuator
 - (3) Margin = Result - Limit

5.3 MEASUREMENT INSTRUMENTS LIST


Item	Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	EMI Test Receiver	R&S	ESCI	101307	12/12/2020
2	Spectrum Analyzer	Agilent	E4407B	US40240708	11/17/2020
3	Loop antenna	SCHWARZBECK K	FMZB1519	1519-062	12/14/2020
4	Broadband antenna	SCHWARZBECK	VULB9168	VULB9168-192	03/22/2021
5	HORN ANTENNA	SCHWARZBECK	BBHA9120D	BBHA 9120D 1065	04/16/2020
6	Preamplifier Amplifier	HP	8447F	3113A05680	12/11/2020
7	PRE-AMPLIFIER	CY	EMC011830	980136	12/11/2020
8	RF Cable	R&S	Test Cable 4	4	12/11/2020
9	RF Cable	R&S	Test Cable 5	5	12/11/2020
10	RF Cable	R&S	Test Cable 9	9	04/22/2020
11	RF Cable	R&S	Test Cable 10	10	12/11/2020
12	Measurement Software	Farad	EZ-EMC (Ver.ATT-03A)	N/A	N/A

5.4 TESTSETUP


9 kHz to 30 MHz



30 MHz to 1 GHz



Above 1 GHz



5.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

5.6 TEST RESULTS - 9 KHZ to 30MHZ

Test Mode:	TX N (HT40) Mode / CH46 (UNII-1)
------------	----------------------------------

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	P
--	--	--	--	P

Note:


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $20 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor

5.7 TEST RESULTS - 30 MHz TO 1000 MHz


Test Mode: TX N (HT40) Mode / CH46 (UNII-1)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.5306	39.44	-11.42	28.02	40.00	-11.98	QP
2	46.0164	41.29	-13.81	27.48	40.00	-12.52	QP
3	73.6170	42.85	-14.73	28.12	40.00	-11.88	QP
4	86.5029	48.88	-15.28	33.60	40.00	-6.40	QP
5	167.8243	44.26	-10.48	33.78	43.50	-9.72	QP
6	277.0935	39.59	-7.92	31.67	46.00	-14.33	QP

Test Mode: TX N (HT40) Mode / CH46 (UNII-1)


Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	149.4857	44.73	-12.53	32.20	43.50	-11.30	QP
2	180.0165	45.18	-9.72	35.46	43.50	-8.04	QP
3	199.2855	45.57	-9.13	36.44	43.50	-7.06	QP
4	249.4250	45.76	-6.07	39.69	46.00	-6.31	QP
5	276.1235	45.76	-5.22	40.54	46.00	-5.46	QP
6	299.3158	47.28	-5.94	41.34	46.00	-4.66	QP


5.8 TEST RESULTS - ABOVE1000 MHz(BAND EDGE)

Orthogonal Axis	X
Test Mode	UNII-1_TX A Mode 5180 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	50.59	-1.90	48.69	68.30	-19.61	peak
2	5150.000	40.69	-1.90	38.79	54.00	-15.21	AVG
3	5182.806	89.13	-1.74	87.39	/	/	AVG
4	5185.411	97.67	-1.74	95.93	/	/	peak


Orthogonal Axis	X
Test Mode	UNII-1_TX A Mode 5180 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	67.98	-1.90	66.08	68.30	-2.22	peak
2	5150.000	52.87	-1.90	50.97	54.00	-3.03	AVG
3	5176.593	103.32	-1.78	101.54	/	/	peak
4	5182.806	94.48	-1.74	92.74	/	/	AVG

Orthogonal Axis	X
Test Mode	UNII-1_TX A Mode 5240 MHz


Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5238.725	98.00	-1.49	96.51	/	/	peak
2	5242.734	89.51	-1.47	88.04	/	/	AVG
3	5350.000	50.36	-0.97	49.39	68.30	-18.91	peak
4	5350.000	39.22	-0.97	38.25	54.00	-15.75	AVG


Orthogonal Axis	X
Test Mode	UNII-1_TX A Mode 5240 MHz

Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5236.721	103.40	-1.50	101.90	/	/	peak
2	5242.734	94.30	-1.47	92.83	/	/	AVG
3	5350.000	48.06	-0.97	47.09	68.30	-21.21	peak
4	5350.000	39.27	-0.97	38.30	54.00	-15.70	AVG

Orthogonal Axis	X
Test Mode	UNII-1_TX N (HT20) Mode 5180 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	50.38	-1.90	48.48	68.30	-19.82	peak
2	5150.000	40.56	-1.90	38.66	54.00	-15.34	AVG
3	5175.992	98.89	-1.78	97.11	/	/	peak
4	5176.994	88.61	-1.78	86.83	/	/	AVG


Orthogonal Axis	X
Test Mode	UNII-1_TX N (HT20) Mode 5180 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	63.64	-1.90	61.74	68.30	-6.56	peak
2	5150.000	50.20	-1.90	48.30	54.00	-5.70	AVG
3	5178.798	93.21	-1.76	91.45	/	/	AVG
4	5183.206	103.38	-1.74	101.64	/	/	peak

Orthogonal Axis	X
Test Mode	UNII-1_TX N (HT20) Mode 5240 MHz


Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5233.922	99.76	-1.51	98.25	/	/	peak
2	5235.525	91.00	-1.50	89.50	/	/	AVG
3	5350.000	49.56	-0.97	48.59	68.30	-19.71	peak
4	5350.000	39.06	-0.97	38.09	54.00	-15.91	AVG


Orthogonal Axis	X
Test Mode	UNII-1_TX N (HT20) Mode 5240 MHz

Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5236.527	94.99	-1.50	93.49	/	/	AVG
2	5243.341	105.05	-1.47	103.58	/	/	peak
3	5350.000	48.47	-0.97	47.50	68.30	-20.80	peak
4	5350.000	38.56	-0.97	37.59	54.00	-16.41	AVG


Orthogonal Axis	X
Test Mode	UNII-1_TX N (HT40) Mode 5190 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	66.76	-1.90	64.86	68.30	-3.44	peak
2	5150.000	53.13	-1.90	51.23	54.00	-2.77	AVG
3	5183.086	97.42	-1.74	95.68	/	/	peak
4	5186.092	87.65	-1.73	85.92	/	/	AVG


Orthogonal Axis	X
Test Mode	UNII-1_TX N (HT40) Mode 5190 MHz

Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	63.28	-1.90	61.38	68.30	-6.92	peak
2	5150.000	50.05	-1.90	48.15	54.00	-5.85	AVG
3	5198.417	86.94	-1.67	85.27	/	/	AVG
4	5201.122	96.81	-1.67	95.14	/	/	peak

Orthogonal Axis	X
Test Mode	UNII-1_TX N (HT40) Mode 5230 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5226.092	90.35	-1.54	88.81	/	/	AVG
2	5234.509	99.37	-1.51	97.86	/	/	peak
3	5350.000	49.39	-0.97	48.42	68.30	-19.88	peak
4	5350.000	40.04	-0.97	39.07	54.00	-14.93	AVG


Orthogonal Axis	X
Test Mode	UNII-1_TX N (HT40) Mode 5230 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5227.896	92.16	-1.53	90.63	/	/	AVG
2	5231.503	102.22	-1.52	100.70	/	/	peak
3	5350.000	48.14	-0.97	47.17	68.30	-21.13	peak
4	5350.000	39.45	-0.97	38.48	54.00	-15.52	AVG

Orthogonal Axis	X
Test Mode	UNII-3_TX A Mode 5745 MHz


Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5644.239	52.61	-0.02	52.59	68.30	-15.71	peak
2	5676.027	52.71	0.04	52.75	87.56	-34.81	peak
3	5703.983	53.08	0.10	53.18	106.42	-53.24	peak
4	5717.059	56.32	0.11	56.43	110.08	-53.65	peak
5	5725.000	65.33	0.13	65.46	122.30	-56.84	peak
6	5742.986	98.49	0.16	98.65	122.30	-23.65	peak


Orthogonal Axis	X
Test Mode	UNII-3_TX A Mode 5745 MHz

Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5624.850	53.28	-0.06	53.22	68.30	-15.08	peak
2	5656.413	52.80	0.01	52.81	73.05	-20.24	peak
3	5696.769	55.55	0.08	55.63	102.91	-47.28	peak
4	5717.735	68.92	0.11	69.03	110.27	-41.24	peak
5	5725.000	77.01	0.13	77.14	122.30	-45.16	peak
6	5741.859	102.64	0.16	102.80	122.30	-19.50	peak

Orthogonal Axis	X
Test Mode	UNII-3_TX A Mode 5785 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5604.734	52.89	-0.08	52.81	68.30	-15.49	peak
2	5664.704	53.46	0.01	53.47	79.18	-25.71	peak
3	5725.000	51.49	0.13	51.62	122.30	-70.68	peak
4	5781.313	98.40	0.23	98.63	122.30	-23.67	peak
5	5850.000	51.04	0.36	51.40	122.30	-70.90	peak
6	5951.227	53.64	0.54	54.18	68.30	-14.12	peak

Orthogonal Axis	X
Test Mode	UNII-3_TX A Mode 5785 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5637.099	53.64	-0.03	53.61	68.30	-14.69	peak
2	5687.074	52.43	0.06	52.49	95.73	-43.24	peak
3	5725.000	50.76	0.13	50.89	122.30	-71.41	peak
4	5781.789	101.61	0.23	101.84	122.30	-20.46	peak
5	5850.000	51.10	0.36	51.46	122.30	-70.84	peak
6	5949.324	53.82	0.54	54.36	68.30	-13.94	peak


Orthogonal Axis	X
Test Mode	UNII-3_TX A Mode 5825 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5826.854	99.66	0.32	99.98	122.30	-22.32	peak
2	5840.130	74.99	0.34	75.33	122.30	-46.97	peak
3	5850.000	56.01	0.36	56.37	122.30	-65.93	peak
4	5904.760	53.85	0.46	54.31	83.28	-28.97	peak
5	5929.058	53.13	0.50	53.63	68.30	-14.67	peak
6	5969.389	54.31	0.57	54.88	68.30	-13.42	peak


Orthogonal Axis	X
Test Mode	UNII-3_TX A Mode 5825 MHz

Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5828.106	102.69	0.32	103.01	122.30	-19.29	peak
2	5850.000	68.40	0.36	68.76	122.30	-53.54	peak
3	5857.164	69.79	0.37	70.16	110.29	-40.13	peak
4	5867.184	57.21	0.38	57.59	107.49	-49.90	peak
5	5905.761	53.97	0.46	54.43	82.54	-28.11	peak
6	5927.806	53.97	0.50	54.47	68.30	-13.83	peak

Orthogonal Axis	X
Test Mode	UNII-3_TX N (HT20) Mode 5745 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5616.508	52.71	-0.07	52.64	68.30	-15.66	peak
2	5645.366	53.02	-0.02	53.00	68.30	-15.30	peak
3	5701.954	59.43	0.09	59.52	105.85	-46.33	peak
4	5712.324	67.72	0.11	67.83	108.75	-40.92	peak
5	5725.000	79.87	0.13	80.00	122.30	-42.30	peak
6	5748.171	103.51	0.17	103.68	122.30	-18.62	peak

Orthogonal Axis	X
Test Mode	UNII-3_TX N (HT20) Mode 5745 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5631.162	52.65	-0.04	52.61	68.30	-15.69	peak
2	5676.703	60.09	0.04	60.13	88.06	-27.93	peak
3	5697.219	68.70	0.08	68.78	103.24	-34.46	peak
4	5708.266	76.53	0.10	76.63	107.61	-30.98	peak
5	5725.000	86.23	0.13	86.36	122.30	-35.94	peak
6	5748.622	105.38	0.17	105.55	122.30	-16.75	peak

Orthogonal Axis	X
Test Mode	UNII-3_TX N (HT20) Mode 5785 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5613.301	53.21	-0.08	53.13	68.30	-15.17	peak
2	5725.000	51.34	0.13	51.47	122.30	-70.83	peak
3	5782.265	101.00	0.24	101.24	122.30	-21.06	peak
4	5850.000	51.42	0.36	51.78	122.30	-70.52	peak
5	5910.771	53.36	0.48	53.84	78.83	-24.99	peak
6	5957.891	54.10	0.56	54.66	68.30	-13.64	peak


Orthogonal Axis	X
Test Mode	UNII-3_TX N (HT20) Mode 5785 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5629.484	52.35	-0.04	52.31	68.30	-15.99	peak
2	5725.000	54.84	0.13	54.97	122.30	-67.33	peak
3	5784.168	104.18	0.24	104.42	122.30	-17.88	peak
4	5850.000	51.22	0.36	51.58	122.30	-70.72	peak
5	5855.561	53.86	0.37	54.23	110.74	-56.51	peak
6	5941.233	53.71	0.52	54.23	68.30	-14.07	peak

Orthogonal Axis	X
Test Mode	UNII-3_TX N (HT20) Mode 5825 MHz


Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5819.589	100.44	0.30	100.74	122.30	-21.56	peak
2	5850.000	58.33	0.36	58.69	122.30	-63.61	peak
3	5868.437	53.93	0.39	54.32	107.14	-52.82	peak
4	5922.044	53.83	0.49	54.32	70.49	-16.17	peak
5	5944.840	53.31	0.52	53.83	68.30	-14.47	peak
6	5969.389	53.25	0.57	53.82	68.30	-14.48	peak


Orthogonal Axis	X
Test Mode	UNII-3_TX N (HT20) Mode 5825 MHz

Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5828.607	104.38	0.32	104.70	122.30	-17.60	peak
2	5850.000	75.40	0.36	75.76	122.30	-46.54	peak
3	5854.158	77.54	0.37	77.91	112.82	-34.91	peak
4	5870.190	64.10	0.39	64.49	106.65	-42.16	peak
5	5930.561	53.20	0.50	53.70	68.30	-14.60	peak
6	5968.637	54.20	0.57	54.77	68.30	-13.53	peak


Orthogonal Axis	X
Test Mode	UNII-3_TX N (HT40) Mode 5755 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5607.941	52.59	-0.08	52.51	68.30	-15.79	peak
2	5647.169	52.92	-0.01	52.91	68.30	-15.39	peak
3	5700.000	55.87	0.08	55.95	105.30	-49.35	peak
4	5711.197	73.51	0.11	73.62	108.44	-34.82	peak
5	5725.000	74.67	0.13	74.80	122.30	-47.50	peak
6	5757.866	98.93	0.19	99.12	122.30	-23.18	peak

Orthogonal Axis	X
Test Mode	UNII-3_TX N (HT40) Mode 5755 MHz


Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5645.366	57.54	-0.02	57.52	68.30	-10.78	peak
2	5653.482	59.91	0.00	59.91	70.88	-10.97	peak
3	5662.049	65.20	0.02	65.22	77.22	-12.00	peak
4	5700.000	72.42	0.08	72.50	105.30	-32.80	peak
5	5725.000	85.22	0.13	85.35	122.30	-36.95	peak
6	5758.091	102.04	0.19	102.23	122.30	-20.07	peak

Orthogonal Axis	X
Test Mode	UNII-3_TX N (HT40) Mode 5795 MHz


Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5798.798	98.39	0.26	98.65	122.30	-23.65	peak
2	5824.098	72.62	0.31	72.93	122.30	-49.37	peak
3	5850.000	52.47	0.36	52.83	122.30	-69.47	peak
4	5880.962	53.39	0.41	53.80	100.89	-47.09	peak
5	5925.801	53.38	0.50	53.88	68.30	-14.42	peak
6	5933.818	53.90	0.52	54.42	68.30	-13.88	peak


Orthogonal Axis	X
Test Mode	UNII-3_TX N (HT40) Mode 5795 MHz

Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5796.293	101.91	0.25	102.16	122.30	-20.14	peak
2	5850.000	68.77	0.36	69.13	122.30	-53.17	peak
3	5858.166	69.15	0.37	69.52	110.01	-40.49	peak
4	5865.431	66.51	0.38	66.89	107.98	-41.09	peak
5	5891.734	56.99	0.43	57.42	92.92	-35.50	peak
6	5924.299	53.51	0.49	54.00	68.82	-14.82	peak

Orthogonal Axis	X
Test Mode	UNII-1_TX AC (VHT20) Mode 5180 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	52.05	-1.90	50.15	68.30	-18.15	peak
2	5150.000	41.96	-1.90	40.06	54.00	-13.94	AVG
3	5177.896	90.79	-1.76	89.03	/	/	AVG
4	5182.705	100.35	-1.74	98.61	/	/	peak


Orthogonal Axis	X
Test Mode	UNII-1_TX AC (VHT20) Mode 5180 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	63.65	-1.90	61.75	68.30	-6.55	peak
2	5150.000	52.88	-1.90	50.98	54.00	-3.02	AVG
3	5177.896	94.14	-1.76	92.38	/	/	AVG
4	5183.307	103.36	-1.74	101.62	/	/	peak


Orthogonal Axis	X
Test Mode	UNII-1_TX AC (VHT20) Mode 5240 MHz

Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5234.890	90.03	-1.51	88.52	/	/	AVG
2	5243.006	99.36	-1.47	97.89	/	/	peak
3	5350.000	48.39	-0.97	47.42	68.30	-20.88	peak
4	5350.000	39.19	-0.97	38.22	54.00	-15.78	AVG

Orthogonal Axis	X
Test Mode	UNII-1_TX AC (VHT20) Mode 5240 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5237.896	94.52	-1.50	93.02	/	/	AVG
2	5242.104	103.00	-1.47	101.53	/	/	peak
3	5350.000	48.05	-0.97	47.08	68.30	-21.22	peak
4	5350.000	38.79	-0.97	37.82	54.00	-16.18	AVG

Orthogonal Axis	X
Test Mode	UNII-1_TX AC (VHT40) Mode 5190 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	50.69	-1.90	48.79	68.30	-19.51	peak
2	5150.000	40.44	-1.90	38.54	54.00	-15.46	AVG
3	5184.289	91.51	-1.74	89.77	/	/	peak
4	5187.896	81.04	-1.73	79.31	/	/	AVG

Orthogonal Axis	X
Test Mode	UNII-1_TX AC (VHT40) Mode 5190 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	62.29	-1.90	60.39	68.30	-7.91	peak
2	5150.000	50.63	-1.90	48.73	54.00	-5.27	AVG
3	5184.589	97.01	-1.74	95.27	/	/	peak
4	5198.116	87.60	-1.67	85.93	/	/	AVG

Orthogonal Axis	X
Test Mode	UNII-1_TX AC (VHT40) Mode 5230 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5222.786	92.13	-1.57	90.56	/	/	peak
2	5227.595	82.70	-1.53	81.17	/	/	AVG
3	5350.000	49.17	-0.97	48.20	68.30	-20.10	peak
4	5350.000	39.28	-0.97	38.31	54.00	-15.69	AVG


Orthogonal Axis	X
Test Mode	UNII-1_TX AC (VHT40) Mode 5230 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5238.116	90.67	-1.49	89.18	/	/	AVG
2	5238.417	100.30	-1.49	98.81	/	/	peak
3	5350.000	49.80	-0.97	48.83	68.30	-19.47	peak
4	5350.000	39.21	-0.97	38.24	54.00	-15.76	AVG


Orthogonal Axis	X
Test Mode	UNII-1_TX AC (VHT80) Mode 5210 MHz

Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	50.45	-1.90	48.55	68.30	-19.75	peak
2	5150.000	40.55	-1.90	38.65	54.00	-15.35	AVG
3	5222.325	77.24	-1.57	75.67	/	/	AVG
4	5228.938	87.27	-1.53	85.74	/	/	peak
5	5350.000	49.58	-0.97	48.61	68.30	-19.69	peak
6	5350.000	39.33	-0.97	38.36	54.00	-15.64	AVG

Orthogonal Axis	X
Test Mode	UNII-1_TX AC (VHT80) Mode 5210 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	65.04	-1.90	63.14	68.30	-5.16	peak
2	5150.000	52.20	-1.90	50.30	54.00	-3.70	AVG
3	5226.834	93.70	-1.54	92.16	/	/	peak
4	5233.447	83.39	-1.51	81.88	/	/	AVG
5	5350.000	49.14	-0.97	48.17	68.30	-20.13	peak
6	5350.000	39.61	-0.97	38.64	54.00	-15.36	AVG

Orthogonal Axis	X
Test Mode	UNII-3_TX AC (VHT20) Mode 5745 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5645.366	52.28	-0.02	52.26	68.30	-16.04	peak
2	5678.958	53.04	0.05	53.09	89.73	-36.64	peak
3	5700.000	51.66	0.08	51.74	105.30	-53.56	peak
4	5716.157	68.43	0.11	68.54	109.82	-41.28	peak
5	5725.000	78.59	0.13	78.72	122.30	-43.58	peak
6	5745.917	102.48	0.16	102.64	122.30	-19.66	peak


Orthogonal Axis	X
Test Mode	UNII-3_TX AC (VHT20) Mode 5745 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5635.446	53.36	-0.03	53.33	68.30	-14.97	peak
2	5687.074	60.01	0.06	60.07	95.73	-35.66	peak
3	5700.000	64.89	0.08	64.97	105.30	-40.33	peak
4	5711.874	75.52	0.11	75.63	108.62	-32.99	peak
5	5725.000	83.40	0.13	83.53	122.30	-38.77	peak
6	5750.877	104.51	0.18	104.69	122.30	-17.61	peak


Orthogonal Axis	X
Test Mode	UNII-3_TX AC (VHT20) Mode 5785 MHz

Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5648.522	53.72	-0.01	53.71	68.30	-14.59	peak
2	5685.646	53.28	0.06	53.34	94.68	-41.34	peak
3	5725.000	50.85	0.13	50.98	122.30	-71.32	peak
4	5786.548	99.29	0.24	99.53	122.30	-22.77	peak
5	5850.000	52.49	0.36	52.85	122.30	-69.45	peak
6	5937.425	53.09	0.51	53.60	68.30	-14.70	peak


Orthogonal Axis	X
Test Mode	UNII-3_TX AC (VHT20) Mode 5785 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5700.000	50.63	0.08	50.71	105.30	-54.59	peak
2	5725.000	50.91	0.13	51.04	122.30	-71.26	peak
3	5783.692	103.60	0.24	103.84	122.30	-18.46	peak
4	5850.000	51.15	0.36	51.51	122.30	-70.79	peak
5	5898.397	53.02	0.45	53.47	87.99	-34.52	peak
6	5968.838	54.40	0.57	54.97	68.30	-13.33	peak

Orthogonal Axis	X
Test Mode	UNII-3_TX AC (VHT20) Mode 5825 MHz


Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5830.611	98.83	0.32	99.15	122.30	-23.15	peak
2	5845.140	70.16	0.34	70.50	122.30	-51.80	peak
3	5850.000	55.17	0.36	55.53	122.30	-66.77	peak
4	5874.950	53.20	0.41	53.61	105.31	-51.70	peak
5	5916.533	53.55	0.47	54.02	74.57	-20.55	peak
6	5949.349	53.98	0.54	54.52	68.30	-13.78	peak

Orthogonal Axis	X
Test Mode	UNII-3_TX AC (VHT20) Mode 5825 MHz


Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5822.846	103.26	0.30	103.56	122.30	-18.74	peak
2	5850.000	72.74	0.36	73.10	122.30	-49.20	peak
3	5870.441	60.75	0.39	61.14	106.58	-45.44	peak
4	5897.244	52.77	0.45	53.22	88.84	-35.62	peak
5	5927.305	53.02	0.50	53.52	68.30	-14.78	peak
6	5971.393	53.56	0.58	54.14	68.30	-14.16	peak

Orthogonal Axis	X
Test Mode	UNII-3_TX AC (VHT40) Mode 5755 MHz


Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5644.239	52.67	-0.02	52.65	68.30	-15.65	peak
2	5700.000	52.29	0.08	52.37	105.30	-52.93	peak
3	5703.532	61.21	0.10	61.31	106.29	-44.98	peak
4	5720.892	73.06	0.12	73.18	112.93	-39.75	peak
5	5725.000	71.25	0.13	71.38	122.30	-50.92	peak
6	5761.698	97.32	0.20	97.52	122.30	-24.78	peak

Orthogonal Axis	X
Test Mode	UNII-3_TX AC (VHT40) Mode 5755 MHz


Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5644.239	53.28	-0.02	53.26	68.30	-15.04	peak
2	5678.733	63.28	0.05	63.33	89.56	-26.23	peak
3	5695.867	70.86	0.07	70.93	102.24	-31.31	peak
4	5721.793	83.59	0.12	83.71	114.99	-31.28	peak
5	5725.000	80.72	0.13	80.85	122.30	-41.45	peak
6	5743.888	101.20	0.16	101.36	122.30	-20.94	peak

Orthogonal Axis	X
Test Mode	UNII-3_TX AC (VHT40) Mode 5795 MHz


Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5789.529	97.30	0.25	97.55	122.30	-24.75	peak
2	5826.854	67.37	0.32	67.69	122.30	-54.61	peak
3	5850.000	51.81	0.36	52.17	122.30	-70.13	peak
4	5865.681	52.62	0.38	53.00	107.91	-54.91	peak
5	5889.980	53.80	0.43	54.23	94.21	-39.98	peak
6	5927.054	53.38	0.50	53.88	68.30	-14.42	peak


Orthogonal Axis	X
Test Mode	UNII-3_TX AC (VHT40) Mode 5795 MHz

Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5789.279	100.98	0.25	101.23	122.30	-21.07	peak
2	5850.000	67.09	0.36	67.45	122.30	-54.85	peak
3	5857.665	69.60	0.37	69.97	110.15	-40.18	peak
4	5881.212	60.42	0.41	60.83	100.70	-39.87	peak
5	5927.054	52.74	0.50	53.24	68.30	-15.06	peak
6	5942.836	53.31	0.52	53.83	68.30	-14.47	peak

Orthogonal Axis	X
Test Mode	UNII-3_TX AC (VHT80) Mode 5775 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5686.598	58.84	0.06	58.90	95.38	-36.48	peak
2	5693.261	59.38	0.07	59.45	100.31	-40.86	peak
3	5725.000	60.86	0.13	60.99	122.30	-61.31	peak
4	5786.548	93.42	0.24	93.66	122.30	-28.64	peak
5	5850.000	57.52	0.36	57.88	122.30	-64.42	peak
6	5998.347	55.09	0.63	55.72	68.30	-12.58	peak


Orthogonal Axis	X
Test Mode	UNII-3_TX AC (VHT80) Mode 5775 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5648.998	61.00	-0.01	60.99	68.30	-7.31	peak
2	5681.363	71.26	0.05	71.31	91.51	-20.20	peak
3	5725.000	76.57	0.13	76.70	122.30	-45.60	peak
4	5754.183	98.00	0.19	98.19	122.30	-24.11	peak
5	5850.000	71.16	0.36	71.52	122.30	-50.78	peak
6	5894.589	62.44	0.43	62.87	90.80	-27.93	peak

5.9 TEST RESULTS - ABOVE1000 MHz (HARMONIC)


Orthogonal Axis	X
Test Mode	UNII-1_TX A Mode 5180 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10360.500	44.94	12.43	57.37	68.30	-10.93	peak
2	10360.500	33.93	12.43	46.36	54.00	-7.64	AVG


Orthogonal Axis	X
Test Mode	UNII-1_TX A Mode 5180 MHz

Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10360.500	44.51	12.43	56.94	68.30	-11.36	peak
2	10360.500	33.18	12.43	45.61	54.00	-8.39	AVG

Orthogonal Axis	X
Test Mode	UNII-1_TX A Mode 5200 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10400.000	45.20	12.58	57.78	68.30	-10.52	peak
2	10400.000	33.07	12.58	45.65	54.00	-8.35	AVG

Orthogonal Axis	X
Test Mode	UNII-1_TX A Mode 5200 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10400.000	44.95	12.58	57.53	68.30	-10.77	peak
2	10400.000	31.54	12.58	44.12	54.00	-9.88	AVG

Orthogonal Axis	X
Test Mode	UNII-1_TX A Mode 5240 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10498.750	49.17	12.97	62.14	68.30	-6.16	peak
2	10498.750	37.26	12.97	50.23	54.00	-3.77	AVG

Orthogonal Axis	X
Test Mode	UNII-1_TX A Mode 5240 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10498.750	47.23	12.97	60.20	68.30	-8.10	peak
2	10498.750	35.82	12.97	48.79	54.00	-5.21	AVG

Orthogonal Axis	X
Test Mode	UNII-1_TX N (HT20) Mode 5180 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10363.500	46.21	12.45	58.66	68.30	-9.64	peak
2	10363.500	34.60	12.45	47.05	54.00	-6.95	AVG


Orthogonal Axis	X
Test Mode	UNII-1_TX N (HT20) Mode 5180 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10362.250	47.26	12.43	59.69	68.30	-8.61	peak
2	10362.250	35.49	12.43	47.92	54.00	-6.08	AVG


Orthogonal Axis	X
Test Mode	UNII-1_TX N (HT20) Mode 5200 MHz

Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10400.000	46.78	12.58	59.36	68.30	-8.94	peak
2	10400.000	34.72	12.58	47.30	54.00	-6.70	AVG

Orthogonal Axis	X
Test Mode	UNII-1_TX N (HT20) Mode 5200 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10400.000	44.72	12.58	57.30	68.30	-11.00	peak
2	10400.000	34.98	12.58	47.56	54.00	-6.44	AVG

Orthogonal Axis	X
Test Mode	UNII-1_TX N (HT20) Mode 5240 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10480.000	46.10	12.90	59.00	68.30	-9.30	peak
2	10480.000	35.30	12.90	48.20	54.00	-5.80	AVG

Orthogonal Axis	X
Test Mode	UNII-1_TX N (HT20) Mode 5240 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10480.000	45.03	12.90	57.93	68.30	-10.37	peak
2	10480.000	34.40	12.90	47.30	54.00	-6.70	AVG

Orthogonal Axis	X
Test Mode	UNII-1_TX N (HT40) Mode 5190 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10380.000	43.32	12.51	55.83	68.30	-12.47	peak
2	10380.000	33.85	12.51	46.36	54.00	-7.64	AVG


Orthogonal Axis	X
Test Mode	UNII-1_TX N (HT40) Mode 5190 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10380.600	44.01	12.51	56.52	68.30	-11.78	peak
2	10380.600	33.44	12.51	45.95	54.00	-8.05	AVG


Orthogonal Axis	X
Test Mode	UNII-1_TX N (HT40) Mode 5230 MHz

Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10460.560	45.18	12.81	57.99	68.30	-10.31	peak
2	10460.560	34.33	12.81	47.14	54.00	-6.86	AVG

Orthogonal Axis	X
Test Mode	UNII-1_TX N (HT40) Mode 5230 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10460.500	45.30	12.81	58.11	68.30	-10.19	peak
2	10460.500	34.81	12.81	47.62	54.00	-6.38	AVG

Orthogonal Axis	X
Test Mode	UNII-3_TX A Mode 5745 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11518.750	45.50	14.86	60.36	68.30	-7.94	peak
2	11518.750	34.76	14.86	49.62	54.00	-4.38	AVG

Orthogonal Axis	X
Test Mode	UNII-3_TX A Mode 5745 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11518.750	44.08	14.86	58.94	68.30	-9.36	peak
2	11518.750	32.10	14.86	46.96	54.00	-7.04	AVG

Orthogonal Axis	X
Test Mode	UNII-3_TX A Mode 5785 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11582.500	46.26	14.85	61.11	68.30	-7.19	peak
2	11582.500	33.10	14.85	47.95	54.00	-6.05	AVG

Orthogonal Axis	X
Test Mode	UNII-3_TX A Mode 5785 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11582.500	45.67	14.85	60.52	68.30	-7.78	peak
2	11582.500	33.99	14.85	48.84	54.00	-5.16	AVG

Orthogonal Axis	X
Test Mode	UNII-3_TX A Mode 5825 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11646.250	45.04	14.85	59.89	68.30	-8.41	peak
2	11646.250	31.71	14.85	46.56	54.00	-7.44	AVG

Orthogonal Axis	X
Test Mode	UNII-3_TX A Mode 5825 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11646.250	46.32	14.85	61.17	68.30	-7.13	peak
2	11646.250	33.78	14.85	48.63	54.00	-5.37	AVG

Orthogonal Axis	X
Test Mode	UNII-3_TX N (HT20) Mode 5745 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11489.700	44.80	14.87	59.67	68.30	-8.63	peak
2	11489.700	33.73	14.87	48.60	54.00	-5.40	AVG

Orthogonal Axis	X
Test Mode	UNII-3_TX N (HT20) Mode 5745 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11518.750	43.80	14.86	58.66	68.30	-9.64	peak
2	11518.750	32.72	14.86	47.58	54.00	-6.42	AVG

Orthogonal Axis	X
Test Mode	UNII-3_TX N (HT20) Mode 5785 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11576.500	44.54	14.86	59.40	68.30	-8.90	peak
2	11576.500	34.70	14.86	49.56	54.00	-4.44	AVG

Orthogonal Axis	X
Test Mode	UNII-3_TX N (HT20) Mode 5785 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11569.800	46.45	14.85	61.30	68.30	-7.00	peak
2	11569.800	35.31	14.85	50.16	54.00	-3.84	AVG

Orthogonal Axis	X
Test Mode	UNII-3_TX N (HT20) Mode 5825 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11650.000	43.09	14.85	57.94	68.30	-10.36	peak
2	11650.000	33.41	14.85	48.26	54.00	-5.74	AVG

Orthogonal Axis	X
Test Mode	UNII-3_TX N (HT20) Mode 5825 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11650.350	41.59	14.84	56.43	68.30	-11.87	peak
2	11650.350	31.46	14.84	46.30	54.00	-7.70	AVG

Orthogonal Axis	X
Test Mode	UNII-3_TX N (HT40) Mode 5755 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11510.300	45.78	14.85	60.63	68.30	-7.67	peak
2	11510.300	34.51	14.85	49.36	54.00	-4.64	AVG

Orthogonal Axis	X
Test Mode	UNII-3_TX N (HT40) Mode 5755 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11510.500	48.35	14.85	63.20	68.30	-5.10	peak
2	11510.500	34.78	14.85	49.63	54.00	-4.37	AVG

Orthogonal Axis	X
Test Mode	UNII-3_TX N (HT40) Mode 5795 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11589.350	45.37	14.86	60.23	68.30	-8.07	peak
2	11589.350	33.96	14.86	48.82	54.00	-5.18	AVG


Orthogonal Axis	X
Test Mode	UNII-3_TX N (HT40) Mode 5795 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11590.850	46.69	14.86	61.55	68.30	-6.75	peak
2	11590.850	32.97	14.86	47.83	54.00	-6.17	AVG


Orthogonal Axis	X
Test Mode	UNII-1_TX AC (VHT20) Mode 5180 MHz

Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10360.000	43.19	12.43	55.62	68.30	-12.68	peak
2	10360.000	33.87	12.43	46.30	54.00	-7.70	AVG


Orthogonal Axis	X
Test Mode	UNII-1_TX AC (VHT20) Mode 5180 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10360.500	45.05	12.43	57.48	68.30	-10.82	peak
2	10360.500	35.19	12.43	47.62	54.00	-6.38	AVG


Orthogonal Axis	X
Test Mode	UNII-1_TX AC (VHT20) Mode 5200 MHz

Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10400.750	43.69	12.58	56.27	68.30	-12.03	peak
2	10400.750	33.81	12.58	46.39	54.00	-7.61	AVG

Orthogonal Axis	X
Test Mode	UNII-1_TX AC (VHT20) Mode 5200 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10400.630	44.48	12.58	57.06	68.30	-11.24	peak
2	10400.630	34.01	12.58	46.59	54.00	-7.41	AVG

Orthogonal Axis	X
Test Mode	UNII-1_TX AC (VHT20) Mode 5240 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10480.650	45.79	12.90	58.69	68.30	-9.61	peak
2	10480.650	33.46	12.90	46.36	54.00	-7.64	AVG


Orthogonal Axis	X
Test Mode	UNII-1_TX AC (VHT20) Mode 5240 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10480.550	49.48	12.90	62.38	68.30	-5.92	peak
2	10480.550	36.73	12.90	49.63	54.00	-4.37	AVG


Orthogonal Axis	X
Test Mode	UNII-1_TX AC (VHT40) Mode 5190 MHz

Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10380.500	46.01	12.51	58.52	68.30	-9.78	peak
2	10380.500	35.97	12.51	48.48	54.00	-5.52	AVG

Orthogonal Axis	X
Test Mode	UNII-1_TX AC (VHT40) Mode 5190 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10380.470	49.01	12.51	61.52	68.30	-6.78	peak
2	10380.470	36.86	12.51	49.37	54.00	-4.63	AVG

Orthogonal Axis	X
Test Mode	UNII-1_TX AC (VHT40) Mode 5230 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10460.150	44.01	12.81	56.82	68.30	-11.48	peak
2	10460.150	33.55	12.81	46.36	54.00	-7.64	AVG

Orthogonal Axis	X
Test Mode	UNII-1_TX AC (VHT40) Mode 5230 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10460.000	48.93	12.81	61.74	68.30	-6.56	peak
2	10460.000	36.19	12.81	49.00	54.00	-5.00	AVG


Orthogonal Axis	X
Test Mode	UNII-1_TX AC (VHT80) Mode 5210 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10420.500	46.26	12.66	58.92	68.30	-9.38	peak
2	10420.500	35.71	12.66	48.37	54.00	-5.63	AVG


Orthogonal Axis	X
Test Mode	UNII-1_TX AC (VHT80) Mode 5210 MHz

Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10420.650	49.70	12.66	62.36	68.30	-5.94	peak
2	10420.650	35.25	12.66	47.91	54.00	-6.09	AVG

Orthogonal Axis	X
Test Mode	UNII-3_TX AC (VHT20) Mode 5745 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11490.750	43.36	14.87	58.23	68.30	-10.07	peak
2	11490.750	33.95	14.87	48.82	54.00	-5.18	AVG

Orthogonal Axis	X
Test Mode	UNII-3_TX AC (VHT20) Mode 5745 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11490.630	46.65	14.87	61.52	68.30	-6.78	peak
2	11490.630	35.23	14.87	50.10	54.00	-3.90	AVG

Orthogonal Axis	X
Test Mode	UNII-3_TX AC (VHT20) Mode 5785 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11570.060	44.57	14.85	59.42	68.30	-8.88	peak
2	11570.060	32.71	14.85	47.56	54.00	-6.44	AVG

Orthogonal Axis	X
Test Mode	UNII-3_TX AC (VHT20) Mode 5785 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11570.500	45.51	14.85	60.36	68.30	-7.94	peak
2	11570.500	34.05	14.85	48.90	54.00	-5.10	AVG

Orthogonal Axis	X
Test Mode	UNII-3_TX AC (VHT20) Mode 5825 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11650.450	44.79	14.84	59.63	68.30	-8.67	peak
2	11650.450	33.24	14.84	48.08	54.00	-5.92	AVG


Orthogonal Axis	X
Test Mode	UNII-3_TX AC (VHT20) Mode 5825 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11650.850	48.73	14.84	63.57	68.30	-4.73	peak
2	11650.850	35.79	14.84	50.63	54.00	-3.37	AVG


Orthogonal Axis	X
Test Mode	UNII-3_TX AC (VHT40) Mode 5755 MHz

Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11510.650	44.99	14.85	59.84	68.30	-8.46	peak
2	11510.650	34.51	14.85	49.36	54.00	-4.64	AVG

Orthogonal Axis	X
Test Mode	UNII-3_TX AC (VHT40) Mode 5755 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11510.100	46.70	14.85	61.55	68.30	-6.75	peak
2	11510.100	35.04	14.85	49.89	54.00	-4.11	AVG

Orthogonal Axis	X
Test Mode	UNII-3_TX AC (VHT40) Mode 5795 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11590.360	43.48	14.86	58.34	68.30	-9.96	peak
2	11590.360	33.44	14.86	48.30	54.00	-5.70	AVG

Orthogonal Axis	X
Test Mode	UNII-3_TX AC (VHT40) Mode 5795 MHz




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11590.360	43.19	14.86	58.05	68.30	-10.25	peak
2	11590.360	32.30	14.86	47.16	54.00	-6.84	AVG

Orthogonal Axis	X
Test Mode	UNII-3_TX AC (VHT80) Mode 5775 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11570.000	44.87	14.85	59.72	68.30	-8.58	peak
2	11570.000	32.24	14.85	47.09	54.00	-6.91	AVG

Orthogonal Axis	X
Test Mode	UNII-3_TX AC (VHT80) Mode 5775 MHz



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	11570.000	48.45	14.85	63.30	68.30	-5.00	peak
2	11570.000	35.29	14.85	50.14	54.00	-3.86	AVG

6. BANDWIDTH TEST

6.1 LIMIT

FCC Part15, Subpart E (15.407) RSS-Gen and RSS-247			
Section	Test Item	Limit	Frequency Range (MHz)
15.407(a) 15.407(e) RSS-247 6.2.1.1 RSS-247 6.2.4.1	26 dB Bandwidth	-	5150-5250
	6dB Bandwidth	Minimum 500 kHz	5725-5850

6.2 TEST PROCEDURE AND SETTING

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below

- b. Spectrum Setting:

For UNII-1:

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> 26dB Bandwidth
RBW	300 kHz (Bandwidth 20 MHz) 1 MHz (Bandwidth 40 MHz and 80 MHz)
VBW	1 MHz (Bandwidth 20 MHz) 3 MHz (Bandwidth 40 MHz and 80 MHz)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

For UNII-3:

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	6dB Bandwidth
RBW	100 kHz
VBW	300 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

- c. Measured the spectrum width with power higher than 26dB / 6dB below carrier.

6.3 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum analyzer	KEYSIGHT	N9010A	MY55150427	2020/05/27
2	Attenuator	Mini-Circuits	BW-S10W2	101109	N/A
3	RF Cable	Mi-cable	C10-01-01-1	100309	N/A

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

6.6 TEST RESULTS

UNII-1_TX A Mode			
Channel	Frequency (MHz)	26 dB Bandwidth (MHz)	99 % Emission Bandwidth (MHz)
36	5180	18.61	16.398
40	5200	18.65	16.381
48	5240	21.99	16.448


CH36



CH40




CH48



UNII-1_TX N (HT20) Mode			
Channel	Frequency (MHz)	26 dB Bandwidth (MHz)	99 % Emission Bandwidth (MHz)
36	5180	19.53	17.557
40	5200	19.47	17.575
48	5240	19.59	17.528

CH36



CH40




CH48




UNII-1_TX N (HT40) Mode			
Channel	Frequency (MHz)	26 dB Bandwidth (MHz)	99 % Emission Bandwidth (MHz)
38	5190	40.49	35.983
46	5230	40.32	35.937

CH38




CH46



UNII-3 TX A Mode					
Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	99% Emission Bandwidth(MHz)	6dB Bandwidth Min. Limit(kHz)	Result
149	5745	16.52	16.463	500	PASS
157	5785	16.53	16.394	500	PASS
165	5825	16.52	16.409	500	PASS


CH149




6 dB Bandwidth
CH157




CH165




CH149



99% Emission Bandwidth
CH157




CH165




UNII-3_TX N (HT20) Mode					
Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	99% Emission Bandwidth(MHz)	6dB Bandwidth Min. Limit(kHz)	Result
149	5745	17.73	17.594	500	PASS
157	5785	17.75	17.552	500	PASS
165	5825	17.72	17.539	500	PASS


CH149




6 dB Bandwidth
CH157




CH165




CH149



99% Emission Bandwidth
CH157




CH165




UNII-3_TX N (HT40) Mode					
Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	99% Emission Bandwidth(MHz)	6dB Bandwidth Min. Limit(kHz)	Result
151	5755	36.46	36.033	500	PASS
159	5795	36.44	35.988	500	PASS

6 dB Bandwidth

CH151




CH159




99% Emission Bandwidth

CH151




CH159




UNII-1_TX AC (VHT20) Mode

Channel	Frequency (MHz)	26 dB Bandwidth (MHz)	99 % Emission Bandwidth (MHz)
36	5180	19.56	17.555
40	5200	19.47	17.563
48	5240	19.51	17.560


CH36



CH40




CH48




UNII-1_TX AC (VHT40) Mode

Channel	Frequency (MHz)	26 dB Bandwidth (MHz)	99 % Emission Bandwidth (MHz)
38	5190	40.18	35.991
46	5230	40.40	35.925

CH38




CH46



UNII-1_TX AC (VHT80) Mode

Channel	Frequency (MHz)	26 dB Bandwidth (MHz)	99 % Emission Bandwidth (MHz)
42	5210	79.15	74.747


CH42



UNII-3_TX AC (VHT20) Mode

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	99% Emission Bandwidth(MHz)	6dB Bandwidth Min. Limit(kHz)	Result
149	5745	17.70	17.757	500	PASS
157	5785	17.72	17.549	500	PASS
165	5825	17.70	17.557	500	PASS

CH149




6 dB Bandwidth
CH157




CH165




CH149



99% Emission Bandwidth
CH157




CH165




UNII-3_TX AC (VHT40) Mode					
Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	99% Emission Bandwidth(MHz)	6dB Bandwidth Min. Limit(kHz)	Result
151	5755	36.49	35.977	500	PASS
159	5795	36.46	35.991	500	PASS

6 dB Bandwidth

CH151




CH159




99% Emission Bandwidth

CH151




CH159




UNII-3_TX AC (VHT80) Mode

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	99% Emission Bandwidth(MHz)	6dB Bandwidth Min. Limit(kHz)	Result
155	5775	75.13	74.768	500	PASS

**6 dB Bandwidth
CH155**



**99% Emission Bandwidth
CH155**



7. MAXIMUM OUTPUT POWER TEST

7.1 LIMIT

FCC Part15, Subpart E (15.407)&RSS-247			
Section	Test Item	Limit	Frequency Range (MHz)
RSS-247 6.2.1.1	EIRP Output Power	not exceed 200 mW or $10 + 10 \log B$, dBm, whichever power is less	5150-5250
15.407(a)	Maximum Output Power	AP device: 1 Watt (30dBm) Client device: 250mW (24dBm)	5150-5250
15.407(a) RSS-247 6.2.4.1	Maximum Output Power	1 Watt (30dBm)	5725-5850

Note:

- For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
- B is the 99% emission bandwidth in megahertz.


7.2 TEST PROCEDURE AND SETTING

- The EUT was directly connected to the power meter and antenna output port as show in the block diagram below.
- Test was performed in accordance with method of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

7.3 MEASUREMENT INSTRUMENTS LIST

Item	Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	Power Sensor	KEYSIGHT	U2021XA	MY55240009	05/27/2020
2	Attenuator	Mini-Circuits	BW-S10W2	101109	N/A
3	RF Cable	Micable	C10-01-01-1	100309	N/A
4	Test Software	KEYSIGHT	Power Panel	V3.11	N/A

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

7.6 TEST RESULTS

UNII-1_TX A Mode_Ant 1 For FCC

Channel	Frequency (MHz)	Output Power (dBm)	Duty Factor	Output Power + Duty Factor (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
36	5180	14.85	0.00	14.85	24.00	0.25	PASS
40	5200	15.21	0.00	15.21	24.00	0.25	PASS
48	5240	16.26	0.00	16.26	24.00	0.25	PASS

UNII-1_TX A Mode_Ant 2 For FCC

Channel	Frequency (MHz)	Output Power (dBm)	Duty Factor	Output Power + Duty Factor (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
36	5180	15.04	0.00	15.04	24.00	0.25	PASS
40	5200	14.65	0.00	14.65	24.00	0.25	PASS
48	5240	15.32	0.00	15.32	24.00	0.25	PASS

UNII-1_TX A Mode_Ant 1 For IC

Channel	Frequency (MHz)	Output Power (dBm)	Duty Factor	EIRP + Duty Factor (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
36	5180	17.85	0.00	17.85	23.00	0.2	PASS
40	5200	18.21	0.00	18.21	23.00	0.2	PASS
48	5240	19.26	0.00	19.26	23.00	0.2	PASS

UNII-1_TX A Mode_Ant 2 For IC

Channel	Frequency (MHz)	Output Power (dBm)	Duty Factor	EIRP + Duty Factor (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
36	5180	18.04	0.00	18.04	23.00	0.2	PASS
40	5200	17.65	0.00	17.65	23.00	0.2	PASS
48	5240	18.32	0.00	18.32	23.00	0.2	PASS

UNII-1_TX N (HT20) Mode _Ant 1							
Channel	Frequency (MHz)	Output Power (dBm)	Duty Factor	Output Power + Duty Factor (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
36	5180	15.52	0.00	15.52	24.00	0.25	PASS
40	5200	14.90	0.00	14.90	24.00	0.25	PASS
48	5240	14.75	0.00	14.75	24.00	0.25	PASS

UNII-1_TX N (HT20) Mode _Ant 2							
Channel	Frequency (MHz)	Output Power (dBm)	Duty Factor	Output Power + Duty Factor (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
36	5180	14.98	0.00	14.98	24.00	0.25	PASS
40	5200	15.39	0.00	15.39	24.00	0.25	PASS
48	5240	15.63	0.00	15.63	24.00	0.25	PASS

UNII-1_TX N (HT20) Mode _Total For FCC					
Channel	Frequency (MHz)	Output Power (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
36	5180	18.27	24.00	0.25	PASS
40	5200	18.16	24.00	0.25	PASS
48	5240	18.22	24.00	0.25	PASS

UNII-1_TX N (HT20) Mode _Total For IC					
Channel	Frequency (MHz)	EIRP Power (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
36	5180	21.27	23.00	0.2	PASS
40	5200	21.16	23.00	0.2	PASS
48	5240	21.22	23.00	0.2	PASS

UNII-1_TX N (HT40) Mode_Ant 1

Channel	Frequency (MHz)	Output Power (dBm)	Duty Factor	Output Power + Duty Factor (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
38	5190	14.97	0.00	14.97	24.00	0.25	PASS
46	5230	15.90	0.00	15.90	24.00	0.25	PASS

UNII-1_TX N (HT40) Mode_Ant 2

Channel	Frequency (MHz)	Output Power (dBm)	Duty Factor	Output Power + Duty Factor (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
38	5190	14.73	0.00	14.73	24.00	0.25	PASS
46	5230	15.63	0.00	15.63	24.00	0.25	PASS

UNII-1_TX N (HT40) Mode_Total For FCC

Channel	Frequency (MHz)	Output Power (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
38	5190	17.86	24.00	0.25	PASS
46	5230	18.78	24.00	0.25	PASS

UNII-1_TX N (HT40) Mode_Total For IC

Channel	Frequency (MHz)	EIRP Power (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
38	5190	20.86	23.00	0.2	PASS
46	5230	21.78	23.00	0.2	PASS

UNII-3_TX A Mode_Ant1							
Channel	Frequency (MHz)	Output Power (dBm)	Duty Factor	Output Power + Duty Factor (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
149	5745	14.99	0.00	14.99	30.00	1.00	PASS
157	5785	14.43	0.00	14.43	30.00	1.00	PASS
165	5825	15.43	0.00	15.43	30.00	1.00	PASS

UNII-3_TX A Mode_Ant2							
Channel	Frequency (MHz)	Output Power (dBm)	Duty Factor	Output Power + Duty Factor (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
149	5745	14.89	0.00	14.89	30.00	1.00	PASS
157	5785	15.29	0.00	15.29	30.00	1.00	PASS
165	5825	15.11	0.00	15.11	30.00	1.00	PASS

UNII-3_TX N (HT20) Mode_Ant1							
Channel	Frequency (MHz)	Output Power (dBm)	Duty Factor	Output Power + Duty Factor (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
149	5745	15.10	0.00	15.10	30.00	1.00	PASS
157	5785	15.03	0.00	15.03	30.00	1.00	PASS
165	5825	14.95	0.00	14.95	30.00	1.00	PASS

UNII-3_TX N (HT20) Mode_Ant 2							
Channel	Frequency (MHz)	Output Power (dBm)	Duty Factor	Output Power + Duty Factor (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
149	5745	15.19	0.00	15.19	30.00	1.00	PASS
157	5785	15.33	0.00	15.33	30.00	1.00	PASS
165	5825	15.15	0.00	15.15	30.00	1.00	PASS

UNII-3_TX N (HT20) Mode_Total					
Channel	Frequency (MHz)	Output Power (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
149	5745	18.16	30.00	1.00	PASS
157	5785	18.19	30.00	1.00	PASS
165	5825	18.06	30.00	1.00	PASS

UNII-3_TX N (HT40) Mode_Ant 1

Channel	Frequency (MHz)	Output Power (dBm)	Duty Factor	Output Power + Duty Factor (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
151	5755	15.27	0.00	15.27	30.00	1.00	PASS
159	5795	15.43	0.00	15.43	30.00	1.00	PASS

UNII-3_TX N (HT40) Mode_Ant 2

Channel	Frequency (MHz)	Output Power (dBm)	Duty Factor	Output Power + Duty Factor (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
151	5755	14.86	0.00	14.86	30.00	1.00	PASS
159	5795	15.43	0.00	15.43	30.00	1.00	PASS

UNII-3_TX N (HT40) Mode_Total

Channel	Frequency (MHz)	Output Power (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
151	5755	18.08	30.00	1.00	PASS
159	5795	18.44	30.00	1.00	PASS

UNII-1_TX AC (VHT20) Mode_Ant 1

Channel	Frequency (MHz)	Output Power (dBm)	Duty Factor	Output Power + Duty Factor (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
36	5180	15.51	0.00	15.51	24.00	0.25	PASS
40	5200	14.96	0.00	14.96	24.00	0.25	PASS
48	5240	15.73	0.00	15.73	24.00	0.25	PASS

UNII-1_TX AC (VHT20) Mode_Ant 2

Channel	Frequency (MHz)	Output Power (dBm)	Duty Factor	Output Power + Duty Factor (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
36	5180	15.14	0.00	15.14	24.00	0.25	PASS
40	5200	15.23	0.00	15.23	24.00	0.25	PASS
48	5240	15.61	0.00	15.61	24.00	0.25	PASS

UNII-1_TX AC (VHT20) Mode_Total For FCC

Channel	Frequency (MHz)	Output Power (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
36	5180	18.34	24.00	0.25	PASS
40	5200	18.11	24.00	0.25	PASS
48	5240	18.68	24.00	0.25	PASS

UNII-1_TX AC (VHT20) Mode_Total For IC

Channel	Frequency (MHz)	EIRP Power (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
36	5180	21.34	23.00	0.2	PASS
40	5200	21.11	23.00	0.2	PASS
48	5240	21.68	23.00	0.2	PASS

UNII-1_TX AC (VHT40) Mode_Ant 1							
Channel	Frequency (MHz)	Output Power (dBm)	Duty Factor	Output Power + Duty Factor (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
38	5190	15.35	0.00	15.35	24.00	0.25	PASS
46	5230	15.23	0.00	15.23	24.00	0.25	PASS

UNII-1_TX AC (VHT40) Mode_Ant 2							
Channel	Frequency (MHz)	Output Power (dBm)	Duty Factor	Output Power + Duty Factor (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
38	5190	14.85	0.00	14.85	24.00	0.25	PASS
46	5230	15.08	0.00	15.08	24.00	0.25	PASS

UNII-1_TX AC (VHT40) Mode_Total For FCC					
Channel	Frequency (MHz)	Output Power (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
38	5190	18.12	24.00	0.25	PASS
46	5230	18.17	24.00	0.25	PASS

UNII-1_TX AC (VHT40) Mode_Total For IC					
Channel	Frequency (MHz)	EIRP Power (dBm))	Max. Limit (dBm)	Max. Limit (W)	Result
38	5190	21.12	23.00	0.2	PASS
46	5230	21.17	23.00	0.2	PASS

UNII-1_TX AC (VHT80) Mode_Ant 1							
Channel	Frequency (MHz)	Output Power (dBm)	Duty Factor	Output Power + Duty Factor (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
42	5210	13.32	0.00	13.32	24.00	0.25	PASS

UNII-1_TX AC (VHT80) Mode_Ant 2							
Channel	Frequency (MHz)	Output Power (dBm)	Duty Factor	Output Power + Duty Factor (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
42	5210	13.02	0.00	13.02	24.00	0.25	PASS

UNII-1_TX AC (VHT80) Mode_Total For FCC					
Channel	Frequency (MHz)	Output Power (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
42	5210	16.18	24.00	0.25	PASS

UNII-1_TX AC (VHT80) Mode_Total For IC					
Channel	Frequency (MHz)	EIRP Power (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
42	5210	19.18	23.00	0.2	PASS

UNII-3_TX AC (VHT20) Mode_Ant 1							
Channel	Frequency (MHz)	Output Power (dBm)	Duty Factor	Output Power + Duty Factor (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
149	5745	15.72	0.00	15.72	30.00	1.00	PASS
157	5785	14.96	0.00	14.96	30.00	1.00	PASS
165	5825	15.08	0.00	15.08	30.00	1.00	PASS

UNII-3_TX AC (VHT20) Mode_Ant 2							
Channel	Frequency (MHz)	Output Power (dBm)	Duty Factor	Output Power + Duty Factor (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
149	5745	15.13	0.00	15.13	30.00	1.00	PASS
157	5785	15.19	0.00	15.19	30.00	1.00	PASS
165	5825	15.76	0.00	15.76	30.00	1.00	PASS

UNII-3_TX AC (VHT20) Mode_Total					
Channel	Frequency (MHz)	Output Power (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
149	5745	18.45	30.00	1.00	PASS
157	5785	18.09	30.00	1.00	PASS
165	5825	18.44	30.00	1.00	PASS

UNII-3_TX AC (VHT40) Mode_Ant 1							
Channel	Frequency (MHz)	Output Power (dBm)	Duty Factor	Output Power + Duty Factor (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
151	5755	15.38	0.00	15.38	30.00	1.00	PASS
159	5795	15.53	0.00	15.53	30.00	1.00	PASS

UNII-3_TX AC (VHT40) Mode_Ant 2							
Channel	Frequency (MHz)	Output Power (dBm)	Duty Factor	Output Power + Duty Factor (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
151	5755	14.89	0.00	14.89	30.00	1.00	PASS
159	5795	15.31	0.00	15.31	30.00	1.00	PASS

UNII-3_TX AC (VHT40) Mode_Total					
Channel	Frequency (MHz)	Output Power (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
151	5755	18.15	30.00	1.00	PASS
159	5795	18.43	30.00	1.00	PASS

UNII-3_TX AC (VHT80) Mode_Ant 1							
Channel	Frequency (MHz)	Output Power (dBm)	Duty Factor	Output Power + Duty Factor (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
155	5775	13.36	0.00	13.36	30.00	1.00	PASS

UNII-3_TX AC (VHT80) Mode_Ant2							
Channel	Frequency (MHz)	Output Power (dBm)	Duty Factor	Output Power + Duty Factor (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
155	5775	13.35	0.00	13.35	30.00	1.00	PASS

UNII-3_TX AC (VHT80) Mode_Total					
Channel	Frequency (MHz)	Output Power (dBm)	Max. Limit (dBm)	Max. Limit (W)	Result
155	5775	16.37	30.00	1.00	PASS

8. POWER SPECTRAL DENSITY TEST

8.1 LIMIT

FCC Part15, Subpart E (15.407)&RSS-247			
Section	Test Item	Limit	Frequency Range (MHz)
RSS-247 6.2.1.2	EIRP Power Spectral Density	10dBm/MHz	5150-5250
15.407(a)	Power Spectral Density	AP device:17dBm/MHz Client device:11dBm/MHz	5150-5250
15.407(a) RSS-247 6.2.4.2	Power Spectral Density	30dBm/500kHz	5725-5850

8.2 TEST PROCEDURE AND SETTING

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- Spectrum Setting:

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RBW	= 1MHz.
VBW	≥ 3MHz.
Detector	RMS
Trace average	100 trace
Sweep Time	Auto

Note:

- For UNII-3, according to KDB publication 789033 D02 General UNII Test Procedures New Rules v02r01, section II.F.5., it is acceptable to set RBW at 1MHz and VBW at 3MHz if the spectrum analyzer does not have 500kHz RBW.
- The value measured with RBW=1MHz is to be added with $10\log(500\text{kHz}/1\text{MHz})$ which is -3dB. For example, if the measured value is +10dBm using RBW=1MHz (that is +10dBm/MHz), then the converted value will be +7dBm/500kHz.

8.3 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum analyzer	KEYSIGHT	N9010A	MY55150427	2020/05/27
2	Attenuator	Mini-Circuits	BW-S10W2	101109	N/A
3	RF Cable	Mi-cable	C10-01-01-1	100309	N/A

8.4 TEST SETUP



8.5 EUT OPERATION CONDITIONS


The EUT was programmed to be in continuously transmitting mode.

8.6 TEST RESULTS


UNII-1_TX A Mode_Ant 1 For FCC						
Channel	Frequency (MHz)	Power Spectral Density (dBm/MHz)	Duty Factor	Power Spectral Density + Duty Factor (dBm/MHz)	Max. Limit (dBm/MHz)	Result
36	5180	4.06	0.00	4.06	11.00	PASS
40	5200	4.49	0.00	4.49	11.00	PASS
48	5240	5.82	0.00	5.82	11.00	PASS

UNII-1_TX A Mode_Ant 1 For IC						
Channel	Frequency (MHz)	Power Spectral Density (dBm/MHz)	Duty Factor	EIRP Power Spectral Density + Duty Factor (dBm/MHz)	Max. Limit (dBm/MHz)	Result
36	5180	7.06	0.00	7.06	10.00	PASS
40	5200	7.49	0.00	7.49	10.00	PASS
48	5240	8.82	0.00	8.82	10.00	PASS


CH36



CH40



CH48




UNII-1_TX A Mode_Ant2 For FCC

Channel	Frequency (MHz)	Power Spectral Density (dBm/MHz)	Duty Factor	Power Spectral Density + Duty Factor (dBm/MHz)	Max. Limit (dBm/MHz)	Result
36	5180	2.23	0.00	2.23	11.00	PASS
40	5200	1.98	0.00	1.98	11.00	PASS
48	5240	2.60	0.00	2.60	11.00	PASS


UNII-1_TX A Mode_Ant2 For IC

Channel	Frequency (MHz)	Power Spectral Density (dBm/MHz)	Duty Factor	EIRP Power Spectral Density + Duty Factor (dBm/MHz)	Max. Limit (dBm/MHz)	Result
36	5180	5.23	0.00	5.23	10.00	PASS
40	5200	4.98	0.00	4.98	10.00	PASS
48	5240	5.60	0.00	5.60	10.00	PASS


CH36



CH40




CH48




UNII-1_TX N (HT20) Mode_Ant 1

Channel	Frequency (MHz)	Power Spectral Density (dBm/MHz)	Duty Factor	Power Spectral Density + Duty Factor (dBm/MHz)	Max. Limit (dBm/MHz)	Result
36	5180	3.90	0.00	3.90	11.00	PASS
40	5200	2.87	0.00	2.87	11.00	PASS
48	5240	2.93	0.00	2.93	11.00	PASS


CH36



CH40




CH48




UNII-1_TX N (HT20) Mode_Ant 2

Channel	Frequency (MHz)	Power Spectral Density (dBm/MHz)	Duty Factor	Power Spectral Density + Duty Factor (dBm/MHz)	Max. Limit (dBm/MHz)	Result
36	5180	2.03	0.00	2.03	11.00	PASS
40	5200	2.49	0.00	2.49	11.00	PASS
48	5240	3.60	0.00	3.60	11.00	PASS


CH36



CH40



CH48



UNII-1_TX N (HT20) Mode_Total For FCC

Channel	Frequency (MHz)	Power Spectral Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
36	5180	6.08	11.00	PASS
40	5200	5.69	11.00	PASS
48	5240	6.29	11.00	PASS


UNII-1_TX N (HT20) Mode_Total For IC

Channel	Frequency (MHz)	EIRP Power Spectral Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
36	5180	9.08	10.00	PASS
40	5200	8.69	10.00	PASS
48	5240	9.29	10.00	PASS


UNII-1_TX N (HT40) Mode_Ant 1

Channel	Frequency (MHz)	Power Spectral Density (dBm/MHz)	Duty Factor	Power Spectral Density + Duty Factor (dBm/MHz)	Max. Limit (dBm/MHz)	Result
38	5190	-0.48	0.00	-0.48	11.00	PASS
46	5230	0.48	0.00	0.48	11.00	PASS

CH38




CH46




UNII-1_TX N (HT40) Mode_Ant2

Channel	Frequency (MHz)	Power Spectral Density (dBm/MHz)	Duty Factor	Power Spectral Density + Duty Factor (dBm/MHz)	Max. Limit (dBm/MHz)	Result
38	5190	0.38	0.00	0.38	11.00	PASS
46	5230	1.71	0.00	1.71	11.00	PASS

CH38



CH46



UNII-1_TX N (HT40) Mode_Total For FCC

Channel	Frequency (MHz)	Power Spectral Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
38	5190	2.98	11.00	PASS
46	5230	4.15	11.00	PASS


UNII-1_TX N (HT40) Mode_Total For IC

Channel	Frequency (MHz)	EIRP Power Spectral Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
38	5190	5.98	10.00	PASS
46	5230	7.15	10.00	PASS


UNII-3_TX A Mode_Ant 1

Channel	Frequency (MHz)	Power Spectral Density (dBm/500 kHz)	Duty Factor	Power Spectral Density + Duty Factor (dBm/500 kHz)	Max. Limit (dBm/500 kHz)	Result
149	5745	-4.36	0.00	-4.36	30.00	PASS
157	5785	-5.30	0.00	-5.30	30.00	PASS
165	5825	-4.87	0.00	-4.87	30.00	PASS


CH149



CH157




CH165




UNII-3_TX A Mode_Ant2

Channel	Frequency (MHz)	Power Spectral Density (dBm/500 kHz)	Duty Factor	Power Spectral Density + Duty Factor (dBm/500 kHz)	Max. Limit (dBm/500 kHz)	Result
149	5745	-5.78	0.00	-5.78	30.00	PASS
157	5785	-5.88	0.00	-5.88	30.00	PASS
165	5825	-5.75	0.00	-5.75	30.00	PASS


CH149



CH157




CH165




UNII-3_TX N (HT20) Mode_Ant 1

Channel	Frequency (MHz)	Power Spectral Density (dBm/500 kHz)	Duty Factor	Power Spectral Density + Duty Factor (dBm/500 kHz)	Max. Limit (dBm/500 kHz)	Result
149	5745	-4.86	0.00	-4.86	30.00	PASS
157	5785	-6.18	0.00	-6.18	30.00	PASS
165	5825	-6.15	0.00	-6.15	30.00	PASS


CH149



CH157




CH165




UNII-3_TX N (HT20) Mode_Ant2

Channel	Frequency (MHz)	Power Spectral Density (dBm/500 kHz)	Duty Factor	Power Spectral Density + Duty Factor (dBm/500 kHz)	Max. Limit (dBm/500 kHz)	Result
149	5745	-5.67	0.00	-5.67	30.00	PASS
157	5785	-5.61	0.00	-5.61	30.00	PASS
165	5825	-5.58	0.00	-5.58	30.00	PASS


CH149



CH157



CH165




UNII-3_TX N (HT20) Mode_Total

Channel	Frequency (MHz)	Power Spectral Density (dBm/MHz)	Max. Limit (dBm/500 kHz)	Result
149	5745	-2.24	30.00	PASS
157	5785	-2.88	30.00	PASS
165	5825	-2.85	30.00	PASS


UNII-3_TX N (HT40) Mode_Ant 1

Channel	Frequency (MHz)	Power Spectral Density (dBm/500 kHz)	Duty Factor	Power Spectral Density + Duty Factor (dBm/500 kHz)	Max. Limit (dBm/500 kHz)	Result
151	5755	-8.913	0.00	-8.913	30.00	PASS
159	5795	-7.199	0.00	-7.199	30.00	PASS

CH151




CH159




UNII-3_TX N (HT40) Mode_Ant2

Channel	Frequency (MHz)	Power Spectral Density (dBm/500 kHz)	Duty Factor	Power Spectral Density + Duty Factor (dBm/500 kHz)	Max. Limit (dBm/500 kHz)	Result
151	5755	-8.78	0.00	-8.78	30.00	PASS
159	5795	-8.34	0.00	-8.34	30.00	PASS

CH151



CH159




UNII-3_TX N (HT40) Mode_Total

Channel	Frequency (MHz)	Power Spectral Density (dBm/MHz)	Max. Limit (dBm/500 kHz)	Result
151	5755	-5.84	30.00	PASS
159	5795	-4.72	30.00	PASS


UNII-1_TX AC (VHT20) Mode_Ant 1

Channel	Frequency (MHz)	Power Spectral Density (dBm/MHz)	Duty Factor	Power Spectral Density + Duty Factor (dBm/MHz)	Max. Limit (dBm/MHz)	Result
36	5180	4.06	0.00	4.06	11.00	PASS
40	5200	3.24	0.00	3.24	11.00	PASS
48	5240	2.03	0.00	4.88	11.00	PASS


CH36



CH40




CH48




UNII-1_TX AC (VHT20) Mode_Ant2

Channel	Frequency (MHz)	Power Spectral Density (dBm/MHz)	Duty Factor	Power Spectral Density + Duty Factor (dBm/MHz)	Max. Limit (dBm/MHz)	Result
36	5180	3.61	0.00	3.61	11.00	PASS
40	5200	3.70	0.00	3.70	11.00	PASS
48	5240	3.20	0.00	4.75	11.00	PASS


CH36



CH40



CH48



UNII-1_TX AC (VHT20) Mode_Total For FCC

Channel	Frequency (MHz)	Power Spectral Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
36	5180	6.85	11.00	PASS
40	5200	6.49	11.00	PASS
48	5240	5.66	11.00	PASS


UNII-1_TX AC (VHT20) Mode_Total For IC

Channel	Frequency (MHz)	EIRP Power Spectral Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
36	5180	9.85	10.00	PASS
40	5200	9.49	10.00	PASS
48	5240	8.66	10.00	PASS


UNII-1_TX AC (VHT40) Mode_Ant 1

Channel	Frequency (MHz)	Power Spectral Density (dBm/MHz)	Duty Factor	Power Spectral Density + Duty Factor (dBm/MHz)	Max. Limit (dBm/MHz)	Result
38	5190	-0.83	0.00	-0.83	11.00	PASS
46	5230	-0.72	0.00	-0.72	11.00	PASS

CH38




CH46




UNII-1_TX AC (VHT40) Mode_Ant2

Channel	Frequency (MHz)	Power Spectral Density (dBm/MHz)	Duty Factor	Power Spectral Density + Duty Factor (dBm/MHz)	Max. Limit (dBm/MHz)	Result
38	5190	0.64	0.00	0.64	11.00	PASS
46	5230	0.80	0.00	0.80	11.00	PASS

CH38



CH46



UNII-1_TX AC (VHT40) Mode_Total For FCC

Channel	Frequency (MHz)	Power Spectral Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
38	5190	2.98	11.00	PASS
46	5230	3.12	11.00	PASS


UNII-1_TX AC (VHT40) Mode_Total For IC

Channel	Frequency (MHz)	EIRP Power Spectral Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
38	5190	5.98	10.00	PASS
46	5230	6.12	10.00	PASS

UNII-1_TX AC (VHT80) Mode_Ant 1

Channel	Frequency (MHz)	Power Spectral Density (dBm/MHz)	Duty Factor	Power Spectral Density + Duty Factor (dBm/MHz)	Max. Limit (dBm/MHz)	Result
42	5210	-5.21	0.00	-5.21	11.00	PASS


CH42



UNII-1_TX AC (VHT80) Mode_Ant2

Channel	Frequency (MHz)	Power Spectral Density (dBm/MHz)	Duty Factor	Power Spectral Density + Duty Factor (dBm/MHz)	Max. Limit (dBm/MHz)	Result
42	5210	-4.03	0.00	-4.03	11.00	PASS

CH42



UNII-1_TX AC (VHT80) Mode_Total For FCC

Channel	Frequency (MHz)	Power Spectral Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
42	5210	-1.57	11.00	PASS


UNII-1_TX AC (VHT80) Mode_Total For IC

Channel	Frequency (MHz)	EIRP Power Spectral Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
42	5210	1.43	10.00	PASS


UNII-3_TX AC (VHT20) Mode_Ant 1

Channel	Frequency (MHz)	Power Spectral Density (dBm/500 kHz)	Duty Factor	Power Spectral Density + Duty Factor (dBm/500 kHz)	Max. Limit (dBm/500 kHz)	Result
149	5745	-4.84	0.00	-4.84	30.00	PASS
157	5785	-5.86	0.00	-5.86	30.00	PASS
165	5825	-6.21	0.00	-6.21	30.00	PASS


CH149



CH157




CH165




UNII-3_TX AC (VHT20) Mode_Ant2

Channel	Frequency (MHz)	Power Spectral Density (dBm/500 kHz)	Duty Factor	Power Spectral Density + Duty Factor (dBm/500 kHz)	Max. Limit (dBm/500 kHz)	Result
149	5745	-5.08	0.00	-5.08	30.00	PASS
157	5785	-5.35	0.00	-5.35	30.00	PASS
165	5825	-4.29	0.00	-4.29	30.00	PASS


CH149



CH157



CH165




UNII-3_TX AC (VHT20) Mode_Total

Channel	Frequency (MHz)	Power Spectral Density (dBm/MHz)	Max. Limit (dBm/500 kHz)	Result
149	5745	-1.95	30.00	PASS
157	5785	-2.59	30.00	PASS
165	5825	-2.13	30.00	PASS


UNII-3_TX AC (VHT40) Mode_Ant 1

Channel	Frequency (MHz)	Power Spectral Density (dBm/500 kHz)	Duty Factor	Power Spectral Density + Duty Factor (dBm/500 kHz)	Max. Limit (dBm/500 kHz)	Result
151	5755	-7.59	0.00	-7.59	30.00	PASS
159	5795	-8.46	0.00	-8.46	30.00	PASS

CH151




CH159




UNII-3_TX AC (VHT40) Mode_Ant2

Channel	Frequency (MHz)	Power Spectral Density (dBm/500 kHz)	Duty Factor	Power Spectral Density + Duty Factor (dBm/500 kHz)	Max. Limit (dBm/500 kHz)	Result
151	5755	-7.73	0.00	-7.73	30.00	PASS
159	5795	-9.23	0.00	-9.23	30.00	PASS

CH151



CH159




UNII-3_TX AC (VHT40) Mode_Total

Channel	Frequency (MHz)	Power Spectral Density (dBm/MHz)	Max. Limit (dBm/500 kHz)	Result
151	5755	-4.65	30.00	PASS
159	5795	-5.82	30.00	PASS

UNII-3_TX AC (VHT80) Mode_Ant 1

Channel	Frequency (MHz)	Power Spectral Density (dBm/500 kHz)	Duty Factor	Power Spectral Density + Duty Factor (dBm/500 kHz)	Max. Limit (dBm/500 kHz)	Result
155	5775	-13.79	0.00	-13.79	30.00	PASS


CH155



UNII-3_TX AC (VHT80) Mode_Ant2

Channel	Frequency (MHz)	Power Spectral Density (dBm/500 kHz)	Duty Factor	Power Spectral Density + Duty Factor (dBm/500 kHz)	Max. Limit (dBm/500 kHz)	Result
155	5775	-12.49	0.00	-12.49	30.00	PASS

CH155



UNII-3_TX AC (VHT80) Mode_Total

Channel	Frequency (MHz)	Power Spectral Density (dBm/MHz)	Max. Limit (dBm/500 kHz)	Result
155	5775	-10.08	30.00	PASS

9. FREQUENCY STABILITY MEASUREMENT

9.1 LIMIT

FCC Part15, Subpart E (15.407)&RSS-GEN			
Section	Test Item	Limit	Frequency Range (MHz)
15.407(g) RSS-GEN 6.11	Frequency Stability	Specified in the user's manual	5150-5250
			5725-5850

9.2 TEST PROCEDURE AND SETTING


- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- b. Spectrum Setting:

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Entire absence of modulation emissions bandwidth
RBW	10 kHz
VBW	10kHz
Sweep Time	Auto

9.3 MEASUREMENT INSTRUMENTS LIST

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum analyzer	KEYSIGHT	N9010A	MY55150427	2020/05/27
2	Attenuator	Mini-Circuits	BW-S10W2	101109	N/A
3	RF Cable	Mi-cable	C10-01-01-1	100309	N/A
4	Temperature conditioning	Guan Jian.HTH1000	-20-130°C	GJ1000-10D001	N/A
5	DC Power Supply	G.KE	IPR-10010D	010931954	N/A

9.4 TEST SETUP



9.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

9.6 TEST RESULTS

Temperature vs. Frequency Stability		
Voltage	Temperature	Measurement Frequency (MHz)
3.3V	(°C)	5180
	-20	5180.012
	25	5180.011
	50	5180.009
2.5V	25	5180.007
Max. Deviation (MHz)		0.012
Max. Deviation (ppm)		2.32

Temperature vs. Frequency Stability		
Voltage	Temperature	Measurement Frequency (MHz)
3.3V	(°C)	5745
	-20	5745.016
	25	5745.012
	50	5745.014
2.5V	25	5745.011
Max. Deviation (MHz)		0.016
Max. Deviation (ppm)		2.79

Note: 2.5V is the end point voltage, and products below 2.5V will cease working.

END OF TEST REPORT