



# TEST REPORT

**APPLICANT** : Shenzhen Chainway Information Technology Co., Ltd

**PRODUCT NAME** : Mobile Data Terminal

**MODEL NAME** : C5

**BRAND NAME** : CHAINWAY

**FCC ID** : 2AC6AC5N

**STANDARD(S)** : 47 CFR Part 15 Subpart C

**RECEIPT DATE** : 2023-02-21

**TEST DATE** : 2023-03-01 to 2023-04-11

**ISSUE DATE** : 2025-07-11

Edited by:

Peng Mi

Peng Mi (Rapporteur)

Approved by:

Shen Junsheng

Shen Junsheng (Supervisor)

**NOTE:** This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

**MORLAB**

Shenzhen Morlab Communications Technology Co., Ltd.  
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,  
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555      Fax: 86-755-36698525  
Http://www.morlab.cn      E-mail: service@morlab.cn





## DIRECTORY

<b>1. Summary of Test Results</b> .....	<b>4</b>
<b>1.1. Testing Applied Standards</b> .....	<b>5</b>
<b>1.2. Test Equipment List</b> .....	<b>6</b>
<b>1.3. Measurement Uncertainty</b> .....	<b>8</b>
<b>1.4. Testing Laboratory</b> .....	<b>8</b>
<b>2. General Description</b> .....	<b>9</b>
<b>2.1. Information of Applicant and Manufacturer</b> .....	<b>9</b>
<b>2.2. Information of EUT</b> .....	<b>9</b>
<b>2.3. Channel List of EUT</b> .....	<b>11</b>
<b>2.4. Test Configuration of EUT</b> .....	<b>12</b>
<b>2.5. Test Conditions</b> .....	<b>12</b>
<b>2.6. Test Setup Layout Diagram</b> .....	<b>12</b>
<b>3. Test Results</b> .....	<b>15</b>
<b>3.1. Antenna Requirement</b> .....	<b>15</b>
<b>3.2. Duty Cycle of Test Signal</b> .....	<b>16</b>
<b>3.3. Maximum Peak Conducted Output Power</b> .....	<b>17</b>
<b>3.4. Maximum Average Conducted Output Power</b> .....	<b>18</b>
<b>3.5. 6 dB Bandwidth</b> .....	<b>19</b>
<b>3.6. Conducted Spurious Emissions and Band Edge</b> .....	<b>20</b>
<b>3.7. Power Spectral Density</b> .....	<b>21</b>
<b>3.8. Conducted Emission</b> .....	<b>22</b>
<b>3.9. Restricted Frequency Bands</b> .....	<b>23</b>
<b>3.10. Radiated Emission</b> .....	<b>24</b>
<b>Annex A Test Data and Result</b> .....	<b>26</b>



Change History		
Version	Date	Reason for change
1.0	2025-07-11	First edition



# 1. Summary of Test Results

No.	Section	Description	Test Date	Test Engineer	Result	Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS <sub>Note1</sub>	/
2	N/A	Duty Cycle of Test Signal	Mar 01, 2023	He Yuyang	PASS <sub>Note1</sub>	/
3	15.247(b)	Maximum Peak Conducted Output Power	Mar 01, 2023	He Yuyang	PASS <sub>Note1</sub>	/
4	15.247(b)	Maximum Average Conducted Output Power	Mar 01, 2023	He Yuyang	PASS <sub>Note1</sub>	/
5	15.247(a)	Bandwidth	Mar 01, 2023	He Yuyang	PASS <sub>Note1</sub>	/
6	15.247(d)	Conducted Spurious Emission and Band Edge	Mar 01, 2023	He Yuyang	PASS <sub>Note1</sub>	/
7	15.247(e)	Power Spectral Density	Mar 01, 2023	He Yuyang	PASS <sub>Note1</sub>	/
8	15.207	Conducted Emission	Mar 07, 2023	Fan Zehang	PASS <sub>Note1</sub>	/
9	15.247(d)	Restricted Frequency Bands	Mar 19, 2023	Su Zhan	PASS <sub>Note1</sub>	/
10	15.209, 15.247(d)	Radiated Emission	Mar 09, 2023	Su Zhan	PASS <sub>Note1</sub>	/

**Note 1:** The test results of these test items in this report refer to the test report (Report No.: SZ22120012W04).

**Note 2:** The tests were performed according to the method of measurements prescribed in ANSIC63.10-2013 and KDB558074 D01 v05r02.

**Note 3:** Any additions, deviation, or exclusions from the method shall be noted in the "Remark".



REPORT No.: SZ25040182W04

## 1.1. Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C Radio Frequency Devices



## 1.2. Test Equipment List

### 1.2.1 Conducted Test Equipment

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
EXA Signal Analyzer	MY53470836	N9010A	Agilent	2023.02.27	2024.02.26
RF Cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
Coaxial Cable	CB02	RF02	Morlab	N/A	N/A
SMA Connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

### 1.2.2 Conducted Emission Test Equipment

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	MY56400093	N9038A	KEYSIGHT	2023.02.09	2024.02.08
LISN	8127449	NSLK 8127	Schwarzbeck	2023.02.21	2024.02.20
Pulse Limiter (10dB)	VTSD 9561 F-B #206	VTSD 9561-F	Schwarzbeck	2022.07.06	2023.07.05
RF Coaxial Cable (DC-100MHz)	BNC	MRE04	Qualwave	2022.07.08	2023.07.07

### 1.2.3 List of Software Used

Description	Manufacturer	Software Version
Test System	MaiWei	2.0.0.0
Morlab EMCR V1.2	Morlab	V1.0
TS+ -[JS32-CE]	Tonscend	V2.5.0.0

**1.2.4 Radiated Test Equipment**

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	MY54130016	N9038A	Agilent	2022.07.06	2023.07.05
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2022.05.25	2025.05.24
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2022.02.11	2025.02.10
Test Antenna - Horn	01774	BBHA 9120D	Schwarzbeck	2022.07.13	2025.07.12
Test Antenna - Horn	BBHA9170 #773	BBHA9170	Schwarzbeck	2022.07.14	2025.07.13
Preamplifier (10MHz-6GHz)	46732	S10M100L38 02	LUCIX CORP.	2022.07.08	2023.07.07
Preamplifier (2GHz-18GHz)	61171/61172	S020180L32 03	LUCIX CORP.	2022.07.08	2023.07.07
Preamplifier (18GHz-40GHz)	DS77209	DCLNA0118-40C-S	Decentest	2022.07.23	2023.07.22
RF Coaxial Cable (DC-18GHz)	MRE001	PE330	Pasternack	2022.07.08	2023.07.07
RF Coaxial Cable (DC-18GHz)	MRE002	CLU18	Pasternack	2022.07.08	2023.07.07
RF Coaxial Cable (DC-18GHz)	MRE003	CLU18	Pasternack	2022.07.08	2023.07.07
RF Coaxial Cable (DC-40GHz)	22290045	QA360-40-K K-0.5	Qualwave	2022.07.08	2023.07.07
RF Coaxial Cable (DC-40GHz)	22290046	QA360-40-K KF-2	Qualwave	2022.07.08	2023.07.07
RF Coaxial Cable (DC-18GHz)	22120181	QA500-18-N N-5	Qualwave	2022.07.08	2023.07.07
Notch Filter	N/A	WRCG-2400-2483.5-60SS	Wainwright	2022.07.08	2023.07.07
Anechoic Chamber	N/A	9m*6m*6m	CRT	2022.05.10	2025.05.09



## 1.3. Measurement Uncertainty

Test Items	Uncertainty	Remark
Peak Output Power	±2.22dB	Confidence levels of 95%
Power Spectral Density	±2.22dB	Confidence levels of 95%
Bandwidth	±5%	Confidence levels of 95%
Conducted Spurious Emission	±2.77dB	Confidence levels of 95%
Restricted Frequency Bands	±5%	Confidence levels of 95%
Radiated Emission	±2.95dB	Confidence levels of 95%
Conducted Emission	±2.44dB	Confidence levels of 95%

## 1.4. Testing Laboratory

Laboratory Name	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone	+86 755 36698555
Facsimile	+86 755 36698525
FCC Designation Number	CN1192
FCC Test Firm Registration Number	226174



## 2. General Description

### 2.1. Information of Applicant and Manufacturer

<b>Applicant</b>	Shenzhen Chainway Information Technology Co., Ltd
<b>Applicant Address</b>	9F Building 2, Daqian Industrial Park, District 67, XingDong Community, Xin'an Street, Bao'an District, Shenzhen, Guangdong, China
<b>Manufacturer</b>	Shenzhen Chainway Information Technology Co., Ltd
<b>Manufacturer Address</b>	9F Building 2, Daqian Industrial Park, District 67, XingDong Community, Xin'an Street, Bao'an District, Shenzhen, Guangdong, China

### 2.2. Information of EUT

<b>Product Name:</b>	Mobile Data Terminal
<b>Sample No.:</b>	12#
<b>Hardware Version:</b>	C5P_Software_version
<b>Software Version:</b>	C5P_Hardware_version
<b>Equipment Type:</b>	Bluetooth LE
<b>Bluetooth Version:</b>	5.0
<b>Modulation Type:</b>	GFSK
<b>Data Rate:</b>	1Mbps, 2Mbps
<b>Operating Frequency Range:</b>	2402MHz-2480MHz
<b>Antenna Type:</b>	PIFA Antenna
<b>Antenna Gain:</b>	2.67dBi
<b>Accessory Information:</b>	Battery 1(for EUT)
	Brand Name: Chainway
	Model No.: C5
	Serial No.: N/A
	Capacity: 6300mAh
	Rated Voltage: 3.6V
	Charge Limit: 4.2V
	Manufacturer: DONGGUAN BOB ELECTRONICS CO.,LTD



<b>Accessory Information:</b>	Battery 2(for EUT handle)	
	Brand Name:	ZOUYOU
	Model No.:	501030
	Serial No.:	N/A
	Capacity:	100mAh
	Rated Voltage:	3.7V
	Charge Limit:	4.2V
	Manufacturer:	Shenzhen Zonyou Power Co., Ltd.
	AC Adapter	
	Brand Name:	ULLPOWER
<b>Accessory Information:</b>	Model No.:	NA010050020
	Serial No.:	N/A
	Rated Input:	100-240V~50/60Hz, 0.5A
	Rated Output:	5V--2A
	Manufacturer:	Shenzhen Shi Yingyuan Electronics Co., Ltd
	USB Cable	
	Model:	1.8.17.095
	Manufacturer:	King Power Electronics Co., Ltd.

**Note 1:** This test report is variant from the original report (Report No.: SZ22120012W04, FCC ID: 2AC6AC5P), based on the similarity between before, made the following changes:

1. Reduce the gain of UHF, from 4.75dbi to 3.75dbi
2. Add NFC antenna
3. Change software and hardware version numbers
4. Change FCC ID

The changes do not affect the test results.

**Note 2:** We use the dedicated software to control the EUT continuous transmission.

**Note 3:** The EUT description presented in the report are provided by applicant and/or manufacturer, and the test laboratory is not responsible for the accuracy of the information. For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



## 2.3. Channel List of EUT

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	<b>2402</b>	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	<b>19</b>	<b>2440</b>	29	2460	<b>39</b>	<b>2480</b>

**Note 1:** The black bold channels were selected for test.

## 2.4. Test Configuration of EUT


Test mode is used to control the EUT under the maximum power level during test.

## 2.5. Test Conditions


Temperature (°C)	15-35
Relative Humidity (%)	30-60
Atmospheric Pressure (kPa)	86-106

## 2.6. Test Setup Layout Diagram

### 2.6.1. Conducted Measurement




### 2.6.2. Conducted Emission Measurement




### 2.6.3.Radiation Measurement


- 1) For radiated emissions from 9kHz to 30MHz



- 2) For radiated emissions from 30MHz to1GHz



## 3) For radiated emissions above 1GHz





## 3. Test Results

### 3.1. Antenna Requirement

#### 3.1.1. Requirement

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

#### 3.1.2. Test Result

Inside of the EUT has a PIFA antenna coupled with the metal shrapnel. Please refer to the EUT photos.



## 3.2. Duty Cycle of Test Signal

### 3.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration( $T$ ) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed  $T$  at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle ( $D$ ). Within this sub clause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than  $\pm 2\%$ ; otherwise, the duty cycle is considered to be non constant.

### 3.2.2. Test Result

Refer to Annex A.1 in this report.



### 3.3. Maximum Peak Conducted Output Power

#### 3.3.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

#### 3.3.2. Test Procedures

KDB 558074 Section 8.3.1 was used in order to prove compliance.

#### 3.3.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

#### 3.3.4. Test Result

Refer to Annex A.2 in this report.



## 3.4. Maximum Average Conducted Output Power

### 3.4.1. Requirement

According to FCC section 15.247(b)(3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum average conducted output power of the intentional radiator shall not exceed 1 Watt.

### 3.4.2. Test Procedures

KDB 558074 Section 8.3.2 was used in order to prove compliance.

### 3.4.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

### 3.4.4. Test Result

Refer to Annex A.3 in this report.



## 3.5.6 dB Bandwidth

### 3.5.1. Requirement

According to FCC section 15.247(a) (2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

### 3.5.1. Test Procedures

The steps for the first option are as follows:

- a) Set analyzer center frequency to channel center frequency
- b) Set RBW to 100kHz
- c) Set VBW to 300kHz
- d) Detector = peak.
- e) Trace mode = max hold
- f) Sweep time = auto couple
- g) Allow the trace to fully stabilize
- h) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., RBW = 100 kHz, VBW  $\geq$  3  $\times$  RBW, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be  $\geq$  6 dB.

### 3.5.2. Test Setup Layout

Refer to chapter 2.6.1 in this report.

### 3.5.3. Test Result

Refer to Annex A.4 in this report.



## 3.6. Conducted Spurious Emissions and Band Edge

### 3.6.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

### 3.6.2. Test Procedures

KDB 558074 Section 8.5 and 8.7 was used in order to prove compliance.

### 3.6.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

### 3.6.4. Test Result

Refer to Annex A.5 and A.6 in this report.



## 3.7. Power Spectral Density

### 3.7.1. Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### 3.7.2. Test Procedures

The measured power spectral density was calculated by the reading of the spectrum analyzer and calibration. Following is the test procedure for PSD test:

- a) Set analyzer center frequency to channel center frequency
- b) Set span to 1.5 times DTS
- c) Set RBW to 3kHz
- d) Set VBW to 10kHz
- e) Detector = peak
- f) Sweep time = auto couple
- g) Trace mode = max hold
- h) Allow trace to fully stabilize
- i) Use the peak marker function to determine the maximum amplitude level within the RBW

### 3.7.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

### 3.7.4. Test Result

Refer to Annex A.7 in this report.



## 3.8. Conducted Emission

### 3.8.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50 $\Omega$  line impedance stabilization network (LISN).

Frequency Range (MHz)	Conducted Limit (dB $\mu$ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

Note:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

### 3.8.2. Test Procedures

The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10: 2013.

### 3.8.3. Test Setup Layout

Refer to chapter 2.6.2 in this report.

### 3.8.4. Test Result

Refer to Annex A.8 in this report.



## 3.9. Restricted Frequency Bands

### 3.9.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

### 3.9.2. Test Procedures

The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for  $f \geq 1\text{GHz}$ , 100 kHz for  $f < 1\text{GHz}$

VBW = 3 MHz

Sweep = auto

Detector function = peak/average

Trace = max hold

Allow the trace to stabilize

### 3.9.3. Test Setup Layout

Refer to chapter 2.6.3 in this report.

### 3.9.4. Test Result

Refer to Annex A.8 in this report.



## 3.10. Radiated Emission

### 3.10.1. Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ( $\mu$ V/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

**Note1:** For above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

**Note2:** For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK). In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).



### 3.10.2. Test Procedures

The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz. The antenna to EUT distance is 3meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 30MHz, the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9kHz-90 kHz, 110kHz-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements and as applicable for average measurements.

The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions. For measurements above 1 GHz, keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

### 3.10.3. Test Setup Layout

Refer to chapter 2.6.3 in this report.

### 3.10.4. Test Result


Refer to Annex A.9 in this report.





## Annex A Test Data and Result

### A.1. Duty Cycle of Test Signal

Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	BLE 1M	2402	Ant1	60.8	2.16	2.63
NVNT	BLE 1M	2440	Ant1	61.6	2.1	2.6
NVNT	BLE 1M	2480	Ant1	61.6	2.1	2.6
NVNT	BLE 2M	2402	Ant1	32	4.95	5
NVNT	BLE 2M	2440	Ant1	32	4.95	5
NVNT	BLE 2M	2480	Ant1	32	4.95	5









REPORT No.: SZ25040182W04


### A.2. Maximum Peak Conducted Output Power


Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (mW)	Limit Conducted (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	-3.17	0	-3.17	0.48	30	Pass
NVNT	BLE 1M	2440	Ant1	-1.86	0	-1.86	0.65	30	Pass
NVNT	BLE 1M	2480	Ant1	-3.29	0	-3.29	0.47	30	Pass
NVNT	BLE 2M	2402	Ant1	-3.26	0	-3.26	0.47	30	Pass
NVNT	BLE 2M	2440	Ant1	-1.89	0	-1.89	0.65	30	Pass
NVNT	BLE 2M	2480	Ant1	-3.35	0	-3.35	0.46	30	Pass


MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.  
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,  
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555 Fax: 86-755-36698525  
Http://www.morlab.cn E-mail: service@morlab.cn









REPORT No.: SZ25040182W04


### A.3. Maximum Average Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (mW)	Limit Conducted (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	-5.4	2.16	-3.24	0.47	30	Pass
NVNT	BLE 1M	2440	Ant1	-4.32	2.1	-2.22	0.60	30	Pass
NVNT	BLE 1M	2480	Ant1	-5.6	2.1	-3.5	0.45	30	Pass
NVNT	BLE 2M	2402	Ant1	-8.29	4.95	-3.34	0.46	30	Pass
NVNT	BLE 2M	2440	Ant1	-6.99	4.95	-2.04	0.63	30	Pass
NVNT	BLE 2M	2480	Ant1	-8.54	4.95	-3.59	0.44	30	Pass

MORLAB


Shenzhen Morlab Communications Technology Co., Ltd.  
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,  
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555 Fax: 86-755-36698525  
Http://www.morlab.cn E-mail: service@morlab.cn





REPORT No.: SZ25040182W04




MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.  
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,  
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555 Fax: 86-755-36698525  
Http://www.morlab.cn E-mail: service@morlab.cn



REPORT No.: SZ25040182W04




MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.  
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,  
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555  
Fax: 86-755-36698525  
Http://www.morlab.cn  
E-mail: service@morlab.cn

**A.4. 6 dB Bandwidth**

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 1M	2402	Ant1	0.695	0.5	Pass
NVNT	BLE 1M	2440	Ant1	0.658	0.5	Pass
NVNT	BLE 1M	2480	Ant1	0.65	0.5	Pass
NVNT	BLE 2M	2402	Ant1	1.153	0.5	Pass
NVNT	BLE 2M	2440	Ant1	1.129	0.5	Pass
NVNT	BLE 2M	2480	Ant1	1.138	0.5	Pass









REPORT No.: SZ25040182W04


#### A.5. Conducted Spurious Emissions


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-34.32	-20	Pass
NVNT	BLE 1M	2440	Ant1	-35.64	-20	Pass
NVNT	BLE 1M	2480	Ant1	-33.97	-20	Pass
NVNT	BLE 2M	2402	Ant1	-34.06	-20	Pass
NVNT	BLE 2M	2440	Ant1	-35.09	-20	Pass
NVNT	BLE 2M	2480	Ant1	-33.76	-20	Pass


**MORLAB**


Shenzhen Morlab Communications Technology Co., Ltd.  
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,  
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China


Tel: 86-755-36698555      Fax: 86-755-36698525  
Http://www.morlab.cn      E-mail: service@morlab.cn


















**A.6. Band Edge**

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-49.87	-20	Pass
NVNT	BLE 1M	2480	Ant1	-52.09	-20	Pass
NVNT	BLE 2M	2402	Ant1	-31.28	-20	Pass
NVNT	BLE 2M	2480	Ant1	-50.23	-20	Pass












### A.7. Power Spectral Density

Condition	Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm/3kHz)	Duty Factor (dB)	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	BLE 1M	2402	Ant1	-17.99	0	-17.99	8	Pass
NVNT	BLE 1M	2440	Ant1	-16.62	0	-16.62	8	Pass
NVNT	BLE 1M	2480	Ant1	-18.1	0	-18.1	8	Pass
NVNT	BLE 2M	2402	Ant1	-20.62	0	-20.62	8	Pass
NVNT	BLE 2M	2440	Ant1	-19.27	0	-19.27	8	Pass
NVNT	BLE 2M	2480	Ant1	-20.67	0	-20.67	8	Pass





REPORT No.: SZ25040182W04

PSD NVNT BLE 1M 2480MHz Ant1



PSD NVNT BLE 2M 2402MHz Ant1




MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.  
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,  
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555 Fax: 86-755-36698525  
Http://www.morlab.cn E-mail: service@morlab.cn



## PSD NVNT BLE 2M 2440MHz Ant1



## PSD NVNT BLE 2M 2480MHz Ant1





## A.8. Conducted Emission

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Set RBW=9kHz, VBW=30kHz. Refer to recorded points and plots below.

**Note:** Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

### A. Test Setup:

Test Mode: EUT + Adapter + Earphone + BT TX


Test voltage: AC 120V/60Hz

The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V}] = U_R + L_{\text{Cable loss}} [\text{dB}] + A_{\text{Factor}}$$


$U_R$ : Receiver Reading

$A_{\text{Factor}}$ : Voltage division factor of LISN

**B. Test Plot:**


(L Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1724	34.94	26.90	64.84	54.84	Line	PASS
2	0.2130	33.27	25.78	63.09	53.09		PASS
3	0.3794	32.43	25.14	58.29	48.29		PASS
4	0.4740	38.69	29.03	56.44	46.44		PASS
5	0.5052	41.31	30.37	56.00	46.00		PASS
6	0.5322	41.62	30.99	56.00	46.00		PASS



(N Phase)

No.	Fre. (MHz)	Emission Level (dB $\mu$ V)		Limit (dB $\mu$ V)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.2492	32.97	26.45	61.78	51.78	Neutral	PASS
2	0.4832	36.83	29.88	56.28	46.28		PASS
3	0.5283	40.62	29.51	56.00	46.00		PASS
4	0.8020	29.84	24.37	56.00	46.00		PASS
5	1.2792	30.35	24.43	56.00	46.00		PASS
6	2.0769	28.40	20.01	56.00	46.00		PASS



### A.9. Restricted Frequency Bands

The lowest and highest channels are tested to verify the Restricted Frequency Bands.

The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V}/\text{m}] = U_R + A_T + A_{\text{Factor}} [\text{dB}]; A_T = L_{\text{Cable loss}} [\text{dB}] - G_{\text{preamp}} [\text{dB}]$$

$A_T$ : Total correction Factor except Antenna

$U_R$ : Receiver Reading

$G_{\text{preamp}}$ : Preamplifier Gain

$A_{\text{Factor}}$ : Antenna Factor at 3m


Note: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (vertical) was recorded in this test report.

#### 1Mbps


Channel	Frequency (MHz)	Detector	Receiver	$A_T$ (dB)	$A_{\text{Factor}}$ (dB@3m)	Max. Emission E (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Verdict
			Reading $U_R$ (dB $\mu$ V)					
0	2355.16	PK	24.34	6.74	27.20	58.28	74	PASS
0	2390.00	AV	10.50	6.74	27.20	44.44	54	PASS
39	2497.40	PK	23.63	6.74	27.20	57.57	74	PASS
39	2483.63	AV	10.21	6.74	27.20	44.15	54	PASS



(PEAK, Channel 0)



(AVERAGE, Channel 0)




(PEAK, Channel 39)



(AVERAGE, Channel 39)

## 2Mbps


Channel	Frequency (MHz)	Detector	Receiver	A <sub>T</sub> (dB)	A <sub>Factor</sub> (dB@3m)	Max. Emission E (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Verdict
			U <sub>R</sub> (dB $\mu$ V)					
0	2372.22	PK	23.64	6.74	27.20	57.58	74	PASS
0	2387.71	AV	10.51	6.74	27.20	44.45	54	PASS
39	2498.17	PK	23.83	6.74	27.20	57.77	74	PASS
39	2483.81	AV	10.26	6.74	27.20	44.20	54	PASS



(PEAK, Channel 0)



(AVERAGE, Channel 0)



(PEAK, Channel 39)



REPORT No.: SZ25040182W04



(AVERAGE, Channel 39)

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.  
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,  
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555  
Fax: 86-755-36698525  
Http://www.morlab.cn  
E-mail: service@morlab.cn



## A.10. Radiated Emission

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak (or average) limit, it is unnecessary to perform an quasi-peak measurement (or average).

The measurement results are obtained as below:

$$E [dB\mu V/m] = U_R + A_T + A_{Factor} [dB]; A_T = L_{Cable\ loss} [dB] - G_{preamp} [dB]$$

$A_T$ : Total correction Factor except Antenna

$U_R$ : Receiver Reading

$G_{preamp}$ : Preamplifier Gain

$A_{Factor}$ : Antenna Factor at 3m

During the test, the total correction Factor  $A_T$  and  $A_{Factor}$  were built in test software.


**Note1:** All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

**Note2:** For the frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

**Note3:** For the frequency, which started from 18GHz to 10th harmonic of the highest frequency, was pre-scanned and the result which was 20dB lower than the limit was not recorded.


**1Mbps**

Plot for Channel 0



Fre. (MHz)	PK (dB $\mu$ V/m)	QP (dB $\mu$ V/m)	AV (dB $\mu$ V/m)	Limit-PK (dB $\mu$ V/m)	Limit-QP (dB $\mu$ V/m)	Limit-AV (dB $\mu$ V/m)	Antenna	Verdict
106.630	31.93	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1232.533	45.00	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2415.467	46.56	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5683.080	46.77	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8393.480	46.81	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12677.760	46.68	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dB $\mu$ V/m)	QP (dB $\mu$ V/m)	AV (dB $\mu$ V/m)	Limit-PK (dB $\mu$ V/m)	Limit-QP (dB $\mu$ V/m)	Limit-AV (dB $\mu$ V/m)	Antenna	Verdict
101.780	31.83	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1232.533	45.51	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
1982.933	47.14	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5692.320	46.37	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8433.520	46.28	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12588.440	47.71	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

## Plot for Channel 19



Fre. (MHz)	PK (dB $\mu$ V/m)	QP (dB $\mu$ V/m)	AV (dB $\mu$ V/m)	Limit-PK (dB $\mu$ V/m)	Limit-QP (dB $\mu$ V/m)	Limit-AV (dB $\mu$ V/m)	Antenna	Verdict
101.780	31.40	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1110.933	45.38	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2030.933	47.11	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5686.160	46.74	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8464.320	46.98	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12138.760	46.90	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dB $\mu$ V/m)	QP (dB $\mu$ V/m)	AV (dB $\mu$ V/m)	Limit-PK (dB $\mu$ V/m)	Limit-QP (dB $\mu$ V/m)	Limit-AV (dB $\mu$ V/m)	Antenna	Verdict
95.960	32.91	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1469.333	46.69	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
1971.200	46.58	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4543.480	46.26	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8479.720	46.73	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12295.840	47.99	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

## Plot for Channel 39



Fre. (MHz)	PK (dB $\mu$ V/m)	QP (dB $\mu$ V/m)	AV (dB $\mu$ V/m)	Limit-PK (dB $\mu$ V/m)	Limit-QP (dB $\mu$ V/m)	Limit-AV (dB $\mu$ V/m)	Antenna	Verdict
104.690	31.80	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1070.933	45.84	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
1902.400	47.78	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5735.440	46.87	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8014.640	46.67	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12693.160	47.79	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dB $\mu$ V/m)	QP (dB $\mu$ V/m)	AV (dB $\mu$ V/m)	Limit-PK (dB $\mu$ V/m)	Limit-QP (dB $\mu$ V/m)	Limit-AV (dB $\mu$ V/m)	Antenna	Verdict
94.990	31.98	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1304.533	45.50	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
1981.867	47.06	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5655.360	47.55	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8251.800	46.70	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12172.640	47.11	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)


**2Mbps**

Plot for Channel 0



Fre. (MHz)	PK (dB $\mu$ V/m)	QP (dB $\mu$ V/m)	AV (dB $\mu$ V/m)	Limit-PK (dB $\mu$ V/m)	Limit-QP (dB $\mu$ V/m)	Limit-AV (dB $\mu$ V/m)	Antenna	Verdict
101.780	31.11	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1088.000	45.84	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
1944.533	46.34	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5741.600	46.95	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8430.440	46.77	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12194.200	47.08	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dB $\mu$ V/m)	QP (dB $\mu$ V/m)	AV (dB $\mu$ V/m)	Limit-PK (dB $\mu$ V/m)	Limit-QP (dB $\mu$ V/m)	Limit-AV (dB $\mu$ V/m)	Antenna	Verdict
106.630	33.07	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1333.333	46.08	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
1989.333	46.81	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5519.840	46.22	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8433.520	46.44	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12188.040	47.37	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

## Plot for Channel 19



Fre. (MHz)	PK (dB $\mu$ V/m)	QP (dB $\mu$ V/m)	AV (dB $\mu$ V/m)	Limit-PK (dB $\mu$ V/m)	Limit-QP (dB $\mu$ V/m)	Limit-AV (dB $\mu$ V/m)	Antenna	Verdict
106.630	31.51	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1185.067	45.86	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2220.800	46.77	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5316.560	47.58	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8270.280	46.84	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12298.920	46.69	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dB $\mu$ V/m)	QP (dB $\mu$ V/m)	AV (dB $\mu$ V/m)	Limit-PK (dB $\mu$ V/m)	Limit-QP (dB $\mu$ V/m)	Limit-AV (dB $\mu$ V/m)	Antenna	Verdict
99.840	31.94	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1137.600	45.28	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
1878.400	46.68	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5729.280	47.02	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8384.240	46.87	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12542.240	47.33	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

## Plot for Channel 39



Fre. (MHz)	PK (dB $\mu$ V/m)	QP (dB $\mu$ V/m)	AV (dB $\mu$ V/m)	Limit-PK (dB $\mu$ V/m)	Limit-QP (dB $\mu$ V/m)	Limit-AV (dB $\mu$ V/m)	Antenna	Verdict
105.660	31.16	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1332.800	45.67	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2408.533	47.64	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5658.440	46.37	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8464.320	48.01	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12154.160	48.10	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dB $\mu$ V/m)	QP (dB $\mu$ V/m)	AV (dB $\mu$ V/m)	Limit-PK (dB $\mu$ V/m)	Limit-QP (dB $\mu$ V/m)	Limit-AV (dB $\mu$ V/m)	Antenna	Verdict
103.720	31.68	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1323.200	45.87	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
1668.800	47.17	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5673.840	46.61	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8664.520	46.77	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12148.000	47.24	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)

END OF REPORT