



# EMC TEST REPORT

**Report No.:** SET2021-01351

**Product Name:** Mobile Data Terminal

**FCC ID:** 2AC6AC90

**Model No. :** C90

**Applicant:** Shenzhen Chainway Information Technology Co.,Ltd

**Address:** 9F Building 2, Daqian Industrial Park, District 67, XingDong

Community, Xin'an Street, Bao'an District, Shenzhen, Guangdong,

China

**Received Date:** 2020.12.14

**Dates of Testing:** 2020.12.14 —2021.01.27

**Issued by:** CCIC Southern Testing Co., Ltd.

Electronic Testing Building, No. 43 Shahe Road, Xili Street,

**Lab Location:** Nanshan District, Shenzhen, Guangdong, China.

**Tel:** 86 755 26627338    **Fax:** 86 755 26627238

This test report consists of **20** pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CCIC-SET. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CCIC-SET within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.



## Test Report

**Product Name** ..... Mobile Data Terminal

**Model No.** ..... C90

**Trade name** ..... CHAINWAY

**Applicant** ..... Shenzhen Chainway Information Technology Co.,Ltd

**Applicant Address** ..... 9F Building 2, Daqian Industrial Park, District 67, XingDong Community, Xin'an Street, Bao'an District, Shenzhen, Guangdong, China

**Manufacturer** ..... Shenzhen Chainway Information Technology Co.,Ltd

**Manufacturer Address** .... 9F Building 2, Daqian Industrial Park, District 67, XingDong Community, Xin'an Street, Bao'an District, Shenzhen, Guangdong, China

**Test Standards** ..... 47 CFR Part 15 Subpart B

**Test Result** ..... PASS

**Tested by** ..... Zhang Pei Sen

Pei Sen Zhang Test Engineer

2021.01.27

**Reviewed by** ..... Chris You

Chris You Senior Engineer

2021.01.27

**Approved by** ..... Shuangwen Zhang

2021.01.27

Shuangwen Zhang, Manager

## TABLE OF CONTENTS

<b>1. GENERAL INFORMATION .....</b>	<b>4</b>
<b>1.1 EUT Description .....</b>	<b>4</b>
<b>1.2 Test Standards and Results .....</b>	<b>5</b>
<b>1.3 Facilities and Accreditations .....</b>	<b>6</b>
1.3.1 Facilities .....	6
1.3.2 Test Environment Conditions.....	6
1.3.3 Measurement Uncertainty .....	6
<b>2. TEST CONDITIONS SETTING.....</b>	<b>7</b>
<b>2.1 Test Peripherals .....</b>	<b>7</b>
<b>2.2 Test Mode .....</b>	<b>7</b>
<b>Test Setup and Equipments List .....</b>	<b>8</b>
2.2.1 Conducted Emission.....	8
2.2.2 Radiated Emission.....	8
<b>3. 47 CFR PART 15B REQUIREMENTS .....</b>	<b>11</b>
<b>3.1 Conducted Emission.....</b>	<b>11</b>
3.1.1 Requirement .....	11
3.1.2 Test Description .....	11
3.1.3 Test Result.....	11
<b>3.2 Radiated Emission .....</b>	<b>14</b>
3.2.1 Requirement .....	14
3.2.2 Test Description .....	15
3.2.3 Test Result.....	15

Change History		
Issue	Date	Reason for change
1.0	2021.01.27	First edition

## 1. GENERAL INFORMATION

### 1.1 EUT Description

EUT Name ..... : Mobile Data Terminal  
Trade Name..... : CHAINWAY  
Brand Name.....: CHAINWAY  
Power supply.....: Battery  
Brand Name: BOB  
Model No.: C90-4800mAh  
Capacitance: 4800mAh  
Rated Voltage:3.85V  
Charge Limit:4.2V  
Manufacturer : DONGGUAN BOB ELECTRONICS CO.,LTD  
Ancillary Equipment.....: AC Adapter:  
Brand Name:   
Model No.: NA010050020  
I/p: 100-240V~50/60Hz ,350mA  
O/p: 5.0V---2A  
Manufacturer : Shenzhen Shi Ying Yuan Electronics Co.,Ltd

*Note 1:*The EUT is a Mobile Data Terminal;

*Note 2:*For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

## 1.2 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart B:

No.	Identity	Document Title
1	47 CFR Part 15 Subpart B 2018	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Result
1	15.107	Conducted Emission	PASS
2	15.109	Radiated Emission	PASS

NOTE:

- (1) The EUT has been tested according to 47 CFR Part 15 Subpart B, Class B. The test procedure is according to ANSI C63.4:2014.

## 1.3 Facilities and Accreditations

### 1.3.1 Facilities

#### FCC-Registration No.: CN1283

CCIC Southern Testing Co., Ltd EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Designation Number: CN1283, valid time is until June 30th, 2021.

#### A2LA Code: 5721.01

CCIC-SET is a third party testing organization accredited by A2LA according to ISO/IEC 17025. The accreditation certificate number is 5721.01.

### 1.3.2 Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature ( °C):	15 °C - 35 °C
Relative Humidity (%):	25% -75%
Atmospheric Pressure (kPa):	86kPa-106kPa

### 1.3.3 Measurement Uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

Uncertainty of Conducted Emission:	$U_c = 3.6 \text{ dB (k=2)}$
Uncertainty of Radiated Emission:	$U_c = 4.5 \text{ dB (k=2)}$

## 2. TEST CONDITIONS SETTING

### 2.1 Test Peripherals

The following is a listing of the EUT and peripherals utilized during the performance of EMC test:

#### Support Equipment:

Description	Brand name	Model	Serial No.	FCCID
Notebook	ThinkPad	E430C	A131101550	N/A
Mouse	Logitech	M100r	25011051	DOC

#### Support Cable:

Description	Shield Type	Ferrite Core	Length
PC Power adapter Cable	Un- shielding	No	1.2m
Mouse Cable	Un- shielding	No	1m

### 2.2 Test Mode

The EUT have the following typical setups during the test:

Setup1: EUT + charger


Setup2: EUT + Connect to a computer to transmit data

Note: Only worst-case mode setup 1 mode data provide at the report

## Test Setup and Equipment List

### 2.2.1 Conducted Emission

#### A. Test Setup:



The EUT is placed on a 0.8m high insulating table, which stands on the grounded conducting floor, and keeps 0.4m away from the grounded conducting wall. The EUT is connected to the power mains through a LISN which provides  $50\Omega/50\mu\text{H}$  of coupling impedance for the measuring instrument. The Common Antenna is used for the call between the EUT and the System Simulator (SS). A Pulse Limiter is used to protect the measuring instrument. The factors of the whole test system are calibrated to correct the reading.


#### B. Equipments List:

Description	Manufacturer	Model	Serial No.	Calibration Date	Calibration Due. Date
Test Receiver	KEYSIGHT	N9038A	A141202036	2020.11.21	2021.09.20
LISN	ROHDE&SCHWARZ	ENV216	A140701847	2020.11.21	2021.09.21
Cable	MATCHING PAD	W7	/	2020.08.02	2021.08.02


### 2.2.2 Radiated Emission

### A. Test Setup:

- 1) For radiated emissions from 30MHz to 1GHz



- 2) For radiated emissions above 1GHz



## B. Test Procedure

The test is performed in a 3m Semi-Anechoic Chamber; the antenna factor, cable loss and so on of the site (factors) is calculated to correct the reading. The EUT is placed on a 0.8m high insulating Turn Table, and keeps 3m away from the Test Antenna, which is mounted on a variable-height antenna master tower.

For the test Antenna:

- 1) In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

## C. Equipments List:

Description	Manufacturer	Model	Serial No.	Calibration Date	Calibration Due. Date
Test Receiver	KEYSIGHT	N9038A	A141202036	2020.11.21	2021.09.20
LISN	ROHDE&SCHWARZ	ENV216	A140701847	2020.11.21	2021.09.21
Shield Room	Xinju Electronics	L7300*W4500 *H3100	A181003226	2018.09.06	2021.09.05
EMI Test Receiver	ROHDE&SCHWARZ	ESCI	A0902601	2020.07.01	2021.06.23
Broadband Ant.	2786	ETC	A150402239	2018.09.17	2021.09.16
3M Anechoic Chamber	Albatross	SAC-3MAC 9*6*6m	A0412375	2019.03.26	2023.03.25
EMI Test Receiver	ROHDE&SCHWARZ	ESW26	A180502935	2020.10.21	2021.08.12
System Simulator	ROHDE&SCHWARZ	CMW500	A150802214	2019.07.30	2021.07.29
5M Anechoic Chamber	Albatross	SAC-5MAC 12.8x6.8x6.4m	A0304210	2019.03.25	2023.03.24
EMI Horn Ant.	ROHDE&SCHWARZ	HF906	A0304225	2019.04.17	2022.04.17

### 3. 47 CFR PART 15B REQUIREMENTS

#### 3.1 Conducted Emission

##### 3.1.1 Requirement

According to FCC section 15.107, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50 $\Omega$  line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

**Note:**

- a) The limit subjects to the Class B digital device.
- b) The lower limit shall apply at the band edges.
- c) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

#### 3.1.2 Test Description

See section 2.2.1 of this report.

#### 3.1.3 Test Result


The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. All test modes are considered, refer to recorded points and plots below.

**Note:**

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a Nominal 120V AC,50/60Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

## Test voltage and frequency (120V AC,60Hz)

### A. Mains terminal disturbance voltage, L phase




(Plot A: L Phase)

Frequency (MHz)	QuasiPeak k	CAverage (dB $\mu$ V)	Cabel Loss (dB)	Corr. (dB)	Margin - QPK	Limit - QPK	Margin - AV	Limit - AV (dB $\mu$ V)
0.523500	46.53	36.05	0.1	20.7	9.47	56.0	9.95	46.0
1.072500	35.59	24.83	0.1	20.4	20.41	56.0	21.17	46.0
1.608000	26.27	17.99	0.1	20.3	29.73	56.0	28.01	46.0
2.094000	27.83	17.60	0.1	20.4	28.17	56.0	28.40	46.0
2.611500	26.21	16.56	0.1	20.1	29.79	56.0	29.44	46.0
2.926500	24.78	14.65	0.1	20.2	31.22	56.0	31.35	46.0

Note: Correction factor=Cabel loss+ attenuation factor  
attenuation factor=10dB

## B. Mains terminal disturbance voltage, N phase



(Plot B: N Phase)

Frequency (MHz)	QuasiPea k	CAverage (dB μV)	Cabel Loss (dB)	Corr. (dB)	Margin - QPK	Limit - QPK	Margin - AV	Limit - AV (dB μV)
0.460500	42.27	35.06	0.1	21.3	14.41	56.7	11.62	46.7
0.487500	43.05	34.57	0.1	20.4	13.16	56.2	11.64	46.2
0.501000	38.24	35.75	0.1	20.6	17.76	56.0	10.25	46.0
0.532500	45.62	40.51	0.1	19.8	10.38	56.0	5.49	46.0
0.879000	40.49	27.10	0.1	20.1	15.51	56.0	18.90	46.0
1.203000	40.14	26.62	0.1	20.5	15.86	56.0	19.38	46.0

## 3.2 Radiated Emission

### 3.2.1 Requirement

According to FCC section 15.109, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency range (MHz)	Field Strength		Field Strength Limitation at 3m Measurement Dist	
	$\mu\text{V/m}$	Dist	(uV/m)	(dBuV/m)
0.009 - 0.490	2400/F(kHz)	300m	10000* 2400/F(kHz)	20log 2400/F(kHz) + 80
0.490 - 1.705	2400/F(kHz)	30m	100* 2400/F(kHz)	20log 2400/F(kHz) + 40
1.705 - 30.00	30	30m	100*30	20log 30 + 40
30.0 - 88.0	100	3m	100	20log 100
88.0 - 216.0	150	3m	150	20log 150
216.0 - 960.0	200	3m	200	20log 200
Above 960.0	500	3m	500	20log 500

- a) As shown in FCC section 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector. When average radiated emission measurements are specified in this part, including emission measurements below 1000MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.
- b) Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.
- c) For below 1G :QP detector RBW 120kHz ,VBW 300kHz.
- d) For Above 1G: PK detector RBW 1MHz,VBW 3MHz for PK value ;AV detector RBW 1MHz, VBW 10Hz for AV value.

#### Note:

- 1) The tighter limit shall apply at the boundary between two frequency range.
- 2) Limitation expressed in dBuV/m is calculated by 20log Emission Level(uV/m).
- 3) If measurement is made at 3m distance, then F.S Limitation at 3m distance is adjusted by using the formula of  $Ld1 = Ld2 * (d2/d1)^2$ .

#### Example:

F.S Limit at 30m distance is 30uV/m, then F.S Limitation at 3m distance is adjusted as  $Ld1 = L1 = 30\text{uV/m} * (10)^2 = 100 * 30\text{uV/m}$ .

### **3.2.2 Test Description**

See section 2.3.2 of this report.


### **3.2.3 Test Result**

The maximum radiated emission is searched using PK, QP and AV detectors; the emission levels more than the limits, and that have narrow margins from the limits will be re-measured with AV and QP detectors. Both the vertical and the horizontal polarizations of the Test Antenna are considered to perform the tests. All test modes are considered, refer to recorded points and plots below.

The amplitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be reported.

Note: All radiated emission tests were performed in X, Y, Z axis direction, and only the worst axis test condition was recorded in this test report.


### A.Radiation disturbances, antenna polarization:Vertical



(Plot C: Test Antenna Vertical 30M - 1G)

Frequency (MHz)	QuasiPeak (dB $\mu$ V/m)	Bandwidth (kHz)	Antenna height (cm)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna	Cable Loss(dB)	ANT. Factor(dB)	Verdict
30.00	32.25	120.000	118	40.0	7.75	Vertical	0.4	26.3	Pass
31.70	31.12	120.000	242	40.0	8.88	Vertical	0.6	26.3	Pass
45.42	27.22	120.000	325	40.0	12.78	Vertical	0.4	26.3	Pass
179.99	23.62	120.000	225	43.5	19.88	Vertical	0.7	29.0	Pass
186.27	23.14	120.000	208	43.5	20.36	Vertical	0.5	29.0	Pass
913.26	35.58	120.000	224	46.0	10.42	Vertical	0.8	29.0	Pass

## B.Radiation disturbances, antenna polarization: Horizontal




(Plot D: Test Antenna Horizontal 30M - 1G)

Frequency (MHz)	QuasiPeak (dB $\mu$ V/m)	Bandwidth (kHz)	Antenna height (cm)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna	Cable Loss(dB)	ANT. Factor(dB)	Verdict
30.00	27.89	120.000	112	40.0	12.11	Horizontal	0.5	26.3	Pass
31.77	31.43	120.000	255	40.0	8.57	Horizontal	0.5	27.4	Pass
43.32	24.85	120.000	108	40.0	15.15	Horizontal	0.6	29.0	Pass
136.52	22.18	120.000	308	43.5	21.32	Horizontal	0.5	28.3	Pass
146.64	23.50	120.000	224	43.5	20.00	Horizontal	0.4	29.4	Pass
882.28	36.76	120.000	332	46.0	9.24	Horizontal	1.0	28.9	Pass

**Test Result: PASS**


### A.Radiation disturbances, antenna polarization: Horizontal



(Plot M: Test Antenna Horizontal 1G – 18G)

NO.	Freq. [MHz]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Height [cm]	Angle [°]	Polarity
1	1941.98	30.17	54.00	23.83	AV	100	70	Horizontal
2	1948.78	38.80	74.00	35.20	PK	100	80	Horizontal
3	2805.76	42.26	74.00	31.74	PK	100	40	Horizontal
4	2832.96	33.02	54.00	20.98	AV	100	50	Horizontal
5	3757.95	46.33	74.00	27.67	PK	100	50	Horizontal
6	3832.76	37.49	54.00	16.51	AV	100	60	Horizontal

## B.Radiation disturbances, antenna polarization: Vertical



(Plot N: Test Antenna Vertical 1G – 18G)

NO.	Freq. [MHz]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Trace	Height [cm]	Angle [°]	Polarity
1	2135.82	32.36	54.00	21.64	AV	100	300	Vertical
2	2142.62	40.87	74.00	33.13	PK	100	130	Vertical
3	2934.98	34.07	54.00	19.93	AV	100	320	Vertical
4	2972.39	43.20	74.00	30.80	PK	100	260	Vertical
5	3730.74	46.28	74.00	27.72	PK	100	110	Vertical
6	3788.55	37.15	54.00	16.85	AV	100	110	Vertical

-----End of Report-----