



REPORT No.: SZ23030137W02

# TEST REPORT

**APPLICANT** : Shenzhen Chainway Information  
Technology Co., Ltd

**PRODUCT NAME** : UHF RFID Scanner

**MODEL NAME** : SR160

**BRAND NAME** : CHAINWAY

**FCC ID** : 2AC6ASR160

**STANDARD(S)** : 47 CFR Part 15 Subpart C

**RECEIPT DATE** : 2023-03-31

**TEST DATE** : 2023-04-26 to 2023-05-10

**ISSUE DATE** : 2023-10-17



Edited by:

*Su Xiaoxian*

Su Xiaoxian (Rapporteur)

Approved by:

*Shen Junsheng*

Shen Junsheng (Supervisor)

**NOTE:** This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

**MORLAB**

Shenzhen Morlab Communications Technology Co., Ltd.  
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,  
Block67, BaoAn District, ShenZhen, Guangdong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn





# DIRECTORY

|                                                    |           |
|----------------------------------------------------|-----------|
| <b>1. Technical Information</b>                    | <b>3</b>  |
| <b>1.1. Applicant and Manufacturer Information</b> | <b>3</b>  |
| <b>1.2. Equipment Under Test (EUT) Description</b> | <b>3</b>  |
| <b>1.3. The Channel Number and Frequency</b>       | <b>5</b>  |
| <b>1.4. Test Standards and Results</b>             | <b>6</b>  |
| <b>1.5. Environmental Conditions</b>               | <b>7</b>  |
| <b>2. 47 CFR Part 15C Requirements</b>             | <b>8</b>  |
| <b>2.1. Antenna Requirement</b>                    | <b>8</b>  |
| <b>2.2. Hopping Mechanism</b>                      | <b>8</b>  |
| <b>2.3. Number of Hopping Frequency</b>            | <b>9</b>  |
| <b>2.4. Duty Cycle of Test Signal</b>              | <b>11</b> |
| <b>2.5. Maximum Peak Conducted Output Power</b>    | <b>12</b> |
| <b>2.6. Maximum Average Conducted Output Power</b> | <b>15</b> |
| <b>2.7. 20 dB Bandwidth</b>                        | <b>16</b> |
| <b>2.8. Carried Frequency Separation</b>           | <b>19</b> |
| <b>2.9. Time of Occupancy (Dwell time)</b>         | <b>21</b> |
| <b>2.10. Conducted Spurious Emissions</b>          | <b>24</b> |
| <b>2.11. Conducted Emission</b>                    | <b>29</b> |
| <b>2.12. Radiated Emission</b>                     | <b>33</b> |
| <b>Annex A Test Uncertainty</b>                    | <b>46</b> |
| <b>Annex B Testing Laboratory Information</b>      | <b>47</b> |

| Change History |            |                   |
|----------------|------------|-------------------|
| Version        | Date       | Reason for change |
| 1.0            | 2023-10-17 | First edition     |
|                |            |                   |



# 1. Technical Information

**Note:** Provide by applicant.

## 1.1. Applicant and Manufacturer Information

|                              |                                                                                                                                    |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| <b>Applicant:</b>            | Shenzhen Chainway Information Technology Co., Ltd                                                                                  |
| <b>Applicant Address:</b>    | 9F Building 2, Daqian Industrial Park, District 67, XingDong Community, Xin'an Street, Bao'an District, Shenzhen, Guangdong, China |
| <b>Manufacturer:</b>         | Shenzhen Chainway Information Technology Co., Ltd                                                                                  |
| <b>Manufacturer Address:</b> | 9F Building 2, Daqian Industrial Park, District 67, XingDong Community, Xin'an Street, Bao'an District, Shenzhen, Guangdong, China |

## 1.2. Equipment Under Test (EUT) Description

|                                   |                               |                                   |
|-----------------------------------|-------------------------------|-----------------------------------|
| <b>Product Name:</b>              | UHF RFID Scanner              |                                   |
| <b>Sample No.:</b>                | 1#                            |                                   |
| <b>Hardware Version:</b>          | SR160_hardware_version P      |                                   |
| <b>Software Version:</b>          | SR160_software_version P      |                                   |
| <b>Modulation Technology:</b>     | FHSS                          |                                   |
| <b>Equipment Type:</b>            | RFID                          |                                   |
| <b>Operating Frequency Range:</b> | 902MHz-928MHz                 |                                   |
| <b>Antenna Type:</b>              | Circular Polarization Antenna |                                   |
| <b>Antenna Gain:</b>              | -6.08dBi                      |                                   |
| <b>Accessory Information:</b>     | Battery                       |                                   |
|                                   | Brand Name:                   | CHAINWAY                          |
|                                   | Model No.:                    | J972                              |
|                                   | Serial No.:                   | N/A                               |
|                                   | Capacity:                     | 2600mAh                           |
|                                   | Rated Voltage:                | 3.7V                              |
|                                   | Charge Limit:                 | 4.2V                              |
|                                   | Manufacturer:                 | Shenzhen Hixon Technology co.,LTD |



|                               |               |                                                                                   |
|-------------------------------|---------------|-----------------------------------------------------------------------------------|
| <b>Accessory Information:</b> | AC Adapter    |                                                                                   |
|                               | Brand Name:   |  |
|                               | Model No.:    | NA010050020                                                                       |
|                               | Serial No.:   | N/A                                                                               |
|                               | Rated Input:  | 100-240V~50/60Hz, 0.5A                                                            |
|                               | Rated Output: | 5V=2A                                                                             |
|                               | Manufacturer: | SHENZHEN SHI YING YUAN<br>ELECTRONICS CO LTD                                      |
|                               | USB Cable     |                                                                                   |
|                               | Model No.:    | 1.8.17.095                                                                        |
|                               | Manufacturer: | King Power Electronics Co., Ltd.                                                  |

**Note 1:** We use the dedicated software to control the EUT continuous transmission.

**Note 2:** For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



### 1.3. The Channel Number and Frequency

| Channel | Frequency (MHz) | Channel   | Frequency (MHz) | Channel | Frequency (MHz) | Channel   | Frequency (MHz) |
|---------|-----------------|-----------|-----------------|---------|-----------------|-----------|-----------------|
| 1       | <b>902.75</b>   | 16        | 910.25          | 31      | 917.25          | 46        | 925.25          |
| 2       | 903.25          | 17        | 910.75          | 32      | 918.25          | 47        | 925.75          |
| 3       | 903.75          | 18        | 911.25          | 33      | 918.75          | 48        | 926.25          |
| 4       | 904.25          | 19        | 911.75          | 34      | 919.25          | 49        | 926.75          |
| 5       | 904.75          | 20        | 912.25          | 35      | 919.75          | <b>50</b> | <b>927.25</b>   |
| 6       | 905.25          | 21        | 912.75          | 36      | 920.25          |           |                 |
| 7       | 905.75          | 22        | 913.25          | 37      | 920.75          |           |                 |
| 8       | 906.25          | 23        | 913.75          | 38      | 921.25          |           |                 |
| 9       | 906.75          | 24        | 914.25          | 39      | 921.75          |           |                 |
| 10      | 907.25          | 25        | 914.75          | 40      | 922.25          |           |                 |
| 11      | 907.75          | <b>26</b> | <b>915.25</b>   | 41      | 922.75          |           |                 |
| 12      | 908.25          | 27        | 915.75          | 42      | 923.25          |           |                 |
| 13      | 908.75          | 28        | 916.25          | 43      | 923.75          |           |                 |
| 14      | 909.25          | 29        | 916.75          | 44      | 924.25          |           |                 |
| 15      | 909.75          | 30        | 917.25          | 45      | 924.75          |           |                 |

**Note 1:** The black bold channels were selected for test.



## 1.4. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C for the EUT FCC ID Certification:

| No. | Identity       | Document Title          |
|-----|----------------|-------------------------|
| 1   | 47 CFR Part 15 | Radio Frequency Devices |

Test detailed items/section required by FCC rules and results are as below:

| No. | Section                | Description                            | Test Date     | Test Engineer | Result | Method Determination /Remark |
|-----|------------------------|----------------------------------------|---------------|---------------|--------|------------------------------|
| 1   | 15.203                 | Antenna Requirement                    | N/A           | N/A           | PASS   | No deviation                 |
| 2   | 15.247(a)<br>15.247(h) | Hopping Mechanism                      | N/A           | N/A           | PASS   | No deviation                 |
| 3   | 15.247(a)              | Number of Hopping Frequency            | Apr. 26, 2023 | He Yuyang     | PASS   | No deviation                 |
| 4   | ANSI C63.10            | Duty Cycle                             | Apr. 26, 2023 | He Yuyang     | PASS   | No deviation                 |
| 5   | 15.247(b)              | Maximum Peak Conducted Output Power    | Apr. 26, 2023 | He Yuyang     | PASS   | No deviation                 |
| 6   | 15.247(b)              | Maximum Average Conducted Output Power | Apr. 26, 2023 | He Yuyang     | PASS   | No deviation                 |
| 7   | 15.247(a)              | 20dB Bandwidth                         | Apr. 26, 2023 | He Yuyang     | PASS   | No deviation                 |
| 8   | 15.247(a)              | Carrier Frequency Separation           | Apr. 26, 2023 | He Yuyang     | PASS   | No deviation                 |
| 9   | 15.247(a)              | Time of Occupancy (Dwell time)         | Apr. 26, 2023 | He Yuyang     | PASS   | No deviation                 |
| 10  | 15.247(d)              | Conducted Spurious Emission            | Apr. 26, 2023 | He Yuyang     | PASS   | No deviation                 |
| 11  | 15.207                 | Conducted Emission                     | Apr. 26, 2023 | Fan Zehang    | PASS   | No deviation                 |
| 12  | 15.209,<br>15.247(d)   | Radiated Emission                      | May. 10, 2023 | Gao Jianrou   | PASS   | No deviation                 |

**Note 1:** The tests were performed according to the method of measurements prescribed in ANSI C63.10-2013 and KDB558074 D01 v05r02.

**Note 2:** Additions to, deviation, or exclusions from the method shall be judged in the "method



determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.

**Note 3:** When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.

## 1.5. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

|                             |        |
|-----------------------------|--------|
| Temperature (°C):           | 15-35  |
| Relative Humidity (%):      | 30-60  |
| Atmospheric Pressure (kPa): | 86-106 |



## 2. 47 CFR Part 15C Requirements

### 2.1. Antenna Requirement

#### 2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

#### 2.1.2. Test Result: Compliant

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

### 2.2. Hopping Mechanism

#### 2.2.1. Requirement

According to FCC §15.247(a)(1), a frequency hopping spread spectrum system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

According to FCC §15.247(h), the incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hop sets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

#### 2.2.2. Result: Compliant

The hopping mechanism of the EUT is based on the protocol that "*ISO18000-6C*".


## 2.3. Number of Hopping Frequency

### 2.3.1. Requirement

According to FCC section 15.247(a)(1)(i), frequency hopping systems operating in the 902MHz to 928MHz bands shall use at least 50 hopping frequencies if the 20dB bandwidth of the hopping channel is less than 250KHz; or at least 25 hopping frequencies if the 20dB bandwidth of the hopping channel is 250KHz or greater.

### 2.3.2. Test Description

#### Test Setup:



The EUT is coupled to the Spectrum Analyzer (SA) with Attenuators the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. During the measurement, the EUT is activated by the PC via Lan port.

### 2.3.3. Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW  $\geq$  1% of the span

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize



## 2.3.4. Test Result

### A.Test Verdict:

| Frequency Block (MHz) | Measured Channel Numbers | Min. Limit | Verdict |
|-----------------------|--------------------------|------------|---------|
| 902-928               | 50                       | 50         | PASS    |

### B.Test Plots:



## 2.4. Duty Cycle of Test Signal

### 2.4.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this sub clause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than  $\pm 2\%$ ; otherwise, the duty cycle is considered to be nonconstant.

### 2.4.2. Test Description

#### Test Setup:



ANSI C63.10 2013 Clause 11.6 was used in order to prove compliance.

### 2.4.3. Test Result

| Duty Cycle (%)<br>(D) | Duty Factor<br>( $10 \cdot \lg[1/D]$ ) |
|-----------------------|----------------------------------------|
| 48.90                 | 3.11                                   |


## 2.5. Maximum Peak Conducted Output Power

### 2.5.1. Requirement

According to FCC section 15.247(b)(2), for frequency hopping systems that operates in the 902MHz to 928MHz band employing at least 50 hopping channels, the maximum peak output power of the intentional radiator shall not exceed 1Watt, and 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels.

### 2.5.2. Test Description

#### Test Setup:



The EUT is coupled to the Spectrum Analyzer (SA) with Attenuators the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. During the measurement, the EUT is activated by the PC via Lan port.




### 2.5.3. Test Result


#### A.Test Verdict:

| Channel | Frequency<br>(MHz) | Measured Output Peak Power |               | Limit |   | Verdict |
|---------|--------------------|----------------------------|---------------|-------|---|---------|
|         |                    | dBm                        | W             | dBm   | W |         |
| 1       | 902.75             | <b>29.38</b>               | <b>0.8670</b> | 30    | 1 | PASS    |
| 26      | 915.25             | 28.87                      | 0.7709        |       |   | PASS    |
| 50      | 927.25             | 28.49                      | 0.7063        |       |   | PASS    |


#### B.Test Plot:



(Channel 1)



(Channel 26)



(Channel 50)

## 2.6. Maximum Average Conducted Output Power


### 2.6.1. Requirement

According to FCC section 15.247(b)(2), for frequency hopping systems that operates in the 902MHz to 928MHz band employing at least 50 hopping channels, the maximum peak output power of the intentional radiator shall not exceed 1Watt, and 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels.

### 2.6.2. Test Description

The measured output power was calculated by the reading of the USB Wideband Power Sensor and calibration.

#### Test Setup:



The EUT is coupled to the Spectrum Analyzer (SA) with Attenuators the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. During the measurement, the EUT is activated by the PC via Lan port.

### 2.6.3. Test Result

| Channel | Frequency<br>(MHz) | Measured     | Average Power  |                        |               | Limit |   | Verdict |
|---------|--------------------|--------------|----------------|------------------------|---------------|-------|---|---------|
|         |                    |              | Duty<br>Factor | Duty Factor Calculated |               |       |   |         |
|         |                    | dBm          |                | dBm                    | W             | dBm   | W |         |
| 1       | 902.75             | 24.99        | 3.11           | 28.10                  | 0.6457        | 30    | 1 | PASS    |
| 26      | 915.25             | <b>25.13</b> |                | <b>28.24</b>           | <b>0.6668</b> |       |   | PASS    |
| 50      | 927.25             | 24.66        |                | 27.77                  | 0.5984        |       |   | PASS    |


## 2.7. 20 dB Bandwidth

### 2.7.1. Definition

According to FCC §15.247(a)(1), the 20dB bandwidth is known as the 99% emission bandwidth, or 20 dB bandwidth ( $10 \cdot \log 1\% = 20\text{dB}$ ) taking the total RF output power.

### 2.7.2. Test Description

#### Test Setup:



The EUT is coupled to the Spectrum Analyzer (SA) with Attenuators the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. During the measurement, the EUT is activated by the PC via Lan port.

### 2.7.3. Test Procedure

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel

RBW  $\geq 1\%$  to 5% of the 20 dB bandwidth

VBW  $\geq$  three times RBW

Sweep = auto

Detector function = peak

Trace = max hold



### A. Test Verdict:

| Channel | Frequency (MHz) | 20 dB Bandwidth (kHz) | Result |
|---------|-----------------|-----------------------|--------|
| 1       | 902.75          | 55.55                 | PASS   |
| 26      | 915.25          | 54.85                 | PASS   |
| 50      | 927.25          | 55.15                 | PASS   |

Agilent Spectrum Analyzer - Occupied BW

RF 50 Ω AC SENSE:INT ALIGN OFF 11:47:04 AM Apr 26, 2023

Center Freq 902.750000 MHz Radio Std: None

#IFGain:Low #Trig: Free Run Avg|Hold> 10/10

#Atten: 34 dB Radio Device: BTS

10 dB/div Ref 42.00 dBm

Log

Center 902.8 MHz Span 300 kHz

#Res BW 1 kHz #VBW 3 kHz Sweep 370.2 ms

| Occupied Bandwidth  |           | Total Power |           |
|---------------------|-----------|-------------|-----------|
| 65.910 kHz          |           | 30.5 dBm    |           |
| Transmit Freq Error | -195 Hz   | OBW Power   | 99.00 %   |
| x dB Bandwidth      | 55.55 kHz | x dB        | -20.00 dB |

Meas Setup

Avg/Hold Num 10 Off

On

Avg Mode Repeat

Exp

OBW Power 99.00 %

x dB -20.00 dB

More 1 of 2

MSG STATUS

(Channel 1)



(Channel 26)



(Channel 50)


## 2.8. Carried Frequency Separation

### 2.8.1. Definition

According to FCC §15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or 20dB bandwidth of the hopping channel, whichever is greater.

### 2.8.2. Test Description

#### Test Setup:



The EUT is coupled to the Spectrum Analyzer (SA) with Attenuators the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. During the measurement, the EUT is activated by the PC via Lan port.

### 2.8.3. Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW)  $\geq 1\%$  of the span

Video (or Average) Bandwidth (VBW)  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.



## 2.8.4. Test Result

### A.Test Verdict:

| Test Mode | Measured Channel Numbers | Carried Frequency Separation (kHz) | 20dB bandwidth (kHz) | Min. Limit     | Verdict |
|-----------|--------------------------|------------------------------------|----------------------|----------------|---------|
| RFID      | 25 and 26                | 499                                | 55.55                | 20dB bandwidth | PASS    |

### B.Test Plot:




## 2.9. Time of Occupancy (Dwell time)

### 2.9.1. Requirement

According to FCC §15.247(a) (1) (iii), frequency hopping systems in the 2400 - 2483.5MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### 2.9.2. Test Description

#### Test Setup:



The EUT is coupled to the Spectrum Analyzer (SA) with Attenuators the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. During the measurement, the EUT is activated by the PC via Lan port.

### 2.9.3. Test Procedure

The transmitter output is connected to a spectrum analyzer. The span is set to 0 Hz, centered on a single, selected hopping channel. The width of a single pulse is measured in a fast scan. The number of pulses is measured in 10 second scan, to enable resolution of each occurrence. The average time of occupancy in the specified 20 second period is equal to (# of pulses in 20s) \* pulse width.




## 2.9.4. Test Result

### GFSK Mode


#### A.Test Verdict:

| Frequency (MHz) | Pulse Width (sec) | Number of pulse in 20 seconds | Average Time of Occupancy (sec) | Limit (sec) | Verdict |
|-----------------|-------------------|-------------------------------|---------------------------------|-------------|---------|
| 915             | 0.024             | 16                            | 0.384                           | 0.4         | PASS    |

#### B.Test Plot:



(Dwell time\_ Pulse Width)



(Dwell time\_Number of pulse)


## 2.10. Conducted Spurious Emissions

### 2.10.1. Requirement

According to FCC §15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

### 2.10.2. Test Description

#### Test Setup:



The EUT is coupled to the Spectrum Analyzer (SA) with Attenuators the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. During the measurement, the EUT is activated by the PC via Lan port.

### 2.10.3. Test Procedure

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize




## 2.10.4. Test Result

### GFSK Mode


#### A.Test Verdict:

| Channel | Frequency (MHz) | Measured Max. Out of Band Emission (dBm) | Limit (dBm)   |                         | Verdict |
|---------|-----------------|------------------------------------------|---------------|-------------------------|---------|
|         |                 |                                          | Carrier Level | Calculated -20dBc Limit |         |
| 1       | 902.75          | -35.375                                  | 28.060        | 8.060                   | PASS    |
| 26      | 915.25          | -35.636                                  | 28.536        | 8.536                   | PASS    |
| 50      | 927.25          | -35.319                                  | 27.955        | 7.955                   | PASS    |


#### B.Test Plot:




(30MHz to 10GHz, Channel 1, GFSK)




(Band edge, Channel 1, GFSK)




(Band edge with hopping on, Channel 1, GFSK)




(30MHz to 10GHz, Channel 26, GFSK)



(30MHz to 10GHz, Channel 50, GFSK)



(Band edge, Channel 50, GFSK)



(Band edge with hopping on, Channel 50, GFSK)

## 2.11. Conducted Emission

### 2.11.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50 $\Omega$  line impedance stabilization network (LISN).


| Frequency Range (MHz) | Conducted Limit (dB $\mu$ V) |          |
|-----------------------|------------------------------|----------|
|                       | Quai-peak                    | Average  |
| 0.15 - 0.50           | 66 to 56                     | 56 to 46 |
| 0.50 - 5              | 56                           | 46       |
| 5- 30                 | 60                           | 50       |

**Note:**

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

### 2.11.2. Test Description

**Test Setup:**



The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10: 2013.



### 2.11.3. Test Result

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Set RBW=9kHz, VBW=30kHz. Refer to recorded points and plots below.

**Note:** Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

#### A. Test Setup:

Test Mode: EUT + PC + USB Cable + RFID TX

Test Voltage: AC 120V/60Hz


The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V]} = U_R + L_{\text{Cable loss [dB]} + A_{\text{Factor}}$$

$U_R$ : Receiver Reading


$A_{\text{Factor}}$ : Voltage division factor of LISN

## B.Test Plot:



(L Phase)

| No. | Fre.<br>(MHz) | Emission Level (dBμV) |         | Limit (dBμV) |         | Power-line | Verdict |
|-----|---------------|-----------------------|---------|--------------|---------|------------|---------|
|     |               | Quai-peak             | Average | Quai-peak    | Average |            |         |
| 1   | 0.1503        | 44.00                 | 29.23   | 65.98        | 55.98   | Line       | PASS    |
| 2   | 0.1767        | 41.09                 | 27.75   | 64.64        | 54.64   |            | PASS    |
| 3   | 0.4448        | 28.64                 | 23.04   | 56.97        | 46.97   |            | PASS    |
| 4   | 0.6249        | 27.83                 | 21.98   | 56.00        | 46.00   |            | PASS    |
| 5   | 1.1451        | 29.12                 | 22.34   | 56.00        | 46.00   |            | PASS    |
| 6   | 1.6648        | 25.58                 | 19.43   | 56.00        | 46.00   |            | PASS    |



(N Phase)

| No. | Fre.<br>(MHz) | Emission Level (dBμV) |         | Limit (dBμV) |         | Power-line | Verdict |
|-----|---------------|-----------------------|---------|--------------|---------|------------|---------|
|     |               | Quai-peak             | Average | Quai-peak    | Average |            |         |
| 1   | 0.1539        | 43.17                 | 29.08   | 65.79        | 55.79   | Neutral    | PASS    |
| 2   | 0.1717        | 42.41                 | 28.51   | 64.88        | 54.88   |            | PASS    |
| 3   | 0.2302        | 34.96                 | 25.87   | 62.44        | 52.44   |            | PASS    |
| 4   | 0.3694        | 28.98                 | 23.08   | 58.51        | 48.51   |            | PASS    |
| 5   | 0.4554        | 28.16                 | 22.64   | 56.78        | 46.78   |            | PASS    |
| 6   | 1.3191        | 29.57                 | 23.67   | 56.00        | 46.00   |            | PASS    |

## 2.12. Radiated Emission

### 2.12.1. Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency (MHz) | Field Strength ( $\mu\text{V/m}$ ) | Measurement Distance (m) |
|-----------------|------------------------------------|--------------------------|
| 0.009 - 0.490   | 2400/F(kHz)                        | 300                      |
| 0.490 - 1.705   | 24000/F(kHz)                       | 30                       |
| 1.705 - 30.0    | 30                                 | 30                       |
| 30 - 88         | 100                                | 3                        |
| 88 - 216        | 150                                | 3                        |
| 216 - 960       | 200                                | 3                        |
| Above 960       | 500                                | 3                        |


**Note1:** For above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

**Note2:** For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK). In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).


## 2.12.2. Test Description

### Test Setup:


- 1) For radiated emissions from 9kHz to 30MHz



- 2) For radiated emissions from 30MHz to 1GHz



### 3) For radiated emissions above 1GHz



The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz. The antenna to EUT distance is 3meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 30MHz, the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9kHz-90 kHz, 110kHz-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements and as applicable for average measurements.

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.



### 2.12.3. Test Result

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak (or average) limit, it is unnecessary to perform an quasi-peak measurement (or average).

The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V/m}] = U_R + A_T + A_{\text{Factor}} [\text{dB}]; A_T = L_{\text{Cable loss}} [\text{dB}] - G_{\text{preamp}} [\text{dB}]$$

$A_T$ : Total correction Factor except Antenna

$U_R$ : Receiver Reading

$G_{\text{preamp}}$ : Preamplifier Gain

$A_{\text{Factor}}$ : Antenna Factor at 3m


During the test, the total correction Factor  $A_T$  and  $A_{\text{Factor}}$  were built in test software.

**Note 1:** All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

**Note 2:** For the frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.


**Note 3:** N/A means the frequency is the basic frequency or the base station frequency, they are no need to verdict.

## Plots for Channel 1




| Fre. (MHz) | PK (dBμV/m) | QP (dBμV/m) | AV (dBμV/m) | Limit-PK (dBμV/m) | Limit-QP (dBμV/m) | Limit-AV (dBμV/m) | Antenna    | Verdict |
|------------|-------------|-------------|-------------|-------------------|-------------------|-------------------|------------|---------|
| 903.000    | 78.20       | N/A         | N/A         | N/A               | 46.00             | N/A               | Horizontal | N/A     |
| 1805.333   | 43.27       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 2707.800   | 45.99       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 3610.240   | 53.09       | N/A         | 48.11       | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 4632.800   | 49.22       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 4805.280   | 51.71       | N/A         | 42.90       | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 7438.680   | 44.46       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |

(X axis, 30MHz to 10GHz)




| Fre. (MHz) | PK (dBμV/m) | QP (dBμV/m) | AV (dBμV/m) | Limit-PK (dBμV/m) | Limit-QP (dBμV/m) | Limit-AV (dBμV/m) | Antenna  | Verdict |
|------------|-------------|-------------|-------------|-------------------|-------------------|-------------------|----------|---------|
| 903.000    | 65.90       | N/A         | N/A         | N/A               | 46.00             | N/A               | Vertical | N/A     |
| 1664.533   | 42.84       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 2707.800   | 48.83       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 3813.520   | 44.87       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 4802.200   | 47.05       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 7940.720   | 47.02       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |

(X axis, 30MHz to 10GHz)




| Fre. (MHz) | PK (dBμV/m) | QP (dBμV/m) | AV (dBμV/m) | Limit-PK (dBμV/m) | Limit-QP (dBμV/m) | Limit-AV (dBμV/m) | Antenna    | Verdict |
|------------|-------------|-------------|-------------|-------------------|-------------------|-------------------|------------|---------|
| 903.000    | 71.77       | N/A         | N/A         | N/A               | 46.00             | N/A               | Horizontal | N/A     |
| 1968.000   | 42.85       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 2707.800   | 48.81       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 3610.240   | 48.46       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 4629.720   | 48.55       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 8436.600   | 46.60       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |

(Y axis, 30MHz to 10GHz)




| Fre. (MHz) | PK (dBμV/m) | QP (dBμV/m) | AV (dBμV/m) | Limit-PK (dBμV/m) | Limit-QP (dBμV/m) | Limit-AV (dBμV/m) | Antenna  | Verdict |
|------------|-------------|-------------|-------------|-------------------|-------------------|-------------------|----------|---------|
| 903.000    | 77.25       | N/A         | N/A         | N/A               | 46.00             | N/A               | Vertical | N/A     |
| 1700.800   | 42.71       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 2707.800   | 43.50       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 3610.240   | 48.05       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 5704.640   | 46.37       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 8950.960   | 47.52       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |

(Y axis, 30MHz to 10GHz)



| Fre. (MHz) | PK (dBμV/m) | QP (dBμV/m) | AV (dBμV/m) | Limit-PK (dBμV/m) | Limit-QP (dBμV/m) | Limit-AV (dBμV/m) | Antenna    | Verdict |
|------------|-------------|-------------|-------------|-------------------|-------------------|-------------------|------------|---------|
| 903.000    | 68.70       | N/A         | N/A         | N/A               | 46.00             | N/A               | Horizontal | N/A     |
| 1402.667   | 42.57       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 2707.800   | 49.10       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 3610.240   | 46.04       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 4805.280   | 48.82       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 8448.920   | 47.25       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |


(Z axis, 30MHz to 10GHz)



| Fre. (MHz) | PK (dBμV/m) | QP (dBμV/m) | AV (dBμV/m) | Limit-PK (dBμV/m) | Limit-QP (dBμV/m) | Limit-AV (dBμV/m) | Antenna  | Verdict |
|------------|-------------|-------------|-------------|-------------------|-------------------|-------------------|----------|---------|
| 903.000    | 71.81       | N/A         | N/A         | N/A               | 46.00             | N/A               | Vertical | N/A     |
| 1805.333   | 44.50       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 2707.800   | 48.49       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 3610.240   | 49.41       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 4632.800   | 48.07       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 4805.280   | 47.64       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 5692.320   | 47.41       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 8445.840   | 46.88       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |


(Z axis, 30MHz to 10GHz)

Plot for Channel 26




| Fre. (MHz) | PK (dBμV/m) | QP (dBμV/m) | AV (dBμV/m) | Limit-PK (dBμV/m) | Limit-QP (dBμV/m) | Limit-AV (dBμV/m) | Antenna    | Verdict |
|------------|-------------|-------------|-------------|-------------------|-------------------|-------------------|------------|---------|
| 915.610    | 74.42       | N/A         | N/A         | N/A               | 46.00             | N/A               | Horizontal | N/A     |
| 1680.000   | 48.96       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 2744.760   | 46.26       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 3659.520   | 56.92       | N/A         | 50.44       | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 5812.440   | 49.01       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 8901.680   | 48.68       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |

(X axis, 30MHz to 10GHz)




| Fre. (MHz) | PK (dBμV/m) | QP (dBμV/m) | AV (dBμV/m) | Limit-PK (dBμV/m) | Limit-QP (dBμV/m) | Limit-AV (dBμV/m) | Antenna  | Verdict |
|------------|-------------|-------------|-------------|-------------------|-------------------|-------------------|----------|---------|
| 915.610    | 58.94       | N/A         | N/A         | N/A               | 46.00             | N/A               | Vertical | N/A     |
| 1679.467   | 46.03       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 2744.760   | 46.58       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 3659.520   | 48.97       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 5855.560   | 48.21       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 9089.560   | 48.76       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |

(X axis, 30MHz to 10GHz)




| Fre. (MHz) | PK (dBμV/m) | QP (dBμV/m) | AV (dBμV/m) | Limit-PK (dBμV/m) | Limit-QP (dBμV/m) | Limit-AV (dBμV/m) | Antenna    | Verdict |
|------------|-------------|-------------|-------------|-------------------|-------------------|-------------------|------------|---------|
| 915.610    | 72.16       | N/A         | N/A         | N/A               | 46.00             | N/A               | Horizontal | PASS    |
| 1600.000   | 44.07       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 2744.760   | 44.95       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 3659.520   | 50.53       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 5809.360   | 48.52       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 8448.920   | 48.69       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |

(Y axis, 30MHz to 10GHz)




| Fre. (MHz) | PK (dBμV/m) | QP (dBμV/m) | AV (dBμV/m) | Limit-PK (dBμV/m) | Limit-QP (dBμV/m) | Limit-AV (dBμV/m) | Antenna  | Verdict |
|------------|-------------|-------------|-------------|-------------------|-------------------|-------------------|----------|---------|
| 915.610    | 69.93       | N/A         | N/A         | N/A               | 46.00             | N/A               | Vertical | N/A     |
| 1600.000   | 45.17       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 2160.000   | 47.22       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 3659.520   | 50.75       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 5381.240   | 48.38       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 8470.480   | 48.47       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |

(Y axis, 30MHz to 10GHz)



| Fre. (MHz) | PK (dBμV/m) | QP (dBμV/m) | AV (dBμV/m) | Limit-PK (dBμV/m) | Limit-QP (dBμV/m) | Limit-AV (dBμV/m) | Antenna    | Verdict |
|------------|-------------|-------------|-------------|-------------------|-------------------|-------------------|------------|---------|
| 915.610    | 64.35       | N/A         | N/A         | N/A               | 46.00             | N/A               | Horizontal | PASS    |
| 1600.000   | 46.69       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 2744.760   | 46.48       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 3659.520   | 47.98       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 5680.000   | 49.19       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 8476.640   | 48.88       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |

(Z axis, 30MHz to 10GHz)




| Fre. (MHz) | PK (dBμV/m) | QP (dBμV/m) | AV (dBμV/m) | Limit-PK (dBμV/m) | Limit-QP (dBμV/m) | Limit-AV (dBμV/m) | Antenna  | Verdict |
|------------|-------------|-------------|-------------|-------------------|-------------------|-------------------|----------|---------|
| 915.610    | 74.06       | N/A         | N/A         | N/A               | 46.00             | N/A               | Vertical | PASS    |
| 1326.933   | 44.30       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 2744.760   | 47.72       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 3659.520   | 54.42       | N/A         | 46.71       | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 5393.560   | 48.83       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 8285.680   | 49.78       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |

(Z axis, 30MHz to 10GHz)




Plot for Channel 50




| Fre. (MHz) | PK (dBμV/m) | QP (dBμV/m) | AV (dBμV/m) | Limit-PK (dBμV/m) | Limit-QP (dBμV/m) | Limit-AV (dBμV/m) | Antenna    | Verdict |
|------------|-------------|-------------|-------------|-------------------|-------------------|-------------------|------------|---------|
| 927.250    | 79.87       | N/A         | N/A         | N/A               | 46.00             | N/A               | Horizontal | N/A     |
| 1854.400   | 45.90       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 2781.720   | 49.66       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 3708.800   | 57.32       | N/A         | 49.36       | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 5621.480   | 48.36       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 6948.960   | 47.57       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |

(X axis, 30MHz to 10GHz)




| Fre. (MHz) | PK (dBμV/m) | QP (dBμV/m) | AV (dBμV/m) | Limit-PK (dBμV/m) | Limit-QP (dBμV/m) | Limit-AV (dBμV/m) | Antenna  | Verdict |
|------------|-------------|-------------|-------------|-------------------|-------------------|-------------------|----------|---------|
| 927.250    | 70.71       | N/A         | N/A         | N/A               | 46.00             | N/A               | Vertical | N/A     |
| 1600.000   | 45.07       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 2781.720   | 48.84       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 3708.800   | 48.24       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 5393.560   | 49.14       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 8421.200   | 49.25       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |

(X axis, 30MHz to 10GHz)




| Fre. (MHz) | PK (dBμV/m) | QP (dBμV/m) | AV (dBμV/m) | Limit-PK (dBμV/m) | Limit-QP (dBμV/m) | Limit-AV (dBμV/m) | Antenna    | Verdict |
|------------|-------------|-------------|-------------|-------------------|-------------------|-------------------|------------|---------|
| 927.250    | 72.59       | N/A         | N/A         | N/A               | 46.00             | N/A               | Horizontal | N/A     |
| 1978.133   | 45.48       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 2781.720   | 45.89       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 3708.800   | 50.33       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 5686.160   | 48.91       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 8448.920   | 48.61       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |

(Y axis, 30MHz to 10GHz)




| Fre. (MHz) | PK (dBμV/m) | QP (dBμV/m) | AV (dBμV/m) | Limit-PK (dBμV/m) | Limit-QP (dBμV/m) | Limit-AV (dBμV/m) | Antenna  | Verdict |
|------------|-------------|-------------|-------------|-------------------|-------------------|-------------------|----------|---------|
| 927.250    | 77.52       | N/A         | N/A         | N/A               | 46.00             | N/A               | Vertical | PASS    |
| 1680.533   | 48.61       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 1854.400   | 47.12       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 2781.720   | 45.33       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 3021.960   | 44.23       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 3708.800   | 51.68       | N/A         | 42.55       | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 7925.320   | 48.75       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |

(Y axis, 30MHz to 10GHz)



| Fre. (MHz) | PK (dBμV/m) | QP (dBμV/m) | AV (dBμV/m) | Limit-PK (dBμV/m) | Limit-QP (dBμV/m) | Limit-AV (dBμV/m) | Antenna    | Verdict |
|------------|-------------|-------------|-------------|-------------------|-------------------|-------------------|------------|---------|
| 927.250    | 71.44       | N/A         | N/A         | N/A               | 46.00             | N/A               | Horizontal | N/A     |
| 1680.000   | 46.70       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 2781.720   | 50.25       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 3708.800   | 48.95       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 4358.680   | 47.96       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |
| 8411.960   | 48.80       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Horizontal | PASS    |

(Z axis, 30MHz to 10GHz)



| Fre. (MHz) | PK (dBμV/m) | QP (dBμV/m) | AV (dBμV/m) | Limit-PK (dBμV/m) | Limit-QP (dBμV/m) | Limit-AV (dBμV/m) | Antenna  | Verdict |
|------------|-------------|-------------|-------------|-------------------|-------------------|-------------------|----------|---------|
| 927.250    | 71.20       | N/A         | N/A         | N/A               | 46.00             | N/A               | Vertical | PASS    |
| 1485.867   | 44.53       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 1854.400   | 46.56       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 2781.720   | 49.11       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 3708.800   | 55.15       | N/A         | 47.37       | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 5649.200   | 48.94       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |
| 9135.760   | 48.84       | N/A         | N/A         | 74.00             | N/A               | 54.00             | Vertical | PASS    |

(Z axis, 30MHz to 10GHz)

## Annex A Test Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for test performed on the EUT as specified in CISPR 16-1-2:

| Test Items                     | Uncertainty |
|--------------------------------|-------------|
| Number of Hopping Frequency    | ±5%         |
| Peak Output Power              | ±2.22dB     |
| 20dB Bandwidth                 | ±5%         |
| Carrier Frequency Separation   | ±5%         |
| Time of Occupancy (Dwell time) | ±5%         |
| Conducted Spurious Emission    | ±2.77dB     |
| Restricted Frequency Bands     | ±5%         |
| Radiated Emission              | ±2.95dB     |
| Conducted Emission             | ±2.44dB     |

This uncertainty represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



## Annex B Testing Laboratory Information

### 1. Identification of the Responsible Testing Laboratory

|                            |                                                                                                                                  |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| <b>Laboratory Name:</b>    | Shenzhen Morlab Communications Technology Co., Ltd.                                                                              |
| <b>Laboratory Address:</b> | FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China |
| <b>Telephone:</b>          | +86 755 36698555                                                                                                                 |
| <b>Facsimile:</b>          | +86 755 36698525                                                                                                                 |

### 2. Identification of the Responsible Testing Location

|                 |                                                                                                                                  |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------|
| <b>Name:</b>    | Shenzhen Morlab Communications Technology Co., Ltd.                                                                              |
| <b>Address:</b> | FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China |

### 3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192, the test firm registration number is 226174.



#### 4. Test Equipments Utilized

##### 4.1 Conducted Test Equipments

| Equipment Name         | Serial No. | Type      | Manufacturer | Cal. Date  | Due Date   |
|------------------------|------------|-----------|--------------|------------|------------|
| EXA Signal Analyzer    | MY53470836 | N9010A    | Agilent      | 2023.02.27 | 2024.02.26 |
| RF Cable (30MHz-26GHz) | CB01       | RF01      | Morlab       | N/A        | N/A        |
| Coaxial Cable          | CB02       | RF02      | Morlab       | N/A        | N/A        |
| SMA Connector          | CN01       | RF03      | HUBER-SUHNER | N/A        | N/A        |
| Computer               | T430i      | Think Pad | Lenovo       | N/A        | N/A        |

##### 4.2 Conducted Emission Test Equipments

| Equipment Name               | Serial No.         | Type             | Manufacturer | Cal. Date  | Due Date   |
|------------------------------|--------------------|------------------|--------------|------------|------------|
| Receiver                     | MY56400093         | N9038A           | KEYSIGHT     | 2023.02.09 | 2024.02.08 |
| LISN                         | 8127449            | NSLK 8127        | Schwarzbeck  | 2023.02.21 | 2024.02.20 |
| Pulse Limiter (10dB)         | VTSD 9561 F-B #206 | VTSD 9561-F      | Schwarzbeck  | 2022.07.06 | 2023.07.05 |
| RF Coaxial Cable (DC-100MHz) | BNC                | MRE04            | Qualwave     | 2022.07.08 | 2023.07.07 |
| Notebook                     | N/A                | A1370            | APPLE        | N/A        | N/A        |
| Notebook Adapter             | N/A                | A1374            | APPLE        | N/A        | N/A        |
| Adapter                      | N/A                | ICP30A-1 20-2000 | ULLPOWER     | N/A        | N/A        |

##### 4.3 List of Software Used

| Description      | Manufacturer | Software Version |
|------------------|--------------|------------------|
| Test System      | Tonscend     | V2.6             |
| MORLAB EMCR V1.2 | MORLAB       | V1.0             |
| TS+ -[JS32-CE]   | Tonscend     | V2.5.0.0         |

**4.4 Radiated Test Equipments**

| Equipment Name              | Serial No.    | Type                  | Manufacturer | Cal. Date  | Due Date   |
|-----------------------------|---------------|-----------------------|--------------|------------|------------|
| Receiver                    | MY54130016    | N9038A                | Agilent      | 2022.07.06 | 2023.07.05 |
| Test Antenna - Bi-Log       | 9163-519      | VULB 9163             | Schwarzbeck  | 2022.05.25 | 2025.05.24 |
| Test Antenna - Loop         | 1519-022      | FMZB1519              | Schwarzbeck  | 2022.02.11 | 2025.02.10 |
| Test Antenna – Horn         | 01774         | BBHA 9120D            | Schwarzbeck  | 2022.07.13 | 2025.07.12 |
| Test Antenna – Horn         | BBHA9170 #773 | BBHA9170              | Schwarzbeck  | 2022.07.14 | 2025.07.13 |
| Preamplifier (10MHz-6GHz)   | 46732         | S10M100L38 02         | LUCIX CORP.  | 2022.07.08 | 2023.07.07 |
| Preamplifier (2GHz-18GHz)   | 61171/61172   | S020180L32 03         | LUCIX CORP.  | 2022.07.08 | 2023.07.07 |
| Preamplifier (18GHz-40GHz)  | DS77209       | DCLNA0118-40C-S       | Decentest    | 2022.07.23 | 2023.07.22 |
| RF Coaxial Cable (DC-18GHz) | MRE001        | PE330                 | Pasternack   | 2022.07.08 | 2023.07.07 |
| RF Coaxial Cable (DC-18GHz) | MRE002        | CLU18                 | Pasternack   | 2022.07.08 | 2023.07.07 |
| RF Coaxial Cable (DC-18GHz) | MRE003        | CLU18                 | Pasternack   | 2022.07.08 | 2023.07.07 |
| RF Coaxial Cable (DC-40GHz) | 22290045      | QA360-40-K K-0.5      | Qualwave     | 2022.07.08 | 2023.07.07 |
| RF Coaxial Cable (DC-40GHz) | 22290046      | QA360-40-K KF-2       | Qualwave     | 2022.07.08 | 2023.07.07 |
| RF Coaxial Cable (DC-18GHz) | 22120181      | QA500-18-N N-5        | Qualwave     | 2022.07.08 | 2023.07.07 |
| Notch Filter                | N/A           | WRCG-2400-2483.5-60SS | Wainwright   | 2022.07.08 | 2023.07.07 |
| Anechoic Chamber            | N/A           | 9m*6m*6m              | CRT          | 2022.05.10 | 2025.05.09 |

END OF REPORT