

# RF Exposure Evaluation Declaration

Product Name : Wireless Outdoor Access Point  
Model No. : AMU24  
FCC ID. : 2ACBOAMU24

Applicant : ALCON Technology Corporation  
Address : 2nd floor, No.480-5, Sec 6, Yen-Ping N.  
Road, Shih-Lin, Taipei, Taiwan R.O.C.

Date of Receipt : 2014/06/04  
Date of Declaration : 2014/07/15  
Report No. : 1460174R-RF-US-Exp  
Report Version : V1.0



The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of QuiTek Corporation.

## 1. RF Exposure Evaluation

### 1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

$P_d$  = power density in  $\text{mW/cm}^2$

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi = 3.1416$

$r$  = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE,  $1 \text{ mW/cm}^2$ . If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance  $r$  where the MPE limit is reached.

### 1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity:  $18^\circ\text{C}$  and 78% RH.

### 1.3. Test Result of RF Exposure Evaluation

Product	Wireless Outdoor Access Point
Test Mode	Transmit
Test Condition	RF Exposure Evaluation

#### Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 9dBi or 7.94 in linear scale.

#### Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11b			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
1	2412	97.0510	0.1534
6	2437	93.7562	0.1482
11	2462	108.1434	0.1709

IEEE 802.11g			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
1	2412	356.4511	0.5633
6	2437	339.6253	0.5367
11	2462	403.6454	0.6379

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>.

Product	Wireless Outdoor Access Point
Test Mode	Transmit
Test Condition	RF Exposure Evaluation

**Antenna Gain**

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 9dBi or 7.94 in linear scale.

**Output Power into Antenna & RF Exposure Evaluation Distance:**

IEEE 802.11n (20MHz) ANT 0+1			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
1	2412	207.0141	0.3271
6	2437	234.9633	0.3713
11	2462	225.9436	0.3571

IEEE 802.11n (40MHz) ANT 0+1			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
3	2422	170.0983	0.2688
6	2437	217.2201	0.3433
9	2452	213.2554	0.3370

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>.