



FCC RF Test Report

APPLICANT : TCL Communication Ltd.
EQUIPMENT : GSM Quad-band / UMTS Quad-band / LTE
hepta-band mobile phone
BRAND NAME : alcatel
MODEL NAME : 6055A
MARKETING NAME : IDOL 4
FCC ID : 2ACCJA018
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E), 27(L)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product testing was completed on Aug. 06, 2016. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-D-2010 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Prepared by: James Huang / Manager

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China



TABLE OF CONTENTS

REVISION HISTORY	4
SUMMARY OF TEST RESULT	5
1 GENERAL DESCRIPTION	7
1.1 Applicant.....	7
1.2 Manufacturer	7
1.3 Product Feature of Equipment Under Test	7
1.4 Product Specification of Equipment Under Test	8
1.5 Specification of Accessory	9
1.6 Modification of EUT	9
1.7 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator	10
1.8 Testing Location	10
1.9 Applicable Standards	11
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	12
2.1 Test Mode.....	12
2.2 Connection Diagram of Test System	13
2.3 Support Unit used in test configuration	14
2.4 Measurement Results Explanation Example	14
3 CONDUCTED TEST RESULT.....	15
3.1 Measuring Instruments.....	15
3.2 Test Setup	15
3.3 Test Result of Conducted Test.....	15
3.4 Conducted Output Power	16
3.5 Peak-to-Average Ratio	17
3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	18
3.7 Conducted Band Edge	19
3.8 Conducted Spurious Emission	20
3.9 Frequency Stability.....	21
4 RADIATED TEST ITEMS	22
4.1 Measuring Instruments.....	22
4.2 Test Setup	22
4.3 Test Result of Radiated Test.....	22
4.4 Effective Radiated Power and Effective Isotropic Radiated Power Measurement	23
4.5 Field Strength of Spurious Radiation Measurement	25
5 LIST OF MEASURING EQUIPMENT	26
6 UNCERTAINTY OF EVALUATION.....	27
APPENDIX A. TEST RESULTS OF CONDUCTED TEST	
APPENDIX B. TEST RESULTS OF RADIATED TEST	
APPENDIX C. TEST SETUP PHOTOGRAPHS	



APPENDIX D. PRODUCT EQUALITY DECLARATION



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG670106A	Rev. 01	This report is for 6055A which is the variant product of 6055U. According to the product equality declaration as Appendix D which is provided by applicant, Based on the similarity between two products, only update Radiated Spurious Emission test data for all Bands, the other test result is not affected; all test cases were leveraged on original report (Sporton Report Number FG642504A).	Aug. 09, 2016

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049 §22.917(b) §24.238(b) §27.53(g)	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22	PASS	-
	§2.1055 §24.235 §27.54		Within Authorized Band		



Report Section	FCC Rule	Description	Limit	Result	Remark
4.4	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
4.5	§2.1053 §22.917(a) §24.238(a) §27.53(h)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 26.64 dB at 1672.000 MHz



1 General Description

1.1 Applicant

TCL Communication Ltd.

5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong Area Shanghai, P. R. China. 201203

1.2 Manufacturer

TCL Communication Ltd

5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong Area Shanghai, P. R. China. 201203

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	GSM Quad-band / UMTS Quad-band / LTE hepta-band mobile phone
Brand Name	alcatel
Model Name	6055A
Marketing Name	IDOL 4
FCC ID	2ACCJA018
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/ HSPA+(16QAM uplink is not supported)/LTE/NFC/ WLAN 2.4GHz 802.11b/g/n HT20/HT40/ WLAN 5GHz 802.11a/n HT20/HT40/ WLAN 5GHz 802.11ac VHT20/VHT40/VHT80/ Bluetooth v3.0+EDR/ Bluetooth v4.0 LE/ Bluetooth v4.2 LE
IMEI Code	Conducted: 014658000003961 for 22H.24E 014658000003755 for 27L Radiation: 014658000003870 for Battery 1 014658000006691 for Battery 2 ERP/EIRP: NA
HW Version	PIO
SW Version	4D26
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	GSM/GPRS/EDGE: 850: 824.2 MHz ~ 848.8 MHz 1900: 1850.2 MHz ~ 1909.8MHz WCDMA: Band V: 826.4 MHz ~ 846.6 MHz Band II: 1852.4 MHz ~ 1907.6 MHz Band IV: 1712.4 MHz ~ 1752.6 MHz
Rx Frequency	GSM/GPRS/EDGE: 850: 869.2 MHz ~ 893.8 MHz 1900: 1930.2 MHz ~ 1989.8 MHz WCDMA: Band V: 871.4 MHz ~ 891.6 MHz Band II: 1932.4 MHz ~ 1987.6 MHz Band IV: 2112.4 MHz ~ 2152.6 MHz
Maximum Output Power to Antenna	GSM/GPRS/EDGE: 850: 32.56 dBm 1900: 30.18 dBm WCDMA: Band V: 23.48 dBm Band II: 23.25 dBm Band IV: 23.53 dBm
Antenna Type	Loop Antenna
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: QPSK (Uplink) HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink) HSPA+: 16QQAM (Uplink is not supported)

1.5 Specification of Accessory

Specification of Accessory for 6055U				
AC Adapter	Brand Name	alcatel	Model Name	UC13US
	Power Rating	I/P: 100-240Vac, 500mA, O/P: 5Vdc, 2000mA		
	P/N	CBA0059AG8C1		
Battery 1	Brand Name	ALCATEL onetouch	Model Name	TLp026EJ
	Power Rating	3.85Vdc, 2610mAh		
Battery 2	Brand Name	ALCATEL onetouch	Model Name	TLp026E2
	Power Rating	3.84Vdc, 2610mAh		
USB Cable	Brand Name	N/A	Model Name	CDA0000049C2
	Signal Line Type	1.0m shielded without core		

Specification of Accessory for 6055A				
AC Adapter 1	Brand Name	alcatel	Model Name	UC13US
	Power Rating	I/P: 100-240Vac, 500mA, O/P: 5.0Vdc, 2A		
	Manufacturer	Aohai	P/N	CBA0059AGAC4
AC Adapter 2	Brand Name	alcatel	Model Name	UC13US
	Power Rating	I/P: 100-240Vac, 500mA, O/P: 5.0Vdc, 2A		
	Manufacturer	TENPAO	P/N	CBA0059AGAC2 CBA0059AG4C2
Battery	Brand Name	ALCATEL onetouch	Model Name	TLp026E2
	Power Rating	3.84Vdc, 2610mAh		
	Manufacturer	SCUD	P/N	CAC2610002C2
USB Cable 1	Brand Name	N/A	Model Name	CDA0000043C8
	Signal Line Type	1.01m shielded without core		
	Manufacturer	PUAN	P/N	N/A
USB Cable 2	Brand Name	N/A	Model Name	CDA0000043C2
	Signal Line Type	1.00m shielded without core		
	Manufacturer	Shenghua	P/N	N/A

1.6 Modification of EUT

No modifications are made to the EUT during all test items.

1.7 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22	GSM850 GSM	GMSK	0.7499	0.0120 ppm	242KGXW
Part 22	GSM850 EDGE class 8	8PSK	0.1910	0.0072 ppm	244KG7W
Part 22	WCDMA Band V RMC 12.2Kbps	QPSK	0.0885	0.0108 ppm	4M12F9W
Part 24	GSM1900 GSM	GMSK	1.6181	0.0027 ppm	242KGXW
Part 24	GSM1900 EDGE class 8	8PSK	0.6699	0.0191 ppm	247KG7W
Part 24	WCDMA Band II RMC 12.2Kbps	QPSK	0.3467	0.0053 ppm	4M12F9W
Part 27	WCDMA Band IV RMC 12.2Kbps	QPSK	0.3614	0.0058 ppm	4M13F9W

1.8 Testing Location

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.	
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958	
Test Site No.	Sporton Site No.	
	TH01-KS	

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-3273456 / FAX: +886-3-3284978	
Test Site No.	Sporton Site No.	FCC/IC Registration No.
	03CH13-HY	TW1098/4086H

Note: The test site complies with ANSI C63.4 2014 requirement.



1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 22(H), 24(E), 27(L)
- ♦ ANSI / TIA / EIA-603-D-2010
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r02 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:


1. 30 MHz to 10th harmonic for GSM850 and WCDMA Band V.
2. 30 MHz to 10th harmonic for WCDMA Band IV.
3. 30 MHz to 10th harmonic for GSM1900 and WCDMA Band II.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	■ GSM Link ■ EDGE class 8 Link	■ GSM Link ■ EDGE class 8 Link
GSM 1900	■ GSM Link ■ EDGE class 8 Link	■ GSM Link ■ EDGE class 8 Link
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band IV	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GW INSTEK	GPD-2303S	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.5 dB and a 10dB attenuator.

Example :

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.5 + 10 = 14.5 \text{ (dB)}\end{aligned}$$

3 Conducted Test Result

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.



3.4 Conducted Output Power

3.4.1 Description of the Conducted Output Power

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.4.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.



3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.7.1.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. Set EUT to transmit at maximum output power.
4. When the duty cycle is less than 98%, then signal gating will be implemented on the spectrum analyzer by triggering from the system simulator.
5. Set the CCDF (Complementary Cumulative Distribution Function) option of the spectrum analyzer.
Record the maximum PAPR level associated with a probability of 0.1%.

3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 4.2.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

3.7.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator.
The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$
$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$$
$$= -13\text{dBm}.$$

3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
= $P(W) - [43 + 10\log(P)]$ (dB)
= $[30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
= -13dBm.

3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 D01 v02r02 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C steps up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 D01 v02r02 Section 9.0.
2. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

4.4 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

4.4.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-D-2010, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r02. The ERP of mobile transmitters must not exceed 7 Watts (Cellular Band) and the EIRP of mobile transmitters are limited to 2 Watts (PCS Band) and 1 Watts (AWS Band).

4.4.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.2.1. (for CDMA/WCDMA), Section 5.2.2.2 (for GSM/GPRS/EDGE) and ANSI / TIA-603-D-2010 Section 2.2.17.
2. The EUT was placed on a non-conductive rotating platform (0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz) in a semi-anechoic chamber. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and a spectrum analyzer with RMS detector per ANSI C63.26 section 5.2.7.
3. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power. The maximum emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna raised and lowered over a range from 1 to 4 meters in both horizontally and vertically polarized orientations.
4. Effective Isotropic Radiated Power (EIRP) was measured by substitution method according to TIA/EIA-603-D. The EUT was replaced by the substitution antenna at same location, and then a known power from S.G. was applied into the dipole antenna through a Tx cable, and then recorded the maximum Analyzer reading through raised and lowered the test antenna. The correction factor (in dB) = S.G. - Tx Cable loss + Substitution antenna gain - Analyzer reading. Then the EUT's EIRP was calculated with the correction factor, $EIRP = LVL + \text{Correction factor}$ and $ERP = EIRP - 2.15$. Take the record of the output power at substitution antenna.



	GSM/GPRS/EDGE	WCDMA/HSPA
SPAN	500kHz	10MHz
RBW	10kHz	100kHz
VBW	30kHz	300kHz
Detector	RMS	RMS
Trace	Average	Average
Average Type	Power	Power
Sweep Count	100	100

4.5 Field Strength of Spurious Radiation Measurement

4.5.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.5.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.8 and ANSI / TIA-603-D-2010 Section 2.2.12.
2. The EUT was placed on a rotatable wooden table 0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
12. $ERP \text{ (dBm)} = EIRP - 2.15$
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Sep. 10, 2015	Apr. 16, 2016~ Apr. 24, 2016	Sep. 09, 2016	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	-40~+150°C	Oct. 24, 2015	Apr. 16, 2016~ Apr. 24, 2016	Oct. 23, 2016	Conducted (TH01-KS)
Spectrum Analyzer	Keysight	N9010A	MY55370526	N/A	Mar. 14, 2016	Aug. 02, 2016 ~ Aug. 06, 2016	Mar. 13, 2017	Radiation (03CH13-HY)
Bilog Antenna	TESEQ	CBL 6111D	37059	30MHz~1GHz	Dec. 29, 2015	Aug. 02, 2016 ~ Aug. 06, 2016	Dec. 28, 2016	Radiation (03CH13-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1328	1GHz ~ 18GHz	Nov. 02, 2015	Aug. 02, 2016 ~ Aug. 06, 2016	Nov. 01, 2016	Radiation (03CH13-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1241	1GHz ~ 18GHz	Apr. 25, 2016	Aug. 02, 2016 ~ Aug. 06, 2016	Apr. 24, 2017	Radiation (03CH13-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170576	18GHz ~ 40GHz	Apr. 15, 2016	Aug. 02, 2016 ~ Aug. 06, 2016	Apr. 14, 2017	Radiation (03CH13-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170584	18GHz- 40GHz	Nov. 02, 2015	Aug. 02, 2016 ~ Aug. 06, 2016	Nov. 01, 2016	Radiation (03CH13-HY)
Amplifier	Sonoma-Instrument	310 N	187282	10MHz~1GHz	Dec. 31, 2015	Aug. 02, 2016 ~ Aug. 06, 2016	Dec. 30, 2016	Radiation (03CH13-HY)
Preamplifier	MITEQ	AMF-7D-00 101800-30-1	1590074	1GHz~18GHz	Jun. 27, 2016	Aug. 02, 2016 ~ Aug. 06, 2016	Jun. 26, 2017	Radiation (03CH13-HY)
Preamplifier	MITEQ	JS44-18004 000-33-8P	1840917	18GHz ~ 40GHz	Jun. 14, 2016	Aug. 02, 2016 ~ Aug. 06, 2016	Jun. 13, 2017	Radiation (03CH13-HY)
Preamplifier	Keysight	83017A	MY53270147	1GHz~26.5GHz	Jan. 30, 2016	Aug. 02, 2016 ~ Aug. 06, 2016	Jan. 29, 2017	Radiation (03CH13-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Aug. 02, 2016 ~ Aug. 06, 2016	N/A	Radiation (03CH13-HY)
Signal Generator	Rohde & Schwarz	SMF100A	101107	100kHz~40GHz	May 19, 2016	Aug. 02, 2016 ~ Aug. 06, 2016	May 18, 2017	Radiation (03CH13-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Aug. 02, 2016 ~ Aug. 06, 2016	N/A	Radiation (03CH13-HY)
Antenna Mast	EMEC	AM-BS-450 0-B	N/A	1m~4m	N/A	Aug. 02, 2016 ~ Aug. 06, 2016	N/A	Radiation (03CH13-HY)

NCR: No Calibration Required

6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.1dB
---	-------

Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.5dB
---	-------

Uncertainty of Radiated Emission Measurement (18GHz ~ 40GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.9dB
---	-------

Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM	32.52	32.56	32.50	30.12	30.17	30.18
GPRS class 8	32.51	32.54	32.49	30.10	30.14	30.15
GPRS class 10	31.14	31.23	30.92	28.42	28.46	28.52
GPRS class 11	29.36	29.50	29.24	26.86	26.75	26.75
GPRS class 12	27.90	28.05	28.01	25.55	25.70	25.71
EGPRS class 8	26.63	26.61	26.69	25.72	25.77	25.80
EGPRS class 10	25.54	25.54	25.60	24.64	24.69	24.72
EGPRS class 11	23.72	23.73	23.84	23.05	23.05	23.05
EGPRS class 12	22.06	22.10	22.22	21.41	21.43	21.45

Conducted Power (*Unit: dBm)									
Band	WCDMA Band V			WCDMA Band II			WCDMA Band IV		
Channel	4132	4182	4233	9262	9400	9538	1312	1413	1513
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6	1712.4	1732.6	1752.6
AMR 12.2K	23.40	23.44	23.45	23.20	23.23	23.20	23.44	23.45	23.51
RMC 12.2K	23.42	23.47	23.48	23.22	23.25	23.23	23.45	23.46	23.53
HSDPA Subtest-1	21.38	21.36	21.40	21.20	21.38	21.28	21.39	21.38	21.47
HSDPA Subtest-2	21.40	21.45	21.42	21.31	21.43	21.29	21.40	21.43	21.58
HSDPA Subtest-3	21.38	21.43	21.39	21.35	21.34	21.30	21.40	21.39	21.53
HSDPA Subtest-4	21.38	21.43	21.39	21.35	21.34	21.37	21.39	21.39	21.53
HSUPA Subtest-1	22.39	22.45	22.38	22.02	22.04	22.10	21.97	22.24	22.32
HSUPA Subtest-2	20.38	20.43	20.47	20.07	20.15	20.08	20.13	20.19	20.25
HSUPA Subtest-3	21.41	21.47	21.38	21.11	21.15	20.12	21.17	21.28	21.33
HSUPA Subtest-4	20.39	20.44	20.47	20.06	21.15	20.11	20.23	20.28	20.35
HSUPA Subtest-5	22.30	22.40	22.30	22.00	22.10	22.00	22.10	22.20	22.30

**Peak-to-Average Ratio**

Mode	GSM850		Limit: 13dB
Mod.	GSM(dB)	EDGE class 8(dB)	Result
Lowest CH	0.26	3.33	PASS
Middle CH	0.26	3.48	
Highest CH	0.26	3.39	


Mode	GSM1900		Limit: 13dB
Mod.	GSM(dB)	EDGE class 8(dB)	Result
Lowest CH	0.23	3.22	PASS
Middle CH	0.23	3.33	
Highest CH	0.23	3.13	

Mode	WCDMA Band V(dB)	WCDMA Band II(dB)	WCDMA Band IV(dB)	Limit: 13dB
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps	Result
Lowest CH	3.10	2.90	2.72	PASS
Middle CH	3.16	2.87	3.04	
Highest CH	3.13	2.61	2.99	



GSM850 (GSM)


Lowest Channel



Date: 22 APR 2016 17:27:24

GSM850 (EDGE class 8)

Lowest Channel



Date: 24 APR 2016 01:17:52

Middle Channel



Date: 22 APR 2016 17:27:43

Middle Channel



Date: 24 APR 2016 01:18:03

Highest Channel



Date: 22 APR 2016 17:27:54

Highest Channel



Date: 24 APR 2016 01:18:15



GSM1900 (GSM)


Lowest Channel



Date: 24 APR 2016 01:35:48


GSM1900 (EDGE class 8)

Lowest Channel



Date: 24 APR 2016 02:34:15

Middle Channel



Date: 24 APR 2016 01:36:01

Middle Channel




Date: 24 APR 2016 02:34:45

Highest Channel



Date: 24 APR 2016 01:36:15

Highest Channel




Date: 24 APR 2016 02:34:58




WCDMA Band V (RMC 12.2Kbps)

Lowest Channel



WCDMA Band II (RMC 12.2Kbps)


Lowest Channel




Middle Channel




Middle Channel



Highest Channel



Highest Channel





WCDMA Band IV (RMC 12.2Kbps)

Lowest Channel




Date: 16 APR 2016 18:04:41

Middle Channel



Date: 16 APR 2016 18:05:00

Highest Channel



Date: 16 APR 2016 18:05:17

**26dB Bandwidth**

Mode	GSM850	
Mod.	GSM(MHz)	EDGE class 8(MHz)
Lowest CH	0.316	0.314
Middle CH	0.311	0.317
Highest CH	0.316	0.314


Mode	GSM1900	
Mod.	GSM(MHz)	EDGE class 8(MHz)
Lowest CH	0.310	0.307
Middle CH	0.314	0.312
Highest CH	0.311	0.313

Mode	WCDMA Band V(MHz)	WCDMA Band II(MHz)	WCDMA Band IV(MHz)
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.69	4.71	4.72
Middle CH	4.69	4.70	4.70
Highest CH	4.69	4.74	4.71




GSM850 (GSM)

Lowest Channel




GSM850 (EDGE class 8)

Lowest Channel



Middle Channel




Middle Channel



Highest Channel




Highest Channel






GSM1900 (GSM)

Lowest Channel




GSM1900 (EDGE class 8)


Lowest Channel




Middle Channel




Middle Channel



Highest Channel




Highest Channel






WCDMA Band V (RMC 12.2Kbps)

Lowest Channel




WCDMA Band II (RMC 12.2Kbps)


Lowest Channel




Middle Channel




Middle Channel



Highest Channel




Highest Channel






WCDMA Band IV (RMC 12.2Kbps)


Lowest Channel



Middle Channel



Highest Channel



**Occupied Bandwidth**

Mode	GSM850	
Mod.	GSM(MHz)	EDGE class 8(MHz)
Lowest CH	0.240	0.237
Middle CH	0.241	0.241
Highest CH	0.242	0.244


Mode	GSM1900	
Mod.	GSM(MHz)	EDGE class 8(MHz)
Lowest CH	0.240	0.247
Middle CH	0.241	0.247
Highest CH	0.242	0.243

Mode	WCDMA Band V(MHz)	WCDMA Band II(MHz)	WCDMA Band IV(MHz)
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.11	4.12	4.13
Middle CH	4.12	4.12	4.11
Highest CH	4.12	4.12	4.12



GSM850 (GSM)


Lowest Channel



Date: 22 APR 2016 17:25:21


GSM850 (EDGE class 8)

Lowest Channel



Date: 22 APR 2016 17:41:01

Middle Channel




Date: 22 APR 2016 17:25:49

Middle Channel



Date: 22 APR 2016 17:41:35

Highest Channel



Date: 22 APR 2016 17:26:17

Highest Channel




Date: 22 APR 2016 17:42:09



GSM1900 (GSM)


Lowest Channel



Date: 24 APR 2016 01:25:17

GSM1900 (EDGE class 8)

Lowest Channel




Date: 24 APR 2016 02:18:35

Middle Channel



Date: 24 APR 2016 01:25:45

Middle Channel




Date: 24 APR 2016 02:18:08

Highest Channel



Date: 24 APR 2016 01:26:14

Highest Channel




Date: 24 APR 2016 02:19:48



WCDMA Band V (RMC 12.2Kbps)


Lowest Channel



Date: 22 APR 2016 18:39:31


WCDMA Band II (RMC 12.2Kbps)

Lowest Channel




Date: 24 APR 2016 02:41:51

Middle Channel




Date: 22 APR 2016 18:39:58

Middle Channel




Date: 24 APR 2016 02:42:20

Highest Channel



Date: 22 APR 2016 18:40:28

Highest Channel




Date: 24 APR 2016 02:42:48




WCDMA Band IV (RMC 12.2Kbps)

Lowest Channel




Date: 16 APR 2016 17:50:52

Middle Channel



Date: 16 APR 2016 17:51:33

Highest Channel



Date: 16 APR 2016 17:52:14




Conducted Band Edge



GSM850 (GSM)

Lowest Band Edge




Highest Band Edge




GSM850 (EDGE class 8)

Lowest Band Edge




Highest Band Edge






GSM1900 (GSM)

Lowest Band Edge




Highest Band Edge




GSM1900 (EDGE class 8)

Lowest Band Edge



Highest Band Edge





WCDMA Band V (RMC 12.2Kbps)

Lowest Band Edge



Highest Band Edge



WCDMA Band II (RMC 12.2Kbps)

Lowest Band Edge



Highest Band Edge





WCDMA Band IV (RMC 12.2Kbps)

Lowest Band Edge



Highest Band Edge






Conducted Spurious Emission



GSM850 (GSM)


Lowest Channel



Date: 22 APR 2016 17:19:55


GSM850 (EDGE class 8)

Lowest Channel




Date: 22 APR 2016 17:43:40

Middle Channel




Date: 22 APR 2016 17:21:11

Middle Channel




Date: 22 APR 2016 17:44:59

Highest Channel



Date: 22 APR 2016 17:22:26

Highest Channel




Date: 22 APR 2016 17:46:20



GSM1900 (GSM)


Lowest Channel



Date: 24 APR 2016 01:31:46


GSM1900 (EDGE class 8)

Lowest Channel




Date: 24 APR 2016 02:24:34

Middle Channel




Date: 24 APR 2016 01:33:02




Date: 24 APR 2016 02:25:58

Highest Channel



Date: 24 APR 2016 01:34:17




Date: 24 APR 2016 02:27:32




WCDMA Band V (RMC 12.2Kbps)

Lowest Channel




WCDMA Band II (RMC 12.2Kbps)


Lowest Channel




Middle Channel




Middle Channel



Highest Channel




Highest Channel






WCDMA Band IV (RMC 12.2Kbps)


Lowest Channel



Middle Channel



Highest Channel



**Frequency Stability**

Test Conditions	Middle Channel	GSM850 (GSM)	GSM850 (EDGE class 8)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0012	0.0024	PASS
40	Normal Voltage	0.0048	0.0048	
30	Normal Voltage	0.0060	0.0012	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0024	0.0012	
0	Normal Voltage	0.0108	0.0012	
-10	Normal Voltage	0.0036	0.0060	
-20	Normal Voltage	0.0024	0.0012	
-30	Normal Voltage	0.0060	0.0024	
20	Maximum Voltage	0.0120	0.0072	
20	Normal Voltage	0.0000	0.0048	
20	Battery End Point	0.0024	0.0036	

Note: Normal Voltage = 3.9 V. ; Battery End Point (BEP) = 3.55 V. ; Maximum Voltage =4.35 V



Test Conditions	Middle Channel	GSM1900 (GSM)	GSM1900 (EDGE class 8)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0005	0.0005	PASS
40	Normal Voltage	0.0016	0.0011	
30	Normal Voltage	0.0005	0.0032	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0016	0.0016	
0	Normal Voltage	0.0011	0.0011	
-10	Normal Voltage	0.0027	0.0191	
-20	Normal Voltage	0.0011	0.0186	
-30	Normal Voltage	0.0021	0.0165	
20	Maximum Voltage	0.0016	0.0005	
20	Normal Voltage	0.0000	0.0000	
20	Battery End Point	0.0021	0.0011	

Note:

1. Normal Voltage = 3.9 V. ; Battery End Point (BEP) = 3.55 V. ; Maximum Voltage =4.35 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.



Test Conditions	Middle Channel	WCDMA Band V (RMC 12.2Kbps)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0012	PASS
40	Normal Voltage	0.0024	
30	Normal Voltage	0.0036	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0048	
0	Normal Voltage	0.0060	
-10	Normal Voltage	0.0012	
-20	Normal Voltage	0.0072	
-30	Normal Voltage	0.0108	
20	Maximum Voltage	0.0048	
20	Normal Voltage	0.0060	
20	Battery End Point	0.0024	

Note: Normal Voltage = 3.9 V. ; Battery End Point (BEP) = 3.55 V. ; Maximum Voltage =4.35 V



Test Conditions	Middle Channel	WCDMA Band II (RMC 12.2Kbps)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0011	PASS
40	Normal Voltage	0.0016	
30	Normal Voltage	0.0053	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0016	
0	Normal Voltage	0.0005	
-10	Normal Voltage	0.0027	
-20	Normal Voltage	0.0016	
-30	Normal Voltage	0.0011	
20	Maximum Voltage	0.0011	
20	Normal Voltage	0.0016	
20	Battery End Point	0.0005	

Note:

1. Normal Voltage = 3.9V. ; Battery End Point (BEP) = 3.55 V. ; Maximum Voltage =4.35 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.



Test Conditions	Middle Channel	WCDMA Band IV (RMC 12.2Kbps)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0058	PASS
40	Normal Voltage	0.0029	
30	Normal Voltage	0.0012	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0046	
0	Normal Voltage	0.0035	
-10	Normal Voltage	0.0017	
-20	Normal Voltage	0.0006	
-30	Normal Voltage	0.0023	
20	Maximum Voltage	0.0040	
20	Normal Voltage	0.0012	
20	Battery End Point	0.0006	

Note:

1. Normal Voltage = 3.9V. ; Battery End Point (BEP) = 3.55 V. ; Maximum Voltage =4.35V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.



Appendix B. Test Results of Radiated Test

ERP/EIRP

Channel	Mode	Horizontal		Vertical	
		ERP(dBm)	ERP(W)	ERP(dBm)	ERP(W)
Lowest	GSM850 GSM	28.75	0.7499	20.91	0.1233
Middle		28.21	0.6622	20.71	0.1178
Highest		27.69	0.5875	21.13	0.1297
Lowest	GSM850 EDGE class 8	22.81	0.1910	14.98	0.0315
Middle		22.70	0.1862	14.27	0.0267
Highest		21.51	0.1416	15.16	0.0328
Lowest	WCDMA Band V RMC 12.2Kbps	19.47	0.0885	11.70	0.0148
Middle		18.84	0.0766	11.39	0.0138
Highest		18.50	0.0708	11.77	0.0150
Limit	ERP < 7W	Result		PASS	



Channel	Mode	Horizontal		Vertical	
		EIRP(dBm)	EIRP(W)	EIRP(dBm)	EIRP(W)
Lowest	GSM1900 GSM	31.17	1.3092	31.34	1.3614
Middle		31.68	1.4723	32.09	1.6181
Highest		31.41	1.3836	31.62	1.4521
Lowest	GSM1900 EDGE class 8	27.19	0.5236	27.41	0.5508
Middle		28.07	0.6412	28.17	0.6561
Highest		28.26	0.6699	28.17	0.6561
Lowest	WCDMA Band II RMC 12.2Kbps	24.35	0.2723	24.48	0.2805
Middle		24.78	0.3006	24.96	0.3133
Highest		24.89	0.3083	25.40	0.3467
Limit	EIRP < 2W	Result		PASS	

Channel	Mode	Horizontal		Vertical	
		EIRP(dBm)	EIRP(W)	EIRP(dBm)	EIRP(W)
Lowest	WCDMA Band IV RMC 12.2Kbps	25.58	0.3614	24.97	0.3141
Middle		25.31	0.3396	25.02	0.3177
Highest		24.62	0.2897	24.64	0.2911
Limit	EIRP < 1W	Result		PASS	

**Radiated Spurious Emission**

GSM850 (GSM)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Low	1648	-44.43	-13	-31.43	-57.78	-46.19	0.98	4.89	H
	2472	-58.33	-13	-45.33	-74.64	-60.21	1.28	5.32	H
	3296	-58.53	-13	-45.53	-77.76	-61.94	1.54	7.10	H
	1648	-43.67	-13	-30.67	-56.39	-45.43	0.98	4.89	V
	2472	-58.23	-13	-45.23	-74.58	-60.11	1.28	5.32	V
	3296	-59.44	-13	-46.44	-78.85	-62.85	1.54	7.10	V
Middle	1672	-44.57	-13	-31.57	-58.03	-46.25	0.99	4.82	H
	2512	-53.64	-13	-40.64	-70.28	-55.61	1.29	5.41	H
	3344	-55.85	-13	-42.85	-74.96	-59.46	1.56	7.31	H
	1672	-39.64	-13	-26.64	-52.3	-41.32	0.99	4.82	V
	2512	-52.32	-13	-39.32	-69.5	-54.29	1.29	5.41	V
	3344	-56.67	-13	-43.67	-76.13	-60.28	1.56	7.31	V
High	1696	-45.93	-13	-32.93	-58.33	-47.53	1.00	4.75	H
	2544	-57.48	-13	-44.48	-74.13	-59.46	1.30	5.44	H
	3392	-58.91	-13	-45.91	-78.42	-62.71	1.57	7.52	H
	1696	-42.68	-13	-29.68	-55.57	-44.28	1.00	4.75	V
	2544	-57.36	-13	-44.36	-74.15	-59.34	1.30	5.44	V
	3392	-58.91	-13	-45.91	-78.34	-62.71	1.57	7.52	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



GSM850 (EDGE class 8)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Low	1648	-45.33	-13	-32.33	-58.49	-47.09	0.98	4.89	H
	2472	-57.33	-13	-44.33	-73.73	-59.21	1.28	5.32	H
	3296	-58.93	-13	-45.93	-78.2	-62.34	1.54	7.10	H
	1648	-44.40	-13	-31.40	-58.04	-46.16	0.98	4.89	V
	2472	-55.40	-13	-42.40	-72	-57.28	1.28	5.32	V
	3296	-59.08	-13	-46.08	-78.84	-62.49	1.54	7.10	V
Middle	1672	-40.63	-13	-27.63	-53.75	-42.31	0.99	4.82	H
	2512	-54.12	-13	-41.12	-70.92	-56.09	1.29	5.41	H
	3344	-56.60	-13	-43.60	-76.75	-60.21	1.56	7.31	H
	1672	-38.11	-13	-25.11	-51.4	-39.79	0.99	4.82	V
	2512	-53.30	-13	-40.30	-69.55	-55.27	1.29	5.41	V
	3344	-58.43	-13	-45.43	-77.99	-62.04	1.56	7.31	V
High	1696	-47.01	-13	-34.01	-61.11	-48.61	1.00	4.75	H
	2544	-56.36	-13	-43.36	-73.4	-58.34	1.30	5.44	H
	3392	-58.97	-13	-45.97	-78	-62.77	1.57	7.52	H
	1696	-42.79	-13	-29.79	-55.52	-44.39	1.00	4.75	V
	2544	-57.16	-13	-44.16	-73.81	-59.14	1.30	5.44	V
	3392	-58.02	-13	-45.02	-78.59	-61.82	1.57	7.52	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



GSM1900 (GSM)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Low	3700	-57.34	-13	-44.34	-77.86	-63.91	1.67	8.24	H
	5548	-53.19	-13	-40.19	-79.84	-60.26	2.65	9.72	H
	7401	-46.48	-13	-33.48	-79.72	-55.62	2.46	11.60	H
	3700	-57.63	-13	-44.63	-78.15	-64.2	1.67	8.24	V
	5548	-50.43	-13	-37.43	-77.08	-57.5	2.65	9.72	V
	7401	-46.58	-13	-33.58	-79.82	-55.72	2.46	11.60	V
Middle	3760	-56.64	-13	-43.64	-77.23	-63.27	1.69	8.31	H
	5639	-52.38	-13	-39.38	-79.27	-59.43	2.71	9.76	H
	7520	-46.19	-13	-33.19	-79.64	-55.58	2.42	11.81	H
	3760	-57.13	-13	-44.13	-77.72	-63.76	1.69	8.31	V
	5639	-49.81	-13	-36.81	-76.7	-56.86	2.71	9.76	V
	7520	-46.37	-13	-33.37	-79.82	-55.76	2.42	11.81	V
High	3820	-57.06	-13	-44.06	-77.75	-63.74	1.70	8.38	H
	5730	-52.44	-13	-39.44	-79.6	-59.47	2.76	9.79	H
	7639	-46.09	-13	-33.09	-79.73	-55.59	2.38	11.88	H
	3820	-56.69	-13	-43.69	-77.38	-63.37	1.70	8.38	V
	5730	-51.00	-13	-38.00	-78.16	-58.03	2.76	9.79	V
	7639	-46.10	-13	-33.10	-79.74	-55.6	2.38	11.88	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



GSM1900 (EDGE class 8)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Low	3700	-57.50	-13	-44.50	-78.02	-64.07	1.67	8.24	H
	5551	-53.18	-13	-40.18	-79.83	-60.25	2.65	9.72	H
	7401	-47.00	-13	-34.00	-80.24	-56.14	2.46	11.60	H
	3700	-57.47	-13	-44.47	-77.99	-64.04	1.67	8.24	V
	5551	-53.12	-13	-40.12	-79.77	-60.19	2.65	9.72	V
	7401	-46.80	-13	-33.80	-80.04	-55.94	2.46	11.60	V
Middle	3760	-57.19	-13	-44.19	-77.78	-63.82	1.69	8.31	H
	5640	-52.72	-13	-39.72	-79.61	-59.77	2.71	9.76	H
	7520	-46.77	-13	-33.77	-80.22	-56.16	2.42	11.81	H
	3760	-57.37	-13	-44.37	-77.96	-64	1.69	8.31	V
	5640	-52.13	-13	-39.13	-79.02	-59.18	2.71	9.76	V
	7520	-46.73	-13	-33.73	-80.18	-56.12	2.42	11.81	V
High	3820	-57.16	-13	-44.16	-77.85	-63.84	1.70	8.38	H
	5729	-52.27	-13	-39.27	-79.43	-59.3	2.76	9.79	H
	7639	-46.10	-13	-33.10	-79.74	-55.6	2.38	11.88	H
	3820	-57.16	-13	-44.16	-77.85	-63.84	1.70	8.38	V
	5729	-52.56	-13	-39.56	-79.72	-59.59	2.76	9.79	V
	7639	-46.00	-13	-33.00	-79.64	-55.5	2.38	11.88	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



WCDMA Band V(RMC 12.2Kbps)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Low	1648	-59.49	-13	-46.49	-72.87	-61.25	0.98	4.89	H
	2472	-61.16	-13	-48.16	-77.99	-63.04	1.28	5.32	H
	3296	-59.46	-13	-46.46	-78.95	-62.87	1.54	7.10	H
	1648	-59.52	-13	-46.52	-72.53	-61.28	0.98	4.89	V
	2472	-61.64	-13	-48.64	-78.18	-63.52	1.28	5.32	V
	3296	-59.31	-13	-46.31	-78.92	-62.72	1.54	7.10	V
Middle	1672	-59.56	-13	-46.56	-72.66	-61.24	0.99	4.82	H
	2504	-61.55	-13	-48.55	-77.73	-63.51	1.29	5.40	H
	3344	-58.06	-13	-45.06	-78.73	-61.67	1.56	7.31	H
	1672	-57.48	-13	-44.48	-70.9	-59.16	0.99	4.82	V
	2504	-61.59	-13	-48.59	-77.47	-63.55	1.29	5.40	V
	3344	-59.68	-13	-46.68	-78.81	-63.29	1.56	7.31	V
High	1696	-59.62	-13	-46.62	-73.06	-61.22	1.00	4.75	H
	2544	-61.16	-13	-48.16	-77.94	-63.14	1.30	5.44	H
	3392	-58.55	-13	-45.55	-78.61	-62.35	1.57	7.52	H
	1696	-58.01	-13	-45.01	-71.52	-59.61	1.00	4.75	V
	2544	-61.96	-13	-48.96	-78.01	-63.94	1.30	5.44	V
	3392	-58.97	-13	-45.97	-78.92	-62.77	1.57	7.52	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



WCDMA Band II(RMC 12.2Kbps)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Low	3703	-57.67	-13	-44.67	-77.63	-64.25	1.67	8.24	H
	5555	-48.04	-13	-35.04	-75.34	-55.11	2.66	9.72	H
	7407	-46.94	-13	-33.94	-79.69	-56.09	2.46	11.61	H
	3703	-57.66	-13	-44.66	-77.62	-64.24	1.67	8.24	V
	5555	-48.26	-13	-35.26	-75.09	-55.33	2.66	9.72	V
	7407	-46.31	-13	-33.31	-79.42	-55.46	2.46	11.61	V
Middle	3764	-57.64	-13	-44.64	-77.85	-64.27	1.69	8.32	H
	5646	-52.06	-13	-39.06	-79.27	-59.11	2.71	9.76	H
	7528	-46.43	-13	-33.43	-79.93	-55.83	2.42	11.82	H
	3764	-56.91	-13	-43.91	-77.35	-63.54	1.69	8.32	V
	5646	-44.79	-13	-31.79	-71.42	-51.84	2.71	9.76	V
	7528	-46.22	-13	-33.22	-79.93	-55.62	2.42	11.82	V
High	3812	-57.48	-13	-44.48	-77.9	-64.15	1.70	8.37	H
	5723	-52.27	-13	-39.27	-79.5	-59.31	2.75	9.79	H
	7630	-46.79	-13	-33.79	-79.89	-56.28	2.39	11.88	H
	3812	-56.68	-13	-43.68	-77.64	-63.35	1.70	8.37	V
	5723	-52.23	-13	-39.23	-79.58	-59.27	2.75	9.79	V
	7630	-46.45	-13	-33.45	-79.92	-55.94	2.39	11.88	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



WCDMA Band IV(RMC 12.2Kbps)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Low	3425	-58.19	-13	-45.19	-78.75	-64.28	1.58	7.67	H
	5137	-53.45	-13	-40.45	-79.22	-60.73	2.42	9.70	H
	6850	-48.71	-13	-35.71	-80.32	-56.69	2.64	10.62	H
	3425	-58.42	-13	-45.42	-78.54	-64.51	1.58	7.67	V
	5137	-53.90	-13	-40.90	-79.07	-61.18	2.42	9.70	V
	6850	-48.26	-13	-35.26	-80.23	-56.24	2.64	10.62	V
Middle	3465	-58.10	-13	-45.10	-78.81	-64.35	1.59	7.85	H
	5198	-53.83	-13	-40.83	-79.61	-61.08	2.45	9.70	H
	6930	-47.19	-13	-34.19	-79.92	-55.29	2.61	10.72	H
	3465	-58.72	-13	-45.72	-78.68	-64.97	1.59	7.85	V
	5198	-54.96	-13	-41.96	-79.8	-62.21	2.45	9.70	V
	6930	-47.23	-13	-34.23	-79.91	-55.33	2.61	10.72	V
High	3505	-58.89	-13	-45.89	-79.05	-65.29	1.61	8.01	H
	5258	-53.90	-13	-40.90	-79.54	-61.11	2.49	9.70	H
	7010	-46.61	-13	-33.61	-79.23	-54.84	2.59	10.82	H
	3505	-58.21	-13	-45.21	-79.11	-64.61	1.61	8.01	V
	5258	-53.71	-13	-40.71	-79.65	-60.92	2.49	9.70	V
	7010	-47.14	-13	-34.14	-79.91	-55.37	2.59	10.82	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



Appendix D. Product Equality Declaration



5F, C building, No. 232, Liang Jing Road
ZhangJiang High-Tech Park, Pudong Area
Shanghai, P.R. China. 201203
TEL: +86(0)21 61460666
FAX: +86(0)21 61460602

Declaration of changes from Initial to Variant

General: 6055A is a variant product of 6055U

● SOFTWARE MODIFICATIONS:

- Protocol Stack changes: No
- MMS/STK/USAT/USIM changes: No
- DM/SUPL/VT/FUMO/SWP/HCI: Yes (6055A does not support DM/FUMO)
- Other changes detailed:
 1. Enable FDD band17
 2. Add UICC base NFC

● HARDWARE MODIFICATIONS:

- Band changes: No
- PCB Layout changes: No
- Main RF components changes:

	Antenna	AP	Modem	Transceiver	Power Amplifier	Rx SAW Filter	ASM
GSM850	No	No	No	No	No	No	No
GSM900	No	No	No	No	No	No	No
GSM1800	No	No	No	No	No	No	No
GSM1900	No	No	No	No	No	No	No

	Antenna	AP	Modem	Transceiver	Power Amplifier	Tx SAW Filter	Duplexer	ASM
UMTS band X	No	No	No	No	No	No	No	No

	Antenna	AP	Modem	Transceiver	Power Amplifier	Tx SAW Filter	Rx SAW Filter	Duplexer	ASM
LTE Band x	No	No	No	No	No	No	No	No	No
LTE Band x	No	No	No	No	No	No	No	No	No

	Antenna	AP	Modem	Transceiver	Power Amplifier	Balun	Band pass filter	Diplexer
Bluetooth	No	No	No	No	No	No	No	No

Wi-Fi	No	No	No	No	No	No	No	No
-------	----	----	----	----	----	----	----	----

- FM changes: No
- LCD/ Speaker/ Camera/ Vibrator changes: No (indicated the changed items if yes)
- Other changes detailed:
Reduce 2db power in band 7.

● **MECHANICAL MODIFICATIONS:**

- Use new metal front/back cover or keypad: No
- Mechanical shell changes:
Whole size of EUT: No
Distance of Ear reference point to bottom of handset: No
Other trinkets to change the surface of handset: No
- Other changes detailed:
1. Different logo on backcover.

APPROVED BY:

Project Manager: *Freda*

Signature: *8.10.*

Date: