



# TEST REPORT

No. I16Z41093-EMC02

for

**TCL Communication Ltd.**

**CDMA EVDO BC0/BC1 2band Mobile phone**

**Model Name: A573VC**

**FCC ID: 2ACCJB027**

**with**

**Hardware Version: PIO**

**Software Version: vQAS3**

**Issued Date: 2016-06-03**

**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

**Test Laboratory:**

**FCC 2.948 Listed: No. 525429**

CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel: +86(0)10-62304633-2512, Fax: +86(0)10-62304633-2504

Email: [ctl\\_terminals@catr.cn](mailto:ctl_terminals@catr.cn), website: [www.chinattl.com](http://www.chinattl.com)



100

## REPORT HISTORY

Report Number	Revision	Description	Issue Date
I16Z41093-EMC02	Rev.0	1st edition	2016-06-03

## **CONTENTS**

1. TEST LABORATORY .....	4
1.1. TESTING LOCATION .....	4
1.2. TESTING ENVIRONMENT .....	4
1.3. PROJECT DATA .....	4
1.4. SIGNATURE .....	4
2. CLIENT INFORMATION .....	5
2.1. APPLICANT INFORMATION .....	5
2.2. MANUFACTURER INFORMATION .....	5
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....	6
3.1. ABOUT EUT .....	6
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST .....	6
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST .....	6
3.4. GENERAL DESCRIPTION .....	7
3.5. EUT SET-UPS .....	7
4. REFERENCE DOCUMENTS .....	8
4.1. REFERENCE DOCUMENTS FOR TESTING .....	8
5. LABORATORY ENVIRONMENT .....	9
6. SUMMARY OF TEST RESULTS .....	10
6.1. SUMMARY OF TEST RESULTS .....	10
6.2. STATEMENTS .....	10
7. TEST EQUIPMENTS UTILIZED .....	11
ANNEX A: MEASUREMENT RESULTS .....	12
A.1 OUTPUT POWER .....	12
A.2 EMISSION LIMIT .....	16

## **1. Test Laboratory**

### **1.1. Testing Location**

**Location 2: CTTL(Shouxiang)**

Address: No. 51 Shouxiang Science Building, Xueyuan Road,  
Haidian District, Beijing, P. R. China 100191

### **1.2. Testing Environment**

Normal Temperature: 15-35°C


Relative Humidity: 20-75%

### **1.3. Project data**

Testing Start Date: 2016-01-13

Testing End Date: 2016-01-13

### **1.4. Signature**




Wang Junqing

(Prepared this test report)



Qu Pengfei

(Reviewed this test report)



Liu Baodian

Deputy Director of the laboratory

(Approved this test report)

## **2. Client Information**

### **2.1. Applicant Information**

Company Name: TCL Communication Ltd.  
Address /Post: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,  
Pudong Area Shanghai, P.R. China.  
City: Shanghai  
Postal Code: 201203  
Country: China  
Contact Person: Gong Zhizhou  
Contact Email: zhizhou.gong@tcl.com  
Telephone: 0086-21-31363544  
Fax: 0086-21-61460602

### **2.2. Manufacturer Information**

Company Name: TCL Communication Ltd.  
Address /Post: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,  
Pudong Area Shanghai, P.R. China.  
City: Shanghai  
Postal Code: 201203  
Country: China  
Telephone: 0086-21-31363544  
Fax: 0086-21-61460602

### **3. Equipment Under Test (EUT) and Ancillary Equipment (AE)**

#### **3.1. About EUT**

Description	CDMA EVDO BC0/BC1 2band Mobile phone
Model Name	A573VC
FCC ID	2ACCJB027
Antenna	Internal
Power supply	Battery ( charged by travel adapter)
Extreme vol. Limits	3.6VDC to 4.35VDC (nominal: 3.8VDC)

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of Telecommunication Metrology Center of MIIT of People's Republic of China.

#### **3.2. Internal Identification of EUT used during the test**

<b>EUT ID*</b>	<b>IMEI</b>	<b>HW Version</b>	<b>SW Version</b>
EUT4	/	PIO	vQAS3

\*EUT ID: is used to identify the test sample in the lab internally.

#### **3.3. Internal Identification of AE used during the test**

<b>AE ID*</b>	<b>Description</b>	<b>SN</b>	<b>Remarks</b>
AE1	Battery	/	/
AE2	Battery	/	15TCT-BA-0201
AE3	Battery	/	15TCT-BA-0193
AE7	Battery	/	15TCT-BA-0360
AE8	Battery	/	15TCT-BA-0358

AE1, AE2, AE3, AE7, AE8

Model	TLi017C1(CAB1780002C1)
Manufacturer	BYD
Capacitance	1780mAh
Nominal voltage	3.8V

\*AE ID: is used to identify the test sample in the lab internally.

### **3.4. General Description**

The Equipment Under Test (EUT) is a model of CDMA EVDO BC0/BC1 2band Mobile phone with integrated antenna.

The EUT supports CDMA Band class 0/Band class 1, supports 1X RTT、EV-DO and rev. A. It has MP3, camera, USB memory, FM radio, GPS, Bluetooth (EDR, BLE), and WLAN (802.11 b/g/n) functions.

Manual and specifications of the EUT were provided to fulfil the test.

Samples undergoing test were selected by the client.

### **3.5. EUT set-ups**

<b>EUT Set-up No.</b>	<b>Combination of EUT and AE</b>	<b>Remarks</b>
Set.3	EUT4 + AE7/AE8	ERP/EIRP/RSE tests

Note: The CDMA EVDO BC0/BC1 2band Mobile phone A573VC manufactured by TCL Communication Ltd. is a variant model based on A571VL for conformance test. According to the declaration of changes, no test needs to be performed, all results are cited from the initial model. The report number for initial model is I15Z43256-EMC02.

## 4. Reference Documents

### 4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 22	PUBLIC MOBILE SERVICES	10-1-15
		Edition
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	10-1-15
		Edition
ANSI/TIA-603-D	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards	2010
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2014
KDB 971168 D01	Measurement Guidance for Certification of Licensed Digital Transmitters	v02r01

## 5. LABORATORY ENVIRONMENT

**Fully-anechoic chamber** FAC-3 (9 meters×6.5 meters×4 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 15 %, Max. = 75 %
Shielding effectiveness	0.014MHz - 1MHz, >60dB; 1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4 Ω
Site voltage standing-wave ratio ( $S_{VSWR}$ )	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 4000 MHz

## 6. SUMMARY OF TEST RESULTS

### 6.1. Summary of test results

Abbreviations used in this clause:		
Verdict Column	P	Pass
	F	Fail
	NA	Not applicable
	NM	Not measured
Location Column	2	The test is performed in test location 2 which is described in section 1.1 of this report

#### CDMA800 BC0

Items	Test Name	Clause in FCC rules	Section in this report	Verdict	Test Location
1	Output Power	22.913(a.2)	5.4	A.1	2
2	Emission Limit	22.917(a), 2.1051	5.5	A.2	2

#### CDMA1900 BC1

Items	Test Name	Clause in FCC rules	Section in this report	Verdict	Test Location
1	Output Power	24.232(c)	5.4	A.1	2
2	Emission Limit	24.238(a), 2.1051	5.5	A.2	2

### 6.2. Statements

The test cases listed in section 6.1 of this report for the EUT specified in section 3 were performed by CTTL according to the standards or reference documents in section 4.1

The EUT met all applicable requirements of the standards or reference documents in section 4.1. This report only deals with the CDMA functions among the features described in section 3.

## 7. Test Equipments Utilized

NO.	NAME	TYPE	SERIES NUMBER	PRODUCER	CAL. DUE DATE	CAL. INTERVAL
1.	EMI Antenna	VULB 9163	9163-234	Schwarzbeck	2016-09-15	3 Years
2.	EMI Antenna	3117	00119024	ETS-Lindgren	2017-01-20	3 Years
3.	EMI Antenna	9117	167	Schwarzbeck	2019-04-13	3 Years
4.	EMI Antenna	3117	00058888	ETS-Lindgren	2017-04-20	3 Years
5.	Signal Generator	N5183A	MY49060052	Agilent	2017-03-07	1 Year
6.	Power Amplifier	5S1G4	0341863	AR	/	1 Year
7.	Universal Radio Communication Tester	E5515C	MY48363198	Agilent	2016-07-06	1 Year
8.	Spectrum Analyzer	E4440A	MY48250642	Agilent	2017-03-03	1 Year

## **ANNEX A: MEASUREMENT RESULTS**

### **A.1 OUTPUT POWER**

#### **Reference**

FCC: CFR Part 22.913 and 24.232

#### **A.1.1 Summary**

During the process of testing, the EUT was controlled via Agilent Universal Radio Communication Tester (E5515C) to ensure max power transmission and proper modulation.

This result contains peak output power and ERP/EIRP measurements for the EUT.

In all cases, output power is within the specified limits.

#### **A.1.2 Radiated**

##### **A.1.2.1 Description**

This is the test for the maximum radiated power from the EUT.


Rule Part 22.913(a) specifies "Maximum ERP. The effective radiated power (ERP) of base transmitters and cellular repeaters must not exceed 500 Watts. The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."

Rule Part 24.232 specifies, "Mobile/portable stations are limited to 2 watts EIRP. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."

##### **A.1.2.2 Method of Measurement**


The measurements procedures in TIA-603-D-2010 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).

3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, a substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the substitution antenna. Adjust the level of the signal generator output until the value of the receiver reaches the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. An amplifier should be connected to the Signal Source output port. And the cable should be connected between the amplifier and the substitution antenna.  
 The cable loss ( $P_{cl}$ ), the substitution antenna Gain ( $G_a$ ) and the amplifier Gain ( $P_{Ag}$ ) should be recorded after test.  
 The measurement results are obtained as described below:  

$$\text{Power (EIRP)} = P_{Mea} - P_{Ag} - P_{cl} - G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (Unit dBi) and known input power.

6. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $ERP = EIRP - 2.15$ .

For test layout photo, please refer to Pic.1 in Annex B.

### CDMA800(BC0)- ERP

#### Limits

Band	Peak ERP (dBm)
CDMA800(BC0)	$\leq 38.45\text{dBm (7W)}$

**Measurement result**
**CDMA800(BC0)\_1xRTT**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Peak ERP(dBm)	Polarization
824.70	-19.05	2.26	-45.79	-0.95	<b>23.28</b>	Horizontal
836.52	-19.66	2.26	-45.66	-0.82	22.41	Vertical
848.31	-20.22	2.27	-45.55	-0.80	21.71	Vertical

Sample calculation: 824.70MHz

$$\begin{aligned}
 \text{Peak ERP (dBm)} &= P_{\text{Mea}}(-19.05 \text{dBm}) - G_a (-0.95 \text{dBi}) - P_{\text{Ag}} (-45.79 \text{ dB}) - P_{\text{cl}} (2.26 \text{ dB}) - 2.15 \text{dBm} \\
 &= 23.28 \text{ dBm}
 \end{aligned}$$

**CDMA800(BC0)\_EVDO**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Peak ERP(dBm)	Polarization
824.70	-19.07	2.26	-45.79	-0.95	<b>23.26</b>	Horizontal
836.52	-19.53	2.26	-45.66	-0.82	22.54	Vertical
848.31	-20.07	2.27	-45.55	-0.80	21.86	Vertical

Sample calculation: 824.70MHz

$$\begin{aligned}
 \text{Peak ERP (dBm)} &= P_{\text{Mea}}(-19.07 \text{dBm}) - G_a (-0.95 \text{dBi}) - P_{\text{Ag}} (-45.79 \text{ dB}) - P_{\text{cl}} (2.26 \text{ dB}) - 2.15 \text{dBm} \\
 &= 23.26 \text{ dBm}
 \end{aligned}$$

**ANALYZER SETTINGS: RBW = 3MHz, VBW=8MHz**

 Note: Expanded measurement uncertainty for CDMA800 (BC0) is  $U = 1.07 \text{dB}$ ,  $k = 2$ .

**CDMA1900(BC1)- EIRP**
**Limits**

Band	Peak EIRP (dBm)
CDMA1900(BC1)	≤33dBm (2W)

**Measurement result**
**CDMA1900(BC1)\_1xRTT**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Peak EIRP(dBm)	Polarization
1851.25	-21.02	2.91	-43.74	-4.87	24.68	Horizontal
1880.00	-20.17	2.85	-43.75	-4.82	25.55	Horizontal
1908.75	-19.38	2.86	-43.77	-4.76	<b>26.29</b>	Horizontal

Sample calculation: 1908.75MHz

$$\begin{aligned}
 \text{Peak EIRP (dBm)} &= P_{\text{Mea}}(-19.38 \text{dBm}) - G_a (-4.76 \text{dBi}) - P_{\text{Ag}} (-43.77 \text{ dB}) - P_{\text{cl}} (2.86 \text{ dB}) \\
 &= 26.29 \text{dBm}
 \end{aligned}$$

**CDMA1900(BC1)\_EVDO**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Peak EIRP(dBm)	Polarization
1851.25	-21.34	2.91	-43.74	-4.87	24.36	Horizontal
1880.00	-20.22	2.85	-43.75	-4.82	25.50	Horizontal
1908.75	-20.05	2.86	-43.77	-4.76	<b>25.62</b>	Horizontal

Sample calculation: 1908.75MHz

$$\begin{aligned}\text{Peak EIRP (dBm)} &= P_{\text{Mea}}(-20.05\text{dBm}) - G_a (-4.76\text{dBi}) - P_{\text{Ag}} (-43.77 \text{ dB}) - P_{\text{cl}} (2.86\text{dB}) \\ &= 25.62\text{dBm}\end{aligned}$$

**ANALYZER SETTINGS: RBW = 3MHz, VBW=8MHz**

Note: Expanded measurement uncertainty for CDMA1900 (BC1) is  $U = 1.07\text{dB}$ ,  $k=2$ .

## **A.2 EMISSION LIMIT**

### **Reference**

FCC: CFR 2.1051, Part 22.917(a), 24.238(a).


### **A.2.1 Measurement Method**

The measurements procedures in TIA-603D-2010 are used. This measurement is carried out in fully-anechoic chamber 3.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1910 MHz. The resolution bandwidth is set 1MHz as outlined in Part 22.917 and 24.238(a). The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of CDMA800 and CDMA 1900.

**The procedure of radiated spurious emissions is as follows:**

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the substitution antenna. Adjust the level of the signal generator output until the value of the receiver reaches the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss ( $P_{pl}$ ) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain ( $G_a$ ) should be recorded after test.

An amplifier should be connected in for the test.

The Path loss ( $P_{pl}$ ) is the summation of the cable loss and the gain of the amplifier.

The measurement results are obtained as described below:

$$\text{Power (EIRP)} = P_{Mea} + P_{pl} + G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (unit: dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $ERP = EIRP - 2.15\text{dB}$ .

#### **A.2.2 Measurement Limit**

Part 22.917(a) and 24.238(a) all specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power ( $P$ ) by a factor of at least  $43 + 10 \log(P)$  dB. The specification that emissions shall be attenuated below the transmitter power ( $P$ ) by at least  $43 + 10 \log (P)$  dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

#### **A.2.3 Measurement Results**

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the CDMA BC0 (836.52MHz, 848.31MHz and 824.7MHz) and CDMA BC1 (1851.25MHz, 1880.00MHz and 1908.75 MHz). It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the CDMA BC0 or CDMA BC1 into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

**CDMA BC0, Channel 384/836.52MHz**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>pl</sub> (dB)	G <sub>a</sub> (dBi)	Peak ERP (dBm)	Limit (dBm)	Polarity
1673.79	-17.19	3.55	-5.19	-17.7	-13.00	H
2509.68	-42.48	4.48	-6.12	-42.99	-13.00	V
3346.59	-49.21	5.22	-7.83	-48.75	-13.00	H
4182.43	-52.6	5.83	-9.08	-51.5	-13.00	H
5019.12	-55.99	6.21	-9.93	-54.42	-13.00	H
5844.13	-56.95	6.59	-10.53	-55.16	-13.00	H

**CDMA BC0, Channel 777/848.31MHz**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>pl</sub> (dB)	G <sub>a</sub> (dBi)	Peak ERP (dBm)	Limit (dBm)	Polarity
1697.3	-38.97	3.45	-5.14	-39.43	-13.00	V
2543.89	-42.44	4.47	-6.18	-42.88	-13.00	V
3392.91	-50.25	5.45	-7.94	-49.91	-13.00	H
4243.92	-54.68	6.05	-9.14	-53.74	-13.00	H
5088.5	-56.45	6.45	-10.02	-55.03	-13.00	H
5937.2	-59.01	6.91	-10.51	-57.56	-13.00	H

**CDMA BC0, Channel 1013/824.7MHz**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>pl</sub> (dB)	G <sub>a</sub> (dBi)	Peak ERP (dBm)	Limit (dBm)	Polarity
1650.08	-35.51	3.42	-5.23	-35.85	-13.00	V
2474.6	-41.46	4.43	-6.02	-42.02	-13.00	V
3299.12	-49.89	5.38	-7.72	-49.7	-13.00	H
4124.89	-47.46	5.79	-9.02	-46.38	-13.00	H
4948.6	-54.6	6.32	-9.85	-53.22	-13.00	H
5769.92	-57.62	6.79	-10.55	-56.01	-13.00	V

**CDMA BC1, Channel 25/1851.25MHz**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>pl</sub> (dB)	G <sub>a</sub> (dBi)	Peak EIRP (dBm)	Limit (dBm)	Polarity
3702.39	-36.8	5.35	-8.48	-33.67	-13.00	H
5553.98	-41.77	6.59	-10.59	-37.77	-13.00	H
7394.71	-57.08	7.14	-12.07	-52.15	-13.00	H
9822.45	-56.16	8.26	-13.08	-51.34	-13.00	V
11451.12	-51.8	8.9	-13.11	-47.59	-13.00	V
13824.6	-48.49	10.04	-14.39	-44.14	-13.00	H

**CDMA BC1, Channel 600/1880.00MHz**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>pl</sub> (dB)	G <sub>a</sub> (dBi)	Peak EIRP (dBm)	Limit (dBm)	Polarity
3759.73	-37.37	5.14	-8.56	-33.95	-13.00	H
5640.43	-37.87	6.85	-10.57	-34.15	-13.00	H
7571.8	-56.62	7.38	-12.26	-51.74	-13.00	V
10221.67	-55.09	8.4	-12.99	-50.5	-13.00	H
12642.24	-48.49	9.46	-13.29	-44.66	-13.00	H
14647.48	-45.96	10.67	-14.28	-42.35	-13.00	H

**CDMA BC1, Channel 1175/1908.75MHz**

Frequency (MHz)	P <sub>Mea</sub> (dBm)	P <sub>pl</sub> (dB)	G <sub>a</sub> (dBi)	Peak EIRP (dBm)	Limit (dBm)	Polarity
3817.54	-37.25	5.45	-8.64	-34.06	-13.00	H
5726.25	-35.28	6.76	-10.55	-31.49	-13.00	H
7454.75	-56.91	7.23	-12.15	-51.99	-13.00	H
9643.16	-57.92	8.41	-13.26	-53.07	-13.00	H
11452.53	-45.21	8.9	-13.11	-41	-13.00	H
13626.34	-49.42	10.3	-14.28	-45.44	-13.00	H

Note: Expanded measurement uncertainty for this test item is  $U = 4.2$  dB,  $k = 2$ .

**\*\*\*END OF REPORT\*\*\***