



FCC PART 15B TEST REPORT

No. 24T04Z102937-004

for

TCL Communication Ltd.

Tablet PC

Model Name: 9469X

FCC ID: 2ACCJB230

with

Hardware Version: 05

Software Version: 1R13

Issued Date: 2025-01-16

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

Test Laboratory:

CTTL-Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel: +86(0)10-62304633-2512, Fax: +86(0)10-62304633-2504

Email: ctl_terminals@caict.ac.cn, website: www.caict.ac.cn

REPORT HISTORY

Report Number	Revision	Description	Issue Date
24T04Z102937-004	Rev.0	1 st edition	2025-01-16

Note: the latest revision of the test report supersedes all previous version.

CONTENTS

1. TEST LABORATORY	4
1.1. TESTING LOCATION	4
1.2. TESTING ENVIRONMENT	4
1.3. PROJECT DATA	4
1.4. SIGNATURE	4
2. CLIENT INFORMATION	5
2.1. APPLICANT INFORMATION	5
2.2. MANUFACTURER INFORMATION	5
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	6
3.1. ABOUT EUT	6
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	6
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	6
3.4. EUT SET-UPS	6
4. REFERENCE DOCUMENTS	7
4.1. REFERENCE DOCUMENTS FOR TESTING	7
5. SUMMARY OF TEST RESULTS	7
6. TEST EQUIPMENTS UTILIZED	8
7. MEASUREMENT UNCERTAINTY	9
ANNEX A: MEASUREMENT RESULTS	10

1. Test Laboratory

1.1. Testing Location

CTTL (BDA)

Address: No.18A, Kangding Street, Beijing Economic-Technology
Development Area, Beijing, P. R. China 100176

1.2. Testing Environment

Normal Temperature: 15-35°C
Relative Humidity: 20-75%

1.3. Project data

Testing Start Date: 2025-01-06
Testing End Date: 2025-01-08

1.4. Signature



Wang Xue

(Prepared this test report)



Zhang Ying

(Reviewed this test report)



Zhang Xia

(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: TCL Communication Ltd.
Address/Post: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science Park, Shatin, NT, Hong Kong
City: Hong Kong
Postal Code: /
Country: China
Contact Person: Ting Wang
Contact Email: ting.wang.hz@tcl.com
Telephone: +86 752 2639091
Fax: 0086-755-36612000-81722

2.2. Manufacturer Information

Company Name: TCL Communication Ltd.
Address/Post: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science Park, Shatin, NT, Hong Kong
City: Hong Kong
Postal Code: /
Country: China
Contact Person: Ting Wang
Contact Email: ting.wang.hz@tcl.com
Telephone: +86 752 2639091
Fax: 0086-755-36612000-81722

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	Tablet PC
Model Name	9469X
FCC ID:	2ACCJB230

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of CTTL, Telecommunication Technology Labs, CAICT.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
UT30a	CMGU9XEMLBJNA6RK	05	1R13

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	Model	Manufacturer
AE1	Battery	TLp078D5	Hunan Gaoyuan Battery Co.,Ltd.
AE2	Charger	QC16US	ShenZhen BaiJunDa Electronics Co.Ltd
AE3	USB Cable1	JWUB1799-YT01R	JUWEI

*AE ID: is used to identify the test sample in the lab internally.

3.4. EUT set-ups

EUT set-up No.	Combination of EUT and AE	Remarks
Set.1	UT30a + AE1 +AE2+AE3	Charger1+MP3+F Camera
Set.2	UT30a + AE1 +AE2+AE3	Charger1+R Camera
Set.3	UT30a + AE1 +AE3	USB
Set.4	UT30a + AE1 +AE3+AE4	FM

Note:

Equipment Under Test (EUT) is a model of Tablet PC.

It has MP3, Camera, USB memory, Bluetooth V5.2, Wi-Fi (802.11a/b/g/n/ac, 802.11n supports 20MHz and 40MHz bandwidth, 802.11ac supports 20MHz, 40MHz and 80MHz bandwidth) and GNSS function.

The device contains receivers which tune and operate between 30MHz-960MHz in the following mode: FM Rx. All licensed band receivers that tune in the range of 30MHz-960MHz are investigated. Only the worst-case emissions are reported.

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 15, Subpart B	Radio frequency devices - Unintentional Radiators	2023
ANSI C63.4	American National Standard for Methods of Measurement of Radio- Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2014

Note: The test methods have no deviation with standards.

5. SUMMARY OF TEST RESULTS

Abbreviations used in this clause:		
Verdict Column	P	Pass
	NA	Not applicable
	F	Fail

Items	Test Name	Clause in FCC rules	Section in this report	Verdict	Test Location
1	Radiated Emission	15.109(a)	B.1	P	CTTL(BDA)
2	Conducted Emission	15.107(a)	B.2	P	CTTL(BDA)

6. Test Equipments Utilized

NO.	Description	TYPE	SERIES NUMBER	MANUFACTURE	CALIBRATION PERIOD	CALIBRATION INTERVAL
1	Test Receiver	ESCI	100766	R&S	1 year	2025-04-18
2	LISN	ENV216	101459	R&S	1 year	2025-05-16
3	Test Receiver	ESU26	100376	R&S	1 year	2025-06-06
4	EMI Antenna	VULB 9163	01177	SCHWARZBECK	1 year	2025-11-19
5	EMI Antenna	3117	00119021	ETS-Lindgren	1 year	2025-09-18
6	Signal Generator	SMBV100A	256585	R&S	1 year	2025-03-03

Semi-anechoic chamber utilized did not exceed following limits along the testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 15 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz, >60dB; 1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4 Ω
Normalised site attenuation (NSA)	< ±4 dB, 10 m distance
Site voltage standing-wave ratio (S _{VSWR})	Between 0 and 6 dB, from 1GHz to 6GHz

Shielded room utilized did not exceed following limits along the testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz, >60dB; 1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4 Ω

7. Measurement Uncertainty

Where relevant, the following measurement uncertainty(worse case) levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Location 1: CTTL(BDA)

Test item	Frequency ranges	Measurement uncertainty
Radiated Emission	30MHz-1GHz	5.73dB($k=2$)
	1GHz-18GHz	5.58dB($k=2$)
Conducted Emission	150kHz-30MHz	AC Power Line: 3.10dB($k=2$)

ANNEX A: MEASUREMENT RESULTS

A.1 Radiated Emission

Reference

FCC: CFR Part 15.109(a).

A.1.1 Method of measurement

The field strength of radiated emissions from the unintentional radiator (USB/OTG mode of MS and charging mode of MS) at distances of 3 meters is tested. Tested in accordance with the procedures of ANSI C63.4 – 2014, section 8.3.

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3/10 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

A.1.2 EUT Operating Mode

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode, and is connected to the other device for charging in OTG mode and is connected to a charger in the case of charging mode.

The EUT was tested while operating in licensed band Rx mode. All licensed band receivers that tune in the range of 30MHz-960MHz, as listed in section 3.4, are investigated. Only the worst case emissions are reported.

All equipment is placed on the test table top and arranged in a typical configuration in accordance with ANSI C63.4-2014 and manipulated to obtain worst case emissions.

The model of the PC is M4000E-17, and the serial number of the PC is M706GWXD. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

Note: I/O information: Printer – USB, Mouse – PS/2, Keyboard – USB.

The EUT was tested while operating in licensed band Rx mode. All licensed band receivers that tune in the range of 30MHz-960MHz, as listed in section 3.4, are investigated. Only the worst case emissions are reported.

All equipment is placed on the test table top and arranged in a typical configuration in accordance with ANSI C63.4-2014 and manipulated to obtain worst case emissions.

A.1.3 Measurement Limit

Frequency range (MHz)	Field strength limit (μ V/m)		
	Quasi-peak	Average	Peak
30-88	100		
88-216	150		
216-960	200		
960-1000	500		
>1000		500	5000

Note: the above limit is for 3 meters test distance. 10 meters' limit is got by converting.

A.1.4 Test Condition

Frequency range (MHz)	RBW/VBW	Sweep Time (s)	Detector
30-1000	120kHz (IF Bandwidth)	5	Peak/Quasi-peak
Above 1000	1MHz/3MHz	15	Peak, Average

A.1.5 Measurement Results

A "reference path loss" is established and the A_{RPL} is the attenuation of "reference path loss". It includes the antenna factor of receive antenna and the path loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{Mea}} + A_{RPL} = P_{\text{Mea}} + G_A + G_{PL}$$

Where

G_A : Antenna factor of receive antenna

G_{PL} : Path Loss

P_{Mea} : Measurement result on receiver.

Measurement results for Set.1:
Charging Mode/Average detector

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17888.500	41.49	-21.0	40.5	21.95	54.0	12.5	H
17889.000	41.44	-21.0	40.5	21.91	54.0	12.6	H
17891.000	41.40	-21.0	40.5	21.90	54.0	12.6	H
17540.500	41.32	-20.7	40.8	21.23	54.0	12.7	H
17885.000	41.31	-21.0	40.5	21.76	54.0	12.7	H
17873.000	41.31	-21.2	40.5	22.00	54.0	12.7	H

Charging Mode/Peak detector

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17997.500	53.8	-21.2	40.6	34.45	74.0	20.2	H
15956.500	53.6	-23.5	40.8	36.23	74.0	20.4	V
17070.000	53.5	-22.0	41.0	34.52	74.0	20.5	H
16961.000	53.5	-22.2	41.2	34.46	74.0	20.5	H
17826.500	53.4	-21.4	40.6	34.28	74.0	20.6	H
17025.500	53.4	-22.3	41.1	34.59	74.0	20.6	H

Measurement results for Set.2:
Charging Mode/Average detector

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17882.500	41.42	-21.0	40.5	21.86	54.0	12.6	H
17881.500	41.40	-21.0	40.5	21.84	54.0	12.6	H
17892.500	41.38	-21.0	40.5	21.90	54.0	12.6	H
17888.000	41.36	-21.0	40.5	21.83	54.0	12.6	H
17885.500	41.36	-21.0	40.5	21.81	54.0	12.6	H
17878.000	41.35	-21.0	40.5	21.86	54.0	12.6	H

Charging Mode/Peak detector

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
16671.500	54.0	-22.5	41.4	35.05	74.0	20.0	H
17675.000	53.7	-21.2	40.5	34.35	74.0	20.3	H
16689.000	53.6	-22.6	41.4	34.81	74.0	20.4	H
17778.500	53.5	-21.4	40.6	34.35	74.0	20.5	V
17879.000	53.4	-21.0	40.5	33.86	74.0	20.6	H
16956.500	53.4	-22.2	41.2	34.38	74.0	20.6	V

Measurement results for Set.3:
USB Mode/Average detector

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
16283.000	40.61	-22.3	40.9	22.03	54.0	13.4	V
16291.000	40.60	-22.0	40.9	21.72	54.0	13.4	V
17540.500	40.52	-20.7	40.8	20.42	54.0	13.5	V
16391.000	40.50	-22.6	40.9	22.19	54.0	13.5	V
16686.000	40.49	-22.6	41.4	21.69	54.0	13.5	V
17877.000	40.49	-21.1	40.5	21.03	54.0	13.5	V

USB Mode/Peak detector


Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
1042.400	57.1	-37.4	26.8	67.80	74.0	16.9	V
1045.600	56.4	-37.4	26.7	67.12	74.0	17.6	V
1039.200	56.4	-37.4	26.8	67.04	74.0	17.6	V
1046.200	56.4	-37.4	26.7	67.09	74.0	17.6	V
1046.000	56.2	-37.4	26.7	66.90	74.0	17.8	V
1039.600	56.1	-37.4	26.8	66.76	74.0	17.9	V

Measurement results for Set.4:
FM Mode/Average detector


Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17867.500	41.46	-21.3	40.5	22.25	54.0	12.5	H
17879.000	41.41	-21.0	40.5	21.88	54.0	12.6	H
17877.000	41.37	-21.1	40.5	21.91	54.0	12.6	H
17879.500	41.36	-21.0	40.5	21.81	54.0	12.6	H
17878.500	41.34	-21.0	40.5	21.83	54.0	12.7	H
17881.500	41.32	-21.0	40.5	21.76	54.0	12.7	H

FM Mode/Peak detector

Frequency (MHz)	Measurement Result (dB μ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB μ V)	Limit (dB μ V/m)	Margin (dB)	Antenna Pol. (H/V)
17543.500	54.1	-20.9	40.8	34.24	74.0	19.9	H
17985.500	53.9	-21.1	40.6	34.44	74.0	20.1	H
17093.000	53.7	-22.4	41.0	35.04	74.0	20.3	H
16655.000	53.5	-22.5	41.4	34.74	74.0	20.5	H
16046.000	53.4	-23.2	40.9	35.73	74.0	20.6	H
16894.500	53.4	-22.4	41.4	34.40	74.0	20.6	H

Measurement results for Set.1:

Fig A.1 Radiated Emission from 30MHz to 1GHz
Final Result 1

Frequency (MHz)	QuasiPeak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBuV/m)	Comment
57.254000	23.9	125.0	V	260.0	-0.3	16.1	40.0	
62.983000	25.9	100.0	V	280.0	-1.7	14.2	40.0	
72.021000	29.6	175.0	V	112.0	-4.8	10.4	40.0	
133.017000	21.3	100.0	V	-16.0	-4.5	22.2	43.5	
164.051000	22.6	100.0	V	-10.0	-3.8	20.9	43.5	
190.532000	26.9	100.0	H	68.0	-1.4	16.6	43.5	


Fig A.2 Radiated Emission from 1GHz to 3GHz




Fig A.3 Radiated Emission from 3GHz to 18GHz

Measurement results for Set.2:




Fig A.4 Radiated Emission from 30MHz to 1GHz

Final Result 1

Frequency (MHz)	QuasiPeak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBuV/m)	Comment
61.873000	24.8	100.0	V	87.0	-1.4	15.2	40.0	
86.765000	32.3	100.0	V	202.0	-4.4	7.7	40.0	
88.779000	31.0	119.0	V	180.0	-3.7	12.5	43.5	
96.351000	25.9	113.0	V	202.0	-1.6	17.6	43.5	
185.183000	20.0	100.0	V	-3.0	-2.2	23.5	43.5	
946.847000	32.9	200.0	H	183.0	13.7	13.1	46.0	




Fig A.5 Radiated Emission from 1GHz to 3GHz






Fig A.6 Radiated Emission from 3GHz to 18GHz

Measurement results for Set.3:

Fig A.7 Radiated Emission from 30MHz to 1GHz
Final Result 1

Frequency (MHz)	QuasiPeak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBuV/m)	Comment
30.445000	35.3	125.0	V	90.0	-3.6	4.7	40.0	
31.050000	32.9	100.0	V	0.0	-3.7	7.1	40.0	
32.736000	29.6	100.0	V	80.0	-3.4	10.4	40.0	
61.508000	31.4	200.0	H	270.0	-1.3	8.6	40.0	
565.266000	39.7	100.0	V	164.0	8.1	6.3	46.0	
589.807000	43.3	113.0	H	286.0	9.2	2.7	46.0	


Fig A.8 Radiated Emission from 1GHz to 3GHz




Fig A.9 Radiated Emission from 3GHz to 18GHz

Measurement results for Set.4:




Fig A.10 Radiated Emission from 30MHz to 1GHz

Final Result 1

Frequency (MHz)	QuasiPeak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBuV/m)	Comment
51.554000	20.3	204.0	V	4.0	0.4	19.7	40.0	
77.975000	18.2	225.0	H	93.0	-6.6	21.8	40.0	
194.144000	18.4	100.0	V	177.0	-0.6	25.1	43.5	
252.792000	20.0	175.0	H	-4.0	1.0	26.0	46.0	
427.392000	25.0	225.0	H	170.0	6.3	21.0	46.0	
859.721000	31.7	125.0	V	177.0	12.7	14.3	46.0	




Fig A.11 Radiated Emission from 1GHz to 3GHz




Fig A.12 Radiated Emission from 3GHz to 18GHz

A.2 Conducted Emission

Reference

FCC: CFR Part 15.107(a).

A.2.1 Method of measurement

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits. Tested in accordance with the procedures of ANSI C63.4 – 2014, section 7.3.

A.2.2 EUT Operating Mode

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is DELL M4000E-17, and the serial number of the PC is M706GWXD. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

Note: I/O information: Printer – USB, Mouse – PS/2, Keyboard – USB.

A.2.3 Measurement Limit

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency

A.2.4 Test Condition in charging mode

Voltage (V)	Frequency (Hz)
120	60

RBW/IF bandwidth	Sweep Time(s)
9kHz	1

A.2.5 Measurement Results

Measurement uncertainty: $U = 3.10 \text{ dB}$, $k=2$.

Charging Mode, Set.1:





Fig A.13 Conducted Emission from 150kHz to 30MHz

Final Result 1

Frequency (MHz)	QuasiPeak (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)	Comment
0.159000	53.0	2000.0	9.000	On	N	20.1	12.5	65.5	
0.181500	51.1	2000.0	9.000	On	N	20.0	13.3	64.4	
0.195000	49.9	2000.0	9.000	On	L1	20.0	13.9	63.8	
0.235500	47.0	2000.0	9.000	On	L1	20.0	15.3	62.3	
0.253500	45.9	2000.0	9.000	On	L1	20.0	15.8	61.6	
0.307500	42.8	2000.0	9.000	On	L1	20.0	17.3	60.0	

Final Result 2


Frequency (MHz)	Average (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)	Comment
0.159000	23.6	2000.0	9.000	On	L1	20.1	31.9	55.5	
0.213000	29.4	2000.0	9.000	On	N	20.0	23.6	53.1	
0.271500	30.4	2000.0	9.000	On	L1	20.0	20.6	51.1	
0.343500	23.5	2000.0	9.000	On	N	20.1	25.6	49.1	
0.555000	22.3	2000.0	9.000	On	N	20.2	23.7	46.0	
0.685500	23.2	2000.0	9.000	On	N	20.1	22.8	46.0	

Charging Mode, Set.2:

Fig A.14 Conducted Emission from 150kHz to 30MHz
Final Result 1

Frequency (MHz)	QuasiPeak (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)	Comment
0.154500	55.3	2000.0	9.000	On	L1	20.1	10.4	65.8	
0.168000	54.0	2000.0	9.000	On	L1	20.0	11.1	65.1	
0.190500	52.7	2000.0	9.000	On	N	20.0	11.3	64.0	
0.208500	50.7	2000.0	9.000	On	N	20.0	12.5	63.3	
0.249000	48.9	2000.0	9.000	On	L1	20.0	12.9	61.8	
0.280500	47.2	2000.0	9.000	On	L1	20.0	13.6	60.8	

Final Result 2

Frequency (MHz)	Average (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)	Comment
0.150000	32.4	2000.0	9.000	On	N	20.2	23.6	56.0	
0.208500	30.6	2000.0	9.000	On	N	20.0	22.7	53.3	
0.280500	26.6	2000.0	9.000	On	N	20.1	24.2	50.8	
0.546000	21.3	2000.0	9.000	On	N	20.2	24.7	46.0	
1.045500	24.1	2000.0	9.000	On	N	20.0	21.9	46.0	
1.513500	27.9	2000.0	9.000	On	L1	19.9	18.1	46.0	

USB Mode, Set.3:

Fig A.15 Conducted Emission from 150kHz to 30MHz
Final Result 1

Frequency (MHz)	QuasiPeak (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)	Comment
0.195000	41.7	2000.0	9.000	On	N	20.0	22.1	63.8	
0.348000	32.1	2000.0	9.000	On	N	20.1	26.9	59.0	
0.487500	37.9	2000.0	9.000	On	N	20.2	18.3	56.2	
0.622500	30.6	2000.0	9.000	On	N	20.1	25.4	56.0	
1.018500	32.6	2000.0	9.000	On	N	20.0	23.4	56.0	
11.895000	49.7	2000.0	9.000	On	L1	20.0	10.3	60.0	

Final Result 2

Frequency (MHz)	Average (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)	Comment
0.195000	39.1	2000.0	9.000	On	L1	20.0	14.7	53.8	
0.348000	32.2	2000.0	9.000	On	L1	20.0	16.8	49.0	
0.487500	37.0	2000.0	9.000	On	L1	20.1	9.2	46.2	
0.622500	31.1	2000.0	9.000	On	L1	20.0	14.9	46.0	
1.018500	30.1	2000.0	9.000	On	N	20.0	15.9	46.0	
11.913000	37.0	2000.0	9.000	On	L1	20.0	13.0	50.0	

*****END OF REPORT*****