



FCC PART 15E TEST REPORT No.25T04Z100410-015

for

TCL Communication Ltd.

Projector

P30D8F

FCC ID: 2ACCJB234

with

Hardware Version: TP3_M_F

Software Version: V11

Issued Date: 2025-07-14

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

Test Laboratory:

CTTL-Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: cttl_terminals@caict.ac.cn, website: www.caict.ac.cn

REPORT HISTORY

Report Number	Revision	Description	Issue Date
25T04Z100410-015	Rev.0	1st edition	2025-07-14

Note: the latest revision of the test report supersedes all previous version.

CONTENTS

1. TEST LABORATORY	5
1.1. INTRODUCTION & ACCREDITATION	5
1.2. TESTING LOCATION	5
1.3. TESTING ENVIRONMENT	5
1.4. PROJECT DATE	5
1.5. SIGNATURE	5
2. CLIENT INFORMATION	6
2.1. APPLICANT INFORMATION	6
2.2. MANUFACTURER INFORMATION	6
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	7
3.1. ABOUT EUT	7
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	7
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	7
3.4. GENERAL DESCRIPTION	7
4. REFERENCE DOCUMENTS	8
4.1. DOCUMENTS SUPPLIED BY APPLICANT	8
4.2. REFERENCE DOCUMENTS FOR TESTING	8
5. LABORATORY ENVIRONMENT	8
6. TEST RESULTS	9
6.1. SUMMARY OF TEST RESULTS	9
6.2. STATEMENTS	9
6.3. TEST CONDITIONS	9
7. TEST FACILITIES UTILIZED	10
8. MEASUREMENT UNCERTAINTY	11
8.1. TRANSMITTER OUTPUT POWER	11
8.2. PEAK POWER SPECTRAL DENSITY	11
8.3. 6dB EMISSION BANDWIDTH	11
8.4. BAND EDGES COMPLIANCE	11
8.5. SPURIOUS EMISSIONS	11
8.6. RADIATED UNWANTED EMISSION	11
8.7. AC POWER-LINE CONDUCTED EMISSION	11
ANNEX A: MEASUREMENT RESULTS	12
A.1. MEASUREMENT METHOD	12
A.2. MAXIMUM PEAK OUTPUT POWER	13
A.2.1 ANTENNA GAIN	13
A.2.2. MAXIMUM AVERAGE OUTPUT POWER-CONDUCTED	13

A.3. PEAK POWER SPECTRAL DENSITY	16
A.4. 6dB EMISSION BANDWIDTH	18
A.5. RADIATED UNWANTED EMISSION	28
A.5.1 LIMITS	28
A.5.2 TEST SETUP	29
A.5.3 TEST PROCEDURES	30
A.5.4 CALCULATION	30
A.6. AC POWERLINE CONDUCTED EMISSION	40
A.6.1 SUMMARY	40
A.6.2 METHOD OF MEASUREMENT	40
A.6.3 TEST CONDITION	40
A.6.4 TEST SETUP	40
A.6.5 MEASUREMENT RESULT AND LIMIT	41
A.7. ANTENNA REQUIREMENT	44
ANNEX B: EUT PARAMETERS.....	44
ANNEX C: ACCREDITATION CERTIFICATE	45

1. Test Laboratory

1.1. Introduction & Accreditation

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2017 accredited test laboratory under American Association for Laboratory Accreditation (A2LA) with lab code 7049.01, and is also an FCC accredited test laboratory (CN1349), and ISED accredited test laboratory (CAB identifier:CN0066). The detail accreditation scope can be found on A2LA website.

1.2. Testing Location

Conducted testing Location:CTTL(Gaolizhang Road)

Address: Cuihu Cloud Center, No.1, Gaolizhang Road, Wenquan,
Haidian District, Beijing, China

Radiated testing Location: CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,
100191, P. R. China

1.3. Testing Environment

Normal Temperature: 15-35°C

Relative Humidity: 20-75%

1.4. Project date

Testing Start Date: 2025-04-24


Testing End Date: 2025-07-14

1.5. Signature



Yao Xingyu

(Prepared this test report)



Zheng Wei

(Reviewed this test report)



Pang Shuai

(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: TCL Communication Ltd.
Address/Post: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science
Park, Shatin, NT, Hong Kong
City: Hong Kong
Postal Code: /
Country: China
Contact Person: Ting Wang
Contact Email: ting.wang.hz@tcl.com
Telephone: +86 752 2639091
Fax: /

2.2. Manufacturer Information

Company Name: TCL Communication Ltd.
Address/Post: 5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science
Park, Shatin, NT, Hong Kong
City: Hong Kong
Postal Code: /
Country: China
Contact Person: Ting Wang
Contact Email: ting.wang.hz@tcl.com
Telephone: +86 752 2639091
Fax: /

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	Projector
Model name	P30D8F
FCC ID	2ACCJB234
WLAN Frequency Band	ISM Band: 5725MHz~5850MHz
Type of modulation	OFDM
Normal Voltage	20V
Extreme High Voltage	21V
Extreme Low Voltage	19V

3.2. Internal Identification of EUT used during the test

EUT ID*	IMEI	HW Version	SW Version	Date of receipt
UT01a	P30D8F3J1EH0001	TP3_M_F	V11	2025-04-01
UT10a	P30D8F3J1EH000A	TP3_M_F	V11	2025-05-09

*EUT ID: is used to identify the test sample in the lab internally.

UT01a is used for Conduction test, UT10a is used for Radiation test.

3.3. Internal Identification of AE used during the test

AE ID*	Description	Model	Manufacturer	Remark
AE1	Battery	TLp043G7	Veken	--
AE2	Adapter	PD100E-B1C0AVU C	Mass Power Electronics Inc.	--
AE3	Cable	UL2725-18	Huizhou Besiter Power Technology Co., Ltd	--

*AE ID: is used to identify the test sample in the lab internally.

3.4. General Description

Equipment Under Test (EUT) is a model of Projector with integrated antenna. It consists of normal options: Battery and Charger.

Manual and specifications of the EUT were provided to fulfil the test.

Samples undergoing test were selected by the Client.

4. Reference Documents

4.1. Documents supplied by applicant

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

FCC Part15	FCC CFR 47, Part 15, Subpart C and E:	
	15.205 Restricted bands of operation;	
	15.207 Conducted limits;	2021
	15.209 Radiated emission limits, general requirements;	
ANSI C63.10	15.407 General technical requirements.	
	Methods of Measurement of Radio-Noise Emissions from	
	Low-Voltage Electrical and Electronic Equipment in the	2013
	Range of 9 kHz to 40 GHz	
UNII: KDB 789033	General U-NII Test Procedures New Rules v02r01	2017-12
D02		

Note:UNII: KDB 789033 D02 is not in the scope of ISO/IEC 17025 accreditation by A2LA.

5. Laboratory Environment

Conducted RF performance testing is performed in shielding room.

EMC performance testing is performed in Semi-anechoic chamber.

6. Test Results

6.1. Summary of Test Results

SUMMARY OF MEASUREMENT RESULTS	Sub-clause of Part15C/E	Sub-clause of IC	Verdict
Maximum Peak Output Power	15.407 (a)	/	P
Peak Power Spectral Density	15.407 (a)	/	P
6dB Emission Bandwidth	15.407 (e)	/	P
Radiated Unwanted Emission	15.407, 15.205, 15.209	/	P
AC Powerline Conducted Emission	15.207	/	P

Please refer to **ANNEX A** for detail.

Terms used in Verdict column

P	Pass, The EUT complies with the essential requirements in the standard.
NM	Not measured, The test was not measured by CTTL
NA	Not Applicable, The test was not applicable
F	Fail, The EUT does not comply with the essential requirements in the standard

6.2. Statements

CTTL has evaluated the test cases as listed in section 6.1 of this report for the EUT specified in section 3 according to the standards or reference documents listed in section 4.

This report only deals with the WLAN function among the features described in section 3.

6.3. Test Conditions

For this report, all the test cases are tested under normal temperature and normal voltage, and also under norm humidity, the specific condition is shown as follows:

Temperature	26°C
Voltage	20V
Humidity	44%

7. Test Facilities Utilized

Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Vector Signal Analyzer	FSW67	104051	Rohde & Schwarz	1 year	2026-06-09
2	LISN	ENV216	101200	Rohde & Schwarz	1 year	2026-06-05
3	Test Receiver	ESCI	100344	Rohde & Schwarz	1 year	2026-04-01
4	Attenuator	10dB/2W	/	Rosenberger	/	/
5	Shielding Room	S81	/	ETS-Lindgren	/	/

Radiated emission test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Test Receiver	FSW67	103290	Rohde & Schwarz	1 year	2026-03-23
2	EMI Antenna	VULB9163	01222	Schwarzbeck	1 year	2025-09-11
3	EMI Antenna	3115	6914	ETS-Lindgren	1 year	2026-03-31

8. Measurement Uncertainty

8.1. Transmitter Output Power

Measurement Uncertainty: 0.387dB,k=1.96

8.2. Peak Power Spectral Density

Measurement Uncertainty: 0.705dB,k=1.96

8.3. 6dB Emission Bandwidth

Measurement Uncertainty: 60.80Hz,k=1.96

8.4. Band Edges Compliance

Measurement Uncertainty : 0.62dB,k=1.96

8.5. Spurious Emissions

Conducted (k=1.96)

Frequency Range	Uncertainty(dB)
$30\text{MHz} \leq f \leq 2\text{GHz}$	1.22
$2\text{GHz} \leq f \leq 3.6\text{GHz}$	1.22
$3.6\text{GHz} \leq f \leq 8\text{GHz}$	1.22
$8\text{GHz} \leq f \leq 12.75\text{GHz}$	1.51
$12.75\text{GHz} \leq f \leq 26\text{GHz}$	1.51
$26\text{GHz} \leq f \leq 40\text{GHz}$	1.59

8.6. Radiated Unwanted Emission

Frequency Range	Uncertainty(dB)
9kHz-30MHz	4.92
$30\text{MHz} \leq f \leq 1\text{GHz}$	4.72
$1\text{GHz} \leq f \leq 18\text{GHz}$	4.84
$18\text{GHz} \leq f \leq 40\text{GHz}$	5.12

8.7. AC Power-line Conducted Emission


Measurement Uncertainty : 3.08dB,k=2

ANNEX A: MEASUREMENT RESULTS

A.1. Measurement Method

A.1.1. Conducted Measurements

- 1). Connect the EUT to the test system correctly.
- 2). Set the EUT to the required work mode.
- 3). Set the EUT to the required channel.
- 4). Set the spectrum analyzer to start measurement.
- 5). Record the values. Vector Signal Analyzer



A.1.2. Radiated Emission Measurements

Measurement performed according to Clause 6.4, 6.5, 6.6 in ANSI C63.10-2013 and II.G.4, II.G.5, II.G.6 in KDB 789033.

The radiated emission test is performed in semi-anechoic chamber. The EUT was placed on a non-conductive table with 80cm above the ground plane for measurement below 1GHz and 1.5m above the ground plane for measurement above 1GHz. The measurement antenna was placed at a distance of 3 meters from the EUT. The test is carried out on both vertical and horizontal polarization and only maximization result of both polarizations is kept. During the test, the turntable is rotated from 0° to 360° and the measurement antenna is moved from 1m to 4m to get the maximization result. The maximization process was repeated with the EUT positioned in each of its three orthogonal orientations

A.2. Maximum Peak Output Power

Measurement Limit and Method:

Standard	Limit (dBm)
FCC CRF Part 15.407(a)	< 30

Set span to encompass the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal.

Set RBW = 1 MHz.

Set VBW $\geq$ 3 MHz.

Number of points in sweep $\geq 2 \times \text{span} / \text{RBW}$.

Sweep time = auto.

Detector = power averaging (rms)

Trace average at least 100 traces in power averaging (rms) mode; however, the number of traces to be averaged shall be increased above 100 as needed to ensure that the average accurately represents the true average over the on and off periods of the transmitter.

Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument's band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at 1 MHz intervals extending across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal. Add 10 log (1/x), where x is the duty cycle

A.2.1 Antenna Gain

Antenna gain is SISO:1dBi(WIFI0)/1.2dBi(WIFI1),MIMO:1.2dBi(WIFI0/WIFI1),and the value is supplied by the applicant or manufacturer.

A.2.2. Maximum Average Output Power-Conducted

EUT ID: UT01a

Measurement Results:

SISO

Mode	Data Rate (Index)	Conducted power					
		5745MHz(Ch149)		5785MHz(Ch157)		5825MHz(Ch165)	
		WIFI0	WIFI1	WIFI0	WIFI1	WIFI0	WIFI1
802.11a	6Mbps	6.96	6.39	6.48	5.93	6.49	5.99
802.11n-HT20	MCS0	3.88	3.44	3.56	3.13	3.57	3.20
802.11ac-VHT20	MCS0	3.87	3.48	3.68	3.13	3.62	3.21

Mode	Data Rate (Index)	Conducted power			
		5755MHz(Ch151)		5795MHz(Ch159)	
		WIFI0	WIFI1	WIFI0	WIFI1
802.11n-HT40	MCS0	2.51	2.32	2.22	1.65
802.11ac-VHT40	MCS0	2.61	2.30	2.36	1.63

Mode	Data Rate (Index)	Conducted power	
		5775MHz(Ch155)	
		WIFI0	WIFI1
802.11ac-VHT80	MCS0	3.78	3.43


MIMO

Mode	Data Rate (Index)	Conducted power								
		5745MHz(Ch149)			5785MHz(Ch157)			5825MHz(Ch165)		
		WIFI0	WIFI1	MIMO	WIFI0	WIFI1	MIMO	WIFI0	WIFI1	MIMO
802.11n-HT20	MCS0	4.02	3.45	6.75	3.79	3.25	6.54	3.71	3.34	6.54
802.11ac-VHT20	MCS0	4.10	3.45	6.80	3.71	3.21	6.48	3.69	3.37	6.54

Mode	Data Rate (Index)	Conducted power						
		5755MHz(Ch151)			5795MHz(Ch159)			
		WIFI0	WIFI1	MIMO	WIFI0	WIFI1	MIMO	MIMO
802.11n-HT40	MCS0	2.81	2.03	5.45	2.61	1.52	5.11	
802.11ac-VHT40	MCS0	2.91	2.01	5.49	2.48	1.44	5.00	

Mode	Data Rate (Index)	Conducted power		
		5775MHz(Ch155)		
		WIFI0	WIFI1	MIMO
802.11ac-VHT80	MCS0	4.02	3.43	6.75

The data rate 6Mbps (11a mode), MCS0 (11n-HT20 mode), MCS0 (11n-HT40 mode), MCS0 (11ac-VHT20 mode), MCS0 (11ac-VHT40 mode), MCS0 (11ac-VHT80 mode) are selected as the worst condition; as the maximum power is got with these data rate. The following cases are performed with this condition.




15:48:20 10.07.2025

Maximum output Power: 11a CH149 WIFI0

The duty cycle of all mode are

Mode	802.11a	802.11n20	802.11ac20	802.11n40	802.11ac40	802.11ac80
Duty Cycle	96%	96%	96%	91%	93%	87%



14:53:16 10.07.2025

Duty cycle

Conclusion: PASS

A.3. Peak Power Spectral Density

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.407(a)	< 30 dBm/500 kHz

Set span to encompass the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal.

Set RBW = 500 kHz.

Set VBW $\geq$ 3 MHz.

Number of points in sweep $\geq 2 \times \text{span} / \text{RBW}$.

Sweep time = auto.

Detector = power averaging (rms)

Trace average at least 100 traces in power averaging (rms) mode; however, the number of traces to be averaged shall be increased above 100 as needed to ensure that the average accurately represents the true average over the on and off periods of the transmitter. Use the peak search function on the instrument to find the peak of the spectrum and record its value. Add $10 \log (1/x)$, where x is the duty cycle.

Measurement Uncertainty:

Measurement Uncertainty	0.75dB
-------------------------	--------


EUT ID: UT01a

Measurement Results:

TestMode	Antenna	Frequency[MHz]	Result [dBm/500KHz]	Limit[dBm/500KHz]	Verdict
11A	WIFI0	5745	-6.46	≤ 30.00	PASS
	WIFI0	5785	-6.50	≤ 30.00	PASS
	WIFI0	5825	-6.71	≤ 30.00	PASS
11N20SISO	WIFI0	5745	-9.36	≤ 30.00	PASS
	WIFI0	5785	-9.72	≤ 30.00	PASS
	WIFI0	5825	-9.75	≤ 30.00	PASS
11AC40SISO	WIFI0	5755	-13.58	≤ 30.00	PASS
	WIFI0	5795	-13.89	≤ 30.00	PASS
11AC80SISO	WIFI0	5775	-15.68	≤ 30.00	PASS
11AC20MIMO	WIFI0	5745	-9.06	≤ 30.00	PASS
	WIFI1	5745	-9.63	≤ 30.00	PASS
	total	5745	-6.33	≤ 30.00	PASS
	WIFI0	5785	-9.47	≤ 30.00	PASS
	WIFI1	5785	-9.93	≤ 30.00	PASS
	total	5785	-6.68	≤ 30.00	PASS
	WIFI0	5825	-9.58	≤ 30.00	PASS
	WIFI1	5825	-9.65	≤ 30.00	PASS
	total	5825	-6.60	≤ 30.00	PASS
11AC40MIMO	WIFI0	5755	-13.41	≤ 30.00	PASS
	WIFI1	5755	-14.29	≤ 30.00	PASS

	total	5755	-10.82	≤30.00	PASS
	WIFI0	5795	-13.80	≤30.00	PASS
	WIFI1	5795	-14.56	≤30.00	PASS
	total	5795	-11.15	≤30.00	PASS
11AC80MIMO	WIFI0	5775	-15.37	≤30.00	PASS
	WIFI1	5775	-16.20	≤30.00	PASS
	total	5775	-12.75	≤30.00	PASS

Note:SISO:All results have been tested, only shows the worst case



Peak Power Spectral Density: 11a CH149 WIFI0

Conclusion: PASS

A.4. 6dB Emission Bandwidth

Measurement Limit:

Standard	Limit (kHz)
FCC 47 CFR Part 15.407 (e)	≥ 500

Set RBW = 100 kHz.

Set the video bandwidth (VBW) $\geq 3 \times$ RBW.

Detector = Peak.

Trace mode = max hold.

Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Measurement Uncertainty:

Measurement Uncertainty	60.80Hz
-------------------------	---------


EUT ID: UT01a


Measurement Result:

TestMode	Antenna	Frequency[MHz]	6db EBW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11A	WIFI0	5745	15.12	5737.40	5752.52	0.5	PASS
	WIFI0	5785	15.12	5777.40	5792.52	0.5	PASS
	WIFI0	5825	15.12	5817.40	5832.52	0.5	PASS
11N20SISO	WIFI0	5745	15.12	5737.44	5752.56	0.5	PASS
	WIFI0	5785	15.12	5777.44	5792.56	0.5	PASS
	WIFI0	5825	15.12	5817.44	5832.56	0.5	PASS
11AC40SISO	WIFI0	5755	35.12	5737.48	5772.60	0.5	PASS
	WIFI0	5795	35.12	5777.48	5812.60	0.5	PASS
11AC80SISO	WIFI0	5775	75.20	5737.40	5812.60	0.5	PASS
11AC20MIMO	WIFI0	5745	15.12	5737.48	5752.60	0.5	PASS
	WIFI1	5745	15.68	5736.92	5752.60	0.5	PASS
	WIFI0	5785	15.16	5777.48	5792.64	0.5	PASS
	WIFI1	5785	16.28	5776.92	5793.20	0.5	PASS
	WIFI0	5825	15.12	5817.52	5832.64	0.5	PASS
	WIFI1	5825	16.32	5816.92	5833.24	0.5	PASS
11AC40MIMO	WIFI0	5755	35.12	5737.48	5772.60	0.5	PASS
	WIFI1	5755	35.12	5737.48	5772.60	0.5	PASS
	WIFI0	5795	35.12	5777.48	5812.60	0.5	PASS
	WIFI1	5795	35.12	5777.48	5812.60	0.5	PASS
11AC80MIMO	WIFI0	5775	75.20	5737.40	5812.60	0.5	PASS
	WIFI1	5775	75.20	5737.40	5812.60	0.5	PASS

Note:SISO:All results have been tested, only shows the worst case


Test graphs as below:






14:55:47 10.07.2025

11N20SISO_WIFI0_5745




15:02:41 10.07.2025

11N20SISO_WIFI0_5785




15:04:05 10.07.2025

11N20SISO_WIFI0_5825




15:05:18 10.07.2025

11AC40SISO_WIFI0_5755




15:49:34 10.07.2025

11AC40SISO_WIFI0_5795



15:50:53 10.07.2025

11AC80SISO_WIFI0_5775




15:59:29 10.07.2025

11AC20MIMO_WIFI0_5745




15:40:02 10.07.2025

11AC20MIMO_WIF11_5745




15:41:10 10.07.2025

11AC20MIMO_WIF10_5785




15:42:47 10.07.2025

11AC20MIMO_WIF11_5785




15:43:55 10.07.2025

11AC20MIMO_WIFI0_5825




15:45:17 10.07.2025

11AC20MIMO_WIFI1_5825




15:46:23 10.07.2025

11AC40MIMO_WIFI0_5755




15:54:33 10.07.2025

11AC40MIMO_WIFI1_5755




15:55:39 10.07.2025

11AC40MIMO_WIFI0_5795




15:56:59 10.07.2025

11AC40MIMO_WIF1_5795




15:58:05 10.07.2025

11AC80MIMO_WIF10_5775



16:04:09 10.07.2025



Conclusion: PASS

A.5. Radiated Unwanted Emission

A.5.1 Limits

Unwanted Emissions in the unrestricted bands shall not exceed the limits that shown in 15.407:

Standard	Limit (dBm/MHz)	
FCC 47 CFR Part 15.407	at the band edge	27
	at 5 MHz above or below the band edge	15.6
	at 25 MHz above or below the band edge	10
	at 75 MHz or more above or below the band edge	-27
	Note: Increasing linearly from point to point.	

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c))

Frequency (MHz)	Field strength(μ V/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30

Frequency of emission (MHz)	Field strength (μ V/m)	Field strength (dBuV/m)	Measurement distance (m)
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Note: When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor (as defined in KDB 789033 II.G.2.d).

A.5.2 Test setup




Figure A.5.1. Test Site Diagram (9kHz-30MHz)




Figure A.5.2. Test Site Diagram (30MHz-1GHz)




Figure A.5.3. Test Site Diagram (1GHz-40GHz)

A.5.3 Test Procedures

Radiated unwanted emissions from the EUT were measured according to ANSI C63.10 and KDB 789033 D02 v02r01.

Test setting

Frequency of emission (MHz)	RBW/VBW
30-1000	100kHz/300kHz
1000-4000	1MHz/3MHz
4000-18000	1MHz/3MHz
18000-26500	1MHz/3MHz
26500-40000	1MHz/3MHz

A.5.4 Calculation

1. The measurement results reported below is calculated by:

Measurement Results (dB μ V/m) = $P_{\text{measurement}}$ (dB μ V) + Cable Loss(dB) + Antenna Factor (dB/m)

Where: $P_{\text{measurement}}$ is the field strength recorded from the instrument

2. Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:

$$E = \text{EIRP} - 20 \log(D) + 104.77$$

Where:

E is the field strength in dB μ V/m

D is the measurement distance in meters

EIRP is the equivalent isotropically radiated power in dBm

Test note

1. The EUT is operating at its maximum duty cycle and its maximum power control level.
2. Investigation has been done on all modes and modulations/data rates. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.
3. Spurious emissions for all channels were investigated and almost the same below 1GHz. According to FCC 47 CFR §15.31, emission levels are not report much lower than the limit by over 20dB
4. The test is carried out on both vertical and horizontal polarization and only maximization result of both polarizations is kept.
5. EUT in each of three orthogonal axis emissions had been tested out only the worst case (axis data) recorded in the report.
6. Measurement frequencies were performed from 9 kHz to the 10th harmonic of highest fundamental frequency or 40GHz, whichever is lower.
7. No spurious emissions were detected within 20dB of the limit below 30MHz. OFS and semi-chamber comparison testing had been performed and the result came out very similar. (KDB 414788)

Note:

A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

P_{Mea} is the field strength recorded from the instrument.

Conclusion: PASS

Average Results:

802.11a

Channel 165

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17918.600	48.52	-25.55	45.40	28.67	54.00	5.48	V
17957.100	48.23	-25.55	45.40	28.38	54.00	5.77	V
14486.050	40.62	-28.78	41.80	27.60	54.00	13.38	H
14475.600	40.52	-28.78	41.80	27.50	54.00	13.48	H
11880.700	37.69	-31.75	39.80	29.64	54.00	16.31	H
11882.900	37.69	-31.75	39.80	29.64	54.00	16.31	V

802.11n-HT20

Channel 165

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17947.200	48.22	-25.55	45.40	28.37	54.00	5.78	V
17941.150	48.10	-25.55	45.40	28.25	54.00	5.90	V
14497.050	40.47	-28.78	41.80	27.45	54.00	13.53	V
14495.950	40.34	-28.78	41.80	27.32	54.00	13.66	V
11886.750	37.65	-31.75	39.80	29.60	54.00	16.35	H
11842.750	37.47	-31.75	39.80	29.42	54.00	16.53	V

802.11n-HT40

Channel 159

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17943.350	48.01	-25.55	45.40	28.16	54.00	5.99	V
17915.850	48.00	-25.55	45.40	28.15	54.00	6.00	H
14495.400	40.50	-28.78	41.80	27.48	54.00	13.50	V
14476.700	40.48	-28.78	41.80	27.46	54.00	13.52	V
11828.450	37.81	-31.84	39.80	29.85	54.00	16.19	V
11870.250	37.56	-31.75	39.80	29.51	54.00	16.44	V

802.11ac-HT20

Channel 165

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17945.000	47.96	-25.55	45.40	28.11	54.00	6.04	H
17926.850	47.90	-25.55	45.40	28.05	54.00	6.10	H
14498.150	40.74	-28.78	41.80	27.72	54.00	13.26	H
14484.950	40.46	-28.78	41.80	27.44	54.00	13.54	V
11820.200	37.52	-31.84	39.80	29.56	54.00	16.48	V
11936.250	37.47	-31.07	39.80	28.74	54.00	16.53	V

802.11ac-HT40

Channel 159

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17944.450	48.24	-25.55	45.40	28.39	54.00	5.76	H
17939.500	48.08	-25.55	45.40	28.23	54.00	5.92	V
14498.150	40.40	-28.78	41.80	27.38	54.00	13.60	H
14475.050	40.39	-28.78	41.80	27.37	54.00	13.61	H
11815.250	37.76	-31.84	39.80	29.80	54.00	16.24	H
11837.250	37.61	-31.75	39.80	29.56	54.00	16.39	H

802.11ac-HT80

Channel 155

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17963.700	48.02	-25.55	45.40	28.17	54.00	5.98	H
17949.950	48.00	-25.55	45.40	28.15	54.00	6.00	H
14493.750	40.94	-28.78	41.80	27.92	54.00	13.06	H
14483.850	40.76	-28.78	41.80	27.74	54.00	13.24	H
11870.800	37.60	-31.75	39.80	29.55	54.00	16.40	H
11819.100	37.54	-31.84	39.80	29.58	54.00	16.46	V

Peak Results:

802.11a

Channel 165

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17958.750	59.82	-25.55	45.40	39.97	74.00	14.18	V
17944.450	59.22	-25.55	45.40	39.37	74.00	14.78	H
14512.450	52.31	-28.78	41.80	39.29	68.20	15.89	H
14620.250	52.23	-28.77	41.70	39.30	68.20	15.97	V
11653.000	48.64	-31.77	39.40	41.01	74.00	25.36	H
11847.150	48.62	-31.75	39.80	40.57	74.00	25.38	H

802.11n-HT20

Channel 165

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17902.100	59.59	-25.55	45.40	39.74	74.00	14.41	H
17954.350	58.87	-25.55	45.40	39.02	74.00	15.13	V
14206.100	52.73	-28.86	41.70	39.89	68.20	15.47	V
14200.050	52.51	-28.86	41.70	39.67	68.20	15.69	H
11824.600	48.66	-31.84	39.80	40.70	74.00	25.34	H
11864.200	48.51	-31.75	39.80	40.46	74.00	25.49	H

802.11n-HT40

Channel 159

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17930.700	58.89	-25.55	45.40	39.04	74.00	15.11	V
17935.650	58.74	-25.55	45.40	38.89	74.00	15.26	H
14291.900	52.58	-28.97	41.70	39.85	68.20	15.62	V
14534.450	52.58	-28.78	41.80	39.56	68.20	15.62	V
11996.750	49.39	-31.07	39.90	40.56	74.00	24.61	V
11814.150	49.13	-31.84	39.80	41.17	74.00	24.87	V

802.11ac-HT20

Channel 165

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17918.050	58.94	-25.55	45.40	39.09	74.00	15.06	V
17925.200	58.93	-25.55	45.40	39.08	74.00	15.07	V
14205.000	52.29	-28.86	41.70	39.45	68.20	15.91	H
14196.750	52.13	-28.86	41.70	39.29	68.20	16.07	V
11856.500	49.58	-31.75	39.80	41.53	74.00	24.42	H
11915.900	49.20	-31.75	39.80	41.15	74.00	24.80	H

802.11ac-HT40

Channel 159

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17926.850	58.99	-25.55	45.40	39.14	74.00	15.01	H
17925.200	58.84	-25.55	45.40	38.99	74.00	15.16	H
14248.450	52.89	-28.86	41.70	40.05	68.20	15.31	V
14200.600	52.64	-28.86	41.70	39.80	68.20	15.56	V
11983.000	49.16	-31.07	39.90	40.33	74.00	24.84	V
11833.950	48.64	-31.75	39.80	40.59	74.00	25.36	V

802.11ac-HT80

Channel 155

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17923.550	59.65	-25.55	45.40	39.80	74.00	14.35	H
17914.750	59.27	-25.55	45.40	39.42	74.00	14.73	H
14158.250	52.84	-28.86	41.80	39.90	68.20	15.36	H
14173.100	52.36	-28.86	41.70	39.52	68.20	15.84	H
11803.150	48.56	-31.84	39.80	40.60	74.00	25.44	V
11785.550	48.50	-31.84	39.80	40.54	74.00	25.50	V

Note: we tested all the antennas and only the worst case show in reported.

Band edge compliance

Mode	Channel	Test Results	Conclusion
802.11a	5745 MHz	Fig.1	P
	5825 MHz	Fig.2	P
802.11n HT20	5745 MHz	Fig.3	P
	5825 MHz	Fig.4	P
802.11n HT40	5755 MHz	Fig.5	P
	5795 MHz	Fig.6	P
802.11ac HT20	5745 MHz	Fig.7	P
	5825 MHz	Fig.8	P
802.11ac HT40	5755 MHz	Fig.9	P
	5795 MHz	Fig.10	P
802.11ac HT80	5775 MHz	Fig.11 Fig.12	P

Note: we tested all the antennas and only the worst case show in reported.

Conclusion: PASS

Test graphs as below:

Conclusion: PASS

Test graphs as below:




Fig. 1 Band Edges (802.11a Ch149,5745MHz)




Fig. 2 Band Edges (802.11a Ch165, 5825MHz)




Fig. 3 Band Edges (802.11n-HT20 Ch149, 5745MHz)




Fig. 4 Band Edges (802.11n-HT20 Ch165, 5825MHz)




Fig. 5 Band Edges (802.11n-HT40 Ch151, 5755MHz)




Fig. 6 Band Edges (802.11n-HT40 Ch159, 5795MHz)




Fig. 7 Band Edges (802.11ac-HT20 Ch149, 5745MHz)




Fig. 8 Band Edges (802.11ac-HT20 Ch165, 5825MHz)




Fig. 9 Band Edges (802.11ac-HT40 Ch151, 5755MHz)




Fig. 10 Band Edges (802.11ac-HT40 Ch159, 5795MHz)




Fig. 11 Band Edges (802.11ac-HT80 Ch155, 5775MHz)




Fig. 12 Band Edges (802.11ac-HT80, 5775MHz)

A.6. AC Powerline Conducted Emission

A.6.1 Summary

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section

A.6.2 Method of Measurement

See Clause 6.2 of ANSI C63.10 specifically.

See Clause 4 and Clause 5 of ANSI C63.10 generally.

The conducted emissions from the AC port of the EUT are measured in a shielding room. The EUT is connected to a Line Impedance Stabilization Network (LISN). An overview sweep with peak detection was performed. The measurements were performed with a quasi-peak detector and if required, an average detector.

The conducted emission measurements were made with the following detector of the test receiver:
Quasi-Peak / Average Detector.


The measurement bandwidth is:

Frequency of Emission (MHz)	RBW/IF bandwidth
0.15-30	9kHz

A.6.3 Test Condition

Voltage (V)	Frequency (Hz)
120	60

A.6.4 Test setup



A.6.5 Measurement Result and limit

Wi-Fi (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dBμV)	Result (dBμV)		Conclusion
		With charger		
		Wi-Fi	Idle	
0.15 to 0.5	66 to 56	Fig.A.6.1	Fig. A.6.2	P
0.5 to 5	56			
5 to 30	60			

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

Wi-Fi (Average Limit)

Frequency range (MHz)	Average Limit (dBμV)	Result (dBμV)		Conclusion
		With charger		
		Wi-Fi	Idle	
0.15 to 0.5	56 to 46	Fig.A.6.1	Fig. A.6.2	P
0.5 to 5	46			
5 to 30	50			

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

Conclusion: Pass

Test graphs as below:




Fig.A.6.1 Conducted Emission(802.11a, Ch149, TX)

Final Result 1

Frequency (MHz)	QuasiPeak (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)	Comment
0.170000	51.4	2000.0	9.000	On	N	19.8	13.6	65.0	
0.258000	43.3	2000.0	9.000	On	N	19.8	18.2	61.5	
0.454000	35.1	2000.0	9.000	On	N	19.9	21.7	56.8	
0.746000	29.7	2000.0	9.000	On	N	19.8	26.3	56.0	
2.062000	26.7	2000.0	9.000	On	L1	19.8	29.3	56.0	
2.398000	27.6	2000.0	9.000	On	N	19.6	28.4	56.0	

Final Result 2

Frequency (MHz)	CAverage (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)	Comment
0.170000	29.4	2000.0	9.000	On	N	19.8	25.5	55.0	
0.286000	22.8	2000.0	9.000	On	N	19.8	27.8	50.6	
0.642000	11.6	2000.0	9.000	On	L1	20.0	34.4	46.0	
1.150000	15.5	2000.0	9.000	On	L1	19.9	30.5	46.0	
2.062000	16.8	2000.0	9.000	On	L1	19.8	29.2	46.0	
2.706000	17.0	2000.0	9.000	On	N	19.6	29.0	46.0	




Fig.A.6.2 Conducted Emission(802.11a, IDLE)

Final Result 1

Frequency (MHz)	QuasiPeak (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)	Comment
0.150000	53.8	2000.0	9.000	On	N	20.1	12.2	66.0	
0.262000	42.4	2000.0	9.000	On	N	19.8	19.0	61.4	
0.506000	33.0	2000.0	9.000	On	N	19.9	23.0	56.0	
0.742000	29.0	2000.0	9.000	On	N	19.8	27.0	56.0	
1.254000	24.3	2000.0	9.000	On	L1	19.9	31.7	56.0	
2.518000	30.4	2000.0	9.000	On	N	19.6	25.6	56.0	

Final Result 2

Frequency (MHz)	CAverage (dBuV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)	Comment
0.150000	33.7	2000.0	9.000	On	N	20.1	22.3	56.0	
0.298000	21.2	2000.0	9.000	On	L1	19.9	29.1	50.3	
0.662000	24.8	2000.0	9.000	On	N	19.8	21.2	46.0	
1.174000	10.9	2000.0	9.000	On	L1	19.9	35.1	46.0	
1.714000	12.3	2000.0	9.000	On	L1	19.8	33.7	46.0	
2.446000	19.3	2000.0	9.000	On	N	19.6	26.7	46.0	

A.7. Antenna Requirement

The antenna of the device is permanently attached. There are no provisions for connection to an external antenna.

The unit complies with the requirement of FCC Part 15.203.

ANNEX B: EUT parameters

Disclaimer: The antenna gain and worse case provided by the client may affect the validity of the measurement results in this report, and the client shall bear the impact and consequences arising therefrom.

ANNEX C: Accreditation Certificate



Accredited Laboratory

A2LA has accredited

TELECOMMUNICATION TECHNOLOGY LABS, CAICT

Beijing, People's Republic of China

for technical competence in the field of

Electrical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 *General requirements for the competence of testing and calibration laboratories*. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).



Presented this 23rd day of July 2024.



Mr. Trace McInturff, Vice President, Accreditation Services
For the Accreditation Council
Certificate Number 7049.01
Valid to July 31, 2026

For the tests to which this accreditation applies, please refer to the laboratory's Electrical Scope of Accreditation.

***** END OF REPORT BODY *****