



FCC PART 15C TEST REPORT No. I16Z40225-SRD05

for

TCL Communication Ltd

**LTE/UMTS/GSM handheld station with
Bluetooth technology, WiFi and FM radio**

5095B

With

FCC ID: 2ACCJH042

Hardware Version: PIO

Software Version: v1K14

Issued Date: 2016-04-19



Note: The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

Test Laboratory:

CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT

No.52, HuayuanNorth Road, Haidian District, Beijing, P. R. China 100191.

Tel: +86(0)10-62304633-2512, Fax: +86(0)10-62304633-2504 Email: cttl_terminals@catr.cn. www.chinattl.com

REPORT HISTORY

Report Number	Revision	Description	Issue Date
I16Z40225-SRD05	Rev.0	1st edition	2016-03-31
I16Z40225-SRD05	Rev.1	2ed edition	2016-04-18
I16Z40225-SRD05	Rev.2	3rd edition	2016-04-19

CONTENTS

CONTENTS	3
1. TEST LATORATORY.....	7
1.1. TESTING LOCATION	7
1.2. PROJECT DATA	7
1.3. SIGNATURE	7
2. CLIENT INFORMATION.....	8
2.1. APPLICANT INFORMATION	8
2.2. MANUFACTURER INFORMATION.....	8
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT(AE)	9
3.1. ABOUT EUT	9
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	9
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	9
3.4. GENERAL DESCRIPTION.....	9
4. REFERENCE DOCUMENTS	10
4.1. DOCUMENTS SUPPLIED BY APPLICANT	10
4.2. REFERENCE DOCUMENTS FOR TESTING.....	10
5. LABORATORY ENVIRONMENT.....	10
6. SUMMARY OF TEST RESULTS	11
6.1. SUMMARY OF TEST RESULTS.....	11
6.2. STATEMENTS.....	11
6.3. TEST CONDITIONS	11
7. TEST EQUIPMENTS UTILIZED	12
ANNEX A: MEASUREMENT RESULTS.....	13
A.1. MEASUREMENT METHOD	13
A.2. MAXIMUM PEAK OUTPUT POWER	14
A.2.1. MAXIMUM PEAK OUTPUT POWER-CONDUCTED	14
A.2.2. MAXIMUM AVERAGE OUTPUT POWER-CONDUCTED	15
A.3. PEAK POWER SPECTRAL DENSITY	16
A.4. OCCUPIED 6dB BANDWIDTH	17
FIG. 1 OCCUPIED 6dB BANDWIDTH (802.11A, CH 149).....	17
FIG. 2 OCCUPIED 6dB BANDWIDTH (802.11A, CH 157).....	18
FIG. 3 OCCUPIED 6dB BANDWIDTH (802.11A, CH 165).....	18
FIG. 4 OCCUPIED 6dB BANDWIDTH (802.11N-HT20, CH 149)	19
FIG. 5 OCCUPIED 6dB BANDWIDTH (802.11N-HT20, CH 157)	19
FIG. 6 OCCUPIED 6dB BANDWIDTH (802.11N-HT20, CH 165)	20

FIG. 7	OCCUPIED 6dB BANDWIDTH (802.11N-HT40, CH 151)	20
FIG. 8	OCCUPIED 6dB BANDWIDTH (802.11N-HT40, CH 159)	21
A.5. TRANSMITTER SPURIOUS EMISSION		22
A.5.1 TRANSMITTER SPURIOUS EMISSION - CONDUCTED		22
FIG. 9	CONDUCTED SPURIOUS EMISSION (802.11A, CH149, 30 MHz-1 GHz).....	24
FIG. 10	CONDUCTED SPURIOUS EMISSION (802.11A, CH149, 1 GHz -12 GHz).....	24
FIG. 11	CONDUCTED SPURIOUS EMISSION (802.11A, CH149, 12 GHz-25 GHz)	24
FIG. 12	CONDUCTED SPURIOUS EMISSION (802.11A, CH149, 25 GHz-40 GHz)	25
FIG. 13	CONDUCTED SPURIOUS EMISSION (802.11A, CH157, 30 MHz-1 GHz).....	25
FIG. 14	CONDUCTED SPURIOUS EMISSION (802.11A, CH157, 1 GHz -12 GHz).....	26
FIG. 15	CONDUCTED SPURIOUS EMISSION (802.11A, CH157, 12 GHz-25 GHz)	26
FIG. 16	CONDUCTED SPURIOUS EMISSION (802.11A, CH157, 25 GHz-40 GHz)	27
FIG. 17	CONDUCTED SPURIOUS EMISSION (802.11A, CH165, 30 MHz-1 GHz).....	27
FIG. 18	CONDUCTED SPURIOUS EMISSION (802.11A, CH165, 1 GHz -12 GHz).....	28
FIG. 19	CONDUCTED SPURIOUS EMISSION (802.11A, CH165, 12 GHz-25 GHz)	28
FIG. 20	CONDUCTED SPURIOUS EMISSION (802.11A, CH165, 25 GHz-40 GHz)	29
FIG. 21	CONDUCTED SPURIOUS EMISSION (802.11N-HT20, CH149, 30 MHz-1 GHz)	29
FIG. 22	CONDUCTED SPURIOUS EMISSION (802.11N-HT20, CH149, 1 GHz -12 GHz)	30
FIG. 23	CONDUCTED SPURIOUS EMISSION (802.11N-HT20, CH149, 12 GHz-25 GHz)	30
FIG. 24	CONDUCTED SPURIOUS EMISSION (802.11N-HT20, CH149, 25 GHz-40 GHz)	31
FIG. 25	CONDUCTED SPURIOUS EMISSION (802.11N-HT20, CH157, 30 MHz-1 GHz)	31
FIG. 26	CONDUCTED SPURIOUS EMISSION (802.11N-HT20, CH157, 1 GHz -12 GHz)	32
FIG. 27	CONDUCTED SPURIOUS EMISSION (802.11N-HT20, CH157, 12 GHz-25 GHz)	32
FIG. 28	CONDUCTED SPURIOUS EMISSION (802.11N-HT20, CH157, 25 GHz-40 GHz)	33
FIG. 29	CONDUCTED SPURIOUS EMISSION (802.11N-HT20, CH165, 30 MHz-1 GHz)	33
FIG. 30	CONDUCTED SPURIOUS EMISSION (802.11N-HT20, CH165, 1 GHz -12 GHz)	34
FIG. 31	CONDUCTED SPURIOUS EMISSION (802.11N-HT20, CH165, 12 GHz-25 GHz)	34
FIG. 32	CONDUCTED SPURIOUS EMISSION (802.11N-HT20, CH165, 25 GHz-40 GHz)	35
FIG. 33	CONDUCTED SPURIOUS EMISSION (802.11N-HT40, CH151, 30 MHz-1 GHz)	35
FIG. 34	CONDUCTED SPURIOUS EMISSION (802.11N-HT40, CH151, 1 GHz -12 GHz)	36
FIG. 35	CONDUCTED SPURIOUS EMISSION (802.11N-HT40, CH151, 12 GHz-25 GHz)	36
FIG. 36	CONDUCTED SPURIOUS EMISSION (802.11N-HT40, CH151, 25 GHz-40 GHz)	37
FIG. 37	CONDUCTED SPURIOUS EMISSION (802.11N-HT40, CH159, 30 MHz-1 GHz)	37
FIG. 38	CONDUCTED SPURIOUS EMISSION (802.11N-HT40, CH159, 1 GHz -12 GHz)	38
FIG. 39	CONDUCTED SPURIOUS EMISSION (802.11N-HT40, CH159, 12 GHz-25 GHz)	38
FIG. 40	CONDUCTED SPURIOUS EMISSION (802.11N-HT40, CH159, 25 GHz-40 GHz)	39
A.5.2 TRANSMITTER SPURIOUS EMISSION - RADIATED		40
FIG. 41	RADIATED SPURIOUS EMISSION (802.11A, CH149, 1 GHz-3 GHz)	43
FIG. 42	RADIATED SPURIOUS EMISSION (802.11A, CH149, 3 GHz-6 GHz)	44
FIG. 43	RADIATED SPURIOUS EMISSION (802.11A, CH149, 6 GHz-18 GHz)	44
FIG. 44	RADIATED SPURIOUS EMISSION (802.11A, CH157, 30 MHz-1 GHz)	45
FIG. 45	RADIATED SPURIOUS EMISSION (802.11A, CH157, 1 GHz-3 GHz)	45
FIG. 46	RADIATED SPURIOUS EMISSION (802.11A, CH157, 3 GHz-6 GHz)	46
FIG. 47	RADIATED SPURIOUS EMISSION (802.11A, CH157, 6 GHz-18 GHz)	46

FIG. 48	RADIATED SPURIOUS EMISSION (802.11A, CH157, 18 GHz-26.5 GHz)	47
FIG. 49	RADIATED EMISSION: 802.11N, (802.11A, CH157, 26.5 GHz - 40 GHz).....	47
FIG. 50	RADIATED SPURIOUS EMISSION (802.11A, CH165, 1 GHz-3 GHz)	48
FIG. 51	RADIATED SPURIOUS EMISSION (802.11A, CH165, 3 GHz-6 GHz)	48
FIG. 52	RADIATED SPURIOUS EMISSION (802.11A, CH165, 6 GHz-18 GHz)	49
FIG. 53	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH149, 1 GHz-3 GHz)	49
FIG. 54	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH149, 3 GHz-6 GHz)	50
FIG. 55	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH149, 6 GHz-18 GHz).....	50
FIG. 56	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH157, 30 MHz-1 GHz).....	51
FIG. 57	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH157, 1 GHz-3 GHz)	51
FIG. 58	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH157, 3 GHz-6 GHz)	52
FIG. 59	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH157, 6 GHz-18 GHz).....	52
FIG. 60	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH157, 18 GHz-26.5 GHz).....	53
FIG. 61	RADIATED EMISSION: 802.11N, (802.11N-HT20, CH157, 26.5 GHz - 40 GHz)	53
FIG. 62	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH165, 1 GHz-3 GHz)	54
FIG. 63	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH165, 3 GHz-6 GHz)	54
FIG. 64	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH165, 6 GHz-18 GHz).....	55
FIG. 65	RADIATED SPURIOUS EMISSION (802.11N-HT40, CH151, 30 MHz-1 GHz).....	55
FIG. 66	RADIATED SPURIOUS EMISSION (802.11N-HT40, CH151, 1 GHz-3 GHz)	56
FIG. 67	RADIATED SPURIOUS EMISSION (802.11N-HT40, CH151, 3 GHz-6 GHz)	56
FIG. 68	RADIATED SPURIOUS EMISSION (802.11N-HT40, CH151, 6 GHz-18 GHz).....	57
FIG. 69	RADIATED SPURIOUS EMISSION (802.11N-HT40, CH151, 18 GHz-26.5 GHz).....	57
FIG. 70	RADIATED EMISSION: 802.11N, (802.11N-HT40, CH151, 26.5 GHz - 40 GHz)	58
FIG. 71	RADIATED SPURIOUS EMISSION (802.11N-HT40, CH159 1 GHz-3 GHz)	58
FIG. 72	RADIATED SPURIOUS EMISSION (802.11N-HT40, CH159 3 GHz-6 GHz)	59
FIG. 73	RADIATED SPURIOUS EMISSION (802.11N-HT40, CH159, 6 GHz-18 GHz).....	59
A.6. BAND EDGES COMPLIANCE		60
A6.1 BAND EDGES - CONDUCTED.....		60
FIG. 74	BAND EDGES (802.11A, 5745MHz)	60
FIG. 75	BAND EDGES (802.11A, 5825MHz)	61
FIG. 76	BAND EDGES (802.11N-HT20, 5745MHz).....	61
FIG. 77	BAND EDGES (802.11N-HT20, 5825MHz).....	62
FIG. 78	BAND EDGES (802.11N-HT40, 5755MHz).....	62
FIG. 79	BAND EDGES (802.11N-HT40, 5795MHz).....	63
A6.2 BAND EDGES - RADIATED.....		63
FIG. 80	BAND EDGES (802.11A, 5745MHz)	64
FIG. 81	BAND EDGES (802.11A, 5825MHz)	64
FIG. 82	BAND EDGES (802.11N-HT20, 5745MHz).....	65
FIG. 83	BAND EDGES (802.11N-HT20, 5825MHz).....	65
FIG. 84	BAND EDGES (802.11N-HT40, 5755MHz).....	66
FIG. 85	BAND EDGES (802.11N-HT40, 5795MHz).....	66
A.7. AC POWERLINE CONDUCTED EMISSION		67
FIG. 86	AC POWERLINE CONDUCTED EMISSION-802.11A	68
FIG. 87	AC POWERLINE CONDUCTED EMISSION-IDLE.....	69



A.8. SPURIOUS EMISSIONS RADIATED < 30MHz.....	70
FIG. 88 RADIATED SPURIOUS EMISSION (802.11A, CH157, 9 kHz ~30 MHz).....	70
ANNEX B: PHOTOGRAPHS OF THE TEST SET-UP	71

1. TEST LABORATORY

1.1. Testing Location

Location 1: CTTL (Huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,
P. R. China 100191

Location 2: CTTL (Shouxiang)

Address: No. 51 Shouxiang Science Building, Xueyuan Road,
Haidian District, Beijing, P. R. China 100191

1.2. Project data

Testing Start Date: 2016-03-01


Testing End Date: 2016-03-15

1.3. Signature




Xu Zhongfei

(Prepared this test report)



Li Zhibin

(Reviewed this test report)



Lv Songdong

(Approved this test report)



2. CLIENT INFORMATION

2.1. Applicant Information

Company Name: TCL Communication Ltd.
Address: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,
Pudong Area Shanghai, P.R. China. 201203
City: Shanghai
Postal Code: 201203
Country: China
Telephone: 0086-21-51798260
Fax: 0086-21-61460602

2.2. Manufacturer Information

Company Name: TCL Communication Ltd.
Address: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,
Pudong Area Shanghai, P.R. China. 201203
City: Shanghai
Postal Code: 201203
Country: China
Telephone: 0086-21-51798260
Fax: 0086-21-61460602

3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT(AE)

3.1. About EUT

Description	LTE/UMTS/GSM handheld station with Bluetooth technology, WiFi and FM radio
Model name	5095B
FCC ID	2ACCJH042
IC ID	/
Type of modulation	OFDM
Antenna	Integral Antenna
Voltage	3.7V DC by Battery

Note: Photographs of EUT are shown in ANNEX C of this test report. Components list, please refer to documents of the manufacturer.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
UT01a	014615000100130	PIO	v1K14
UT02a	014615000100122	PIO	v1K14

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	Type	SN
AE1	Battery	CAC2960001C1	/
AE2	Charger	CBA0061AG0C1	/

*AE ID: is used to identify the test sample in the lab internally.

3.4. General Description

Equipment Under Test (EUT) is a LTE/UMTS/GSM handheld station with Bluetooth technology, WiFi and FM radio with integrated antenna. It consists of normal options: Battery and Charger.

Manual and specifications of the EUT were provided to fulfil the test.

Samples undergoing test were selected by the Client.



4. REFERENCE DOCUMENTS

4.1. Documents supplied by applicant

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

	FCC CFR 47, Part 15, Subpart C:	
	15.205 Restricted bands of operation;	
FCC Part15	15.209 Radiated emission limits, general requirements;	2015
	Subpart E—Unlicensed National Information Infrastructure Devices	
	Methods of Measurement of Radio-Noise Emissions from	
ANSI C63.10	Low-Voltage Electrical and Electronic Equipment in the	2013
	Range of 9 kHz to 40 GHz	

5. LABORATORY ENVIRONMENT

Conducted RF performance testing is performed in shielding room.

EMC performance testing is performed in Semi-anechoic chamber.

6. SUMMARY OF TEST RESULTS

6.1. Summary of Test Results

SUMMARY OF MEASUREMENT RESULTS	Sub-clause of Part15C	Sub-clause of IC	Verdict
Maximum Peak Output Power	15.407 (a)	/	P
Peak Power Spectral Density	15.407 (a)	/	P
Occupied 6dB Bandwidth	15.407(e)	/	P
Band Edges Compliance	15.407 (b)	/	P
Transmitter Spurious Emission - Conducted	15.407,15.205	/	P
Transmitter Spurious Emission - Radiated	15.407, 15.205, 15.209	/	P
AC Powerline Conducted Emission	15.107, 15.207	/	P
99% Occupied Bandwidth	/	/	P
Transmitter Spurious Emission - Radiated < 30MHz	15.407, 15.209	/	P

Please refer to **ANNEX A** for detail.

Terms used in Verdict column

P	Pass, The EUT complies with the essential requirements in the standard.
NM	Not measured, The test was not measured by CTTL
NA	Not Applicable, The test was not applicable
F	Fail, The EUT does not comply with the essential requirements in the standard

6.2. Statements

CTTL has evaluated the test cases requested by the client/manufacture as listed in section 6.1 of this report for the EUT specified in section 3 according to the standards or reference documents listed in section 4.1.

This report only deals with the WLAN function among the features described in section 3.

6.3. Test Conditions

For this report, all the test cases are tested under normal temperature and normal voltage, and also under norm humidity, the specific condition is shown as follows:

Temperature	26°C
Voltage	3.7V
Humidity	44%

7. TEST EQUIPMENTS UTILIZED

8. Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration date	Calibration Due date
1	Vector Signal Analyzer	FSQ40	200089	Rohde & Schwarz	2015-07-08	2016-07-07
2	Test Receiver	ESS	847151/015	Rohde & Schwarz	2015-11-29	2016-11-28
3	LISN	ESH2-Z5	829991/012	Rohde & Schwarz	2015-4-15	2016-4-14
4	Shielding Room	S81	/	ETS-Lindgren	/	/

9. Radiated emission test system


No.	Equipment	Model	Serial Number	Manufacturer	Calibration date	Calibration Due date
1	Test Receiver	ESCI 7	100948	Rohde & Schwarz	2015-07-17	2016-07-16
2	Loop antenna	HFH2-Z2	829324/007	Rohde & Schwarz	2014-12-17	2017-12-16
3	BiLog Antenna	VULB9163	234	Schwarzbeck	2013-09-16	2016-09-15
4	Dual-Ridge Waveguide Horn Antenna	3115	6914	EMCO	2014-12-16	2017-12-15
5	Dual-Ridge Waveguide Horn Antenna	3116	2661	ETS-Lindgren	2014-06-18	2017-06-17
6	Vector Signal Analyzer	FSV	101047	Rohde & Schwarz	2015-07-04	2016-07-03
7	Semi-anechoic chamber	/	CT000332-1074	Frankonia German	/	/

ANNEX A: MEASUREMENT RESULTS

A.1. Measurement Method

A.1.1. Conducted Measurements

- 1). Connect the EUT to the test system correctly.
- 2). Set the EUT to the required work mode.
- 3). Set the EUT to the required channel.
- 4). Set the spectrum analyzer to start measurement.
- 5). Record the values. Vector Signal Analyzer




A.1.2. Radiated Emission Measurements

In the case of radiated emission, the used settings are as follows,

Sweep frequency from 30 MHz to 1GHz, RBW = 100 kHz, VBW = 300 kHz;

Sweep frequency from 1 GHz to 26GHz, RBW = 1MHz, VBW = 10Hz;



The measurement is made according to ANSI C63.10.

The radiated emission test is performed in semi-anechoic chamber. The distance from the EUT to the reference point of measurement antenna is 3m. The test is carried out on both vertical and horizontal polarization and only maximization result of both polarizations is kept. During the test, the turntable is rotated 360° and the measurement antenna is moved from 1m to 4m to get the maximization result.

A.2. Maximum Peak Output Power

Measurement Limit and Method:

Standard	Limit (dBm)
FCC CRF Part 15.407(a)	< 30

A.2.1. Maximum Peak Output Power-conducted

Measurement Results:

802.11a mode

Mode	Data Rate (Mbps)	Test Result (dBm)		
		5745MHz (Ch149)	5785MHz (Ch157)	5825MHz (Ch165)
802.11a	6	14.25	/	/
	9	14.67	/	/
	12	14.87	/	/
	18	14.96	/	/
	24	15.45	/	/
	36	15.54	/	/
	48	15.82	/	/
	54	15.87	14.04	17.41

The data rate 54Mbps is selected as worse condition, and the following cases are performed with this condition.

802.11n-HT20 mode

Mode	Data Rate (Index)	Test Result (dBm)		
		5745MHz (Ch149)	5785MHz (Ch157)	5825MHz (Ch165)
802.11n (20MHz)	MCS0	14.31	/	/
	MCS1	14.29	/	/
	MCS2	14.28	/	/
	MCS3	15.01	/	/
	MCS4	14.97	/	/
	MCS5	14.88	/	/
	MCS6	15.18	/	/
	MCS7	15.21	13.61	16.88

The data rate MCS7 is selected as worse condition, and the following cases are performed with this condition.

802.11n-HT40 mode

Mode	Data Rate (Index)	Test Result (dBm)	
		5755MHz (Ch151)	5795MHz (Ch159)
802.11n (40MHz)	MCS0	13.68	/
	MCS1	13.64	/
	MCS2	12.96	/
	MCS3	14.06	/
	MCS4	13.97	/
	MCS5	13.63	/
	MCS6	14.13	/
	MCS7	14.14	13.98

The data rate MCS7 is selected as worse condition, and the following cases are performed with this condition.

Conclusion: PASS

A.2.2. Maximum Average Output Power-Conducted

Method of Measurement: See ANSI C63.10-clause 12.3.2.2 Method SA-1

802.11a mode

Mode	Test Result (dBm)		
	5745MHz (Ch149)	5785MHz (Ch157)	5825MHz (Ch165)
802.11a	8.64	8.45	9.84

802.11n-HT20 mode

Mode	Test Result (dBm)		
	5745MHz (Ch149)	5785MHz (Ch157)	5825MHz(Ch165)
802.11n(20MHz)	8.03	7.83	9.81

802.11n-HT40 mode

Mode	Test Result (dBm)	
	5755MHz (Ch151)	5795MHz(Ch159)
802.11n(40MHz)	7.12	7.22

Conclusion: PASS

A.3. Peak Power Spectral Density

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.407(a)	< 30 dBm/500 kHz

The measurement is made according to ANSI C63.10 and KDB789033 D02

Measurement Uncertainty:

Measurement Uncertainty	0.75dB
-------------------------	--------

Measurement Results:

Mode	Channel	Power Spectral Density (dBm/500kHz)	Conclusion
802.11a	149	6.94	P
	157	7.18	P
	165	6.83	P
802.11n HT20	149	5.88	P
	157	6.54	P
	165	6.52	P
802.11n HT40	151	4.84	P
	159	4.85	P

Conclusion: PASS

A.4. Occupied 6dB Bandwidth

Measurement Limit:

Standard	Limit (kHz)
FCC 47 CFR Part 15.407(e)	≥ 500

The measurement is made according to KDB789033 D02 .

Measurement Uncertainty:

Measurement Uncertainty	60.80Hz
-------------------------	---------

Measurement Result:

Mode	Channel	Occupied 6dB Bandwidth (kHz)		conclusion
802.11a	149	Fig.1	15950	P
	157	Fig.2	15900	P
	165	Fig.3	16050	P
802.11n HT20	149	Fig.4	17100	P
	157	Fig.5	17400	P
	165	Fig.6	17450	P
802.11n HT40	151	Fig.7	35360	P
	159	Fig.8	35840	P

Conclusion: PASS

Test graphs as below:




Fig. 1 Occupied 6dB Bandwidth (802.11a, Ch 149)




Fig. 2 Occupied 6dB Bandwidth (802.11a, Ch 157)




Fig. 3 Occupied 6dB Bandwidth (802.11a, Ch 165)




Fig. 4 Occupied 6dB Bandwidth (802.11n-HT20, Ch 149)




Fig. 5 Occupied 6dB Bandwidth (802.11n-HT20, Ch 157)




Fig. 6 Occupied 6dB Bandwidth (802.11n-HT20, Ch 165)




Fig. 7 Occupied 6dB Bandwidth (802.11n-HT40, Ch 151)




Fig. 8 Occupied 6dB Bandwidth (802.11n-HT40, Ch 159)

A.5. Transmitter Spurious Emission

Measurement Limit:

Standard	Frequency (MHz)	Limit (dBm/MHz)
FCC 47 CFR Part 15.407	5725MHz~5850MHz	< -27

The measurement is made according to ANSI C63.10 .

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Measurement Uncertainty:

Frequency Range	Uncertainty(dB)
30MHz ≤ f ≤ 2GHz	0.63
2GHz ≤ f ≤ 3.6GHz	0.82
3.6GHz ≤ f ≤ 8GHz	1.55
8GHz ≤ f ≤ 20GHz	1.86
20GHz ≤ f ≤ 22GHz	1.90
22GHz ≤ f ≤ 26GHz	2.20

A.5.1 Transmitter Spurious Emission - Conducted

Measurement Results:

802.11a mode

MODE	Channel	Frequency Range	Test Results	Conclusion
802.11a	149	30 MHz ~ 1 GHz	Fig.9	P
		1 GHz ~ 12 GHz	Fig.10	P
		12 GHz ~ 25 GHz	Fig.11	P
		25 GHz ~ 40 GHz	Fig.12	P
	157	30 MHz ~ 1 GHz	Fig.13	P
		1 GHz ~ 12 GHz	Fig.14	P
		12 GHz ~ 25 GHz	Fig.15	P
		25 GHz ~ 40 GHz	Fig.16	P
	165	30 MHz ~ 1 GHz	Fig.17	P
		1 GHz ~ 12 GHz	Fig.18	P
		12 GHz ~ 25 GHz	Fig.19	P
		25 GHz ~ 40 GHz	Fig.20	P

802.11n-HT20 mode

MODE	Channel	Frequency Range	Test Results	Conclusion
802.11n HT20	149	30 MHz ~ 1 GHz	Fig.21	P
		1 GHz ~ 12 GHz	Fig.22	P
		12 GHz ~ 25 GHz	Fig.23	P
		25 GHz ~ 40 GHz	Fig.24	P
	157	30 MHz ~ 1 GHz	Fig.25	P
		1 GHz ~ 12 GHz	Fig.26	P
		12 GHz ~ 25 GHz	Fig.27	P
		25 GHz ~ 40 GHz	Fig.28	P
	165	30 MHz ~ 1 GHz	Fig.29	P
		1 GHz ~ 12 GHz	Fig.30	P
		12 GHz ~ 25 GHz	Fig.31	P
		25 GHz ~ 40 GHz	Fig.32	P

802.11n-HT40 mode

MODE	Channel	Frequency Range	Test Results	Conclusion
802.11n HT40	151	30 MHz ~ 1 GHz	Fig.33	P
		1 GHz ~ 12 GHz	Fig.34	P
		12 GHz ~ 25 GHz	Fig.35	P
		25 GHz ~ 40 GHz	Fig.36	P
	159	30 MHz ~ 1 GHz	Fig.37	P
		1 GHz ~ 12 GHz	Fig.38	P
		12 GHz ~ 25 GHz	Fig.39	P
		25 GHz ~ 40 GHz	Fig.40	P

Conclusion: PASS

Test graphs as below:




Fig. 9 Conducted Spurious Emission (802.11a, Ch149, 30 MHz-1 GHz)




Fig. 10 Conducted Spurious Emission (802.11a, Ch149, 1 GHz -12 GHz)




Fig. 11 Conducted Spurious Emission (802.11a, Ch149, 12 GHz-25 GHz)




Fig. 12 Conducted Spurious Emission (802.11a, Ch149, 25 GHz-40 GHz)




Fig. 13 Conducted Spurious Emission (802.11a, Ch157, 30 MHz-1 GHz)




Fig. 14 Conducted Spurious Emission (802.11a, Ch157, 1 GHz -12 GHz)




Fig. 15 Conducted Spurious Emission (802.11a, Ch157, 12 GHz-25 GHz)




Fig. 16 Conducted Spurious Emission (802.11a, Ch157, 25 GHz-40 GHz)




Fig. 17 Conducted Spurious Emission (802.11a, Ch165, 30 MHz-1 GHz)




Fig. 18 Conducted Spurious Emission (802.11a, Ch165, 1 GHz -12 GHz)




Fig. 19 Conducted Spurious Emission (802.11a, Ch165, 12 GHz-25 GHz)




Fig. 20 Conducted Spurious Emission (802.11a, Ch165, 25 GHz-40 GHz)




Fig. 21 Conducted Spurious Emission (802.11n-HT20, Ch149, 30 MHz-1 GHz)




Fig. 22 Conducted Spurious Emission (802.11n-HT20, Ch149, 1 GHz -12 GHz)




Fig. 23 Conducted Spurious Emission (802.11n-HT20, Ch149, 12 GHz-25 GHz)




Fig. 24 Conducted Spurious Emission (802.11n-HT20, Ch149, 25 GHz-40 GHz)




Fig. 25 Conducted Spurious Emission (802.11n-HT20, Ch157, 30 MHz-1 GHz)




Fig. 26 Conducted Spurious Emission (802.11n-HT20, Ch157, 1 GHz -12 GHz)




Fig. 27 Conducted Spurious Emission (802.11n-HT20, Ch157, 12 GHz-25 GHz)




Fig. 28 Conducted Spurious Emission (802.11n-HT20, Ch157, 25 GHz-40 GHz)




Fig. 29 Conducted Spurious Emission (802.11n-HT20, Ch165, 30 MHz-1 GHz)




Fig. 30 Conducted Spurious Emission (802.11n-HT20, Ch165, 1 GHz -12 GHz)




Fig. 31 Conducted Spurious Emission (802.11n-HT20, Ch165, 12 GHz-25 GHz)




Fig. 32 Conducted Spurious Emission (802.11n-HT20, Ch165, 25 GHz-40 GHz)




Fig. 33 Conducted Spurious Emission (802.11n-HT40, Ch151, 30 MHz-1 GHz)




Fig. 34 Conducted Spurious Emission (802.11n-HT40, Ch151, 1 GHz -12 GHz)




Fig. 35 Conducted Spurious Emission (802.11n-HT40, Ch151, 12 GHz-25 GHz)