



TEST REPORT

No. I16Z40225-EMC01

for

TCL Communication Ltd

LTE/UMTS/GSM handheld station with Bluetooth technology, WiFi

and FM radio

Model Name: 5095B

FCC ID: 2ACCJH042

with

Hardware Version: P10

Software Version: v1K14

Issued Date: 2016-04-14

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

Test Laboratory:

FCC 2.948 Listed: No.525429

CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel: +86(0)10-62304633-2512, Fax: +86(0)10-62304633-2504

Email: ctl_terminals@catr.cn, website: www.chinattl.com

REPORT HISTORY

Report Number	Revision	Description	Issue Date
I16Z40225-EMC01	Rev.0	1 st edition	2016-03-25
I16Z40225-EMC01	Rev.1	2 nd edition	2016-04-14

CONTENTS

1. TEST LABORATORY	4
1.1. TESTING LOCATION	4
1.2. TESTING ENVIRONMENT	4
1.3. PROJECT DATA	4
1.4. SIGNATURE	4
2. CLIENT INFORMATION	5
2.1. APPLICANT INFORMATION	5
2.2. MANUFACTURER INFORMATION	5
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	6
3.1. ABOUT EUT	6
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	6
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	6
3.4. EUT SET-UPS	8
4. REFERENCE DOCUMENTS	9
4.1. REFERENCE DOCUMENTS FOR TESTING	9
5. LABORATORY ENVIRONMENT	10
6. SUMMARY OF TEST RESULTS	11
7. TEST EQUIPMENTS UTILIZED	12
ANNEX A: MEASUREMENT RESULTS	13

1. Test Laboratory

1.1. Testing Location

Location 1: CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China
100191


1.2. Testing Environment

Normal Temperature: 15-35°C
Relative Humidity: 20-75%

1.3. Project data

Testing Start Date: 2016-03-14
Testing End Date: 2016-03-18


1.4. Signature



Wang Junqing
(Prepared this test report)



Qu Pengfei
(Reviewed this test report)



Liu Baodian
Deputy Director of the laboratory
(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: TCL Communication Ltd
Address /Post: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,
Pudong Area Shanghai, P.R. China. 201203
City: Shanghai
Postal Code: 201203
Country: P. R. China
Contact Person: Gong Zhizhou
Contact Email: zhizhou.gong@tcl.com
Telephone: 0086-21-51798260
Fax: 0086-21-61460602

2.2. Manufacturer Information

Company Name: TCL Communication Ltd
Address /Post: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,
Pudong Area Shanghai, P.R. China. 201203
City: Shanghai
Postal Code: 201203
Country: P. R. China
Telephone: 0086-21-51798260
Fax: 0086-21-61460602

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	LTE/UMTS/GSM handheld station with Bluetooth technology, WiFi and FM radio
Model Name	5095B
FCC ID	2ACCJH042
Extreme vol. Limits	3.5VDC to 4.2VDC (nominal: 3.7VDC)

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
EUT1	014615000100148	PIO	v1K14

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	SN	Remarks
AE1	Battery	/	inbulit
AE2	Battery	/	inbulit
AE3	USB cable	/	14TCT-DC-0826
AE4	USB cable	/	16TCT-DC-0085
AE7	Travel charger	/	16TCT-CH-0417
AE8	Travel charger	/	/
AE1			
	Model	CAC2960001C1	
	Manufacturer	BYD	
	Capacitance	2960mAh	
	Nominal voltage	3.84V	
AE2			
	Model	CAC2960003C2	
	Manufacturer	SCUD	
	Capacitance	2960mAh	
	Nominal voltage	3.84V	

AE3

Model CDA0000024C2
Manufacturer JUWEI
Length of cable 75cm

AE4

Model CDA0000024C8
Manufacturer PUAN
Length of cable 75cm

AE7

Model CBA0061AG0C1
Manufacturer BYD
Length of cable /

AE8

Model CBA0061AG0C2
Manufacturer Tenpao
Length of cable /

*AE ID: is used to identify the test sample in the lab internally.

Note: The USB cables are shielded.

3.4. EUT set-ups

EUT set-up No.	Combination of EUT and AE	Remarks
Set.1	EUT1+ AE1 + AE7+ AE3/AE4	Charger
Set.2	EUT1+ AE1 + AE8+ AE3/AE4	Charger
Set.3	EUT1+ AE1 + AE3	USB mode
Set.4	EUT1+ AE1 + AE4	USB mode

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 15, Subpart B	Radio frequency devices - Unintentional Radiators	2015
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low - Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2014

5. LABORATORY ENVIRONMENT

Semi-anechoic chamber SAC-1 (23 meters×17meters×10meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 15 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz, >60dB; 1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 M
Ground system resistance	< 4
Normalised site attenuation (NSA)	< ±4 dB, 10 m distance
Site voltage standing-wave ratio (S_{VSWR})	Between 0 and 6 dB, from 1GHz to 6GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

Shielded room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz, >60dB; 1MHz – 1000MHz, >90dB.
Electrical insulation	> 2 M
Ground system resistance	< 4

6. SUMMARY OF TEST RESULTS

Abbreviations used in this clause:				
Verdict Column	P	Pass		
	NA	Not applicable		
	F	Fail		
Location Column	A/B/C/D	The test is performed in test location A, B, C or D which are described in section 1.1 of this report		

Items	Test Name	Clause in FCC rules	Clause in IC rules	Section in this report	Verdict	Test Location
1	Radiated Emission	15.109(a)	Section 5	B.1	P	A
2	Conducted Emission	15.107(a)	Section 5	B.2	P	A

7. Test Equipments Utilized

NO.	Description	TYPE	SERIES NUMBER	MANUFACTUR E	CAL DUE DATE	CALIBRATI ON INTERVAL
1	Test Receiver	ESU26	100235	R&S	2017-03-02	1 year
2	Universal Radio Communication Tester	CMU200	109914	R&S	2016-03-26	1 year
3	Universal Radio Communication Tester	CMW500	143008	R&S	2016-12-09	1 year
4	LISN	ENV216	101200	R&S	2016-07-07	1 year
5	EMI Antenna	VULB 9163	9163-514	Schwarzbeck	2017-11-24	3 years
6	EMI Antenna	3115	6914	ETS-Lindgren	2016-12-15	3 years
7	PC	OPTIPLEX 380	2X1YV2X	DELL	N/A	N/A
8	Printer	P1606dn	VNC3L52122	HP	N/A	N/A
9	Keyboard	L100	CN0RH6596589 07ATOI40	DELL	N/A	N/A
10	Mouse	M-UAE119	LZ935220ZRC	Lenovo	N/A	N/A

ANNEX A: MEASUREMENT RESULTS

A.1 Radiated Emission

Reference

FCC: CFR Part 15.109(a).

A.1.1 Method of measurement

The field strength of radiated emissions from the unintentional radiator (USB mode of MS and charging mode of MS) at distances of 10 meters(for 30MHz-1GHz) and 3 meters (for above 1GHz) is tested. Tested in accordance with the procedures of ANSI C63.4 – 2014, section 8.3.

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3/10 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

A.1.2 EUT Operating Mode:

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is DELL OPTIPLEX 380, and the serial number of the PC is 2X1YV2X. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

Note: I/O information: Printer – USB, Mouse – PS/2, Keyboard – USB.

A.1.3 Measurement Limit

Frequency range (MHz)	Field strength limit (μ V/m)		
	Quasi-peak	Average	Peak
30-88	100		
88-216	150		
216-960	200		
960-1000	500		
>1000		500	5000

Note: the above limit is for 3 meters test distance. 10 meters' limit is got by converting.

A.1.4 Test Condition

Frequency range (MHz)	RBW/VBW	Sweep Time (s)	Detector
30-1000	120kHz (IF Bandwidth)	5	Peak/Quasi-peak
Above 1000	1MHz/1MHz	15	Peak, Average

A.1.5 Measurement Results

A "reference path loss" is established and the A_{RPL} is the attenuation of "reference path loss". It includes the antenna factor of receive antenna and the path loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{Mea}} + A_{RPL} = P_{\text{Mea}} + G_A + G_{PL}$$

Where

G_A : Antenna factor of receive antenna

G_{PL} : Path Loss

P_{Mea} : Measurement result on receiver.

Measurement uncertainty (worst case): $U = 4.3 \text{ dB}$, $k=2$.

Measurement results for Set.1:

Charging Mode/Average detector

Frequency(MHz)	Result(dB μ V/m)	G_{PL} (dB)	G_A (dB/m)	P_{Mea} (dB μ V)	Polarity
17949.850	51.3	-17.7	45.6	23.400	HORIZONTAL
17926.900	50.9	-17.7	45.6	23.000	HORIZONTAL
17972.800	50.7	-17.7	45.6	22.800	VERTICAL
17901.400	50.7	-18.5	45.6	23.600	HORIZONTAL
17983.850	50.5	-17.7	45.6	22.600	HORIZONTAL
17909.050	50.4	-18.5	45.6	23.300	VERTICAL

Charging Mode/Peak detector

Frequency(MHz)	Result(dB μ V/m)	G_{PL} (dB)	G_A (dB/m)	P_{Mea} (dB μ V)	Polarity
17919.250	61.1	-17.7	45.6	33.200	HORIZONTAL
17856.350	61.0	-18.5	45.6	33.900	VERTICAL
17092.200	61.0	-19.8	41.5	39.300	HORIZONTAL
17827.450	60.8	-18.5	45.6	33.700	VERTICAL
17977.900	60.8	-17.7	45.6	32.900	VERTICAL
17975.350	60.8	-17.7	45.6	32.900	HORIZONTAL

Measurement results for Set.2:
Charging Mode/Average detector

Frequency(MHz)	Result(dB μ V/m)	G _{PL} (dB)	G _A (dB/m)	P _{Mea} (dB μ V)	Polarity
17942.200	50.9	-17.7	45.6	23.000	VERTICAL
17974.500	50.9	-17.7	45.6	23.000	HORIZONTAL
17939.650	50.7	-17.7	45.6	22.800	HORIZONTAL
17897.150	50.6	-18.5	45.6	23.500	HORIZONTAL
17933.700	50.5	-17.7	45.6	22.600	VERTICAL
17997.450	50.4	-17.7	45.6	22.500	VERTICAL

Charging Mode/Peak detector

Frequency(MHz)	Result(dB μ V/m)	G _{PL} (dB)	G _A (dB/m)	P _{Mea} (dB μ V)	Polarity
17977.900	61.5	-17.7	45.6	33.600	HORIZONTAL
17870.800	61.2	-18.5	45.6	34.100	HORIZONTAL
17997.450	60.9	-17.7	45.6	33.000	VERTICAL
17959.200	60.6	-17.7	45.6	32.700	VERTICAL
17791.750	60.5	-18.5	45.6	33.400	VERTICAL
17816.400	60.4	-18.5	45.6	33.300	HORIZONTAL

Measurement results for Set.3:
USB Mode/Average detector

Frequency(MHz)	Result(dB μ V/m)	G _{PL} (dB)	G _A (dB/m)	P _{Mea} (dB μ V)	Polarity
17908.200	50.8	-18.5	45.6	23.700	VERTICAL
17949.000	50.7	-17.7	45.6	22.800	HORIZONTAL
17921.800	50.7	-17.7	45.6	22.800	HORIZONTAL
17965.150	50.5	-17.7	45.6	22.600	VERTICAL
17916.700	50.5	-17.7	45.6	22.600	HORIZONTAL
17960.050	50.4	-17.7	45.6	22.500	HORIZONTAL

USB Mode/Average detector

Frequency(MHz)	Result(dB μ V/m)	G _{PL} (dB)	G _A (dB/m)	P _{Mea} (dB μ V)	Polarity
17456.850	61.2	-19.2	41.5	38.900	HORIZONTAL
17964.300	60.9	-17.7	45.6	33.000	VERTICAL
17842.750	60.7	-18.5	45.6	33.600	HORIZONTAL
17784.950	60.7	-18.5	45.6	33.600	HORIZONTAL
17949.000	60.6	-17.7	45.6	32.700	VERTICAL
17865.700	60.6	-18.5	45.6	33.500	VERTICAL



Measurement results for Set.4:**USB Mode/Average detector**

Frequency(MHz)	Result(dB μ V/m)	G _{PL} (dB)	G _A (dB/m)	P _{Mea} (dB μ V)	Polarity
17944.750	51.0	-17.7	45.6	23.100	HORIZONTAL
17991.500	50.9	-17.7	45.6	23.000	VERTICAL
17940.500	50.8	-17.7	45.6	22.900	HORIZONTAL
17992.350	50.6	-17.7	45.6	22.700	VERTICAL
17926.050	50.6	-17.7	45.6	22.700	VERTICAL
17916.700	50.5	-17.7	45.6	22.600	HORIZONTAL

USB Mode/Average detector


Frequency(MHz)	Result(dB μ V/m)	G _{PL} (dB)	G _A (dB/m)	P _{Mea} (dB μ V)	Polarity
17825.750	61.0	-18.5	45.6	33.900	HORIZONTAL
17941.350	60.7	-17.7	45.6	32.800	HORIZONTAL
17962.600	60.5	-17.7	45.6	32.600	VERTICAL
17996.600	60.5	-17.7	45.6	32.600	HORIZONTAL
17776.450	60.5	-18.5	45.6	33.400	VERTICAL
17754.350	60.4	-18.5	45.6	33.300	VERTICAL

Note: The measurement results of Set.1, Set.2, Set.3 and Set.4 showed here are worst cases of the combinations of different batteries and USB cables.


Charging Mode, Set.1**Figure A.1 Radiated Emission from 30MHz to 1GHz****Figure A.2 Radiated Emission from 1GHz to 18GHz**

Charging Mode, Set.2

Normal RE_30M-1GHz_10m


**Figure A.3 Radiated Emission from 30MHz to 1GHz**

Normal RE_1G-18GHz

**Figure A.4 Radiated Emission from 1GHz to 18GHz**


USB Mode, Set.3

Normal RE_30M-1GHz_10m


Figure A.5 Radiated Emission from 30MHz to 1GHz
Final Result 1


Frequency (MHz)	QuasiPeak (dB μ V/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)
31.164000	27.2	113.0	V	270.0	-13.9	2.8	30.0

Normal RE_1G-18GHz


Figure A.6 Radiated Emission from 1GHz to 18GHz


USB Mode, Set.4

Normal RE_30M-1GHz_10m


Figure A.7 Radiated Emission from 30MHz to 1GHz
Final Result 1

Frequency (MHz)	QuasiPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
31.455000	29.2	107.0	V	23.0	-13.9	0.8	30.0
33.150000	28.3	175.0	V	15.0	-13.6	1.7	30.0
33.215000	29.9	125.0	V	30.0	-13.5	0.1	30.0

Normal RE_1G-18GHz


Figure A.8 Radiated Emission from 1GHz to 18GHz

A.2 Conducted Emission

Reference

FCC: CFR Part 15.107(a).

A.2.1 Method of measurement

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits. Tested in accordance with the procedures of ANSI C63.4 – 2014, section 7.3.

A.2.2 EUT Operating Mode

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is DELL OPTIPLEX 380, and the serial number of the PC is 2X1YV2X. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

Note: I/O information: Printer – USB, Mouse – PS/2, Keyboard – USB.

A.2.3 Measurement Limit

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency

A.2.4 Test Condition in charging mode

Voltage (V)	Frequency (Hz)
120	60

RBW/IF bandwidth	Sweep Time(s)
9kHz	1

A.2.5 Measurement Results

Measurement uncertainty: $U = 2.9 \text{ dB}$, $k=2$.

Charging Mode, Set.1




Figure A.9 Conducted Emission


Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time(ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.159000	62.6	2000.0	9.000	On	L1	19.9	2.9	65.5
0.289500	55.3	2000.0	9.000	On	N	19.8	5.3	60.5
0.465000	49.6	2000.0	9.000	On	N	19.9	7.0	56.6
0.762000	48.9	2000.0	9.000	On	N	19.8	7.1	56.0
1.257000	40.7	2000.0	9.000	On	N	19.7	15.3	56.0
14.212500	42.8	2000.0	9.000	On	N	19.9	17.2	60.0

Final Result 2

Frequency (MHz)	CAverage (dBµV)	Meas. Time(ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.208500	36.9	2000.0	9.000	On	L1	19.8	16.4	53.3
0.271500	34.0	2000.0	9.000	On	N	19.8	17.1	51.1
0.654000	35.3	2000.0	9.000	On	N	19.8	10.7	46.0
0.784500	30.0	2000.0	9.000	On	N	19.8	16.0	46.0
1.963500	19.5	2000.0	9.000	On	N	19.7	26.5	46.0
15.720000	32.6	2000.0	9.000	On	L1	20.0	17.4	50.0

Note: The measurement results showed here are worst cases of the combinations of different batteries and USB cables.


Charging Mode, Set.2

Figure A.10 Conducted Emission
Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time(ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.208500	47.7	2000.0	9.000	On	L1	19.8	15.5	63.3
0.271500	44.7	2000.0	9.000	On	L1	19.8	16.3	61.1
0.460500	38.6	2000.0	9.000	On	L1	19.9	18.1	56.7
0.883500	41.8	2000.0	9.000	On	N	19.8	14.2	56.0
2.854500	40.4	2000.0	9.000	On	L1	18.9	15.6	56.0
4.636500	38.2	2000.0	9.000	On	N	19.6	17.8	56.0

Final Result 2

Frequency (MHz)	CAverage (dBµV)	Meas. Time(ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.208500	34.1	2000.0	9.000	On	L1	19.8	19.2	53.3
0.271500	32.9	2000.0	9.000	On	L1	19.8	18.2	51.1
0.667500	38.5	2000.0	9.000	On	N	19.8	7.5	46.0
0.798000	31.7	2000.0	9.000	On	N	19.8	14.3	46.0
17.389500	34.4	2000.0	9.000	On	L1	20.0	15.6	50.0
18.186000	37.9	2000.0	9.000	On	L1	19.9	12.1	50.0

Note: The measurement results showed here are worst cases of the combinations of different batteries and USB cables.


USB Mode, Set.3

Figure A.11 Conducted Emission
Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time(ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.213000	45.9	2000.0	9.000	On	N	19.8	17.2	63.1
0.424500	39.0	2000.0	9.000	On	N	19.9	18.4	57.4
0.559500	43.7	2000.0	9.000	On	L1	19.9	12.3	56.0
0.811500	37.0	2000.0	9.000	On	N	19.8	19.0	56.0
1.990500	36.7	2000.0	9.000	On	N	19.7	19.3	56.0
23.977500	42.5	2000.0	9.000	On	L1	20.0	17.5	60.0

Final Result 2

Frequency (MHz)	CAverage (dBµV)	Meas. Time(ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.177000	46.2	2000.0	9.000	On	N	19.8	8.4	54.6
0.276000	37.7	2000.0	9.000	On	N	19.8	13.2	50.9
0.555000	36.1	2000.0	9.000	On	L1	19.9	9.9	46.0
1.990500	30.7	2000.0	9.000	On	N	19.7	15.3	46.0
4.875000	29.6	2000.0	9.000	On	N	19.6	16.4	46.0
23.977500	42.7	2000.0	9.000	On	N	20.1	7.3	50.0

Note: The measurement results showed here are worst cases of the combinations of different batteries and USB cables.

USB Mode, Set.4

Figure A.12 Conducted Emission
Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time(ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	44.7	2000.0	9.000	On	L1	20.2	21.3	66.0
0.424500	39.6	2000.0	9.000	On	L1	19.9	17.8	57.4
0.559500	43.6	2000.0	9.000	On	L1	19.9	12.4	56.0
1.990500	36.2	2000.0	9.000	On	N	19.7	19.8	56.0
9.141000	23.3	2000.0	9.000	On	N	19.7	36.7	60.0
23.977500	42.0	2000.0	9.000	On	L1	20.0	18.0	60.0

Final Result 2

Frequency (MHz)	CAverage (dBµV)	Meas. Time(ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.177000	46.2	2000.0	9.000	On	N	19.8	8.5	54.6
0.276000	37.7	2000.0	9.000	On	N	19.8	13.2	50.9
0.555000	36.1	2000.0	9.000	On	L1	19.9	9.9	46.0
1.986000	30.6	2000.0	9.000	On	N	19.7	15.4	46.0
4.402500	30.4	2000.0	9.000	On	N	19.6	15.6	46.0
23.977500	42.4	2000.0	9.000	On	N	20.1	7.6	50.0

Note: The measurement results showed here are worst cases of the combinations of different batteries and USB cables.

*****END OF REPORT*****