



# FCC PART 15C TEST REPORT

**BLUETOOTH LOW ENERGY (BLE) PART**

**No. I16Z41709-SRD03**

**for**

**TCL Communication Ltd.**

**LTE / UMTS / GSM mobile phone**

**Model Name: 5080A**

**FCC ID: 2ACCJH059**

**with**

**Hardware Version: PIO**

**Software Version: 2CA6**

**Issued Date: 2016-8-30**



**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

**Test Laboratory:**

CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT.  
No.52, HuayuanNorth Road, Haidian District, Beijing, P. R. China 100191.

Tel: +86(0)10-62304633-2512, Fax: +86(0)10-62304633-2504

Email: [ctl\\_terminals@catr.cn](mailto:ctl_terminals@catr.cn), website: [www.chinattl.com](http://www.chinattl.com)



## **REPORT HISTORY**

<b>Report Number</b>	<b>Revision</b>	<b>Description</b>	<b>Issue Date</b>
I16Z41709-SRD03	Rev.0	1st edition	2016-8-30

## **CONTENTS**

<b>1. TEST LABORATORY .....</b>	<b>4</b>
<b>1.1. TESTING LOCATION .....</b>	<b>4</b>
<b>1.2. TESTING ENVIRONMENT .....</b>	<b>4</b>
<b>1.3. PROJECT DATA .....</b>	<b>4</b>
<b>1.4. SIGNATURE.....</b>	<b>4</b>
<b>2. CLIENT INFORMATION.....</b>	<b>5</b>
<b>2.1. APPLICANT INFORMATION.....</b>	<b>5</b>
<b>2.2. MANUFACTURER INFORMATION.....</b>	<b>5</b>
<b>3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....</b>	<b>6</b>
<b>3.1. ABOUT EUT .....</b>	<b>6</b>
<b>3.2. INTERNAL IDENTIFICATION OF EUT .....</b>	<b>6</b>
<b>3.3. INTERNAL IDENTIFICATION OF AE .....</b>	<b>6</b>
<b>3.4. NORMAL ACCESSORY SETTING .....</b>	<b>8</b>
<b>3.5. GENERAL DESCRIPTION.....</b>	<b>8</b>
<b>4. REFERENCE DOCUMENTS .....</b>	<b>9</b>
<b>4.1. DOCUMENTS SUPPLIED BY APPLICANT .....</b>	<b>9</b>
<b>4.2. REFERENCE DOCUMENTS FOR TESTING.....</b>	<b>9</b>
<b>5. TEST RESULTS .....</b>	<b>10</b>
<b>5.1. SUMMARY OF TEST RESULTS.....</b>	<b>10</b>
<b>5.2. STATEMENTS.....</b>	<b>10</b>
<b>6. TEST FACILITIES UTILIZED .....</b>	<b>11</b>
<b>ANNEX A: DETAILED TEST RESULTS.....</b>	<b>12</b>
<b>A.1. MEASUREMENT METHOD .....</b>	<b>12</b>
<b>A.2. PEAK OUTPUT POWER - CONDUCTED .....</b>	<b>13</b>
<b>A.3. FREQUENCY BAND EDGES - CONDUCTED.....</b>	<b>14</b>
<b>A.4. TRANSMITTER SPURIOUS EMISSION - CONDUCTED .....</b>	<b>16</b>
<b>A.5. TRANSMITTER SPURIOUS EMISSION - RADIATED .....</b>	<b>25</b>
<b>A.6. 6dB BANDWIDTH.....</b>	<b>34</b>
<b>A.7. MAXIMUM POWER SPECTRAL DENSITY LEVEL .....</b>	<b>37</b>
<b>A.8. AC POWERLINE CONDUCTED EMISSION.....</b>	<b>40</b>
<b>ANNEX B: ACCREDITATION CERTIFICATE.....</b>	<b>47</b>

## 1. Test Laboratory

### 1.1. Testing Location

Location 1:CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,  
P. R. China100191

Location 2: CTTL(BDA)

Address: No.18A, Kangding Street, Beijing Economic-Technology  
Development Area, Beijing, P. R. China 100176

Location 3:CTTL(Shouxiang)

Address: No. 51 Shouxiang Science Building, Xueyuan Road,  
Haidian District, Beijing, P. R. China100191

### 1.2. Testing Environment

Normal Temperature: 15-35°C

Extreme Temperature: -10/+55°C

Relative Humidity: 20-75%

### 1.3. Project data

Testing Start Date: 2016-8-4


Testing End Date: 2016-8-30

### 1.4. Signature




Sun Zhenyu

(Prepared this test report)



Li Zhuofang

(Reviewed this test report)



Lv Songdong

(Approved this test report)



## **2. Client Information**

### **2.1. Applicant Information**

Company Name: TCL Communication Ltd.  
Address /Post: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,  
Pudong Area Shanghai, P.R. China. 201203  
City: Shanghai  
Postal Code: 201203  
Country: China  
Telephone: 0086-21-31363544  
Fax: 0086-21-61460602

### **2.2. Manufacturer Information**

Company Name: TCL Communication Ltd.  
Address /Post: 5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park,  
Pudong Area Shanghai, P.R. China. 201203  
City: Shanghai  
Postal Code: 201203  
Country: China  
Telephone: 0086-21-31363544  
Fax: 0086-21-61460602

### **3. Equipment Under Test (EUT) and Ancillary Equipment (AE)**

#### **3.1. About EUT**

Description	LTE / UMTS / GSM mobile phone
Model Name	5080A
FCC ID	2ACCJH059
Frequency Band	ISM 2400MHz~2483.5MHz
Type of Modulation(LE mode)	GFSK (Bluetooth Low Energy)
Number of Channels(LE mode)	40
Power Supply	3.8V DC by Battery

#### **3.2. Internal Identification of EUT**

<b>EUT ID*</b>	<b>SN or IMEI</b>	<b>HW Version</b>	<b>SW Version</b>
EUT1	014726000000558	PIO	2CA6
EUT2	014726000000434	PIO	2CA6

\*EUT ID: is used to identify the test sample in the lab internally.

#### **3.3. Internal Identification of AE**

<b>AE ID*</b>	<b>Description</b>		
AE1	battery	/	/
AE2	battery	/	/
AE3	battery	/	/
AE4	battery	/	/
AE5	Travel charger	/	16TCT-CH-0881
AE6	Travel charger	/	16TCT-CH-0885
AE7	Travel charger	/	16TCT-CH-0803
AE8	Travel charger	/	16TCT-CH-0860
AE9	USB cable	/	16TCT-DC-0373
AE10	USB cable	/	16TCT-CH-0884
AE11	USB cable	/	16TCT-DC-0394
AE12	USB cable	/	16TCT-DC-0419
AE13	Travel charger	/	16TCT-CH-0875
AE14	Travel charger	/	/
AE15	Travel charger	/	19TCT-CH-0615
AE16	Travel charger	/	16TCT-CH-0846
AE17	USB cable	/	16TCT-DC-0377
AE18	USB cable	/	16TCT-DC-0393
AE19	USB cable	/	16TCT-DC-0415
AE20	USB cable	/	/

AE1

Model CAC2400006CJ  
Manufacturer Coslight  
Capacitance 2400 mAh  
Nominal voltage 3.85V

AE2

Model CAC2400008C1  
Manufacturer BYD  
Capacitance 2400 mAh  
Nominal voltage 3.85V

AE3

Model CAC2400007C2  
Manufacturer SCUD  
Capacitance 2400 mAh  
Nominal voltage 3.85V

AE4

Model CAC2400022CC  
Manufacturer TCL  
Capacitance 2400 mAh  
Nominal voltage 3.85V

AE5, AE13

Model CBA0059AGAC4  
Manufacturer Aohai  
Length of cable /

AE6

Model CBA0059AGAC2  
Manufacturer Tenpao  
Length of cable /

AE7, AE15

Model CBA0058AGAC2  
Manufacturer Tenpao  
Length of cable /

AE8, AE16

Model CBA0058AGAC3  
Manufacturer Yingju  
Length of cable /

AE9, AE17

Model CDA3122002C1  
Manufacturer Juwei  
Length of cable 99cm

AE10

Model CDA3122005C1  
Manufacturer Juwei

Length of cable	99cm
AE11, AE18	
Model	CDA3122002C8
Manufacturer	PUAN
Length of cable	99cm
AE12, AE19	
Model	CDA3122005C8
Manufacturer	PUAN
Length of cable	99cm
AE20	
Model	CDA0000024C2
Manufacturer	Juwei
Length of cable	99cm

\*AE ID: is used to identify the test sample in the lab internally.

### **3.4. Normal Accessory setting**

Fully charged battery is used during the test.

### **3.5. General Description**

The Equipment Under Test (EUT) is a model of LTE / UMTS / GSM mobile phone with integrated antenna. It consists of normal options: lithium battery, charger. Manual and specifications of the EUT were provided to fulfil the test. Samples undergoing test were selected by the Client.

## 4. Reference Documents

### 4.1. Documents supplied by applicant

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

### 4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part15	FCC CFR 47, Part 15, Subpart C: 15.205 Restricted bands of operation; 15.209 Radiated emission limits, general requirements; 15.247 Operation within the bands 902–928MHz, 2400–2483.5 MHz, and 5725–5850 MHz.	October, 2015
ANSI C63.10	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices	June,2013

The test methods used have no deviation with standards above.

## 5. Test Results

### 5.1. Summary of Test Results

Abbreviations used in this clause:

**P** Pass, The EUT complies with the essential requirements in the standard.  
**F** Fail, The EUT does not comply with the essential requirements in the standard  
**NA** Not Applicable, The test was not applicable  
**NP** Not Performed, The test was not performed by CTTL

SUMMARY OF MEASUREMENT RESULTS	Sub-clause	Verdict
6dB Bandwidth	15.247 (a)(2)	<b>P</b>
Peak Output Power - Conducted	15.247 (b)(1)	<b>P</b>
Maximum Power Spectral Density Level	15.247(e)	<b>P</b>
Conducted Emission	15.247 (d)	<b>P</b>
Radiated Emission	15.247, 15.205, 15.209	<b>P</b>
Frequency Band Edges	15.247 (d)	<b>P</b>
AC Powerline Conducted Emission	15.107, 15.207	<b>P</b>

Please refer to **ANNEX A** for detail.

The measurement is made according to ANSI C63.10.

### 5.2. Statements

CTTL has evaluated the test cases requested by the applicant /manufacturer as listed in section 5.1 of this report for the EUT specified in section 3 according to the standards or reference documents listed in section 4.2

## 6. Test Facilities Utilized

### Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Vector Signal Analyzer	FSQ26	200136	Rohde & Schwarz	1 year	2017-01-06
2	Shielding Room	S81	/	ETS-Lindgren	/	/
3	Test Receiver	ESCI	100766	Rohde & Schwarz	1 year	2017-03-30
4	LISN	ESH2-Z5	829991-0 12	Rohde & Schwarz	1 year	2017-04-11

### Radiated emission test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Test Receiver	ESU26	100235	Rohde & Schwarz	1 year	2017-03-02
2	Loop antenna	HFH2-Z2	829324/00 7	Rohde & Schwarz	3 years	2017-12-16
3	BiLog Antenna	VULB9163	301	Schwarzbeck	3 years	2017-12-16
4	Dual-Ridge Waveguide Horn Antenna	3115	6914	EMCO	3 years	2017-12-15
5	Dual-Ridge Waveguide Horn Antenna	3116	2661	ETS-Lindgren	3 years	2017-06-17
6	Vector Signal Analyzer	FSV40	101047	Rohde & Schwarz	1 year	2017-06-28
7	Semi-anechoic chamber	/	CT000332 -1074	Frankonia German	/	/
8	Test Receiver	ESU26	100376	Rohde & Schwarz	1 year	2016-10-29

### Test Software Utilized

Test Item	Test Software and Version	Software Vendor
Radiated Continuous Emission	EMC32 V8.40.0	R&S
Conducted Continuous Emission	EMC32 V8.5.1	R&S


## **ANNEX A: Detailed Test Results**

### **A.1. Measurement Method**

#### **A.1.1. Conducted Measurements**

The measurement is made according to ANSI C63.10.

- 1). Connect the EUT to the test system correctly.
- 2). Set the EUT to the required work mode (Transmitter, receiver or transmitter & receiver).
- 3). Set the EUT to the required channel.
- 4). Set the EUT hopping mode (hopping or hopping off).
- 5). Set the spectrum analyzer to start measurement.
- 6). Record the values. Vector Signal Analyzer



#### **A.1.2. Radiated Emission Measurements**


The measurement is made according to ANSI C63.10.

The radiated emission test is performed in semi-anechoic chamber. The distance from the EUT to the reference point of measurement antenna is 3m. The test is carried out on both vertical and horizontal polarization and only maximization result of both polarizations is kept. During the test, the turntable is rotated 360° and the measurement antenna is moved from 1m to 4m to get the maximization result.

In the case of radiated emission, the used settings are as follows,

Sweep frequency from 30 MHz to 1GHz, RBW = 100 kHz, VBW = 300 kHz;

Sweep frequency from 1 GHz to 26GHz, RBW = 1MHz, VBW = 1MHz;



## A.2. Peak Output Power - Conducted

**Method of Measurement: See ANSI C63.10-clause 11.9.1.1**

- a) Set the RBW = 1 MHz.
- b) Set VBW = 3 MHz.
- c) Set span = 3 MHz.
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

**Measurement Limit:**

Standard	Limit (dBm)
FCC Part 15.247(b)(1)	< 30

**Measurement Results:**

**For GFSK**

Channel No.	Frequency (MHz)	Peak Conducted Output Power (dBm)	Conclusion
0	2402	-2.00	P
19	2440	-1.16	P
39	2480	-1.99	P

**Conclusion: PASS**

### A.3. Frequency Band Edges - Conducted

**Method of Measurement: See ANSI C63.10-clause 6.10.4**

Connect the spectrum analyzer to the EUT using an appropriate RF cable connected to the EUT output. Configure the spectrum analyzer settings as described below.

- a) Set Span = 8MHz
- b) Sweep Time: coupled
- c) Set the RBW= 100 kHz
- c) Set the VBW= 300 kHz
- d) Detector: Peak
- e) Trace: Max hold

Observe the stored trace and measure the amplitude delta between the peak of the fundamental and the peak of the band-edge emission. This is not an absolute field strength measurement; it is only a relative measurement to determine the amount by which the emission drops at the band edge relative to the highest fundamental emission level.

**Measurement Limit:**

Standard	Limit (dBc)
FCC 47 CFR Part 15.247 (d)	< -20


**Measurement Result:**

**For GFSK**

Channel No.	Frequency (MHz)	Hopping	Band Edge Power (dBc)		Conclusion
0	2402	Hopping OFF	Fig.1	-46.12	P
39	2480	Hopping OFF	Fig.2	-49.75	P


**Conclusion: PASS**

Test graphs as below



Date: 5.AUG.2016 10:29:02

Fig.1. Frequency Band Edges: GFSK, 2402 MHz, Hopping Off



Date: 5.AUG.2016 10:37:47

Fig.2. Frequency Band Edges: GFSK, 2480 MHz, Hopping Off

#### **A.4. Transmitter Spurious Emission - Conducted**

**Method of Measurement: See ANSI C63.10-clause 11.11.2 and clause 11.11.3**

**Measurement Procedure – Reference Level**

1. Set the RBW = 100 kHz.
2. Set the VBW = 300 kHz.
3. Set the span to  $\geq 1.5$  times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.

8. Use the peak marker function to determine the maximum PSD level. Next, determine the power in 100 kHz band segments outside of the authorized frequency band using the following measurement:

**Measurement Procedure - Unwanted Emissions**

1. Set RBW = 100 kHz.
2. Set VBW = 300 kHz.
3. Set span to encompass the spectrum to be examined.
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

7. Allow the trace to stabilize (this may take some time, depending on the extent of the span).


Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified above.

**Measurement Limit:**

Standard	Limit
FCC 47 CFR Part 15.247 (d)	20dB below peak output power in 100 kHz bandwidth

**Measurement Results:**
**For GFSK**

Channel No.	Frequency (MHz)	Frequency Range	Test Results	Conclusion
0	2402	Center Frequency	Fig.3	P
		30 MHz ~ 1 GHz	Fig.4	P
		1 GHz ~ 3 GHz	Fig.5	P
		3 GHz ~ 10 GHz	Fig.6	P
		10GHz ~ 26 GHz	Fig.7	P
19	2440	Center Frequency	Fig.8	P
		30 MHz ~ 1 GHz	Fig.9	P
		1 GHz ~ 3 GHz	Fig.10	P
		3 GHz ~ 10 GHz	Fig.11	P
		10GHz ~ 26 GHz	Fig.12	P
39	2480	Center Frequency	Fig.13	P
		30 MHz ~ 1 GHz	Fig.14	P
		1 GHz ~ 3GHz	Fig.15	P
		3 GHz ~ 10 GHz	Fig.16	P
		10 GHz ~ 26 GHz	Fig.17	P

**Conclusion: PASS**
**Test graphs as below**


Date: 5.AUG.2016 10:27:21

Fig.3. Transmitter Spurious Emission - Conducted: GFSK,2402MHz




Fig.4. Transmitter Spurious Emission - Conducted: GFSK, 2402 MHz, 30MHz - 1GHz




Fig.5. Transmitter Spurious Emission - Conducted: GFSK, 2402 MHz, 1GHz - 3GHz




Fig.6. Transmitter Spurious Emission - Conducted: GFSK, 2402 MHz,3GHz - 10GHz






Fig.7. Transmitter Spurious Emission - Conducted: GFSK, 2402 MHz,10GHz - 26GHz




Date: 5.AUG.2016 10:31:25

Fig.8. Transmitter Spurious Emission - Conducted: GFSK, 2440MHz




Date: 5.AUG.2016 10:31:42

Fig.9. Transmitter Spurious Emission - Conducted: GFSK, 2440 MHz, 30MHz - 1GHz



Date: 5.AUG.2016 10:32:14

Fig.10. Transmitter Spurious Emission - Conducted: GFSK, 2440 MHz, 1GHz – 3GHz



Date: 5.AUG.2016 10:32:30

Fig.11. Transmitter Spurious Emission - Conducted: GFSK, 2440 MHz, 3GHz – 10GHz




Fig.12. Transmitter Spurious Emission - Conducted: GFSK, 2440 MHz, 10GHz – 26GHz






Fig.13. Transmitter Spurious Emission - Conducted: GFSK, 2480 MHz




Date: 5.AUG.2016 10:36:22

Fig.14. Transmitter Spurious Emission - Conducted: GFSK, 2480 MHz, 30MHz - 1GHz




Date: 5.AUG.2016 10:36:54

Fig.15. Transmitter Spurious Emission - Conducted: GFSK, 2480 MHz, 1GHz - 3GHz



Date: 5.AUG.2016 10:37:10

Fig.16. Transmitter Spurious Emission - Conducted: GFSK, 2480 MHz, 3GHz - 10GHz



Date: 5.AUG.2016 10:37:26

Fig.17. Transmitter Spurious Emission - Conducted: GFSK, 2480 MHz, 10GHz - 26GHz

## A.5. Transmitter Spurious Emission - Radiated

### Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

The measurement is made according to ANSI C63.10

### Limit in restricted band:

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

### Test Condition

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	100KHz/300KHz	5
1000-4000	1MHz/1MHz	15
4000-18000	1MHz/1MHz	40
18000-26500	1MHz/1MHz	20

### Measurement Results:

A "reference path loss" is established and the  $A_{RPL}$  is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable los.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{Mea}} + A_{\text{RPL}}$$

### For GFSK

Frequency	Frequency Range	Test Results	Conclusion
2402 MHz	1 GHz ~ 3 GHz	Fig.18	P
	3 GHz ~ 18 GHz	Fig.19	P
2441 MHz	9 kHz ~ 30 MHz	Fig.20	P
	30 MHz ~ 1 GHz	Fig.21	P
	1 GHz ~ 3 GHz	Fig.22	P
	3 GHz ~ 18 GHz	Fig.23	P

2480 MHz	1 GHz ~ 3 GHz	Fig.24	P
	3 GHz ~ 18 GHz	Fig.25	P
Power	2.38GHz~2.4GHz---L	Fig.26	P
Power	2.45GHz~2.5GHz---H	Fig.27	P
For all channels	18 GHz ~ 26.5 GHz	Fig.28	P

**GFSK 2402MHz–Average**

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
2388.510	45.8	-11.1	56.9	H
17990.500	51.3	27.9	23.4	H
17971.000	51.3	27.9	23.4	V
17952.000	51.3	27.9	23.4	H
17921.000	51.1	27.9	23.2	V
17950.500	51.1	27.9	23.2	H

**GFSK 2440MHz–Average**

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
17981.000	51.4	27.9	23.5	V
17991.500	51.4	27.9	23.5	V
17906.000	51.4	27.1	24.3	V
17959.500	51.3	27.9	23.4	H
17996.000	51.3	27.9	23.4	H
17969.000	51.2	27.9	23.3	H

**GFSK 2480MHz–Average**

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
2484.340	46.0	-11.2	57.2	H
17988.500	51.4	27.9	23.5	H
17991.500	51.3	27.9	23.4	V
17990.000	51.3	27.9	23.4	H
17980.000	51.2	27.9	23.3	H
17931.000	51.2	27.9	23.3	V

**GFSK 2402MHz–Peak**

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
2388.005	58.6	-11.1	69.7	H
17873.000	63.5	27.1	36.4	H
17866.000	63.2	27.1	36.1	V
17986.500	63.1	27.9	35.2	H
17912.000	63.1	27.1	36.0	H
17995.000	63.0	27.9	35.1	H

**GFSK 2440MHz-Peak**

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
17919.500	63.5	27.9	35.6	H
17888.500	63.2	27.1	36.1	H
17963.500	63.1	27.9	35.2	V
17917.500	63.0	27.9	35.1	H
17954.000	62.6	27.9	34.7	H
17892.500	62.6	27.1	35.5	V

**GFSK 2480MHz-Peak**

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	PMea(dBuV/m)	Polarity
2483.535	59.9	-11.2	71.1	H
17907.500	63.2	27.1	36.1	H
17921.000	63.0	27.9	35.1	V
17961.500	62.9	27.9	35.0	H
17916.000	62.7	27.9	34.8	V
17911.500	62.7	27.1	35.6	H

Sample calculation: GFSK 2480MHz-Peak, 2483.535MHz

$$\text{Peak ERP(dBm)} = P_{\text{Mea}}(71.1 \text{ dBuV/m}) + A_{\text{Rpl}} (-11.2 \text{ dB}) = 59.9 \text{ dBuV/m}$$

**Conclusion: PASS**

**Test graphs as below:**




Fig.18. Transmitter Spurious Emission - Radiated: GFSK, 2402MHz, 1 GHz - 3GHz




Fig.19. Transmitter Spurious Emission - Radiated: GFSK, 2402MHz, 3 GHz - 18 GHz




Fig.20. Transmitter Spurious Emission - Radiated: GFSK, 2440MHz, 9 kHz - 30 MHz




Fig.21. Transmitter Spurious Emission - Radiated: GFSK, 2440MHz, 30 MHz - 1 GHz




Fig.22. Transmitter Spurious Emission - Radiated: GFSK, 2440MHz, 1 GHz - 3 GHz




Fig.23. Transmitter Spurious Emission - Radiated: GFSK, 2440MHz, 3 GHz - 18 GHz




Fig.24. Transmitter Spurious Emission - Radiated: GFSK, 2480MHz, 1 GHz - 3 GHz




Fig.25. Transmitter Spurious Emission - Radiated: GFSK, 2480MHz, 3 GHz - 18 GHz




Fig.26. Transmitter Spurious Emission - Radiated (Power): GFSK low channel




Fig.27. Transmitter Spurious Emission - Radiated (Power): GFSK high channel




Fig.28. Transmitter Spurious Emission - Radiated: GFSK, 18 GHz - 26 GHz

## A.6. 6dB Bandwidth

### Method of Measurement:

The measurement is made according to ANSI C63.10 clause 11.8.1

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) = 300 kHz.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(a)(2)	>= 500KHz


### Measurement Results:

#### For GFSK

Channel No.	Frequency (MHz)	6dB Bandwidth (kHz)	Conclusion
0	2402	Fig.29	692.31
19	2440	Fig.30	695.51
39	2480	Fig.31	695.51


**Conclusion: PASS**

**Test graphs as below:**




Date: 5.AUG.2016 10:26:35

Fig.29. 6dB Bandwidth: GFSK, 2402 MHz



Date: 5.AUG.2016 10:30:40

Fig.30. 6dB Bandwidth: GFSK, 2440 MHz



Date: 5.AUG.2016 10:35:19

Fig.31. 6dB Bandwidth: GFSK, 2480 MHz

## A.7. Maximum Power Spectral Density Level

### Method of Measurement:

The measurement is made according to ANSI C63.10 clause 11.10.2

1. Set the RBW = 3 kHz.
2. Set the VBW = 10 kHz.
3. Set the span to 2 times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum amplitude level within the RBW.

### Measurement Limit:


Standard	Limit
FCC 47 CFR Part 15.247(e)	<=8.0dBm/3kHz

### Measurement Results:

#### For GFSK


Channel No.	Frequency (MHz)	Maximum Power Spectral Density Level(dBm/3kHz)		Conclusion
0	2402	Fig.32	-17.90	P
19	2440	Fig.33	-17.14	P
39	2480	Fig.34	-17.97	P

Test graphs as below:




Date: 5.AUG.2016 10:27:03

Fig.32. Maximum Power Spectral Density Level Function: GFSK, 2402 MHz



Date: 5.AUG.2016 10:31:07

Fig.33. Maximum Power Spectral Density Level Function: GFSK, 2440 MHz



Date: 5.AUG.2016 10:35:47

## A.8. AC Powerline Conducted Emission

### Method of Measurement: See ANSI C63.10-clause 6.2

1. the one EUT cable configuration and arrangement and mode of operation that produced the emission with the highest amplitude relative to the limit is selected for the final measurement, while applying the appropriate modulating signal to the EUT.
2. If the EUT is relocated from an exploratory test site to a final test site, the highest emissions shall be remaximized at the final test location before final ac power-line conducted emission measurements are performed.
3. The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment in the system) is then performed for the full frequency range for which the EUT is being tested for compliance without further variation of the EUT arrangement, cable positions, or EUT mode of operation.
4. If the EUT is comprised of equipment units that have their own separate ac power connections, e.g., floor-standing equipment with independent power cords for each shelf that are able to connect directly to the ac power network, each current-carrying conductor of one unit is measured while the other units are connected to a second (or more) LISN(s). All units shall be separately measured. If a power strip is provided by the manufacturer, to supply all of the units making up the EUT, only the conductors in the power cord of the power strip shall be measured.
5. If the EUT uses a detachable antenna, these measurements shall be made with a suitable dummy load connected to the antenna output terminals; otherwise, the tests shall be made with the antenna connected and, if adjustable, fully extended. When measuring the ac conducted emissions from a device that operates between 150 kHz and 30 MHz a non-detachable antenna may be replaced with a dummy load for the measurements within the fundamental emission band of the transmitter, but only for those measurements.<sup>36</sup> Record the six highest EUT emissions relative to the limit of each of the current-carrying conductors of the power cords of the equipment that comprises the EUT over the frequency range specified by the procuring or regulatory agency. Diagram or photograph the test setup that was used. See Clause 8 for full reporting requirements.

#### Test Condition

Voltage (V)	Frequency (Hz)
120	60

#### Measurement Result and limit:

##### Bluetooth (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dB $\mu$ V)	Conclusion
0.15 to 0.5	66 to 56	P
0.5 to 5	56	
5 to 30	60	

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

**Bluetooth (Average Limit)**


Frequency range (MHz)	Average Limit (dB $\mu$ V)	Conclusion
0.15 to 0.5	56 to 46	P
0.5 to 5	46	
5 to 30	50	

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

The measurement is made according to ANSI C63.10

**Conclusion: PASS**


**Test graphs as below:**

**Traffic (CBA0059AGAC4):**

**Final Result 1**

Frequency (MHz)	QuasiPeak (dB $\mu$ V)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
13.524001	50.0	GND	L1	10.9	10.0	60.0
13.564501	49.4	GND	L1	10.9	10.6	60.0
13.609501	49.1	GND	L1	10.9	10.9	60.0
13.654501	50.8	GND	L1	10.9	9.2	60.0
13.695001	49.2	GND	L1	10.9	10.8	60.0
14.374501	50.0	GND	L1	10.9	10.0	60.0

**Final Result 2**


Frequency (MHz)	Average (dB $\mu$ V)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
0.631501	39.4	GND	L1	10.3	6.6	46.0
10.185001	40.4	GND	L1	10.7	9.6	50.0
10.270501	38.3	GND	L1	10.7	11.7	50.0
13.609501	39.4	GND	L1	10.9	10.6	50.0
13.695001	35.8	GND	L1	10.9	14.2	50.0
14.374501	40.5	GND	L1	10.9	9.5	50.0

**Idle (CBA0059AGAC4):**

**Final Result 1**

Frequency (MHz)	QuasiPeak (dB $\mu$ V)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
10.297501	38.6	GND	L1	10.7	21.4	60.0
13.524001	50.3	GND	L1	10.9	9.7	60.0
13.569001	50.6	GND	L1	10.9	9.4	60.0
13.654501	50.9	GND	L1	10.9	9.1	60.0
13.690501	39.2	GND	L1	10.9	20.8	60.0
14.410501	43.2	GND	L1	10.9	16.8	60.0

**Final Result 2**


Frequency (MHz)	Average (dB $\mu$ V)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
0.631501	39.3	GND	L1	10.3	6.7	46.0
0.721501	38.1	GND	L1	10.3	7.9	46.0
1.266001	37.1	GND	L1	10.3	8.9	46.0
10.230001	41.5	GND	L1	10.7	8.5	50.0
13.524001	39.9	GND	L1	10.9	10.1	50.0
13.654501	40.5	GND	L1	10.9	9.5	50.0

**Traffic (CBA0059AGAC2):**

**Final Result 1**

Frequency (MHz)	QuasiPeak (dB $\mu$ V)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
8.848501	41.4	GND	L1	10.6	18.6	60.0
9.132001	41.3	GND	L1	10.7	18.7	60.0
9.190501	41.7	GND	L1	10.7	18.3	60.0
9.312001	42.2	GND	L1	10.7	17.8	60.0
9.645001	43.9	GND	L1	10.7	16.1	60.0
9.735001	44.0	GND	L1	10.7	16.0	60.0

**Final Result 2**


Frequency (MHz)	Average (dB $\mu$ V)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
0.537001	27.0	GND	L1	10.3	19.0	46.0
8.857501	29.6	GND	L1	10.6	20.4	50.0
9.114001	28.8	GND	L1	10.7	21.2	50.0
9.132001	28.9	GND	L1	10.7	21.1	50.0
9.775501	32.3	GND	L1	10.7	17.7	50.0
10.500001	32.3	GND	L1	10.7	17.7	50.0

**Traffic (CBA0058AGAC2):**

**Final Result 1**

Frequency (MHz)	QuasiPeak (dB $\mu$ V)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
8.848501	41.4	GND	L1	10.6	18.6	60.0
9.132001	41.3	GND	L1	10.7	18.7	60.0
9.190501	41.7	GND	L1	10.7	18.3	60.0
9.312001	42.2	GND	L1	10.7	17.8	60.0
9.645001	43.9	GND	L1	10.7	16.1	60.0
9.735001	44.0	GND	L1	10.7	16.0	60.0

**Final Result 2**

Frequency (MHz)	Average (dB $\mu$ V)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
0.537001	27.0	GND	L1	10.3	19.0	46.0
8.857501	29.6	GND	L1	10.6	20.4	50.0
9.114001	28.8	GND	L1	10.7	21.2	50.0
9.132001	28.9	GND	L1	10.7	21.1	50.0
9.775501	32.3	GND	L1	10.7	17.7	50.0
10.500001	32.3	GND	L1	10.7	17.7	50.0

**Traffic (CBA0058AGAC3):**

**Final Result 1**

Frequency (MHz)	QuasiPeak (dB $\mu$ V)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
9.172501	40.0	GND	L1	10.7	20.0	60.0
9.807001	40.8	GND	L1	10.7	19.2	60.0
10.369501	41.0	GND	L1	10.7	19.0	60.0
10.882501	40.4	GND	L1	10.7	19.6	60.0
11.530501	40.4	GND	L1	10.8	19.6	60.0
12.138001	39.6	GND	L1	10.8	20.4	60.0

**Final Result 2**

Frequency (MHz)	Average (dB $\mu$ V)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
0.586501	32.3	GND	L1	10.3	13.7	46.0
3.858001	27.5	GND	L1	10.4	18.5	46.0
9.235501	31.8	GND	L1	10.7	18.2	50.0
9.807001	32.0	GND	L1	10.7	18.0	50.0
10.324501	31.0	GND	L1	10.7	19.0	50.0
10.437001	31.8	GND	L1	10.7	18.2	50.0

## ANNEX B: Accreditation Certificate



**China National Accreditation Service for Conformity Assessment**

### **LABORATORY ACCREDITATION CERTIFICATE**

**(No. CNAS L0570 )**

**Telecommunication Technology Labs,**

**Academy of Telecommunication Research, MIIT**

No.52, Huayuan North Road, Haidian District, Beijing, China

No.51, Xueyuan Road, Haidian District, Beijing, China

*to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories(CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing and calibration.*

*The scope of accreditation is detailed in the attached schedule bearing the same accreditation number as above. The schedule forms an integral part of this certificate.*

**Date of Issue:** 2014-10-29

**Date of Expiry:** 2017-06-19

**Date of Initial Accreditation:** 1998-07-03



Signed on behalf of China National Accreditation Service  
for Conformity Assessment

China National Accreditation Service for Conformity Assessment (CNAS) is authorized by Certification and Accreditation Administration of the People's Republic of China (CNCA) to operate the national accreditation schemes for conformity assessment. CNAS is the signatory to International Laboratory Accreditation Cooperation Multilateral Recognition Arrangement (ILAC MRA) and Asia Pacific Laboratory Accreditation Cooperation Multilateral Recognition Arrangement (APLAC MRA).

No.CNAS AL 2

0011149

**\*\*\*END OF REPORT\*\*\***