



SAR TEST REPORT

No. I16Z42266-SEM01

For

TCL Communication Ltd.

LTE / UMTS / GSM mobile phone

Modelname: 5085A

With

Hardware Version: PIO

Software Version: 1AA4

FCC ID: 2ACCJH060

Issued Date: 2016-12-29



中国认可
国际互认
检测
TESTING
CNAS L0570

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

Test Laboratory:

CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT

No. 51 Shouxiang Science Building, Xueyuan Road, Haidian District, Beijing, P. R. China100191

Tel:+86(0)10-62304633-2512,Fax:+86(0)10-62304633-2504

Email: ctl_terminals@catr.cn, website:www.chinattl.com



REPORT HISTORY

Report Number	Revision	Issue Date	Description
I16Z42266-SEM01	Rev.0	2016-12-29	Initial creation of test report

TABLE OF CONTENT

1 TEST LABORATORY	5
1.1 TESTING LOCATION	5
1.2 TESTING ENVIRONMENT.....	5
1.3 PROJECT DATA	5
1.4 SIGNATURE.....	5
2 STATEMENT OF COMPLIANCE	6
3 CLIENT INFORMATION	8
3.1 APPLICANT INFORMATION	8
3.2 MANUFACTURER INFORMATION	8
4 EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	9
4.1 ABOUT EUT	9
4.2 INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	9
4.3 INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	9
5 TEST METHODOLOGY	10
5.1 APPLICABLE LIMIT REGULATIONS	10
5.2 APPLICABLE MEASUREMENT STANDARDS.....	10
6 SPECIFIC ABSORPTION RATE (SAR).....	11
6.1 INTRODUCTION.....	11
6.2 SAR DEFINITION	11
7 TISSUE SIMULATING LIQUIDS	12
7.1 TARGETS FOR TISSUE SIMULATING LIQUID	12
7.2 DIELECTRIC PERFORMANCE	12
8 SYSTEM VERIFICATION	19
8.1 SYSTEM SETUP.....	19
8.2 SYSTEM VERIFICATION.....	20
9 MEASUREMENT PROCEDURES	21
9.1 TESTS TO BE PERFORMED	21
9.2 GENERAL MEASUREMENT PROCEDURE.....	22
9.3 WCDMA MEASUREMENT PROCEDURES FOR SAR	24
9.4 SAR MEASUREMENT FOR LTE.....	25
9.5 BLUETOOTH & WI-FI MEASUREMENT PROCEDURES FOR SAR	25
9.6 POWER DRIFT.....	26
10 AREA SCAN BASED 1-G SAR.....	26
10.1 REQUIREMENT OF KDB.....	26
10.2 FAST SAR ALGORITHMS	26
11 CONDUCTED OUTPUT POWER.....	27

11.1 MANUFACTURING TOLERANCE	27
11.2 GSM MEASUREMENT RESULT	32
11.3 WCDMA MEASUREMENT RESULT	33
11.4 LTE MEASUREMENT RESULT	34
11.5 WI-FI AND BT MEASUREMENT RESULT	47
12 SIMULTANEOUS TX SAR CONSIDERATIONS	49
12.1 INTRODUCTION	49
12.2 TRANSMIT ANTENNA SEPARATION DISTANCES	49
12.3 SAR MEASUREMENT POSITIONS	50
12.4 STANDALONE SAR TEST EXCLUSION CONSIDERATIONS	50
13 EVALUATION OF SIMULTANEOUS	51
14 SAR TEST RESULT	52
14.1 THE EVALUATION OF MULTI-BATTERIES	52
14.2 SAR RESULTS FOR FAST SAR	53
14.3 SAR RESULTS FOR STANDARD PROCEDURE	64
14.4 WLAN EVALUATION	69
15 SAR MEASUREMENT VARIABILITY	72
16 MEASUREMENT UNCERTAINTY	73
16.1 MEASUREMENT UNCERTAINTY FOR NORMAL SAR TESTS (300MHz~3GHz)	73
16.2 MEASUREMENT UNCERTAINTY FOR NORMAL SAR TESTS (3~6GHz)	74
16.3 MEASUREMENT UNCERTAINTY FOR FAST SAR TESTS (300MHz~3GHz)	75
16.4 MEASUREMENT UNCERTAINTY FOR FAST SAR TESTS (3~6GHz)	76
17 MAIN TEST INSTRUMENTS	77
ANNEX A GRAPH RESULTS	78
ANNEX B SYSTEM VERIFICATION RESULTS	126
ANNEX C SAR MEASUREMENT SETUP	139
ANNEX D POSITION OF THE WIRELESS DEVICE IN RELATION TO THE PHANTOM	145
ANNEX E EQUIVALENT MEDIA RECIPES	148
ANNEX F SYSTEM VALIDATION	149
ANNEX G PROBE CALIBRATION CERTIFICATE	150
ANNEX H DIPOLE CALIBRATION CERTIFICATE	161
ANNEX J ACCREDITATION CERTIFICATE	209

1 Test Laboratory

1.1 Testing Location

Company Name:	CTTL(Shouxiang)
Address:	No. 51 Shouxiang Science Building, Xueyuan Road, Haidian District, Beijing, P. R. China100191

1.2 Testing Environment

Temperature:	18°C~25°C,
Relative humidity:	30%~ 70%
Ground system resistance:	< 0.5 Ω
Ambient noise & Reflection:	< 0.012 W/kg


1.3 Project Data

Project Leader:	Qi Dianyuan
Test Engineer:	Lin Xiaojun
Testing Start Date:	December 6, 2016
Testing End Date:	December 11, 2016


1.4 Signature



Lin Xiaojun
(Prepared this test report)



Qi Dianyuan
(Reviewed this test report)



Lu Bingsong
Deputy Director of the laboratory
(Approved this test report)

2 Statement of Compliance

The maximum results of SAR found during testing for TCL Communication Ltd. LTE / UMTS / GSM mobile phone 5085A are as follows:

Table 2.1: Highest Reported SAR (1g)

Exposure Configuration	Technology Band	Highest Reported SAR 1g(W/Kg)	Equipment Class
Head (Separation Distance 0mm)	GSM 850	0.34	PCE
	PCS 1900	0.21	
	UMTS FDD 5	0.46	
	UMTS FDD 4	0.36	
	UMTS FDD 2	0.39	
	LTE Band 2	0.29	
	LTE Band 4	0.45	
	LTE Band 5	0.46	
	LTE Band 7	0.31	
	LTE Band 12	0.24	
	LTE Band 13	0.16	
	WLAN 2.4 GHz	0.75	DTS
Hotspot (Separation Distance 10mm)	GSM 850	0.42	PCE
	PCS 1900	0.55	
	UMTS FDD 5	0.48	
	UMTS FDD 4	0.72	
	UMTS FDD 2	0.73	
	LTE Band 2	0.93	
	LTE Band 4	1.03	
	LTE Band 5	0.50	
	LTE Band 7	0.87	
	LTE Band 12	0.33	
	LTE Band 13	0.25	
	WLAN 2.4 GHz	0.23	DTS

The SAR values found for the Mobile Phone are below the maximum recommended levels of 1.6 W/Kg as averaged over any 1g tissue according to the ANSI C95.1-1992.

For body worn operation, this device has been tested and meets FCC RF exposure guidelines when used with any accessory that contains no metal and which provides a minimum separation distance of 10 mm between this device and the body of the user. Use of other accessories may not ensure compliance with FCC RF exposure guidelines.

The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power output.

The measurement together with the test system set-up is described in annex C of this test report. A detailed description of the equipment under test can be found in chapter 4 of this test report. The highest reported SAR value is obtained at the case of **(Table 2.1)**, and the values are: **1.03 W/kg(1g)**.

Table 2.2: The sum of reported SAR values for main antenna and WiFi

	Position	Main antenna	WiFi	Sum
Highest reported SAR value for Head	Left hand, Touch cheek	0.46	0.49	0.95
	Right hand, Touch cheek	0.32	0.75	1.07
Highest reported SAR value for Body	Front	0.99	0.14	1.13
	Top	/	0.23	0.23
	Bottom	1.03	/	1.03

Table 2.3: The sum of reported SAR values for main antenna and BT

	Position	Main antenna	BT	Sum
Maximum reported SAR value for Head	Left hand, Touch cheek	0.46	0.23 ^[1]	0.69
Maximum reported SAR value for Body	Front	0.99	0.12 ^[1]	1.11

[1] - Estimated SAR for Bluetooth (see the table 13.3)

According to the above tables, the highest sum of reported SAR values is **1.13 W/kg (1g)**. The detail for simultaneous transmission consideration is described in chapter 13.

3 Client Information

3.1 Applicant Information

Company Name:	TCL Communication Ltd.
Address/Post:	5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong Area Shanghai, P.R. China. 201203
City:	Shanghai
Country:	China
Contact Person:	Gong Zhizhou
E-mail:	zhizhou.gong@tcl.com
Telephone:	0086-21-31363544
Fax:	0086-21-61460602

3.2 Manufacturer Information

Company Name:	TCL Communication Ltd.
Address/Post:	5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong Area Shanghai, P.R. China. 201203
City:	Shanghai
Country:	China
Contact Person:	Gong Zhizhou
E-mail:	zhizhou.gong@tcl.com
Telephone:	0086-21-31363544
Fax:	0086-21-61460602

4 Equipment Under Test (EUT) and Ancillary Equipment (AE)

4.1 About EUT

Description:	LTE / UMTS / GSM mobile phone
Model name:	5085A
Operating mode(s):	GSM 850/900/1800/1900, WCDMA 850/900/1700/1900/2100 BT, Wi-Fi, LTE Band 2/3/4/5/7/12/13/17/28
Tested Tx Frequency:	825 – 848.8 MHz (GSM 850)
	1850.2 – 1910 MHz (GSM 1900)
	826.4–846.6 MHz (WCDMA 850 Band V)
	1712.4 – 1752.6 MHz (WCDMA 1700 Band IV)
	1852.4–1907.6 MHz (WCDMA1900 Band II)
	1860 – 1900 MHz (LTE Band 2)
	1720 – 1745 MHz (LTE Band 4)
	824.7 – 848.3 MHz (LTE Band 5)
	2502.5 – 2567.5 MHz (LTE Band 7)
	699.7 – 715.3 MHz (LTE Band 12)
	779.5 –784.5 MHz (LTE Band 13)
	706.5 –713.5 MHz (LTE Band 17)
	2412 – 2462 MHz (Wi-Fi 2.4G)
GPRS/EGPRS Multislot Class:	12
GPRS capability Class:	B
Test device Production information:	Production unit
Device type:	Portable device
Antenna type:	Integrated antenna
Accessories/Body-worn configurations:	Headset
Hotspot mode:	Support

4.2 Internal Identification of EUT used during the test

EUT ID*	IMEI	HW	SW Version
EUT1	014809000201572	PIO	1AA4
EUT2	014809000201010	PIO	1AA4
EUT3	014809000201473	PIO	1AA4
EUT4	014809000201481	PIO	1AA4
EUT5	014809000201077	PIO	1AA4

*EUT ID: is used to identify the test sample in the lab internally.

Note: It is performed to test SAR with the EUT1&2&3&4 and conducted power with the EUT5.

4.3 Internal Identification of AE used during the test

AE ID*	Description	Model	SN	Manufacturer
AE1	Battery	CAC2710008CJ	/	COSLIGHT
AE2	Battery	CAC2710004C1	/	BYD
AE3	Battery	CAC2710005CC	/	Jinneng
AE4	Headset	CCB0049A10C1	/	Juwei
AE5	Headset	CCB0049A10C4	/	Meihao
AE6	Lighting cover	/	/	/

*AE ID: is used to identify the test sample in the lab internally.

Note: AE6 is a PC cover with LED lighting, the lights will turn on when some actions active, like incoming call, play music and so on.

5 TEST METHODOLOGY

5.1 Applicable Limit Regulations

ANSI C95.1–1992:IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

It specifies the maximum exposure limit of **1.6 W/kg** as averaged over any 1 gram of tissue for portable devices being used within 20 cm of the user in the uncontrolled environment.

5.2 Applicable Measurement Standards

IEEE 1528–2013: Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.

KDB447498 D01: General RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

KDB648474 D04 Handset SAR v01r03: SAR Evaluation Considerations for Wireless Handsets.

KDB941225 D01 SAR test for 3G devices v03r01: SAR Measurement Procedures for 3G Devices

KDB941225 D05 SAR for LTE Devices v02r05: SAR Evaluation Considerations for LTE Devices

KDB941225 D06 Hotspot Mode SAR v02r01: SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities

KDB248227 D01 802.11 Wi-Fi SAR v02r02: SAR GUIDANCE FOR IEEE 802.11 (Wi-Fi) TRANSMITTERS

KDB865664 D01SAR measurement 100 MHz to 6 GHz v01r04: SAR Measurement Requirements for 100 MHz to 6 GHz.

KDB865664 D02RF Exposure Reporting v01r02: RF Exposure Compliance Reporting and Documentation Considerations

6 Specific Absorption Rate (SAR)

6.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

6.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$SAR = c \left(\frac{\delta T}{\delta t} \right)$$

Where: C is the specific heat capacity, δT is the temperature rise and δt is the exposure duration, or related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

7 Tissue Simulating Liquids

7.1 Targets for tissue simulating liquid

Table 7.1: Targets for tissue simulating liquid


Frequency(MHz)	Liquid Type	Conductivity(σ)	$\pm 5\%$ Range	Permittivity(ϵ)	$\pm 5\%$ Range
750	Head	0.89	0.85~0.93	41.94	39.8~44.0
750	Body	0.96	0.91~1.01	55.5	52.7~58.3
835	Head	0.90	0.86~0.95	41.5	39.4~43.6
835	Body	0.97	0.92~1.02	55.2	52.4~58.0
1750	Head	1.37	1.30~1.44	40.08	38.1~42.1
1750	Body	1.49	1.42~1.56	53.4	50.7~56.1
1900	Head	1.40	1.33~1.47	40.0	38.0~42.0
1900	Body	1.52	1.44~1.60	53.3	50.6~56.0
2450	Head	1.80	1.71~1.89	39.2	37.2~41.2
2450	Body	1.95	1.85~2.05	52.7	50.1~55.3
2600	Head	1.96	1.86~2.06	39.01	37.06~40.96
2600	Body	2.16	2.05~2.27	52.5	49.9~55.1

7.2 Dielectric Performance

Table 7.2: Dielectric Performance of Tissue Simulating Liquid

Measurement Date (yyyy-mm-dd)	Type	Frequency	Permittivity ϵ	Drift (%)	Conductivity σ (S/m)	Drift (%)
2016-12-8	Head	750 MHz	42.59	1.55	0.906	1.80
	Body	750 MHz	54.55	-1.71	0.931	-3.02
2016-12-6	Head	835 MHz	41.83	0.80	0.885	-1.67
	Body	835 MHz	56.31	2.01	0.942	-2.89
2016-12-9	Head	1750 MHz	39.35	-1.82	1.355	-1.09
	Body	1750 MHz	52.3	-2.06	1.475	-1.01
2016-12-7	Head	1900 MHz	40.85	2.13	1.385	-1.07
	Body	1900 MHz	53.74	0.83	1.55	1.97
2016-12-11	Head	2450 MHz	38.16	-2.65	1.78	-1.11
	Body	2450 MHz	51.96	-1.40	1.956	0.31
2016-12-10	Head	2600 MHz	38.45	-1.44	1.924	-1.84
	Body	2600 MHz	53.62	2.13	2.165	0.23


Note: The liquid temperature is 22.0°C




Picture 7-1 Liquid depth in the Head Phantom (750MHz)



Picture 7-2 Liquid depth in the Flat Phantom (750MHz)




Picture 7-3 Liquid depth in the Head Phantom (835 MHz)



Picture 7-4 Liquid depth in the Flat Phantom (835 MHz)




Picture 7-5 Liquid depth in the Head Phantom (1750 MHz)



Picture 7-6 Liquid depth in the Flat Phantom (1750MHz)




Picture 7-7 Liquid depth in the Head Phantom (1900 MHz)




Picture 7-8 Liquid depth in the Flat Phantom (1900MHz)




Picture 7-9 Liquid depth in the Head Phantom (2450MHz)



Picture 7-10 Liquid depth in the Flat Phantom (2450MHz)



Picture 7-11 Liquid depth in the HeadPhantom (2600 MHz Head)




Picture 7-12 Liquid depth in the Flat Phantom (2600MHz)


8 System verification

8.1 System Setup

In the simplified setup for system evaluation, the DUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:



Picture 8.1 System Setup for System Evaluation



Picture 8.2 Photo of Dipole Setup

8.2 System Verification

SAR system verification is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device.

The system verification results are required that the area scan estimated 1-g SAR is within 3% of the zoom scan 1-g SAR. The details are presented in annex B.

Table 8.1: System Verification of Head

Measurement Date (yyyy-mm-dd)	Frequency	Target value (W/kg)		Measured value(W/kg)		Deviation	
		10 g Average	1 g Average	10 g Average	1 g Average	10 g Average	1 g Average
2016-12-8	750 MHz	5.46	8.33	5.60	8.48	2.56%	1.80%
2016-12-6	835 MHz	6.18	9.44	6.28	9.52	1.62%	0.85%
2016-12-9	1750 MHz	19.50	36.80	19.9	37.2	1.95%	1.20%
2016-12-7	1900 MHz	21.20	40.70	21.8	42.0	3.02%	3.19%
2016-12-11	2450 MHz	24.60	52.80	24.9	53.2	1.30%	0.76%
2016-12-10	2600 MHz	25.20	56.70	25.9	57.6	2.70%	1.59%

Table 8.2: System Verification of Body

Measurement Date (yyyy-mm-dd)	Frequency	Target value (W/kg)		Measured value (W/kg)		Deviation	
		10 g Average	1 g Average	10 g Average	1 g Average	10 g Average	1 g Average
2016-12-8	750 MHz	5.76	8.78	5.64	8.64	-2.08%	-1.59%
2016-12-6	835 MHz	6.36	9.69	6.52	9.88	2.52%	1.96%
2016-12-9	1750 MHz	19.60	37.00	19.80	37.32	1.02%	0.86%
2016-12-7	1900 MHz	21.30	40.10	21.40	40.80	0.47%	1.75%
2016-12-11	2450 MHz	24.10	51.20	24.56	51.60	1.91%	0.78%
2016-12-10	2600 MHz	24.80	55.30	25.28	56.00	1.94%	1.27%

9 Measurement Procedures

9.1 Tests to be performed

In order to determine the highest value of the peak spatial-average SAR of a handset, all device positions, configurations and operational modes shall be tested for each frequency band according to steps 1 to 3 below. A flowchart of the test process is shown in picture 9.1.


Step 1: The tests described in 9.2 shall be performed at the channel that is closest to the centre of the transmit frequency band (f_c) for:

- a) all device positions (cheek and tilt, for both left and right sides of the SAM phantom, as described in annex D),
- b) all configurations for each device position in a), e.g., antenna extended and retracted, and
- c) all operational modes, e.g., analogue and digital, for each device position in a) and configuration in b) in each frequency band.

If more than three frequencies need to be tested according to 11.1 (i.e., $N_c > 3$), then all frequencies, configurations and modes shall be tested for all of the above test conditions.

Step 2: For the condition providing highest peak spatial-average SAR determined in Step 1, perform all tests described in 9.2 at all other test frequencies, i.e., lowest and highest frequencies. In addition, for all other conditions (device position, configuration and operational mode) where the peak spatial-average SAR value determined in Step 1 is within 3 dB of the applicable SAR limit, it is recommended that all other test frequencies shall be tested as well.

Step 3: Examine all data to determine the highest value of the peak spatial-average SAR found in Steps 1 to 2.



Picture 9.1Block diagram of the tests to be performed

9.2 General Measurement Procedure

The area and zoom scan resolutions specified in the table below must be applied to the SAR measurements and fully documented in SAR reports to qualify for TCB approval. Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the

higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1-g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std 1528-2003. The results should be documented as part of the system validation records and may be requested to support test results when all the measurement parameters in the following table are not satisfied.

			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}			≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm	$3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx_{Zoom} , Δy_{Zoom}			≤ 2 GHz: ≤ 8 mm $2 - 3$ GHz: ≤ 5 mm*	$3 - 4$ GHz: ≤ 5 mm* $4 - 6$ GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$		≤ 5 mm	$3 - 4$ GHz: ≤ 4 mm $4 - 5$ GHz: ≤ 3 mm $5 - 6$ GHz: ≤ 2 mm
	graded grid	$\Delta z_{Zoom}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	$3 - 4$ GHz: ≤ 3 mm $4 - 5$ GHz: ≤ 2.5 mm $5 - 6$ GHz: ≤ 2 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	$3 - 4$ GHz: ≥ 28 mm $4 - 5$ GHz: ≥ 25 mm $5 - 6$ GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <u>reported</u> SAR from the area scan based 1-g SAR estimation procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

9.3 WCDMA Measurement Procedures for SAR

The following procedures are applicable to WCDMA handsets operating under 3GPP Release99, Release 5 and Release 6. The default test configuration is to measure SAR with an established radio link between the DUT and a communication test set using a 12.2kbps RMC (reference measurement channel) configured in Test Loop Mode 1. SAR is selectively confirmed for other physical channel configurations (DPCCH & DPDCH_n), HSDPA and HSPA (HSUPA/HSDPA) modes according to output power, exposure conditions and device operating capabilities. Both uplink and downlink should be configured with the same RMC or AMR, when required. SAR for Release 5 HSDPA and Release 6 HSPA are measured using the applicable FRC (fixed reference channel) and E-DCH reference channel configurations. Maximum output power is verified according to applicable versions of 3GPP TS 34.121 and SAR must be measured according to these maximum output conditions. When Maximum Power Reduction (MPR) is not implemented according to Cubic Metric (CM) requirements for Release 6 HSPA, the following procedures do not apply.

For Release 5 HSDPA Data Devices:

Sub-test	β_c	β_d	β_d (SF)	β_c / β_d	β_{hs}	CM/dB
1	2/15	15/15	64	2/15	4/15	0.0
2	12/15	15/15	64	12/15	24/25	1.0
3	15/15	8/15	64	15/8	30/15	1.5
4	15/15	4/15	64	15/4	30/15	1.5

For Release 6 HSPA Data Devices

Sub-test	β_c	β_d	β_d (SF)	β_c / β_d	β_{hs}	β_{ec}	β_{ed}	β_{ed} (SF)	β_{ed} (codes)	CM (dB)	MPR (dB)	AG Index	E-TFCI
1	11/15	15/15	64	11/15	22/15	209/225	1039/225	4	1	1.5	1.5	20	75
2	6/15	15/15	64	6/15	12/15	12/15	12/15	4	1	1.5	1.5	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1}:47/15$ $\beta_{ed2}:47/15$	4	2	1.5	1.5	15	92
4	2/15	15/15	64	2/15	4/15	4/15	56/75	4	1	1.5	1.5	17	71
5	15/15	15/15	64	15/15	24/15	30/15	134/15	4	1	1.5	1.5	21	81

Rel.8 DC-HSDPA (Cat 24)

SAR test exclusion for Rel.8 DC-HSDPA must satisfy the SAR test exclusion requirements of Rel.5 HSDPA. SAR test exclusion for DC-HSDPA devices is determined by power measurements according to the H-Set 12, Fixed Reference Channel (FRC) configuration in Table C.8.1.12 of 3GPP TS 34.121-1. A primary and a secondary serving HS-DSCH Cell are required to perform the power measurement and for the results to qualify for SAR test exclusion.

9.4 SAR Measurement for LTE

SAR tests for LTE are performed with a base station simulator, Rohde & Schwarz CMW500. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. All powers were measured with the CMW 500.

It is performed for conducted power and SAR based on the KDB941225 D05.

SAR is evaluated separately according to the following procedures for the different test positions in each exposure condition – head, body, body-worn accessories and other use conditions. The procedures in the following subsections are applied separately to test each LTE frequency band.

1) QPSK with 1 RB allocation

Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.

2) QPSK with 50% RB allocation

The procedures required for 1 RB allocation in 1) are applied to measure the SAR for QPSK with 50% RB allocation.

3) QPSK with 100% RB allocation

For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation in 1) and 2) are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

9.5 Bluetooth & Wi-Fi Measurement Procedures for SAR

Normal network operating configurations are not suitable for measuring the SAR of 802.11 transmitters in general. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure that the results are consistent and reliable.

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in a test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.

9.6 Power Drift

To control the output power stability during the SAR test, DASY4 system calculates the power drift by measuring the E-field at the same location at the beginning and at the end of the measurement for each test position. These drift values can be found in section 14 labeled as: (Power Drift [dB]). This ensures that the power drift during one measurement is within 5%.

10 Area Scan Based 1-g SAR

10.1 Requirement of KDB

According to the KDB447498 D01 v05, when the implementation is based on the specific polynomial fit algorithm as presented at the 29th Bioelectromagnetics Society meeting (2007) and the estimated 1-g SAR is ≤ 1.2 W/kg, a zoom scan measurement is not required provided it is also not needed for any other purpose; for example, if the peak SAR location required for simultaneous transmission SAR test exclusion can be determined accurately by the SAR system or manually to discriminate between distinctive peaks and scattered noisy SAR distributions from area scans.

There must not be any warning or alert messages due to various measurement concerns identified by the SAR system; for example, noise in measurements, peaks too close to scan boundary, peaks are too sharp, spatial resolution and uncertainty issues etc. The SAR system verification must also demonstrate that the area scan estimated 1-g SAR is within 3% of the zoom scan 1-g SAR (See Annex B). When all the SAR results for each exposure condition in a frequency band and wireless mode are based on estimated 1-g SAR, the 1-g SAR for the highest SAR configuration must be determined by a zoom scan.

10.2 Fast SAR Algorithms

The approach is based on the area scan measurement applying a frequency dependent attenuation parameter. This attenuation parameter was empirically determined by analyzing a large number of phones. The MOTOROLA FAST SAR was developed and validated by the MOTOROLA Research Group in Ft. Lauderdale.

In the initial study, an approximation algorithm based on Linear fit was developed. The accuracy of the algorithm has been demonstrated across a broad frequency range (136-2450 MHz) and for both 1- and 10-g averaged SAR using a sample of 264 SAR measurements from 55 wireless handsets. For the sample size studied, the root-mean-squared errors of the algorithm were 1.2% and 5.8% for 1- and 10-g averaged SAR, respectively. The paper describing the algorithm in detail is expected to be published in August 2004 within the Special Issue of Transactions on MTT.

In the second step, the same research group optimized the fitting algorithm to an Polynomial fit whereby the frequency validity was extended to cover the range 30-6000 MHz. Details of this study can be found in the BEMS 2007 Proceedings.

Both algorithms are implemented in DASY software.

11 Conducted Output Power

11.1 Manufacturing tolerance

Table 11.1-1: GSM Speech

GSM 850			
Channel	Channel 251	Channel 190	Channel 128
Target (dBm)	32.3	32.3	32.3
Tune-up(dBm)	33.3	33.3	33.3
GSM 1900			
Channel	Channel 810	Channel 661	Channel 512
Target (dBm)	29.3	29.3	29.3
Tune-up(dBm)	30.3	30.3	30.3

Table 11.1-2: GPRS and EGPRS

GSM 850 GPRS/EGPRS (GMSK)				
Channel		251	190	128
1 Txslot	Target (dBm)	32.1	32.1	32.1
	Tune-up(dBm)	33.1	33.1	33.1
2 Txslots	Target (dBm)	29.5	29.5	29.5
	Tune-up(dBm)	30.5	30.5	30.5
3 Txslots	Target (dBm)	27.5	27.5	27.5
	Tune-up(dBm)	28.5	28.5	28.5
4 Txslots	Target (dBm)	26.5	26.5	26.5
	Tune-up(dBm)	27.5	27.5	27.5
GSM 850 EGPRS (8PSK)				
Channel		810	661	512
1 Txslot	Target (dBm)	26	26	26
	Tune-up(dBm)	27	27	27
2 Txslots	Target (dBm)	25	25	25
	Tune-up(dBm)	26	26	26
3 Txslots	Target (dBm)	23.5	23.5	23.5
	Tune-up(dBm)	24.5	24.5	24.5
4 Txslots	Target (dBm)	23	23	23
	Tune-up(dBm)	24	24	24
GSM 1900 GPRS/EGPRS (GMSK)				
Channel		810	661	512
1 Txslot	Target (dBm)	29	29	29
	Tune-up(dBm)	30	30	30
2 Txslots	Target (dBm)	27	27	27
	Tune-up(dBm)	28	28	28
3 Txslots	Target (dBm)	25	25	25
	Tune-up(dBm)	26	26	26

4 Txslots	Target (dBm)	24	24	24
	Tune-up(dBm)	25	25	25
GSM 1900 EGPRS (8PSK)				
	Channel	810	661	512
1 Txslot	Target (dBm)	26	26	26
	Tune-up(dBm)	27	27	27
2 Txslots	Target (dBm)	25	25	25
	Tune-up(dBm)	26	26	26
3 Txslots	Target (dBm)	23	23	23
	Tune-up(dBm)	24	24	24
4 Txslots	Target (dBm)	21.5	21.5	21.5
	Tune-up(dBm)	22.5	22.5	22.5

Table 11.1-3: WCDMA

WCDMA 850 CS			
Channel	Channel 4233	Channel 4182	Channel 4132
Target (dBm)	23	23	23
Tune-up(dBm)	24	24	24
HSUPA (sub-test 1)			
Channel	Channel 4233	Channel 4182	Channel 4132
Target (dBm)	20.1	20.1	20.1
Tune-up(dBm)	21.1	21.1	21.1
HSUPA (sub-test 2/4)			
Channel	Channel 4233	Channel 4182	Channel 4132
Target (dBm)	20	20	20
Tune-up(dBm)	21	21	21
HSUPA (sub-test 3)			
Channel	Channel 4233	Channel 4182	Channel 4132
Target (dBm)	21	21	21
Tune-up(dBm)	22	22	22
HSUPA (sub-test 5)			
Channel	Channel 4233	Channel 4182	Channel 4132
Target (dBm)	22	22	22
Tune-up(dBm)	23	23	23
DC-HSDPA (sub-test 1~4)			
Channel	Channel 4233	Channel 4182	Channel 4132
Target (dBm)	21	21	21
Tune-up(dBm)	22	22	22
HSPA+			
Channel	Channel 4233	Channel 4182	Channel 4132
Target (dBm)	21	21	21
Tune-up(dBm)	22	22	22

WCDMA 1700 CS			
Channel	Channel 1513	Channel 1412	Channel 1312
Target (dBm)	23	23	23
Tune-up(dBm)	24	24	24
HSUPA (sub-test 1/2/4)			
Channel	Channel 1513	Channel 1412	Channel 1312
Target (dBm)	20	20	20
Tune-up(dBm)	21	21	21
HSUPA (sub-test 3)			
Channel	Channel 1513	Channel 1412	Channel 1312
Target (dBm)	21	21	21
Tune-up(dBm)	22	22	22
HSUPA (sub-test 5)			
Channel	Channel 1513	Channel 1412	Channel 1312
Target (dBm)	22	22	22
Tune-up(dBm)	23	23	23
DC-HSDPA (sub-test 1~4)			
Channel	Channel 1513	Channel 1412	Channel 1312
Target (dBm)	22	22	22
Tune-up(dBm)	23	23	23
HSPA+			
Channel	Channel 1513	Channel 1412	Channel 1312
Target (dBm)	22	22	22
Tune-up(dBm)	23	23	23
WCDMA 1900 CS			
Channel	Channel 9538	Channel 9400	Channel 9262
Target (dBm)	23	23	23
Tune-up(dBm)	24	24	24
HSUPA (sub-test 1/2)			
Channel	Channel 9538	Channel 9400	Channel 9262
Target (dBm)	21	21	21
Tune-up(dBm)	22	22	22
HSUPA (sub-test 3)			
Channel	Channel 9538	Channel 9400	Channel 9262
Target (dBm)	22	22	22
Tune-up(dBm)	23	23	23
HSUPA (sub-test 4)			
Channel	Channel 9538	Channel 9400	Channel 9262
Target (dBm)	20	20	20
Tune-up(dBm)	21	21	21
HSUPA (sub-test 5)			
Channel	Channel 9538	Channel 9400	Channel 9262
Target (dBm)	22.5	22.5	22.5

Tune-up(dBm)	23.5	23.5	23.5
DC-HSDPA (sub-test 1~4)			
Channel	Channel 9538	Channel 9400	Channel 9262
Target (dBm)	22	22	22
Tune-up(dBm)	23	23	23
HSPA+			
Channel	Channel 9538	Channel 9400	Channel 9262
Target (dBm)	22	22	22
Tune-up(dBm)	23	23	23

Table 11.1-4: LTE

Mode	Target (dBm)	Tune-up(dBm)
LTE Band 2	23	24
LTE Band 4	23	24
LTE Band 5	23.5	24.5
LTE Band 7	23.4	24.4
LTE Band 12	23.5	24.5
LTE Band 13	23.5	24.5
LTE Band 17	23.5	24.5

LTE MPR will follow up 3GPP setting as below:

Modulation	Channel bandwidth / Transmission bandwidth (NRB)						MPR (dB)
	1.4MHz	3.0MHz	5MHz	10MHz	15MHz	20MHz	
QPSK	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	0
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	2

Table 11.1-5: Bluetooth

GFSK	Channel	Channel 0	Channel 39	Channel 78
	Target (dBm)	6.5	6.5	6.5
	Tune-up(dBm)	7.5	7.5	7.5
EDR2M-4_DQPSK	Target (dBm)	5	6	5
	Tune-up(dBm)	6	7	6
EDR3M-8DPSK	Target (dBm)	5	6	5
	Tune-up(dBm)	6	7	6

Table 11.1-6: WiFi

WiFi 802.11b (2.4GHz)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	16	18.5	17
Tune-up(dB)	17	19.5	18

WiFi 802.11g (2.4GHz)			
Data Rate	Channel 1	Channel 6	Channel 11
Target (dBm)	12	15.5	13
Tune-up(dB)	13	16.5	14
WiFi 802.11n-20 (2.4GHz) MCS0~7			
Data Rate	Channel 1	Channel 6	Channel 11
Target (dBm)	12	14	13
Tune-up(dB)	13	15	14
WiFi 802.11n-40 (2.4GHz) MCS0~7			
Data Rate	Channel 3	Channel 6	Channel 9
Target (dBm)	10	13.5	11
Tune-up(dB)	11	14.5	12

11.2 GSM Measurement result

During the process of testing, the EUT was controlled via Agilent Digital Radio Communication tester (E5515C) to ensure the maximum power transmission and proper modulation. This result contains conducted output power for the EUT. In all cases, the measured peak output power should be greater and within 5% than EMI measurement.

Table 11.2-1: The conducted power measurement results for GSM850/1900

GSM 850MHz	Conducted Power (dBm)		
	Channel 251(848.8MHz)	Channel 190(836.6MHz)	Channel 128(824.2MHz)
	32.96	32.98	32.86
GSM 1900MHz	Conducted Power(dBm)		
	Channel 810(1909.8MHz)	Channel 661(1880MHz)	Channel 512(1850.2MHz)
	29.75	29.72	29.70

Table 11.2-2: The conducted power measurement results for GPRS and EGPRS

GSM 850 GPRS (GMSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	251	190	128		251	190	128
1 Txslot	33.00	32.99	32.94	-9.03	23.97	23.96	23.91
2 Txslots	29.69	29.64	29.59	-6.02	23.67	23.62	23.57
3Txslots	27.61	27.59	27.52	-4.26	23.35	23.33	23.26
4 Txslots	26.71	26.73	26.70	-3.01	23.70	23.72	23.69
GSM 850 EGPRS (GMSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	251	190	128		251	190	128
1 Txslot	33.00	32.98	32.93	-9.03	23.97	23.95	23.90
2 Txslots	29.67	29.63	29.58	-6.02	23.65	23.61	23.56
3Txslots	27.59	27.57	27.50	-4.26	23.33	23.31	23.24
4 Txslots	26.62	26.58	26.48	-3.01	23.61	23.57	23.47
GSM 850 EGPRS (8PSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	251	190	128		251	190	128
1 Txslot	26.81	26.72	26.69	-9.03	17.78	17.69	17.66
2 Txslots	25.96	25.90	25.90	-6.02	19.94	19.88	19.88
3Txslots	24.22	24.19	24.26	-4.26	19.96	19.93	20.00
4 Txslots	23.38	23.30	23.37	-3.01	20.37	20.29	20.36
PCS1900 GPRS (GMSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	810	661	512		810	661	512
1 Txslot	29.80	29.72	29.71	-9.03	20.77	20.69	20.68
2 Txslots	27.09	27.05	27.01	-6.02	21.07	21.03	20.99
3Txslots	25.12	25.03	24.98	-4.26	20.86	20.77	20.72
4 Txslots	24.07	24.01	23.90	-3.01	21.06	21.00	20.89
PCS1900 EGPRS (GMSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	810	661	512		810	661	512
1 Txslot	29.79	29.73	29.71	-9.03	20.76	20.70	20.68
2 Txslots	27.09	27.05	27.00	-6.02	21.07	21.03	20.98

3Txslots	25.11	25.03	24.97	-4.26	20.85	20.77	20.71
4 Txslots	24.05	24.00	23.89	-3.01	21.04	20.99	20.88
PCS1900 EGPRS (8PSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	810	661	512		810	661	512
1 Txslot	26.73	26.75	26.79	-9.03	17.70	17.72	17.76
2 Txslots	25.61	25.64	25.63	-6.02	19.59	19.62	19.61
3Txslots	23.70	23.68	23.65	-4.26	19.44	19.42	19.39
4 Txslots	22.39	22.40	22.39	-3.01	19.38	19.39	19.38

NOTES:

1) Division Factors

To average the power, the division factor is as follows:

1TX-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB

2TX-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB

3TX-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB

4TX-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB

According to the conducted power as above, the body measurements are performed with 1Txslots for GSM850 and 2Txslots for PCS1900.

11.3 WCDMA Measurement result

Table 11.3-1: The conducted Power for WCDMA

Item	band	FDDV result		
	ARFCN	4132(826.4MHz)	4182(836.4MHz)	4233(846.6MHz)
WCDMA	1	23.60	23.59	23.56
HSUPA	1	20.55	20.56	21.00
	2	20.56	20.29	20.55
	3	21.57	21.22	21.55
	4	20.04	19.68	20.00
	5	22.54	22.39	22.51
HSPA+	1	21.86	21.95	21.99
DC-HSDPA	1	21.89	21.94	21.91
	2	21.86	21.92	21.89
	3	21.83	21.95	21.86
	4	21.81	21.93	21.88
Item	band	FDDIV result		
	ARFCN	1312(1712.4MHz)	1412(1732.4MHz)	1513(1752.6MHz)
WCDMA	1	23.38	23.37	23.39
HSUPA	1	20.92	20.88	20.89
	2	20.95	20.89	20.37
	3	21.95	21.89	21.36
	4	20.44	20.35	19.82
	5	22.88	22.82	22.85

HSPA+	1	22.03	22.03	22.05
DC-HSDPA	1	22.05	22.02	22.05
	2	22.01	22.03	22.02
	3	22.02	22.01	22.01
	4	22.01	22.02	22.03
Item	band	FDDII result		
	ARFCN	9262(1852.4MHz)	9400(1880MHz)	9538(1907.6MHz)
WCDMA	1	23.56	23.66	23.52
HSUPA	1	20.85	20.41	20.43
	2	20.27	20.43	20.30
	3	21.25	21.43	21.30
	4	19.81	19.91	19.85
	5	22.24	22.41	22.28
HSPA+	1	22.12	21.93	22.01
DC-HSDPA	1	21.88	21.99	21.84
	2	21.85	21.95	21.82
	3	21.87	21.93	21.81
	4	21.83	21.92	21.83

11.4 LTE Measurement result

Table 11.4-1: The conducted Power for LTE

Band 2							
Bandwidth (MHz)	RB allocation	Frequency (MHz)	Max. Target Power (dBm)	QPSK		16QAM	
	RB offset (Start RB)			Actual output power (dBm)	MPR	Actual output power (dBm)	MPR
1.4 MHz	1RB High (5)	1909.3	24	23.70	0	22.72	1
		1880	24	23.45	0	22.61	1
		1850.7	24	23.39	0	22.38	1
	1RB Middle (3)	1909.3	24	23.71	0	22.71	1
		1880	24	23.43	0	22.59	1
		1850.7	24	23.45	0	22.39	1
	1RB Low (0)	1909.3	24	23.71	0	22.75	1
		1880	24	23.48	0	22.62	1
		1850.7	24	23.45	0	22.39	1
	3RB High (3)	1909.3	24	23.68	0	22.78	1
		1880	24	23.52	0	22.66	1
		1850.7	24	23.42	0	22.51	1
	3RB Middle (1)	1909.3	24	23.65	0	22.73	1
		1880	24	23.49	0	22.60	1
		1850.7	24	23.40	0	22.47	1

	3RB Low (0)	1909.3	24	23.73	0	22.82	1
		1880	24	23.58	0	22.70	1
		1850.7	24	23.48	0	22.56	1
	6RB (0)	1909.3	24	22.63	1	21.53	2
		1880	24	22.50	1	21.43	2
		1850.7	24	22.41	1	21.32	2
3 MHz	1RB High (14)	1908.5	24	23.45	0	22.48	1
		1880	24	23.34	0	22.50	1
		1851.5	24	23.42	0	22.55	1
	1RB Middle (7)	1908.5	24	23.55	0	22.55	1
		1880	24	23.39	0	22.54	1
		1851.5	24	23.52	0	22.60	1
	1RB Low (0)	1908.5	24	23.53	0	22.59	1
		1880	24	23.36	0	22.52	1
		1851.5	24	23.51	0	22.56	1
	8RB High (7)	1908.5	24	22.50	1	21.53	2
		1880	24	22.44	1	21.53	2
		1851.5	24	22.44	1	21.50	2
	8RB Middle (4)	1908.5	24	22.52	1	21.57	2
		1880	24	22.45	1	21.54	2
		1851.5	24	22.44	1	21.49	2
	8RB Low (0)	1908.5	24	22.53	1	21.56	2
		1880	24	22.44	1	21.52	2
		1851.5	24	22.47	1	21.50	2
	15RB (0)	1908.5	24	22.49	1	21.53	2
		1880	24	22.43	1	21.49	2
		1851.5	24	22.40	1	21.43	2
5 MHz	1RB High (24)	1907.5	24	23.50	0	22.63	1
		1880	24	23.37	0	22.64	1
		1852.5	24	23.44	0	22.71	1
	1RB Middle (12)	1907.5	24	23.58	0	22.73	1
		1880	24	23.42	0	22.69	1
		1852.5	24	23.54	0	22.77	1
	1RB Low (0)	1907.5	24	23.60	0	22.94	1
		1880	24	23.44	0	22.68	1
		1852.5	24	23.61	0	22.76	1
	12RB High (13)	1907.5	24	22.51	1	21.66	2
		1880	24	22.49	1	21.64	2
		1852.5	24	22.44	1	21.59	2
	12RB Middle (6)	1907.5	24	22.57	1	21.67	2
		1880	24	22.49	1	21.61	2
		1852.5	24	22.46	1	21.58	2
	12RB	1907.5	24	22.59	1	21.72	2

	Low (0)	1880	24	22.51	1	21.66	2
		1852.5	24	22.47	1	21.59	2
	25RB (0)	1907.5	24	22.12	1	21.38	2
		1880	24	22.46	1	21.53	2
		1852.5	24	22.41	1	21.48	2
10 MHz	1RB High (49)	1905	24	23.53	0	22.55	1
		1880	24	23.41	0	22.59	1
		1855	24	23.44	0	22.60	1
	1RB Middle (24)	1905	24	23.55	0	22.69	1
		1880	24	23.41	0	22.55	1
		1855	24	23.47	0	22.61	1
	1RB Low (0)	1905	24	23.37	0	22.29	1
		1880	24	23.46	0	22.81	1
		1855	24	23.68	0	22.61	1
	25RB High (25)	1905	24	22.49	1	21.55	2
		1880	24	22.44	1	21.50	2
		1855	24	22.37	1	21.40	2
	25RB Middle (12)	1905	24	22.50	1	21.57	2
		1880	24	22.46	1	21.53	2
		1855	24	22.42	1	21.46	2
	25RB Low (0)	1905	24	22.69	1	21.11	2
		1880	24	22.42	1	21.54	2
		1855	24	22.41	1	21.45	2
	50RB (0)	1905	24	22.36	1	21.45	2
		1880	24	22.30	1	21.28	2
		1855	24	22.08	1	21.29	2
15 MHz	1RB High (74)	1902.5	24	23.60	0	22.59	1
		1880	24	23.41	0	22.60	1
		1857.5	24	23.42	0	22.57	1
	1RB Middle (37)	1902.5	24	23.39	0	22.59	1
		1880	24	23.50	0	22.46	1
		1857.5	24	23.47	0	22.56	1
	1RB Low (0)	1902.5	24	23.44	0	22.57	1
		1880	24	23.36	0	22.51	1
		1857.5	24	23.45	0	22.49	1
	36RB High (38)	1902.5	24	22.65	1	21.62	2
		1880	24	22.53	1	21.56	2
		1857.5	24	22.51	1	21.55	2
	36RB Middle (19)	1902.5	24	22.65	1	21.21	2
		1880	24	22.53	1	21.64	2
		1857.5	24	22.48	1	21.53	2
	36RB Low (0)	1902.5	24	22.54	1	21.54	2
		1880	24	22.37	1	21.49	2
		1857.5	24	22.55	1	21.46	2
	75RB (0)	1902.5	24	22.59	1	21.54	2
		1880	24	22.48	1	21.45	2
		1857.5	24	22.46	1	21.44	2
20 MHz	1RB High (99)	1900	24	23.63	0	22.63	1
		1880	24	23.48	0	22.66	1

		1860	24	23.45	0	22.63	1
	1RB Middle (50)	1900	24	23.38	0	22.57	1
		1880	24	23.25	0	22.43	1
		1860	24	23.45	0	22.49	1
		1900	24	23.42	0	22.57	1
	1RB Low (0)	1880	24	23.38	0	22.56	1
		1860	24	23.46	0	22.55	1
		1900	24	22.56	1	21.59	2
	50RB High (50)	1880	24	22.51	1	21.54	2
		1860	24	22.46	1	21.49	2
		1900	24	22.46	1	21.51	2
	50RB Middle (25)	1880	24	22.50	1	21.42	2
		1860	24	22.62	1	21.10	2
		1900	24	22.44	1	21.48	2
	50RB Low (0)	1880	24	22.40	1	21.42	2
		1860	24	22.39	1	21.41	2
		1900	24	22.44	1	21.46	2
	100RB (0)	1880	24	22.41	1	21.41	2
		1860	24	22.37	1	21.38	2
Band 4							
Bandwidth (MHz)	RB allocation	Frequency (MHz)	Max. Target Power (dBm)	QPSK		16QAM	
	RB offset (Start RB)			Actual output power (dBm)	MPR	Actual output power (dBm)	MPR
1.4 MHz	1RB High (5)	1754.3	24	23.24	0	22.28	1
		1732.5	24	23.16	0	22.27	1
		1710.7	24	23.17	0	22.29	1
	1RB Middle (3)	1754.3	24	23.15	0	22.22	1
		1732.5	24	23.17	0	22.20	1
		1710.7	24	23.14	0	22.27	1
	1RB Low (0)	1754.3	24	23.11	0	22.17	1
		1732.5	24	23.15	0	22.25	1
		1710.7	24	23.16	0	22.28	1
	3RB High (3)	1754.3	24	23.21	0	22.19	1
		1732.5	24	23.20	0	22.34	1
		1710.7	24	23.22	0	22.36	1
	3RB Middle (1)	1754.3	24	23.09	0	22.14	1
		1732.5	24	23.10	0	22.25	1
		1710.7	24	23.13	0	22.28	1
	3RB Low (0)	1754.3	24	23.14	0	22.25	1
		1732.5	24	23.20	0	22.35	1
		1710.7	24	23.23	0	22.39	1
	6RB (0)	1754.3	24	22.16	1	21.01	2
		1732.5	24	22.13	1	21.04	2
		1710.7	24	22.16	1	21.07	2
3 MHz	1RB High (14)	1753.5	24	23.13	0	22.19	1
		1732.5	24	23.11	0	22.22	1

	1RB Middle (7)	1711.5	24	23.17	0	22.27	1
		1753.5	24	23.16	0	22.19	1
		1732.5	24	23.20	0	22.31	1
		1711.5	24	23.23	0	22.31	1
	1RB Low (0)	1753.5	24	23.12	0	22.18	1
		1732.5	24	23.18	0	22.29	1
		1711.5	24	23.20	0	22.32	1
	8RB High (7)	1753.5	24	22.19	1	21.19	2
		1732.5	24	22.20	1	21.27	2
		1711.5	24	22.25	1	21.32	2
	8RB Middle (4)	1753.5	24	22.18	1	21.21	2
		1732.5	24	22.22	1	21.29	2
		1711.5	24	22.27	1	21.35	2
	8RB Low (0)	1753.5	24	22.18	1	21.19	2
		1732.5	24	22.21	1	21.28	2
		1711.5	24	22.25	1	21.32	2
	15RB (0)	1753.5	24	22.12	1	21.12	2
		1732.5	24	22.18	1	21.21	2
		1711.5	24	22.23	1	21.27	2
5 MHz	1RB High (24)	1752.5	24	23.15	0	22.33	1
		1732.5	24	23.19	0	22.44	1
		1712.5	24	23.22	0	22.47	1
	1RB Middle (12)	1752.5	24	23.20	0	22.39	1
		1732.5	24	23.25	0	22.49	1
		1712.5	24	23.28	0	22.53	1
	1RB Low (0)	1752.5	24	23.16	0	22.35	1
		1732.5	24	23.28	0	22.51	1
		1712.5	24	23.27	0	22.52	1
	12RB High (13)	1752.5	24	22.16	1	21.26	2
		1732.5	24	22.22	1	21.36	2
		1712.5	24	22.25	1	21.41	2
	12RB Middle (6)	1752.5	24	22.15	1	21.27	2
		1732.5	24	22.23	1	21.36	2
		1712.5	24	22.26	1	21.41	2
	12RB Low (0)	1752.5	24	22.16	1	21.26	2
		1732.5	24	22.25	1	21.37	2
		1712.5	24	22.29	1	21.44	2
	25RB (0)	1752.5	24	22.10	1	21.14	2
		1732.5	24	22.20	1	21.27	2
		1712.5	24	22.25	1	21.32	2
10 MHz	1RB High (49)	1750	24	23.29	0	22.34	1
		1732.5	24	23.21	0	22.32	1

	1RB Middle (24)	1715	24	23.21	0	22.31	1
		1750	24	23.21	0	22.27	1
		1732.5	24	23.19	0	22.28	1
		1715	24	23.20	0	22.28	1
	1RB Low (0)	1750	24	23.17	0	22.25	1
		1732.5	24	23.30	0	22.39	1
		1715	24	23.24	0	22.33	1
	25RB High (25)	1750	24	22.20	1	21.22	2
		1732.5	24	22.19	1	21.23	2
		1715	24	22.19	1	21.22	2
	25RB Middle (12)	1750	24	22.19	1	21.21	2
		1732.5	24	22.21	1	21.21	2
		1715	24	22.19	1	21.24	2
	25RB Low (0)	1750	24	22.13	1	21.16	2
		1732.5	24	22.21	1	21.24	2
		1715	24	22.20	1	21.24	2
	50RB (0)	1750	24	22.19	1	21.20	2
		1732.5	24	22.23	1	21.24	2
		1715	24	22.23	1	21.26	2
15 MHz	1RB High (74)	1747.5	24	23.30	0	22.36	1
		1732.5	24	23.17	0	22.31	1
		1717.5	24	23.19	0	22.30	1
	1RB Middle (37)	1747.5	24	23.22	0	22.31	1
		1732.5	24	23.24	0	22.35	1
		1717.5	24	23.25	0	22.34	1
	1RB Low (0)	1747.5	24	23.17	0	22.22	1
		1732.5	24	23.29	0	22.37	1
		1717.5	24	23.25	0	22.36	1
	36RB High (38)	1747.5	24	22.32	1	21.32	2
		1732.5	24	22.30	1	21.32	2
		1717.5	24	22.28	1	21.31	2
	36RB Middle (19)	1747.5	24	22.26	1	21.27	2
		1732.5	24	22.31	1	21.31	2
		1717.5	24	22.31	1	21.32	2
	36RB Low (0)	1747.5	24	22.23	1	21.25	2
		1732.5	24	22.37	1	21.34	2
		1717.5	24	22.33	1	21.33	2
	75RB (0)	1747.5	24	22.40	1	21.25	2
		1732.5	24	22.36	1	21.33	2
		1717.5	24	22.32	1	21.29	2
20 MHz	1RB High (99)	1745	24	23.41	0	22.48	1
		1732.5	24	23.22	0	22.37	1
		1720	24	23.31	0	22.44	1
	1RB Middle (50)	1745	24	23.21	0	22.33	1
		1732.5	24	23.21	0	22.34	1
		1720	24	23.28	0	22.39	1
	1RB Low (0)	1745	24	23.34	0	22.46	1
		1732.5	24	23.32	0	22.43	1

		1720	24	23.35	0	22.38	1
	50RB High (50)	1745	24	22.28	1	21.30	2
		1732.5	24	22.21	1	21.23	2
		1720	24	22.23	1	21.28	2
	50RB Middle (25)	1745	24	22.22	1	21.22	2
		1732.5	24	22.24	1	21.26	2
		1720	24	22.24	1	21.28	2
	50RB Low (0)	1745	24	22.28	1	21.19	2
		1732.5	24	22.27	1	21.29	2
		1720	24	22.31	1	21.34	2
	100RB (0)	1745	24	22.26	1	21.26	2
		1732.5	24	22.49	1	21.30	2
		1720	24	22.28	1	21.39	2
Band 5							
Bandwidth (MHz)	RB allocation	Frequency (MHz)	Max. Target Power (dBm)	QPSK		16QAM	
	RB offset (Start RB)			Actual output power (dBm)	MPR	Actual output power (dBm)	MPR
1.4 MHz	1RB High (5)	848.3	24.5	24.21	0	23.10	1
		836.5	24.5	24.08	0	23.04	1
		824.7	24.5	24.08	0	23.41	1
	1RB Middle (3)	848.3	24.5	24.28	0	23.16	1
		836.5	24.5	24.18	0	23.14	1
		824.7	24.5	24.13	0	23.10	1
	1RB Low (0)	848.3	24.5	24.19	0	23.04	1
		836.5	24.5	24.08	0	23.02	1
		824.7	24.5	24.09	0	22.54	1
	3RB High (3)	848.3	24.5	24.13	0	23.21	1
		836.5	24.5	24.08	0	23.20	1
		824.7	24.5	24.16	0	23.28	1
	3RB Middle (1)	848.3	24.5	24.06	0	23.11	1
		836.5	24.5	24.03	0	23.14	1
		824.7	24.5	24.11	0	23.23	1
	3RB Low (0)	848.3	24.5	24.12	0	23.19	1
		836.5	24.5	24.10	0	23.23	1
		824.7	24.5	24.18	0	23.32	1
	6RB (0)	848.3	24.5	23.18	1	21.99	2
		836.5	24.5	23.09	1	21.95	2
		824.7	24.5	23.11	1	22.00	2
3 MHz	1RB High (14)	847.5	24.5	24.19	0	23.07	1
		836.5	24.5	24.05	0	23.10	1
		825.5	24.5	24.06	0	23.04	1
	1RB Middle	847.5	24.5	24.21	0	23.06	1
		836.5	24.5	24.10	0	23.16	1

	(7)	825.5	24.5	24.13	0	23.11	1
	1RB Low (0)	847.5	24.5	24.15	0	23.03	1
		836.5	24.5	24.05	0	23.14	1
		825.5	24.5	24.12	0	23.11	1
	8RB High (7)	847.5	24.5	23.18	1	22.14	2
		836.5	24.5	23.13	1	22.16	2
		825.5	24.5	23.14	1	22.19	2
	8RB Middle (4)	847.5	24.5	23.19	1	22.15	2
		836.5	24.5	23.13	1	22.17	2
		825.5	24.5	23.16	1	22.23	2
	8RB Low (0)	847.5	24.5	23.15	1	22.13	2
		836.5	24.5	23.12	1	22.17	2
		825.5	24.5	23.18	1	22.23	2
	15RB (0)	847.5	24.5	23.10	1	22.09	2
		836.5	24.5	23.08	1	22.10	2
		825.5	24.5	23.10	1	22.15	2
5 MHz	1RB High (24)	846.5	24.5	24.17	0	23.12	1
		836.5	24.5	24.07	0	23.27	1
		826.5	24.5	24.06	0	23.09	1
	1RB Middle (12)	846.5	24.5	24.16	0	23.09	1
		836.5	24.5	24.12	0	23.34	1
		826.5	24.5	24.12	0	23.14	1
	1RB Low (0)	846.5	24.5	24.14	0	23.11	1
		836.5	24.5	24.11	0	23.29	1
		826.5	24.5	24.16	0	23.18	1
	12RB High (13)	846.5	24.5	23.11	1	22.19	2
		836.5	24.5	23.09	1	22.23	2
		826.5	24.5	23.09	1	22.25	2
	12RB Middle (6)	846.5	24.5	23.10	1	22.19	2
		836.5	24.5	23.12	1	22.24	2
		826.5	24.5	23.10	1	22.28	2
	12RB Low (0)	846.5	24.5	23.10	1	22.19	2
		836.5	24.5	23.09	1	22.21	2
		826.5	24.5	23.15	1	22.29	2
	25RB (0)	846.5	24.5	23.07	1	22.08	2
		836.5	24.5	23.06	1	22.11	2
		826.5	24.5	23.09	1	22.16	2
10 MHz	1RB High (49)	844.0	24.5	24.31	0	23.14	1
		836.5	24.5	24.06	0	23.14	1
		829.0	24.5	24.14	0	23.08	1
	1RB Middle	844.0	24.5	24.25	0	23.13	1
		836.5	24.5	24.15	0	23.21	1

	(24)	829.0	24.5	24.15	0	23.10	1
	1RB Low (0)	844.0	24.5	24.14	0	23.08	1
		836.5	24.5	24.10	0	23.15	1
		829.0	24.5	24.17	0	23.13	1
	25RB High (25)	844.0	24.5	23.09	1	22.09	2
		836.5	24.5	23.06	1	22.09	2
		829.0	24.5	23.10	1	22.12	2
	25RB Middle (12)	844.0	24.5	23.08	1	22.09	2
		836.5	24.5	23.05	1	22.10	2
		829.0	24.5	23.07	1	22.12	2
	25RB Low (0)	844.0	24.5	23.04	1	22.06	2
		836.5	24.5	23.04	1	22.07	2
		829.0	24.5	23.09	1	22.14	2
	50RB (0)	844.0	24.5	23.09	1	22.07	2
		836.5	24.5	23.09	1	22.09	2
		829.0	24.5	23.10	1	22.13	2
Band 7							
Bandwidth (MHz)	RB allocation	Frequency (MHz)	Max. Target Power (dBm)	QPSK		16QAM	
	RB offset (Start RB)			Actual output power (dBm)	MPR	Actual output power (dBm)	MPR
5 MHz	1RB High (24)	2567.5	24.4	23.83	0	22.84	1
		2535	24.4	23.68	0	22.75	1
		2502.5	24.4	23.69	0	22.83	1
	1RB Middle (12)	2567.5	24.4	23.88	0	22.88	1
		2535	24.4	23.77	0	22.82	1
		2502.5	24.4	23.85	0	22.87	1
	1RB Low (0)	2567.5	24.4	23.90	0	22.88	1
		2535	24.4	23.79	0	22.78	1
		2502.5	24.4	23.90	0	22.83	1
	12RB High (13)	2567.5	24.4	22.85	1	21.97	2
		2535	24.4	22.77	1	21.92	2
		2502.5	24.4	22.85	1	22.00	2
	12RB Middle (6)	2567.5	24.4	22.87	1	22.00	2
		2535	24.4	22.80	1	21.94	2
		2502.5	24.4	22.90	1	22.00	2
	12RB Low (0)	2567.5	24.4	22.33	1	21.36	2
		2535	24.4	22.80	1	21.94	2
		2502.5	24.4	22.90	1	21.99	2
	25RB (0)	2567.5	24.4	22.70	1	21.75	2
		2535	24.4	22.75	1	21.82	2
		2502.5	24.4	22.86	1	21.88	2
10 MHz	1RB High (49)	2565	24.4	23.91	0	22.84	1
		2535	24.4	23.77	0	22.90	1
		2505	24.4	23.95	0	22.90	1
	1RB Middle	2565	24.4	23.84	0	22.73	1
		2535	24.4	23.82	0	23.06	1

	(24)	2505	24.4	23.96	0	22.65	1
	1RB Low (0)	2565	24.4	23.78	0	22.68	1
		2535	24.4	23.69	0	22.78	1
		2505	24.4	23.90	0	22.76	1
	25RB High (25)	2565	24.4	22.82	1	22.18	2
		2535	24.4	22.75	1	21.79	2
		2505	24.4	22.87	1	21.89	2
	25RB Middle (12)	2565	24.4	22.70	1	21.71	2
		2535	24.4	22.76	1	21.41	2
		2505	24.4	22.90	1	21.44	2
	25RB Low (0)	2565	24.4	22.68	1	21.70	2
		2535	24.4	22.64	1	21.68	2
		2505	24.4	22.79	1	21.78	2
	50RB (0)	2565	24.4	22.71	1	21.71	2
		2535	24.4	22.65	1	21.69	2
		2505	24.4	22.79	1	21.80	2
15 MHz	1RB High (74)	2562.5	24.4	23.94	0	23.15	1
		2535	24.4	23.79	0	22.97	1
		2507.5	24.4	23.91	0	23.21	1
	1RB Middle (37)	2562.5	24.4	23.95	0	23.11	1
		2535	24.4	23.68	0	22.80	1
		2507.5	24.4	23.72	0	23.03	1
	1RB Low (0)	2562.5	24.4	23.96	0	23.07	1
		2535	24.4	23.76	0	22.83	1
		2507.5	24.4	23.76	0	22.95	1
	36RB High (38)	2562.5	24.4	22.87	1	21.93	2
		2535	24.4	22.85	1	21.89	2
		2507.5	24.4	22.89	1	22.09	2
	36RB Middle (19)	2562.5	24.4	22.97	1	21.91	2
		2535	24.4	22.55	1	21.73	2
		2507.5	24.4	22.72	1	21.72	2
	36RB Low (0)	2562.5	24.4	22.97	1	21.87	2
		2535	24.4	22.75	1	21.75	2
		2507.5	24.4	22.73	1	21.71	2
	75RB (0)	2562.5	24.4	23.00	1	21.93	2
		2535	24.4	22.77	1	21.75	2
		2507.5	24.4	22.79	1	21.75	2
20 MHz	1RB High (99)	2560	24.4	23.92	0	23.33	1
		2535	24.4	24.03	0	22.92	1
		2510	24.4	24.12	0	23.20	1
	1RB Middle (50)	2560	24.4	23.89	0	23.26	1
		2535	24.4	23.75	0	22.89	1
		2510	24.4	23.70	0	23.20	1
	1RB Low (0)	2560	24.4	23.93	0	23.29	1
		2535	24.4	23.84	0	22.89	1
		2510	24.4	23.71	0	23.10	1
	50RB High (50)	2560	24.4	22.87	1	21.85	2
		2535	24.4	22.70	1	21.74	2
		2510	24.4	22.55	1	21.71	2
	50RB Middle (25)	2560	24.4	22.81	1	21.77	2
		2535	24.4	22.69	1	21.69	2
		2510	24.4	22.68	1	21.69	2
	50RB Low (0)	2560	24.4	22.81	1	21.77	2
		2535	24.4	22.71	1	21.72	2

		2510	24.4	22.67	1	21.67	2
	100RB (0)	2560	24.4	22.83	1	21.81	2
		2535	24.4	22.69	1	21.69	2
		2510	24.4	22.69	1	21.69	2
Band 12							
Bandwidth(MHz)	RB allocation	Frequency(MHz)	Max. Target Power (dBm)	QPSK		16QAM	
	RB offset (Start RB)			Actual output power (dBm)	MPR	Actual output power (dBm)	MPR
1.4 MHz	1RB High (5)	715.3	24.5	24.05	0	22.99	1
		707.5	24.5	24.24	0	23.23	1
		699.7	24.5	24.19	0	23.14	1
	1RB Middle (3)	715.3	24.5	24.17	0	23.09	1
		707.5	24.5	24.34	0	23.30	1
		699.7	24.5	24.27	0	23.20	1
	1RB Low (0)	715.3	24.5	24.14	0	23.06	1
		707.5	24.5	24.27	0	23.23	1
		699.7	24.5	24.19	0	23.10	1
	3RB High (3)	715.3	24.5	24.07	0	23.17	1
		707.5	24.5	24.28	0	23.28	1
		699.7	24.5	24.20	0	23.29	1
	3RB Middle (1)	715.3	24.5	24.06	0	23.15	1
		707.5	24.5	24.25	0	23.35	1
		699.7	24.5	24.14	0	23.23	1
	3RB Low (0)	715.3	24.5	24.15	0	23.26	1
		707.5	24.5	24.32	0	23.33	1
		699.7	24.5	24.21	0	23.32	1
	6RB (0)	715.3	24.5	23.03	1	21.91	2
		707.5	24.5	23.22	1	22.10	2
		699.7	24.5	23.17	1	22.03	2
3 MHz	1RB High (14)	714.5	24.5	24.03	0	22.96	1
		707.5	24.5	24.17	0	23.24	1
		700.5	24.5	24.26	0	23.19	1
	1RB Middle (7)	714.5	24.5	24.15	0	23.06	1
		707.5	24.5	24.25	0	23.33	1
		700.5	24.5	24.22	0	23.15	1
	1RB Low (0)	714.5	24.5	24.18	0	23.14	1
		707.5	24.5	24.24	0	23.34	1
		700.5	24.5	24.19	0	23.12	1
	8RB High (7)	714.5	24.5	23.15	1	22.15	2
		707.5	24.5	23.29	1	22.33	2
		700.5	24.5	23.27	1	22.28	2
	8RB Middle (4)	714.5	24.5	23.16	1	22.19	2
		707.5	24.5	23.31	1	22.37	2
		700.5	24.5	23.24	1	22.28	2
	8RB Low (0)	714.5	24.5	23.21	1	22.24	2
		707.5	24.5	23.31	1	22.36	2
		700.5	24.5	23.25	1	22.26	2
15RB (0)	714.5	24.5	23.11	1	22.13	2	
	707.5	24.5	23.26	1	22.28	2	
	700.5	24.5	23.21	1	22.23	2	
5 MHz	1RB High (24)	713.5	24.5	24.01	0	23.00	1
		707.5	24.5	24.19	0	22.93	1

		701.5	24.5	24.18	0	23.20	1	
	1RB Middle (12)	713.5	24.5	24.21	0	23.19	1	
		707.5	24.5	24.29	0	22.98	1	
		701.5	24.5	24.30	0	23.28	1	
	1RB Low (0)	713.5	24.5	24.26	0	23.23	1	
		707.5	24.5	24.29	0	22.99	1	
		701.5	24.5	24.23	0	23.20	1	
	12RB High (13)	713.5	24.5	23.15	1	22.30	2	
		707.5	24.5	23.26	1	22.43	2	
		701.5	24.5	23.25	1	22.42	2	
	12RB Middle (6)	713.5	24.5	23.18	1	22.32	2	
		707.5	24.5	23.27	1	22.44	2	
		701.5	24.5	23.25	1	22.42	2	
	12RB Low (0)	713.5	24.5	23.23	1	22.38	2	
		707.5	24.5	23.29	1	22.44	2	
		701.5	24.5	23.20	1	22.35	2	
	25RB (0)	713.5	24.5	23.13	1	22.20	2	
		707.5	24.5	23.23	1	22.30	2	
		701.5	24.5	23.19	1	22.25	2	
	10 MHz	1RB High (49)	711	24.5	24.04	0	22.96	1
			707.5	24.5	24.14	0	23.23	1
704			24.5	24.28	0	23.25	1	
1RB Middle (24)		711	24.5	24.24	0	23.18	1	
		707.5	24.5	24.28	0	23.38	1	
		704	24.5	24.30	0	23.25	1	
1RB Low (0)		711	24.5	24.32	0	23.25	1	
		707.5	24.5	24.27	0	23.34	1	
		704	24.5	24.25	0	23.19	1	
25RB High (25)		711	24.5	23.08	1	22.14	2	
		707.5	24.5	23.19	1	22.24	2	
		704	24.5	23.22	1	22.29	2	
25RB Middle (12)		711	24.5	23.13	1	22.21	2	
		707.5	24.5	23.24	1	22.28	2	
		704	24.5	23.25	1	22.27	2	
25RB Low (0)		711	24.5	23.22	1	22.24	2	
		707.5	24.5	23.21	1	22.26	2	
		704	24.5	23.20	1	22.25	2	
50RB (0)		711	24.5	23.17	1	22.19	2	
		707.5	24.5	23.24	1	22.28	2	
		704	24.5	23.26	1	22.27	2	
Band 13								
Bandwidth (MHz)	RB allocation	Frequency (MHz)	Max. Target Power (dBm)	QPSK		16QAM		
	RB offset (Start RB)			Actual output power (dBm)	MPR	Actual output power (dBm)	MPR	
5 MHz	1RB High (24)	784.5	24.5	23.88	0	22.91	1	
		782	24.5	23.92	0	22.92	1	
		779.5	24.5	23.99	0	22.97	1	
	1RB Middle	784.5	24.5	23.59	0	22.72	1	
		782	24.5	23.61	0	22.72	1	

	(12)	779.5	24.5	23.58	0	22.62	1
	1RB Low (0)	784.5	24.5	23.68	0	22.57	1
		782	24.5	23.53	0	22.49	1
		779.5	24.5	23.57	0	22.53	1
	12RB High (13)	784.5	24.5	22.95	1	22.09	2
		782	24.5	22.99	1	22.12	2
		779.5	24.5	23.00	1	22.15	2
	12RB Middle (6)	784.5	24.5	22.82	1	22.02	2
		782	24.5	22.90	1	22.07	2
		779.5	24.5	22.85	1	22.04	2
	12RB Low (0)	784.5	24.5	22.95	1	22.13	2
		782	24.5	22.95	1	22.12	2
		779.5	24.5	22.89	1	22.00	2
	25RB (0)	784.5	24.5	22.78	1	21.83	2
		782	24.5	22.67	1	21.59	2
		779.5	24.5	22.65	1	21.66	2
10 MHz	1RB High (49)	782	24.5	23.91	0	23.37	1
	1RB Middle (24)	782	24.5	24.03	0	23.42	1
	1RB Low (0)	782	24.5	24.12	0	22.97	1
	25RB High (25)	782	24.5	22.94	1	22.00	2
	25RB Middle (12)	782	24.5	22.97	1	22.00	2
	25RB Low (0)	782	24.5	22.98	1	22.03	2
	50RB (0)	782	24.5	22.97	1	22.00	2
Band 17							
Bandwidth (MHz)	RB allocation	Frequency (MHz)	Max. Target Power (dBm)	QPSK		16QAM	
	RB offset (Start RB)			Actual output power (dBm)	MPR	Actual output power (dBm)	MPR
5 MHz	1RB High (24)	713.5	24.5	23.85	0	23.07	1
		710	24.5	23.98	0	22.99	1
		706.5	24.5	24.03	0	23.06	1
	1RB Middle (12)	713.5	24.5	23.96	0	23.20	1
		710	24.5	24.10	0	23.11	1
		706.5	24.5	24.23	0	23.26	1
	1RB Low (0)	713.5	24.5	24.07	0	23.28	1
		710	24.5	24.22	0	23.24	1
		706.5	24.5	24.16	0	23.18	1

	12RB High (13)	713.5	24.5	22.97	1	22.13	2
		710	24.5	23.07	1	22.25	2
		706.5	24.5	23.22	1	22.39	2
	12RB Middle (6)	713.5	24.5	23.00	1	22.15	2
		710	24.5	23.15	1	22.32	2
		706.5	24.5	23.26	1	22.42	2
	12RB Low (0)	713.5	24.5	23.07	1	22.36	2
		710	24.5	23.19	1	22.33	2
		706.5	24.5	23.23	1	22.38	2
	25RB (0)	713.5	24.5	22.87	1	21.88	2
		710	24.5	23.09	1	22.19	2
		706.5	24.5	23.20	1	22.27	2
10 MHz	1RB High (49)	711	24.5	23.92	0	22.84	1
		710	24.5	23.99	0	22.91	1
		709	24.5	23.99	0	22.98	1
	1RB Middle (24)	711	24.5	24.07	0	23.16	1
		710	24.5	24.15	0	23.10	1
		709	24.5	24.20	0	23.13	1
	1RB Low (0)	711	24.5	24.29	0	23.35	1
		710	24.5	24.25	0	23.18	1
		709	24.5	24.21	0	23.16	1
	25RB High (25)	711	24.5	23.11	1	22.00	2
		710	24.5	23.04	1	22.06	2
		709	24.5	23.04	1	22.18	2
	25RB Middle (12)	711	24.5	23.03	1	22.11	2
		710	24.5	23.08	1	22.15	2
		709	24.5	23.14	1	22.19	2
	25RB Low (0)	711	24.5	23.14	1	22.19	2
		710	24.5	23.18	1	22.20	2
		709	24.5	23.18	1	22.24	2
	50RB (0)	711	24.5	23.06	1	22.09	2
		710	24.5	23.12	1	22.16	2
		709	24.5	23.15	1	22.19	2

11.5 Wi-Fi and BT Measurement result

The output power of BT antenna is as following:

Mode	Conducted Power (dBm)		
	Channel 0 (2402MHz)	Channel 39 (2441MHz)	Channel 78(2480MHz)
GFSK	7.23	7.36	6.94
EDR2M-4_DQPSK	5.95	6.07	5.60
EDR3M-8DPSK	5.88	5.32	5.53

The average conducted power for Wi-Fi is as following:

802.11b (dBm)

Channel\data rate	1Mbps	2Mbps	5.5Mbps	11Mbps
-------------------	-------	-------	---------	--------

1	16.67	/	16.62	/
6	18.94	18.91	19.14	18.92
11	17.41	/	17.45	/

802.11g (dBm)

Channel\data rate	6Mbps	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
1	12.71	/	12.81	/	/	/	/	/
6	15.75	15.70	16.10	16.06	15.58	15.50	15.80	15.77
11	13.59	/	13.61	/	/	/	/	/

802.11n (dBm) - HT20 (2.4G)


Channel\data rate	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
1	12.69	/	/	/	/	/	/	/
6	14.83	14.77	14.73	14.68	14.60	14.82	14.78	14.73
11	13.58	/	/	/	/	/	/	/

802.11n (dBm) – HT40 (2.4G)

Channel\data rate	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
3	10.88	/	/	/	/	/	/	/
6	14.10	14.03	13.72	13.62	13.49	13.57	13.53	13.49
9	11.38	/	/	/	/	/	/	/

12.1 Introduction

12.2 Transmit Antenna Separation Distances



Note: Diversity antenna only using for receive.

12.3 SAR Measurement Positions

According to the KDB941225 D06 Hot Spot SAR v01, the edges with less than 2.5 cm distance to the antennas need to be tested for SAR.

SAR measurement positions						
Mode	Front	Rear	Left edge	Right edge	Top edge	Bottom edge
Main antenna	Yes	Yes	Yes	Yes	No	Yes
WLAN	Yes	Yes	Yes	No	Yes	No

12.4 Standalone SAR Test Exclusion Considerations

Standalone 1-g head or body SAR evaluation by measurement or numerical simulation is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied. The 1-g SAR test exclusion threshold for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \right] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR, where}$$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Table 12.1: Standalone SAR test exclusion considerations

Band/Mode	F(GHz)	Position	SAR test exclusion threshold(mW)	RF output power		SAR test exclusion
				dBm	mW	
Bluetooth	2.441	Head	9.60	7.5	5.62	Yes
		Body	19.20	7.5	5.62	Yes
2.4GHz WLAN	2.45	Head	9.58	19.5	89.13	No
		Body	19.17	19.5	89.13	No

13 Evaluation of Simultaneous

Table 13.1: The sum of reported SAR values for main antenna and WiFi

	Position	Main antenna	WiFi	Sum
Highest reported SAR value for Head	Left hand, Touch cheek	0.46	0.49	0.95
	Right hand, Touch cheek	0.32	0.75	1.07
Highest reported SAR value for Body	Front	0.99	0.14	1.13
	Top	/	0.23	0.23
	Bottom	1.03	/	1.03

Table 13.2: The sum of reported SAR values for main antenna and BT

	Position	Main antenna	BT	Sum
Maximum reported SAR value for Head	Left hand, Touch cheek	0.46	0.23 ^[1]	0.69
Maximum reported SAR value for Body	Front	0.99	0.12 ^[1]	1.11

[1] - Estimated SAR for Bluetooth (see the table 13.3)

Table 13.3: Estimated SAR for Bluetooth

Mode/Band	F (GHz)	Position	Distance (mm)	Upper limit of power *		Estimated _{1g} (W/kg)
				dBm	mW	
Bluetooth	2.441	Head	5	7.5	5.62	0.23
Bluetooth	2.441	Body	10	7.5	5.62	0.12

* - Maximum possible output power declared by manufacturer

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance,mm)]·[√f(GHz)/x] W/kg for test separation distances ≤ 50 mm;
where x = 7.5 for 1-g SAR.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

Conclusion:

According to the above tables, the sum of reported SAR values is<1.6W/kg. So the simultaneous transmission SAR with volume scans is not required.

14 SAR Test Result

It is determined by user manual for the distance between the EUT and the phantom bottom.

The distance is 10 mm and just applied to the condition of body worn accessory.

It is performed for all SAR measurements with area scan based 1-g SAR estimation (Fast SAR). A zoom scan measurement is added when the estimated 1-gSAR is the highest measured SAR in each exposure configuration, wireless mode and frequency band combination or more than 1.2W/kg.

The calculated SAR is obtained by the following formula:

$$\text{Reported SAR} = \text{Measured SAR} \times 10^{(P_{\text{Target}} - P_{\text{Measured}})/10}$$

Where P_{Target} is the power of manufacturing upper limit;

P_{Measured} is the measured power in chapter 11.

Table 14.1: Duty Cycle

Mode	Duty Cycle
Speech for GSM850/1900	1:8.3
GPRS&EGPRS for GSM850	1:8.3
GPRS&EGPRS for GSM1900	1:4
WCDMA<E	1:1

14.1 The evaluation of multi-batteries

We'll perform the head measurement in all bands with the primary battery depending on the evaluation of multi-batteries and retest on highest value point with other batteries. Then, repeat the measurement in the Body test.

Table 14.1-1: The evaluation of multi-batteries for Head Test

Frequency		Mode/Band	Side	Test Position	Battery Type	SAR(1g)	Power Drift(dB)
MHz	Ch.					(W/kg)	
9800	1880	WCDMA1900	Left	Touch	CAC2710008CJ	0.350	0.10
9800	1880	WCDMA1900	Left	Touch	CAC2710004C1	0.289	0.18
9800	1880	WCDMA1900	Left	Touch	CAC2710005CC	0.271	0.12

Note: According to the values in the above table, the battery, CAC2710008CJ, is the primary battery. We'll perform the head measurement with this battery and retest on highest value point with others.

Table 14.1-2: The evaluation of multi-batteries for Body Test

Frequency		Mode/Band	Test Position	Spacing (mm)	Battery Type	SAR(1g)	Power Drift(dB)
MHz	Ch.					(W/kg)	
9800	1880	WCDMA1900	Front	10	CAC2710008CJ	0.533	0.08
9800	1880	WCDMA1900	Front	10	CAC2710004C1	0.506	-0.06
9800	1880	WCDMA1900	Front	10	CAC2710005CC	0.504	0.07

Note: According to the values in the above table, the battery, CAC2710008CJ, is the primary battery. We'll perform the body measurement with this battery and retest on highest value point with others.

14.2 SAR results for Fast SAR

Note:

B1: The battery of CAC2710004C1

B2: The battery of CAC2710005CC

C1: The Lighting cover

Table 14.2-1: SAR Values (GSM 850 MHz Band - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Side	Test Position	Figure No./Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
251	848.8	Left	Touch	Fig.1	32.96	33.3	0.236	0.26	0.312	0.34	-0.07
190	836.6	Left	Touch	/	32.98	33.3	0.228	0.25	0.300	0.32	0.01
128	824.2	Left	Touch	/	32.86	33.3	0.196	0.22	0.266	0.29	0.01
190	836.6	Left	Tilt	/	32.98	33.3	0.134	0.14	0.166	0.18	-0.03
190	836.6	Right	Touch	/	32.98	33.3	0.162	0.17	0.206	0.22	-0.06
190	836.6	Right	Tilt	/	32.98	33.3	0.113	0.12	0.142	0.15	0.02
251	848.8	Left	Touch	B1	32.96	33.3	0.233	0.25	0.310	0.34	-0.01
251	848.8	Left	Touch	B2	32.96	33.3	0.231	0.25	0.308	0.33	-0.03
251	848.8	Left	Touch	C1	32.96	33.3	0.214	0.23	0.274	0.30	0.03

Table 14.2-2: SAR Values (GSM 850 MHz Band - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Mode (number of timeslots)	Test Position	Figure No./Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
190	836.6	GPRS (1)	Front	/	32.99	33.1	0.129	0.13	0.233	0.24	0.04
251	848.8	GPRS (1)	Rear	Fig.2	33.00	33.1	0.318	0.33	0.408	0.42	-0.02
190	836.6	GPRS (1)	Rear	/	32.99	33.1	0.202	0.21	0.357	0.37	0.03
128	824.2	GPRS (1)	Rear	/	32.94	33.1	0.202	0.21	0.286	0.30	-0.12
190	836.6	GPRS (1)	Left	/	32.99	33.1	0.164	0.17	0.258	0.26	0.09
190	836.6	GPRS (1)	Right	/	32.99	33.1	0.093	0.10	0.146	0.15	-0.07
190	836.6	GPRS (1)	Bottom	/	32.99	33.1	0.094	0.10	0.182	0.19	0.05
251	848.8	EGPRS (1)	Rear	/	33.00	33.1	0.212	0.22	0.396	0.41	0.03
251	848.8	GPRS (1)	Rear	B1	33.00	33.1	0.188	0.19	0.343	0.35	0.01
251	848.8	GPRS (1)	Rear	B2	33.00	33.1	0.199	0.20	0.366	0.37	0.06
251	848.8	GPRS (1)	Rear	C1	33.00	33.1	0.210	0.21	0.289	0.30	-0.03

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.2-3: SAR Values(GSM 1900 MHz Band - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Side	Test Position	Figure No./Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
810	1909.8	Left	Touch	/	29.75	30.3	0.084	0.10	0.132	0.15	0.09
661	1880	Left	Touch	/	29.72	30.3	0.105	0.12	0.165	0.19	0.11
512	1850.2	Left	Touch	Fig.3	29.70	30.3	0.116	0.13	0.181	0.21	0.08
661	1880	Left	Tilt	/	29.72	30.3	0.030	0.03	0.058	0.07	-0.02
661	1880	Right	Touch	/	29.72	30.3	0.093	0.11	0.146	0.17	0.10
661	1880	Right	Tilt	/	29.72	30.3	0.034	0.04	0.052	0.06	0.02
512	1850.2	Left	Touch	B1	29.70	30.3	0.113	0.13	0.178	0.20	0.14
512	1850.2	Left	Touch	B2	29.70	30.3	0.110	0.13	0.176	0.20	0.08
512	1850.2	Left	Touch	C1	29.70	30.3	0.104	0.12	0.163	0.19	-0.02

Table 14.2-4: SAR Values (GSM 1900 MHz Band - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Mode (number of timeslots)	Test Position	Figure No./Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
661	1880	GPRS (2)	Front	/	27.05	28	0.220	0.27	0.314	0.39	0.04
661	1880	GPRS (2)	Rear	/	27.05	28	0.210	0.26	0.321	0.40	0.02
661	1880	GPRS (2)	Left	/	27.05	28	0.044	0.05	0.061	0.08	0.06
661	1880	GPRS (2)	Right	/	27.05	28	0.071	0.09	0.104	0.13	0.12
810	1909.8	GPRS (2)	Bottom	/	27.09	28	0.214	0.26	0.355	0.44	0.03
661	1880	GPRS (2)	Bottom	/	27.05	28	0.248	0.31	0.416	0.52	0.17
512	1850.2	GPRS (2)	Bottom	Fig.4	27.01	28	0.270	0.34	0.438	0.55	-0.08
512	1850.2	EGPRS (2)	Bottom	/	27.00	28	0.238	0.30	0.390	0.49	0.03
512	1850.2	GPRS (2)	Bottom	B1	27.01	28	0.243	0.30	0.415	0.52	0.12
512	1850.2	GPRS (2)	Bottom	B2	27.01	28	0.189	0.24	0.314	0.39	0.06
512	1850.2	GPRS (2)	Bottom	C1	27.01	28	0.243	0.31	0.413	0.52	-0.16

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.2-5: SAR Values (WCDMA 850 MHz Band - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Side	Test Position	Figure No./Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
4233	846.6	Left	Touch	/	23.56	24	0.288	0.32	0.379	0.42	0.04
4182	836.4	Left	Touch	/	23.59	24	0.256	0.28	0.354	0.39	0.03
4132	826.4	Left	Touch	/	23.60	24	0.227	0.25	0.297	0.33	-0.01
4182	836.4	Left	Tilt	/	23.59	24	0.156	0.17	0.199	0.22	0.08
4182	836.4	Right	Touch	/	23.59	24	0.136	0.15	0.172	0.19	0.04
4182	836.4	Right	Tilt	/	23.59	24	0.129	0.14	0.161	0.18	-0.01
4233	846.6	Left	Touch	C1/ Fig.5	23.56	24	0.316	0.35	0.415	0.46	-0.07
4182	836.4	Left	Touch	C1	23.59	24	0.281	0.31	0.388	0.43	0.03
4132	826.4	Left	Touch	C1	23.60	24	0.249	0.27	0.325	0.36	-0.01
4233	846.6	Left	Touch	C1/B1	23.56	24	0.304	0.34	0.399	0.44	0.01
4233	846.6	Left	Touch	C1/B2	23.56	24	0.298	0.33	0.395	0.44	0.05

Table 14.2-6: SAR Values (WCDMA 850 MHz Band - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C				
Frequency		Test Position	Figure No./Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz									
4182	836.4	Front	/	23.59	24	0.259	0.28	0.253	0.28	0.06
4233	846.6	Rear	Fig.6	23.56	24	0.337	0.37	0.437	0.48	0.04
4182	836.4	Rear	/	23.59	24	0.309	0.34	0.394	0.43	0.11
4132	826.4	Rear	/	23.60	24	0.259	0.28	0.330	0.36	-0.02
4182	836.4	Left	/	23.59	24	0.175	0.19	0.192	0.21	0.08
4182	836.4	Right	/	23.59	24	0.140	0.15	0.152	0.17	-0.12
4182	836.4	Bottom	/	23.59	24	0.143	0.16	0.201	0.22	0.09
4233	846.6	Rear	B1	23.56	24	0.320	0.35	0.415	0.46	0.01
4233	846.6	Rear	B2	23.56	24	0.301	0.33	0.380	0.42	0.16
4233	846.6	Rear	C1	23.56	24	0.313	0.35	0.406	0.45	0.12

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.2-7: SAR Values(WCDMA 1700 MHz Band - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Side	Test Position	Figure No./Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
1738	1752.6	Left	Touch	Fig.7	23.39	24	0.194	0.22	0.315	0.36	0.02
1637	1732.4	Left	Touch	/	23.37	24	0.182	0.21	0.294	0.34	0.02
1537	1712.4	Left	Touch	/	23.38	24	0.168	0.19	0.270	0.31	0.12
1637	1732.4	Left	Tilt	/	23.37	24	0.063	0.07	0.112	0.13	0.04
1637	1732.4	Right	Touch	/	23.37	24	0.173	0.20	0.278	0.32	0.11
1637	1732.4	Right	Tilt	/	23.37	24	0.056	0.06	0.093	0.11	-0.02
1738	1752.6	Left	Touch	B1	23.39	24	0.178	0.20	0.291	0.33	0.05
1738	1752.6	Left	Touch	B2	23.39	24	0.167	0.19	0.286	0.33	0.14
1738	1752.6	Left	Touch	C1	23.39	24	0.172	0.20	0.267	0.31	0.12

Table 14.2-8: SAR Values (WCDMA 1700 MHz Band - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C				
Frequency		Test Position	Figure No./Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz									
1637	1732.4	Front	/	23.37	24	0.342	0.40	0.522	0.60	-0.02
1637	1732.4	Rear	/	23.37	24	0.345	0.40	0.529	0.61	0.11
1637	1732.4	Left	/	23.37	24	0.060	0.07	0.089	0.10	0.08
1637	1732.4	Right	/	23.37	24	0.129	0.15	0.209	0.24	-0.12
1738	1752.6	Bottom	Fig.8	23.39	24	0.335	0.39	0.623	0.72	0.00
1637	1732.4	Bottom	/	23.37	24	0.332	0.38	0.610	0.71	0.04
1537	1712.4	Bottom	/	23.38	24	0.318	0.37	0.577	0.67	-0.09
1738	1752.6	Bottom	B1	23.39	24	0.333	0.38	0.621	0.71	-0.13
1738	1752.6	Bottom	B2	23.39	24	0.295	0.34	0.541	0.62	0.05
1738	1752.6	Bottom	C1	23.39	24	0.268	0.31	0.487	0.56	0.04

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.2-9: SAR Values(WCDMA 1900 MHz Band - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Side	Test Position	Figure No./Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
9938	1907.6	Left	Touch	/	23.46	24	0.173	0.20	0.288	0.33	0.08
9800	1880	Left	Touch	Fig.9	23.49	24	0.219	0.25	0.350	0.39	0.10
9662	1852.4	Left	Touch	/	23.38	24	0.182	0.21	0.300	0.35	0.02
9800	1880	Left	Tilt	/	23.49	24	0.048	0.05	0.094	0.11	0.11
9800	1880	Right	Touch	/	23.49	24	0.156	0.18	0.254	0.29	0.09
9800	1880	Right	Tilt	/	23.49	24	0.055	0.06	0.087	0.10	0.04
9800	1880	Left	Touch	B1	23.49	24	0.174	0.20	0.289	0.33	0.18
9800	1880	Left	Touch	B2	23.49	24	0.162	0.18	0.271	0.30	0.12
9800	1880	Left	Touch	C1	23.49	24	0.181	0.20	0.290	0.33	-0.06

Table 14.2-10: SAR Values (WCDMA 1900 MHz Band - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C				
Frequency		Test Position	Figure No./Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz									
9800	1880	Front	/	23.49	24	0.375	0.42	0.533	0.60	0.08
9800	1880	Rear	/	23.49	24	0.384	0.43	0.547	0.62	0.10
9800	1880	Left	/	23.49	24	0.092	0.10	0.127	0.14	-0.02
9800	1880	Right	/	23.49	24	0.122	0.14	0.177	0.20	0.12
9938	1907.6	Bottom	/	23.46	24	0.387	0.44	0.637	0.72	-0.08
9800	1880	Bottom	Fig.10	23.49	24	0.399	0.45	0.652	0.73	-0.11
9662	1852.4	Bottom	/	23.38	24	0.381	0.44	0.628	0.72	0.09
9800	1880	Bottom	B1	23.49	24	0.382	0.43	0.623	0.70	0.16
9800	1880	Bottom	B2	23.49	24	0.361	0.41	0.587	0.66	0.04
9800	1880	Bottom	C1	23.49	24	0.394	0.44	0.629	0.71	0.08

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.2-11: SAR Values (LTE Band2 - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C						
Frequency		Mode	Side	Test Position	Figure No./ Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz											
19100	1900	1RB_High	Left	Touch	Fig.11	23.63	24	0.162	0.18	0.264	0.29	0.02
19100	1900	1RB_High	Left	Tilt	/	23.63	24	0.045	0.05	0.080	0.09	-0.08
19100	1900	1RB_High	Right	Touch	/	23.63	24	0.135	0.15	0.217	0.24	0.04
19100	1900	1RB_High	Right	Tilt	/	23.63	24	0.045	0.05	0.069	0.07	-0.01
18700	1860	50RB_Mid	Left	Touch	/	22.62	23	0.139	0.15	0.224	0.24	-0.05
18700	1860	50RB_Mid	Left	Tilt	/	22.62	23	0.036	0.04	0.064	0.07	0.12
18700	1860	50RB_Mid	Right	Touch	/	22.62	23	0.113	0.12	0.181	0.20	0.08
18700	1860	50RB_Mid	Right	Tilt	/	22.62	23	0.040	0.04	0.062	0.07	0.03
19100	1900	1RB_High	Left	Touch	B1	23.63	24	0.117	0.13	0.206	0.22	0.08
19100	1900	1RB_High	Left	Touch	B2	23.63	24	0.106	0.12	0.186	0.20	0.02
19100	1900	1RB_High	Left	Touch	C1	23.63	24	0.153	0.17	0.242	0.26	0.08

Note1: The LTE mode is QPSK_20MHz.

Table 14.2-12: SAR Values (LTE Band2 - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Mode	Test Position	Figure No./ Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
19100	1900	1RB_High	Front	/	23.63	24	0.392	0.43	0.658	0.72	0.08
19100	1900	1RB_High	Rear	/	23.63	24	0.350	0.38	0.641	0.70	0.07
19100	1900	1RB_High	Left	/	23.63	24	0.086	0.09	0.141	0.15	-0.04
19100	1900	1RB_High	Right	/	23.63	24	0.108	0.12	0.192	0.21	-0.05
19100	1900	1RB_High	Bottom	Fig.12	23.63	24	0.455	0.50	0.850	0.93	-0.01
18900	1880	1RB_High	Bottom	/	23.48	24	0.397	0.45	0.783	0.88	0.04
18700	1860	1RB_Low	Bottom	/	23.46	24	0.413	0.47	0.791	0.90	-0.17
18700	1860	50RB_Mid	Front	/	22.62	23	0.332	0.36	0.559	0.61	0.05
18700	1860	50RB_Mid	Rear	/	22.62	23	0.297	0.32	0.543	0.59	-0.01
18700	1860	50RB_Mid	Left	/	22.62	23	0.072	0.08	0.121	0.13	-0.03
18700	1860	50RB_Mid	Right	/	22.62	23	0.098	0.11	0.170	0.19	-0.02
18700	1860	50RB_Mid	Bottom	/	22.62	23	0.349	0.38	0.694	0.76	0.07
19100	1900	100RB	Bottom	/	22.44	23	0.345	0.39	0.687	0.78	-0.04
19100	1900	1RB_High	Bottom	B1	23.63	24	0.416	0.45	0.816	0.89	0.02
19100	1900	1RB_High	Bottom	B2	23.63	24	0.423	0.46	0.831	0.90	0.01
19100	1900	1RB_High	Bottom	C1	23.63	24	0.409	0.45	0.757	0.82	0.06

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The LTE mode is QPSK_20MHz.

Table 14.2-13: SAR Values(LTE Band4 - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C						
Frequency		Mode	Side	Test Position	Figure No./ Note	Conduct ed Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Powe r Drift (dB)
Ch.	MHz											
20300	1745	1RB_High	Left	Touch	Fig.13	23.41	24	0.249	0.29	0.393	0.45	-0.15
20300	1745	1RB_High	Left	Tilt	/	23.41	24	0.081	0.09	0.138	0.16	0.02
20300	1745	1RB_High	Right	Touch	/	23.41	24	0.231	0.26	0.271	0.31	-0.03
20300	1745	1RB_High	Right	Tilt	/	23.41	24	0.073	0.08	0.112	0.13	-0.04
20050	1720	50RB_Low	Left	Touch	/	22.31	23	0.174	0.20	0.271	0.32	-0.01
20050	1720	50RB_Low	Left	Tilt	/	22.31	23	0.043	0.05	0.071	0.08	0.05
20050	1720	50RB_Low	Right	Touch	/	22.31	23	0.159	0.19	0.247	0.29	0.06
20050	1720	50RB_Low	Right	Tilt	/	22.31	23	0.039	0.05	0.056	0.07	0.06
20300	1745	1RB_High	Left	Touch	B1	23.41	24	0.247	0.28	0.387	0.44	0.02
20300	1745	1RB_High	Left	Touch	B2	23.41	24	0.241	0.28	0.378	0.43	-0.06
20300	1745	1RB_High	Left	Touch	C1	23.41	24	0.208	0.24	0.351	0.40	0.03

Note1: The LTE mode is QPSK_20MHz.

Table 14.2-14: SAR Values (LTE Band4 - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Mode	Test Position	Figure No./Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
20300	1745	1RB_High	Front	/	23.41	24	0.507	0.58	0.863	0.99	-0.08
20175	1732.5	1RB_Low	Front	/	23.32	24	0.401	0.47	0.762	0.89	0.02
20050	1720	1RB_Low	Front	/	23.35	24	0.411	0.48	0.696	0.81	-0.06
20300	1745	1RB_High	Rear	/	23.41	24	0.466	0.53	0.805	0.92	-0.14
20175	1732.5	1RB_Low	Rear	/	23.32	24	0.429	0.50	0.732	0.86	-0.03
20050	1720	1RB_Low	Rear	/	23.35	24	0.397	0.46	0.680	0.79	0.03
20300	1745	1RB_High	Left	/	23.41	24	0.106	0.12	0.173	0.20	0.08
20300	1745	1RB_High	Right	/	23.41	24	0.181	0.21	0.306	0.35	0.04
20300	1745	1RB_High	Bottom	Fig.14	23.41	24	0.481	0.55	0.899	1.03	0.02
20175	1732.5	1RB_Low	Bottom	/	23.32	24	0.428	0.50	0.834	0.98	-0.01
20050	1720	1RB_Low	Bottom	/	23.35	24	0.393	0.46	0.764	0.89	-0.16
20050	1720	50RB_Low	Front	/	22.31	23	0.322	0.38	0.546	0.64	-0.01
20050	1720	50RB_Low	Rear	/	22.31	23	0.311	0.36	0.527	0.62	0.03
20050	1720	50RB_Low	Left	/	22.31	23	0.059	0.07	0.094	0.11	-0.11
20050	1720	50RB_Low	Right	/	22.31	23	0.137	0.16	0.236	0.28	0.02
20050	1720	50RB_Low	Bottom	/	22.31	23	0.314	0.37	0.597	0.70	0.04
20175	1732.5	100RB	Front	/	22.49	23	0.335	0.38	0.561	0.63	0.02
20175	1732.5	100RB	Rear	/	22.49	23	0.327	0.37	0.558	0.63	0.04
20175	1732.5	100RB	Bottom	/	22.49	23	0.316	0.36	0.618	0.70	-0.14

20300	1745	1RB_High	Bottom	B1	23.41	24	0.435	0.50	0.867	0.99	-0.07
20300	1745	1RB_High	Bottom	B2	23.41	24	0.442	0.51	0.877	1.00	-0.01
20300	1745	1RB_High	Bottom	C1	23.41	24	0.492	0.56	0.873	1.00	0.06

Note1: The distance between the EUT and the phantom bottom is 10mm.Note2: The LTE mode is QPSK_20MHz.

Table 14.2-15: SAR Values (LTE Band5 - Head)

Ambient Temperature: 23.0°C						Liquid Temperature: 22.5°C						
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz											
20600	844	1RB_High	Left	Touch	Fig.15	24.31	24.5	0.331	0.35	0.436	0.46	-0.02
20600	844	1RB_High	Left	Tilt	/	24.31	24.5	0.192	0.20	0.245	0.26	0.04
20600	844	1RB_High	Right	Touch	/	24.31	24.5	0.236	0.25	0.304	0.32	-0.01
20600	844	1RB_High	Right	Tilt	/	24.31	24.5	0.156	0.16	0.193	0.20	-0.04
20450	829	25RB_High	Left	Touch	/	23.10	23.5	0.190	0.21	0.249	0.27	0.06
20450	829	25RB_High	Left	Tilt	/	23.10	23.5	0.095	0.10	0.120	0.13	0.08
20450	829	25RB_High	Right	Touch	/	23.10	23.5	0.136	0.15	0.177	0.19	0.02
20450	829	25RB_High	Right	Tilt	/	23.10	23.5	0.087	0.10	0.105	0.12	0.01
20600	844	1RB_High	Left	Touch	B1	24.31	24.5	0.329	0.34	0.431	0.45	-0.05
20600	844	1RB_High	Left	Touch	B2	24.31	24.5	0.314	0.33	0.425	0.44	-0.03
20600	844	1RB_High	Left	Touch	C1	24.31	24.5	0.326	0.34	0.426	0.45	-0.07

Note1: The LTE mode is QPSK_10MHz.

Table 14.2-16: SAR Values (LTE Band5 - Body)

Ambient Temperature: 22.5°C						Liquid Temperature: 22.0°C					
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
20600	844	1RB_High	Front	/	24.31	24.5	0.259	0.27	0.316	0.33	0.08
20600	844	1RB_High	Rear	Fig.16	24.31	24.5	0.284	0.30	0.479	0.50	-0.02
20600	844	1RB_High	Left	/	24.31	24.5	0.265	0.28	0.359	0.37	0.01
20600	844	1RB_High	Right	/	24.31	24.5	0.122	0.13	0.166	0.17	-0.07
20600	844	1RB_High	Bottom	/	24.31	24.5	0.151	0.16	0.264	0.28	0.03
20450	829	25RB_High	Front	/	23.10	23.5	0.137	0.15	0.166	0.18	0.12
20450	829	25RB_High	Rear	/	23.10	23.5	0.172	0.19	0.241	0.26	-0.01
20450	829	25RB_High	Left	/	23.10	23.5	0.141	0.15	0.193	0.21	0.07
20450	829	25RB_High	Right	/	23.10	23.5	0.069	0.08	0.095	0.10	-0.05
20450	829	25RB_High	Bottom	/	23.10	23.5	0.078	0.09	0.138	0.15	0.17
20600	844	1RB_High	Rear	B1	24.31	24.5	0.239	0.25	0.385	0.40	0.03
20600	844	1RB_High	Rear	B2	24.31	24.5	0.205	0.21	0.323	0.34	0.00
20600	844	1RB_High	Rear	C1	24.31	24.5	0.246	0.26	0.372	0.39	0.01

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The LTE mode is QPSK_10MHz.

Table 14.2-17: SAR Values(LTE Band7 - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C						
Frequency		Mode	Side	Test Position	Figure No./ Note	Conduct ed Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g)(W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz											
20850	2510	1RB_High	Left	Touch	/	24.12	24.4	0.089	0.09	0.145	0.15	0.02
20850	2510	1RB_High	Left	Tilt	/	24.12	24.4	0.064	0.07	0.114	0.12	0.14
20850	2510	1RB_High	Right	Touch	Fig.17	24.12	24.4	0.161	0.17	0.295	0.31	0.11
20850	2510	1RB_High	Right	Tilt	/	24.12	24.4	0.047	0.05	0.084	0.09	0.08
21350	2560	50RB_High	Left	Touch	/	22.87	23.4	0.077	0.09	0.126	0.14	0.12
21350	2560	50RB_High	Left	Tilt	/	22.87	23.4	0.056	0.06	0.097	0.11	-0.06
21350	2560	50RB_High	Right	Touch	/	22.87	23.4	0.143	0.16	0.258	0.29	0.11
21350	2560	50RB_High	Right	Tilt	/	22.87	23.4	0.043	0.05	0.078	0.09	0.09
20850	2510	1RB_High	Right	Touch	B1	24.12	24.4	0.141	0.15	0.268	0.29	-0.02
20850	2510	1RB_High	Right	Touch	B2	24.12	24.4	0.153	0.16	0.279	0.30	0.10
20850	2510	1RB_High	Right	Touch	C1	24.12	24.4	0.129	0.14	0.237	0.25	0.07

Note1: The LTE mode is QPSK_20MHz.

Table 14.2-18: SAR Values (LTE Band7 - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Mode	Test Position	Figure No./Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
20850	2510	1RB_High	Front	/	24.12	24.4	0.177	0.19	0.339	0.36	0.06
20850	2510	1RB_High	Rear	/	24.12	24.4	0.224	0.24	0.424	0.45	0.04
20850	2510	1RB_High	Left	/	24.12	24.4	0.037	0.04	0.061	0.07	0.12
20850	2510	1RB_High	Right	/	24.12	24.4	0.084	0.09	0.156	0.17	0.03
21350	2560	1RB_Low	Bottom	/	23.93	24.4	0.374	0.42	0.775	0.86	0.16
21100	2535	1RB_High	Bottom	/	24.03	24.4	0.370	0.40	0.774	0.84	0.13
20850	2510	1RB_High	Bottom	Fig.18	24.12	24.4	0.401	0.43	0.816	0.87	0.08
21350	2560	50RB_High	Front	/	22.87	23.4	0.119	0.13	0.225	0.25	0.06
21350	2560	50RB_High	Rear	/	22.87	23.4	0.169	0.19	0.321	0.36	0.04
21350	2560	50RB_High	Left	/	22.87	23.4	0.032	0.04	0.053	0.06	0.08
21350	2560	50RB_High	Right	/	22.87	23.4	0.067	0.08	0.125	0.14	-0.08
21350	2560	50RB_High	Bottom	/	22.87	23.4	0.288	0.33	0.601	0.68	-0.12
21350	2560	100RB	Bottom	/	22.83	23.4	0.282	0.32	0.589	0.67	-0.09
20850	2510	1RB_High	Bottom	B1	24.12	24.4	0.374	0.40	0.787	0.84	-0.08
20850	2510	1RB_High	Bottom	B2	24.12	24.4	0.356	0.38	0.788	0.84	-0.13
20850	2510	1RB_High	Bottom	C1	24.12	24.4	0.348	0.37	0.754	0.80	0.11

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The LTE mode is QPSK_20MHz.

Table 14.2-19: SAR Values (LTE Band12 - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C						
Frequency		Mode	Side	Test Position	Figure No./ Note	Conduct ed Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz											
23130	711	1RB_Low	Left	Touch	Fig.19	24.32	24.5	0.179	0.19	0.228	0.24	0.11
23130	711	1RB_Low	Left	Tilt	/	24.32	24.5	0.110	0.11	0.148	0.15	0.06
23130	711	1RB_Low	Right	Touch	/	24.32	24.5	0.124	0.13	0.170	0.18	-0.16
23130	711	1RB_Low	Right	Tilt	/	24.32	24.5	0.093	0.10	0.124	0.13	0.04
23060	704	25RB_Mid	Left	Touch	/	23.25	23.5	0.097	0.10	0.131	0.14	0.01
23060	704	25RB_Mid	Left	Tilt	/	23.25	23.5	0.067	0.07	0.090	0.10	0.03
23060	704	25RB_Mid	Right	Touch	/	23.25	23.5	0.075	0.08	0.103	0.11	0.03
23060	704	25RB_Mid	Right	Tilt	/	23.25	23.5	0.055	0.06	0.074	0.08	-0.01
23130	711	1RB_Low	Left	Touch	B1	24.32	24.5	0.155	0.16	0.211	0.22	-0.08
23130	711	1RB_Low	Left	Touch	B2	24.32	24.5	0.152	0.16	0.209	0.22	0.03
23130	711	1RB_Low	Left	Touch	C1	24.32	24.5	0.165	0.17	0.216	0.23	0.13

Note1: The LTE mode is QPSK_10MHz.

Table 14.2-20: SAR Values (LTE Band12 - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Mode	Test Position	Figure No./Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
23130	711	1RB_Low	Front	/	24.32	24.5	0.214	0.22	0.299	0.31	-0.08
23130	711	1RB_Low	Rear	Fig.20	24.32	24.5	0.250	0.26	0.314	0.33	-0.06
23130	711	1RB_Low	Left	/	24.32	24.5	0.069	0.07	0.102	0.11	0.12
23130	711	1RB_Low	Right	/	24.32	24.5	0.129	0.13	0.196	0.20	0.06
23130	711	1RB_Low	Bottom	/	24.32	24.5	0.033	0.03	0.068	0.07	0.03
23060	704	25RB_Mid	Front	/	23.25	23.5	0.169	0.18	0.235	0.25	0.09
23060	704	25RB_Mid	Rear	/	23.25	23.5	0.194	0.21	0.272	0.29	0.12
23060	704	25RB_Mid	Left	/	23.25	23.5	0.064	0.07	0.098	0.10	0.19
23060	704	25RB_Mid	Right	/	23.25	23.5	0.115	0.12	0.174	0.18	0.15
23060	704	25RB_Mid	Bottom	/	23.25	23.5	0.027	0.03	0.055	0.06	0.05
23130	711	1RB_Low	Rear	B1	24.32	24.5	0.195	0.20	0.300	0.31	0.02
23130	711	1RB_Low	Rear	B2	24.32	24.5	0.184	0.19	0.258	0.27	0.08
23130	711	1RB_Low	Rear	C1	24.32	24.5	0.131	0.14	0.186	0.19	0.01

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The LTE mode is QPSK_10MHz.

Table 14.2-21: SAR Values (LTE Band13 - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C						
Frequency		Mode	Side	Test Position	Figure No./ Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz											
23230	782	1RB_Low	Left	Touch	Fig.21	24.12	24.5	0.114	0.12	0.147	0.16	0.05
23230	782	1RB_Low	Left	Tilt	/	24.12	24.5	0.084	0.09	0.104	0.11	0.02
23230	782	1RB_Low	Right	Touch	/	24.12	24.5	0.098	0.11	0.124	0.14	0.06
23230	782	1RB_Low	Right	Tilt	/	24.12	24.5	0.077	0.08	0.093	0.10	0.12
23230	782	25RB_Low	Left	Touch	/	22.98	23.5	0.092	0.10	0.117	0.13	0.19
23230	782	25RB_Low	Left	Tilt	/	22.98	23.5	0.066	0.07	0.083	0.09	0.03
23230	782	25RB_Low	Right	Touch	/	22.98	23.5	0.077	0.09	0.098	0.11	0.09
23230	782	25RB_Low	Right	Tilt	/	22.98	23.5	0.059	0.07	0.072	0.08	-0.16
23230	782	1RB_Low	Left	Touch	B1	24.12	24.5	0.110	0.12	0.144	0.16	0.01
23230	782	1RB_Low	Left	Touch	B2	24.12	24.5	0.108	0.12	0.138	0.15	0.04
23230	782	1RB_Low	Left	Touch	C1	24.12	24.5	0.100	0.11	0.127	0.14	-0.13

Note1: The LTE mode is QPSK_10MHz.

Table 14.2-22: SAR Values (LTE Band13 - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Mode	Test Position	Figure No./Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
23230	782	1RB_Low	Front	/	24.12	24.5	0.123	0.13	0.171	0.19	0.08
23230	782	1RB_Low	Rear	Fig.22	24.12	24.5	0.183	0.20	0.232	0.25	-0.02
23230	782	1RB_Low	Left	/	24.12	24.5	0.132	0.14	0.198	0.22	0.02
23230	782	1RB_Low	Right	/	24.12	24.5	0.079	0.09	0.119	0.13	0.03
23230	782	1RB_Low	Bottom	/	24.12	24.5	0.033	0.04	0.065	0.07	0.01
23230	782	25RB_Low	Front	/	22.98	23.5	0.098	0.11	0.136	0.15	0.12
23230	782	25RB_Low	Rear	/	22.98	23.5	0.136	0.15	0.190	0.21	0.18
23230	782	25RB_Low	Left	/	22.98	23.5	0.104	0.12	0.157	0.18	-0.07
23230	782	25RB_Low	Right	/	22.98	23.5	0.062	0.07	0.095	0.11	0.06
23230	782	25RB_Low	Bottom	/	22.98	23.5	0.027	0.03	0.052	0.06	0.09
23230	782	1RB_Low	Rear	B1	24.12	24.5	0.156	0.17	0.217	0.24	0.01
23230	782	1RB_Low	Rear	B2	24.12	24.5	0.125	0.14	0.174	0.19	0.06
23230	782	1RB_Low	Rear	C1	24.12	24.5	0.114	0.12	0.183	0.20	-0.09

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The LTE mode is QPSK_10MHz.

14.3 SAR results for Standard procedure

There is zoom scan measurement to be added for the highest measured SAR in each exposure configuration/band.

Table 14.3-1: SAR Values (GSM 850 MHz Band - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Side	Test Position	Figure No./Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
251	848.8	Left	Touch	Fig.1	32.96	33.3	0.236	0.26	0.312	0.34	-0.07

Table 14.3-2: SAR Values (GSM 850 MHz Band - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Mode (number of timeslots)	Test Position	Figure No./Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
251	848.8	GPRS (1)	Rear	Fig.2	33.00	33.1	0.318	0.33	0.408	0.42	-0.02

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.3-3: SAR Values(GSM 1900 MHz Band - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Side	Test Position	Figure No./Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
512	1850.2	Left	Touch	Fig.3	29.70	30.3	0.116	0.13	0.181	0.21	0.08

Table 14.3-4: SAR Values (GSM 1900 MHz Band - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Mode (number of timeslots)	Test Position	Figure No./Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
512	1850.2	GPRS (2)	Bottom	Fig.4	27.01	28	0.270	0.34	0.438	0.55	-0.08

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.3-5: SAR Values (WCDMA 850 MHz Band - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Side	Test Position	Figure No./Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
4233	846.6	Left	Touch	C1/ Fig.5	23.56	24	0.316	0.35	0.415	0.46	-0.07

Table 14.3-6: SAR Values (WCDMA 850 MHz Band - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C				
Frequency		Test Position	Figure No./Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz									
4233	846.6	Rear	Fig.6	23.56	24	0.337	0.37	0.437	0.48	0.04

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.3-7: SAR Values(WCDMA 1700 MHz Band - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Side	Test Position	Figure No./Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
1738	1752.6	Left	Touch	Fig.7	23.39	24	0.194	0.22	0.315	0.36	0.02

Table 14.3-8: SAR Values (WCDMA 1700 MHz Band - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C				
Frequency		Test Position	Figure No./Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz									
1738	1752.6	Bottom	Fig.8	23.39	24	0.335	0.39	0.623	0.72	0.00

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.3-9: SAR Values(WCDMA 1900 MHz Band - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Side	Test Position	Figure No./Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
9800	1880	Left	Touch	Fig.9	23.49	24	0.219	0.25	0.350	0.39	0.10

Table 14.3-10: SAR Values (WCDMA 1900 MHz Band - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C				
Frequency		Test Position	Figure No./Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz									
9800	1880	Bottom	Fig.10	23.49	24	0.399	0.45	0.652	0.73	-0.11

Note1: The distance between the EUT and the phantom bottom is 10mm.

Table 14.3-11: SAR Values (LTE Band2 - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C						
Frequency		Mode	Side	Test Position	Figure No./ Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz											
19100	1900	1RB_High	Left	Touch	Fig.11	23.63	24	0.162	0.18	0.264	0.29	0.02

Note1: The LTE mode is QPSK_20MHz.

Table 14.3-12: SAR Values (LTE Band2 - Body)

Ambient Temperature: 23.0 °C Liquid Temperature: 22.5 °C											
Frequency		Mode	Test Position	Figure No./ Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
19100	1900	1RB_High	Bottom	Fig.12	23.63	24	0.455	0.50	0.850	0.93	-0.01

Note1: The distance between the EUT and the phantom bottom is 10mm. Note2: The LTE mode is QPSK_20MHz.

Table 14.3-13: SAR Values(LTE Band4 - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C						
Frequency		Mode	Side	Test Position	Figure No./ Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz											
20300	1745	1RB_High	Left	Touch	Fig.13	23.41	24	0.249	0.29	0.393	0.45	-0.15

Note1: The LTE mode is QPSK_20MHz.

Table 14.3-14: SAR Values (LTE Band4 - Body)

Ambient Temperature: 23.0 °C												Liquid Temperature: 22.5 °C			
Frequency		Mode	Test Position	Figure No./Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)				
Ch.	MHz														
20300	1745	1RB High	Bottom	Fig.14	23.41	24	0.481	0.55	0.899	1.03	0.02				

Note1: The distance between the EUT and the phantom bottom is 10mm.Note2: The LTE mode is QPSK_20MHz.

Table 14.3-15: SAR Values (LTE Band5 - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C						
Frequency		Mode	Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz											
20600	844	1RB_High	Left	Touch	Fig.15	24.31	24.5	0.331	0.35	0.436	0.46	-0.02

Note1: The LTE mode is QPSK_10MHz.

Table 14.3-16: SAR Values (LTE Band5 - Body)

Ambient Temperature: 22.5 °C						Liquid Temperature: 22.0 °C					
Frequency		Mode	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
20600	844	1RB_High	Rear	Fig.16	24.31	24.5	0.284	0.30	0.479	0.50	-0.02

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The LTE mode is QPSK_10MHz.

Table 14.3-17: SAR Values(LTE Band7 - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C						
Frequency		Mode	Side	Test Position	Figure No./ Note	Conduct ed Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g)(W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz											
20850	2510	1RB_High	Right	Touch	Fig.17	24.12	24.4	0.161	0.17	0.295	0.31	0.11

Note1: The LTE mode is QPSK_20MHz.

Table 14.3-18: SAR Values (LTE Band7 - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Mode	Test Position	Figure No./Note	Conducte d Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
20850	2510	1RB_High	Bottom	Fig.18	24.12	24.4	0.401	0.43	0.816	0.87	0.08

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The LTE mode is QPSK_20MHz.

Table 14.3-19: SAR Values (LTE Band12 - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C						
Frequency		Mode	Side	Test Position	Figure No./ Note	Conduct ed Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz											
23130	711	1RB_Low	Left	Touch	Fig.19	24.32	24.5	0.179	0.19	0.228	0.24	0.11

Note1: The LTE mode is QPSK_10MHz.

Table 14.3-20: SAR Values (LTE Band12 - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Mode	Test Position	Figure No./Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
23130	711	1RB_Low	Rear	Fig.20	24.32	24.5	0.250	0.26	0.314	0.33	-0.06

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The LTE mode is QPSK_10MHz.

Table 14.3-21: SAR Values (LTE Band13 - Head)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C						
Frequency		Mode	Side	Test Position	Figure No./ Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz											
23230	782	1RB_Low	Left	Touch	Fig.21	24.12	24.5	0.114	0.12	0.147	0.16	0.05

Note1: The LTE mode is QPSK_10MHz.

Table 14.3-22: SAR Values (LTE Band13 - Body)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Mode	Test Position	Figure No./Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
Ch.	MHz										
23230	782	1RB_Low	Rear	Fig.22	24.12	24.5	0.183	0.20	0.232	0.25	-0.02

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The LTE mode is QPSK_10MHz.

14.4 WLAN Evaluation

According to the KDB248227 D01, SAR is measured for 2.4GHz 802.11b DSSS using the initial test position procedure.

Head Evaluation

Table 14.4-1: SAR Values(WLAN - Head)– 802.11b 5.5Mbps (Fast SAR)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Side	Test Position	Figure No./ Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g)(W/kg)	Power Drift (dB)
MHz	Ch.										
2437	6	Left	Touch	/	19.14	19.5	0.228	0.25	0.445	0.48	0.09
2437	6	Left	Tilt	/	19.14	19.5	0.236	0.26	0.474	0.51	0.01
2437	6	Right	Touch	/	19.14	19.5	0.359	0.39	0.777	0.84	0.08
2437	6	Right	Tilt	/	19.14	19.5	0.295	0.32	0.648	0.70	0.14

As shown above table, the initial test position for head is “Right Touch”. So the head SAR of WLAN is presented as below:

Table 14.4-2: SAR Values(WLAN - Head)– 802.11b 5.5Mbps (Full SAR)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C					
Frequency		Side	Test Position	Figure No./ Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g)(W/kg)	Power Drift (dB)
MHz	Ch.										
2437	6	Right	Touch	Fig.23	19.14	19.5	0.319	0.35	0.679	0.74	0.08
2437	6	Right	Tilt	/	19.14	19.5	0.271	0.29	0.600	0.65	0.14
2437	6	Right	Touch	B1	19.14	19.5	0.283	0.31	0.616	0.67	0.10
2437	6	Right	Touch	B2	19.14	19.5	0.312	0.34	0.675	0.73	0.13
2437	6	Right	Touch	C1	19.14	19.5	0.278	0.30	0.626	0.68	-0.02

Note1: When the reported SAR of the initial test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position using subsequent highest estimated 1-g SAR conditions determined by area scans, on the highest maximum output power channel, until the reported SAR is $\leq$ 0.8 W/kg.

Note2: For all positions/configurations tested using the initial test position and subsequent test positions, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel until the reported SAR is $\leq$ 1.2 W/kg or all required channels are tested.

According to the KDB248227 D01, The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit. The scaled reported SAR is presented as below.

Table 14.4-3: SAR Values (WLAN - Head) – 802.11b 5.5Mbps (Scaled Reported SAR)

Ambient Temperature: 23.0 °C					Liquid Temperature: 22.5 °C		
Frequency		Side	Test Position	Actual duty factor	maximum duty factor	Reported SAR (1g)(W/kg)	Scaled reported SAR (1g)(W/kg)
MHz	Ch.						
2437	6	Left	Touch	98.25%	100%	0.48	0.49
2437	6	Right	Touch	98.25%	100%	0.74	0.75

SAR is not required for OFDM because the 802.11b adjusted SAR $\leq$ 1.2 W/kg.

Body Evaluation

Table 14.4-4: SAR Values(WLAN - Body)– 802.11b 5.5Mbps (Fast SAR)

Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C				
Frequency		Test Position	Figure No./ Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured	Reported	Measured	Reported	Power Drift
MHz	Ch.					SAR(10g) (W/kg)	SAR(10g) (W/kg)	SAR(1g) (W/kg)	SAR(1g)(W/kg)	
2437	6	Front	/	19.14	19.5	0.070	0.08	0.128	0.14	-0.12
2437	6	Rear	/	19.14	19.5	0.066	0.07	0.118	0.13	0.11
2437	6	Left	/	19.14	19.5	0.034	0.04	0.066	0.07	0.03
2437	6	Top	/	19.14	19.5	0.108	0.12	0.206	0.22	0.01

As shown above table, the initial test position for body is “Top”. So the body SAR of WLAN is presented as below:

Table 14.4-5: SAR Values(WLAN - Body)– 802.11b 5.5Mbps (Full SAR)


Ambient Temperature: 23.0 °C						Liquid Temperature: 22.5 °C				
Frequency		Test Position	Figure No./ Note	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured	Reported	Measured	Reported	Power Drift
MHz	Ch.					SAR(10g) (W/kg)	SAR(10g) (W/kg)	SAR(1g) (W/kg)	SAR(1g)(W/kg)	
2437	6	Top	Fig.24	19.14	19.5	0.111	0.12	0.211	0.23	0.01
2437	6	Top	B1	19.14	19.5	0.089	0.10	0.162	0.18	0.11
2437	6	Top	B2	19.14	19.5	0.097	0.11	0.187	0.20	0.06
2437	6	Top	C1	19.14	19.5	0.094	0.10	0.182	0.20	-0.02

According to the KDB248227 D01, The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit. The scaled reported SAR is presented as below.

Table 14.4-6: SAR Values (WLAN - Body) – 802.11b 5.5Mbps (Scaled Reported SAR)

Ambient Temperature: 23.0 °C					Liquid Temperature: 22.5 °C	
Frequency		Test Position	Actual duty factor	maximum duty factor	Reported SAR (1g)(W/kg)	Scaled reported SAR (1g)(W/kg)
MHz	Ch.					
2437	6	Front	98.25%	100%	0.14	0.14
2437	6	Top	98.25%	100%	0.23	0.23

SAR is not required for OFDM because the 802.11b adjusted SAR ≤ 1.2 W/kg.



Picture 14.1 Duty factor plot

15 SAR Measurement Variability

SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium.

The following procedures are applied to determine if repeated measurements are required.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

Table 15.1: SAR Measurement Variability for Body LTE B2 (1g)

Frequency		Mode	Test Position	Spacing (mm)	Original SAR (W/kg)	First Repeated SAR (W/kg)	The Ratio	Second Repeated SAR (W/kg)
Ch.	MHz							
19100	1900	1RB_High	Bottom	10	0.850	0.844	1.01	/

Table 15.2: SAR Measurement Variability for Body LTE B4 (1g)

Frequency		Mode	Test Position	Spacing (mm)	Original SAR (W/kg)	First Repeated SAR (W/kg)	The Ratio	Second Repeated SAR (W/kg)
Ch.	MHz							
20300	1745	1RB_High	Bottom	10	0.899	0.891	1.01	/

Table 15.3: SAR Measurement Variability for Body LTE B7 (1g)

Frequency		Mode	Test Position	Spacing (mm)	Original SAR (W/kg)	First Repeated SAR (W/kg)	The Ratio	Second Repeated SAR (W/kg)
Ch.	MHz							
20850	2510	1RB_High	Bottom	10	0.816	0.809	1.01	/