



The Photos of SAR test

No. I16Z42410-SEM01

For

TCL Communication Ltd.

LTE / UMTS / GSM mobile phone

Modelname: 5046J

With

Hardware Version: PIO

Software Version: v5JE3

FCC ID: 2ACCJH070



Note:


The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

Test Laboratory:


CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT
No. 51 Shouxiang Science Building, Xueyuan Road, Haidian District, Beijing, P. R. China 100191
Tel: +86(0)10-62304633-2512, Fax: +86(0)10-62304633-2504
Email: ctl_terminals@catr.cn, website: www.chinattl.com



Picture 1: Constituents of the sample




Picture 2: Left Hand Touch Cheek Position



Picture 3: Left Hand Tilt 15° Position




Picture 4: Right Hand Touch Cheek Position




Picture 5: Right Hand Tilt 15° Position

Test positions for body:


The Body SAR is tested at the following 6 test positions all with the distance =10mm between the EUT and the phantom bottom:




Picture 6: Front



Picture 7: Rear



Picture 8: Left



Picture 9: Right



Picture 10: Bottom



Picture 11: Top